

# FCC DFS REPORT

## FCC Certification

**Applicant Name:**

LG Electronics MobileComm U.S.A., Inc.

**Date of Issue:**

April 20, 2016

**Test Site/Location:**

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Address:**

1000 Sylvan Avenue, Englewood Cliffs NJ 07632

**Report No.:** HCT-R-1604-F058

**HCT FRN:** 0005866421

**IC Recognition No.:** 5944A-5

**FCC ID** : ZNFDM02H

**APPLICANT** : LG Electronics MobileComm U.S.A., Inc.

**Model(s):**

DM-02H

**Additional Model(s):**

DS1604

**EUT Type:**

Cellular/PCS GSM/WCDMA Phone with WLAN, Bluetooth and NFC

**Max. RF**

**Output Power:**

| Band   | Mode           | Frequency Range (MHz) | Power (dBm) | Power (W) |
|--------|----------------|-----------------------|-------------|-----------|
| UNII2A | 802.11a        | 5260 – 5320           | 12.61       | 0.0182    |
|        | 802.11n_HT20   | 5260 – 5320           | 8.56        | 0.0072    |
|        | 802.11n_HT40   | 5270 – 5310           | 9.75        | 0.0094    |
|        | 802.11ac_VHT20 | 5260 – 5320           | 8.46        | 0.0070    |
|        | 802.11ac_VHT40 | 5270 – 5310           | 9.82        | 0.0096    |
|        | 802.11ac_VHT80 | 5290                  | 9.09        | 0.0081    |
| UNII2C | 802.11a        | 5500 – 5700           | 12.94       | 0.0197    |
|        | 802.11n_HT20   | 5500 – 5700           | 8.95        | 0.0079    |
|        | 802.11n_HT40   | 5510 – 5670           | 9.57        | 0.0091    |
|        | 802.11ac_VHT20 | 5500 – 5700           | 8.81        | 0.0076    |
|        | 802.11ac_VHT40 | 5510 – 5670           | 9.50        | 0.0089    |
|        | 802.11ac_VHT80 | 5530                  | 8.89        | 0.0077    |

**Modulation type**

OFDM

**FCC Classification:**

Unlicensed National Information Infrastructure (UNII)

**FCC Rule Part(s):**

Part 15.407(DFS)

**Engineering Statement:**

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.


HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



**Report prepared by**

: Seoul Ki Lee

**Test Engineer of RF Team**



**Approved by**

: Jong Seok Lee

**Manager of RF Team**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

| TEST REPORT NO. | DATE           | DESCRIPTION             |
|-----------------|----------------|-------------------------|
| HCT-R-1604-F058 | April 20, 2016 | - First Approval Report |
|                 |                |                         |
|                 |                |                         |
|                 |                |                         |

## Table of Contents

|                                                         |    |
|---------------------------------------------------------|----|
| 1. GENERAL INFORMATION .....                            | 4  |
| 2. EUT DESCRIPTION .....                                | 4  |
| 3. SCOPE .....                                          | 5  |
| 4. INSTRUMENT CALIBRATION.....                          | 5  |
| 5. FACILITIES AND ACCREDITATIONS .....                  | 5  |
| 5.1 FACILITIES .....                                    | 5  |
| 5.2 EQUIPMENT .....                                     | 5  |
| 6. SUMMARY OF TEST RESULTS .....                        | 6  |
| 7. DESCRIPTION OF DYNAMIC FREQUENCY SELECTION TEST..... | 7  |
| 7.1 APPLICABILITY .....                                 | 7  |
| 7.2 REQUIREMENTS.....                                   | 8  |
| 7.3 DFS DETECTION THRESHOLD VALUES .....                | 10 |
| 7.4 PARAMETERS OF DFS TEST SIGNALS.....                 | 11 |
| 7.5 TEST AND MEASUREMENT SYSTEM .....                   | 13 |
| 7.6 DESCRIPTION OF EUT.....                             | 15 |
| 7.7 UNII2A TEST RESULT .....                            | 16 |
| 7.8 UNII2C TEST RESULT .....                            | 19 |
| 8. LIST OF TEST EQUIPMENT .....                         | 22 |

## 1. GENERAL INFORMATION

**Applicant:** LG Electronics MobileComm U.S.A., Inc  
**Address:** 1000 Sylvan Avenue, Englewood Cliffs NJ 07632  
**FCC ID:** ZNFD02H  
**EUT Type:** Cellular/PCS GSM/WCDMA Phone with WLAN, Bluetooth and NFC  
**Model (s):** DM-02H  
**Additional Model(s):** DS1604  
**Date(s) of Tests:** April 14, 2016 ~ April 15, 2016  
**Place of Tests:** HCT Co., Ltd.  
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea

## 2. EUT DESCRIPTION

|                              |                                                                                                                                                         |                                                              |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| <b>Model</b>                 | DM-02H                                                                                                                                                  |                                                              |
| <b>Additional Model</b>      | DS1604                                                                                                                                                  |                                                              |
| <b>EUT Type</b>              | <b>Cellular/PCS GSM/WCDMA Phone with WLAN, Bluetooth and NFC</b>                                                                                        |                                                              |
| <b>Power Supply</b>          | DC 3.85 V                                                                                                                                               |                                                              |
| <b>Battery Information</b>   | Model: BL-T25<br>Type: Li-ion Battery                                                                                                                   |                                                              |
| <b>Frequency Range</b>       | TX_20 MHz BW:                                                                                                                                           | 5260 MHz - 5320 MHz (UNII 2A)/ 5500 MHz - 5700 MHz (UNII 2C) |
|                              | 40 MHz BW:                                                                                                                                              | 5270 MHz - 5310 MHz (UNII 2A)/ 5510 MHz - 5670 MHz (UNII 2C) |
|                              | 80 MHz BW:                                                                                                                                              | 5290 MHz (UNII 2A)/ 5530 MHz (UNII 2C)                       |
|                              | RX_20 MHz BW:                                                                                                                                           | 5260 MHz - 5320 MHz (UNII 2A)/ 5500 MHz - 5700 MHz (UNII 2C) |
|                              | 40 MHz BW:                                                                                                                                              | 5270 MHz - 5310 MHz (UNII 2A)/ 5510 MHz - 5670 MHz (UNII 2C) |
|                              | 80 MHz BW:                                                                                                                                              | 5290 MHz (UNII 2A)/ 5530 MHz (UNII 2C)                       |
| <b>Modulation Type</b>       | OFDM(802.11a, 802.11n, 802.11ac)                                                                                                                        |                                                              |
| <b>Antenna Specification</b> | Manufacturer: LS Mtron Co., Ltd.<br>Antenna type: INTERNAL ANTENNA<br>Peak Gain : -2.55 dBi (5260~5320 UNII2A BAND) / -3.05 dBi (5500~5700 UNII2C BAND) |                                                              |

### 3. SCOPE

This report has been prepared to demonstrate compliance with the requirements for Dynamic Frequency Selection(DFS) as stated in KDB 905462 D02 v02. Testing was performed in accordance with the measurement procedure described in FCC KDB 905462 D02 v02.

### 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

### 5. FACILITIES AND ACCREDITATIONS

#### 5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 07, 2015 (Registration Number: 90661)

#### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 6. SUMMARY OF TEST RESULTS

| Band   | Parameter                         | Limit                                                       | Result |
|--------|-----------------------------------|-------------------------------------------------------------|--------|
| UNII2A | Channel Move Time                 | 10 seconds                                                  | PASS   |
|        | Channel Closing Transmission Time | 200 ms + aggregate of 60 ms over remaining 10 second period | PASS   |
|        | Non-occupancy Period              | 30 minutes                                                  | PASS   |
| UNII2C | Channel Move Time                 | 10 seconds                                                  | PASS   |
|        | Channel Closing Transmission Time | 200 ms + aggregate of 60 ms over remaining 10 second period | PASS   |
|        | Non-occupancy Period              | 30 minutes                                                  | PASS   |

## 7. DESCRIPTION OF DYNAMIC FREQUENCY SELECTION TEST

### 7.1 APPLICABILITY

The following table from KDB905462 D02 v02(04/08/2016) lists the applicable requirements for the DFS testing. The device evaluated in this report is considered a client device without radar detection capability.

| Requirement                     | Operation Mode |                                |                             |
|---------------------------------|----------------|--------------------------------|-----------------------------|
|                                 | Master         | Client Without Radar Detection | Client With Radar Detection |
| Non-Occupancy Period            | Yes            | Not required                   | Yes                         |
| DFS Detection Threshold         | Yes            | Not required                   | Yes                         |
| Channel Availability Check Time | Yes            | Not required                   | Not required                |
| Uniform Spreading               | Yes            | Not required                   | Not required                |
| U-NII Detection Bandwidth       | Yes            | Not required                   | Yes                         |

Table 1-1. DFS Applicability

| Requirement                       | Operation Mode |                                |                             |
|-----------------------------------|----------------|--------------------------------|-----------------------------|
|                                   | Master         | Client Without Radar Detection | Client With Radar Detection |
| DFS Detection Threshold           | Yes            | Not required                   | Yes                         |
| Channel Closing Transmission Time | Yes            | Yes                            | Yes                         |
| Channel Move Time                 | Yes            | Yes                            | Yes                         |
| U-NII Detection Bandwidth         | Yes            | Not required                   | Yes                         |

Table 1-2. DFS Applicability During Normal Operation

## 7.2 REQUIREMENTS

Per KDB905462 D02 v02(04/08/2016) the following are the requirements for Client Devices:

- a) A Client Device will not transmit before having received appropriate control signals from a Master Device.
- b) A Client Device will stop all its transmissions whenever instructed by a Master Device to which it is associated and will meet the Channel Move Time and Channel Closing Transmission Time requirements.  
The Client Device will not resume any transmissions until it has again received control signals from a Master Device.
- c) If a Client Device is performing In-Service Monitoring and detects a Radar Waveform above the DFS Detection Threshold, it will inform the Master Device. This is equivalent to the Master Device detecting the Radar Waveform and d) through f) of section 5.1.1 apply.
- d) Irrespective of Client Device or Master Device detection the Channel Move Time and Channel Closing Transmission Time requirements remain the same.

Channel Move Time and Channel Closing Transmission Time requirements are listed following table.

| Parameter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Value                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Non-occupancy period                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Minimum 30 minutes                                                                                              |
| Channel Availability Check Time                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 60 seconds                                                                                                      |
| Channel Move Time                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 10 seconds<br>See Note 1.                                                                                       |
| Channel Closing Transmission Time                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 200 milliseconds + an<br>Aggregate of 60 milliseconds over<br>Remaining 10 second period. See Notes<br>1 and 2. |
| U-NII Detection Bandwidth                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Minimum 100 % of the U-NII<br>99 % transmission<br>Power bandwidth. See Note 3.                                 |
| <p><b>Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.</b></p> <p><b>Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of The Channel Move Time plus any additional intermittent control signals required to facilitate a Channell move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.</b></p> <p><b>Note3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used.</b></p> <p><b>For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed With no data traffic.</b></p> |                                                                                                                 |

Table 1-3: DFS Response requirements

### 7.3 DFS DETECTION THRESHOLD VALUES

The DFS detection thresholds are defined for Master devices and Client Devices with In-service monitoring. These detection thresholds are listed in the following table.

| Maximum Transmit Power                                                                                                                                                                                                                                                                           | Value<br>(See Notes 1 and 2) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| ≥ 200 milliwatt                                                                                                                                                                                                                                                                                  | -64 dBm                      |
| < 200 milliwatt                                                                                                                                                                                                                                                                                  | -62 dBm                      |
| Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.                                                                                                                                                                                                         |                              |
| Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. |                              |

Table 1-4: Detection Thresholds for Master Devices and Client Devices with Radar Detection

## 7.4 PARAMETERS OF DFS TEST SIGNALS

As the EUT is a Client Device with no Radar Detection only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time. Table 1-5 lists the parameters for the Short Pulse Radar Waveforms. A plot of the Radar pulse Type 0 used for testing is included in Section 7.7 of this report.

| Radar Type                                                                                                                          | Pulse Width (μsec) | PRI (μsec)                                                                                                                                                                              | Number Of Pulses                                                                                                | Minimum Percentage of Successful Detection | Minimum Number of Trials |
|-------------------------------------------------------------------------------------------------------------------------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|--------------------------------------------|--------------------------|
| 0                                                                                                                                   | 1                  | 1428                                                                                                                                                                                    | 18                                                                                                              | See Note 1                                 | See Note 1               |
| 1                                                                                                                                   | 1                  | Test A: 15 unique PRI values<br>Randomly selected<br>From the list of 23 PRI values in<br>Table 5a                                                                                      | Roundup $\left\{ \frac{1}{360} \right\}$<br>$\left\{ \frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right\}$ | 60%                                        | 30                       |
|                                                                                                                                     |                    | Test B: 15 unique PRI values<br>Randomly selected<br>within the range<br>of 518-3066 μ sec, with a<br>minimum<br>increment of 1 μ sec,<br>excluding PRI values<br>selected in<br>Test A |                                                                                                                 |                                            |                          |
| 2                                                                                                                                   | 1-5                | 150-230                                                                                                                                                                                 | 23-29                                                                                                           | 60%                                        | 30                       |
| 3                                                                                                                                   | 6-10               | 200-500                                                                                                                                                                                 | 16-18                                                                                                           | 60%                                        | 30                       |
| 4                                                                                                                                   | 11-20              | 200-500                                                                                                                                                                                 | 12-16                                                                                                           | 60%                                        | 30                       |
|                                                                                                                                     |                    |                                                                                                                                                                                         |                                                                                                                 | 80%                                        | 120                      |
| Note1: Short pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests. |                    |                                                                                                                                                                                         |                                                                                                                 |                                            |                          |

Table 1-5: Parameters for Short Pulse Radar Waveforms

## 7.5 TEST AND MEASUREMENT SYSTEM

### General Test Setup Procedure:

1. The EUT was operating 802.11ac\_VHT80 mode (MCS0) during the test.
2. Connect FCC approved Master AP to a network, via wired Ethernet, that allows connection to an FTP server.
3. Associate the EUT with the Master AP.
4. Launch the FTP application on the EUT.
5. Connect to the FTP server application to the FTP server hosting the file
6. Initiate an FTP download of the file from the host.
7. Monitor the channel loading during transfer.
8. Reduce the maximum allowed data rate for the Master AP, using the AP's GUI interface.
9. Repeat steps 5-7 until the channel loading is as close to 20 % as possible.
10. Record the data rate setting on the Master AP and the channel loading.
11. While the system is performing an FTP transfer using the settings from item 9 above, perform the Channel Closing Transmission Time and Channel Move Time Measurements as required by KDB905462 D02 v02 using a conducted test.

### PROCEDURE

The KDB905462 D02 v02 describes a radiated test setup and a conducted test setup. A radiated test setup was used for this testing. Figure 3-1 shows the typical test setup. Each one channel selected between 5260 and 5320 MHz, 5500 and 5720 is chosen for the testing.




Figure 3-1. Conducted Test Setup for DFS

1. The radar pulse generator is setup to provide a pulse at the frequency that the Master and Client are operating. A Type 0 radar pulse with a 1  $\mu$ s pulse width and a 1428  $\mu$ s PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at a level of approximately -62 dBm at the antenna of the Master device.
3. The Client Device (EUT) is set up per the diagram in Figure 3-1 and communications between the Master device and the Client is established.
4. The MPEG file specified by the FCC ("*6½ Magic Hours*") is streamed from the "file computer" through the Master to the Slave Device and played in full motion video using Media Player Classic Ver.6.4.8.6 in order to properly load the network.
5. The spectrum analyzer is set to record about 15 sec window to any transmissions occurring up to and after 10 sec.
6. The system is again setup and the monitoring time is shortened in order to capture the Channel Closing Transmission Time. This time is measured to insure that the Client ceases transmission within 200 ms and the aggregate of emissions occurring after 200 ms up to 10 sec do not exceed 60 ms.

(Note: the channel may be different since the Master and Client have changed channels due to the detection of the initial radar pulse.)

7. After the initial radar burst the channel is monitored for 30 minutes to insure no transmissions or beacons occur. A second monitoring setup is used to verify that the Master and Client have both moved to different channels.

## **SYSTEM CALIBRATION**

**A-50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a coaxial cable. The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of - 62 dBm as measured on the spectrum analyzer.**

**Without changing any of the instrument settings, the spectrum analyzer is reconnected to the common port of the spectrum analyzer combiner or divider.**

**The spectrum analyzer displays the level of the signal generator higher than the client TX level. Because we can not search the signal generator in the spectrum analyzer when the signal generator level is - 62 dBm. The spectrum analyzer will still indicate the level higher than the client TX level.**

## 7.6 DESCRIPTION OF EUT

The EUT operates over the 5260 MHz - 5320 MHz and 5500 MHz - 5700 MHz ranges.

The EUT is a slave device without radar detection.

The EUT antenna has a gain of -2.55 dBi in 5260 MHz - 5320 MHz band and -3.05 dBi in 5500 MHz- 5700 MHz band.

The highest power level within these bands is 10.06 dBm EIRP in the 5260 MHz - 5320 MHz band and 9.89 dBm EIRP in the 5500 MHz – 5700 MHz band.

The EUT one transmitter/receiver chain connected to a coaxial cable to perform conducted tests.

TPC is not required since the maximum EIRP is less than 500 mW.


The EUT utilizes the 802.11a/n/ac architecture.

The nominal channel bandwidth is implemented: 20 MHz, 40 MHz, 80 MHz

## 7.7 UNII2A TEST RESULT

### RESULT PLOTS(UNII2A Band)


Type0 Radar Pulse Number




### Marker Descriptions:

Number of Pulse Form M1R to M1 : 18


Type0 PRI



Time Display, Non WLAN Channel Traffic




Time Display, WLAN Channel Traffic (Streaming Video)





- Channel Move Time : 0.305046 s (Limit : 10 s)
- Channel Closing Transmission Time, Aggregate Time After 200 ms : 0.000144 s (Limit : 60 ms)


Non-occupancy Period – Monitoring live time spectrum analyzer – Elapse time 30 minutes



## 7.8 UNII2C TEST RESULT

### RESULT PLOTS\_(UNII2C Band)


Type0 Radar Pulse Number




#### Marker Descriptions:

Number of Pulse Form M1R to M1 : 18


Type0 PRI



Time Display, Non WLAN Channel Traffic




Time Display, WLAN Channel Traffic (Streaming Video)





- Channel Move Time : 0.13681 s (Limit : 10 s)
- Channel Closing Transmission Time, Aggregate Time After 200 ms : 0.005919 s (Limit : 60 ms)

#### Non-occupancy Period – Monitoring live spectrum analyzer – Elapse time 30 minutes



## 8. LIST OF TEST EQUIPMENT

| Manufacturer        | Model / Equipment                        | Calibration Date | Calibration Interval | Serial No.                          |
|---------------------|------------------------------------------|------------------|----------------------|-------------------------------------|
| SAMSUNG ELECTRONICS | WEA453e / Wireless AP<br>(Master Device) | N/A              | N/A                  | S2LF812265<br>FCC ID:<br>A3LWEA453E |
| ADLINK              | PXI/DFS Measurement System(S/G)          | 03/28/2016       | Annual               | 302581/735                          |
| ADLINK              | PXI/DFS Measurement System(S/A)          | 03/28/2016       | Annual               | 303582/113                          |
| Agilent             | N9020A / SIGNAL ANALYZER                 | 06/30/2015       | Annual               | MY51110085                          |
| Agilent             | N9030A / SIGNAL ANALYZER                 | 11/24/2015       | Annual               | MY49431210                          |
| Agilent             | N1911A/Power Meter                       | 07/09/2015       | Annual               | MY45100523                          |
| Agilent             | N1921A /Power Sensor                     | 03/11/2016       | Annual               | MY52260025                          |
| Hewlett Packard     | 11636B/Power Divider                     | 01/26/2016       | Annual               | 0531                                |
| Agilent             | 87300B/Directional Coupler               | 11/30/2015       | Annual               | 3116A03621                          |
| Hewlett Packard     | 11667B / Power Splitter                  | 06/15/2015       | Annual               | 5001                                |
| Hewlett Packard     | E3632A / DC POWER SUPPLY                 | 03/09/2016       | Annual               | KR75303962                          |
| Agilent             | 8493C / Attenuator(10 dB)                | 07/23/2015       | Annual               | 07560                               |
| WEINSCHTEL          | 2-3 / Attenuator(3 dB)                   | 10/26/2015       | Annual               | BR0617                              |
| Weinschel           | AF9003-69-31 / Step Attenuator           | 10/14/2015       | Annual               | 5701                                |
| Narda               | 922695 / 4 Way Divider                   | 09/22/2015       | Annual               | 15298                               |