

RF TEST REPORT

Test item : GSM&WCDMA Phone with Bluetooth, WLAN and NFC
Model No. : LG-E460, E460, LGE460
Order No. : DEMC1301-00135
Date of receipt : 2013-01-14
Test duration : 2013-01-28 ~ 2013-02-25
Date of issue : 2013-02-25
Use of report : FCC Original Grant

Applicant : LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Test laboratory : Digital EMC Co., Ltd.
683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

Test specification : FCC Part 15 Subpart C 247
Test environment : See appended test report
Test result : Pass Fail

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:


Witnessed by:

Reviewed by:



Engineer
Hyun-Su, Son

N/A



Technical Director
Harvey Sung

Test Report Version

Test Report No.	Date	Description
DRTFCC1302-0126	Feb. 15, 2013	Initial issue
DRTFCC1302-0126(1)	Feb. 25, 2013	Update conducted spurious test procedure

Table of Contents

1. General Information	5
1.1. Testing Laboratory	5
1.2. Details of Applicant	5
1.3. Description of EUT	5
1.4. Declaration by the manufacturer	5
1.5. Information about the FHSS characteristics:	6
1.5.1. Pseudorandom Frequency Hopping Sequence	6
1.5.2. Equal Hopping Frequency Use	6
1.5.3. System Receiver Input Bandwidth.....	6
1.6. Test Equipment List	7
1.7. Summary of Test Results	8
1.8. Conclusion of the worst-case and operation mode	9
2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	10
2.1. Test Setup	10
2.2. Limit.....	10
2.3. Test Procedures.....	11
2.3.1. Test Procedures for Radiated Spurious Emissions.....	11
2.3.2. Test Procedures for Conducted Spurious Emissions	11
2.4. Test Results	12
2.4.1. Radiated Emission	12
2.4.2. Conducted Spurious Emissions	15
3. Carrier Frequency Separation.....	33
3.1. Test Setup.....	33
3.2. Limit.....	33
4. Number of Hopping Frequencies	38
4.1. Test Setup.....	38
4.2. Limit.....	38
5. 20dBc BW.....	47
5.1. Test Setup	47
5.2. Limit.....	47
5.3. Test Procedure	47
5.4. Test Results	47
6. Time of Occupancy (Dwell Time).....	53
6.1. Test Setup	53
6.2. Limit.....	53
6.3. Test Procedure	53
6.4. Test Results	53
7. Maximum Peak Output Power Measurement	58
7.1. Test Setup	58
7.2. Limit.....	58
7.3. Test Procedure.....	58
7.4. Test Results	59
8. Transmitter AC Power Line Conducted Emission	65

8.1. Test Setup 65
8.2. Limit..... 65
8.3. Test Procedures..... 65
8.4. Test Results 66
9. Antenna Requirement 68
APPENDIX I 69

1. General Information

1.1. Testing Laboratory

Digital EMC Co., Ltd.

683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

www.digitalemc.com

Test Lab Site Number : 678747

Telephone : + 82-31-321-2664

FAX : + 82-31-321-1664

1.2. Details of Applicant

Applicant : LG Electronics MobileComm U.S.A., Inc.
 Address : 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
 Contact person : Cheol GooLee
 Phone No. : +82-2-2033-1111

1.3. Description of EUT

Product	GSM&WCDMA Phone with Bluetooth, WLAN and NFC
Model Name	LG-E460, E460, LGE460 ※ 3 models are same mechanical, electrical and functional. ※ The only difference is the model name, which are changed for marketing purpose.
Serial Number	Identical prototype
Power Supply	Lithium Ion Battery: DC 3.8V
Frequency Range	2402 ~ 2480MHz
Modulation Technique	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channels	79
Antenna Type	Internal Antenna
Antenna Gain	PK :0.7dBi

1.4. Declaration by the manufacturer

- N/A

1.5. Information about the FHSS characteristics:

1.5.1. Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1600 hops/s.

1.5.2. Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

1.5.3. System Receiver Input Bandwidth

Each channel bandwidth is 1MHz

1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent	E4440A	12/09/18	13/09/18	MY45304199
Spectrum Analyzer	Rohde Schwarz	FSQ26	12/02/06	13/02/06	200445
			13/02/14	14/02/14	
Power Splitter	Anritsu	K241B	12/09/17	13/09/17	020611
Digital Multimeter	H.P	34401A	12/03/05	13/03/05	3146A13475
Signal Generator	Rohde Schwarz	SMR20	12/03/05	13/03/05	101251
Bluetooth Tester	TESCOM	TC-3000B	12/07/01	13/07/01	3000B640046
Thermo hygrometer	BODYCOM	BJ5478	12/06/20	13/06/20	120612-2
DC Power Supply	HP	6622A	12/03/05	13/03/05	3448A03760
High-pass filter	Wainwright	WHNX3.0	12/09/17	13/09/17	9
LOOP Antenna	Schwarzbeck	FMZB1513	12/09/24	13/09/24	1513-128
BILOG ANTENNA	SCHAFFNER	CBL6112B	12/11/16	14/11/16	2737
HORN ANT	ETS	3115	12/02/20	14/02/20	6419
HORN ANT	A.H.Systems	SAS-574	11/03/25	13/03/25	154
Amplifier (22dB)	H.P	8447E	13/01/08	14/01/08	2945A02865
Amplifier (30dB)	Agilent	8449B	12/03/05	13/03/05	3008A00370
EMI TEST RECEIVER	R&S	ESU	13/01/08	14/01/08	100014
EMI TEST RECEIVER	R&S	ESCI	12/03/06	13/03/06	100364
CVCF	KIKUSUI	PCR1000L	12/09/15	13/09/15	14110610
LISN	R&S	ESH2-Z5	12/09/18	13/09/18	828739/006

1.7. Summary of Test Results

FCC Part Section(s)	Parameter	Limit (Using in 2400~ 2483.5MHz)	Test Condition	Status Note 1
15.247(a)	Carrier Frequency Separation	>= 20dB BW or >= Two-Thirds of the 20dB BW	Conducted	C
	Number of Hopping Frequencies	>= 15 hops		C
	20 dB Bandwidth	None		C
	Dwell Time	=< 0.4 seconds		C
15.247(b)	Transmitter Output Power	=< 1Watt , if CHs >= 75 Others =<0.125W		C
15.247(d)	Band-edge	The radiated emission to any 100 kHz of out-band shall be at least 20dB below the highest in-band spectral density.		C
	Conducted Spurious Emissions			C
15.205 15.209	RadiatedEmissions	FCC 15.209 Limits		Radiated
15.207	AC Conducted Emissions	FCC 15.207 Limits	AC Line Conducted	C
15.203	Antenna Requirements	FCC 15.203	-	C

Note 1: **C**=Comply **NC**=Not Comply **NT**=Not Tested **NA**=Not Applicable

Note 2:The sample was tested according to the following specification:
 ANSI C63.10-2009, DA00-705

1.8. Conclusion of the worst-case and operation mode

The EUT has three type of modulation (GFSK, $\pi/4$ DQPSK and 8DPSK).

Therefore all applicable requirements were tested with all the modulations.

The field strength of spurious emission was measured in three orthogonal EUT positions(X-axis, Y-axis and Z-axis).

Tested frequency information,

- Hopping Function: Enable

	TXFrequency(MHz)	RX Frequency(MHz)
Hopping Band	2402 ~ 2480	2402 ~ 2480

- Hopping Function: Disable

	TXFrequency(MHz)	RX Frequency(MHz)
Lowest Channel	2402	2402
Middle Channel	2441	2441
Highest Channel	2480	2480

2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

2.1. Test Setup

Refer to the APPENDIX I.

2.2. Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	3600 ~ 4400	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	4.5 ~ 5.15	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	5.35 ~ 5.46	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~	1660 ~ 1710	7.25 ~ 7.75	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.52525	1718.8 ~ 1722.2	8.025 ~ 8.5	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	156.7 ~ 156.9	2200 ~ 2300	9.0 ~ 9.2	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	162.0125 ~ 167.17	2310 ~ 2390	9.3 ~ 9.5	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	167.72 ~ 173.2	2483.5 ~ 2500	10.6 ~ 12.7	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	240 ~ 285	2655 ~ 2900	13.25 ~ 13.4	
8.291 ~ 8.294	37.5 ~ 38.25	322 ~ 335.4	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	399.90 ~ 410	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	608 ~ 614	3345.8 ~ 3358		
		960 ~ 1240			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the ANSI C63.10-2009

2.3.1. Test Procedures for Radiated Spurious Emissions

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Note : Measurement Instrument Setting for Radiated Emission Measurements.

1. Frequency Range \leq 1 GHz

RBW = 100 or 120 KHz, VBW = 3 x RBW , Detector = Peak or Quasi Peak

2. Frequency Range $>$ 1 GHz

Peak Measurement $>$ 1 GHz

RBW = 1 MHz , VBW = 3 MHz, Detector = Peak

Average Measurement $>$ 1GHz

VBW = 1 KHz (Reduce VBW to at least 100 times less than the RBW, but no less than 10 Hz.)

Note1: The reduced VBW measurement method of Section 4.2.3.2.3 in ANSI C63.10 is used.

Note2: If necessary, ANSI C63.10 Section 4.2.3.2.4 is applied for pulsed emissions as following description.

Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 s. As an alternative (provided the unlicensed wireless device operates for longer than 0.1 s) or in cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval while the field strength is at its maximum value. Please see Note 4 of the radiated emission tables for calculation of Duty cycle Correction Factor (DCF).

2.3.2. Test Procedures for Conducted Spurious Emissions

1. The transmitter output was connected to the spectrum analyzer.
2. The **reference level** of the fundamental frequency was measured with the spectrum analyzer using RBW=100 kHz, VBW=300kHz.
3. The conducted spurious emission was performed using the spectrum analyzer's spurious measurement function from 30 MHz to 25 GHz with the 12 sub measurement ranges. The each sub ranges were set as below.

RBW= 1 MHz, VBW= 3 MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SPAN = MAX 3 GHz (Below 10 GHz) and MAX 5 GHz (Above 10 GHz) , BINS = 10001 (Each sub range below 10 GHz) and 20001 (Each sub range above 10 GHz)

LIMIT LINE = 20 dB below of the reference level of above measurement procedure. (RBW = 100 KHz , VBW = 300 KHz)

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 KHz, VBW = 300 KHz, SPAN = 100 MHz and BINS = 2001 to get accurate emission level within 100 KHz BW.

Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.

2.4. Test Results

Ambient temperature : 21°C
 Relative humidity : 44%

2.4.1. Radiated Emission

9KHz ~ 25GHz Data(Modulation: GFSK)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2385.84	H	Y	PK	50.59	-5.24	N/A	45.35	74.00	28.65
2386.00	H	Y	AV	40.49	-5.24	N/A	35.25	54.00	18.75
4803.82	H	Y	PK	45.32	2.11	N/A	47.43	74.00	26.57
4804.03	H	Y	AV	35.65	2.11	N/A	37.76	54.00	16.24

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.49	H	Y	PK	44.92	2.16	N/A	47.08	74.00	26.92
4882.04	H	Y	AV	35.14	2.16	N/A	37.30	54.00	16.70

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.57	H	Y	PK	62.67	-4.99	N/A	57.68	74.00	16.32
2483.50	H	Y	AV	41.95	-4.99	N/A	36.96	54.00	17.04
4960.06	H	Y	PK	45.95	1.70	N/A	47.65	74.00	26.35
4959.98	H	Y	AV	36.08	1.70	N/A	37.78	54.00	16.22

Note.

- 1.No other spurious and harmonic emissions were reported greater than listed emissions above table.
- 2.Above listed point data is the worst case data.
- 3.Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} + \text{D.C.F.} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,

4.D.C.F Calculation. (D.C.F. = Duty Cycle Correction Factor)

- Time to cycle through all channels= $\Delta t = \tau_{[ms]} \times 79$ channels , where τ = pulse width
- $100ms / \Delta t_{[ms]} = H$ -> Round up to next highest integer, to account for worst case, H'
- The Worst Case Dwell Time = $\tau_{[ms]} \times H'$
- Duty Cycle Correction = $20 \times \text{Log}(\text{The Worst Case Dwell Time} / 100ms)$ dB

9KHz ~ 25GHz Data(Modulation: $\pi/4$ DQPSK)

▪ **Lowest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2386.08	H	Y	PK	52.18	-5.24	N/A	46.94	74.00	27.06
2386.32	H	Y	AV	42.15	-5.24	N/A	36.91	54.00	17.09
4804.33	H	Y	PK	44.15	2.11	N/A	46.26	74.00	27.74
4804.10	H	Y	AV	33.43	2.11	N/A	35.54	54.00	18.46

▪ **Middle Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.97	H	Y	PK	43.25	2.16	N/A	45.41	74.00	28.59
4882.08	H	Y	AV	32.78	2.16	N/A	34.94	54.00	19.06

▪ **Highest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.50	H	Y	PK	58.82	-4.99	N/A	53.83	74.00	20.17
2483.50	H	Y	AV	40.93	-4.99	N/A	35.94	54.00	18.06
4960.34	H	Y	PK	44.86	1.70	N/A	46.56	74.00	27.44
4959.96	H	Y	AV	33.03	1.70	N/A	34.73	54.00	19.27

Note.

- 1.No other spurious and harmonic emissions were reported greater than listed emissions above table.
- 2.Above listed point data is the worst case data.
- 3.Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} + \text{D.C.F.} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,

4.D.C.F Calculation. (D.C.F. = Duty Cycle Correction Factor)

- Time to cycle through all channels= $\Delta t = \tau_{[ms]} \times 79$ channels , where τ = pulse width
- $100ms / \Delta t_{[ms]} = H$ -> Round up to next highest integer, to account for worst case. H'
- The Worst Case Dwell Time = $\tau_{[ms]} \times H'$
- Duty Cycle Correction = $20 \times \text{Log}(\text{The Worst Case Dwell Time} / 100ms)$ dB

9KHz ~ 25GHz Data(Modulation: 8DPSK)

▪ **Lowest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2386.25	H	Y	PK	52.30	-5.24	N/A	47.06	74.00	26.94
2384.24	H	Y	AV	42.12	-5.24	N/A	36.88	54.00	17.12
4804.42	H	Y	PK	44.45	2.11	N/A	46.56	74.00	27.44
4803.70	H	Y	AV	33.32	2.11	N/A	35.43	54.00	18.57

▪ **Middle Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.36	H	Y	PK	44.74	2.16	N/A	46.90	74.00	27.10
4881.95	H	Y	AV	32.66	2.16	N/A	34.82	54.00	19.18

▪ **Highest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.52	H	Y	PK	59.58	-4.99	N/A	54.59	74.00	19.41
2483.55	H	Y	AV	40.97	-4.99	N/A	35.98	54.00	18.02
4960.23	H	Y	PK	44.57	1.70	N/A	46.27	74.00	27.73
4959.98	H	Y	AV	33.26	1.70	N/A	34.96	54.00	19.04

Note.

- 1.No other spurious and harmonic emissions were reported greater than listed emissions above table.
- 2.Above listed point data is the worst case data.
- 3.Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} + \text{D.C.F.} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,


4.D.C.F Calculation. (D.C.F. = Duty Cycle Correction Factor)

- Time to cycle through all channels= $\Delta t = \tau_{[ms]} \times 79$ channels , where τ = pulse width
- $100ms / \Delta t_{[ms]} = H$ -> Round up to next highest integer, to account for worst case, H'
- The Worst Case Dwell Time = $\tau_{[ms]} \times H'$
- Duty Cycle Correction = $20 \times \text{Log}(\text{The Worst Case Dwell Time} / 100ms)$ dB

2.4.2. Conducted Spurious Emissions


Low Band-edge

Lowest Channel Modulation: **GFSK**





Low Band-edge

Hopping mode Modulation: **GFSK**




Conducted Spurious Emissions

Lowest Channel Modulation: **GFSK**




Reference for limit


Middle Channel Modulation: **GFSK**



Conducted Spurious Emissions

Middle Channel Modulation: **GFSK**






Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
10.000 G	12.000 G	1.00 M	11.752100 G	-45.16
12.000 G	15.000 G	1.00 M	14.707950 G	-45.95
15.000 G	20.000 G	1.00 M	17.792250 G	-44.24
20.000 G	25.000 G	1.00 M	24.816500 G	-41.25


High Band-edge

Highest Channel & Modulation: **GFSK**




High Band-edge

Hopping mode & Modulation: **GFSK**




Conducted Spurious Emissions

Highest Channel Modulation: **GFSK**




Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
30.000 M	1.000 G	1.00 M	943.352000 M	-49.31
1.000 G	2.000 G	1.00 M	1.068600 G	-48.21
2.000 G	2.400 G	1.00 M	2.353400 G	-47.28
2.400 G	2.483 G	1.00 M	2.480077 G	5.45
2.483 G	3.000 G	1.00 M	2.483603 G	-36.80
3.000 G	6.000 G	1.00 M	3.560400 G	-46.40
6.000 G	9.000 G	1.00 M	8.139000 G	-46.33
9.000 G	10.000 G	1.00 M	9.921300 G	-46.46



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
10.000 G	12.000 G	1.00 M	11.529900 G	-45.63
12.000 G	15.000 G	1.00 M	12.590100 G	-46.26
15.000 G	20.000 G	1.00 M	19.189000 G	-44.49
20.000 G	25.000 G	1.00 M	24.856500 G	-41.32


Low Band-edge

Lowest Channel Modulation: **$\pi/4$ DQPSK**





Low Band-edge

Hopping mode Modulation: **$\pi/4$ DQPSK**




Conducted Spurious Emissions

Lowest Channel Modulation: $\pi/4$ DQPSK




Reference for limit


Middle Channel&Modulation: **$\pi/4$ DQPSK**



Conducted Spurious Emissions

Middle Channel&Modulation: **$\pi/4$ DQPSK**






Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
10.000 G	12.000 G	1.00 M	10.838400 G	-45.98
12.000 G	15.000 G	1.00 M	13.493550 G	-46.44
15.000 G	20.000 G	1.00 M	18.354000 G	-44.47
20.000 G	25.000 G	1.00 M	24.023750 G	-41.03


High Band-edge

Highest Channel&Modulation: $\pi/4$ DQPSK




High Band-edge

Hopping mode& Modulation: $\pi/4$ DQPSK




Conducted Spurious Emissions

Highest Channel & Modulation: **$\pi/4$ DQPSK**




Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
30.000 M	1.000 G	1.00 M	981.085000 M	-49.69
1.000 G	2.000 G	1.00 M	1.966400 G	-47.64
2.000 G	2.400 G	1.00 M	2.397720 G	-47.31
2.400 G	2.483 G	1.00 M	2.480202 G	4.23
2.483 G	3.000 G	1.00 M	2.483500 G	-37.92
3.000 G	6.000 G	1.00 M	3.573300 G	-46.83
6.000 G	9.000 G	1.00 M	8.737200 G	-46.94
9.000 G	10.000 G	1.00 M	9.743200 G	-45.80



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
10.000 G	12.000 G	1.00 M	10.250200 G	-45.96
12.000 G	15.000 G	1.00 M	12.921300 G	-46.04
15.000 G	20.000 G	1.00 M	19.888000 G	-44.40
20.000 G	25.000 G	1.00 M	24.875250 G	-41.75

Low Band-edge

Lowest Channel Modulation: **8DPSK**





Low Band-edge

Hopping mode Modulation: **8DPSK**




Conducted Spurious Emissions

Lowest Channel Modulation: **8DPSK**




Reference for limit


Middle Channel Modulation: **8DPSK**



Conducted Spurious Emissions

Middle Channel Modulation: **8DPSK**






Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
10.000 G	12.000 G	1.00 M	10.630600 G	-45.97
12.000 G	15.000 G	1.00 M	12.066750 G	-46.40
15.000 G	20.000 G	1.00 M	18.295500 G	-44.67
20.000 G	25.000 G	1.00 M	24.820750 G	-40.41


High Band-edge

Highest Channel Modulation: **8DPSK**




High Band-edge

Hopping mode Modulation: **8DPSK**




Conducted Spurious Emissions

Highest Channel Modulation: **8DPSK**



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
30.000 M	1.000 G	1.00 M	819.386000 M	-48.77
1.000 G	2.000 G	1.00 M	1.846600 G	-47.72
2.000 G	2.400 G	1.00 M	2.398120 G	-48.05
2.400 G	2.483 G	1.00 M	2.480018 G	3.90
2.483 G	3.000 G	1.00 M	2.483500 G	-37.93
3.000 G	6.000 G	1.00 M	5.189100 G	-46.73
6.000 G	9.000 G	1.00 M	8.738400 G	-46.79
9.000 G	10.000 G	1.00 M	9.698500 G	-46.67



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]
10.000 G	12.000 G	1.00 M	10.943800 G	-45.39
12.000 G	15.000 G	1.00 M	14.070300 G	-45.92
15.000 G	20.000 G	1.00 M	19.994750 G	-45.01
20.000 G	25.000 G	1.00 M	24.808000 G	-40.34

3. Carrier Frequency Separation

3.1. Test Setup

Refer to the APPENDIX I.

3.2. Limit

Limit: $\geq 20\text{dB BW}$ or $\geq \text{Two-Thirds of the } 20\text{dB BW}$

- Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = wide enough to capture the peaks of two adjacent channels

RBW = 1% of the span

Sweep = auto

VBW = \geq RBW

Detector function = peak

Trace = max hold

- Measurement Data: Comply

- FH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	Test Case 1	2440.976	2441.981	1.005
	Test Case 2	2441.033	2442.038	1.005
	Test Case 3	2440.151	2441.153	1.002

- AFH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	Test Case 1	2409.968	2410.970	1.002
	Test Case 2	2411.006	2412.014	1.008
	Test Case 3	2411.153	2412.155	1.002


Note 1: See next pages for actual measured spectrum plots.

- Minimum Standard:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
 Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


Carrier Frequency Separation (FH)

Hopping mode: Enable&Test Case 1




Carrier Frequency Separation (FH)

Hopping mode: Enable&Test Case 2




Carrier Frequency Separation (FH)

Hopping mode: Enable&Test Case 3




Carrier Frequency Separation (AFH)

Hopping mode: Enable&Test Case 1




Carrier Frequency Separation (AFH)

Hopping mode: Enable&Test Case 2



Carrier Frequency Separation (AFH)

Hopping mode: Enable&Test Case 3



4. Number of Hopping Frequencies

4.1. Test Setup

Refer to the APPENDIX I.

4.2. Limit

Limit: >= 15 hops

- Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

Span = 25MHz Plot 1: Start Frequency = 2389.5MHz, Stop Frequency = 2414.5 MHz
 Plot 2: Start Frequency = 2414.5MHz, Stop Frequency = 2439.5 MHz
 Plot 3: Start Frequency = 2439.5MHz, Stop Frequency = 2464.5 MHz
 Plot 4: Start Frequency = 2464.5MHz, Stop Frequency = 2489.5 MHz

RBW = 1% of the span or more

Sweep = auto

VBW = ≥ RBW

Detector function = peak

Trace = max hold

- Measurement Data: Comply

- FH mode

Hopping mode	Test mode	Test Result (Total Hops)
Enable	Test Case 1	79
	Test Case 2	79
	Test Case 3	79

- AFH mode


Hopping mode	Test mode	Test Result (Total Hops)
Enable	Test Case 1	20
	Test Case 2	20
	Test Case 3	20

Note 1: See next pages for actual measured spectrum plots.


- Minimum Standard:

At least 15 hopes


Number of Hopping Frequencies 1(FH) Hopping mode: Enable & Test Case 1




Number of Hopping Frequencies 2(FH) Hopping mode: Enable & Test Case 1




Number of Hopping Frequencies 3(FH) Hopping mode: Enable & Test Case 1




Number of Hopping Frequencies 4(FH) Hopping mode: Enable & Test Case 1




Number of Hopping Frequencies 1(FH) Hopping mode: Enable & Test Case 2




Number of Hopping Frequencies 2(FH) Hopping mode: Enable & Test Case 2




Number of Hopping Frequencies 3(FH) Hopping mode: Enable & Test Case 2




Number of Hopping Frequencies 4(FH) Hopping mode: Enable & Test Case 2




Number of Hopping Frequencies 1(FH) Hopping mode: Enable & Test Case 3




Number of Hopping Frequencies 2(FH) Hopping mode: Enable & Test Case 3




Number of Hopping Frequencies 3(FH) Hopping mode: Enable & Test Case 3




Number of Hopping Frequencies 4(FH) Hopping mode: Enable & Test Case 3




Number of Hopping Frequencies 1(AFH) Hopping mode: Enable & Test Case 1



Number of Hopping Frequencies 1(AFH) Hopping mode: Enable & Test Case 2



Number of Hopping Frequencies 1(AFH) Hopping mode: Enable & Test Case 3



Copyright 2000-2007 Agilent Technologies

5. 20dBc BW

5.1. Test Setup

Refer to the APPENDIX I.

5.2. Limit

Limit: Not Applicable

5.3. Test Procedure

1. The 20dBc band width were measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using $RBW \geq 1\%$ of the 20 dB bandwidth, $VBW \geq RBW$, Span = 3MHz.

5.4. Test Results


Ambient temperature : 24°C
 Relative humidity : 43%

Modulation	Tested Channel	20dBc BW (MHz)
<u>GFSK</u>	Lowest	0.930
	Middle	0.930
	Highest	0.930
<u>$\pi/4$DQPSK</u>	Lowest	1.305
	Middle	1.281
	Highest	1.311
<u>8DPSK</u>	Lowest	1.269
	Middle	1.272
	Highest	1.269

Note 1: See next pages for actual measured spectrum plots.

20dBc Bandwidth

Lowest Channel Modulation: **GFSK**




20dBc Bandwidth

Middle Channel Modulation: **GFSK**



20dBc Bandwidth

Highest Channel Modulation: **GFSK**




20dBc Bandwidth

Lowest Channel Modulation: **$\pi/4$ DQPSK**



20dBc Bandwidth

Middle Channel Modulation: **$\pi/4$ DQPSK**




20dBc Bandwidth

Highest Channel Modulation: **$\pi/4$ DQPSK**



20dBc Bandwidth

Lowest Channel Modulation: **8DPSK**




20dBc Bandwidth

Middle Channel Modulation: **8DPSK**



20dBc Bandwidth

Highest Channel & Modulation: 8DPSK



6. Time of Occupancy (Dwell Time)

6.1. Test Setup

Refer to the APPENDIX I.

6.2. Limit

Limit: Not Applicable

6.3. Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

RBW = 1 MHz

Trace = max hold

Span = zero

VBW = ≥ RBW

Detector function = peak

6.4. Test Results

Ambient temperature : 24°C

Relative humidity : 43 %

- FH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	DH 5	79	2.870	3.750	0.306
	2 DH 5	79	2.870	3.750	0.306
	3 DH 5	79	2.870	3.750	0.306

- AFH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	DH 5	20	2.870	3.750	0.153
	2 DH 5	20	2.870	3.750	0.153
	3 DH 5	20	2.870	3.750	0.153

Note 1: Dwell Time = $0.4 \times \text{Hopping channel} \times \text{Burst ON time} \times ((\text{Hopping rate} \div \text{Time slots}) \div \text{Hopping channel})$


- Time slots for DH5 = 6 slots(TX = 5 slot / RX = 1 slot)

- Hopping Rate = 1600 for FH mode & 800 for AFH mode

Note 2: See next pages for actual measured spectrum plots.


Time of Occupancy (FH)

Hopping mode: Enable & Test Case 1




Time of Occupancy (FH)

Hopping mode: Enable & Test Case 2




Time of Occupancy (FH)

Hopping mode: Enable & Test Case 3




Time of Occupancy (AFH)

Hopping mode: Enable& Test Case 1




Time of Occupancy (AFH)

Hopping mode: Enable& Test Case 2



Time of Occupancy (AFH)

Hopping mode: Enable & Test Case 3



7. Maximum Peak Output Power Measurement

7.1. Test Setup

Refer to the APPENDIX I.

7.2. Limit

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. §15.247(b)(1), For frequency hopping systems operating in the 2400 – 2483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725 – 5805 MHz band: 1 Watt.

7.3. Test Procedure

1. The RF power output was measured with a Spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using ;
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq 20dB BW
VBW \geq RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.4. Test Results


Ambient temperature : 24°C
 Relative humidity : 43 %

Modulation	Tested Channel	Peak Output Power	
		dBm	mW
<u>GFSK</u>	Lowest	5.20	3.311
	Middle	4.78	3.006
	Highest	5.59	3.622
<u>$\pi/4$DQPSK</u>	Lowest	4.30	2.692
	Middle	3.94	2.477
	Highest	4.75	2.985
<u>8DPSK</u>	Lowest	4.45	2.786
	Middle	4.40	2.754
	Highest	5.32	3.404

Note 1: See next pages for actual measured spectrum plots.

Peak Output Power

Lowest Channel Modulation: **GFSK**




Peak Output Power

Middle Channel Modulation: **GFSK**




Peak Output Power

Highest Channel Modulation: **GFSK**




Peak Output Power

Lowest Channel Modulation: **$\pi/4$ DQPSK**




Peak Output Power

Middle Channel Modulation: **$\pi/4$ QPSK**




Peak Output Power

Highest Channel Modulation: **$\pi/4$ QPSK**



Peak Output Power

Lowest Channel Modulation: **8DPSK**




Peak Output Power

Middle Channel Modulation: **8DPSK**



Peak Output Power

Highest Channel Modulation: **8DPSK**



8. Transmitter AC Power Line Conducted Emission

8.1. Test Setup

Refer to test setup photo.

8.2. Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

8.3. Test Procedures

Conducted emissions from the EUT were measured according to the dictates of ANSI C63.10-2009

1. The test procedure is performed in a 6.5 m x 3.5 m x 3.5 m (L x W x H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) x 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

8.4. Test Results

AC Line Conducted Emissions (Graph)& Modulation: **GFSK**





Results of Conducted Emission

Digital EMC
 Date : 2013-02-04

Model No.	: LG-E480	Reference No.	:
Type	:	Power Supply	: 120 V 60 Hz
Serial No.	: Identical prototype	Temp/Humi.	: 24 °C 45 % R.H.
Test Condition	: BT	Operator	: H.S SON
Memo	: Hopping Mode		

LIMIT : CISPR22_B QP
 CISPR22_B AV



9. Antenna Requirement

■ **Procedure:**

Describe how the EUT complies with the requirement that either its antenna is permanently attached, or that it employs a unique antenna connector, for every antenna proposed for use with the EUT.

■ **Conclusion: Comply**

The internal antenna is attached on the main PCB using the special spring tension. (Refer to Internal Photo file.)

■ **Minimum Standard:**


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions.

APPENDIX I


Test set up Diagrams&Path lossInformation

▪Radiated Measurement

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 25GHz Emissions.



▪Conducted Measurement



Offset value information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	5.80	15	8.48
1	6.36	20	8.77
2.402 & 2.441 & 2.480	6.84	26.5	9.32
5	7.24	-	-
10	7.86	-	-

Note. 1: The path loss from EUT to Spectrum analyzer were measured and used for test.

Path loss (= S/A's Offset value) = Cable A + Power Splitter + Cable B

Note. 2: For conducted spurious emissions, the offset values were saved as the transducer factors on the spurious measurement function of the spectrum analyzer and the transducer factor of tested frequency is calculated and corrected automatically by the spectrum analyzer's measurement function.