

## Attachment 1. – Dipole Validation Plots

## DIGITAL EMC CO., LTD

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.876 \text{ mho/m}$ ;  $\epsilon_r = 42.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section


### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

### Dipole Validation

Area Scan (51x101x1): Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Zoom Scan (7x7x7)/Cube 0: Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.032 dB  
 Peak SAR (extrapolated) = 3.49 W/kg  
 SAR(1 g) = 2.32 W/kg; SAR(10 g) = 1.52 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.955 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section


### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

### Dipole Validation

**Area Scan (41x11x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = -0.027 dB  
Peak SAR (extrapolated) = 3.73 W/kg  
SAR(1 g) = 2.49 W/kg; SAR(10 g) = 1.64 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.882 \text{ mho/m}$ ;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section


### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

### Dipole Validation

**Area Scan (61x81x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.059 dB  
 Peak SAR (extrapolated) = 3.61 W/kg  
 SAR(1 g) = 2.39 W/kg; SAR(10 g) = 1.57 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.954 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section


### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

### Dipole Validation

Area Scan (41x111x1): Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Zoom Scan (7x7x7)/Cube 0: Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = -0.009 dB  
Peak SAR (extrapolated) = 3.69 W/kg  
SAR(1 g) = 2.48 W/kg; SAR(10 g) = 1.63 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d029**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.44 \text{ mho/m}$ ;  $\epsilon_r = 40.7$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519

Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

### Dipole Validation


**Area Scan (61x91x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = -0.002 dB

Peak SAR (extrapolated) = 20.0 W/kg

SAR(1 g) = 10.4 W/kg; SAR(10 g) = 5.28 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d029**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-01-27; Electronics: DAE3 Sn519

Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

### Dipole Validation


**Area Scan (51x71x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Power Drift = 0.048 dB

Peak SAR (extrapolated) = 20.3 W/kg

SAR(1 g) = 10.6 W/kg; SAR(10 g) = 5.38 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d029**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.42 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519

Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-20; Ambient Temp: 21.9; Tissue Temp: 22.1

### Dipole Validation


**Area Scan (61x91x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.110 dB

Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.21 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d029**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 51.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-01-27; Electronics: DAE3 Sn519

Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-20; Ambient Temp: 21.9; Tissue Temp: 22.1

### Dipole Validation


**Area Scan (51x91x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Power Drift = -0.004 dB

Peak SAR (extrapolated) = 18.5 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.4 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:726**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.83 \text{ mho/m}$ ;  $\epsilon_r = 40.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(7.12, 7.12, 7.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

### Dipole Validation


**Area Scan (51x71x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = -0.010 dB

Peak SAR (extrapolated) = 28.5 W/kg

SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.05 W/kg



## DIGITAL EMC CO., LTD

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:726**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 51.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section


### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(6.95, 6.95, 6.95); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

### Dipole Validation

**Area Scan (51x71x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Power Drift = 0.007 dB  
 Peak SAR (extrapolated) = 27.7 W/kg  
 SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.12 W/kg



## Attachment 2. – SAR Test Plots

**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.878 \text{ mho/m}$ ;  $\epsilon_r = 42.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**Left Touch, GSM850 Ch. 190, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.020 dB  
 Peak SAR (extrapolated) = 0.148 W/kg  
 SAR(1 g) = 0.117 W/kg; SAR(10 g) = 0.089 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 824.2 \text{ MHz}$ ;  $\sigma = 0.867 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**Right Touch, GSM850 Ch. 128, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.167 dB  
 Peak SAR (extrapolated) = 0.216 W/kg  
 SAR(1 g) = 0.171 W/kg; SAR(10 g) = 0.130 W/kg



**DIGITAL EMC CO., LTD**

**DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.878 \text{ mho/m}$ ;  $\epsilon_r = 42.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**Right Touch, GSM850 Ch. 190, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.054 dB  
 Peak SAR (extrapolated) = 0.159 W/kg  
 SAR(1 g) = 0.125 W/kg; SAR(10 g) = 0.095 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 848.8 \text{ MHz}$ ;  $\sigma = 0.889 \text{ mho/m}$ ;  $\epsilon_r = 42.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**Right Touch, GSM850 Ch. 251, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.194 dB  
Peak SAR (extrapolated) = 0.134 W/kg  
SAR(1 g) = 0.107 W/kg; SAR(10 g) = 0.081 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.878 \text{ mho/m}$ ;  $\epsilon_r = 42.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519

Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**Left Tilt, GSM850 Ch. 190, Ant Internal, Standard Battery****Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = 0.089 dB

Peak SAR (extrapolated) = 0.102 W/kg

SAR(1 g) = 0.084 W/kg; SAR(10 g) = 0.065 W/kg



0 dB = 0.093mW/g

**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.878 \text{ mho/m}$ ;  $\epsilon_r = 42.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**Right Tilt, GSM850 Ch. 190, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.055 dB  
 Peak SAR (extrapolated) = 0.098 W/kg  
 SAR(1 g) = 0.080 W/kg; SAR(10 g) = 0.062 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: PCS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.4$  mho/m;  $\epsilon_r = 40.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

**Left Touch, PCS1900 Ch. 512, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Power Drift = 0.049 dB  
 Peak SAR (extrapolated) = 0.692 W/kg  
 SAR(1 g) = 0.423 W/kg; SAR(10 g) = 0.262 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

**Left Touch, PCS1900 Ch. 661, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.027 dB  
Peak SAR (extrapolated) = 0.881 W/kg  
SAR(1 g) = 0.541 W/kg; SAR(10 g) = 0.331 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: PCS1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 1909.8 \text{ MHz}$ ;  $\sigma = 1.45 \text{ mho/m}$ ;  $\epsilon_r = 40.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

**Left Touch, PCS1900 Ch. 810, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.022 dB  
 Peak SAR (extrapolated) = 1.05 W/kg  
 SAR(1 g) = 0.621 W/kg; SAR(10 g) = 0.365 W/kg



**DIGITAL EMC CO., LTD**

**DUT: LG-E612g; Type: Bar**

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.43 \text{ mho/m}$ ;  $\epsilon_r = 40.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

**Right Touch, PCS1900 Ch. 661, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.068 dB  
 Peak SAR (extrapolated) = 0.712 W/kg  
 SAR(1 g) = 0.466 W/kg; SAR(10 g) = 0.284 W/kg



## DIGITAL EMC CO., LTD

**DUT: LG-E612g; Type: Bar**

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section


### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

**Left Tilt, PCS1900 Ch. 661, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = 0.063 dB  
Peak SAR (extrapolated) = 0.187 W/kg  
SAR(1 g) = 0.112 W/kg; SAR(10 g) = 0.065 W/kg



## DIGITAL EMC CO., LTD

**DUT: LG-E612g; Type: Bar**

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Right Section


### DASY4 Configuration:

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-21; Ambient Temp: 22.0; Tissue Temp: 22.2

**Right Tilt, PCS1900 Ch. 661, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = 0.099 dB  
Peak SAR (extrapolated) = 0.224 W/kg  
SAR(1 g) = 0.139 W/kg; SAR(10 g) = 0.081 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 826.4 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 826.4 \text{ MHz}$ ;  $\sigma = 0.875 \text{ mho/m}$ ;  $\epsilon_r = 41.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

**Left Touch, WCDMA850 Ch. 4132, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = -0.103 dB  
 Peak SAR (extrapolated) = 0.273 W/kg  
 SAR(1 g) = 0.220 W/kg; SAR(10 g) = 0.169 W/kg



0 dB = 0.245mW/g

**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.883 \text{ mho/m}$ ;  $\epsilon_r = 41.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

**Left Touch, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**


**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.193 W/kg

SAR(1 g) = 0.153 W/kg; SAR(10 g) = 0.116 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 846.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 846.6 \text{ MHz}$ ;  $\sigma = 0.892 \text{ mho/m}$ ;  $\epsilon_r = 41.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

**Left Touch, WCDMA850 Ch. 4233, Ant Internal, Standard Battery****Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = 0.062 dB

Peak SAR (extrapolated) = 0.176 W/kg

SAR(1 g) = 0.140 W/kg; SAR(10 g) = 0.107 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.883 \text{ mho/m}$ ;  $\epsilon_r = 41.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

**Right Touch, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = -0.105 dB  
 Peak SAR (extrapolated) = 0.177 W/kg  
 SAR(1 g) = 0.141 W/kg; SAR(10 g) = 0.108 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.883 \text{ mho/m}$ ;  $\epsilon_r = 41.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

**Left Tilt, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**

**Area Scan (71x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.064 dB  
 Peak SAR (extrapolated) = 0.141 W/kg  
 SAR(1 g) = 0.116 W/kg; SAR(10 g) = 0.090 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.883 \text{ mho/m}$ ;  $\epsilon_r = 41.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(8.94, 8.94, 8.94); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-24; Ambient Temp: 22.1; Tissue Temp: 22.5

**Right Tilt, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.105 dB  
 Peak SAR (extrapolated) = 0.132 W/kg  
 SAR(1 g) = 0.108 W/kg; SAR(10 g) = 0.083 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-20; Ambient Temp: 21.9; Tissue Temp: 22.1

**Left Touch, WCDMA1900 Ch. 9262, Ant Internal, Standard Battery**


**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = 0.055 dB

Peak SAR (extrapolated) = 0.780 W/kg

SAR(1 g) = 0.486 W/kg; SAR(10 g) = 0.302 W/kg



0 dB = 0.594mW/g

**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-20; Ambient Temp: 21.9; Tissue Temp: 22.1

**Left Touch, WCDMA1900 Ch. 9400, Ant Internal, Standard Battery**


**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = 0.047 dB

Peak SAR (extrapolated) = 1.19 W/kg

SAR(1 g) = 0.733 W/kg; SAR(10 g) = 0.446 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-20; Ambient Temp: 21.9; Tissue Temp: 22.1

**Left Touch, WCDMA1900 Ch. 9538, Ant Internal, Standard Battery**


**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = -0.028 dB

Peak SAR (extrapolated) = 1.20 W/kg

SAR(1 g) = 0.743 W/kg; SAR(10 g) = 0.451 W/kg





**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-20; Ambient Temp: 21.9; Tissue Temp: 22.1

**Left Tilt, WCDMA1900 Ch. 9400, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Power Drift = 0.180 dB  
 Peak SAR (extrapolated) = 0.244 W/kg  
 SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.089 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.97, 7.97, 7.97); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-20; Ambient Temp: 21.9; Tissue Temp: 22.1

**Right Tilt, WCDMA1900 Ch. 9400, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = 0.105 dB  
Peak SAR (extrapolated) = 0.277 W/kg  
SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.106 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: W-LAN; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.84 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.12, 7.12, 7.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

**Left Touch, W-LAN(802.11b) Ch. 11, Ant Internal, Standard Battery**

**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.104 dB  
 Peak SAR (extrapolated) = 1.91 W/kg  
 SAR(1 g) = 0.762 W/kg; SAR(10 g) = 0.324 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: W-LAN; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.84$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.12, 7.12, 7.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

**Right Touch, W-LAN(802.11b) Ch. 11, Ant Internal, Standard Battery**

**Area Scan (81x111x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Power Drift = 0.044 dB  
 Peak SAR (extrapolated) = 1.42 W/kg  
 SAR(1 g) = 0.644 W/kg; SAR(10 g) = 0.293 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: W-LAN; Frequency: 2412 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.79$  mho/m;  $\epsilon_r = 40.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.12, 7.12, 7.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

**Left Tilt, W-LAN(802.11b) Ch. 1, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Power Drift = -0.019 dB  
 Peak SAR (extrapolated) = 1.90 W/kg  
 SAR(1 g) = 0.779 W/kg; SAR(10 g) = 0.335 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: W-LAN; Frequency: 2437 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2437 \text{ MHz}$ ;  $\sigma = 1.82 \text{ mho/m}$ ;  $\epsilon_r = 40.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.12, 7.12, 7.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

**Left Tilt, W-LAN(802.11b) Ch. 6, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = -0.185 dB  
 Peak SAR (extrapolated) = 1.79 W/kg  
 SAR(1 g) = 0.732 W/kg; SAR(10 g) = 0.315 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: W-LAN; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.84$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.12, 7.12, 7.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

**Left Tilt, W-LAN(802.11b) Ch. 11, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Power Drift = 0.168 dB  
 Peak SAR (extrapolated) = 1.88 W/kg  
 SAR(1 g) = 0.768 W/kg; SAR(10 g) = 0.326 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: W-LAN; Frequency: 2462 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.84$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Right Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(7.12, 7.12, 7.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM 1800/1900 MHz; Type: SAM; Serial: TP-1224  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-26; Ambient Temp: 22.2; Tissue Temp: 22.6

**Right Tilt, W-LAN(802.11b) Ch. 11, Ant Internal, Standard Battery**

**Area Scan (81x111x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Power Drift = -0.051 dB  
 Peak SAR (extrapolated) = 1.47 W/kg  
 SAR(1 g) = 0.647 W/kg; SAR(10 g) = 0.291 W/kg



0 dB = 0.881mW/g

**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Bottom, GSM850 GPRS Class 10 Ch. 190, Ant Internal**


**Area Scan (61x81x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.191 dB

Peak SAR (extrapolated) = 0.135 W/kg

SAR(1 g) = 0.079 W/kg; SAR(10 g) = 0.046 W/kg



**DIGITAL EMC CO., LTD**

**DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Front, GSM850 GPRS Class 10 Ch. 190, Ant Internal**

**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.045 dB  
 Peak SAR (extrapolated) = 0.262 W/kg  
 SAR(1 g) = 0.192 W/kg; SAR(10 g) = 0.139 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 Ch. 190, Ant Internal**

**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.062 dB  
 Peak SAR (extrapolated) = 0.269 W/kg  
 SAR(1 g) = 0.207 W/kg; SAR(10 g) = 0.156 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 Ch. 190, Ant Internal**

**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.062 dB  
 Peak SAR (extrapolated) = 0.248 W/kg  
 SAR(1 g) = 0.158 W/kg; SAR(10 g) = 0.114 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 8 Ch. 190, Ant Internal**

Area Scan (81x111x1): Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Zoom Scan (5x5x7)/Cube 0: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.117 dB  
 Peak SAR (extrapolated) = 0.258 W/kg  
 SAR(1 g) = 0.200 W/kg; SAR(10 g) = 0.151 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 8 Ch. 190, Ant Internal**

**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Power Drift = 0.117 dB  
 Peak SAR (extrapolated) = 0.248 W/kg  
 SAR(1 g) = 0.163 W/kg; SAR(10 g) = 0.114 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 824.2 \text{ MHz}$ ;  $\sigma = 0.944 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 10 Ch. 128, Ant Internal**


**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = -0.010 dB

Peak SAR (extrapolated) = 0.423 W/kg

SAR(1 g) = 0.323 W/kg; SAR(10 g) = 0.244 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 824.2 \text{ MHz}$ ;  $\sigma = 0.944 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519

Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 10 Ch. 128, Ant Internal**Area Scan (81x111x1): Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ Zoom Scan (5x5x7)/Cube 1: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = -0.010 dB

Peak SAR (extrapolated) = 0.400 W/kg

SAR(1 g) = 0.265 W/kg; SAR(10 g) = 0.180 W/kg



0 dB = 0.338mW/g

**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.15  
Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.956$  mho/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section


**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 10 Ch. 190, Ant Internal**

**Area Scan (81x111x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = 0.060 dB  
Peak SAR (extrapolated) = 0.347 W/kg  
SAR(1 g) = 0.267 mW/g; SAR(10 g) = 0.201 mW/g



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 10 Ch. 190, Ant Internal**


**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.060 dB

Peak SAR (extrapolated) = 0.330 W/kg

SAR(1 g) = 0.219 W/kg; SAR(10 g) = 0.152 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 848.8 \text{ MHz}$ ;  $\sigma = 0.968 \text{ mho/m}$ ;  $\epsilon_r = 53.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 10 Ch. 251, Ant Internal**


**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.039 dB

Peak SAR (extrapolated) = 0.304 W/kg

SAR(1 g) = 0.236 W/kg; SAR(10 g) = 0.178 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 848.8 \text{ MHz}$ ;  $\sigma = 0.968 \text{ mho/m}$ ;  $\epsilon_r = 53.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 10 Ch. 251, Ant Internal**


**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.039 dB

Peak SAR (extrapolated) = 0.277 W/kg

SAR(1 g) = 0.178 mW/g; SAR(10 g) = 0.118 mW/g



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.956$  mho/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 11 Ch. 190, Ant Internal****Area Scan (81x111x1):** Measurement grid: dx=15mm, dy=15mm**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.398 W/kg

SAR(1 g) = 0.220 W/kg; SAR(10 g) = 0.164 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 11 Ch. 190, Ant Internal**


**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.269 W/kg

SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.124 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 12 Ch. 190, Ant Internal**


**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.353 W/kg

SAR(1 g) = 0.228 W/kg; SAR(10 g) = 0.171 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Rear, GSM850 GPRS Class 12 Ch. 190, Ant Internal**


**Area Scan (81x111x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.277 W/kg

SAR(1 g) = 0.184 W/kg; SAR(10 g) = 0.129 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Right, GSM850 GPRS Class 10 Ch. 190, Ant Internal**


**Area Scan (61x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = -0.121 dB

Peak SAR (extrapolated) = 0.355 W/kg

SAR(1 g) = 0.255 W/kg; SAR(10 g) = 0.179 W/kg



**DIGITAL EMC CO., LTD****DUT: LG-E612g; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.15  
 Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.956 \text{ mho/m}$ ;  $\epsilon_r = 53.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section

**DASY4 Configuration:**

Probe: EX3DV4 - SN3643; ConvF(9.12, 9.12, 9.12); Calibrated: 2012-01-27; Electronics: DAE3 Sn519  
 Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223  
 Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Test Date: 2012-04-23; Ambient Temp: 21.8; Tissue Temp: 22.0

**1 cm space from Body, Left, GSM850 GPRS Class 10 Ch. 190, Ant Internal**

**Area Scan (61x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Power Drift = 0.022 dB

Peak SAR (extrapolated) = 0.342 W/kg

SAR(1 g) = 0.184 W/kg; SAR(10 g) = 0.125 W/kg

