

## MEASUREMENT REPORT FCC Part 90

**Applicant Name:**  
 LG Electronics USA, Inc.  
 111 Sylvan Avenue, North Building  
 Englewood Cliffs, NJ 07632  
 United States


**Date of Testing:**  
 6/28 - 8/20/2020  
**Test Site/Location:**  
 PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
 1M2006150095-04.ZNF

<b>FCC ID:</b>	<b>ZNFF100TM</b>
<b>APPLICANT:</b>	<b>LG Electronics USA, Inc.</b>

**Application Type:** Certifications  
**Model:** LM-F100TM  
**Additional Model(s):** LMF100TM, F100TM  
**EUT Type:** Portable Handset  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part:** §2.1049, §22(H), §90(S)  
**Test Procedure(s):** ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
 Randy Ortanez  
 President




<b>FCC ID:</b> ZNFF100TM	 Proud to be part of element	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M2006150095-04.ZNF	<b>Test Dates:</b> 6/28 - 8/20/2020	<b>EUT Type:</b> Portable Handset		Page 1 of 48

## TABLE OF CONTENTS


1.0	INTRODUCTION .....	4
1.1	Scope .....	4
1.2	PCTEST Test Location .....	4
1.3	Test Facility / Accreditations .....	4
2.0	PRODUCT INFORMATION .....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities .....	5
2.3	Test Configuration .....	5
2.4	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Radiated Power and Radiated Spurious Emissions .....	6
4.0	MEASUREMENT UNCERTAINTY .....	8
5.0	TEST EQUIPMENT CALIBRATION DATA .....	9
6.0	SAMPLE CALCULATIONS .....	10
7.0	TEST RESULTS .....	11
7.1	Summary .....	11
7.2	Occupied Bandwidth .....	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal .....	23
7.4	Band Edge Emissions at Antenna Terminal .....	29
7.5	Conducted Power Output Data .....	35
7.6	Radiated Power (ERP) .....	36
7.7	Radiated Spurious Emissions Measurements .....	38
7.8	Frequency Stability / Temperature Variation .....	43
8.0	CONCLUSION .....	48

<b>FCC ID:</b> ZNFF100TM	 Proud to be part of  element	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M2006150095-04.ZNF	<b>Test Dates:</b> 6/28 - 8/20/2020	<b>EUT Type:</b> Portable Handset		Page 2 of 48



## MEASUREMENT REPORT

### FCC Part 22(H) & 90



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	Measurement	Max. Power [W]	Max. Power [dBm]	Emission Designator	
LTE Band 26	15 MHz	QPSK	821.5	ERP	0.028	14.41	13M4G7D	
		16QAM	821.5	ERP	0.022	13.46	13M4W7D	
		64QAM	821.5	ERP	0.017	12.43	13M4W7D	
	15 MHz	QPSK	821.5	Conducted	0.327	25.14	13M4G7D	
		16QAM	821.5	Conducted	0.279	24.45	13M4W7D	
		64QAM	821.5	Conducted	0.210	23.22	13M4W7D	
	10 MHz	QPSK	819.0	Conducted	0.328	25.16	8M97G7D	
		16QAM	819.0	Conducted	0.262	24.18	8M96W7D	
		64QAM	819.0	Conducted	0.214	23.30	8M96W7D	
	5 MHz	QPSK	816.5 - 821.5	Conducted	0.342	25.34	4M51G7D	
		16QAM	816.5 - 821.5	Conducted	0.274	24.37	4M50W7D	
		64QAM	816.5 - 821.5	Conducted	0.222	23.46	4M51W7D	
	3 MHz	QPSK	815.5 - 822.5	Conducted	0.338	25.29	2M69G7D	
		16QAM	815.5 - 822.5	Conducted	0.276	24.41	2M70W7D	
		64QAM	815.5 - 822.5	Conducted	0.215	23.33	2M69W7D	
	1.4 MHz	QPSK	814.7 - 823.3	Conducted	0.326	25.13	1M08G7D	
		16QAM	814.7 - 823.3	Conducted	0.274	24.38	1M08W7D	
		64QAM	814.7 - 823.3	Conducted	0.215	23.33	1M08W7D	
	CDMA BC10	N/A	CDMA	817.9 - 823.1	Conducted	0.331	25.20	1M27F9W

#### EUT Overview

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 3 of 48	

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

**Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.**

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 4 of 48

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFF100TM**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 90(R), 22(H) and 90(S).

**Test Device Serial No.:** 00151, 00227, 00219, 00277

### 2.2 Device Capabilities

This device contains the following capabilities:

800/850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-Band 5G NR, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

The EUT is capable of operating in screen closed and screen open configurations. The worst-case configuration for radiated emissions was determined from open and closed configurations in X, Y, and Z orientations for horizontal and vertical antenna polarizations. The worst case radiated emissions data is shown in this report. Additionally, the EUT is support a camera that mechanically pops up from the device. The worst case configuration was investigated with the camera down and popped up and worst case radiated data is reported herein.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFF100TM	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 5 of 48	

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

### 3.2 Radiated Power and Radiated Spurious Emissions §2.1053, §90.635, §90(S)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

The calculated  $P_d$  levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of  $43 + 10 \log_{10}(\text{Power [Watts]})$  specified in 90(S).

The RSE measurements are also performed using a field strength measurement method using the following formula:

$$\begin{aligned} \text{Field Strength [dBuV/m]} &= \text{RSE raw level [dBm]} + \text{AFCL [dB/m]} + 10 \\ \text{EIRP Spurious Level [dBm]} &= \text{Field Strength} + 20 \log(D) - 104.8 \end{aligned}$$

Where D: Test distance, AFCL: Antenna Factor + Cable Loss

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 6 of 48	

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

FCC ID: ZNFF100TM	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 7 of 48

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFF100TM	 <b>PCTEST</b> <sup>®</sup> Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 8 of 48

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx4	Licensed Transmitter Cable Set	7/9/2020	Annual	7/9/2021	LTx4
Agilent	N9020A	MXA Signal Analyzer	4/20/2020	Annual	4/20/2021	US46470561
Agilent	N9030A	PXA Signal Analyzer (44GHz)	6/12/2020	Annual	6/12/2021	MY52350166
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2019	Biennial	10/10/2021	121034
Espec	ESX-2CA	Environmental Chamber	8/13/2019	Annual	8/13/2020	17620
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/12/2020	Biennial	3/12/2022	128337
Rohde & Schwarz	CMW500	Radio Communication Tester	8/26/2019	Annual	8/26/2020	100976
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	7/15/2020	Annual	7/15/2021	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/23/2019	Annual	9/23/2020	100348
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/10/2020	Annual	2/10/2021	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/21/2020	Annual	2/21/2021	102133
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107
Sunol	DRH-118	Horn Antenna (1-18 GHz)	8/27/2019	Biennial	8/27/2021	A042511

**Table 5-1. Test Equipment**

**Notes:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 9 of 48	

## 6.0 SAMPLE CALCULATIONS

### Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### Spurious Radiated Emission – BC10

**Example: Channel 476 CDMA BC10 Mode 3<sup>rd</sup> Harmonic (2453.70MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 2453.70 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc.

### Emission Designator

#### QPSK Modulation

**Emission Designator = 8M62G7D**

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

#### 16QAM Modulation

**Emission Designator = 8M45W7D**

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

### Spurious Radiated Emission – LTE Band

**Example: Middle Channel LTE Mode 2<sup>nd</sup> Harmonic (1564 MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 10 of 48	

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: LG Electronics USA, Inc.  
 FCC ID: ZNFF100TM  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): CDMA / EvDO / LTE  
 Band: Band Class 10 / Band 26

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 90(S).691(a)	Conducted Band Edge / Spurious Emissions	On all frequencies between 769-775 MHz and 799-805 MHz, attenuation by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.  On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, attenuation by at least $43 + 10 \log(P)$ dB.(Band 14)  > $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge (Band 26)		PASS	Sections 7.3, 7.4
2.1055 90.213	Frequency Stability	< 2.5 ppm		PASS	Section 7.8
2.1046 90.635	Conducted Power	< 100 Watts		PASS	Section 7.5
22.913(a.2)	Effective Radiated Power (Band 26)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
2.1053 90(S).691(a)	Radiated Spurious Emissions	> $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge		PASS	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 11 of 48	

- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 4.5.
- 5) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 5.3.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 12 of 48

## 7.2 Occupied Bandwidth

### §2.1049

#### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

#### Test Notes


None.

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 13 of 48

**CDMA BC10**




**Plot 7-1. Occupied Bandwidth Plot (CDMA/EvDO, Ch. 476)**




**Plot 7-2. Occupied Bandwidth Plot (CDMA/EvDO, Ch. 684)**

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	<b>LG</b>	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 14 of 48

## LTE Band 26



Plot 7-3. Occupied Bandwidth Plot (LTE Band 26 - 15MHz QPSK - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26 - 15MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 15 of 48




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26 - 15MHz 64-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 26 - 10MHz QPSK - Full RB Configuration)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 16 of 48




Plot 7-7. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 16-QAM - Full RB Configuration)



Plot 7-8. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 17 of 48




Plot 7-9. Occupied Bandwidth Plot (LTE Band 26 - 5MHz QPSK - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 18 of 48




Plot 7-11. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 64-QAM - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (LTE Band 26 - 3MHz QPSK - Full RB Configuration)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 19 of 48




Plot 7-13. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 16-QAM - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 20 of 48




Plot 7-15. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-16. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 21 of 48



Plot 7-17. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 22 of 48

### 7.3 Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §90(S).691(a)

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

**The minimum permissible attenuation level of any spurious emission is  $43 + 10 \log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.**

#### Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW  $\geq$  100kHz
3. VBW  $\geq$  3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

#### Test Notes


Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 23 of 48

**CDMA BC10**




**Plot 7-18. Conducted Spurious Plot (CDMA/EvDO, Ch. 476)**




**Plot 7-19. Conducted Spurious Plot (CDMA/EvDO, Ch. 476)**

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 24 of 48




Plot 7-20. Conducted Spurious Plot (CDMA/EvDO, Ch. 476)




Plot 7-21. Conducted Spurious Plot (CDMA/EvDO, Ch. 684)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 25 of 48




Plot 7-22. Conducted Spurious Plot (CDMA/EvDO, Ch. 684)




Plot 7-23. Conducted Spurious Plot (CDMA/EvDO, Ch. 684)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 26 of 48

**LTE Band 26**




**Plot 7-24. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)**



**Plot 7-25. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)**

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 27 of 48



Plot 7-26. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)

FCC ID: ZNFF100TM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 28 of 48

## 7.4 Band Edge Emissions at Antenna Terminal

### §2.1051 §90(S).691(a)

#### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

**For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by greater than 37.5 kHz is  $43 + 10\log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by up to and including 37.5 kHz is  $50 + 10\log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.**

#### Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

#### Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

#### Test Notes

For channel edge emission, the signal analyzer's "ACP" measurement capability is used.


Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFF100TM	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 29 of 48

**CDMA BC10**




**Plot 7-27. Channel Edge Plot (CDMA BC10 - Ch. 476)**




**Plot 7-28. Channel Edge Plot (CDMA BC10 - Ch. 684)**

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 30 of 48

## LTE Band 26




Plot 7-29. Channel Edge Plot (LTE Band 26 - 15MHz QPSK)




Plot 7-30. Channel Edge Plot (LTE Band 26 - 10MHz QPSK - High Channel)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 31 of 48




Plot 7-31. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - Low Channel)




Plot 7-32. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - High Channel)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 32 of 48




Plot 7-33. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - Low Channel)




Plot 7-34. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - High Channel)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 33 of 48



Plot 7-35. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - Low Channel)



Plot 7-36. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - High Channel)

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 34 of 48

## 7.5 Conducted Power Output Data

§2.1046 §90.635

Frequency [MHz]	Channel	Battery Type	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
817.90	476	Standard	25.20	0.331	50.00	-24.80
823.10	684	Standard	25.11	0.324	50.00	-24.89

Table 7-2. CDMA BC10 Conducted Power Output Data

Bandwidth	Modulation	Channel	Frequency [MHz]	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
15 MHz	QPSK	26765	821.5	25.14	0.327	50.00	-24.86
	16-QAM	26765	821.5	24.45	0.279	50.00	-25.55
	64-QAM	26765	821.5	23.22	0.210	50.00	-26.78
10 MHz	QPSK	26740	819.0	25.16	0.328	50.00	-24.84
	16-QAM	26740	819.0	24.18	0.262	50.00	-25.82
	64-QAM	26740	819.0	23.30	0.214	50.00	-26.70
5 MHz	QPSK	26715	816.5	25.34	0.342	50.00	-24.66
		26765	821.5	25.17	0.329	50.00	-24.83
	16-QAM	26715	816.5	24.23	0.265	50.00	-25.77
		26765	821.5	24.37	0.274	50.00	-25.63
	64-QAM	26715	816.5	23.25	0.211	50.00	-26.75
		26765	821.5	23.46	0.222	50.00	-26.54
3 MHz	QPSK	26705	815.5	25.29	0.338	50.00	-24.71
		26775	822.5	25.18	0.330	50.00	-24.82
	16-QAM	26705	815.5	24.28	0.268	50.00	-25.72
		26775	822.5	24.41	0.276	50.00	-25.59
	64-QAM	26705	815.5	23.08	0.203	50.00	-26.92
		26775	822.5	23.33	0.215	50.00	-26.67
1.4 MHz	QPSK	26697	814.7	25.13	0.326	50.00	-24.87
		26783	823.3	25.07	0.321	50.00	-24.93
	16-QAM	26697	814.7	24.37	0.274	50.00	-25.63
		26783	823.3	24.38	0.274	50.00	-25.62
	64-QAM	26697	814.7	22.74	0.188	50.00	-27.26
		26783	823.3	23.33	0.215	50.00	-26.67

Table 7-3. LTE Band 26 Conducted Power Output Data

### NOTES:

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. This unit was tested with its standard battery.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 35 of 48	

## 7.6 Radiated Power (ERP)

### §22.913(a.2)

#### Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

#### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

#### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 36 of 48	

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Radiated Test Setup <1GHz

## Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
821.50	15	QPSK	H	139	123	1 / 74	9.86	6.70	<b>14.41</b>	0.028	38.45	-24.04
821.50	15	16-QAM	H	139	123	1 / 74	8.91	6.70	<b>13.46</b>	0.022	38.45	-24.99
821.50	15	64-QAM	H	139	123	1 / 74	7.88	6.70	<b>12.43</b>	0.017	38.45	-26.02
821.50	15	QPSK (Camera)	H	370	323	1 / 74	9.39	6.70	13.94	<b>0.025</b>	38.45	-24.51
821.50	15	QPSK (WCP)	H	370	323	1 / 74	6.33	6.70	10.88	0.012	38.45	-27.57

Table 7-37. ERP Data (Band 26)

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 37 of 48

## 7.7 Radiated Spurious Emissions Measurements

### §2.1053 §90(S).691(a)

#### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

#### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12


#### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq 2 \times$  span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize


FCC ID: ZNFF100TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 38 of 48

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Test Instrument & Measurement Setup < 1GHz**



**Figure 7-6. Test Instrument & Measurement Setup >1 GHz**

**Test Notes**


1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. This unit was tested with its standard battery.

FCC ID: ZNFF100TM	<b>PCTEST</b> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 39 of 48

4. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
5. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 40 of 48

## CDMA BC10



Plot 7-38. Radiated Spurious Plot (CDMA BC10)

Frequency (MHz):	817.9
Modulation:	CDMA BC10

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1635.8	H	-	-	-67.35	2.91	42.56	-52.70	-13.00	-39.70
2453.7	H	-	-	-62.23	6.72	51.49	-43.76	-13.00	-30.76

Table 7-4. CDMA BC10 Radiated Spurious Data (Ch. 476)


Frequency (MHz):	823.1
Modulation:	CDMA BC10

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1646.2	H	-	-	-67.00	2.92	42.92	-52.34	-13.00	-39.34
2469.3	H	-	-	-62.86	6.90	51.04	-44.21	-13.00	-31.21

Table 7-5. CDMA BC10 Radiated Spurious Data (Ch. 684)

FCC ID: ZNFF100TM	 <b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 41 of 48

## LTE Band 26



Plot 7-39. Radiated Spurious Plot (Band 26)

Bandwidth (MHz):	15
Frequency (MHz):	821.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	H	400	206	-76.29	-6.80	23.91	-71.35	-13.00	-58.35
2464.5	H	394	21	-71.73	-2.93	32.34	-62.92	-13.00	-49.92
3286.0	H	-	-	-77.85	0.29	29.44	-65.82	-13.00	-52.82
4107.5	H	-	-	-76.65	2.34	32.69	-62.57	-13.00	-49.57

Table 7-6. Radiated Spurious Data (LTE Band 26)

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 42 of 48	

## 7.8 Frequency Stability / Temperature Variation

### §2.1055 §90.213

#### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.***

#### Test Procedure Used

ANSI/TIA-603-E-2016

#### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

#### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

#### Test Notes

None

FCC ID: ZNFF100TM	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 LG	Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset	Page 43 of 48	

**Frequency Stability / Temperature Variation**  
**§2.1055, §90.213**


Operating Frequency (Hz):	817,900,000
Ref. Voltage (VDC):	3.80
Deviation Limit:	± 0.00025% or 2.5 ppm

Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 30	817,900,047	47	0.0000057
		- 20	817,900,099	99	0.0000121
		- 10	817,900,024	24	0.0000029
		0	817,899,956	-44	-0.0000054
		+ 10	817,899,926	-74	-0.0000090
		+ 20 (Ref)	817,899,919	-81	-0.0000099
		+ 30	817,899,876	-124	-0.0000152
		+ 40	817,900,053	53	0.0000065
		+ 50	817,900,021	21	0.0000026
Battery Endpoint	3.40	+ 20	817,899,948	-52	-0.0000064

**Table 7-7. CDMA BC10 Frequency Stability Data**

FCC ID: ZNFF100TM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M2006150095-04.ZNF	<b>Test Dates:</b> 6/28 - 8/20/2020	<b>EUT Type:</b> Portable Handset	Page 44 of 48	

**Frequency Stability / Temperature Variation**  
**\$2.1055, \$90.213**



**Figure 7-7. CDMA BC10 Frequency Stability Chart**

FCC ID: ZNFF100TM	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 45 of 48

**Frequency Stability / Temperature Variation**  
**§2.1055, §90.213**


Operating Frequency (Hz):	819,000,000
Ref. Voltage (VDC):	3.80
Deviation Limit:	± 0.00025% or 2.5 ppm

Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 30	818,999,933	-67	-0.0000082
		- 20	818,999,978	-22	-0.0000027
		- 10	818,999,861	-139	-0.0000170
		0	819,000,046	46	0.0000056
		+ 10	818,999,933	-67	-0.0000082
		+ 20 (Ref)	819,000,041	41	0.0000050
		+ 30	819,000,136	136	0.0000166
		+ 40	818,999,911	-89	-0.0000109
		+ 50	818,999,864	-136	-0.0000166
Battery Endpoint	3.40	+ 20	819,000,086	86	0.0000105

**Table 7-8. LTE Band 26 Frequency Stability Data**

FCC ID: ZNFF100TM	 <b>PCTEST</b> Proud to be part of  element	<b>MEASUREMENT REPORT (CERTIFICATION)</b>	 <b>LG</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M2006150095-04.ZNF	<b>Test Dates:</b> 6/28 - 8/20/2020	<b>EUT Type:</b> Portable Handset	Page 46 of 48	

**Frequency Stability / Temperature Variation**  
**\$2.1055, \$90.213**



**Table 7-9. LTE Band 26 Frequency Stability Chart**

FCC ID: ZNFF100TM	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2006150095-04.ZNF	Test Dates: 6/28 - 8/20/2020	EUT Type: Portable Handset		Page 47 of 48

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFF100TM** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: ZNFF100TM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M2006150095-04.ZNF	<b>Test Dates:</b> 6/28 - 8/20/2020	<b>EUT Type:</b> Portable Handset		Page 48 of 48