

MEASUREMENT REPORT

FCC PART 15.247 WLAN

Applicant Name:

LG Electronics USA, Inc.
111 Sylvan Avenue, North Building
Englewood Cliffs, NJ 07632
United States

Date of Testing:

09/08/2020 - 10/05/2020

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M2007230115-07.ZNF

FCC ID:

ZNFF100TM

APPLICANT:

LG Electronics USA, Inc.

Application Type:

Class II Permissive Change

Model:

LM-F100TM

Additional Model(s):

LMF100TM, F100TM

EUT Type:

Portable Handset

Frequency Range:

2412 – 2462MHz

Modulation Type:

CCK/DSSS/OFDM

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

Test Procedure(s):


ANSI C63.10-2013, KDB 558074 D01 v05r02, KDB 648474 D03 v01r04
KDB 662911 D01 v02r01

Class II Permissive Change:

Please see FCC change document

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 1 of 23

T A B L E O F C O N T E N T S

1.0	INTRODUCTION.....	3
1.1	Scope	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION	4
2.1	Equipment Description	4
2.2	Device Capabilities	4
2.3	Test Configuration	5
2.4	Software and Firmware	5
2.5	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Emissions.....	6
3.3	Environmental Conditions.....	6
4.0	ANTENNA REQUIREMENTS	7
5.0	MEASUREMENT UNCERTAINTY.....	8
6.0	TEST EQUIPMENT CALIBRATION DATA.....	9
7.0	TEST RESULTS.....	10
7.1	Summary	10
7.2	Radiated Spurious Emission Measurements – Above 1 GHz.....	11
7.2.1	SISO Antenna-1 Radiated Spurious Emission Measurements	14
7.2.2	SISO Antenna-1 Radiated Restricted Band Edge Measurements	20
7.2.3	SISO Antenna-2 Radiated Restricted Band Edge Measurements	21
7.2.4	MIMO Radiated Restricted Band Edge Measurements	22
8.0	CONCLUSION	23

FCC ID: ZNFF100TM	 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 2 of 23

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISSED.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 3 of 23

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFF100TM**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

Test Device Serial No.: 03791, 03783

2.2 Device Capabilities

This device contains the following capabilities:

800/850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-Band 5G NR, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Table 2-1. Frequency/ Channel Operations

Note: The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of ANSI C63.10-2013 and KDB 558074 D01 v05r02. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycles				
802.11 Mode/Band		Duty Cycle [%]		
		ANT1	ANT2	MIMO
2.4GHz	b	99.2	99.2	99.3
	g	98.1	98.1	98.1
	n	98.0	98.0	97.9
	ac	98.3	98.5	98.4

Table 2-2. Measured Duty Cycles

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07-ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 4 of 23	

The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		SDM		CDD	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
2.4GHz	11b	✓	✓	✗	✗	✓	✓
	11g	✓	✓	✗	✗	✓	✓
	11n	✓	✓	✓	✓	✓	✓
	11ac	✓	✓	✓	✓	✓	✓

Table 2-3. Frequency / Channel Operations

✓ = Support ; ✗ = NOT Support

SISO = Single Input Single Output

SDM = Spatial Diversity Multiplexing – MIMO function

CDD = Cyclic Delay Diversity - 2Tx Function

Data Rates Supported: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)
6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (g)
6.5/7.2Mbps, 13/14.4Mbps, 19.5/21.7Mbps, 26/28.9Mbps, 39/43.3Mbps,
52/57.8Mbps, 58.5/65Mbps, 65/72.2Mbps (n)
13/14.4Mbps, 26/28.9Mbps, 39/43.3Mbps, 52/57.8Mbps, 78/86.7Mbps,
104/115.6Mbps, 117/130Mbps, 130/144.4Mbps (MIMO n)

2.3 Test Configuration

The EUT was tested per the guidance of KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing. See 3.2 for radiated emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

The EUT is capable of operating in screen closed and screen open configurations. The worst-case configuration for radiated emissions was determined from open and closed configurations in X, Y, and Z orientations for horizontal and vertical antenna polarizations. The worst case radiated emissions data is shown in this report. Additionally, the EUT is support a camera that mechanically pops up from the device. The worst case configuration was investigated with the camera down and popped up and worst case radiated data is reported herein.

2.4 Software and Firmware

The test was conducted with firmware version 10 installed on the EUT.

2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 5 of 23	

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 6 of 23	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connections to an external antenna.

Conclusion:

The EUT unit complies with the requirement of §15.203.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 7 of 23

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFF100TM	 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 8 of 23

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	10/30/2019	Annual	10/30/2020	WL25-1
-	WL40-1	Conducted Cable Set (40GHz)	10/30/2019	Annual	10/30/2020	WL40-1
Agilent	N9038A	MXE EMI Receiver	8/11/2020	Annual	8/11/2021	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	8/17/2020	Annual	8/17/2021	MY52350166
Anritsu	ML2496A	Power Meter	11/6/2019	Annual	11/6/2020	1405003
Anritsu	MA2411B	Pulse Power Sensor	10/15/2019	Annual	10/15/2020	1339026
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2019	Biennial	10/10/2021	121034
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
Emco	3116	Horn Antenna (18 - 40GHz)	6/7/2018	Triennial	6/7/2021	9203-2178
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	7/15/2020	Annual	7/15/2021	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/23/2019	Annual	9/23/2020	100348
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/10/2020	Annual	2/10/2021	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/21/2020	Annual	2/21/2021	102133
Solar Electronics	8012-50-R-24-BNC	Line Impedance Stabilization Network	10/1/2019	Biennial	10/1/2021	310233
Sunol Science	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 9 of 23	

7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.

FCC ID: ZNFF100TM

FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.2

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 10 of 23

7.2 Radiated Spurious Emission Measurements – Above 1 GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-2 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-2. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3

KDB 558074 D01 v05r02 – Sections 8.6, 8.7

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 11 of 23	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-2.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. Radiated spurious emissions were investigated while operating in MIMO mode, however, it was determined that single antenna operation produced the worst case emissions. Since the emissions

FCC ID: ZNFF100TM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	LG	Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 12 of 23

produced from MIMO operation were found to be more than 20dB below the limit, the MIMO emissions are not reported.

8. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Sample Calculations

Determining Spurious Emissions Levels

- o Field Strength Level $[\text{dB}\mu\text{V/m}] = \text{Analyzer Level} [\text{dBm}] + 107 + \text{AFCL} [\text{dB/m}]$
- o $\text{AFCL} [\text{dB/m}] = \text{Antenna Factor} [\text{dB/m}] + \text{Cable Loss} [\text{dB}]$
- o $\text{Margin} [\text{dB}] = \text{Field Strength Level} [\text{dB}\mu\text{V/m}] - \text{Limit} [\text{dB}\mu\text{V/m}]$

Radiated Band Edge Measurement Offset

- o The amplitude offset shown in the radiated restricted band edge plots in Section 7.2 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset	Page 13 of 23	

7.2.1 SISO Antenna-1 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	V	104	126	-78.05	6.73	35.68	53.98	-18.30
4874.00	Peak	V	104	126	-66.40	6.73	47.33	73.98	-26.65
7311.00	Avg	V	-	-	-80.45	13.46	40.01	53.98	-13.97
7311.00	Peak	V	-	-	-67.78	13.46	52.68	73.98	-21.30
12185.00	Avg	V	-	-	-81.51	17.64	43.13	53.98	-10.85
12185.00	Peak	V	-	-	-69.03	17.64	55.61	73.98	-18.37

Table 7-3. Radiated Measurements SISO ANT1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	V	-	-	-78.42	6.73	35.31	53.98	-18.67
4874.00	Peak	V	-	-	-66.04	6.73	47.69	73.98	-26.29
7311.00	Avg	V	-	-	-80.14	13.46	40.32	53.98	-13.66
7311.00	Peak	V	-	-	-67.68	13.46	52.78	73.98	-21.20
12185.00	Avg	V	-	-	-81.27	17.64	43.37	53.98	-10.61
12185.00	Peak	V	-	-	-68.80	17.64	55.84	73.98	-18.14

Table 7-4. Radiated Measurements SISO ANT1 Swivel Open

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 14 of 23

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	V	100	-1	-76.36	6.73	37.37	53.98	-16.61
4874.00	Peak	V	100	-1	-65.30	6.73	48.43	73.98	-25.55
7311.00	Avg	V	-	-	-80.09	13.46	40.37	53.98	-13.61
7311.00	Peak	V	-	-	-67.10	13.46	53.36	73.98	-20.62
12185.00	Avg	V	-	-	-81.26	17.64	43.38	53.98	-10.60
12185.00	Peak	V	-	-	-68.79	17.64	55.85	73.98	-18.13

Table 7-5. Radiated Measurements SISO ANT1 Camera Pop-Out

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	V	-	-	-78.48	6.73	35.25	53.98	-18.73
4874.00	Peak	V	-	-	-66.36	6.73	47.37	73.98	-26.61
7311.00	Avg	V	-	-	-80.06	13.46	40.40	53.98	-13.58
7311.00	Peak	V	-	-	-67.65	13.46	52.81	73.98	-21.17
12185.00	Avg	V	-	-	-81.26	17.64	43.38	53.98	-10.60
12185.00	Peak	V	-	-	-69.03	17.64	55.61	73.98	-18.37

Table 7-6. Radiated Measurements SISO ANT1 Swivel Open + Camera Pop-Out

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	V	-	-	-78.41	6.73	35.32	53.98	-18.66
4874.00	Peak	V	-	-	-65.89	6.73	47.84	73.98	-26.14
7311.00	Avg	V	-	-	-80.12	13.46	40.34	53.98	-13.64
7311.00	Peak	V	-	-	-67.69	13.46	52.77	73.98	-21.21
12185.00	Avg	V	-	-	-81.26	17.64	43.38	53.98	-10.60
12185.00	Peak	V	-	-	-68.87	17.64	55.77	73.98	-18.21

Table 7-7. Radiated Measurements SISO ANT1 with WCP

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 15 of 23

SISO Antenna-2 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11b
Worst Case Transfer Rate:	1 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2437MHz
Channel:	06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-78.62	6.73	35.11	53.98	-18.87
4874.00	Peak	H	-	-	-66.50	6.73	47.23	73.98	-26.75
7311.00	Avg	H	-	-	-80.44	13.46	40.02	53.98	-13.96
7311.00	Peak	H	-	-	-68.31	13.46	52.15	73.98	-21.83
12185.00	Avg	H	-	-	-81.49	17.64	43.15	53.98	-10.83
12185.00	Peak	H	-	-	-67.75	17.64	56.89	73.98	-17.09

Table 7-8. Radiated Measurements SISO ANT2

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	144	58	-73.92	6.73	39.81	53.98	-14.17
4874.00	Peak	H	144	58	-63.95	6.73	49.78	73.98	-24.20
7311.00	Avg	H	169	313	-76.18	13.46	44.28	53.98	-9.70
7311.00	Peak	H	169	313	-64.76	13.46	55.70	73.98	-18.28
12185.00	Avg	H	-	-	-77.15	17.64	47.49	53.98	-6.49
12185.00	Peak	H	-	-	-63.58	17.64	61.06	73.98	-12.92

Table 7-9. Radiated Measurements SISO ANT2 Swivel Open

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 16 of 23

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	191	2	-72.10	6.73	41.63	53.98	-12.35
4874.00	Peak	H	191	2	-62.64	6.73	51.09	73.98	-22.89
7311.00	Avg	H	164	260	-76.70	13.46	43.76	53.98	-10.22
7311.00	Peak	H	164	260	-65.19	13.46	55.27	73.98	-18.71
12185.00	Avg	H	-	-	-77.18	17.64	47.46	53.98	-6.52
12185.00	Peak	H	-	-	-64.82	17.64	59.82	73.98	-14.16

Table 7-10. Radiated Measurements SISO ANT2 Camera Pop-Out

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	158	342	-72.37	6.73	41.36	53.98	-12.62
4874.00	Peak	H	158	342	-63.26	6.73	50.47	73.98	-23.51
7311.00	Avg	H	165	315	-75.82	13.46	44.64	53.98	-9.34
7311.00	Peak	H	165	315	-64.92	13.46	55.54	73.98	-18.44
12185.00	Avg	H	-	-	-77.16	17.64	47.48	53.98	-6.50
12185.00	Peak	H	-	-	-64.52	17.64	60.12	73.98	-13.86

Table 7-11. Radiated Measurements SISO ANT2 Swivel Open + Camera Pop-Out

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	122	9	-75.12	6.73	38.61	53.98	-15.37
4874.00	Peak	H	122	9	-63.79	6.73	49.94	73.98	-24.04
7311.00	Avg	H	102	369	-75.74	13.46	44.72	53.98	-9.26
7311.00	Peak	H	102	369	-64.55	13.46	55.91	73.98	-18.07
12185.00	Avg	H	-	-	-77.17	17.64	47.47	53.98	-6.51
12185.00	Peak	H	-	-	-64.87	17.64	59.77	73.98	-14.21

Table 7-12. Radiated Measurements SISO ANT2 with WCP

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 17 of 23

MIMO/CDD Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11n
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-78.44	6.73	35.29	53.98	-18.69
4874.00	Peak	H	-	-	-66.02	6.73	47.71	73.98	-26.27
7311.00	Avg	H	-	-	-80.02	13.46	40.44	53.98	-13.54
7311.00	Peak	H	-	-	-67.15	13.46	53.31	73.98	-20.67
12185.00	Avg	H	-	-	-81.24	17.64	43.40	53.98	-10.58
12185.00	Peak	H	-	-	-68.58	17.64	56.06	73.98	-17.92

Table 7-13. Radiated Measurements MIMO

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-76.81	6.73	36.92	53.98	-17.06
4874.00	Peak	H	-	-	-64.24	6.73	49.49	73.98	-24.49
7311.00	Avg	H	-	-	-77.56	13.46	42.90	53.98	-11.08
7311.00	Peak	H	-	-	-65.07	13.46	55.39	73.98	-18.59
12185.00	Avg	H	-	-	-77.10	17.64	47.54	53.98	-6.44
12185.00	Peak	H	-	-	-64.78	17.64	59.86	73.98	-14.12

Table 7-14. Radiated Measurements MIMO Swivel Open

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07-ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 18 of 23

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-76.68	6.73	37.05	53.98	-16.93
4874.00	Peak	H	-	-	-64.36	6.73	49.37	73.98	-24.61
7311.00	Avg	H	-	-	-77.50	13.46	42.96	53.98	-11.02
7311.00	Peak	H	-	-	-64.79	13.46	55.67	73.98	-18.31
12185.00	Avg	H	-	-	-77.08	17.64	47.56	53.98	-6.42
12185.00	Peak	H	-	-	-64.10	17.64	60.54	73.98	-13.44

Table 7-15. Radiated Measurements MIMO Camera Pop-Out

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-76.49	6.73	37.24	53.98	-16.74
4874.00	Peak	H	-	-	-64.07	6.73	49.66	73.98	-24.32
7311.00	Avg	H	-	-	-77.55	13.46	42.91	53.98	-11.07
7311.00	Peak	H	-	-	-64.94	13.46	55.52	73.98	-18.46
12185.00	Avg	H	-	-	-77.12	17.64	47.52	53.98	-6.46
12185.00	Peak	H	-	-	-64.71	17.64	59.93	73.98	-14.05

Table 7-16. Radiated Measurements MIMO Swivel Open + Camera Pop-Out

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-76.81	6.73	36.92	53.98	-17.06
4874.00	Peak	H	-	-	-64.47	6.73	49.26	73.98	-24.72
7311.00	Avg	H	-	-	-77.21	13.46	43.25	53.98	-10.73
7311.00	Peak	H	-	-	-64.67	13.46	55.79	73.98	-18.19
12185.00	Avg	H	-	-	-77.10	17.64	47.54	53.98	-6.44
12185.00	Peak	H	-	-	-64.55	17.64	60.09	73.98	-13.89

Table 7-17. Radiated Measurements MIMO with WCP


FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 19 of 23

7.2.2 SISO Antenna-1 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1




Plot 7-1. Radiated Restricted Lower Band Edge Measurement SISO ANT1 (Average)




Plot 7-2. Radiated Restricted Lower Band Edge Measurement SISO ANT1 (Peak)

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11



Plot 7-3. Radiated Restricted Upper Band Edge Measurement SISO ANT1 (Average)



Plot 7-4. Radiated Restricted Upper Band Edge Measurement SISO ANT1 (Peak)


FCC ID: ZNFF100TM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	LG	Approved by: Quality Manager
Test Report S/N: 1M2007230115-07-ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 20 of 23

7.2.3 SISO Antenna-2 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1




Plot 7-5. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Average)




Plot 7-6. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Peak)

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11



Plot 7-7. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Average)



Plot 7-8. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Peak)


FCC ID: ZNFF100TM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	LG	Approved by: Quality Manager
Test Report S/N: 1M2007230115-07-ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 21 of 23

7.2.4 MIMO Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1




Plot 7-9. Radiated Restricted Lower Band Edge Measurement MIMO (Average)




Plot 7-10. Radiated Restricted Lower Band Edge Measurement MIMO (Peak)

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11



Plot 7-11. Radiated Restricted Upper Band Edge Measurement MIMO (Average)



Plot 7-12. Radiated Restricted Upper Band Edge Measurement MIMO (Peak)

FCC ID: ZNFF100TM	PCTEST Proud to be part of element	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07-ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 22 of 23

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFF100TM** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

FCC ID: ZNFF100TM		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M2007230115-07.ZNF	Test Dates: 09/08/2020 - 10/05/2020	EUT Type: Portable Handset		Page 23 of 23