

On your side

HCT

TEST REPORT

EMI Test for FCC Certification of LM-F100VM Model

APPLICANT

LG Electronics USA, Inc.

REPORT NO.

HCT-EM-2008-FC010-R1

DATE OF ISSUE

September 07, 2020

Tested by
Ki-Min Lee

(signature)


Technical Manager
Jeong-Hyun Choi

(signature)


HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 645 6300 Fax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

EMI Test for
FCC Certification

REPORT NO.

HCT-EM-2008-FC010-R1

DATE OF ISSUE

September 07, 2020

FCC ID.

ZNFF100VM

Applicant

LG Electronics USA, Inc.

111 Sylvan Avenue, North Building , Englewood Cliffs NJ 07632 United States

Product Name

Multi-band CDMA/GSM/EDGE/WCDMA/LTE/5G NR Phone with WLAN, BT and RFID

Model Name

LM-F100VM

Series Model Name

Refer to the clause 1.1 Description of EUT

Date of Test

July 29, 2020 to August 18, 2020

Test Standard Used

FCC CFR 47 PART 15 Subpart B Class B
ANSI C63.4-2014

Test Results

Refer to the present document

Manufacturer

LG Electronics Inc.

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	August 19, 2020	Initial Release
1	September 07, 2020	Revised the frequency range

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)
I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.
HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

The above Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme) / A2LA(American Association for Laboratory Accreditation), which signed the ILAC-MRA.

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

CONTENTS

1. GENERAL INFORMATION	5
1.1 Description of EUT	5
1.2 Tested System Details	5
1.3 Cable Description	8
1.4 Noise Suppression Parts on Cable. (I/O Cable)	8
1.5 Test Facility	9
1.6 Calibration of Measuring Instrument	9
1.7 Measurement Uncertainty	10
2. DESCRIPTION OF TEST	11
2.1 Measurement of Conducted Emission	11
2.2 Measurement of Radiated Emission	12
2.3 Configuration of Tested System	13
3. PRELIMINARY TEST	14
3.1 Conducted Emission	14
3.2 Radiated Emission	14
4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY	15
4.1 Conducted Emission	15
4.2 Radiated Emission Below 1 GHz	22
4.3 Radiated Emission Above 1 GHz	24
5. CONCLUSION	27
6. APPENDIX A. TEST SETUP PHOTO	28

1. GENERAL INFORMATION

1.1 Description of EUT

FCC ID	ZNFF100VM
Model Name	LM-F100VM
Series Model Name	LMF100VM, F100VM, LM-F101V, LMF101V, F101V
Product Name	Multi-band CDMA/GSM/EDGE/WCDMA/LTE/5G NR Phone with WLAN, BT and RFID
TX Frequency	<p>824.70 MHz to 848.31 MHz (CDMA BC0)</p> <p>1 851.25 MHz to 1 908.75 MHz (CDMA BC1)</p> <p>824.20 MHz to 848.80 MHz (GSM 850)</p> <p>1 850.20 MHz to 1 909.80 MHz (GSM 1 900)</p> <p>1 852.4 MHz to 1 907.6 MHz (WCDMA B2)</p> <p>1712.4 MHz to 1752.6 MHz (WCDMA B4)</p> <p>826.40 MHz to 846.60 MHz (WCDMA B5)</p> <p>1 850 MHz to 1 910 MHz (LTE B2)</p> <p>1 710 MHz to 1 755 MHz (LTE B4)</p> <p>824 MHz to 849 MHz (LTE B5)</p> <p>699 MHz to 716 MHz (LTE B12)</p> <p>777 MHz to 787 MHz (LTE B13)</p> <p>788 MHz to 798 MHz (LTE B14)</p> <p>2 305 MHz to 2 315 MHz (LTE B30)</p> <p>2 496 MHz to 2 690 MHz (LTE B41)</p> <p>3 550 MHz to 3 700 MHz (LTE B48)</p> <p>1 710 MHz to 1 780 MHz (LTE B66)</p> <p>2 402 MHz to 2 480 MHz (Bluetooth)</p> <p>2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)</p> <p>5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1)</p> <p>5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A)</p> <p>5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C)</p> <p>5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3)</p> <p>13.56 MHz (NFC)</p> <p>1 850 MHz to 1 910 MHz (5G NR n2)</p> <p>824 MHz to 849 MHz (5G NR n5)</p> <p>1 710 MHz to 1 780 MHz (5G NR n66)</p> <p>37 000 MHz to 40 000 MHz (5G NR n260)</p> <p>27 500 MHz to 28 350 MHz (5G NR n261)</p>

RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 862.00 MHz to 894.00 MHz (CDMA BC10) 869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.40 MHz to 891.60 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 729 MHz to 746 MHz (LTE B12) 746 MHz to 756 MHz (LTE B13) 758 MHz to 768 MHz (LTE B14) 717 MHz to 728 MHz (LTE B29) 2 350 MHz to 2 360 MHz (LTE B30) 2 496 MHz to 2 690 MHz (LTE B41) 5 150 MHz to 5 925 MHz (LTE B46) 3 550 MHz to 3 700 MHz (LTE B48) 2 110 MHz to 2 200 MHz (LTE B66) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3) 13.56 MHz (NFC) 1 930 MHz to 1 990 MHz (5G NR n2) 869 MHz to 894 MHz (5G NR n5) 2 110 MHz to 2 200 MHz (5G NR n66) 37 000 MHz to 40 000 MHz (5G NR n260) 27 500 MHz to 28 350 MHz (5G NR n261)
--------------	--

1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer
EUT	LM-F100VM	-	LG
Notebook PC	ProBook650G2	5CG6331M0P	HP
Notebook PC adaptor	Series PPP009L-E	-	LITE-ON TECHNOLOGY (CHANGZHOU)
Gateway	DIR-806M	-	D-Link
Gateway adaptor	AMS1-0501200FK	-	D-Link
Serial mouse	Serial 2 Button mouse	02031069	Radio Shack
RJ45 cable	-	-	-
DATA cable	EAD65830101	-	LUXSHARE
DATA cable	EAD65830102	-	NINGBO
Micro SD card	SAMSUNG EVO+ microSDXC CLASS10 UHS-I (256 GB)	-	SAMSUNG

1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	USB Type C (Data Cable)	Y	Y	(P,D) 1.0
	USB Type C (Earphone)	N/A	N	(D) 1.2
Notebook PC	RJ 45	N/A	N	(D) 1.6
	Serial(Mouse)	N/A	Y	(D) 1.8
	DC IN	N	N/A	(P) 1.8
Gateway	DC IN	N	N/A	(P) 1.8

NOTE. The marked "(D)" means the data cable and "(P)" means the power cable.

1.4 Noise Suppression Parts on Cable (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	USB Type C (Data Cable)	N	N/A	Y	Both End
	USB Type C (Earphone)	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial(Mouse)	N	N/A	Y	Notebook End

1.5 Test Facility

Test site is located at 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, South Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Designation No.
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	KR0032
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #1	
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #2	
Filing the EMI Measurement Facility (3 m Semi Anechoic Chamber and Shielded Room)	IC 5944A-4
Filing the EMI Measurement Facility (10 m Semi-Anechoic Chamber)	IC 5944A-2

1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5:2017

1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty
Conducted Emission (0.15 MHz to 30 MHz)	1.58 dB
Radiated Emissions (30 MHz to 1 GHz)	4.86 dB
Radiated Emissions (1 GHz to 18 GHz)	4.58 dB
Radiated Emissions (18 GHz to 40 GHz)	5.54 dB

2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

Conducted Emission Limits

Frequency (MHz)	Resolution Bandwidth (kHz)	Class A		Class B	
		Quasi-Peak (dBµV)	Average (dBµV)	Quasi-Peak (dBµV)	Average (dBµV)
0.15 to 0.5	9	79	66	66 to 56*	56 to 46*
0.5 to 5	9	73	60	56	46
5 to 30	9	73	60	60	50

NOTE. Decreases with the logarithm of the frequency.

2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
(1 GHz to 40 GHz)

Radiated Emission Limits


Frequency (MHz)	Class A			Class B		
	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}\mu\text{V}/\text{m}$)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}\mu\text{V}/\text{m}$)
30 to 88	10	90	39.0	3	100	40.0
88 to 216	10	150	43.5	3	150	43.5
216 to 960	10	210	46.4	3	200	46.0
Above 960	10	300	49.5	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Class A		Class B		
		Peak ($\text{dB}\mu\text{V}/\text{m}$)	Average ($\text{dB}\mu\text{V}/\text{m}$)	Peak ($\text{dB}\mu\text{V}/\text{m}$)	Average ($\text{dB}\mu\text{V}/\text{m}$)	
Above 1 000	3	80	60	74	54	

2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



3. PRELIMINARY TEST

3.1 Conducted Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: Data Communication mode

3.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: Data Communication mode

4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission

4.1.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
<input checked="" type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.10.2020
<input checked="" type="checkbox"/>	LISN	Rohde & Schwarz	ENV216	102245	1 year	09.11.2019
<input checked="" type="checkbox"/>	LISN	Rohde & Schwarz	ENV216	100073	1 year	04.27.2020
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-


4.1.2 Operating Condition

The test results of conducted emission at mains ports provide the following information:

Test Standard Used	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	150 kHz to 30 MHz
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operating Mode	Data Communication mode
Worst Case of Data Cable	LUXSHARE (EAD65830101)
Kind of Test Site	EMI Shielded Room
Temperature	24.4 °C
Relative Humidity	45.1 %
Test Date	July 29, 2020

4.1.3 Measuring Data

Figure 1: Conducted Emission, AC Main Port, Line (L1)



QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.150000	47.4	9.000	L1	9.7	18.6	66.0
0.160000	45.6	9.000	L1	9.7	19.9	65.5
0.164000	44.7	9.000	L1	9.7	20.6	65.3
0.184000	46.6	9.000	L1	9.7	17.7	64.3
0.192000	46.7	9.000	L1	9.7	17.3	63.9
0.200000	46.4	9.000	L1	9.7	17.2	63.6
3.438000	35.9	9.000	L1	9.8	20.1	56.0
3.496000	36.3	9.000	L1	9.8	19.7	56.0
3.524000	36.0	9.000	L1	9.8	20.0	56.0
3.646000	35.9	9.000	L1	9.8	20.1	56.0
3.656000	35.7	9.000	L1	9.8	20.3	56.0
3.780000	34.5	9.000	L1	9.8	21.5	56.0
6.710000	31.3	9.000	L1	9.9	28.7	60.0
9.152000	31.7	9.000	L1	9.9	28.3	60.0
9.290000	32.8	9.000	L1	9.9	27.2	60.0
9.322000	32.9	9.000	L1	9.9	27.1	60.0
9.382000	32.9	9.000	L1	9.9	27.1	60.0
9.394000	32.6	9.000	L1	9.9	27.4	60.0


Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.152000	27.5	9.000	L1	9.7	28.4	55.9
0.162000	27.6	9.000	L1	9.7	27.7	55.4
0.170000	26.9	9.000	L1	9.7	28.1	55.0
0.186000	35.7	9.000	L1	9.7	18.5	54.2
0.194000	35.6	9.000	L1	9.7	18.3	53.9
0.202000	33.9	9.000	L1	9.7	19.7	53.5
3.496000	27.6	9.000	L1	9.8	18.4	46.0
3.618000	26.9	9.000	L1	9.8	19.1	46.0
3.646000	26.9	9.000	L1	9.8	19.1	46.0
3.686000	26.0	9.000	L1	9.8	20.0	46.0
3.774000	26.0	9.000	L1	9.8	20.0	46.0
3.780000	25.9	9.000	L1	9.8	20.1	46.0
9.152000	22.8	9.000	L1	9.9	27.2	50.0
9.224000	24.2	9.000	L1	9.9	25.8	50.0
9.246000	23.9	9.000	L1	9.9	26.1	50.0
9.290000	24.7	9.000	L1	9.9	25.3	50.0
9.322000	24.7	9.000	L1	9.9	25.3	50.0
9.394000	24.7	9.000	L1	9.9	25.3	50.0

Figure 2: Conducted Emission, AC Main Port, Line (N)



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.150000	47.0	9.000	N	9.7	19.0	66.0
0.162000	45.1	9.000	N	9.7	20.2	65.4
0.184000	49.0	9.000	N	9.7	15.3	64.3
0.192000	48.2	9.000	N	9.7	15.7	63.9
0.198000	47.8	9.000	N	9.7	15.9	63.7
0.204000	47.1	9.000	N	9.7	16.4	63.4
3.936000	34.6	9.000	N	9.8	21.4	56.0
3.956000	35.7	9.000	N	9.8	20.3	56.0
3.960000	33.4	9.000	N	9.8	22.6	56.0
4.064000	34.9	9.000	N	9.8	21.1	56.0
4.070000	34.6	9.000	N	9.8	21.4	56.0
4.134000	34.9	9.000	N	9.8	21.1	56.0
5.136000	33.4	9.000	N	9.8	26.6	60.0
5.228000	31.6	9.000	N	9.8	28.4	60.0
5.316000	30.6	9.000	N	9.8	29.4	60.0
5.342000	31.1	9.000	N	9.8	28.9	60.0
9.492000	31.4	9.000	N	9.9	28.6	60.0
9.612000	31.3	9.000	N	9.9	28.7	60.0

CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.150000	27.3	9.000	N	9.7	28.7	56.0
0.154000	27.2	9.000	N	9.7	28.6	55.8
0.186000	35.8	9.000	N	9.7	18.4	54.2
0.192000	36.1	9.000	N	9.7	17.9	53.9
0.198000	35.2	9.000	N	9.7	18.5	53.7
0.204000	33.1	9.000	N	9.7	20.4	53.4
3.954000	26.8	9.000	N	9.8	19.2	46.0
4.018000	26.4	9.000	N	9.8	19.6	46.0
4.070000	27.2	9.000	N	9.8	18.8	46.0
4.092000	23.0	9.000	N	9.8	23.0	46.0
4.134000	25.6	9.000	N	9.8	20.4	46.0
4.344000	21.0	9.000	N	9.8	25.0	46.0
5.132000	24.8	9.000	N	9.8	25.2	50.0
5.178000	23.0	9.000	N	9.8	27.0	50.0
5.228000	23.5	9.000	N	9.8	26.5	50.0
5.268000	21.3	9.000	N	9.8	28.7	50.0
5.342000	21.8	9.000	N	9.8	28.2	50.0
5.346000	21.9	9.000	N	9.8	28.1	50.0

4.2 Radiated Emission Below 1 GHz

4.2.1 Measuring instruments

Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
<input checked="" type="checkbox"/> EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.12.2020
<input checked="" type="checkbox"/> Bi-Log antenna	Schwarzbeck	VULB 9168	255	2 year	03.26.2019
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn table	INNCO Systems	1060	-	N/A	-
<input checked="" type="checkbox"/> Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-

4.2.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	30 MHz to 1 000 MHz
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operating Mode	Data Communication mode
Worst Case of Data Cable	LUXSHARE (EAD65830101)
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.6 °C
Relative Humidity	48.4 %
Test Date	August 06, 2020

4.2.3 Measuring Data

Frequency (MHz)	Quasi Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
35.611360	25.4	100.0	V	112.0	18.7	14.6	40.0
65.322080	30.1	100.0	V	278.0	18.7	9.9	40.0
145.910680	31.3	174.8	H	317.0	19.2	12.2	43.5
182.100000	32.7	100.0	V	236.0	17.8	10.8	43.5
216.847240	32.9	116.8	H	312.0	17.3	13.1	46.0
648.103920	34.4	100.0	V	0.0	28.0	11.6	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

4.3 Radiated Emission Above 1 GHz

4.3.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
<input checked="" type="checkbox"/>	EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.12.2020
<input checked="" type="checkbox"/>	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/>	Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/>	Turn table	INNCO Systems	1060	-	N/A	-
<input checked="" type="checkbox"/>	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/>	Low noise amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.03.2020
<input checked="" type="checkbox"/>	Low noise amplifier	TESTEK	TK-PA1840H	170030-L	1 year	02.13.2020
<input type="checkbox"/>	Horn antenna	Schwarzbeck	BBHA 9120D	1641	1 year	06.24.2020
<input checked="" type="checkbox"/>	Horn antenna	Schwarzbeck	BBHA 9120D	01836	1 year	07.23.2020
<input checked="" type="checkbox"/>	Horn antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	1 year	12.03.2019
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-

4.3.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	40 000 MHz
Tested Frequency Range	1 GHz to 40 GHz
Operating Mode	Data Communication mode
Worst Case of Data Cable	LUXSHARE (EAD65830101)
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.6 / 21.8 °C
Relative Humidity	46.1 / 45.7 %
Test Date	July 31 / August 18, 2020

4.3.3 Measuring Data

Frequency (MHz)	Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1596.905000	46.6	199.6	V	227.0	-27.3	27.4	74.0
2468.220000	41.9	159.6	V	205.0	-24.2	32.1	74.0
3999.745000	43.3	233.4	V	0.0	-20.3	30.7	74.0
9651.850000	43.4	292.4	V	0.0	-9.2	30.6	74.0
14571.840000	47.1	248.5	V	0.0	-0.5	26.9	74.0
17972.695000	55.4	290.7	V	109.0	9.2	18.6	74.0

Frequency (MHz)	CAverage (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1596.905000	27.9	199.6	V	227.0	-27.3	26.1	54.0
2468.220000	22.7	159.6	V	205.0	-24.2	31.3	54.0
3999.745000	23.2	233.4	V	0.0	-20.3	30.8	54.0
9651.850000	30.5	292.4	V	0.0	-9.2	23.5	54.0
14571.840000	34.5	248.5	V	0.0	-0.5	19.5	54.0
17972.695000	42.6	290.7	V	109.0	9.2	11.4	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

5. CONCLUSION

The data collected shows that the **Product Name: Multi-band CDMA/GSM/EDGE/WCDMA/LTE/5G NR Phone with WLAN, BT and RFID / Model Name: LM-F100VM** complies with §15.107 and §15.109 of the FCC rules.

6. APPENDIX A. TEST SETUP PHOTO

Please refer to Appendix. A and test setup photo file no. as follows;

File No.	Date of Issue	Description
HCT-EM-2008-FC010-P	August 19, 2020	Initial Release

End of report