

EMI TEST REPORT

FCC CERTIFICATION / ISED

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632
United States

Date of Receipt: February 26, 2018**Date of Issue: March 16, 2018****Test Report No. HCT-EM-1803-FI001****FCC ID
IC****ZNFG710TM
2703C-G710AWM****Rule Part(s) / Standard(s):** FCC CFR 47 PART 15 Subpart B Class B

ICES-003 Issue 6 Class B / ANSI C63.4-2014

EUT Type: Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN,
Bluetooth and RFID**Model Name:** LM-G710AWM**Additional Model Name:** LMG710AWM, G710AWM, LM-G710TM, LMG710TM, G710TM**Date of Test:** March 08, 2018 – March 11, 2018

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Dong-Hwan Seo
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



REVISION HISTORY

The revision history for this document is shown in table.

Report No.	Issue Date	Description
HCT-EM-1803-FI001	March 16, 2018	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s)	4
1.3 Test Facility	5
1.4 Calibration of Measuring Instrument	5
1.5 Tested System Details	6
1.6 Cable Description	7
1.7 Noise Suppression Parts on Cable. (I/O Cable)	7
2. MEASUREMENT UNCERTAINTY	8
3. DESCRIPTION OF TEST	9
3.1 Measurement of Conducted Emission.....	9
3.2 Measurement of Radiated Measurements	10
4. PRELIMINARY TEST	12
4.1 Conducted Emission Test	12
4.2 Radiated Emission Test	12
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	13
5.1 Conducted Emission Test	13
5.2 Radiated Emission Test	20
6. LIST OF TEST EQUIPMENT.....	22
7. CONCLUSION.....	23
8. APPENDIX A. TEST SETUP PHOTOGRAPHS	24



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFG710TM
IC	2703C-G710AWM
Model	LM-G710AWM
Additional Model	LMG710AWM, G710AWM, LM-G710TM, LMG710TM, G710TM
EUT Type	Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN, Bluetooth and RFID
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 2 496 MHz to 2 570 MHz (LTE B7) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 788 MHz to 798 MHz (LTE B14) 704 MHz to 716 MHz (LTE B17) 1 850 MHz to 1 915 MHz (LTE B25) 2 305 MHz to 2 315 MHz (LTE B30) 2 496 MHz to 2 690 MHz (LTE B41) 1 710 MHz to 1 780 MHz (LTE B66) 663 MHz to 698 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3) 13.56 MHz (RFID)
RX Frequency	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.40 MHz to 891.60 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 2 516 MHz to 2 690 MHz (LTE B7) 729 MHz to 746 MHz (LTE B12)



RX Frequency	746 MHz to 756 MHz (LTE B13) 758 MHz to 768 MHz (LTE B14) 734 MHz to 746 MHz (LTE B17) 1 925 MHz to 1 990 MHz (LTE B25) 717 MHz to 728 MHz (LTE B29) 2 350 MHz to 2 360 MHz (LTE B30) 2 496 MHz to 2 690 MHz (LTE B41) 5150 MHz to 5925 MHz (LTE B46) 2 110 MHz to 2 200 MHz (LTE B66) 617 MHz to 652 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3) 13.56 MHz (RFID)
--------------	---

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	

1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer	FCC ID / DoC/IC
EUT	LM-G710AWM	-	LG	ZNFG710TM 2703C-G710AWM
Data cable	EAD64746101	-	Ningbo Broad	-
Data cable	EAD64746102	-	Luxshare	-
Earphone	EAB64168751	-	I-SOUND	-
Notebook PC	ProBook6560b	5CB2053MXF	HP	DoC
Notebook PC adaptor	Series PPP009L-E	-	Lite-On Technology	-
Gateway	TL-WR747N	-	TP-LINK	-
Gateway adaptor	T120150-2H1	-	TP-LINK	-
Serial mouse	Serial 2 button mouse	02031069	Radio shack	FSUGMZE3
RJ45 cable	-	-	-	-
Micro SD card	256GB EVO+UHS-I MicroSDXC U1	-	SAMSUNG	-



1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	USB Type C	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.6
	Serial (Mouse)	N/A	Y	(D)1.8
	DC IN	N	N/A	(P)1.8
Gateway	DC IN	N	N/A	(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	USB Type C	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	1.82 dB ($k = 2$)
3 m Radiated Emissions (30 MHz to 1 GHz)	5.20 dB ($k = 2$)
10 m Radiated Emissions (30 MHz to 1 GHz)	5.01 dB ($k = 2$)
3 m Radiated Emissions (1 GHz to 18 GHz)	5.24 dB ($k = 2$)
3 m Radiated Emissions (18 GHz to 40 GHz)	5.40 dB ($k = 2$)



3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

3.3 Configuration of Tested System



Non-Conductive Table
Power Line: 120 VAC, 60 Hz



4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

4. 2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B ICES-003 Issue 6 Class B / ANSI C63.4-2014
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
Worst Data Cable	EAD64746102 (Luxshare)
Kind of Test Site	Shielded Room
Temperature	21.3 °C
Relative Humidity	35.4 %
Test Date	March 08, 2018

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Conducted Emission, AC Main Port, Data Communication Mode, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	43.9	9.000	L1	9.6	22.1	66.0
0.156000	43.0	9.000	L1	9.6	22.7	65.7
0.160000	43.8	9.000	L1	9.6	21.7	65.5
0.164000	45.4	9.000	L1	9.6	19.9	65.3
0.172000	45.4	9.000	L1	9.6	19.5	64.9
0.180000	43.9	9.000	L1	9.6	20.5	64.5
1.114000	30.3	9.000	L1	9.7	25.7	56.0
1.146000	29.8	9.000	L1	9.7	26.2	56.0
1.162000	30.2	9.000	L1	9.7	25.8	56.0
4.432000	28.6	9.000	L1	9.8	27.4	56.0
4.506000	28.0	9.000	L1	9.8	28.0	56.0
4.718000	26.6	9.000	L1	9.8	29.4	56.0
9.438000	33.4	9.000	L1	9.9	26.6	60.0
9.456000	33.3	9.000	L1	9.9	26.7	60.0
9.480000	33.3	9.000	L1	9.9	26.7	60.0
9.624000	33.3	9.000	L1	10.0	26.7	60.0
9.668000	33.3	9.000	L1	10.0	26.7	60.0
9.782000	32.4	9.000	L1	10.0	27.6	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	26.9	9.000	L1	9.6	29.0	55.9
0.160000	30.9	9.000	L1	9.6	24.5	55.5
0.164000	32.3	9.000	L1	9.6	23.0	55.3
0.172000	32.0	9.000	L1	9.6	22.9	54.9
0.180000	32.8	9.000	L1	9.6	21.7	54.5
0.190000	29.1	9.000	L1	9.6	24.9	54.0
1.114000	23.7	9.000	L1	9.7	22.3	46.0
1.146000	23.4	9.000	L1	9.7	22.6	46.0
1.162000	23.2	9.000	L1	9.7	22.8	46.0
4.320000	20.9	9.000	L1	9.8	25.1	46.0
4.352000	20.6	9.000	L1	9.8	25.4	46.0
4.432000	20.1	9.000	L1	9.8	25.9	46.0
9.248000	25.3	9.000	L1	9.9	24.7	50.0
9.310000	25.6	9.000	L1	9.9	24.4	50.0
9.438000	26.6	9.000	L1	9.9	23.4	50.0
9.456000	26.4	9.000	L1	9.9	23.6	50.0
9.584000	26.5	9.000	L1	10.0	23.5	50.0
9.782000	25.6	9.000	L1	10.0	24.4	50.0



Figure 2: Conducted Emission, AC Main Port, Data Communication Mode, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	44.2	9.000	N	9.6	21.8	66.0
0.156000	43.2	9.000	N	9.6	22.5	65.7
0.164000	45.0	9.000	N	9.6	20.2	65.3
0.168000	45.1	9.000	N	9.6	20.0	65.1
0.182000	43.5	9.000	N	9.6	20.9	64.4
0.188000	42.2	9.000	N	9.6	21.9	64.1
1.118000	29.2	9.000	N	9.7	26.8	56.0
1.150000	29.4	9.000	N	9.7	26.6	56.0
2.882000	30.3	9.000	N	9.8	25.7	56.0
3.004000	30.2	9.000	N	9.8	25.8	56.0
3.086000	29.9	9.000	N	9.8	26.1	56.0
3.436000	27.7	9.000	N	9.8	28.3	56.0
9.156000	34.1	9.000	N	10.0	25.9	60.0
9.246000	34.8	9.000	N	10.0	25.2	60.0
9.258000	35.0	9.000	N	10.0	25.0	60.0
9.340000	35.1	9.000	N	10.0	24.9	60.0
9.392000	35.3	9.000	N	10.0	24.7	60.0
9.422000	34.1	9.000	N	10.0	25.9	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.7	9.000	N	9.6	27.3	56.0
0.158000	30.3	9.000	N	9.6	25.3	55.6
0.168000	32.8	9.000	N	9.6	22.2	55.1
0.174000	33.1	9.000	N	9.6	21.7	54.8
0.180000	31.8	9.000	N	9.6	22.7	54.5
0.186000	32.2	9.000	N	9.6	22.0	54.2
1.074000	23.2	9.000	N	9.7	22.8	46.0
1.150000	23.3	9.000	N	9.7	22.7	46.0
2.882000	22.2	9.000	N	9.8	23.8	46.0
3.004000	22.4	9.000	N	9.8	23.6	46.0
3.086000	21.8	9.000	N	9.8	24.2	46.0
3.436000	19.8	9.000	N	9.8	26.2	46.0
9.156000	27.1	9.000	N	10.0	22.9	50.0
9.246000	28.0	9.000	N	10.0	22.0	50.0
9.258000	27.9	9.000	N	10.0	22.1	50.0
9.340000	28.4	9.000	N	10.0	21.6	50.0
9.392000	28.4	9.000	N	10.0	21.6	50.0
9.422000	28.2	9.000	N	10.0	21.8	50.0



5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B ICES-003 Issue 6 Class B / ANSI C63.4-2014
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
Worst Data Cable	EAD64746102 (Luxshare)
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.5 °C
Relative Humidity	35.6 %
Test Date	March 08, 2018

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
54.660800	26.6	100.0	V	30.0	20.0	13.4	40.0
81.154400	32.9	385.9	H	274.0	15.5	7.1	40.0
152.067200	34.8	198.7	H	331.0	20.0	8.7	43.5
180.150400	30.3	149.8	H	144.0	18.7	13.2	43.5
374.984000	33.4	100.0	H	44.0	22.4	12.6	46.0
874.979200	36.8	100.0	H	0.0	30.9	9.2	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B ICES-003 Issue 6 Class B / ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	5 825 MHz
Upper Frequency	1 GHz to 29.125 GHz
Operation Mode	Data Communication mode
Worst Data Cable	EAD64746102 (Luxshare)
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.4 °C
Relative Humidity	35.0 %
Test Date	March 11, 2018

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1000.100000	45.5	199.8	H	37.0	-12.8	28.5	74.0
1400.000000	47.8	213.7	V	176.0	-11.4	26.2	74.0
2099.875000	47.3	99.7	V	60.0	-9.6	26.7	74.0
2660.910000	47.0	99.8	V	212.0	-7.4	27.0	74.0
5986.045000	46.6	99.8	V	109.0	0.9	27.4	74.0
9768.500000	51.0	150.0	H	52.0	11.1	23.0	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1000.100000	32.6	199.8	H	37.0	-12.8	21.4	54.0
1400.000000	46.0	213.7	V	176.0	-11.4	8.0	54.0
2099.875000	25.0	99.7	V	60.0	-9.6	29.0	54.0
2660.910000	23.7	99.8	V	212.0	-7.4	30.3	54.0
5986.045000	31.4	99.8	V	109.0	0.9	22.6	54.0
9768.500000	38.6	150.0	H	52.0	11.1	15.4	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	CAL Date
<u>Conducted Emission</u>					
☐ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.20.2017
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	06.27.2017
☒ LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	05.22.2017
☐ LISN	Rohde & Schwarz	ENV216	100073	1 year	07.18.2017
☒ LISN	Rohde & Schwarz	ENV216	102245	1 year	12.20.2017
☒ Software	Rohde & Schwarz	EMC32 VER8.54.0	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
☒ Trilog Antenna	Schwarzbeck	VULB 9168	760	2 year	04.06.2017
☐ Antenna master	HD GmbH	MA240	240/520	N/A	-
☐ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Antenna master	INNCO Systems	MA4000-XP-ET	-	N/A	-
☒ Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515/L	N/A	-
☒ Turn Table	INNCO Systems	-	-	N/A	-
☒ Turn Table controller	INNCO Systems	CO2000	-	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-
-For measurement above 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
☒ Antenna master	INNCO Systems	MA4000-XP-ET	-	N/A	-
☒ Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515/L	N/A	-
☒ Turn Table	INNCO Systems	-	-	N/A	-
☒ Turn Table controller	INNCO Systems	CO2000	-	N/A	-
☒ Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.01.2017
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
☒ Power Amplifier	TESTEK	TK-PA1840H	170030-L	1 year	12.20.2017
☒ Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	2 year	12.05.2017
☐ Horn Antenna	Schwarzbeck	BBHA 9120D	1300	2 year	06.30.2017
☐ Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170124	2 year	04.25.2017
☐ EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-



7. CONCLUSION

The data collected shows that the **EUT Type: Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN, Bluetooth and RFID, Model: LM-G710AWM** complies with §15.107 and §15.109 of the FCC rules and ICES-003 Issue 6 of the IC rules.



8. APPENDIX A. TEST SETUP PHOTOGRAPHS

Please refer to Appendix A