

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2007-0196(2)
2. Customer
 - Name : LG Electronics USA, Inc.
 - Address : 111 Sylvan Avenue, North Building Englewood Cliffs, NJ 07632
3. Use of Report : FCC Original Grant
4. Product Name / Model Name : Mobile Phone / LM-G910EMW
FCC ID : ZNFG910EMW
5. Test Method Used : KDB558074 D01v05r02, ANSI C63.10-2013
Test Specification : FCC Part 15.247
6. Date of Test : 2020.04.16 ~ 2020.05.19, 2020.06.11 ~ 2020.07.01
7. Location of Test : Permanent Testing Lab On Site Testing
8. Testing Environment : Refer to appended test report.
9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Affirmation	Tested by Name : JungWoo Kim 	Reviewed by Name : GeunKi Son 
-------------	---	--

2020 . 07 . 10 .

DT&C Co., Ltd.

Not abided by KS Q ISO / IEC 17025 and KOLAS accreditation.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2007-0196	Jul. 03, 2020	Initial issue	InHee Bae	GeunKi Son
DRTFCC2007-0196(1)	Jul. 09, 2020	Revised the section 1	JungWoo Kim	GeunKi Son
DRTFCC2007-0196(2)	Jul. 10, 2020	Revised the section 1	JungWoo Kim	GeunKi Son

Table of Contents

- 1. General Information 4**
 - 1.1 Explanations for Reference Test Data 4
 - 1.1.1 Introduction 4
 - 1.1.2 Explain the Differences 4
 - 1.1.3 Spot Check Verification Data 4
 - 1.1.4 Refer Section 4
 - 1.2 Testing Laboratory 5
 - 1.3 Test Environment 5
 - 1.4 Measurement Uncertainty 5
 - 1.5 Details of Applicant 6
 - 1.6 Description of EUT 6
 - 1.7 Declaration by the applicant / manufacturer 6
 - 1.8 Test Equipment List 7
 - 1.9 Summary of Test Results 9
- 2. Test Methodology 10**
 - 2.1 EUT Configuration 10
 - 2.2 EUT Exercise 10
 - 2.3 General Test Procedures 10
 - 2.4 Description of Test Modes 10
 - 2.5 Instrument Calibration 10
- 3. Test Result 11**
 - 3.1 Maximum Peak Conducted Output Power 11
 - 3.1.1 Test Setup 11
 - 3.1.2 Test Procedures 11
 - 3.1.3 Test Results 11
 - 3.2 6 dB Bandwidth Measurement 16
 - 3.2.1 Test Setup 16
 - 3.2.2 Test Procedures 16
 - 3.2.3 Test Results 16
 - 3.3 Maximum Power Spectral Density 21
 - 3.3.1 Test Setup 21
 - 3.3.2 Test Procedures 21
 - 3.3.3 Test Results 21
 - 3.4 Unwanted Emissions (Conducted) 26
 - 3.4.1 Test Setup 26
 - 3.4.2 Test Procedures 26
 - 3.4.3 Test Results 27
 - 3.5 Unwanted Emissions (Radiated) 43
 - 3.5.1 Test Setup 44
 - 3.5.2 Test Procedures 44
 - 3.5.3 Test Results 45
 - 3.6 Power line Conducted Emissions 48
 - 3.6.1 Test Setup 48
 - 3.6.2 Test Procedures 48
 - 3.6.3 Test Results 48
 - 3.7 Occupied Bandwidth 52
 - 3.7.1 Test Setup 52
 - 3.7.2 Test Procedures 52
 - 3.7.3 Test Results 52
- 4. ANTENNA REQUIREMENTS 53**
- APPENDIX I 54**
- APPENDIX II 55**
- APPENDIX III 57**

1. General Information

1.1 Explanations for Reference Test Data

1.1.1 Introduction

This report includes the BLE test data of FCC ID: ZNFG910HMW with reference to KDB 484596 D01v01. The applicant takes full responsibility that the test data as reference section below represents compliance for FCC ID: ZNFG910EMW

Reference FCC ID	Exhibit type	Separated FCC ID
ZNFG910HMW	Original Grant	ZNFG910EMW

1.1.2 Explain the Differences

FCC ID: ZNFG910EMW is same the internal printed circuit board with FCC ID: ZNFG910HMW. Two products differ only the depopulation of components for the purposes of adding or removing frequency bands of operating in non US. (It does not changed the SW/HW component of BLE).

Change Bands(Frequency) Information

FCC ID	ZNFG910EMW	ZNFG910HMW
LTE	B1,2,3,4,5,7,8,12,13,17,20,28,32,38,39,40,41,66	B1,2,3,4,5,7,8,12,13,17,20,25,26,28,38,40,41,66

Component Changes Information

REF.	ZNFG910EMW	ZNFG910HMW	Changes(vs ZNFG910HMW)
U1201	EAN64893201	EAN64996301	MB L-PAMID
FL1360	EAM64393501	DNI	B32 PRx SAW added (B32 is supported)
FL1301	EAN64973501	DNI	B32 DRx module added (B32 is supported)
FL5610	EAM62491401	DNI	GPS Extractor (for B32) added
FL5602	DNI	EAM65742901	GPS SAW deleted
FL1201	EAM64390401	DNI	B39 PRx SAW added (B39 is supported)

1.1.3 Spot Check Verification Data

Equipment Class (capability)	FCC Part	Mode	TX Freq. (MHz)	Test item	Test note	Detector Mode	Reference FCC ID: ZNFG910HMW		Separated FCC ID: ZNFG910EMW		Limit (dBuV/m)	Deviation (dB)
							Frequency (MHz)	Result (dBuV/m)	Frequency (MHz)	Result (dBuV/m)		
DTS (Bluetooth LE)	15.247	2Mbps	2 480	Radiated Band edge	With DD+WCP	Average	2 483.97	46.87	2 483.71	46.18	54.00	-0.69
		2Mbps	2 480	Radiated Spurious emission	With DD+WCP	Average	7 440.05	47.88	7 439.52	47.63	54.00	-0.25

Note1: The spot check were performed based on worst-case results reported in the original FCC report. The spot check test results are within 3dB and two products shows a good correlation. It also complies with the FCC/IC limit.

1.1.4 Refer Section

Reference FCC ID: ZNFG910HMW

Equipment Class	FCC Part	Capability	Band(MHz)	Exhibit type	Report title	Reference Sections
DSS	Part 15.247	BLE	2 402 ~ 2 480	Original Grant	DTS-LE	All

1.2 Testing Laboratory

DT&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.		
- FCC MRA Accredited Test Firm No. : KR0034		
www.dtn.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.3 Test Environment

Ambient Condition	
▪ Temperature	+20 °C ~ +25 °C
▪ Relative Humidity	35 % ~ 45 %

1.4 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014 and ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Test items	Measurement uncertainty
Transmitter Output Power	0.9 dB (The confidence level is about 95 %, $k = 2$)
Conducted spurious emission	0.9 dB (The confidence level is about 95 %, $k = 2$)
AC conducted emission	3.6 dB (The confidence level is about 95 %, $k=2$)
Radiated spurious emission (1 GHz Below)	4.9 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (1 GHz ~ 18 GHz)	5.0 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, $k = 2$)

1.5 Details of Applicant

Applicant : LG Electronics USA, Inc.
 Address : 111 Sylvan Avenue, North Building Englewood Cliffs, NJ 07632
 Contact person : Kyung-Su Han

1.6 Description of EUT

EUT	Mobile Phone
Model Name	LM-G910EMW
Add Model Name	LMG910EMW, G910EMW
Serial Number	Identical prototype
Power Supply	DC 3.87 V
Frequency Range	2 402 MHz ~ 2 480 MHz
Max. RF Output Power	7.45 dBm
Modulation Technique	GFSK
Antenna Specification	Antenna Type: PIFA Antenna Gain: -2.43 dBi (PK)

1.7 Declaration by the applicant / manufacturer

N/A

1.8 Test Equipment List

Date of Test(original test): 2020-04-16 ~ 2020-05-19

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY50410357
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY48011700
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY48010133
DC Power Supply	Agilent Technologies	66332A	19/06/25	20/06/25	MY43000211
Multimeter	FLUKE	17B	19/12/16	20/12/16	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	19/12/16	20/12/16	255571
Signal Generator	ANRITSU	MG3695C	19/12/16	20/12/16	173501
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-1
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-2
Thermohygrometer	BODYCOM	BJ5478	19/09/18	20/09/18	N/A
HYGROMETER	TESTO	608-H1	20/01/21	21/01/21	34862883
Loop Antenna	Schwarzbeck	FMZB1513	20/02/19	22/02/19	1513-128
BILOG ANTENNA	Schwarzbeck	VULB 9160	19/04/23	21/04/23	9160-3362
Horn Antenna	ETS-Lindgren	3115	20/01/30	22/01/30	6419
Horn Antenna	A.H.Systems Inc.	SAS-574	19/07/03	21/07/03	155
PreAmplifier	tsj	MLA-0118-B01-40	19/12/16	20/12/16	1852267
PreAmplifier	tsj	MLA-1840-J02-45	19/06/27	20/06/27	16966-10728
PreAmplifier	H.P	8447D	19/12/16	20/12/16	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	19/06/26	20/06/26	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	19/06/26	20/06/26	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	19/06/27	20/06/27	3
Attenuator	Hefei Shunze	SS5T2.92-10-40	19/06/27	20/06/27	16012202
Attenuator	SRTechnology	F01-B0606-01	19/06/27	20/06/27	13092403
Attenuator	Aeroflex/Weinschel	20515	19/06/27	20/06/27	Y2370
Attenuator	SMAJK	SMAJK-2-3	19/06/27	20/06/27	2
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2488B MA2491A	20/01/02	21/01/02	0846002
			20/01/02	21/01/02	0845295
EMI Receiver	ROHDE&SCHWARZ	ESW44	19/07/30	20/07/30	101645
HYGROMETER	TESTO	608-H1	20/01/21	21/01/21	34862883
EMI Test Receiver	Rohde Schwarz	ESC17	20/01/20	21/01/20	100910
PULSE LIMITER	Rohde Schwarz	ESH3-Z2	19/09/17	20/09/17	101333
LISN	SCHWARZBECK	NNLK 8121	19/05/23	20/05/23	6183
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-04
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-07
Cable	DT&C	Cable	20/01/13	21/01/13	G-13
Cable	DT&C	Cable	20/01/13	21/01/13	G-14
Cable	HUBER+SUHNER	SUCOFLEX 104	20/01/13	21/01/13	G-15
Cable	Radiall	TESTPRO3	20/01/16	21/01/16	M-01
Cable	Junkosha	MWX315	20/01/16	21/01/16	M-05
Cable	Junkosha	MWX221	20/01/16	21/01/16	M-06
Cable	DT&C	Cable	20/01/16	21/01/16	RF-82

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017

Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.

Date of Test(Spot check verification): 2020.06.11 ~ 2020.07.01

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY48011700
DC Power Supply	Agilent Technologies	66332A	19/06/25	20/06/25	MY43000211
			20/06/24	21/06/24	
Multimeter	FLUKE	17B	19/12/16	20/12/16	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	19/12/16	20/12/16	255571
Signal Generator	ANRITSU	MG3695C	19/12/16	20/12/16	173501
Thermohygrometer	BODYCOM	BJ5478	19/09/18	20/09/18	N/A
Horn Antenna	ETS-Lindgren	3115	20/01/30	22/01/30	6419
PreAmplifier	tsj	MLA-0118-B01-40	19/12/16	20/12/16	1852267
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	19/06/26	20/06/26	8
			20/06/24	21/06/24	
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	19/06/26	20/06/26	1
			20/06/24	21/06/24	
Attenuator	Hefei Shunze	SS5T2.92-10-40	19/06/27	20/06/27	16012202
			20/06/24	21/06/24	
Attenuator	SRTechnology	F01-B0606-01	19/06/27	20/06/27	13092403
			20/06/24	21/06/24	
Attenuator	Aeroflex/Weinschel	20515	19/06/27	20/06/27	Y2370
			20/06/24	21/06/24	
Attenuator	SMAJK	SMAJK-2-3	19/06/27	20/06/27	2
			20/06/24	21/06/24	
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2488B MA2491A	20/01/02	21/01/02	0846002 0845295
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-04
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-07
Cable	DT&C	Cable	20/01/13	21/01/13	G-13
Cable	DT&C	Cable	20/01/13	21/01/13	G-14
Cable	HUBER+SUHNER	SUCOFLEX 104	20/01/13	21/01/13	G-15

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017

Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.

1.9 Summary of Test Results

FCC Part	RSS Std.	Parameter	Limit	Test Condition	Status Note 1
15.247(a)	RSS-247 [5.2]	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	RSS-247 [5.4]	Transmitter Output Power	< 1 Watt		C
15.247(d)	RSS-247 [5.5]	Out of Band Emissions / Band Edge	20 dBc in any 100 kHz BW		C
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8 dBm/3 kHz		C
-	RSS-Gen [6.7]	Occupied Bandwidth (99 %)	NA		NA
15.247(d) 15.205 15.209	RSS-247 [5.5] RSS-GEN [8.9] RSS-GEN [8.10]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	FCC 15.209 limits	Radiated	C Note 3,4
15.207	RSS-Gen [8.8]	AC Line Conducted Emissions	FCC 15.207 limits	AC Line Conducted	C
15.203	-	Antenna Requirements	FCC 15.203	-	C

Note 1: **C**=Comply **NC**=Not Comply **NT**=Not Tested **NA**=Not Applicable
 Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS.
 Note 3: This test item was performed in each axis and the worst case data was reported.
 Note 4: This device supports wireless charging capability & Can use Dual Screen.
 So per KDB648474 D03v01r04, the radiated test items were performed all not charging, charging and Dual Screen conditions, the handset is placed on the representative charging pad under normal conditions and in a simulated call configuration.

2. Test Methodology

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB558074 D01v05r02 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB558074 D01v05r02. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the test mode to fix the TX frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3 General Test Procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB558074 D01v05r02.

So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB558074 D01v05r02. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on section 12.1 of the KDB558074 D01v05r02.

The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axes.

2.4 Description of Test Modes

The EUT has been tested with the operating condition for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting. The Bluetooth low energy mode with below low, middle and high channels were tested and reported.

Test Mode	Description	Frequency [MHz]		
		Lowest Frequency	Middle Frequency	Highest Frequency
TM 1	BT LE(1Mbps)	2 402	2 440	2 480
TM 2	BT LE(2Mbps)	2 402	2 440	2 480
TM 3	BT LE(1 Mbps) with WPC	2 402	2 440	2 480
TM 4	BT LE(2 Mbps) with WPC	2 402	2 440	2 480
TM 5	BT LE(2 Mbps) with Dual Display	2 402	2 440	2 480
TM 6	BT LE(2 Mbps) with Dual Display+WPC	2 402	2 440	2 480

2.5 Instrument Calibration

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

3. Test Result

3.1 Maximum Peak Conducted Output Power

▣ Test Requirements and limit, §15.247(b) & RSS-247 [5.4]

A transmitter antenna terminal of EUT is connected to the input of a spectrum analyzer.

Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

3.1.1 Test Setup

Refer to the APPENDIX I.

3.1.2 Test Procedures

- KDB558074 D01v05r02 - Section 8.3.1.3
- ANSI C63.10-2013 – Section 11.9.1.1

RBW ≥ DTS bandwidth

1. Set the RBW ≥ DTS bandwidth. **Actual RBW = 2 MHz & 2.4 MHz**
2. Set VBW ≥ 3 x RBW. **Actual VBW = 6 MHz & 8 MHz**
3. Set span ≥ 3 x RBW.
4. Sweep time = **auto couple**
5. Detector = **peak**
6. Trace mode = **max hold**
7. Allow trace to fully stabilize
8. Use peak marker function to determine the peak amplitude level.

3.1.3 Test Results

Test mode	Tested Channel	Burst Average Output Power	Peak Output Power
		dBm	dBm
TM 1	Lowest	6.98	7.37
	Middle	6.46	6.56
	Highest	5.50	5.63
TM 2	Lowest	6.97	7.45
	Middle	6.46	6.72
	Highest	5.45	5.65

Note 1 : The Burst average output power was tested using an average power meter for reference only.

Note 2 : See next pages for actual measured spectrum plots.


Peak Output Power

TM 1 Test Channel : Lowest




Peak Output Power

TM 1 Test Channel : Middle




Peak Output Power

TM 1 Test Channel : Highest




Peak Output Power

TM 2 Test Channel : Lowest




Peak Output Power

TM 2 Test Channel : Middle



Peak Output Power

TM 2 Test Channel : Highest



3.2 6 dB Bandwidth Measurement

■ Test Requirements and limit, §15.247(a) & RSS-247 [5.2]

The bandwidth at 6 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the EUT's antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6 dB bandwidth is 500 kHz.

3.2.1 Test Setup

Refer to the APPENDIX I.

3.2.2 Test Procedures

- KDB558074 D01v05r02 - Section 8.2
- ANSI C63.10-2013 – Section 11.8.2

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.

(RBW : 100 kHz / VBW : 300 kHz)

3. Detector = **peak**.
4. Trace mode = **max hold**.
5. Sweep = **auto couple**.
6. Allow the trace to stabilize.
7. Option 1 - Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Option 2 - The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

3.2.3 Test Results

Test Mode	Tested Channel	Test Results [MHz]
TM 1	Lowest	0.671
	Middle	0.667
	Highest	0.668
TM 2	Lowest	1.138
	Middle	1.170
	Highest	1.147

6 dB Bandwidth

TM 1 Test Channel : Lowest




6 dB Bandwidth

TM 1 Test Channel : Middle



6 dB Bandwidth

TM 1 Test Channel : Highest




6 dB Bandwidth

TM 2 Test Channel : Lowest




6 dB Bandwidth

TM 2 Test Channel : Middle



6 dB Bandwidth

TM 2 Test Channel : Highest



3.3 Maximum Power Spectral Density.

▣ Test requirements and limit, §15.247(e) & RSS-247 [5.2]

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

3.3.1 Test Setup

Refer to the APPENDIX I.

3.3.2 Test Procedures

- KDB558074 D01v05r02 - Section 8.4
- ANSI C63.10-2013 – Section 11.10.2

Method PKPSD (peak PSD)

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to **1.5 times** the DTS bandwidth.
3. Set the RBW : **3 kHz ≤ RBW ≤ 100 kHz**.
4. Set the VBW ≥ **3 x RBW**.
5. Detector = **peak**.
6. Sweep time = **auto couple**.
7. Trace mode = **max hold**.
8. Allow trace to fully stabilize.
9. Use the **peak marker function** to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

3.3.3 Test Results

Test Mode	Tested Channel	PKPSD [dBm]
TM 1	Lowest	-8.81
	Middle	-9.71
	Highest	-10.77
TM 2	Lowest	-11.32
	Middle	-12.02
	Highest	-13.25

Maximum PKPSD

TM 1 Test Channel : Lowest



Maximum PKPSD

TM 1 Test Channel : Middle



Maximum PKPSD

TM 1 Test Channel : Highest




Maximum PKPSD

TM 2 Test Channel : Lowest




Maximum PKPSD

TM 2 Test Channel : Middle



Maximum PKPSD

TM 2 Test Channel : Highest



3.4 Unwanted Emissions (Conducted)

■ Test requirements and limit, §15.247(d) & RSS-247 [5.5]

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions :

If **the peak output power procedure** is used to measure the fundamental emission power to demonstrate compliance to **15.247(b)(3)** requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated **by at least 20 dB** relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to **15.247(b)(3)** requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured inband average PSD level.

In either case, attenuation to levels below the general emission limits specified in §15.209(a) is not required.

3.4.1 Test Setup

Refer to the APPENDIX I including path loss

3.4.2 Test Procedures

- KDB558074 D01v05r02 - Section 8.5
- ANSI C63.10-2013 – Section 11.11

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency.
2. Set the span to ≥ 1.5 times the DTS bandwidth.
3. Set the RBW = 100 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum PSD level
LIMIT LINE = 20 dB below of the reference level.

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = **100 kHz.(Actual 1 MHz , See below note)**
3. Set the VBW $\geq 3 \times$ RBW.**(Actual 3 MHz, See below note)**
4. Detector = **peak**.
5. Ensure that the number of measurement points \geq span / RBW
6. Sweep time = **auto couple**.
7. Trace mode = **max hold**.
8. **Allow the trace to stabilize** (this may take some time, depending on the extent of the span).
9. Use the peak marker function to determine the maximum amplitude level.

Note : The conducted spurious emission was tested with below settings.

Frequency range	RBW	VBW	Detector	Trace	Sweep Point
9 kHz ~ 30 MHz	100 kHz	300 kHz	Peak	Max Hold	40 001
30 MHz ~ 10 GHz	1 MHz	3 MHz			
10 GHz ~ 25 GHz	1 MHz	3 MHz			


If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2 001 to get accurate emission level within 100 kHz BW.

3.4.3 Test Results


TM 1 Reference (Test Channel : Lowest)




TM 1 Low Band-edge (Test Channel : Lowest)




TM 1 Conducted Spurious Emissions 1 (Test Channel : Lowest)



TM 1 Conducted Spurious Emissions 2 (Test Channel : Lowest)




TM 1 Conducted Spurious Emissions 3 (Test Channel : Lowest)




TM 1 Reference (Test Channel : Middle)




TM 1 Conducted Spurious Emissions 1 (Test Channel : Middle)




TM 1 Conducted Spurious Emissions 2 (Test Channel : Middle)




TM 1 Conducted Spurious Emissions 3 (Test Channel : Middle)




TM 1 Reference (Test Channel : Highest)




TM 1 High Band-edge (Test Channel : Highest)




TM 1 Conducted Spurious Emissions 1 (Test Channel : Highest)




TM 1 Conducted Spurious Emissions 2 (Test Channel : Highest)




TM 1 Conducted Spurious Emissions 3 (Test Channel : Highest)




TM 2 Reference (Test Channel : Lowest)




TM 2 Low Band-edge (Test Channel : Lowest)




TM 2 Conducted Spurious Emissions 1 (Test Channel : Lowest)



TM 2 Conducted Spurious Emissions 2 (Test Channel : Lowest)




TM 2 Conducted Spurious Emissions 3 (Test Channel : Lowest)




TM 2 Reference (Test Channel : Middle)




TM 2 Conducted Spurious Emissions 1 (Test Channel : Middle)




TM 2 Conducted Spurious Emissions 2 (Test Channel : Middle)




TM 2 Conducted Spurious Emissions 3 (Test Channel : Middle)




TM 2 Reference (Test Channel : Highest)




TM 2 High Band-edge (Test Channel : Highest)




TM 2 Conducted Spurious Emissions 1 (Test Channel : Highest)



TM 2 Conducted Spurious Emissions 2 (Test Channel : Highest)



TM 2 Conducted Spurious Emissions 3 (Test Channel : Highest)



3.5 Unwanted Emissions (Radiated)

▣ **Test Requirements and limit,**

§15.247(d), §15.205, §15.209 & RSS-247 [5.5], RSS-Gen [8.9], RSS-Gen [8.10]

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) and (b), then the 15.209(a) limit in the table below has to be followed.

▪ **FCC Part 15.209(a) and (b)**

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

▪ **FCC Part 15.205 (a) :** Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~ 156.52525	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.7 ~ 156.9	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	162.0125 ~ 167.17	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	167.72 ~ 173.2	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	240 ~ 285	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	322 ~ 335.4	2690 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	960 ~ 1240	3345.8 ~ 3358		
			3600 ~ 4400		

▪ **FCC Part 15.205(b) :** The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

3.5.1 Test Setup

Refer to the APPENDIX I.

3.5.2 Test Procedures

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

Note: Measurement Instrument Setting for Radiated Emission Measurements.

- KDB558074 D01v05r02 - Section 8.6
- ANSI C63.10-2013 – Section 11.12

1. Frequency Range Below 1 GHz

RBW = 100 or 120 kHz, VBW = 3 x RBW, Detector = Peak or Quasi Peak

2. Frequency Range > 1 GHz

Peak Measurement > 1 GHz

RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Sweep time = Auto, Trace mode = Max Hold until the trace stabilizes

Average Measurement > 1GHz

1. RBW = 1 MHz (unless otherwise specified).
2. VBW \geq 3 x RBW.
3. Detector = RMS (Number of points \geq 2 x Span / RBW)
4. Averaging type = power (i.e., RMS).
5. Sweep time = auto.
6. Perform a trace average of at least 100 traces.
7. A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step 4, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step 4, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (\geq 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

Test Mode	Duty Cycle (%)	T _{on} (ms)	T _{on} + T _{off} (ms)	DCF = 10 log(1 / Duty) (dB)
TM 1	85.63	2.145	2.505	0.67
TM 2	57.75	1.080	1.870	2.38

Note : Refer to appendix II for duty cycle measurement procedure and plots

3.5.3 Test Results

- Test Notes

1. The radiated emissions were investigated 9 kHz to 25 GHz. And no other spurious and harmonic emissions were found below listed frequencies.
2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3 m to 1 m. In this case, the distance factor (-9.54 dB) is applied to the result.

- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,

DCF = Duty Cycle Correction Factor.

Frequency Range : 9 kHz ~ 25 GHz _ TM 1 _ Nomal

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 389.92	V	Z	PK	49.36	4.80	N/A	N/A	54.16	74.00	19.84
2 389.92	V	Z	AV	38.62	4.80	0.67	N/A	44.09	54.00	9.91
4 803.94	V	Y	PK	50.12	0.78	N/A	N/A	50.90	74.00	23.10
4 803.71	V	Y	AV	38.64	0.78	0.67	N/A	40.09	54.00	13.91

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4 879.97	V	Y	PK	50.39	1.31	N/A	N/A	51.70	74.00	22.30
4 879.67	V	Y	AV	39.40	1.31	0.67	N/A	41.38	54.00	12.62

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 483.72	V	Z	PK	48.87	5.25	N/A	N/A	54.12	74.00	19.88
2 483.63	V	Z	AV	39.16	5.25	0.67	N/A	45.08	54.00	8.92
4 959.90	V	Y	PK	49.54	1.61	N/A	N/A	51.15	74.00	22.85
4 959.96	V	Y	AV	38.99	1.61	0.67	N/A	41.27	54.00	12.73

Frequency Range : 9 kHz ~ 25 GHz _TM 2_Nomal
▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 389.78	V	Y	PK	48.82	4.80	N/A	N/A	53.62	74.00	20.38
2 389.86	V	Y	AV	38.32	4.80	2.38	N/A	45.50	54.00	8.50
4 803.64	V	Y	PK	48.98	0.78	N/A	N/A	49.76	74.00	24.24
4 803.92	V	Y	AV	38.81	0.78	2.38	N/A	41.97	54.00	12.03

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4 879.60	V	Y	PK	50.07	1.31	N/A	N/A	51.38	74.00	22.62
4 879.95	V	Y	AV	39.38	1.31	2.38	N/A	43.07	54.00	10.93

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 483.71	V	Y	PK	49.82	5.25	N/A	N/A	55.07	74.00	18.93
2 483.68	V	Y	AV	38.75	5.25	2.38	N/A	46.38	54.00	7.62
4 959.95	V	Y	PK	49.01	1.61	N/A	N/A	50.62	74.00	23.38
4 959.65	V	Y	AV	38.81	1.61	2.38	N/A	42.80	54.00	11.20

Frequency Range : 9 kHz ~ 25 GHz _ TM 3_ Wireless Charging
▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 483.81	H	X	PK	48.94	5.26	N/A	N/A	54.20	74.00	19.80
2 483.73	H	X	AV	38.78	5.25	0.67	N/A	44.70	54.00	9.30
4 959.63	H	X	PK	49.23	1.61	N/A	N/A	50.84	74.00	23.16
4 959.87	H	X	AV	39.02	1.61	0.67	N/A	41.30	54.00	12.70

Frequency Range : 9 kHz ~ 25 GHz _ TM 4_ Wireless Charging
▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 483.86	V	X	PK	49.43	5.26	N/A	N/A	54.69	74.00	19.31
2 483.79	V	X	AV	38.84	5.26	2.38	N/A	46.48	54.00	7.52
4 959.95	V	X	PK	50.16	1.61	N/A	N/A	51.77	74.00	22.23
4 959.61	V	X	AV	38.83	1.61	2.38	N/A	42.82	54.00	11.18

Frequency Range : 9 kHz ~ 25 GHz _ TM 5_ With Dual Display
▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 484.10	V	Y	PK	49.92	5.26	N/A	N/A	55.18	74.00	18.82
2 484.07	V	Y	AV	39.18	5.26	2.37	N/A	46.81	54.00	7.19
4 960.32	V	Y	PK	49.96	1.61	N/A	N/A	51.57	74.00	22.43
4 960.02	V	Y	AV	38.89	1.61	2.37	N/A	42.87	54.00	11.13
7 439.93	V	Y	PK	46.96	9.18	N/A	N/A	56.14	74.00	17.86
7 439.87	V	Y	AV	36.16	9.18	2.37	N/A	47.71	54.00	6.29

Frequency Range : 9 kHz ~ 25 GHz _ TM 6_ With Dual Display + WPC
▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 483.90	V	X	PK	49.59	5.26	N/A	N/A	54.85	74.00	19.15
2 483.97	V	X	AV	39.24	5.26	2.37	N/A	46.87	54.00	7.13
4 959.54	V	X	PK	49.23	1.61	N/A	N/A	50.84	74.00	23.16
4 959.97	V	X	AV	38.95	1.61	2.37	N/A	42.93	54.00	11.07
7 440.16	V	X	PK	47.04	9.18	N/A	N/A	56.22	74.00	17.78
7 440.05	V	X	AV	36.33	9.18	2.37	N/A	47.88	54.00	6.12

3.6 Power line Conducted Emissions

▣ Test Requirements and limit, §15.207 & RSS-Gen [8.8]

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

3.6.1 Test Setup

See test photographs for the actual connections between EUT and support equipment.

3.6.2 Test Procedures

Conducted emissions from the EUT were measured according to the ANSI C63.10-2013.

1. The test procedure is performed in a 6.5 m x 3.5 m x 3.5 m (L x W x H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) x 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

3.6.3 Test Results

Refer to the next page. (The worst case data was reported. The worst data is TM 1 & Middle)

AC Line Conducted Emissions (Graph)

Results of Conducted Emission

DTNC



Date 2020-05-08

Order No. DTNC2004-03119
 Model No. LM-G910HMW
 Serial No.
 Test Condition LE

Reference No.
 Power Supply 120 V, 60 Hz
 Temp/Humi. 23 'C / 42 %
 Operator InHee Bae

Memo

LIMIT : FCC P15.207 QP
 FCC P15.207 AV



AC Line Conducted Emissions (List)

Results of Conducted Emission

DTNC

Date 2020-05-08

Order No.	DTNC2004-03119	Reference No.	
Model No.	LM-G910HMW	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 °C / 42 %
Test Condition	LE	Operator	InHee Bae

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.15894	15.68	5.50	10.00	25.68	15.50	65.52	55.52	39.84	40.02	N
2	0.16998	14.98	5.01	10.02	25.00	15.03	64.96	54.96	39.96	39.93	N
3	0.17465	14.53	4.45	10.02	24.55	14.47	64.74	54.74	40.19	40.27	N
4	0.17694	18.72	6.35	10.02	28.74	16.37	64.63	54.63	35.89	38.26	N
5	0.19984	13.42	3.90	10.02	23.44	13.92	63.62	53.62	40.18	39.70	N
6	0.22391	13.10	3.62	10.02	23.12	13.64	62.67	52.67	39.55	39.03	N
7	0.24386	12.24	3.56	10.03	22.27	13.59	61.96	51.96	39.69	38.37	N
8	0.24717	11.67	3.42	10.03	21.70	13.45	61.85	51.85	40.15	38.40	N
9	0.25816	12.65	3.48	10.03	22.68	13.51	61.49	51.49	38.81	37.98	N
10	0.30742	11.49	2.90	10.03	21.52	12.93	60.04	50.04	38.52	37.11	N
11	0.42675	20.16	11.63	10.06	30.22	21.69	57.32	47.32	27.10	25.63	N
12	0.42984	20.05	11.17	10.06	30.11	21.23	57.26	47.26	27.15	26.03	N
13	0.66703	15.17	6.97	10.05	25.22	17.02	56.00	46.00	30.78	28.98	N
14	0.80607	13.16	5.21	10.06	23.22	15.27	56.00	46.00	32.78	30.73	N
15	0.88050	15.49	6.55	10.05	25.54	16.60	56.00	46.00	30.46	29.40	N
16	0.94589	13.83	5.82	10.05	23.88	15.87	56.00	46.00	32.12	30.13	N
17	0.97205	13.02	5.54	10.06	23.08	15.60	56.00	46.00	32.92	30.40	N
18	2.13555	14.11	5.95	10.11	24.22	16.06	56.00	46.00	31.78	29.94	N
19	2.32864	13.94	6.01	10.13	24.07	16.14	56.00	46.00	31.93	29.86	N
20	2.64881	13.96	6.11	10.14	24.10	16.25	56.00	46.00	31.90	29.75	N
21	2.99294	12.74	4.76	10.15	22.89	14.91	56.00	46.00	33.11	31.09	N
22	3.37865	14.00	6.50	10.17	24.17	16.67	56.00	46.00	31.83	29.33	N
23	3.76741	12.60	4.49	10.19	22.79	14.68	56.00	46.00	33.21	31.32	N
24	3.97367	12.85	4.86	10.19	23.04	15.05	56.00	46.00	32.96	30.95	N
25	4.12237	12.47	4.18	10.19	22.66	14.37	56.00	46.00	33.34	31.63	N
26	6.40490	7.74	0.82	10.25	17.99	11.07	60.00	50.00	42.01	38.93	N
27	6.76358	7.77	0.56	10.27	18.04	10.83	60.00	50.00	41.96	39.17	N
28	9.51794	10.40	2.14	10.33	20.73	12.47	60.00	50.00	39.27	37.53	N
29	9.93158	10.19	1.80	10.35	20.54	12.15	60.00	50.00	39.46	37.85	N
30	11.02023	9.17	0.90	10.36	19.53	11.26	60.00	50.00	40.47	38.74	N
31	15.38763	8.46	-0.93	10.44	18.90	9.51	60.00	50.00	41.10	40.49	N
32	18.65245	6.53	-0.99	10.50	17.03	9.51	60.00	50.00	42.97	40.49	N
33	20.10087	6.74	-0.41	10.53	17.27	10.12	60.00	50.00	42.73	39.88	N
34	21.00926	5.25	-1.22	10.55	15.80	9.33	60.00	50.00	44.20	40.67	N
35	0.15356	15.48	6.82	10.01	25.49	16.83	65.81	55.81	40.32	38.98	L
36	0.19764	14.12	4.38	10.02	24.14	14.40	63.71	53.71	39.57	39.31	L
37	0.21172	14.45	4.53	10.02	24.47	14.55	63.14	53.14	38.67	38.59	L
38	0.24469	13.34	4.24	10.02	23.36	14.26	61.94	51.94	38.58	37.68	L
39	0.42387	24.44	15.20	10.04	34.48	25.24	57.37	47.37	22.89	22.13	L
40	0.81850	21.54	11.28	10.06	31.60	21.34	56.00	46.00	24.40	24.66	L
41	1.23789	18.75	9.34	10.07	28.82	19.41	56.00	46.00	27.18	26.59	L
42	1.52132	18.32	9.15	10.10	28.42	19.25	56.00	46.00	27.58	26.75	L
43	1.91039	17.58	8.55	10.12	27.70	18.67	56.00	46.00	28.30	27.33	L
44	2.48222	18.51	8.93	10.13	28.64	19.06	56.00	46.00	27.36	26.94	L
45	2.53214	18.20	8.86	10.13	28.33	18.99	56.00	46.00	27.67	27.01	L
46	3.40447	17.35	8.13	10.16	27.51	18.29	56.00	46.00	28.49	27.71	L
47	9.76487	12.37	4.10	10.34	22.71	14.44	60.00	50.00	37.29	35.56	L
48	10.34332	12.64	4.14	10.34	22.98	14.48	60.00	50.00	37.02	35.52	L

AC Line Conducted Emissions (List)

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
49	11.67256	12.91	3.58	10.37	23.28	13.95	60.00	50.00	36.72	36.05	L
50	12.29301	12.86	2.97	10.38	23.24	13.35	60.00	50.00	36.76	36.65	L
51	19.66773	9.19	-1.36	10.50	19.69	9.14	60.00	50.00	40.31	40.86	L
52	20.19936	9.22	-1.16	10.50	19.72	9.34	60.00	50.00	40.28	40.66	L
53	20.96213	7.55	-1.62	10.51	18.06	8.89	60.00	50.00	41.94	41.11	L

3.7 Occupied Bandwidth

■ Test Requirements, RSS-Gen [6.7]

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99 % emission bandwidth, as calculated or measured.

3.7.1 Test Setup

-NA

3.7.2 Test Procedures

The 99 % power bandwidth was measured with a calibrated spectrum analyzer.

The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately $3 \times$ RBW.

Spectrum analyzer plots are included on the following pages.

3.7.3 Test Results

-NA

4. ANTENNA REQUIREMENTS

▣ **According to FCC 47 CFR §15.203**


“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

**The antenna is attached on the device by means of unique coupling method (Spring Tension).
Therefore this E.U.T Complies with the requirement of §15.203**


APPENDIX I

Test set up diagrams

▪ Radiated Measurement



▪ Conducted Measurement




Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	0.34	15	2.87
1	0.69	20	3.25
2.402 & 2.440 & 2.480	1.10	25	3.76
5	1.80	-	-
10	2.15	-	-

Note 1: The path loss from EUT to Spectrum analyzer was measured and used for test.
 Path loss (S/A's correction factor) = Cable A

Duty Cycle

TM 2 Test Channel : Middle




APPENDIX III

Unwanted Emissions (Radiated) Test Plot


TM1 & Lowest & Z & Ver

Detector Mode : PK




TM1 & Lowest & Z & Ver

Detector Mode : AV




TM1 & Highest & Z & Ver

Detector Mode : PK




TM1 & Highest & Z & Ver

Detector Mode : AV




TM1 & Middle & Y & Ver

Detector Mode : AV




TM2 & Lowest & Y & Ver

Detector Mode : PK




TM2 & Lowest & Y & Ver

Detector Mode : AV



TM2 & Highest & Y & Ver

Detector Mode : PK




TM2 & Highest & Y & Ver

Detector Mode : AV



TM2 & Middle & Y & Ver


Detector Mode : AV



Unwanted Emissions (Radiated) Test Plot_Wireless Charging

TM3 & Highest & X & Hor

Detector Mode : PK




TM3 & Highest & X & Hor

Detector Mode : AV




TM3 & Highest & X & Hor

Detector Mode : AV




TM4 & Highest & X & Hor

Detector Mode : PK




TM4 & Highest & X & Hor

Detector Mode : AV



TM4 & Highest & X & Hor


Detector Mode : AV



Unwanted Emissions (Radiated) Test Plot_With Dual Display


TM5 & Highest & Y & Ver

Detector Mode : PK




TM5 & Highest & Y & Ver

Detector Mode : AV



TM5 & Highest & Y & Ver


Detector Mode : AV



Unwanted Emissions (Radiated) Test Plot_With Dual Display+WPC


TM6 & Highest & X & Ver

Detector Mode : PK



TM6 & Highest & X & Ver

Detector Mode : AV



TM6 & Highest & X & Ver

Detector Mode : AV

