



FCC 47 CFR PART 15 SUBPART C

**CERTIFICATION TEST REPORT
FOR
GSM/WCDMA/LTE PHONE + BLUETOOTH, DTS/UNII a/b/g/n & NFC**

MODEL NUMBER: LG-H443, H443, LGH443

FCC ID: ZNFH443

REPORT NUMBER: 14I19589-E2

ISSUE DATE: JANUARY 6, 2015

Prepared for
**LG ELECTRONICS MOBILECOMM U.S.A., INC
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS,
NEW JERSEY, 07632, U.S.A**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	1/6/15	Initial Issue	P. Zhang

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>6</i>
4.2. <i>SAMPLE CALCULATION</i>	<i>6</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>6</i>
5. EQUIPMENT UNDER TEST	7
5.1. <i>DESCRIPTION OF EUT</i>	<i>7</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>7</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>7</i>
5.4. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>8</i>
5.5. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>9</i>
6. TEST AND MEASUREMENT EQUIPMENT	11
7. SUMMARY TABLE	12
8. ANTENNA PORT TEST RESULTS	13
8.1. <i>20 dB AND 99% BANDWIDTH</i>	<i>13</i>
8.1.1. <i>BASIC DATA RATE GFSK MODULATION</i>	<i>13</i>
8.1.2. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	<i>13</i>
8.2. <i>HOPPING FREQUENCY SEPARATION</i>	<i>26</i>
8.3. <i>NUMBER OF HOPPING CHANNELS.....</i>	<i>28</i>
8.4. <i>AVERAGE TIME OF OCCUPANCY.....</i>	<i>33</i>
8.5. <i>OUTPUT POWER.....</i>	<i>40</i>
8.5.1. <i>BASIC DATA RATE GFSK MODULATION</i>	<i>40</i>
8.5.2. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	<i>40</i>
8.5.3. <i>OUTPUT POWER PLOTS.....</i>	<i>41</i>
8.6. <i>AVERAGE POWER.....</i>	<i>47</i>
8.6.1. <i>BASIC DATA RATE GFSK MODULATION</i>	<i>47</i>
8.6.2. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	<i>47</i>
8.7. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	<i>48</i>
8.7.1. <i>BASIC DATA RATE GFSK MODULATION</i>	<i>49</i>
8.7.2. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	<i>57</i>
9. RADIATED TEST RESULTS.....	65
9.1. <i>LIMITS AND PROCEDURE.....</i>	<i>65</i>

9.2.	<i>TRANSMITTER ABOVE 1 GHz</i>	66
9.2.1.	BASIC DATA RATE GFSK MODULATION.....	66
9.2.2.	ENHANCED DATA RATE 8PSK MODULATION.....	79
9.3.	<i>WORST-CASE BELOW 1 GHz</i>	92
10.	AC POWER LINE CONDUCTED EMISSIONS	95
11.	SETUP PHOTOS	100

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S.A., INC
EUT DESCRIPTION: GSM/WCDMA/LTE PHONE + BLUETOOTH, DTS/UNII a/b/g/n & NFC
MODEL: LG-H443, H443, LGH443
SERIAL NUMBER: 43-03532 (Radiated); 43-03534 (Conducted)
DATE TESTED: DECEMBER 17, 2014 - JANUARY 2, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



PENG ZHANG
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.



CHARLES VERGONIO
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
<input type="checkbox"/> Chamber A(IC: 2324B-1)	<input type="checkbox"/> Chamber D(IC: 2324B-4)
<input type="checkbox"/> Chamber B(IC: 2324B-2)	<input type="checkbox"/> Chamber E(IC: 2324B-5)
<input checked="" type="checkbox"/> Chamber C(IC: 2324B-3)	<input type="checkbox"/> Chamber F(IC: 2324B-6)
	<input type="checkbox"/> Chamber G(IC: 2324B-7)
	<input type="checkbox"/> Chamber H(IC: 2324B-8)

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE PHONE + BLUETOOTH, DTS/UNII a/b/g/n & NFC.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	6.20	4.17
2402 - 2480	Enhanced 8PSK	6.38	4.35

Note: GFSK, Pi/4-DQPSK, 8DPSK average Power are all investigated, The GFSK & 8DPSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 8.6.

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -3.1dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	LG	N/A	N/A	N/A
Earphone	LG	N/A	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	02/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00980	11/14/15
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/15
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/15
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/15
CBT Bluetooth Tester	R & S	CBT	None	07/12/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/15
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15

7. SUMMARY TABLE

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
2.1049	RSS-GEN 4.6	Occupied Band width (99%)	N/A	Conducted	Pass	1.226MHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-43.19dBm
15.247 (b)(1)	RSS-210 A8.4	TX conducted output power	<21dBm		Pass	6.38dBm
15.247 (a)(1)	RSS-210 A8.1(b)	Hopping frequency separation	> 25KHz		Pass	1MHz
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	79
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Avg Time of Occupancy	< 0.4sec		Pass	0.288sec
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10		Radiated	Pass
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m	Pass		40.65dBuV/m

8. ANTENNA PORT TEST RESULTS

8.1. 20 dB AND 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to \geq 1% of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.

RESULTS

8.1.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	0.921	0.879
Middle	2441	0.925	0.903
High	2480	0.926	0.91
Worst		0.926	0.91


8.1.2. ENHANCED DATA RATE 8DPSK MODULATION

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	1.255	1.190
Middle	2441	1.276	1.223
High	2480	1.274	1.226
Worst		1.276	1.226


20 dB AND 99% BANDWIDTH PLOTS

GFSK 20 dB BANDWIDTH


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL




GFSK 99% BANDWIDTH


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL




8PSK 20 dB BANDWIDTH


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL



8PSK 99% BANDWIDTH

LOW CHANNEL



MID CHANNEL

Agilent 09:00:27 Dec 17, 2014		R T	Freq/Channel
Ch Freq 2.441 GHz		Trig Free	
Occupied Bandwidth		Averages: 100	
Ref 20.6 dBm #Atten 20 dB		Center Freq 2.44100000 GHz	
# Samp 10 Log dB/Offst 10.6 dB		Start Freq 2.43950000 GHz	
		Stop Freq 2.44250000 GHz	
Center 2.441 000 GHz		CF Step 300.000000 kHz	
#Res BW 120 kHz		Auto Man	
#VBW 360 kHz		Freq Offset 0.00000000 Hz	
#Sweep 100 ms (601 pts)		Signal Track On Off	
Occupied Bandwidth 1.2231 MHz		Occ BW % Pwr 99.00 % x dB -20.00 dB	
Transmit Freq Error 14.277 kHz			
x dB Bandwidth 1.327 MHz*			
Copyright 2000-2011 Agilent Technologies			

HIGH CHANNEL

Agilent 09:00:54 Dec 17, 2014		R T	Freq/Channel
Ch Freq 2.48 GHz		Trig Free	
Occupied Bandwidth		Averages: 100	
Ref 20.6 dBm #Atten 20 dB		Center Freq 2.4800000 GHz	
# Samp 10 Log dB/Offst 10.6 dB		Start Freq 2.47850000 GHz	
		Stop Freq 2.48150000 GHz	
Center 2.480 000 GHz Span 3 MHz #Res BW 120 kHz #VBW 360 kHz #Sweep 100 ms (601 pts)		CF Step 300.000000 kHz Auto Man	
Occupied Bandwidth 1.2267 MHz		Freq Offset 0.00000000 Hz	
Occ BW % Pwr 99.00 % x dB -20.00 dB		Signal Track On Cf	
Transmit Freq Error 15.778 kHz x dB Bandwidth 1.337 MHz*			
Copyright 2000-2011 Agilent Technologies			

8.2. HOPPING FREQUENCY SEPARATION

LIMIT

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION PLOT



8.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS

Normal Mode: 79 Channels observed.


NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, FIRST SEGMENT)



NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, SECOND SEGMENT)



NUMBER OF HOPPING CHANNELS (30 MHz SPAN, THIRD SEGMENT)



8.4. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{ pulse width}$.


RESULTS

DH Packet	Pulse Width (msec)	Number of Pulses in 3.16 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
GFSK Normal Mode					
DH1	0.380	31.0	0.1178	0.4	-0.2822
DH3	1.625	13.0	0.2113	0.4	-0.1888
DH5	2.883	10.0	0.2883	0.4	-0.1117
GFSK AFH Mode					
DH Packet	Pulse Width (msec)	Number of Pulses in 0.8 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
DH1	0.380	7.8	0.0295	0.4	-0.37055
DH3	1.625	3.3	0.0528	0.4	-0.34719
DH5	2.883	2.5	0.0721	0.4	-0.32793

NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD - DH1



PULSE WIDTH - DH5



8.5. OUTPUT POWER

LIMIT

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21dBm.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

8.5.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	5.76	21	-15.24
Middle	2441	6.00	21	-15.00
High	2480	6.20	21	-14.80
Worst		6.20		-14.80


8.5.2. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	5.84	21	-15.16
Middle	2441	6.19	21	-14.81
High	2480	6.38	21	-14.62
Worst		6.38		-14.62


8.5.3. OUTPUT POWER PLOTS

GFSK OUTPUT POWER

LOW CHANNEL




MID CHANNEL



8PSK OUTPUT POWER

LOW CHANNEL



8.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.7 dB (including 10 dB pad and 0.7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

8.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	5.5
Middle	2441	5.8
High	2480	6.0
Worst		6.0

8.6.2. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	3.1
Middle	2441	3.4
High	2480	3.6
Worst		3.6

8.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.

RESULTS


8.7.1. BASIC DATA RATE GFSK MODULATION

SPURIOUS EMISSIONS, LOW CHANNEL

LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL

MID CHANNEL BANDEDGE




MID CHANNEL SPURIOUS




SPURIOUS EMISSIONS, HIGH CHANNEL

HIGH CHANNEL BANDEDGE




HIGH CHANNEL SPURIOUS




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

LOW BANDEDGE WITH HOPPING ON




HIGH BANDEGE WITH HOPPING ON




8.7.2. ENHANCED DATA RATE 8PSK MODULATION

SPURIOUS EMISSIONS, LOW CHANNEL

LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL

MID CHANNEL BANDEDGE




MID CHANNEL SPURIOUS




SPURIOUS EMISSIONS, HIGH CHANNEL

HIGH CHANNEL BANDEDGE




HIGH CHANNEL SPURIOUS




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

LOW BANDEDGE WITH HOPPING ON



HIGH BANDEGE WITH HOPPING ON



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 1/T (on time) for average measurement. $GFSK = 1/T = 1 / 0.0038S = 260Hz$.

The spectrum from 1GHzHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz

9.2.1. BASIC DATA RATE GFSK MODULATION

RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.74	PK	32.1	-23.1	48.74	-	-	74	-25.26	6	110	H
2	* 2.368	42.61	PK	32	-23.1	51.51	-	-	74	-22.49	6	110	H
3	* 2.39	29.88	VB1T	32.1	-23.1	38.88	54	-15.12	-	-	6	110	H
4	* 2.368	30.66	VB1T	32	-23.1	39.56	54	-14.44	-	-	6	110	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.71	PK	32.1	-23.1	49.71	-	-	74	-24.29	121	164	V
2	* 2.378	42.88	PK	32.1	-23.1	51.88	-	-	74	-22.12	121	164	V
3	* 2.39	30.29	VB1T	32.1	-23.1	39.29	54	-14.71	-	-	121	164	V
4	* 2.337	30.9	VB1T	31.9	-23.1	39.7	54	-14.3	-	-	121	164	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	44.82	PK	32.3	-22.8	54.32	-	-	74	-19.68	5	154	H
2	* 2.484	47.96	PK	32.3	-22.8	57.46	-	-	74	-16.54	5	154	H
3	* 2.484	30.81	VB1T	32.3	-22.8	40.31	54	-13.69	-	-	5	154	H
4	* 2.484	31.1	VB1T	32.3	-22.8	40.6	54	-13.4	-	-	5	154	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.57	PK	32.3	-22.8	50.07	-	-	74	-23.93	304	248	V
3	* 2.484	30.83	VB1T	32.3	-22.8	40.33	54	-13.67	-	-	304	248	V
2	2.502	43.02	PK	32.3	-22.8	52.52	-	-	74	-21.48	304	248	V
4	2.523	31.05	VB1T	32.4	-22.8	40.65	54	-13.35	-	-	304	248	V


HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA


TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	* 2.71	32.82	PK	32.6	-22.8	42.62	-	-	74	-31.38	0-360	100	V
5	* 4.551	30.77	PK	34	-31.1	33.67	-	-	74	-40.33	0-360	200	V
1	1.935	32.78	PK	31.4	-23.2	40.98	-	-	-	-	0-360	100	H
2	6.334	30.41	PK	35.4	-29.1	36.71	-	-	-	-	0-360	100	H
6	9.608	31.32	PK	36.7	-25.3	42.72	-	-	-	-	0-360	200	V
3	10.397	28.53	PK	37.3	-25.4	40.43	-	-	-	-	0-360	200	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL




Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/F Itr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 4.685	30.74	PK	34.1	-30.7	34.14	-	-	74	-39.86	0-360	100	H
4	* 3.772	31.01	PK	33.2	-31.3	32.91	-	-	74	-41.09	0-360	100	V
1	1.715	33.2	PK	29.2	-23.4	39	-	-	-	-	0-360	100	H
5	7.133	30.01	PK	35.6	-28.1	37.51	-	-	-	-	0-360	100	V
3	8.768	29.85	PK	35.9	-27.4	38.35	-	-	-	-	0-360	200	H
6	9.764	30.42	PK	36.9	-26	41.32	-	-	-	-	0-360	200	V

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


HIGH CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 4.93	30.66	PK	34	-30.6	34.06	-	-	74	-39.94	0-360	100	H
1	2.057	33.35	PK	31.6	-23.2	41.75	-	-	-	-	0-360	200	H
4	3.322	32.02	PK	32.9	-31.3	33.62	-	-	-	-	0-360	100	V
5	6.167	31.74	PK	35.3	-29.8	37.24	-	-	-	-	0-360	200	V
3	6.981	32.1	PK	35.6	-29.6	38.1	-	-	-	-	0-360	100	H
6	9.92	29.68	PK	36.9	-25.6	40.98	-	-	-	-	0-360	200	V

9.2.2. ENHANCED DATA RATE 8PSK MODULATION RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.66	PK	32.1	-23.1	48.66	-	-	74	-25.34	6	113	H
2	* 2.339	42.59	PK	31.9	-23.1	51.39	-	-	74	-22.61	6	113	H
3	* 2.39	30.22	VB1T	32.1	-23.1	39.22	54	-14.78	-	-	6	113	H
4	* 2.382	30.79	VB1T	32.1	-23.1	39.79	54	-14.21	-	-	6	113	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.42	PK	32.1	-23.1	50.42	-	-	74	-23.58	116	250	V
2	* 2.376	43.26	PK	32	-23.1	52.16	-	-	74	-21.84	116	250	V
3	* 2.39	30.47	VB1T	32.1	-23.1	39.47	54	-14.53	-	-	116	250	V
4	* 2.368	31.2	VB1T	32	-23.1	40.1	54	-13.9	-	-	116	250	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.89	PK	32.3	-22.8	50.39	-	-	74	-23.61	35	109	H
2	* 2.484	46.04	PK	32.3	-22.8	55.54	-	-	74	-18.46	35	109	H
3	* 2.484	30.85	VB1T	32.3	-22.8	40.35	54	-13.65	-	-	35	109	H
4	2.532	30.95	VB1T	32.4	-22.7	40.65	54	-13.35	-	-	35	109	H


VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	39.97	PK	32.3	-22.8	49.47	-	-	74	-24.53	298	245	V
3	* 2.484	30.89	VB1T	32.3	-22.8	40.39	54	-13.61	-	-	298	245	V
4	* 2.484	31.15	VB1T	32.3	-22.8	40.65	54	-13.35	-	-	298	245	V
2	2.533	43.32	PK	32.4	-22.7	53.02	-	-	74	-20.98	298	245	V

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL




Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 3.81	31.22	PK	33.2	-31.2	33.22	-	-	74	-40.78	0-360	200	V
1	2.073	33.19	PK	31.6	-23.1	41.69	-	-	-	-	0-360	100	H
4	3.377	32.43	PK	32.9	-31.6	33.73	-	-	-	-	0-360	100	V
5	6.324	31.81	PK	35.4	-29.2	38.01	-	-	-	-	0-360	100	V
3	7.152	29.9	PK	35.6	-28.2	37.3	-	-	-	-	0-360	100	V
6	9.607	32.56	PK	36.7	-25.2	44.06	-	-	-	-	0-360	100	V

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL




Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 4.636	32.23	PK	34.1	-30.9	35.43	-	-	74	-38.57	0-360	200	H
4	* 3.536	31.74	PK	33	-31.1	33.64	-	-	74	-40.36	0-360	200	V
1	1.975	33.2	PK	31.5	-23.3	41.4	-	-	-	-	0-360	100	H
5	6.165	31.33	PK	35.3	-29.8	36.83	-	-	-	-	0-360	200	V
3	6.611	30.75	PK	35.6	-28.6	37.75	-	-	-	-	0-360	100	H
6	9.764	30.72	PK	36.9	-26	41.62	-	-	-	-	0-360	200	V

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA


TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.2	38.19	PK	29.2	-23.8	43.59	-	-	74	-30.41	0-360	100	H
3	* 3.967	32.26	PK	33.3	-31.1	34.46	-	-	74	-39.54	0-360	200	H
4	* 5.102	30.28	PK	34.2	-30.1	34.38	-	-	74	-39.62	0-360	100	V
2	2.087	32.98	PK	31.5	-23.1	41.38	-	-	-	-	0-360	200	H
5	7.913	30.48	PK	35.8	-27.6	38.68	-	-	-	-	0-360	200	V
6	9.919	30.38	PK	36.9	-25.6	41.68	-	-	-	-	0-360	200	V


9.3. WORST-CASE BELOW 1 GHz

GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T185 (dB/m)	Amp/Cbl (dB/m)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	34.25	44.51	PK	17.8	-27.5	34.81	40	-5.19	0-360	300	H
2	64.8075	50.24	PK	7.6	-27.2	30.64	40	-9.36	0-360	300	H
3	88.8838	48.25	PK	7.5	-26.9	28.85	43.52	-14.67	0-360	100	V
5	98.5525	46.46	PK	9.5	-26.8	29.16	43.52	-14.36	0-360	200	H
4	112.7475	42.78	PK	12.7	-26.7	28.78	43.52	-14.74	0-360	100	V
6	211.2	36	PK	10.3	-25.7	20.6	43.52	-22.92	0-360	100	H
8	248.9	37.02	PK	11.5	-25.3	23.22	46.02	-22.8	0-360	100	V
9	260.5	40.72	PK	12.2	-25.3	27.62	46.02	-18.4	0-360	100	V
7	556	34.15	PK	18.2	-25.8	26.55	46.02	-19.47	0-360	200	H
10	676	34.8	PK	19.8	-25.3	29.3	46.02	-16.72	0-360	100	V

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT




LINE 1 RESULTS

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.3705	49.2	PK	.4	0	49.6	58.5	-8.9	-	-
2	.3705	37.14	Av	.4	0	37.54	-	-	48.5	-10.96
3	1.86	51.33	PK	.2	.1	51.63	56	-4.37	-	-
4	1.86	35.65	Av	.2	.1	35.95	-	-	46	-10.05
5	16.395	41.89	PK	.3	.2	42.39	60	-17.61	-	-
6	16.395	21.86	Av	.3	.2	22.36	-	-	50	-27.64

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
7	.384	44.77	PK	.5	0	45.27	58.2	-12.93	-	-
8	.384	26.22	Av	.5	0	26.72	-	-	48.2	-21.48
9	1.581	40.67	PK	.2	.1	40.97	56	-15.03	-	-
10	1.581	22.83	Av	.2	.1	23.13	-	-	46	-22.87
11	12.048	34.77	PK	.2	.2	35.17	60	-24.83	-	-
12	12.048	16.61	Av	.2	.2	17.01	-	-	50	-32.99