

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Receipt: January 12, 2016**Date of Issue: January 22, 2016****Test Report No. HCT-E-1601-F039****HCT FRN: 0005866421****FCC ID :****ZNFH830**

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN, Bluetooth and RFID
Model Name: LG-H830
Additional Model Name: LGH830, H830
Test Port: Micro USB / Earphone Port
Date of Test: January 17, 2016 – January 19, 2016

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Jea-Woong Lee
Test Engineer
EMC Team
Certification Division

Reviewed By

Kyoung-Hee Yoon
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1601-F039	January 22, 2016	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	5
1.3 Test Facility	5
1.4 Tested System Details.....	6
1.5 Cable Description	7
1.6 Noise Suppression Parts on Cable. (I/O Cable)	7
2. DESCRIPTION OF TEST	8
3. PRELIMINARY TEST	11
3.1 Conducted Emission Test	11
3. 2 Radiated Emission Test	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
4.1 Conducted Emission Test	12
4.2 Radiated Emission Test	19
5. LIST OF TEST EQUIPMENT	21
6. CONCLUSION	22

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model	LG-H830
FCC ID	ZNFH830
Additional Model	LGH830, H830
EUT Type	Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN, Bluetooth and RFID
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 826.40 MHz to 846.60 MHz (WCDMA 850) 1712.4 MHz to 1752.6 MHz (WCDMA 1 700) 1 852.4 MHz to 1 907.6 MHz (WCDMA 1 900) 1 850.7 MHz to 1 909.3 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12)
RX Frequency	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 871.40 MHz to 891.60 MHz (WCDMA 850) 2 112.4 MHz to 2 152.6 MHz (WCDMA 1 700) 1 932.4 MHz to 1 987.6 MHz (WCDMA 1 900) 1 930.00 MHz to 1 990.00MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 729 MHz to 746 MHz (LTE B12)



1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
HCT FRN: 0005866421 Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
HCT FRN: 0005866421 Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-H830	LG	ZNFH830	Notebook PC, Earphone
USB cable	EAD63849201	Ningbo Broad	-	EUT, Notebook PC
USB cable	EAD63849203	KSD	-	EUT, Notebook PC
USB cable	EAD63849202	CRESYN	-	EUT, Notebook PC
Earphone	EAB62910501	I-SOUND	-	EUT
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	PPP009D	DELTA Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	TL-WR747N	TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	-	Gateway
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	16 GB	Samsung	-	EUT



1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)2.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	EUT End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V/m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



3. PRELIMINARY TEST

3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

3. 2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY


4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	CRESYN(EAD63849202) *NOTE: The worst-case emissions are reported.
Kind of Test Site	Shielded Room
Temperature	21.9 °C
Relative Humidity	30.9 %
Test Date	January 17, 2016

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

**Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)**




QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	48.3	9.000	L1	9.7	17.7	66.0
0.156000	46.8	9.000	L1	9.6	18.9	65.7
0.166000	45.1	9.000	L1	9.6	20.1	65.2
0.174000	43.7	9.000	L1	9.6	21.1	64.8
0.196000	49.7	9.000	L1	9.6	14.1	63.8
0.200000	49.4	9.000	L1	9.6	14.2	63.6
3.654000	37.3	9.000	L1	9.8	18.7	56.0
3.872000	36.2	9.000	L1	9.8	19.8	56.0
3.892000	36.8	9.000	L1	9.8	19.2	56.0
3.972000	36.8	9.000	L1	9.8	19.2	56.0
4.004000	36.0	9.000	L1	9.8	20.0	56.0
4.230000	35.8	9.000	L1	9.8	20.2	56.0
20.446000	33.7	9.000	L1	10.3	26.3	60.0
20.576000	33.6	9.000	L1	10.3	26.4	60.0
20.788000	33.7	9.000	L1	10.3	26.3	60.0
20.860000	33.4	9.000	L1	10.3	26.6	60.0
21.288000	32.6	9.000	L1	10.3	27.4	60.0
22.418000	33.4	9.000	L1	10.3	26.6	60.0



CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.196000	32.2	9.000	L1	9.6	21.6	53.8
0.198000	32.5	9.000	L1	9.6	21.2	53.7
0.204000	32.1	9.000	L1	9.6	21.3	53.4
0.212000	27.1	9.000	L1	9.6	26.0	53.1
0.260000	25.9	9.000	L1	9.6	25.5	51.4
0.262000	26.3	9.000	L1	9.6	25.1	51.4
3.606000	28.4	9.000	L1	9.8	17.6	46.0
3.654000	28.3	9.000	L1	9.8	17.7	46.0
3.676000	28.4	9.000	L1	9.8	17.6	46.0
3.958000	27.7	9.000	L1	9.8	18.3	46.0
3.972000	27.8	9.000	L1	9.8	18.2	46.0
4.740000	27.5	9.000	L1	9.9	18.5	46.0
20.446000	26.7	9.000	L1	10.3	23.3	50.0
20.860000	25.3	9.000	L1	10.3	24.7	50.0
21.210000	24.8	9.000	L1	10.3	25.2	50.0
21.218000	26.1	9.000	L1	10.3	23.9	50.0
21.288000	25.8	9.000	L1	10.3	24.2	50.0
22.416000	25.4	9.000	L1	10.3	24.6	50.0

**Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)**



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	48.5	9.000	N	9.6	17.5	66.0
0.162000	46.0	9.000	N	9.6	19.4	65.4
0.168000	45.1	9.000	N	9.6	20.0	65.1
0.176000	43.7	9.000	N	9.6	21.0	64.7
0.186000	42.6	9.000	N	9.6	21.6	64.2
0.198000	49.4	9.000	N	9.6	14.3	63.7
3.962000	37.0	9.000	N	9.8	19.0	56.0
4.032000	37.0	9.000	N	9.8	19.0	56.0
4.102000	37.7	9.000	N	9.8	18.4	56.0
4.252000	35.2	9.000	N	9.8	20.8	56.0
4.348000	34.7	9.000	N	9.8	21.3	56.0
4.526000	36.4	9.000	N	9.8	19.6	56.0
20.368000	33.2	9.000	N	10.3	26.8	60.0
20.508000	33.9	9.000	N	10.3	26.1	60.0
20.722000	34.2	9.000	N	10.3	25.8	60.0
20.794000	34.2	9.000	N	10.3	25.8	60.0
22.276000	33.1	9.000	N	10.3	26.9	60.0
22.412000	32.9	9.000	N	10.3	27.1	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.194000	30.8	9.000	N	9.6	23.1	53.9
0.202000	32.2	9.000	N	9.6	21.3	53.5
0.210000	29.5	9.000	N	9.6	23.7	53.2
0.260000	25.8	9.000	N	9.6	25.6	51.4
0.268000	25.9	9.000	N	9.6	25.3	51.2
0.276000	24.8	9.000	N	9.6	26.1	50.9
3.676000	28.5	9.000	N	9.8	17.5	46.0
3.750000	28.5	9.000	N	9.8	17.5	46.0
3.892000	28.1	9.000	N	9.8	17.9	46.0
3.962000	27.8	9.000	N	9.8	18.2	46.0
4.032000	27.9	9.000	N	9.8	18.1	46.0
4.348000	26.9	9.000	N	9.8	19.2	46.0
20.368000	26.5	9.000	N	10.3	23.5	50.0
20.508000	26.8	9.000	N	10.3	23.2	50.0
20.722000	26.2	9.000	N	10.3	23.8	50.0
20.794000	26.4	9.000	N	10.3	23.6	50.0
21.086000	25.5	9.000	N	10.3	24.5	50.0
22.418000	25.4	9.000	N	10.3	24.6	50.0



4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	Ningbo Broad (EAD63849201) *NOTE: The worst-case emissions are reported.
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.6 °C
Relative Humidity	31.7 %
Test Date	January 19, 2016

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)
55.910541	30.8	100.0	V	120.0	15.7	9.2	40.0
85.068858	33.0	250.0	H	87.0	11.7	7.0	40.0
802.003447	36.5	100.0	H	210.0	28.4	9.5	46.0
849.960641	35.6	193.0	H	298.0	29.1	10.4	46.0
949.923837	36.7	100.0	H	300.0	30.3	9.3	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	2.15 GHz
Testing Frequency Range	1 GHz to 10.75 GHz
Operation Mode	Data Communication mode
USB Cable Type	CRESYN(EAD63849202) *NOTE: The worst-case emissions are reported.
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.6 °C
Relative Humidity	31.7 %
Test Date	January 19, 2016

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1332.314630	48.7	150.0	V	199.0	-9.8	25.3	74.0
1400.050100	49.0	100.0	H	342.0	-9.6	25.0	74.0
1996.643287	53.2	100.0	V	233.0	-8.4	20.8	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1332.314630	31.2	150.0	V	199.0	-9.8	22.8	54.0
1400.050100	46.5	100.0	H	342.0	-9.6	7.6	54.0
1996.643287	36.6	100.0	V	233.0	-8.4	17.4	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	12.28.2015
☒ LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	12.28.2015
☒ LISN	Rohde & Schwarz	ENV216	100073	1 year	12.28.2015
☒ Software	Rohde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.01.2015
☒ Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17.2014
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Turn Table	EMCO	1060-2M	-	N/A	-
☒ Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.05.2015
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.01.2015
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Turn Table	EMCO	1060-2M	-	N/A	-
☒ Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐ Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.06.2015
☒ Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.15.2015
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.07.2014
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.05.2015
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32	-	-	-



6. CONCLUSION

The data collected shows that the **EUT Type: Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN, Bluetooth and RFID, Model: LG-H830, FCC ID: ZNFH830** complies with §15.107 and §15.109 of the FCC rules.