



SAR EVALUATION REPORT

Applicant Name:
 LG Electronics MobileComm U.S.A., Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 08/08/16 - 08/18/16
Test Site/Location:
 PCTEST Lab, Columbia, MD, USA
Document Serial No.:
 0Y1608121352-R1.ZNF

FCC ID: ZNFH910

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A., INC.

DUT Type: Portable Handset
Application Type: Class II Permissive Change
FCC Rule Part(s): CFR §2.1093
Model(s): LG-H910, LGH910, H910, LG-H915, LGH915, H915
Permissive Change(s): See FCC Change Document

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)	10 gm Phablet (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.39	0.51	0.73	N/A
PCE	UMTS 850	826.40 - 846.60 MHz	0.74	0.37	0.51	N/A
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.21	0.57	0.67	N/A
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.16	0.37	0.37	N/A
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.29	0.73	0.73	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	0.83	0.34	0.43	N/A
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.78	0.40	0.56	N/A
PCE	LTE Band 66 (AWS)	1712.5 - 1777.5 MHz	0.33	0.37	0.72	N/A
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.34	0.92	0.92	N/A
PCE	LTE Band 30	2307.5 - 2312.5 MHz	0.20	0.54	0.60	N/A
PCE	LTE Band 7	2502.5 - 2567.5 MHz	0.13	0.67	1.13	N/A
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.44	0.29	0.36	N/A
NII	U-NII-1	5180 - 5240 MHz	N/A	N/A	0.21	N/A
NII	U-NII-2A	5260 - 5320 MHz	0.31	<0.1	N/A	0.60
NII	U-NII-2C	5500 - 5720 MHz	0.42	< 0.1	N/A	0.95
NII	U-NII-3	5745 - 5825 MHz	0.37	< 0.1	0.14	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A	<0.1	N/A	< 0.1
Simultaneous SAR per KDB 690783 D01v01r03:			1.54	1.44	1.59	1.31

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

Note: This revised Test Report (S/N: 0Y1608121352-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
 President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 1 of 82

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	12
3	INTRODUCTION	13
4	DOSIMETRIC ASSESSMENT	14
5	DEFINITION OF REFERENCE POINTS	15
6	TEST CONFIGURATION POSITIONS	16
7	RF EXPOSURE LIMITS	20
8	FCC MEASUREMENT PROCEDURES.....	21
9	RF CONDUCTED POWERS	27
10	SYSTEM VERIFICATION.....	48
11	SAR DATA SUMMARY	52
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	68
13	SAR MEASUREMENT VARIABILITY	75
14	ADDITIONAL TUNER TESTING PER FCC GUIDANCE.....	76
15	EQUIPMENT LIST.....	78
16	MEASUREMENT UNCERTAINTIES.....	79
17	CONCLUSION.....	80
18	REFERENCES	81
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 2 of 82	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1712.5 - 1777.5 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 30	Voice/Data	2307.5 - 2312.5 MHz
LTE Band 7	Voice/Data	2502.5 - 2567.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz

1.2 Power Reduction for SAR

This device uses a fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description. The reduced powers for the power reduction mechanism were confirmed via conducted power measurements at the RF port (See Section 9).

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 3 of 82	

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum PCE Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.7	33.7	32.2	29.7	28.7	27.2	27.2	26.7	26.7
	Nominal	33.2	33.2	31.7	29.2	28.2	26.7	26.7	26.2	26.2
GSM/GPRS/EDGE 1900	Maximum	30.7	30.7	29.2	27.2	25.7	26.2	26.2	25.7	25.7
	Nominal	30.2	30.2	28.7	26.7	25.2	25.7	25.7	25.2	25.2

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	24.7	24.7	24.7
	Nominal	24.2	24.2	24.2
UMTS Band 4 (1750 MHz)	Maximum	25.0	25.0	25.0
	Nominal	24.5	24.5	24.5
UMTS Band 2 (1900 MHz)	Maximum	25.0	25.0	25.0
	Nominal	24.5	24.5	24.5

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	25.0
	Nominal	24.5
LTE Band 17	Maximum	25.0
	Nominal	24.5
LTE Band 5 (Cell)	Maximum	25.0
	Nominal	24.5
LTE Band 66 (AWS)	Maximum	25.0
	Nominal	24.5
LTE Band 4 (AWS)	Maximum	25.0
	Nominal	24.5
LTE Band 2 (PCS)	Maximum	25.2
	Nominal	24.7
LTE Band 30	Maximum	23.7
	Nominal	23.2
LTE Band 7	Maximum	23.7
	Nominal	23.2

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 4 of 82	

1.3.1 Maximum WLAN/BT Power

This device only supports SISO operations on the secondary antenna for 802.11b. The below 802.11 a/g/n/ac secondary antenna powers are included to represent the maximum allowed output power the device can operate in CDD or MIMO SDM modes for simultaneous transmission evaluation purposes.

Mode / Band		Modulated Average - Single Tx Chain (Primary) (dBm)			Mode / Band		Modulated Average - Single Tx Chain (Secondary) (dBm)		
		Ch. 1-3	Ch. 4-8	Ch. 9-11			Ch. 1-3	Ch. 4-8	Ch. 9-11
IEEE 802.11b (2.4 GHz)	Maximum	19.0	20.0	18.0	IEEE 802.11b (2.4 GHz)	Maximum	19.5	20.0	19.0
	Nominal	18.0	19.0	17.0		Nominal	18.5	19.0	18.0
IEEE 802.11g (2.4 GHz)	Maximum	14.5	15.5	13.5	IEEE 802.11g (2.4 GHz)	Maximum	15.0	15.5	14.5
	Nominal	13.5	14.5	12.5		Nominal	14.0	14.5	13.5
IEEE 802.11n (2.4 GHz)	Maximum	14.5	15.5	13.5	IEEE 802.11n (2.4 GHz)	Maximum	15.0	15.5	14.5
	Nominal	13.5	14.5	12.5		Nominal	14.0	14.5	13.5
IEEE 802.11ac (2.4 GHz)	Maximum	14.5	15.5	13.5	IEEE 802.11ac (2.4 GHz)	Maximum	15.0	15.5	14.5
	Nominal	13.5	14.5	12.5		Nominal	14.0	14.5	13.5

Mode / Band		Modulated Average - MIMO (dBm)		
		Ch. 1-3	Ch. 4-8	Ch. 9-11
IEEE 802.11g (2.4 GHz)	Maximum	17.8	18.5	17.0
	Nominal	16.8	17.5	16.0
IEEE 802.11n (2.4 GHz)	Maximum	17.8	18.5	17.0
	Nominal	16.8	17.5	16.0
IEEE 802.11ac (2.4 GHz)	Maximum	17.8	18.5	17.0
	Nominal	16.8	17.5	16.0

Mode / Band		Modulated Average - Single Tx Chain (Primary) (dBm)			
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth
			Ch. 38, 62, 102	Ch. 46, 54, 110, 134, 142, 151, 159	Ch. 42, 58, 106
IEEE 802.11a (5 GHz)	Maximum	15.0			
	Nominal	14.0			
IEEE 802.11n (5 GHz)	Maximum	15.0	12.0	14.0	
	Nominal	14.0	11.0	13.0	
IEEE 802.11ac (5 GHz)	Maximum	15.0	12.0	14.0	11.5
	Nominal	14.0	11.0	13.0	10.5

Mode / Band		Modulated Average - Single Tx Chain (Secondary) (dBm)			
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth
			Ch. 38, 62, 102	Ch. 46, 54, 110, 134, 142, 151, 159	Ch. 42, 58, 106
IEEE 802.11a (5 GHz)	Maximum	14.0			
	Nominal	13.0			
IEEE 802.11n (5 GHz)	Maximum	14.0	11.0	13.0	
	Nominal	13.0	10.0	12.0	
IEEE 802.11ac (5 GHz)	Maximum	14.0	11.0	13.0	10.5
	Nominal	13.0	10.0	12.0	9.5

Mode / Band		Modulated Average - MIMO (dBm)			
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth
			Ch. 38, 62, 102	Ch. 46, 54, 110, 134, 142, 151, 159	Ch. 42, 58, 106
IEEE 802.11a (5 GHz)	Maximum	17.5			
	Nominal	16.5			
IEEE 802.11n (5 GHz)	Maximum	17.5	14.5	16.5	
	Nominal	16.5	13.5	15.5	
IEEE 802.11ac (5 GHz)	Maximum	17.5	14.5	16.5	14.0
	Nominal	16.5	13.5	15.5	13.0

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 5 of 82

Mode / Band		Modulated Average (dBm)
Bluetooth (1 Mbps)	Maximum	13.0
	Nominal	12.0
Bluetooth (2 Mbps)	Maximum	11.0
	Nominal	10.0
Bluetooth (3 Mbps)	Maximum	11.0
	Nominal	10.0
Bluetooth LE	Maximum	6.0
	Nominal	5.0

1.3.2 Reduced WLAN Power

This device only supports SISO operations on the secondary antenna for 802.11b. The below 802.11 a/g/n/ac secondary antenna powers are included to represent the maximum allowed output power the device can operate in CDD or MIMO SDM modes for simultaneous transmission evaluation purposes.

Mode / Band		Modulated Average - Single Tx Chain (Primary) (dBm)	Mode / Band		Modulated Average - Single Tx Chain (Secondary) (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	12.5	IEEE 802.11b (2.4 GHz)	Maximum	5.5
	Nominal	11.5		Nominal	4.5
IEEE 802.11g (2.4 GHz)	Maximum	12.5	IEEE 802.11g (2.4 GHz)	Maximum	5.5
	Nominal	11.5		Nominal	4.5
IEEE 802.11n (2.4 GHz)	Maximum	12.5	IEEE 802.11n (2.4 GHz)	Maximum	5.5
	Nominal	11.5		Nominal	4.5
IEEE 802.11ac (2.4 GHz)	Maximum	12.5	IEEE 802.11ac (2.4 GHz)	Maximum	5.5
	Nominal	11.5		Nominal	4.5

Mode / Band		Modulated Average - MIMO (dBm)
IEEE 802.11g (2.4 GHz)	Maximum	13.3
	Nominal	12.3
IEEE 802.11n (2.4 GHz)	Maximum	13.3
	Nominal	12.3
IEEE 802.11ac (2.4 GHz)	Maximum	13.3
	Nominal	12.3

Mode / Band		Modulated Average - Single Tx Chain (Primary) (dBm)				
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth	
			Ch. 38, 62, 102	Ch. 46, 54, 110, 134, 142, 151, 159	Ch. 42, 58, 106	Ch. 138, 155
IEEE 802.11a (5 GHz)	Maximum	13.0				
	Nominal	12.0				
IEEE 802.11n (5 GHz)	Maximum	13.0	12.0	13.0		
	Nominal	12.0	11.0	12.0		
IEEE 802.11ac (5 GHz)	Maximum	13.0	12.0	13.0	11.5	13.0
	Nominal	12.0	11.0	12.0	10.5	12.0

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 6 of 82

Mode / Band		Modulated Average - Single Tx Chain (Secondary) (dBm)				
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth	
IEEE 802.11a (5 GHz)	Maximum	5.5				
	Nominal	4.5				
IEEE 802.11n (5 GHz)	Maximum	5.5	5.5			
	Nominal	4.5	4.5			
IEEE 802.11ac (5 GHz)	Maximum	5.5	5.5		5.5	
	Nominal	4.5	4.5		4.5	
Mode / Band		Modulated Average - MIMO (dBm)				
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth	
			Ch. 38, 62, 102	Ch. 46, 54, 110, 134, 142, 151, 159	Ch. 42, 58, 106	Ch. 138, 155
IEEE 802.11a (5 GHz)	Maximum	13.7				
	Nominal	12.7				
IEEE 802.11n (5 GHz)	Maximum	13.7	12.9	13.7		
	Nominal	12.7	11.9	12.7		
IEEE 802.11ac (5 GHz)	Maximum	13.7	12.9	13.7	12.5	13.7
	Nominal	12.7	11.9	12.7	11.5	12.7

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”

**Table 1-1
Device Edges/Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850 Ant 1	Yes	Yes	No	Yes	Yes	Yes
UMTS 850 Ant 1	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750 Ant 2	Yes	Yes	No	Yes	No	Yes
GPRS 1900 Ant 2	Yes	Yes	No	Yes	No	Yes
UMTS 1900 Ant 2	Yes	Yes	No	Yes	No	Yes
LTE Band 12 Ant 1	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell) Ant 1	Yes	Yes	No	Yes	Yes	Yes
LTE Band 66 (AWS) Ant 2	Yes	Yes	No	Yes	No	Yes
LTE Band 2 (PCS) Ant 2	Yes	Yes	No	Yes	No	Yes
LTE Band 30 Ant 1	Yes	Yes	No	Yes	Yes	Yes
LTE Band 7 Ant 1	Yes	Yes	No	Yes	Yes	Yes
UMTS 850 Ant 3	Yes	Yes	Yes	No	Yes	Yes
LTE Band 12 Ant 3	Yes	Yes	Yes	No	Yes	Yes
LTE Band 5 (Cell) Ant 3	Yes	Yes	Yes	No	Yes	Yes
2.4 GHz WLAN Primary	Yes	Yes	Yes	No	Yes	No
2.4 GHz WLAN Secondary	Yes	Yes	Yes	No	Yes	No
5 GHz WLAN Primary	Yes	Yes	Yes	No	Yes	No
5 GHz WLAN Secondary	Yes	Yes	Yes	No	Yes	No
Bluetooth	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 7 of 82

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	GSM voice + 2.4 GHz W-FI	Yes	Yes	N/A	Yes	
2	GSM voice + 5 GHz W-FI	Yes	Yes	N/A	Yes	
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes	
4	GSM voice + 2.4 GHz W-FI MIMO	Yes	Yes	N/A	Yes	
5	GSM voice + 5 GHz W-FI MIMO	Yes	Yes	N/A	Yes	
6	UMTS + 2.4 GHz W-FI	Yes	Yes	Yes	Yes	
7	UMTS + 5 GHz W-FI	Yes	Yes	Yes	Yes	
8	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes	
9	UMTS + 2.4 GHz W-FI MIMO	Yes	Yes	Yes	Yes	
10	UMTS + 5 GHz W-FI MIMO	Yes	Yes	Yes	Yes	
11	LTE + 2.4 GHz W-FI	Yes	Yes	Yes	Yes	
12	LTE + 5 GHz W-FI	Yes	Yes	Yes	Yes	
13	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes	
14	LTE + 2.4 GHz W-FI MIMO	Yes	Yes	Yes	Yes	
15	LTE + 5 GHz W-FI MIMO	Yes	Yes	Yes	Yes	
16	GPRS/EDGE + 2.4 GHz W-FI	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
17	GPRS/EDGE + 5 GHz W-FI	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
18	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	Yes*	N/A	Yes	*-Pre-installed VOIP applications are considered.
19	GPRS/EDGE + 2.4 GHz W-FI MIMO	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
20	GPRS/EDGE + 5 GHz W-FI MIMO	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 8 of 82

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. 2.4 GHz WLAN and 5 GHz WLAN that share the same antenna path cannot transmit simultaneously.
3. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
4. Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call only. Simultaneous transmission scenarios involving WIFI direct are listed in the above table.
5. 5 GHz Wireless Router is only supported for the U-NII-1 and U-NII-3 by S/W, therefore U-NII-2A and U-NII-2C were not evaluated for wireless router conditions.
6. This device supports 2x2 MIMO Tx for WLAN 802.11 a/g/n/ac when both primary and secondary WLAN antennas transmit together. Independent (SISO) WLAN transmission from the secondary WLAN antenna is limited to 2.4 GHz 802.11b mode only.
7. This device supports VOLTE and VoWIFI.

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-1 & U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, Head and Bodyworn SAR are not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02. 10g SAR measurements analysis applies a factor of 2.5 to the procedures outlines above.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-2A & U-NII-2C WIFI, only 2.4 GHz, U-NII-1 and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) Band gap channels are supported

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4 GHz U-NII-1 and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg.

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 9 of 82

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

This device supports both LTE Band 12 and LTE Band 17. Since the supported frequency span for LTE Band 17 falls completely within the supported frequency span for LTE Band 12, LTE Band 17 target power is less than or equal to LTE Band 12 target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE Band 12.

This device supports both LTE Band 66 and LTE Band 4. Since the supported frequency span for LTE Band 4 falls completely within the supported frequency span for LTE Band 66, LTE Band 4 target power is less than or equal to LTE Band 66 target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE Band 66.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was not evaluated for licensed technologies since wireless router 1g SAR was < 1.2 W/kg for these modes.

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 10 of 82

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number	Phablet Serial Number
GSM/GPRS/EDGE 850 Ant 1	09403	09403	09403	-
UMTS 850 Ant 1	09403	09403	09403	-
UMTS 1750 Ant 2	09403	09403	09403	-
GSM/GPRS/EDGE 1900 Ant 2	09395	09403	09403	-
UMTS 1900 Ant 2	09395	09395	09395	-
LTE Band 12 Ant 1	09346	09379	09379	-
LTE Band 5 (Cell) Ant 1	09346	09346	09346	-
LTE Band 66 (AWS) Ant 2	09346	09346	09346	-
LTE Band 2 (PCS) Ant 2	09353	09379	09379	-
LTE Band 30 Ant 1	09346	09346	09346	-
LTE Band 7 Ant 1	09346	09346	09346	-
UMTS 850 Ant 3	09403	09403	09403	-
LTE Band 12 Ant 3	09346	09379	09379	-
LTE Band 5 (Cell) Ant 3	09361	09346	09346	-
2.4 GHz WLAN Primary/ Secondary	09486	09486	09486	-
5 GHz WLAN Primary/ Secondary	09486	09486	09486	09486
Bluetooth	N/A	09486	N/A	09486

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 11 of 82

2

LTE INFORMATION

LTE Information			
FCC ID	ZNFH910		
Form Factor	Portable Handset		
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)		
	LTE Band 17 (706.5 - 713.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 66 (AWS) (1712.5 - 1777.5 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
	LTE Band 30 (2307.5 - 2312.5 MHz)		
Channel Bandwidths	LTE Band 7 (2502.5 - 2567.5 MHz)		
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 17: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 66 (AWS): 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	LTE Band 30: 5 MHz, 10 MHz		
	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	Low	Mid	High
LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)	1745 (132322)	1777.5 (132647)
LTE Band 66 (AWS): 10 MHz	1715 (132022)	1745 (132322)	1775 (132622)
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)	1745 (132322)	1772.5 (132597)
LTE Band 66 (AWS): 20 MHz	1720 (132072)	1745 (132322)	1770 (132572)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
LTE Band 30: 5 MHz	2307.5 (27685)	2310 (27710)	2312.5 (27735)
LTE Band 30: 10 MHz	N/A	2310 (27710)	N/A
LTE Band 7: 5 MHz	2502.5 (20775)	2535 (21100)	2567.5 (21425)
LTE Band 7: 10 MHz	2505 (20800)	2535 (21100)	2565 (21400)
LTE Band 7: 15 MHz	2507.5 (20825)	2535 (21100)	2562.5 (21375)
LTE Band 7: 20 MHz	2510 (20850)	2535 (21100)	2560 (21350)
UE Category	11		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations		
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 3 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICN, WIF1 Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.		

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 12 of 82	

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1
SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 13 of 82

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASy manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.



**Figure 4-1
Sample SAR Area
Scan**

**Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04***

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{area}, \Delta y_{area}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{zoom}, \Delta y_{zoom}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFH910	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 14 of 82

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 15 of 82

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 16 of 82




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 17 of 82

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person’s face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user’s body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 18 of 82	

6.8 Phablet Configurations

For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna ≤ 25 mm from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 19 of 82	

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 20 of 82

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 21 of 82

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 22 of 82

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 23 of 82

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 24 of 82

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6).

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 25 of 82

8.6.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is <1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 26 of 82

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

Maximum Burst-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	33.57	33.41	32.13	29.62	28.61	27.15	27.19	26.56	26.51
	190	33.41	33.33	32.14	29.66	28.59	27.09	27.13	26.45	26.32
	251	33.47	33.54	32.20	29.64	28.65	26.95	27.07	26.52	26.38
GSM 1900	512	30.56	30.56	29.08	27.05	25.57	26.04	26.11	25.60	25.67
	661	30.54	30.41	29.06	26.96	25.44	26.01	26.05	25.64	25.70
	810	30.45	30.39	29.09	27.03	25.32	26.06	25.93	25.60	25.66
Calculated Maximum Frame-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	24.54	24.38	26.11	25.36	25.60	18.12	21.17	22.30	23.50
	190	24.38	24.30	26.12	25.40	25.58	18.06	21.11	22.19	23.31
	251	24.44	24.51	26.18	25.38	25.64	17.92	21.05	22.26	23.37
GSM 1900	512	21.53	21.53	23.06	22.79	22.56	17.01	20.09	21.34	22.66
	661	21.51	21.38	23.04	22.70	22.43	16.98	20.03	21.38	22.69
	810	21.42	21.36	23.07	22.77	22.31	17.03	19.91	21.34	22.65
GSM 850	Frame	24.17	24.17	25.68	24.94	25.19	17.67	20.68	21.94	23.19
GSM 1900	Avg. Targets:	21.17	21.17	22.68	22.44	22.19	16.67	19.68	20.94	22.19

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 12 (Max 4 Tx uplink slots)
EDGE Multislot class: 12 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A




Figure 9-1
Power Measurement Setup

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 27 of 82	

9.2 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.63	24.66	24.46	24.70	24.73	24.90	24.85	24.89	24.90	-
99		12.2 kbps AMR	24.57	24.65	24.62	24.72	24.73	24.87	24.83	24.76	24.98	-
6	HSDPA	Subtest 1	24.51	24.66	24.25	24.65	24.71	24.81	24.83	24.72	24.88	0
6		Subtest 2	24.48	24.65	24.48	24.67	24.66	24.75	24.57	24.74	24.96	0
6		Subtest 3	23.90	24.11	23.98	24.08	24.17	24.39	24.08	24.39	24.46	0.5
6		Subtest 4	23.93	24.13	23.95	24.20	24.16	24.38	24.25	24.22	24.33	0.5
6	HSUPA	Subtest 1	23.79	23.74	23.86	24.45	24.27	24.35	24.74	24.77	24.65	0
6		Subtest 2	22.41	22.59	22.38	22.66	22.74	22.90	22.78	22.75	22.99	2
6		Subtest 3	23.32	23.50	23.43	23.64	23.80	23.78	23.93	23.66	23.79	1
6		Subtest 4	22.40	22.62	22.35	22.66	22.72	22.86	22.94	23.00	22.65	2
6		Subtest 5	23.72	23.84	23.73	24.32	24.29	24.45	24.69	24.94	24.97	0

This device does not support DC-HSDPA.




Figure 9-2
Power Measurement Setup

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 28 of 82	

9.3 LTE Conducted Powers

9.3.1 LTE Band 12

**Table 9-1
LTE Band 12 Conducted Powers - 10 MHz Bandwidth**

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.92	0	0
	1	25	24.94		0
	1	49	24.99		0
	25	0	23.88	0-1	1
	25	12	23.79		1
	25	25	23.79		1
	50	0	23.82		1
16QAM	1	0	23.96	0-1	1
	1	25	23.94		1
	1	49	23.93		1
	25	0	22.90	0-2	2
	25	12	22.87		2
	25	25	22.86		2
	50	0	22.85		2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-2
LTE Band 12 Conducted Powers - 5 MHz Bandwidth**

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.00	24.91	24.95	0	0
	1	12	24.92	24.98	24.80		0
	1	24	24.85	24.93	24.83		0
	12	0	23.68	23.79	23.78	0-1	1
	12	6	23.71	23.74	23.84		1
	12	13	23.63	23.75	23.80		1
	25	0	23.65	23.71	23.76		1
16QAM	1	0	23.95	23.92	23.74	0-1	1
	1	12	23.96	23.94	23.92		1
	1	24	23.94	23.96	23.74		1
	12	0	22.71	22.80	22.78	0-2	2
	12	6	22.72	22.79	22.81		2
	12	13	22.71	22.78	22.75		2
	25	0	22.66	22.79	22.71		2

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 29 of 82

**Table 9-3
LTE Band 12 Conducted Powers - 3 MHz Bandwidth**

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.91	24.95	24.90	0	0
	1	7	24.98	24.80	24.86		0
	1	14	24.93	24.83	24.74		0
	8	0	23.79	23.78	23.85	0-1	1
	8	4	23.74	23.84	23.80		1
	8	7	23.75	23.80	23.74		1
	15	0	23.71	23.76	23.83		1
16QAM	1	0	23.92	23.74	23.88	0-1	1
	1	7	23.94	23.92	23.88		1
	1	14	23.96	23.74	23.84		1
	8	0	22.80	22.78	22.82	0-2	2
	8	4	22.79	22.81	22.78		2
	8	7	22.78	22.75	22.75		2
	15	0	22.79	22.71	22.80		2

**Table 9-4
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth**

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.90	24.68	24.84	0	0
	1	2	24.92	24.75	24.76		0
	1	5	24.83	24.66	24.59		0
	3	0	24.80	24.94	24.96		0
	3	2	24.99	25.00	24.73		0
	3	3	24.93	24.83	24.76	0	
	6	0	23.67	23.63	23.74	0-1	1
16QAM	1	0	23.89	23.75	23.62	0-1	1
	1	2	23.92	23.84	23.79		1
	1	5	23.94	23.72	23.67		1
	3	0	23.81	23.78	23.87		1
	3	2	23.83	23.91	23.97		1
	3	3	23.95	23.75	23.95	1	
	6	0	22.76	22.53	22.75	0-2	2

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 30 of 82

9.3.2

LTE Band 5 (Cell)

Table 9-5
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.91	0	0
	1	25	25.00		0
	1	49	24.90		0
	25	0	23.88	0-1	1
	25	12	23.85		1
	25	25	23.87		1
	50	0	23.84		1
16QAM	1	0	23.97	0-1	1
	1	25	23.77		1
	1	49	23.97		1
	25	0	22.92	0-2	2
	25	12	22.86		2
	25	25	22.88		2
	50	0	22.89		2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-6
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.91	24.94	24.94	0	0
	1	12	24.99	24.90	24.96		0
	1	24	24.93	24.98	24.95		0
	12	0	23.79	23.69	23.79	0-1	1
	12	6	23.73	23.74	23.79		1
	12	13	23.78	23.75	23.77		1
	25	0	23.74	23.70	23.66		1
16QAM	1	0	23.76	23.94	24.00	0-1	1
	1	12	23.85	23.96	23.82		1
	1	24	23.85	23.98	23.90		1
	12	0	22.88	22.72	22.82	0-2	2
	12	6	22.83	22.82	22.82		2
	12	13	22.86	22.77	22.79		2
	25	0	22.72	22.75	22.70		2

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 31 of 82

Table 9-7
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.96	24.97	24.73	0	0
	1	7	24.97	24.95	24.75		0
	1	14	24.85	24.98	24.72		0
	8	0	23.89	23.70	23.77	0-1	1
	8	4	23.87	23.75	23.70		1
	8	7	23.96	23.73	23.71		1
	15	0	23.95	23.77	23.73		1
16QAM	1	0	24.00	23.75	23.79	0-1	1
	1	7	23.95	23.85	23.73		1
	1	14	23.96	23.89	23.83		1
	8	0	22.99	22.66	22.77	0-2	2
	8	4	22.94	22.75	22.72		2
	8	7	22.85	22.71	22.61		2
	15	0	22.97	22.70	22.71		2

Table 9-8
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.93	24.94	24.73	0	0
	1	2	24.97	24.95	24.88		0
	1	5	24.95	24.90	24.80		0
	3	0	24.82	24.89	24.92		0
	3	2	24.92	24.90	24.75		0
	3	3	24.83	24.80	24.80		0
	6	0	23.78	23.70	23.84	0-1	1
16QAM	1	0	23.94	23.74	23.68	0-1	1
	1	2	23.92	23.85	23.67		1
	1	5	23.93	23.69	23.67		1
	3	0	23.91	23.80	23.91		1
	3	2	23.95	23.85	23.80		1
	3	3	23.92	23.75	23.78		1
	6	0	22.93	22.64	22.70	0-2	2

FCC ID: ZNFH910	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 32 of 82

9.3.3

LTE Band 66 (AWS)

Table 9-9
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.96	24.93	25.00	0	0
	1	50	24.90	24.90	24.91		0
	1	99	24.92	24.87	24.95		0
	50	0	23.88	23.95	23.88	0-1	1
	50	25	23.96	23.97	23.84		1
	50	50	23.71	23.98	23.72		1
16QAM	100	0	23.85	23.92	23.82	0-1	1
	1	0	23.92	23.95	23.91		1
	1	50	23.90	24.00	23.99		1
	1	99	23.91	24.00	24.00	0-2	2
	50	0	22.90	22.87	22.91		2
	50	25	22.96	23.00	22.89		2
	50	50	22.67	22.94	22.74	2	
	100	0	22.84	22.98	22.93	2	

Table 9-10
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.93	24.89	24.99	0	0
	1	36	24.94	24.96	24.95		0
	1	74	24.96	25.00	24.86		0
	36	0	23.88	23.95	23.92	0-1	1
	36	18	23.91	23.91	23.91		1
	36	37	23.83	23.91	23.82		1
16QAM	75	0	23.85	23.87	23.96	0-1	1
	1	0	23.95	23.95	23.91		1
	1	36	23.94	23.98	23.92		1
	1	74	23.63	23.93	23.97	0-2	1
	36	0	22.89	22.96	22.99		2
	36	18	22.89	22.93	22.91		2
	36	37	22.81	22.94	22.85	2	
	75	0	22.86	22.86	22.95	2	

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 33 of 82

Table 9-11
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.95	24.99	25.00	0	0
	1	25	24.96	24.85	24.99		0
	1	49	24.96	25.00	24.91		0
	25	0	23.97	23.82	23.94	0-1	1
	25	12	23.95	23.91	23.93		1
	25	25	23.91	23.94	23.99		1
	50	0	23.98	23.97	23.98		1
16QAM	1	0	23.95	23.91	23.92	0-1	1
	1	25	23.91	24.00	23.96		1
	1	49	23.93	23.98	23.90		1
	25	0	22.94	22.76	22.98	0-2	2
	25	12	22.95	22.93	22.95		2
	25	25	22.95	23.00	22.94		2
	50	0	22.96	22.99	22.98		2

Table 9-12
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.94	24.95	24.93	0	0
	1	12	24.85	24.89	24.92		0
	1	24	24.91	24.95	24.90		0
	12	0	23.92	23.82	24.00	0-1	1
	12	6	23.91	23.91	23.87		1
	12	13	23.86	23.89	23.90		1
	25	0	23.92	23.89	23.90		1
16QAM	1	0	23.91	23.97	23.99	0-1	1
	1	12	23.91	23.97	23.92		1
	1	24	23.99	23.90	23.94		1
	12	0	22.94	22.87	22.94	0-2	2
	12	6	22.90	22.90	22.91		2
	12	13	22.87	22.98	22.93		2
	25	0	22.99	22.87	22.95		2

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 34 of 82

9.3.4

LTE Band 2 (PCS)

Table 9-13
LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 2 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18700 (1860.0 MHz)	18900 (1880.0 MHz)	19100 (1900.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.19	25.14	25.16	0	0
	1	50	25.16	25.16	25.17		0
	1	99	25.08	25.11	25.17		0
	50	0	24.16	24.01	23.98	0-1	1
	50	25	24.07	23.95	24.02		1
	50	50	24.00	23.93	24.04		1
	100	0	24.05	23.90	23.97		1
16QAM	1	0	24.15	24.18	24.00	0-1	1
	1	50	24.11	24.15	24.02		1
	1	99	24.14	24.14	24.01		1
	50	0	23.17	22.97	23.03	0-2	2
	50	25	23.12	22.99	23.10		2
	50	50	23.01	22.88	23.05		2
	100	0	23.08	22.95	23.05		2

Table 9-14
LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 2 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18675 (1857.5 MHz)	18900 (1880.0 MHz)	19125 (1902.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.10	25.20	25.17	0	0
	1	36	25.12	24.97	25.18		0
	1	74	25.18	24.89	25.16		0
	36	0	23.99	23.99	24.05	0-1	1
	36	18	24.05	23.93	24.10		1
	36	37	23.92	23.92	24.12		1
	75	0	23.98	23.97	24.10		1
16QAM	1	0	24.12	24.08	24.10	0-1	1
	1	36	24.10	24.08	24.15		1
	1	74	24.19	24.03	24.20		1
	36	0	23.08	23.05	23.14	0-2	2
	36	18	23.15	22.93	23.11		2
	36	37	23.07	22.96	23.12		2
	75	0	23.00	22.94	23.00		2

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 35 of 82

Table 9-15
LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 2 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18650 (1855.0 MHz)	18900 (1880.0 MHz)	19150 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.18	25.18	25.18	0	0
	1	25	25.16	25.09	25.20		0
	1	49	25.20	25.09	25.12		0
	25	0	24.14	24.13	24.19	0-1	1
	25	12	24.19	24.03	24.19		1
	25	25	24.10	24.01	24.13		1
16QAM	50	0	24.18	24.02	24.13	0-1	1
	1	0	24.17	24.12	24.13		1
	1	25	24.17	24.07	24.20		1
	1	49	24.10	24.17	24.19	0-2	1
	25	0	23.20	22.97	23.15		2
	25	12	23.20	23.09	23.13		2
	25	25	23.19	23.08	23.05	2	
	50	0	23.16	23.06	23.20	2	

Table 9-16
LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 2 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18625 (1852.5 MHz)	18900 (1880.0 MHz)	19175 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.18	25.00	25.19	0	0
	1	12	25.14	24.89	25.17		0
	1	24	25.18	24.79	25.10		0
	12	0	24.16	23.93	24.19	0-1	1
	12	6	24.14	23.97	24.18		1
	12	13	24.14	23.87	24.05		1
16QAM	25	0	24.10	23.95	24.18	0-1	1
	1	0	24.11	24.12	24.18		1
	1	12	24.18	24.13	24.19		1
	1	24	24.11	24.09	24.19	0-2	1
	12	0	23.12	23.01	23.18		2
	12	6	23.13	23.01	23.04		2
	12	13	23.20	22.83	23.15	2	
	25	0	23.15	22.95	23.20	2	

FCC ID: ZNFH910	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 36 of 82

Table 9-17
LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 2 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18615 (1851.5 MHz)	18900 (1880.0 MHz)	19185 (1908.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.11	25.01	25.19	0	0
	1	7	25.16	25.11	25.13		0
	1	14	25.14	24.90	25.09		0
	8	0	24.13	24.05	24.01	0-1	1
	8	4	24.13	23.97	24.01		1
	8	7	24.10	23.99	24.03		1
16QAM	15	0	24.11	23.95	24.10	0-1	1
	1	0	24.15	24.16	24.10		1
	1	7	24.12	24.04	24.19		1
	1	14	24.20	24.13	24.09	0-2	1
	8	0	23.17	23.00	23.03		2
	8	4	23.12	22.98	23.11		2
	8	7	23.16	22.87	23.09	2	
	15	0	23.20	22.88	23.17	2	

Table 9-18
LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 2 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18607 (1850.7 MHz)	18900 (1880.0 MHz)	19193 (1909.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.13	24.82	25.13	0	0
	1	2	25.18	25.00	25.14		0
	1	5	25.13	24.84	25.14		0
	3	0	24.99	25.15	25.19		0
	3	2	25.11	25.18	25.19		0
	3	3	25.17	25.08	25.20		0
16QAM	6	0	24.03	23.93	24.13	0-1	1
	1	0	24.15	24.07	24.14	0-1	1
	1	2	24.20	24.07	24.17		1
	1	5	24.11	23.94	23.90		1
	3	0	24.13	24.19	24.09		1
	3	2	24.13	24.08	24.11		1
3	3	24.11	24.05	24.19	1		
	6	0	23.10	22.73	23.12	0-2	2

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 37 of 82

9.3.5

LTE Band 30

Table 9-19
LTE Band 30 Conducted Powers - 10 MHz Bandwidth

LTE Band 30 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.70	0	0
	1	25	23.59		0
	1	49	23.60		0
	25	0	22.55	0-1	1
	25	12	22.46		1
	25	25	22.47		1
	50	0	22.51		1
16QAM	1	0	22.68	0-1	1
	1	25	22.62		1
	1	49	22.69		1
	25	0	21.55	0-2	2
	25	12	21.51		2
	25	25	21.44		2
	50	0	21.51		2

Table 9-20
LTE Band 30 Conducted Powers - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.62	0	0
	1	12	23.50		0
	1	24	23.67		0
	12	0	22.49	0-1	1
	12	6	22.43		1
	12	13	22.43		1
	25	0	22.40		1
16QAM	1	0	22.64	0-1	1
	1	12	22.70		1
	1	24	22.61		1
	12	0	21.52	0-2	2
	12	6	21.49		2
	12	13	21.44		2
	25	0	21.36		2

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 38 of 82

9.3.6

LTE Band 7

Table 9-21
LTE Band 7 Conducted Powers - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.64	23.66	23.65	0	0	
	1	50	23.65	23.62	23.66		0	
	1	99	23.65	23.68	23.62		0	
	50	0	22.37	22.36	22.60	0-1	1	
	50	25	22.39	22.31	22.51		1	
	50	50	22.27	22.29	22.42		1	
16QAM	100	0	22.38	22.37	22.50	0-1	1	
	1	0	22.69	22.43	22.65		0-1	1
	1	50	22.61	22.35	22.64			1
	1	99	22.53	22.44	22.66	0-2		1
	50	0	21.36	21.44	21.38		2	
	50	25	21.39	21.37	21.48		2	
16QAM	50	50	21.21	21.32	21.36	0-2	2	
	100	0	21.41	21.35	21.52		2	

Table 9-22
LTE Band 7 Conducted Powers - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.69	23.67	23.63	0	0	
	1	36	23.61	23.70	23.56		0	
	1	74	23.66	23.67	23.58		0	
	36	0	22.50	22.35	22.47	0-1	1	
	36	18	22.47	22.35	22.53		1	
	36	37	22.41	22.32	22.47		1	
16QAM	75	0	22.37	22.29	22.44	0-1	1	
	1	0	22.62	22.61	22.60		0-1	1
	1	36	22.70	22.47	22.51			1
	1	74	22.69	22.41	22.66	0-2		1
	36	0	21.48	21.37	21.48		2	
	36	18	21.52	21.38	21.51		2	
16QAM	36	37	21.40	21.32	21.51	0-2	2	
	75	0	21.37	21.28	21.49		2	

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 39 of 82

Table 9-23
LTE Band 7 Conducted Powers - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.69	23.69	23.62	0	0	
	1	25	23.63	23.68	23.68		0	
	1	49	23.52	23.70	23.64		0	
	25	0	22.50	22.48	22.67	0-1	1	
	25	12	22.55	22.36	22.61		1	
	25	25	22.49	22.39	22.64		1	
16QAM	50	0	22.49	22.38	22.66	0-1	1	
	1	0	22.68	22.67	22.61		0-1	1
	1	25	22.64	22.55	22.68			1
	1	49	22.66	22.61	22.69	0-2		1
	25	0	21.51	21.51	21.53		2	
	25	12	21.55	21.40	21.48		2	
	25	25	21.53	21.40	21.56	0-2	2	
	50	0	21.44	21.37	21.66		2	

Table 9-24
LTE Band 7 Conducted Powers - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.66	23.66	23.63	0	0	
	1	12	23.63	23.61	23.68		0	
	1	24	23.68	23.67	23.45		0	
	12	0	22.41	22.33	22.61	0-1	1	
	12	6	22.36	22.32	22.59		1	
	12	13	22.35	22.30	22.55		1	
16QAM	25	0	22.28	22.32	22.60	0-1	1	
	1	0	22.56	22.61	22.68		0-1	1
	1	12	22.49	22.61	22.70			1
	1	24	22.50	22.52	22.62	0-2		1
	12	0	21.44	21.36	21.66		2	
	12	6	21.38	21.37	21.65		2	
	12	13	21.38	21.31	21.61	0-2	2	
	25	0	21.26	21.28	21.58		2	

FCC ID: ZNFH910	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 40 of 82

9.3.7

LTE Carrier Aggregation Conducted Powers

Table 9-25
LTE Carrier Aggregation Conducted Powers 2CC Powers

PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC					SCC				Power		
			PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Rel 10 Tx.Power (dBm)	LTE Rel. 8 Tx.Power (dBm)
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B2	15	740	1944	24.83	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B4	20	2175	2132.5	24.91	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B5	10	2525	881.5	24.94	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B12	10	5095	737.5	24.91	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B29	10	9715	722.5	24.90	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B30	10	9820	2355	24.87	25.20
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B2	20	900	1960	24.91	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B4	5	1975	2112.5	24.92	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B5	10	2525	881.5	24.88	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B7	20	3100	2655	24.90	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B12	10	5095	737.5	24.90	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B17	10	5790	740	24.97	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B29	10	9715	722.5	24.91	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B30	10	9820	2355	24.84	25.00
LTE B12	5	23035	701.5	QPSK	1	0	5035	731.5	LTE B2	20	900	1960	25.00	25.00
LTE B12	5	23035	701.5	QPSK	1	0	5035	731.5	LTE B4	20	2175	2132.5	24.96	25.00
LTE B12	5	23035	701.5	QPSK	1	0	5035	731.5	LTE B30	10	9820	2355	24.96	25.00
LTE B17	5	23790	710	QPSK	1	0	5790	740	LTE B4	10	2175	2132.5	24.75	25.00
LTE B5	10	20525	836.5	QPSK	1	25	2525	881.5	LTE B2	20	900	1960	24.99	25.00
LTE B5	10	20525	836.5	QPSK	1	25	2525	881.5	LTE B4	20	2175	2132.5	24.97	25.00
LTE B5	10	20525	836.5	QPSK	1	25	2525	881.5	LTE B30	10	9820	2355	24.93	25.00
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	23.62	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B4	20	2175	2132.5	23.69	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B5	10	2525	881.5	23.51	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B12	10	5095	737.5	23.58	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B29	10	9715	722.5	23.57	23.70
LTE B7	15	21100	2535	QPSK	1	36	3100	2655	LTE B4	20	2175	2132.5	23.59	23.70
LTE B2	10	18650	1855	QPSK	1	49	650	1935	LTE B17	10	5790	740	25.08	25.20
LTE B17	5	23790	710	QPSK	1	0	5790	740	LTE B2	10	900	1960	24.75	25.00

Table 9-26
LTE Carrier Aggregation Conducted Powers 3CC Powers

PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC					SCC			SCC			Power				
			PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Rel 10 Tx.Power (dBm)	LTE Rel. 8 Tx.Power (dBm)
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B4	20	2175	2132.5	LTE B5	10	2525	881.5	24.84	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	24.90	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.80	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.84	25.20
LTE B2	15	18900	1880	QPSK	1	0	900	1960	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	24.91	25.20
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	24.81	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.80	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	24.89	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.99	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B2	20	900	1960	LTE B12	10	5095	737.5	24.91	25.00
LTE B4	10	20300	1745	QPSK	1	49	2300	2145	LTE B2	20	900	1960	LTE B5	10	2525	881.5	24.95	25.00
LTE B12	5	23035	701.5	QPSK	1	0	5035	731.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	25.00	25.00
LTE B12	5	23035	701.5	QPSK	1	0	5035	731.5	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	25.00	25.00
LTE B12	5	23035	701.5	QPSK	1	0	5035	731.5	LTE B4	20	2175	2132.5	LTE B2	20	900	1960	24.98	25.00
LTE B12	5	23035	701.5	QPSK	1	0	5035	731.5	LTE B7	20	3100	2655	LTE B4	20	2175	2132.5	24.96	25.00
LTE B5	10	20525	836.5	QPSK	1	25	2525	881.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	24.84	25.00
LTE B5	10	20525	836.5	QPSK	1	25	2525	881.5	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	24.80	25.00
LTE B5	10	20525	836.5	QPSK	1	25	2525	881.5	LTE B4	20	2175	2132.5	LTE B2	20	900	1960	25.00	25.00
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B29	10	9715	722.5	LTE B2	20	900	1960	23.69	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B29	10	9715	722.5	LTE B4	20	2175	2132.5	23.66	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B5	10	2525	881.5	LTE B4	20	2175	2132.5	23.68	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B5	10	2525	881.5	LTE B2	20	900	1960	23.68	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B12	10	5095	737.5	LTE B2	20	900	1960	23.58	23.70
LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B12	10	5095	737.5	LTE B4	20	2175	2132.5	23.60	23.70
LTE B7	15	21100	2535	QPSK	1	36	3100	2655	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	23.64	23.70

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 41 of 82

Notes:

1. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.
2. All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
3. Since the supported frequency span for LTE B4 falls completely within the supported frequency span for LTE B66, both LTE bands have the same target power, and both LTE bands share the same transmission path, the configuration with the highest conducted power from LTE B66 was used to assess LTE CA combinations with LTE B4.
4. Since the supported frequency span for LTE B17 falls completely within the supported frequency span for LTE B12, both LTE bands have the same target power, and both LTE bands share the same transmission path, the configuration with the highest conducted power from LTE B12 was used to assess LTE CA combinations with LTE B17.




Figure 9-3
Power Measurement Setup

FCC ID: ZNFH910	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 42 of 82

9.4 WLAN Conducted Powers

Table 9-27
2.4 GHz WLAN Maximum Average RF Power – Primary Antenna

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]			
		IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ac
2412	1	18.36	14.45	13.91	13.92
2427	4	19.23	15.35	14.69	14.71
2437	6	19.34	15.25	14.80	14.75
2447	8	19.45	15.35	14.78	14.75
2462	11	17.23	13.35	13.16	13.04

Table 9-28
2.4 GHz WLAN Maximum Average RF Power – Secondary Antenna

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]			
		IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ac
2412	1	19.07	14.95	14.26	14.37
2427	4	19.45	15.30	14.63	14.65
2437	6	19.74	15.39	14.83	14.87
2447	8	19.50	15.38	14.73	14.79
2462	11	18.60	14.44	13.76	13.75

Table 9-29
2.4 GHz WLAN Reduced Average RF Power – Primary Antenna

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]			
		IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ac
2412	1	11.59	12.26	12.11	12.16
2437	6	11.95	12.38	12.33	12.40
2462	11	11.78	12.37	12.05	12.13

Table 9-30
2.4 GHz WLAN Reduced Average RF Power – Secondary Antenna

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]			
		IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ac
2412	1	4.82	5.11	4.88	4.84
2437	6	5.49	5.49	5.48	5.46
2462	11	5.22	5.43	5.12	5.23

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 43 of 82

Table 9-31
5 GHz WLAN Maximum Average RF Power – Primary Antenna

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	14.38	14.31	14.46
5200	40	14.38	14.55	14.53
5220	44	14.32	14.41	14.38
5240	48	14.51	14.36	14.45
5260	52	14.88	14.71	14.70
5280	56	14.70	14.60	14.65
5300	60	14.73	14.53	14.61
5320	64	14.68	14.62	14.63
5500	100	14.42	14.33	14.38
5580	116	14.39	14.32	14.23
5660	132	14.40	14.16	14.32
5720	144	14.21	14.10	14.30
5745	149	14.56	14.30	14.36
5785	157	14.48	14.34	14.45
5825	165	14.53	14.42	14.41

Table 9-32
5 GHz WLAN Maximum Average RF Power – Secondary Antenna

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	13.50	13.39	13.40
5200	40	13.79	13.37	13.30
5220	44	13.51	13.41	13.32
5240	48	13.49	13.50	13.36
5260	52	13.54	13.41	13.41
5280	56	13.47	13.49	13.30
5300	60	13.47	13.34	13.35
5320	64	13.45	13.43	13.40
5500	100	13.15	13.08	13.09
5580	116	13.50	13.25	13.33
5660	132	13.55	13.40	13.47
5720	144	13.56	13.52	13.45
5745	149	13.65	13.55	13.51
5785	157	13.38	13.56	13.57
5825	165	13.32	13.38	13.44

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 44 of 82

Table 9-33
5 GHz WLAN Reduced Average RF Power – Primary Antenna (40MHz)

Freq [MHz]	Channel	5GHz (40MHz) Conducted Power [dBm]	
		IEEE Transmission Mode	
		802.11n	802.11ac
5190	38	11.39	11.25
5230	46	12.01	12.24
5270	54	12.07	12.06
5310	62	11.10	11.40

Table 9-34
5 GHz WLAN Reduced Average RF Power – Primary Antenna (80MHz)

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5530	106	10.63
5690	138	11.92
5775	155	11.85

Table 9-35
5 GHz WLAN Reduced Average RF Power – Secondary Antenna

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	4.56
5290	58	4.66
5530	106	4.71
5690	138	4.92
5775	155	4.69

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 45 of 82

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.
- This device only supports SISO operations on the secondary antenna for 802.11b. The above 802.11 a/g/n/ac secondary antenna powers are included to represent the maximum allowed output power the device can operate in CDD or MIMO SDM modes for simultaneous transmission evaluation purposes.




Figure 9-4
Power Measurement Setup for Bandwidths < 50 MHz




Figure 9-5
Power Measurement Setup for Bandwidths > 50 MHz

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 46 of 82	

9.5 Bluetooth Conducted Powers

Table 9-36
Bluetooth Average RF Powers

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	10.05	10.123
2441	1.0	39	12.44	17.548
2480	1.0	78	12.72	18.709
2402	2.0	0	6.93	4.927
2441	2.0	39	8.59	7.233
2480	2.0	78	8.17	6.568
2402	3.0	0	6.94	4.939
2441	3.0	39	8.61	7.266
2480	3.0	78	8.24	6.666

Note: The bolded data rate and channel above were tested for SAR.




Figure 9-6
Power Measurement Setup

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 47 of 82

10 SYSTEM VERIFICATION

10.1 Tissue Verification

**Table 10-1
Measured Head Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
8/15/2016	750H	21.5	700	0.865	43.159	0.889	42.201	-2.70%	2.27%
			710	0.872	42.972	0.890	42.149	-2.02%	1.95%
			740	0.902	42.639	0.893	41.994	1.01%	1.54%
			755	0.919	42.463	0.894	41.916	2.80%	1.30%
8/10/2016	835H	21.7	820	0.872	40.522	0.899	41.578	-3.00%	-2.54%
			835	0.885	40.244	0.900	41.500	-1.67%	-3.03%
			850	0.899	40.093	0.916	41.500	-1.86%	-3.39%
8/15/2016	1750H	21.8	1710	1.329	38.898	1.348	40.142	-1.41%	-3.10%
			1750	1.369	38.696	1.371	40.079	-0.15%	-3.45%
			1790	1.408	38.532	1.394	40.016	1.00%	-3.71%
8/8/2016	1900H	21.7	1850	1.391	40.152	1.400	40.000	-0.64%	0.38%
			1880	1.421	40.033	1.400	40.000	1.50%	0.08%
			1910	1.452	39.920	1.400	40.000	3.71%	-0.20%
8/15/2016	2300H-2600H	22.5	2300	1.613	39.507	1.670	39.500	-3.41%	0.02%
			2310	1.630	39.487	1.679	39.480	-2.92%	0.02%
			2400	1.723	39.159	1.756	39.289	-1.88%	-0.33%
			2450	1.780	38.943	1.800	39.200	-1.11%	-0.66%
			2500	1.839	38.711	1.855	39.136	-0.86%	-1.09%
			2550	1.893	38.541	1.909	39.073	-0.84%	-1.36%
8/8/2016	5200H-5800H	21.7	2600	1.941	38.323	1.964	39.009	-1.17%	-1.76%
			5240	4.477	36.207	4.696	35.940	-4.66%	0.74%
			5260	4.486	36.197	4.717	35.917	-4.90%	0.78%
			5280	4.516	36.157	4.737	35.894	-4.67%	0.73%
			5300	4.523	36.135	4.758	35.871	-4.94%	0.74%
			5600	4.860	35.746	5.065	35.529	-4.05%	0.61%
			5680	4.943	35.599	5.147	35.437	-3.96%	0.46%
			5700	4.964	35.606	5.168	35.414	-3.95%	0.54%
			5745	5.024	35.508	5.214	35.363	-3.64%	0.41%
5765	5.049	35.468	5.234	35.340	-3.53%	0.36%			
5785	5.069	35.415	5.255	35.317	-3.54%	0.28%			

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 48 of 82

**Table 10-2
Measured Body Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
8/9/2016	750B	21.0	700	0.920	55.196	0.959	55.726	-4.07%	-0.95%
			710	0.929	55.059	0.96	55.687	-3.23%	-1.13%
			740	0.958	54.689	0.963	55.57	-0.52%	-1.59%
			755	0.973	54.575	0.964	55.512	0.93%	-1.69%
8/17/2016	835B	22.4	820	0.989	54.510	0.969	55.258	2.06%	-1.35%
			835	1.004	54.370	0.970	55.200	3.51%	-1.50%
			850	1.018	54.221	0.988	55.154	3.04%	-1.69%
8/8/2016	1750B	21.4	1710	1.444	52.198	1.463	53.537	-1.30%	-2.50%
			1750	1.489	52.018	1.488	53.432	0.07%	-2.65%
			1790	1.532	51.847	1.514	53.326	1.19%	-2.77%
8/10/2016	1900B	21.6	1850	1.529	53.120	1.520	53.300	0.59%	-0.34%
			1880	1.563	52.999	1.520	53.300	2.83%	-0.56%
			1910	1.595	52.941	1.520	53.300	4.93%	-0.67%
8/15/2016	1900B	22.0	1850	1.532	52.664	1.520	53.300	0.79%	-1.19%
			1880	1.565	52.557	1.520	53.300	2.96%	-1.39%
			1910	1.595	52.451	1.520	53.300	4.93%	-1.59%
8/18/2016	1900B	23.3	1850	1.512	52.940	1.520	53.300	-0.53%	-0.68%
			1880	1.549	52.836	1.520	53.300	1.91%	-0.87%
			1910	1.584	52.785	1.520	53.300	4.21%	-0.97%
8/10/2016	2300B-2600B	23.0	2300	1.842	51.585	1.809	52.900	1.82%	-2.49%
			2310	1.852	51.566	1.816	52.887	1.98%	-2.50%
			2400	1.967	51.186	1.902	52.767	3.42%	-3.00%
			2450	2.032	51.051	1.950	52.700	4.21%	-3.13%
			2500	2.099	50.828	2.021	52.636	3.86%	-3.43%
			2550	2.162	50.658	2.092	52.573	3.35%	-3.64%
			2600	2.238	50.493	2.163	52.509	3.47%	-3.84%
8/15/2016	2450B-2600B	23.2	2400	1.953	52.593	1.902	52.767	2.68%	-0.33%
			2450	2.027	52.369	1.950	52.700	3.95%	-0.63%
			2500	2.095	52.115	2.021	52.636	3.66%	-0.99%
			2550	2.154	51.944	2.092	52.573	2.96%	-1.20%
08/12/2016	5200B-5800B	22.8	2600	2.216	51.743	2.163	52.509	2.45%	-1.46%
			5200	5.442	47.077	5.299	49.014	2.70%	-3.95%
			5240	5.505	46.974	5.346	48.960	2.97%	-4.06%
			5260	5.524	46.993	5.369	48.933	2.89%	-3.96%
			5500	5.820	46.621	5.650	48.607	3.01%	-4.09%
			5600	5.945	46.456	5.766	48.471	3.10%	-4.16%
			5700	6.079	46.205	5.883	48.336	3.33%	-4.41%
			5745	6.194	46.081	5.936	48.275	4.35%	-4.54%
			5765	6.237	46.088	5.959	48.248	4.67%	-4.48%
			5785	6.249	46.111	5.982	48.220	4.46%	-4.37%
08/15/2016	5200B-5800B	22.0	5240	5.512	48.306	5.346	48.960	3.11%	-1.34%
			5260	5.539	48.279	5.369	48.933	3.17%	-1.34%
			5500	5.855	47.808	5.650	48.607	3.63%	-1.64%
			5560	5.958	47.742	5.720	48.526	4.16%	-1.62%
			5580	5.956	47.732	5.743	48.499	3.71%	-1.58%
			5600	5.975	47.645	5.766	48.471	3.62%	-1.70%
			5660	6.100	47.538	5.837	48.390	4.51%	-1.76%
			5700	6.137	47.534	5.883	48.336	4.32%	-1.66%
			5745	6.202	47.409	5.936	48.275	4.48%	-1.79%
			5765	6.233	47.411	5.959	48.248	4.60%	-1.73%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 49 of 82

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.


**Table 10-3
System Verification Results**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
K	750	HEAD	08/15/2016	23.7	21.5	0.200	1054	7409	1.520	8.220	7.600	-7.54%
K	835	HEAD	08/10/2016	23.5	21.7	0.200	4d133	7409	1.740	9.320	8.700	-6.65%
G	1750	HEAD	08/15/2016	23.5	22.0	0.100	1148	3334	3.900	36.200	39.000	7.73%
I	1900	HEAD	08/08/2016	21.4	21.7	0.100	5d149	3333	4.220	40.100	42.200	5.24%
I	2300	HEAD	08/15/2016	22.6	22.5	0.100	1064	3333	4.830	47.600	48.300	1.47%
I	2450	HEAD	08/15/2016	22.6	22.5	0.100	981	3333	5.090	52.800	50.900	-3.60%
I	2600	HEAD	08/15/2016	22.6	22.5	0.100	1004	3333	5.780	55.700	57.800	3.77%
D	5250	HEAD	08/08/2016	20.1	22.4	0.050	1191	3914	3.830	82.500	76.600	-7.15%
D	5600	HEAD	08/08/2016	20.1	22.4	0.050	1191	3914	3.830	84.500	76.600	-9.35%
D	5750	HEAD	08/08/2016	20.1	22.4	0.050	1191	3914	3.700	80.000	74.000	-7.50%
G	750	BODY	08/09/2016	23.1	21.9	0.200	1054	3334	1.710	8.560	8.550	-0.12%
G	835	BODY	08/17/2016	21.8	22.0	0.200	4d133	3334	1.980	9.500	9.900	4.21%
F	1750	BODY	08/08/2016	20.9	21.4	0.100	1008	3209	3.690	37.300	36.900	-1.07%
H	1900	BODY	08/10/2016	21.9	21.8	0.100	5d080	3319	4.090	39.100	40.900	4.60%
G	1900	BODY	08/15/2016	22.4	22.4	0.100	5d080	3334	4.220	39.100	42.200	7.93%
G	1900	BODY	08/18/2016	22.1	23.3	0.100	5d080	3334	3.950	39.100	39.500	1.02%
E	2300	BODY	08/10/2016	23.6	23.0	0.100	1064	7406	4.950	45.500	49.500	8.79%
E	2450	BODY	08/10/2016	23.6	23.0	0.100	719	7406	5.270	51.900	52.700	1.54%
E	2450	BODY	08/15/2016	22.9	22.8	0.100	981	7406	5.110	50.800	51.100	0.59%
E	2600	BODY	08/10/2016	23.6	23.0	0.100	1071	7406	5.950	54.900	59.500	8.38%
E	2600	BODY	08/15/2016	22.9	22.8	0.100	1071	7406	5.900	54.900	59.000	7.47%
J	5250	BODY	08/12/2016	21.3	21.0	0.050	1191	7357	3.970	77.200	79.400	2.85%
J	5600	BODY	08/12/2016	21.3	21.0	0.050	1191	7357	4.460	81.900	89.200	8.91%
J	5750	BODY	08/12/2016	21.3	21.0	0.050	1191	7357	3.880	77.100	77.600	0.65%

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 50 of 82	

**Table 10-4
System Verification Results – 10g**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)
E	2450	BODY	08/15/2016	22.9	22.8	0.100	981	7406	2.360	23.800	23.600	-0.84%
D	5250	BODY	08/15/2016	22.0	22.7	0.050	1237	3914	1.050	21.000	21.000	0.00%
D	5600	BODY	08/15/2016	22.0	22.7	0.050	1237	3914	1.140	21.500	22.800	6.05%
D	5750	BODY	08/15/2016	22.0	22.7	0.050	1237	3914	1.000	20.900	20.000	-4.31%



**Figure 10-1
System Verification Setup Diagram**



**Figure 10-2
System Verification Setup Photo**

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 51 of 82

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.7	33.41	-0.02	Right	Cheek	09403	1	1:8.3	0.259	1.069	0.277	
836.60	190	GSM 850	GSM	33.7	33.41	0.08	Right	Tilt	09403	1	1:8.3	0.128	1.069	0.137	
836.60	190	GSM 850	GSM	33.7	33.41	0.04	Left	Cheek	09403	1	1:8.3	0.223	1.069	0.238	
836.60	190	GSM 850	GSM	33.7	33.41	0.07	Left	Tilt	09403	1	1:8.3	0.135	1.069	0.144	
836.60	190	GSM 850	GPRS	32.2	32.14	-0.05	Right	Cheek	09403	2	1:4.15	0.387	1.014	0.392	A1
836.60	190	GSM 850	GPRS	32.2	32.14	0.06	Right	Tilt	09403	2	1:4.15	0.208	1.014	0.211	
836.60	190	GSM 850	GPRS	32.2	32.14	0.08	Left	Cheek	09403	2	1:4.15	0.329	1.014	0.334	
836.60	190	GSM 850	GPRS	32.2	32.14	0.06	Left	Tilt	09403	2	1:4.15	0.218	1.014	0.221	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-2
UMTS 850 Head SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Tuner State	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.03	Right	Cheek	Ant 1	9	09403	1:1	0.238	1.009	0.240	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.17	Right	Tilt	Ant 1	9	09403	1:1	0.105	1.009	0.106	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.16	Left	Cheek	Ant 1	9	09403	1:1	0.221	1.009	0.223	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.04	Left	Tilt	Ant 1	9	09403	1:1	0.122	1.009	0.123	
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.07	Right	Cheek	Ant 3	N/A	09403	1:1	0.734	1.009	0.741	A2
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.08	Right	Tilt	Ant 3	N/A	09403	1:1	0.606	1.009	0.611	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.02	Left	Cheek	Ant 3	N/A	09403	1:1	0.526	1.009	0.531	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.00	Left	Tilt	Ant 3	N/A	09403	1:1	0.475	1.009	0.479	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 52 of 82

**Table 11-3
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	25.0	24.73	-0.04	Right	Cheek	09403	1:1	0.124	1.064	0.132	
1732.40	1412	UMTS 1750	RMC	25.0	24.73	0.11	Right	Tilt	09403	1:1	0.103	1.064	0.110	
1732.40	1412	UMTS 1750	RMC	25.0	24.73	0.14	Left	Cheek	09403	1:1	0.200	1.064	0.213	A3
1732.40	1412	UMTS 1750	RMC	25.0	24.73	0.01	Left	Tilt	09403	1:1	0.118	1.064	0.126	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-4
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.7	30.54	0.02	Right	Cheek	09395	1	1:8.3	0.094	1.038	0.098	
1880.00	661	GSM 1900	GSM	30.7	30.54	0.02	Right	Tilt	09395	1	1:8.3	0.076	1.038	0.079	
1880.00	661	GSM 1900	GSM	30.7	30.54	0.08	Left	Cheek	09395	1	1:8.3	0.158	1.038	0.164	A4
1880.00	661	GSM 1900	GSM	30.7	30.54	0.15	Left	Tilt	09395	1	1:8.3	0.062	1.038	0.064	
1880.00	661	GSM 1900	GPRS	27.2	26.96	0.07	Right	Cheek	09395	3	1:2.76	0.068	1.057	0.072	
1880.00	661	GSM 1900	GPRS	27.2	26.96	-0.15	Right	Tilt	09395	3	1:2.76	0.057	1.057	0.060	
1880.00	661	GSM 1900	GPRS	27.2	26.96	0.03	Left	Cheek	09395	3	1:2.76	0.140	1.057	0.148	
1880.00	661	GSM 1900	GPRS	27.2	26.96	0.13	Left	Tilt	09395	3	1:2.76	0.044	1.057	0.047	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-5
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	25.0	24.89	-0.04	Right	Cheek	09395	1:1	0.199	1.026	0.204	
1880.00	9400	UMTS 1900	RMC	25.0	24.89	0.14	Right	Tilt	09395	1:1	0.151	1.026	0.155	
1880.00	9400	UMTS 1900	RMC	25.0	24.89	0.07	Left	Cheek	09395	1:1	0.286	1.026	0.293	A5
1880.00	9400	UMTS 1900	RMC	25.0	24.89	0.08	Left	Tilt	09395	1:1	0.118	1.026	0.121	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 53 of 82

**Table 11-6
LTE Band 12 Head SAR**

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Antenna Config.	Tuner State	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
707.50	23095	Md	LTE Band 12	10	25.0	24.99	0.04	0	Right	Cheek	Ant 1	74	QPSK	1	49	09346	1:1	0.246	1.002	0.246	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	-0.01	1	Right	Cheek	Ant 1	74	QPSK	25	0	09346	1:1	0.193	1.028	0.198	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	-0.04	0	Right	Tilt	Ant 1	74	QPSK	1	49	09346	1:1	0.145	1.002	0.145	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	0.07	1	Right	Tilt	Ant 1	74	QPSK	25	0	09346	1:1	0.101	1.028	0.104	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	-0.02	0	Left	Cheek	Ant 1	74	QPSK	1	49	09346	1:1	0.207	1.002	0.207	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	-0.01	1	Left	Cheek	Ant 1	74	QPSK	25	0	09346	1:1	0.191	1.028	0.196	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	0.16	0	Left	Tilt	Ant 1	74	QPSK	1	49	09346	1:1	0.126	1.002	0.126	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	-0.12	1	Left	Tilt	Ant 1	74	QPSK	25	0	09346	1:1	0.104	1.028	0.107	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	0.05	0	Right	Cheek	Ant 3	N/A	QPSK	1	49	09346	1:1	0.824	1.002	0.826	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	-0.01	1	Right	Cheek	Ant 3	N/A	QPSK	25	0	09346	1:1	0.589	1.028	0.605	
707.50	23095	Md	LTE Band 12	10	24.0	23.82	0.01	1	Right	Cheek	Ant 3	N/A	QPSK	50	0	09346	1:1	0.610	1.042	0.636	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	-0.02	0	Right	Tilt	Ant 3	N/A	QPSK	1	49	09346	1:1	0.823	1.002	0.825	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	0.03	1	Right	Tilt	Ant 3	N/A	QPSK	25	0	09346	1:1	0.591	1.028	0.608	
707.50	23095	Md	LTE Band 12	10	24.0	23.82	-0.02	1	Right	Tilt	Ant 3	N/A	QPSK	50	0	09346	1:1	0.603	1.042	0.628	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	0.03	0	Left	Cheek	Ant 3	N/A	QPSK	1	49	09346	1:1	0.534	1.002	0.535	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	-0.01	1	Left	Cheek	Ant 3	N/A	QPSK	25	0	09346	1:1	0.398	1.028	0.409	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	0.06	0	Left	Tilt	Ant 3	N/A	QPSK	1	49	09346	1:1	0.549	1.002	0.550	
707.50	23095	Md	LTE Band 12	10	24.0	23.88	0.03	1	Left	Tilt	Ant 3	N/A	QPSK	25	0	09346	1:1	0.401	1.028	0.412	
707.50	23095	Md	LTE Band 12	10	25.0	24.99	-0.04	0	Right	Cheek	Ant 3	N/A	QPSK	1	49	09346	1:1	0.832	1.002	0.834	A6
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue Entry Represents Variability Measurement

**Table 11-7
LTE Band 5 (Cell) Head SAR**

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Antenna Config.	Tuner State	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	-0.06	0	Right	Cheek	Ant 1	9	QPSK	1	25	09346	1:1	0.233	1.000	0.233	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	-0.01	1	Right	Cheek	Ant 1	9	QPSK	25	0	09346	1:1	0.199	1.028	0.205	
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	-0.03	0	Right	Tilt	Ant 1	9	QPSK	1	25	09346	1:1	0.108	1.000	0.108	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	0.03	1	Right	Tilt	Ant 1	9	QPSK	25	0	09346	1:1	0.094	1.028	0.097	
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	0.03	0	Left	Cheek	Ant 1	9	QPSK	1	25	09346	1:1	0.246	1.000	0.246	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	0.07	1	Left	Cheek	Ant 1	9	QPSK	25	0	09346	1:1	0.190	1.028	0.195	
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	-0.02	0	Left	Tilt	Ant 1	9	QPSK	1	25	09346	1:1	0.132	1.000	0.132	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	0.02	1	Left	Tilt	Ant 1	9	QPSK	25	0	09346	1:1	0.099	1.028	0.102	
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	-0.08	0	Right	Cheek	Ant 3	N/A	QPSK	1	25	09361	1:1	0.780	1.000	0.780	A7
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	0.13	1	Right	Cheek	Ant 3	N/A	QPSK	25	0	09361	1:1	0.593	1.028	0.610	
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	-0.05	0	Right	Tilt	Ant 3	N/A	QPSK	1	25	09361	1:1	0.684	1.000	0.684	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	-0.03	1	Right	Tilt	Ant 3	N/A	QPSK	25	0	09361	1:1	0.554	1.028	0.570	
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	0.03	0	Left	Cheek	Ant 3	N/A	QPSK	1	25	09361	1:1	0.646	1.000	0.646	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	0.02	1	Left	Cheek	Ant 3	N/A	QPSK	25	0	09361	1:1	0.506	1.028	0.520	
836.50	20525	Md	LTE Band 5 (Cell)	10	25.0	25.00	-0.01	0	Left	Tilt	Ant 3	N/A	QPSK	1	25	09361	1:1	0.571	1.000	0.571	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.88	0.06	1	Left	Tilt	Ant 3	N/A	QPSK	25	0	09361	1:1	0.464	1.028	0.477	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 54 of 82	

**Table 11-8
LTE Band 66 (AWS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	0.11	0	Right	Cheek	QPSK	1	0	09346	1:1	0.150	1.000	0.150	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	0.00	1	Right	Cheek	QPSK	50	50	09346	1:1	0.112	1.005	0.113	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	-0.19	0	Right	Tilt	QPSK	1	0	09346	1:1	0.112	1.000	0.112	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	-0.06	1	Right	Tilt	QPSK	50	50	09346	1:1	0.074	1.005	0.074	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	0.14	0	Left	Cheek	QPSK	1	0	09346	1:1	0.330	1.000	0.330	A8
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	0.09	1	Left	Cheek	QPSK	50	50	09346	1:1	0.241	1.005	0.242	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	-0.21	0	Left	Tilt	QPSK	1	0	09346	1:1	0.137	1.000	0.137	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	-0.16	1	Left	Tilt	QPSK	50	50	09346	1:1	0.094	1.005	0.094	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-9
LTE Band 2 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.16	0	Right	Cheek	QPSK	1	0	09353	1:1	0.199	1.002	0.199	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	0.00	1	Right	Cheek	QPSK	50	0	09353	1:1	0.160	1.009	0.161	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.05	0	Right	Tilt	QPSK	1	0	09353	1:1	0.130	1.002	0.130	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	-0.16	1	Right	Tilt	QPSK	50	0	09353	1:1	0.091	1.009	0.092	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.04	0	Left	Cheek	QPSK	1	0	09353	1:1	0.334	1.002	0.335	A9
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	0.02	1	Left	Cheek	QPSK	50	0	09353	1:1	0.244	1.009	0.246	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.05	0	Left	Tilt	QPSK	1	0	09353	1:1	0.167	1.002	0.167	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	0.04	1	Left	Tilt	QPSK	50	0	09353	1:1	0.131	1.009	0.132	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-10
LTE Band 30 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.03	0	Right	Cheek	QPSK	1	0	09346	1:1	0.111	1.000	0.111	
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	-0.03	1	Right	Cheek	QPSK	25	0	09346	1:1	0.079	1.035	0.082	
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.03	0	Right	Tilt	QPSK	1	0	09346	1:1	0.065	1.000	0.065	
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.03	1	Right	Tilt	QPSK	25	0	09346	1:1	0.047	1.035	0.049	
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.03	0	Left	Cheek	QPSK	1	0	09346	1:1	0.203	1.000	0.203	A10
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.16	1	Left	Cheek	QPSK	25	0	09346	1:1	0.147	1.035	0.152	
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.05	0	Left	Tilt	QPSK	1	0	09346	1:1	0.115	1.000	0.115	
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.04	1	Left	Tilt	QPSK	25	0	09346	1:1	0.079	1.035	0.082	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 55 of 82	

**Table 11-11
LTE Band 7 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.10	0	Right	Cheek	QPSK	1	99	09346	1:1	0.075	1.005	0.075	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	0.15	1	Right	Cheek	QPSK	50	0	09346	1:1	0.066	1.023	0.068	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.13	0	Right	Tilt	QPSK	1	99	09346	1:1	0.045	1.005	0.045	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	-0.07	1	Right	Tilt	QPSK	50	0	09346	1:1	0.042	1.023	0.043	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.08	0	Left	Cheek	QPSK	1	99	09346	1:1	0.133	1.005	0.134	A11
2560.00	21350	High	LTE Band 7	20	22.7	22.60	0.07	1	Left	Cheek	QPSK	50	0	09346	1:1	0.109	1.023	0.112	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.15	0	Left	Tilt	QPSK	1	99	09346	1:1	0.029	1.005	0.029	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	0.20	1	Left	Tilt	QPSK	50	0	09346	1:1	0.028	1.023	0.029	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-12
DTS Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	12.5	11.95	-0.20	Right	Cheek	Primary	09486	1	99.9	0.132	-	1.135	1.001	-	
2437	6	802.11b	DSSS	22	12.5	11.95	0.02	Right	Tilt	Primary	09486	1	99.9	0.141	-	1.135	1.001	-	
2437	6	802.11b	DSSS	22	12.5	11.95	0.03	Left	Cheek	Primary	09486	1	99.9	0.408	0.389	1.135	1.001	0.442	A12
2437	6	802.11b	DSSS	22	12.5	11.95	0.03	Left	Tilt	Primary	09486	1	99.9	0.368	0.338	1.135	1.001	0.384	
2437	6	802.11b	DSSS	22	5.5	5.49	0.04	Right	Cheek	Secondary	09486	1	99.9	0.033	-	1.002	1.001	-	
2437	6	802.11b	DSSS	22	5.5	5.49	0.05	Right	Tilt	Secondary	09486	1	99.9	0.027	-	1.002	1.001	-	
2437	6	802.11b	DSSS	22	5.5	5.49	0.14	Left	Cheek	Secondary	09486	1	99.9	0.083	0.069	1.002	1.001	0.069	
2437	6	802.11b	DSSS	22	5.5	5.49	0.04	Left	Tilt	Secondary	09486	1	99.9	0.066	-	1.002	1.001	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 56 of 82	

**Table 11-13
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)	(Power)	(Duty Cycle)	(W/kg)	
5270	54	802.11n	OFDM	40	13.0	12.07	0.18	Right	Cheek	Primary	09486	13.5	99.3	0.232	-	1.239	1.007	-	
5270	54	802.11n	OFDM	40	13.0	12.07	0.13	Right	Tilt	Primary	09486	13.5	99.3	0.291	-	1.239	1.007	-	
5270	54	802.11n	OFDM	40	13.0	12.07	0.15	Left	Cheek	Primary	09486	13.5	99.3	0.456	-	1.239	1.007	-	
5270	54	802.11n	OFDM	40	13.0	12.07	0.04	Left	Tilt	Primary	09486	13.5	99.3	0.492	0.247	1.239	1.007	0.308	
5290	58	802.11ac	OFDM	80	5.5	4.66	0.02	Right	Cheek	Secondary	09486	29.3	98.4	0.067	-	1.213	1.016	-	
5290	58	802.11ac	OFDM	80	5.5	4.66	0.01	Right	Tilt	Secondary	09486	29.3	98.4	0.098	-	1.213	1.016	-	
5290	58	802.11ac	OFDM	80	5.5	4.66	0.05	Left	Cheek	Secondary	09486	29.3	98.4	0.334	-	1.213	1.016	-	
5290	58	802.11ac	OFDM	80	5.5	4.66	0.02	Left	Tilt	Secondary	09486	29.3	98.4	0.471	0.234	1.213	1.016	0.288	
5690	138	802.11ac	OFDM	80	13.0	11.92	0.06	Right	Cheek	Primary	09486	29.3	98.4	0.305	-	1.282	1.016	-	
5690	138	802.11ac	OFDM	80	13.0	11.92	0.06	Right	Tilt	Primary	09486	29.3	98.4	0.351	-	1.282	1.016	-	
5690	138	802.11ac	OFDM	80	13.0	11.92	0.06	Left	Cheek	Primary	09486	29.3	98.4	0.480	0.174	1.282	1.016	0.227	
5690	138	802.11ac	OFDM	80	13.0	11.92	-0.05	Left	Tilt	Primary	09486	29.3	98.4	0.630	0.321	1.282	1.016	0.418	A13
5690	138	802.11ac	OFDM	80	5.5	4.92	0.11	Right	Cheek	Secondary	09486	29.3	98.4	0.102	-	1.143	1.016	-	
5690	138	802.11ac	OFDM	80	5.5	4.92	0.02	Right	Tilt	Secondary	09486	29.3	98.4	0.133	-	1.143	1.016	-	
5690	138	802.11ac	OFDM	80	5.5	4.92	0.13	Left	Cheek	Secondary	09486	29.3	98.4	0.204	-	1.143	1.016	-	
5690	138	802.11ac	OFDM	80	5.5	4.92	0.13	Left	Tilt	Secondary	09486	29.3	98.4	0.247	0.132	1.143	1.016	0.153	
5775	155	802.11ac	OFDM	80	13.0	11.85	0.08	Right	Cheek	Primary	09486	29.3	98.4	0.215	-	1.303	1.016	-	
5775	155	802.11ac	OFDM	80	13.0	11.85	0.05	Right	Tilt	Primary	09486	29.3	98.4	0.250	-	1.303	1.016	-	
5775	155	802.11ac	OFDM	80	13.0	11.85	0.02	Left	Cheek	Primary	09486	29.3	98.4	0.471	-	1.303	1.016	-	
5775	155	802.11ac	OFDM	80	13.0	11.85	0.06	Left	Tilt	Primary	09486	29.3	98.4	0.605	0.279	1.303	1.016	0.369	
5775	155	802.11ac	OFDM	80	5.5	4.69	0.02	Right	Cheek	Secondary	09486	29.3	98.4	0.090	-	1.205	1.016	-	
5775	155	802.11ac	OFDM	80	5.5	4.69	0.10	Right	Tilt	Secondary	09486	29.3	98.4	0.115	-	1.205	1.016	-	
5775	155	802.11ac	OFDM	80	5.5	4.69	0.00	Left	Cheek	Secondary	09486	29.3	98.4	0.160	-	1.205	1.016	-	
5775	155	802.11ac	OFDM	80	5.5	4.69	0.19	Left	Tilt	Secondary	09486	29.3	98.4	0.204	0.110	1.205	1.016	0.135	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 57 of 82	

11.2 Standalone Body-Worn SAR Data

Table 11-14
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Tuner State	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.7	33.41	-0.01	10 mm	Ant 1	N/A	09403	1	1:8.3	back	0.350	1.069	0.374	
836.60	190	GSM 850	GPRS	32.2	32.14	-0.01	10 mm	Ant 1	N/A	09403	2	1:4.15	back	0.503	1.014	0.510	A14
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.03	10 mm	Ant 1	9	09403	N/A	1:1	back	0.369	1.009	0.372	A16
836.60	4183	UMTS 850	RMC	24.7	24.66	0.01	10 mm	Ant 3	N/A	09403	N/A	1:1	back	0.141	1.009	0.142	
1732.40	1412	UMTS 1750	RMC	25.0	24.73	0.05	10 mm	Ant 2	N/A	09403	N/A	1:1	back	0.532	1.064	0.566	A18
1880.00	661	GSM 1900	GSM	30.7	30.54	-0.02	10 mm	Ant 2	N/A	09403	1	1:8.3	back	0.261	1.038	0.271	
1880.00	661	GSM 1900	GPRS	27.2	26.96	-0.13	10 mm	Ant 2	N/A	09403	3	1:2.76	back	0.351	1.057	0.371	A20
1880.00	9400	UMTS 1900	RMC	25.0	24.89	0.01	10 mm	Ant 2	N/A	09395	N/A	1:1	back	0.709	1.026	0.727	A21
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-15
LTE Body-Worn SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Tuner State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	-0.04	0	Ant 1	74	09379	QPSK	1	49	10 mm	back	1:1	0.337	1.002	0.338	A22
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.03	1	Ant 1	74	09379	QPSK	25	0	10 mm	back	1:1	0.233	1.028	0.240	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	-0.11	0	Ant 3	N/A	09379	QPSK	1	49	10 mm	back	1:1	0.112	1.002	0.112	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.01	1	Ant 3	N/A	09379	QPSK	25	0	10 mm	back	1:1	0.088	1.028	0.090	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.04	0	Ant 1	10	09346	QPSK	1	25	10 mm	back	1:1	0.395	1.000	0.395	A24
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	-0.01	1	Ant 1	10	09346	QPSK	25	0	10 mm	back	1:1	0.298	1.028	0.306	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.02	0	Ant 3	N/A	09346	QPSK	1	25	10 mm	back	1:1	0.142	1.000	0.142	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	0.01	1	Ant 3	N/A	09346	QPSK	25	0	10 mm	back	1:1	0.100	1.028	0.103	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	-0.05	0	Ant 2	N/A	09346	QPSK	1	0	10 mm	back	1:1	0.368	1.000	0.368	A26
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	0.01	1	Ant 2	N/A	09346	QPSK	50	50	10 mm	back	1:1	0.330	1.005	0.332	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	-0.02	0	Ant 2	N/A	09379	QPSK	1	0	10 mm	back	1:1	0.878	1.002	0.880	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	25.2	25.16	-0.02	0	Ant 2	N/A	09379	QPSK	1	50	10 mm	back	1:1	0.798	1.009	0.805	
1900.00	19100	High	LTE Band 2 (PCS)	20	25.2	25.17	0.01	0	Ant 2	N/A	09379	QPSK	1	50	10 mm	back	1:1	0.808	1.007	0.814	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	0.00	1	Ant 2	N/A	09379	QPSK	50	0	10 mm	back	1:1	0.660	1.009	0.666	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.05	-0.01	1	Ant 2	N/A	09379	QPSK	100	0	10 mm	back	1:1	0.649	1.035	0.672	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.18	0	Ant 2	N/A	09379	QPSK	1	0	10 mm	back	1:1	0.921	1.002	0.923	A28
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.01	0	Ant 1	N/A	09346	QPSK	1	0	10 mm	back	1:1	0.536	1.000	0.536	A29
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.01	1	Ant 1	N/A	09346	QPSK	25	0	10 mm	back	1:1	0.387	1.035	0.401	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.04	0	Ant 1	N/A	09346	QPSK	1	99	10 mm	back	1:1	0.666	1.005	0.669	A31
2560.00	21350	High	LTE Band 7	20	22.7	22.60	0.05	1	Ant 1	N/A	09346	QPSK	50	0	10 mm	back	1:1	0.598	1.023	0.612	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram														

Note: Blue Entry Represents Variability Measurement

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 58 of 82

**Table 11-16
DTS Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)	(W/kg)			(W/kg)	
2447	8	802.11b	DSSS	22	20.0	19.45	-0.01	10 mm	Primary	09486	1	back	99.9	0.310	0.201	1.135	1.001	0.228	
2437	6	802.11b	DSSS	22	20.0	19.74	0.14	10 mm	Secondary	09486	1	back	99.9	0.387	0.270	1.062	1.001	0.287	A33
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-17
NII Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	15.0	14.88	0.03	10 mm	Primary	09486	6	back	99.4	0.040	0.016	1.028	1.006	0.017	
5260	52	802.11a	OFDM	20	14.0	13.54	0.20	10 mm	Secondary	09486	6	back	99.4	0.142	0.069	1.112	1.006	0.077	A35
5500	100	802.11a	OFDM	20	15.0	14.42	-0.02	10 mm	Primary	09486	6	back	99.4	0.155	0.062	1.143	1.006	0.071	
5720	144	802.11a	OFDM	20	14.0	13.56	0.13	10 mm	Secondary	09486	6	back	99.4	0.135	0.054	1.107	1.006	0.060	
5745	149	802.11a	OFDM	20	15.0	14.56	-0.10	10 mm	Primary	09486	6	back	99.4	0.118	0.060	1.107	1.006	0.067	
5745	149	802.11a	OFDM	20	14.0	13.65	0.02	10 mm	Secondary	09486	6	back	99.4	0.160	0.067	1.084	1.006	0.073	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-18
DSS Body-Worn SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #		
MHz	Ch.											(W/kg)		(W/kg)			
2480	78	Bluetooth	FHSS	13.0	12.72	0.04	10 mm	09486	1	back	1:1	0.009	1.067	0.010	A37		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 59 of 82

11.3 Standalone Hotspot SAR Data

**Table 11-19
GPRS/UMTS Hotspot SAR Data**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Tuner State	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	32.2	32.14	-0.01	10 mm	Ant 1	N/A	09403	2	1.4.15	back	0.503	1.014	0.510	
836.60	190	GSM 850	GPRS	32.2	32.14	0.07	10 mm	Ant 1	N/A	09403	2	1.4.15	front	0.552	1.014	0.560	
836.60	190	GSM 850	GPRS	32.2	32.14	-0.02	10 mm	Ant 1	N/A	09403	2	1.4.15	bottom	0.719	1.014	0.729	A15
836.60	190	GSM 850	GPRS	32.2	32.14	0.11	10 mm	Ant 1	N/A	09403	2	1.4.15	right	0.671	1.014	0.680	
836.60	190	GSM 850	GPRS	32.2	32.14	0.03	10 mm	Ant 1	N/A	09403	2	1.4.15	left	0.406	1.014	0.412	
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.03	10 mm	Ant 1	9	09403	N/A	1:1	back	0.369	1.009	0.372	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.02	10 mm	Ant 1	9	09403	N/A	1:1	front	0.436	1.009	0.440	
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.04	10 mm	Ant 1	9	09403	N/A	1:1	bottom	0.503	1.009	0.508	A17
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.04	10 mm	Ant 1	9	09403	N/A	1:1	right	0.417	1.009	0.421	
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.04	10 mm	Ant 1	9	09403	N/A	1:1	left	0.292	1.009	0.295	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.01	10 mm	Ant 3	N/A	09403	N/A	1:1	back	0.141	1.009	0.142	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.00	10 mm	Ant 3	N/A	09403	N/A	1:1	front	0.125	1.009	0.126	
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.02	10 mm	Ant 3	N/A	09403	N/A	1:1	top	0.140	1.009	0.141	
836.60	4183	UMTS 850	RMC	24.7	24.66	-0.14	10 mm	Ant 3	N/A	09403	N/A	1:1	right	0.072	1.009	0.073	
836.60	4183	UMTS 850	RMC	24.7	24.66	0.04	10 mm	Ant 3	N/A	09403	N/A	1:1	left	0.044	1.009	0.044	
1732.40	1412	UMTS 1750	RMC	25.0	24.73	0.05	10 mm	Ant 2	N/A	09403	N/A	1:1	back	0.532	1.064	0.566	
1732.40	1412	UMTS 1750	RMC	25.0	24.73	0.08	10 mm	Ant 2	N/A	09403	N/A	1:1	front	0.628	1.064	0.668	A19
1732.40	1412	UMTS 1750	RMC	25.0	24.73	-0.03	10 mm	Ant 2	N/A	09403	N/A	1:1	bottom	0.418	1.064	0.445	
1732.40	1412	UMTS 1750	RMC	25.0	24.73	-0.03	10 mm	Ant 2	N/A	09403	N/A	1:1	left	0.375	1.064	0.399	
1880.00	661	GSM 1900	GPRS	27.2	26.96	-0.13	10 mm	Ant 2	N/A	09403	3	1.2.76	back	0.351	1.057	0.371	A20
1880.00	661	GSM 1900	GPRS	27.2	26.96	0.03	10 mm	Ant 2	N/A	09403	3	1.2.76	front	0.311	1.057	0.329	
1880.00	661	GSM 1900	GPRS	27.2	26.96	0.05	10 mm	Ant 2	N/A	09403	3	1.2.76	bottom	0.187	1.057	0.198	
1880.00	661	GSM 1900	GPRS	27.2	26.96	-0.03	10 mm	Ant 2	N/A	09403	3	1.2.76	left	0.220	1.057	0.233	
1880.00	9400	UMTS 1900	RMC	25.0	24.89	0.01	10 mm	Ant 2	N/A	09395	N/A	1:1	back	0.709	1.026	0.727	A21
1880.00	9400	UMTS 1900	RMC	25.0	24.89	-0.01	10 mm	Ant 2	N/A	09395	N/A	1:1	front	0.675	1.026	0.693	
1880.00	9400	UMTS 1900	RMC	25.0	24.89	0.01	10 mm	Ant 2	N/A	09395	N/A	1:1	bottom	0.360	1.026	0.369	
1880.00	9400	UMTS 1900	RMC	25.0	24.89	-0.03	10 mm	Ant 2	N/A	09395	N/A	1:1	left	0.554	1.026	0.568	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak							Body 1.6 W/kg (mW/g) averaged over 1 gram										
Uncontrolled Exposure/General Population																	

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 60 of 82	

**Table 11-20
LTE Band 12 Hotspot SAR**

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Tuner State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	-0.04	0	Ant 1	74	09379	QPSK	1	49	10 mm	back	1:1	0.337	1.002	0.338	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.03	1	Ant 1	74	09379	QPSK	25	0	10 mm	back	1:1	0.233	1.028	0.240	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	0.01	0	Ant 1	74	09379	QPSK	1	49	10 mm	front	1:1	0.305	1.002	0.306	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.02	1	Ant 1	74	09379	QPSK	25	0	10 mm	front	1:1	0.218	1.028	0.224	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	-0.02	0	Ant 1	74	09379	QPSK	1	49	10 mm	bottom	1:1	0.287	1.002	0.288	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.02	1	Ant 1	74	09379	QPSK	25	0	10 mm	bottom	1:1	0.176	1.028	0.181	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	0.13	0	Ant 1	74	09379	QPSK	1	49	10 mm	right	1:1	0.431	1.002	0.432	A23
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.03	1	Ant 1	74	09379	QPSK	25	0	10 mm	right	1:1	0.296	1.028	0.304	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	0.01	0	Ant 1	74	09379	QPSK	1	49	10 mm	left	1:1	0.230	1.002	0.230	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	0.04	1	Ant 1	74	09379	QPSK	25	0	10 mm	left	1:1	0.160	1.028	0.164	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	-0.11	0	Ant 3	N/A	09379	QPSK	1	49	10 mm	back	1:1	0.112	1.002	0.112	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.01	1	Ant 3	N/A	09379	QPSK	25	0	10 mm	back	1:1	0.088	1.028	0.090	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	0.07	0	Ant 3	N/A	09379	QPSK	1	49	10 mm	front	1:1	0.117	1.002	0.117	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.09	1	Ant 3	N/A	09379	QPSK	25	0	10 mm	front	1:1	0.081	1.028	0.083	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	0.04	0	Ant 3	N/A	09379	QPSK	1	49	10 mm	top	1:1	0.148	1.002	0.148	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.01	1	Ant 3	N/A	09379	QPSK	25	0	10 mm	top	1:1	0.088	1.028	0.090	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	-0.04	0	Ant 3	N/A	09379	QPSK	1	49	10 mm	right	1:1	0.079	1.002	0.079	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.02	1	Ant 3	N/A	09379	QPSK	25	0	10 mm	right	1:1	0.073	1.028	0.075	
707.50	23095	Mid	LTE Band 12	10	25.0	24.99	-0.08	0	Ant 3	N/A	09379	QPSK	1	49	10 mm	left	1:1	0.084	1.002	0.084	
707.50	23095	Mid	LTE Band 12	10	24.0	23.88	-0.07	1	Ant 3	N/A	09379	QPSK	25	0	10 mm	left	1:1	0.071	1.028	0.073	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-21
LTE Band 5 (Cell) Hotspot SAR**

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Tuner State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.																(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.04	0	Ant 1	10	09346	QPSK	1	25	10 mm	back	1:1	0.395	1.000	0.395	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	-0.01	1	Ant 1	10	09346	QPSK	25	0	10 mm	back	1:1	0.298	1.028	0.306	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.08	0	Ant 1	10	09346	QPSK	1	25	10 mm	front	1:1	0.462	1.000	0.462	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	0.09	1	Ant 1	10	09346	QPSK	25	0	10 mm	front	1:1	0.345	1.028	0.355	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.16	0	Ant 1	10	09346	QPSK	1	25	10 mm	bottom	1:1	0.564	1.000	0.564	A25
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	-0.04	1	Ant 1	10	09346	QPSK	25	0	10 mm	bottom	1:1	0.446	1.028	0.458	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	-0.01	0	Ant 1	10	09346	QPSK	1	25	10 mm	right	1:1	0.470	1.000	0.470	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	0.04	1	Ant 1	10	09346	QPSK	25	0	10 mm	right	1:1	0.362	1.028	0.372	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	-0.02	0	Ant 1	10	09346	QPSK	1	25	10 mm	left	1:1	0.303	1.000	0.303	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	-0.01	1	Ant 1	10	09346	QPSK	25	0	10 mm	left	1:1	0.232	1.028	0.238	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.02	0	Ant 3	N/A	09346	QPSK	1	25	10 mm	back	1:1	0.142	1.000	0.142	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	0.01	1	Ant 3	N/A	09346	QPSK	25	0	10 mm	back	1:1	0.100	1.028	0.103	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	-0.04	0	Ant 3	N/A	09346	QPSK	1	25	10 mm	front	1:1	0.184	1.000	0.184	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	-0.02	1	Ant 3	N/A	09346	QPSK	25	0	10 mm	front	1:1	0.127	1.028	0.131	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	-0.02	0	Ant 3	N/A	09346	QPSK	1	25	10 mm	top	1:1	0.151	1.000	0.151	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	-0.06	1	Ant 3	N/A	09346	QPSK	25	0	10 mm	top	1:1	0.111	1.028	0.114	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.06	0	Ant 3	N/A	09346	QPSK	1	25	10 mm	right	1:1	0.069	1.000	0.069	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	0.03	1	Ant 3	N/A	09346	QPSK	25	0	10 mm	right	1:1	0.047	1.028	0.048	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	25.00	0.07	0	Ant 3	N/A	09346	QPSK	1	25	10 mm	left	1:1	0.033	1.000	0.033	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.88	-0.03	1	Ant 3	N/A	09346	QPSK	25	0	10 mm	left	1:1	0.023	1.028	0.024	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 61 of 82	

**Table 11-22
LTE Band 66 (AWS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	-0.05	0	09346	QPSK	1	0	10 mm	back	1:1	0.368	1.000	0.368	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	0.01	1	09346	QPSK	50	50	10 mm	back	1:1	0.330	1.005	0.332	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	0.04	0	09346	QPSK	1	0	10 mm	front	1:1	0.722	1.000	0.722	A27
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	0.03	1	09346	QPSK	50	50	10 mm	front	1:1	0.529	1.005	0.532	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	-0.14	0	09346	QPSK	1	0	10 mm	bottom	1:1	0.345	1.000	0.345	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	0.00	1	09346	QPSK	50	50	10 mm	bottom	1:1	0.277	1.005	0.278	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	25.00	0.01	0	09346	QPSK	1	0	10 mm	left	1:1	0.607	1.000	0.607	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.98	0.02	1	09346	QPSK	50	50	10 mm	left	1:1	0.451	1.005	0.453	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-23
LTE Band 2 (PCS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	-0.02	0	09379	QPSK	1	0	10 mm	back	1:1	0.878	1.002	0.880	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	25.2	25.16	-0.02	0	09379	QPSK	1	50	10 mm	back	1:1	0.798	1.009	0.805	
1900.00	19100	High	LTE Band 2 (PCS)	20	25.2	25.17	0.01	0	09379	QPSK	1	50	10 mm	back	1:1	0.808	1.007	0.814	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	0.00	1	09379	QPSK	50	0	10 mm	back	1:1	0.660	1.009	0.666	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.05	-0.01	1	09379	QPSK	100	0	10 mm	back	1:1	0.649	1.035	0.672	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.11	0	09379	QPSK	1	0	10 mm	front	1:1	0.758	1.002	0.760	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	0.01	1	09379	QPSK	50	0	10 mm	front	1:1	0.589	1.009	0.594	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.02	0	09379	QPSK	1	0	10 mm	bottom	1:1	0.485	1.002	0.486	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	0.00	1	09379	QPSK	50	0	10 mm	bottom	1:1	0.349	1.009	0.352	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	-0.01	0	09379	QPSK	1	0	10 mm	left	1:1	0.627	1.002	0.628	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.2	24.16	-0.09	1	09379	QPSK	50	0	10 mm	left	1:1	0.476	1.009	0.480	
1860.00	18700	Low	LTE Band 2 (PCS)	20	25.2	25.19	0.18	0	09379	QPSK	1	0	10 mm	back	1:1	0.921	1.002	0.923	A28
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

Note: Blue Entry Represents Variability

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 62 of 82

**Table 11-24
LTE Band 30 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.01	0	09346	QPSK	1	0	10 mm	back	1:1	0.536	1.000	0.536	
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.01	1	09346	QPSK	25	0	10 mm	back	1:1	0.387	1.035	0.401	
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	-0.04	0	09346	QPSK	1	0	10 mm	front	1:1	0.598	1.000	0.598	A30
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.00	1	09346	QPSK	25	0	10 mm	front	1:1	0.476	1.035	0.493	
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.03	0	09346	QPSK	1	0	10 mm	bottom	1:1	0.423	1.000	0.423	
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	-0.04	1	09346	QPSK	25	0	10 mm	bottom	1:1	0.317	1.035	0.328	
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.05	0	09346	QPSK	1	0	10 mm	right	1:1	0.074	1.000	0.074	
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.12	1	09346	QPSK	25	0	10 mm	right	1:1	0.051	1.035	0.053	
2310.00	27710	Mid	LTE Band 30	10	23.7	23.70	0.06	0	09346	QPSK	1	0	10 mm	left	1:1	0.176	1.000	0.176	
2310.00	27710	Mid	LTE Band 30	10	22.7	22.55	0.05	1	09346	QPSK	25	0	10 mm	left	1:1	0.130	1.035	0.135	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-25
LTE Band 7 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.04	0	09346	QPSK	1	99	10 mm	back	1:1	0.666	1.005	0.669	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	0.05	1	09346	QPSK	50	0	10 mm	back	1:1	0.598	1.023	0.612	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.01	0	09346	QPSK	1	99	10 mm	front	1:1	0.348	1.005	0.350	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	0.01	1	09346	QPSK	50	0	10 mm	front	1:1	0.329	1.023	0.337	
2510.00	20850	Low	LTE Band 7	20	23.7	23.65	-0.03	0	09346	QPSK	1	99	10 mm	bottom	1:1	0.796	1.012	0.806	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	-0.04	0	09346	QPSK	1	99	10 mm	bottom	1:1	1.040	1.005	1.045	
2560.00	21350	High	LTE Band 7	20	23.7	23.66	-0.17	0	09346	QPSK	1	50	10 mm	bottom	1:1	1.120	1.009	1.130	A32
2510.00	20850	Low	LTE Band 7	20	22.7	22.39	-0.14	1	09346	QPSK	50	25	10 mm	bottom	1:1	0.600	1.074	0.644	
2535.00	21100	Mid	LTE Band 7	20	22.7	22.36	-0.08	1	09346	QPSK	50	0	10 mm	bottom	1:1	0.693	1.081	0.749	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	-0.16	1	09346	QPSK	50	0	10 mm	bottom	1:1	0.918	1.023	0.939	
2560.00	21350	High	LTE Band 7	20	22.7	22.50	-0.15	1	09346	QPSK	100	0	10 mm	bottom	1:1	0.902	1.047	0.944	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.02	0	09346	QPSK	1	99	10 mm	right	1:1	0.079	1.005	0.079	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	0.06	1	09346	QPSK	50	0	10 mm	right	1:1	0.061	1.023	0.062	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.68	0.05	0	09346	QPSK	1	99	10 mm	left	1:1	0.097	1.005	0.097	
2560.00	21350	High	LTE Band 7	20	22.7	22.60	-0.05	1	09346	QPSK	50	0	10 mm	left	1:1	0.084	1.023	0.086	
2560.00	21350	High	LTE Band 7	20	23.7	23.66	-0.06	0	09346	QPSK	1	50	10 mm	bottom	1:1	1.100	1.009	1.110	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue Entry Represents Variability

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 63 of 82	

**Table 11-26
WLAN Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2447	8	802.11b	DSSS	22	20.0	19.45	-0.01	10 mm	Primary	09486	1	back	99.9	0.310	-	1.135	1.001	-	
2447	8	802.11b	DSSS	22	20.0	19.45	-0.14	10 mm	Primary	09486	1	front	99.9	0.356	0.269	1.135	1.001	0.306	
2447	8	802.11b	DSSS	22	20.0	19.45	0.03	10 mm	Primary	09486	1	top	99.9	0.209	-	1.135	1.001	-	
2447	8	802.11b	DSSS	22	20.0	19.45	-0.08	10 mm	Primary	09486	1	right	99.9	0.255	-	1.135	1.001	-	
2437	6	802.11b	DSSS	22	20.0	19.74	0.14	10 mm	Secondary	09486	1	back	99.9	0.387	-	1.062	1.001	-	
2437	6	802.11b	DSSS	22	20.0	19.74	-0.16	10 mm	Secondary	09486	1	front	99.9	0.446	-	1.062	1.001	-	
2437	6	802.11b	DSSS	22	20.0	19.74	0.12	10 mm	Secondary	09486	1	top	99.9	0.527	0.337	1.062	1.001	0.358	A34
2437	6	802.11b	DSSS	22	20.0	19.74	0.08	10 mm	Secondary	09486	1	right	99.9	0.053	-	1.062	1.001	-	
5240	48	802.11a	OFDM	20	15.0	14.51	-0.15	10 mm	Primary	09486	6	back	99.4	0.064	-	1.119	1.006	-	
5240	48	802.11a	OFDM	20	15.0	14.51	0.14	10 mm	Primary	09486	6	front	99.4	0.037	-	1.119	1.006	-	
5240	48	802.11a	OFDM	20	15.0	14.51	0.19	10 mm	Primary	09486	6	top	99.4	0.099	0.049	1.119	1.006	0.055	
5240	48	802.11a	OFDM	20	15.0	14.51	0.15	10 mm	Primary	09486	6	right	99.4	0.015	-	1.119	1.006	-	
5200	40	802.11a	OFDM	20	14.0	13.79	-0.15	10 mm	Secondary	09486	6	back	99.4	0.124	-	1.050	1.006	-	
5200	40	802.11a	OFDM	20	14.0	13.79	0.11	10 mm	Secondary	09486	6	front	99.4	0.283	-	1.050	1.006	-	
5200	40	802.11a	OFDM	20	14.0	13.79	0.04	10 mm	Secondary	09486	6	top	99.4	0.411	0.200	1.050	1.006	0.211	A36
5200	40	802.11a	OFDM	20	14.0	13.79	0.11	10 mm	Secondary	09486	6	right	99.4	0.042	-	1.050	1.006	-	
5745	149	802.11a	OFDM	20	15.0	14.56	0.02	10 mm	Primary	09486	6	back	99.4	0.118	-	1.107	1.006	-	
5745	149	802.11a	OFDM	20	15.0	14.56	0.04	10 mm	Primary	09486	6	front	99.4	0.102	-	1.107	1.006	-	
5745	149	802.11a	OFDM	20	15.0	14.56	-0.11	10 mm	Primary	09486	6	top	99.4	0.276	0.120	1.107	1.006	0.134	
5745	149	802.11a	OFDM	20	15.0	14.56	0.03	10 mm	Primary	09486	6	right	99.4	0.047	-	1.107	1.006	-	
5745	149	802.11a	OFDM	20	14.0	13.65	0.02	10 mm	Secondary	09486	6	back	99.4	0.160	-	1.084	1.006	-	
5745	149	802.11a	OFDM	20	14.0	13.65	0.10	10 mm	Secondary	09486	6	front	99.4	0.108	-	1.084	1.006	-	
5745	149	802.11a	OFDM	20	14.0	13.65	0.14	10 mm	Secondary	09486	6	top	99.4	0.279	0.124	1.084	1.006	0.135	
5745	149	802.11a	OFDM	20	14.0	13.65	0.12	10 mm	Secondary	09486	6	right	99.4	0.094	-	1.084	1.006	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 64 of 82	

11.4 Standalone Phablet SAR Data

**Table 11-27
WLAN Phablet SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g) (W/kg)	Plot #
MHz	Ch.													W/kg	(W/kg)	(W/kg)	(W/kg)		
5260	52	802.11a	OFDM	20	15.0	14.88	0.10	0 mm	Primary	09486	6	back	99.4	1.275	-	1.028	1.006	-	-
5260	52	802.11a	OFDM	20	15.0	14.88	0.18	0 mm	Primary	09486	6	front	99.4	0.409	-	1.028	1.006	-	-
5260	52	802.11a	OFDM	20	15.0	14.88	0.02	0 mm	Primary	09486	6	top	99.4	3.016	0.152	1.028	1.006	0.157	-
5260	52	802.11a	OFDM	20	15.0	14.88	0.11	0 mm	Primary	09486	6	right	99.4	0.380	-	1.028	1.006	-	-
5260	52	802.11a	OFDM	20	14.0	13.54	0.16	0 mm	Secondary	09486	6	back	99.4	1.858	-	1.112	1.006	-	-
5260	52	802.11a	OFDM	20	14.0	13.54	-0.12	0 mm	Secondary	09486	6	front	99.4	3.642	-	1.112	1.006	-	-
5260	52	802.11a	OFDM	20	14.0	13.54	0.01	0 mm	Secondary	09486	6	top	99.4	6.793	0.537	1.112	1.006	0.601	-
5260	52	802.11a	OFDM	20	14.0	13.54	0.14	0 mm	Secondary	09486	6	right	99.4	0.341	-	1.112	1.006	-	-
5500	100	802.11a	OFDM	20	15.0	14.42	0.14	0 mm	Primary	09486	6	back	99.4	3.076	-	1.143	1.006	-	-
5500	100	802.11a	OFDM	20	15.0	14.42	0.12	0 mm	Primary	09486	6	front	99.4	0.901	-	1.143	1.006	-	-
5500	100	802.11a	OFDM	20	15.0	14.42	0.02	0 mm	Primary	09486	6	top	99.4	5.851	0.318	1.143	1.006	0.366	-
5500	100	802.11a	OFDM	20	15.0	14.42	0.13	0 mm	Primary	09486	6	right	99.4	0.788	-	1.143	1.006	-	-
5720	144	802.11a	OFDM	20	14.0	13.56	0.19	0 mm	Secondary	09486	6	back	99.4	2.519	-	1.107	1.006	-	-
5720	144	802.11a	OFDM	20	14.0	13.56	0.15	0 mm	Secondary	09486	6	front	99.4	2.404	-	1.107	1.006	-	-
5500	100	802.11a	OFDM	20	14.0	13.15	-0.06	0 mm	Secondary	09486	6	top	99.4	10.688	0.773	1.216	1.006	0.946	-
5580	116	802.11a	OFDM	20	14.0	13.50	-0.07	0 mm	Secondary	09486	6	top	99.4	13.200	0.788	1.122	1.006	0.889	A38
5660	132	802.11a	OFDM	20	14.0	13.55	-0.06	0 mm	Secondary	09486	6	top	99.4	11.562	0.727	1.109	1.006	0.811	-
5720	144	802.11a	OFDM	20	14.0	13.56	-0.10	0 mm	Secondary	09486	6	top	99.4	7.693	0.583	1.107	1.006	0.649	-
5720	144	802.11a	OFDM	20	14.0	13.56	0.12	0 mm	Secondary	09486	6	right	99.4	0.243	-	1.107	1.006	-	-
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Phablet 4.0 W/kg (mW/g) averaged over 10 grams											

**Table 11-28
Bluetooth Phablet SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g) (W/kg)	Plot #
MHz	Ch.											(W/kg)	(W/kg)	(W/kg)	
2480	78	Bluetooth	FHSS	13.0	12.72	0.03	0 mm	09486	1	back	1:1	0.038	1.067	0.041	-
2480	78	Bluetooth	FHSS	13.0	12.72	-0.01	0 mm	09486	1	front	1:1	0.051	1.067	0.054	A39
2480	78	Bluetooth	FHSS	13.0	12.72	0.10	0 mm	09486	1	top	1:1	0.029	1.067	0.031	-
2480	78	Bluetooth	FHSS	13.0	12.72	-0.03	0 mm	09486	1	right	1:1	0.031	1.067	0.033	-
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams								

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 65 of 82	

11.5 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Per FCC KDB Publication 648474 D04v01r03, this device is considered a “phablet” since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
11. This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
12. This device supports dynamic antenna tuning for some bands on Antenna 1. Per FCC Guidance, SAR was measured according to the normally required SAR measurement configurations with the tuner active. The auto-tune state determined by the device was verified before and after each SAR measurement and is listed in the tables above. Please see Section 14 for supplemental data.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address possible VoIP scenarios.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 66 of 82	

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
4. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.
6. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
7. Under normal operation this device supports independent (SISO) WLAN transmission from the primary antenna for all modes and from the secondary antenna for 2.4 GHz 802.11b mode only. Other WLAN modes tested for standalone scenarios for the secondary antenna were evaluated using the test mode software provided by the manufacturer to determine simultaneous transmission SAR compliance for potential MIMO operations.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 67 of 82

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Primary Antenna SAR (W/kg)	2.4 GHz WLAN Secondary Antenna SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Head SAR	GSM/GPRS 850	0.392	0.442	0.069	0.903
	UMTS 850	0.741	0.442	0.069	1.252
	UMTS 1750	0.213	0.442	0.069	0.724
	GSM/GPRS 1900	0.164	0.442	0.069	0.675
	UMTS 1900	0.293	0.442	0.069	0.804
	LTE Band 12	0.834	0.442	0.069	1.345
	LTE Band 5 (Cell)	0.780	0.442	0.069	1.291
	LTE Band 66 (AWS)	0.330	0.442	0.069	0.841
	LTE Band 2 (PCS)	0.335	0.442	0.069	0.846
	LTE Band 30	0.203	0.442	0.069	0.714
	LTE Band 7	0.134	0.442	0.069	0.645

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 68 of 82

**Table 12-2
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Primary Antenna SAR (W/kg)	5 GHz WLAN Secondary Antenna SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Head SAR	GSM/GPRS 850	0.392	0.418	0.288	1.098
	UMTS 850	0.741	0.418	0.288	1.447
	UMTS 1750	0.213	0.418	0.288	0.919
	GSM/GPRS 1900	0.164	0.418	0.288	0.870
	UMTS 1900	0.293	0.418	0.288	0.999
	LTE Band 12	0.834	0.418	0.288	1.540
	LTE Band 5 (Cell)	0.780	0.418	0.288	1.486
	LTE Band 66 (AWS)	0.330	0.418	0.288	1.036
	LTE Band 2 (PCS)	0.335	0.418	0.288	1.041
	LTE Band 30	0.203	0.418	0.288	0.909
	LTE Band 7	0.134	0.418	0.288	0.840

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 69 of 82	

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Primary Antenna SAR (W/kg)	2.4 GHz WLAN Secondary Antenna SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Body-Worn	GSM/GPRS 850	0.510	0.228	0.287	1.025
	UMTS 850	0.372	0.228	0.287	0.887
	UMTS 1750	0.566	0.228	0.287	1.081
	GSM/GPRS 1900	0.371	0.228	0.287	0.886
	UMTS 1900	0.727	0.228	0.287	1.242
	LTE Band 12	0.338	0.228	0.287	0.853
	LTE Band 5 (Cell)	0.395	0.228	0.287	0.910
	LTE Band 66 (AWS)	0.368	0.228	0.287	0.883
	LTE Band 2 (PCS)	0.923	0.228	0.287	1.438
	LTE Band 30	0.536	0.228	0.287	1.051
	LTE Band 7	0.669	0.228	0.287	1.184

Table 12-4
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Primary Antenna SAR (W/kg)	5 GHz WLAN Secondary Antenna SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Body-Worn	GSM/GPRS 850	0.510	0.071	0.077	0.658
	UMTS 850	0.372	0.071	0.077	0.520
	UMTS 1750	0.566	0.071	0.077	0.714
	GSM/GPRS 1900	0.371	0.071	0.077	0.519
	UMTS 1900	0.727	0.071	0.077	0.875
	LTE Band 12	0.338	0.071	0.077	0.486
	LTE Band 5 (Cell)	0.395	0.071	0.077	0.543
	LTE Band 66 (AWS)	0.368	0.071	0.077	0.516
	LTE Band 2 (PCS)	0.923	0.071	0.077	1.071
	LTE Band 30	0.536	0.071	0.077	0.684
	LTE Band 7	0.669	0.071	0.077	0.817

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 70 of 82

**Table 12-5
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM/GPRS 850	0.510	0.010	0.520
	UMTS 850	0.372	0.010	0.382
	UMTS 1750	0.566	0.010	0.576
	GSM/GPRS 1900	0.371	0.010	0.381
	UMTS 1900	0.727	0.010	0.737
	LTE Band 12	0.338	0.010	0.348
	LTE Band 5 (Cell)	0.395	0.010	0.405
	LTE Band 66 (AWS)	0.368	0.010	0.378
	LTE Band 2 (PCS)	0.923	0.010	0.933
	LTE Band 30	0.536	0.010	0.546
	LTE Band 7	0.669	0.010	0.679

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 71 of 82

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Primary Antenna SAR (W/kg)	2.4 GHz WLAN Secondary Antenna SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	
Hotspot SAR	GPRS 850	0.729	0.306	0.358	1.393
	UMTS 850	0.508	0.306	0.358	1.172
	UMTS 1750	0.668	0.306	0.358	1.332
	GPRS 1900	0.371	0.306	0.358	1.035
	UMTS 1900	0.727	0.306	0.358	1.391
	LTE Band 12	0.432	0.306	0.358	1.096
	LTE Band 5 (Cell)	0.564	0.306	0.358	1.228
	LTE Band 66 (AWS)	0.722	0.306	0.358	1.386
	LTE Band 2 (PCS)	0.923	0.306	0.358	1.587
	LTE Band 30	0.598	0.306	0.358	1.262
	LTE Band 7	1.130	0.306	0.358	See Table 12-7

Table 12-7
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Simult Tx	Configuration	LTE Band 7 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	
Hotspot SAR	Back	0.669	0.306*	0.358*	1.333
	Front	0.350	0.306	0.358*	1.014
	Top	-	0.306*	0.358	0.664
	Bottom	1.130	-	-	1.130
	Right	0.079	0.306*	0.358*	0.743
	Left	0.097	-	-	0.097

Note: (*) Represents Worst Case Configuration

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 72 of 82

Table 12-8
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Primary Antenna SAR (W/kg)	5 GHz WLAN Secondary Antenna SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	
Hotspot SAR	GPRS 850	0.729	0.134	0.211	1.074
	UMTS 850	0.508	0.134	0.211	0.853
	UMTS 1750	0.668	0.134	0.211	1.013
	GPRS 1900	0.371	0.134	0.211	0.716
	UMTS 1900	0.727	0.134	0.211	1.072
	LTE Band 12	0.432	0.134	0.211	0.777
	LTE Band 5 (Cell)	0.564	0.134	0.211	0.909
	LTE Band 66 (AWS)	0.722	0.134	0.211	1.067
	LTE Band 2 (PCS)	0.923	0.134	0.211	1.268
	LTE Band 30	0.598	0.134	0.211	0.943
	LTE Band 7	1.130	0.134	0.211	1.475

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 73 of 82

12.6 Phablet SAR Simultaneous Transmission Analysis

Main antenna, 2.4 GHz WIFI SAR testing was not required for phablet exposure conditions per FCC KDB 648474 D04v01r02. Therefore, no further analysis beyond **Table 12-9** was required to determine that possible simultaneous scenarios would not exceed the SAR limit.

Table 12-9
Simultaneous Transmission Scenario for MIMO 5 GHz WLAN (Phablet at 0.0 cm)

Simult Tx	5 GHz WLAN Primary Antenna SAR (W/kg)	5 GHz WLAN Secondary Antenna SAR (W/kg)	Σ SAR (W/kg)
Phablet SAR	0.366	0.946	1.312

12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 74 of 82

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

**Table 13-1
Head SAR Measurement Variability Results**

HEAD VARIABILITY RESULTS													
Band	FREQUENCY		Mode/Band	Service	Side	Test Position	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
750	707.50	23095	LTE Band 12, 10 MHz Bandwidth, Ant 3	QPSK, 1 RB, 49 RB Offset	Right	Cheek	0.824	0.832	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 13-2
Body SAR Measurement Variability Results**

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1860.00	18700	LTE Band 2 (PCS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	back	10 mm	0.878	0.921	1.05	N/A	N/A	N/A	N/A
2600	2560.00	21350	LTE Band 7, 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	bottom	10 mm	1.120	1.100	1.02	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 75 of 82	

The following test procedures were followed to demonstrate that the SAR results in Section 11 represented the appropriate SAR test conditions. For bands with dynamic tuning implemented, SAR was measured according to the required FCC SAR test procedures with the dynamic tuner active to allow the device to automatically tune to the antenna state for the respective RF exposure test configurations. Additional single point SAR time-sweep measurements were evaluated for other tuner states to determine that the other tuner configurations would result in equivalent or lower SAR values. The additional tuner hardware has no influence to the antenna characteristics, other than impedance matching.

To evaluate all of the tuner states, the 144 tuner states were divided evenly among band, mode and exposure combinations so that at least one single point SAR measurement was measured among the configurations. Single point time-sweep measurements were performed at the peak SAR location determined by the zoom scan of the configuration with the highest reported SAR for each combination. The tuner state was able to be established remotely so that the device was not moved for the entire series of single point SAR for the tuner states in each combination. The SAR probe remained stationary at the same position throughout the entire series of single point measurements for each combination.

The operational description contains more information about the design and implementation of the dynamic antenna tuning.

**Table 14-1
Supplemental Head SAR Data**

Supplemental Head SAR Data					
LTE Band 12		LTE Band 5		UMTS Band 5	
QPSK, 10MHz Bandwidth, 1 RB, 49 RB Offset		QPSK, 10MHz Bandwidth, 1 RB, 25 RB Offset		RMC	
Test Position	Right Cheek	Test Position	Left Cheek	Test Position	Right Cheek
Frequency (MHz)	707.5	Frequency (MHz)	836.5	Frequency (MHz)	836.6
Channel	23095	Channel	20525	Channel	4183
Measured 1g SAR (W/kg)	0.246	Measured 1g SAR (W/kg)	0.246	Measured 1g SAR (W/kg)	0.238
Average Value of Time Sweep (W/kg)		Average Value of Time Sweep (W/kg)		Average Value of Time Sweep (W/kg)	
Auto-tune (State 74)	0.269	Auto-tune (State 9)	0.267	Auto-tune (State 9)	0.260
Default (State 74)	0.273	Default (State 9)	0.274	Default (State 2)	0.241
State 1	0.239	State 7	0.259	State 9	0.259
State 21	0.207	State 8	0.257	State 26	0.246
State 29	0.131	State 11	0.258	State 27	0.238
State 39	0.224	State 14	0.166	State 33	0.156
State 42	0.208	State 17	0.095	State 35	0.114
State 45	0.176	State 19	0.230	State 47	0.224
State 48	0.131	State 24	0.242	State 50	0.183
State 51	0.095	State 32	0.165	State 53	0.124
State 54	0.055	State 56	0.253	State 57	0.247
State 55	0.245	State 61	0.251	State 64	0.248
State 58	0.246	State 63	0.244	State 66	0.226
State 60	0.227	State 65	0.228	State 68	0.203
State 69	0.098	State 72	0.122	State 70	0.161
State 92	0.235	State 78	0.201	State 91	0.158
State 94	0.239	State 82	0.170	State 103	0.071
State 97	0.206	State 84	0.129	State 114	0.172
State 112	0.256	State 87	0.069	State 117	0.148
State 113	0.242	State 90	0.028	State 120	0.095
State 115	0.215	State 99	0.141	State 123	0.053
State 121	0.098	State 102	0.090	State 126	0.022
State 124	0.051	State 105	0.050	State 130	0.190
State 131	0.250	State 134	0.186	State 132	0.185
State 136	0.169	State 137	0.130	State 138	0.112
State 140	0.083	State 139	0.100	State 142	0.045
State 144	0.028	State 141	0.066	State 143	0.037

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 76 of 82	

**Table 14-2
Supplemental Body SAR Data**

Supplemental Body SAR Data					
LTE Band 12		LTE Band 5		UMTS Band 5	
QPSK, 10MHz Bandwidth, 1 RB, 49 RB Offset		QPSK, 10MHz Bandwidth, 1 RB, 25 RB Offset		RMC	
Test Position	Right Edge	Test Position	Bottom Edge	Test Position	Bottom Edge
Frequency (MHz)	707.5	Frequency (MHz)	836.5	Frequency (MHz)	836.6
Channel	23095	Channel	20525	Channel	4183
Measured 1g SAR (W/kg)	0.431	Measured 1g SAR (W/kg)	0.564	Measured 1g SAR (W/kg)	0.503
Average Value of Time Sweep (W/kg)		Average Value of Time Sweep (W/kg)		Average Value of Time Sweep (W/kg)	
Auto-tune (State 74)	0.731	Auto-tune (State 10)	1.003	Auto-tune (State 9)	0.845
Default (State 74)	0.717	Default (State 9)	1.039	Default (State 2)	0.799
State 2	0.730	State 9	1.039	State 3	0.810
State 4	0.702	State 10	1.009	State 5	0.842
State 6	0.665	State 19	0.909	State 9	0.871
State 10	0.505	State 25	0.999	State 12	0.748
State 13	0.317	State 34	0.560	State 15	0.530
State 16	0.167	State 36	0.398	State 18	0.277
State 20	0.639	State 40	1.040	State 28	0.794
State 22	0.623	State 43	1.021	State 30	0.697
State 23	0.603	State 46	0.978	State 37	0.684
State 30	0.390	State 49	0.826	State 38	0.847
State 31	0.358	State 52	0.622	State 41	0.852
State 44	0.597	State 55	0.831	State 59	0.835
State 67	0.403	State 62	0.983	State 76	0.636
State 73	0.581	State 71	0.513	State 79	0.634
State 75	0.738	State 74	0.743	State 85	0.332
State 77	0.700	State 81	0.691	State 88	0.159
State 80	0.618	State 100	0.478	State 93	0.624
State 83	0.392	State 101	0.391	State 95	0.587
State 86	0.235	State 108	0.085	State 96	0.567
State 89	0.109	State 110	0.764	State 104	0.204
State 98	0.520	State 119	0.441	State 106	0.125
State 107	0.119	State 122	0.275	State 111	0.628
State 109	0.624	State 125	0.141	State 118	0.453
State 116	0.553	State 127	0.575	State 129	0.625
State 128	0.725	State 133	0.685	State 135	0.559

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 77 of 82

15 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753E	(30kHz-6GHz) Network Analyzer	3/2/2016	Annual	3/2/2017	JP38020182
Agilent	8753ES	S-Parameter Network Analyzer	11/4/2015	Annual	11/4/2016	US39170118
Agilent	E4432B	ESG-D Series Signal Generator	3/5/2016	Annual	3/5/2017	US40053896
Agilent	E4438C	ESG Vector Signal Generator	3/13/2015	Biennial	3/13/2017	MY42082659
Agilent	E5515C	Wireless Communications Test Set	11/4/2014	Biennial	11/4/2016	GB43193563
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/2/2016	Annual	3/2/2017	MY45470194
Agilent	N5182A	MXG Vector Signal Generator	3/5/2016	Annual	3/5/2017	MY47420800
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB44450273
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433978
Anritsu	MA24106A	USB Power Sensor	3/4/2016	Annual	3/4/2017	1344557
Anritsu	MA24106A	USB Power Sensor	3/28/2016	Annual	3/28/2017	1344554
Anritsu	MA2411B	Pulse Power Sensor	12/7/2015	Annual	12/7/2016	1339018
Anritsu	MA2411B	Pulse Power Sensor	2/28/2016	Annual	2/28/2017	1207470
Anritsu	MA2481A	Power Sensor	3/3/2016	Annual	3/3/2017	5318
Anritsu	MA2481A	Power Sensor	3/3/2016	Annual	3/3/2017	2400
Anritsu	ML2438A	Power Meter	3/3/2016	Annual	3/3/2017	1070030
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	941001
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	1039008
Anritsu	ML2496A	Power Meter	2/28/2016	Annual	2/28/2017	1306009
Anritsu	ML2496A	Power Meter	3/5/2016	Annual	3/5/2017	1351001
Anritsu	MI8820C	Radio Communication Analyzer	9/1/2015	Annual	9/1/2016	6201144419
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4040	Digital Thermometer	3/18/2015	Biennial	3/18/2017	150194896
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261701
Control Company	4353	Long Stem Thermometer	3/5/2015	Biennial	3/5/2017	150149565
Gigatronics	80701A	(0.05-18GHz) Power Sensor	11/4/2015	Annual	11/4/2016	1833460
Gigatronics	8651A	Universal Power Meter	11/4/2015	Annual	11/4/2016	8650319
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	S1P-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6°CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	11/6/2015	Biennial	11/6/2017	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	3/29/2016	Annual	3/29/2017	836371/0079
Rohde & Schwarz	CMW500	Radio Communication Tester	4/27/2016	Annual	4/27/2017	101699
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
SPEAG	DAK-12	Dielectric Assessment Kit (10MHz - 3GHz)	3/1/2016	Annual	3/1/2017	1102
SPEAG	DAK-3.5	Dielectric Assessment Kit	10/20/2015	Annual	10/20/2016	1091
SPEAG	ES3DV3	SAR Probe	11/17/2015	Annual	11/17/2016	3334
SPEAG	EX3DV4	SAR Probe	5/17/2016	Annual	5/17/2017	7409
SPEAG	ES3DV3	SAR Probe	10/29/2015	Annual	10/29/2016	3333
SPEAG	EX3DV4	SAR Probe	2/22/2016	Annual	2/22/2017	3914
SPEAG	ES3DV3	SAR Probe	3/18/2016	Annual	3/18/2017	3209
SPEAG	ES3DV3	SAR Probe	3/18/2016	Annual	3/18/2017	3319
SPEAG	EX3DV4	SAR Probe	4/19/2016	Annual	4/19/2017	7406
SPEAG	EX3DV4	SAR Probe	4/19/2016	Annual	4/19/2017	7357
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2015	Annual	11/11/2016	1415
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/11/2016	Annual	5/11/2017	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/27/2015	Annual	10/27/2016	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/18/2016	Annual	2/18/2017	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2015	Annual	11/11/2016	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/14/2016	Annual	3/14/2017	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/14/2016	Annual	4/14/2017	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/19/2016	Annual	2/19/2017	665
SPEAG	D750V3	750 MHz Dipole	3/16/2016	Annual	3/16/2017	1054
SPEAG	D835V2	835 MHz SAR Dipole	7/14/2016	Annual	7/14/2017	4d133
SPEAG	D1750V2	SAR Dipole	5/9/2016	Annual	5/9/2017	1148
SPEAG	D1900V2	1900 MHz SAR Dipole	7/15/2016	Annual	7/15/2017	5d149
SPEAG	D2450V2	2450 MHz SAR Dipole	8/20/2015	Annual	8/20/2016	719
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Annual	7/25/2017	981
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/16/2015	Annual	9/16/2016	1191
SPEAG	D1765V2	1765 MHz SAR Dipole	5/11/2016	Annual	5/11/2017	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	7/8/2016	Annual	7/8/2017	5d080
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/2/2016	Annual	8/2/2017	1237
SPEAG	D2300V2	2300 MHz SAR Dipole	12/8/2015	Annual	12/8/2016	1064
SPEAG	D2600V2	2600 MHz SAR Dipole	10/21/2015	Annual	10/21/2016	1071
SPEAG	D2600V2	2600 MHz SAR Dipole	4/19/2016	Annual	4/19/2017	1004

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 78 of 82

16 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset			Page 79 of 82

17 CONCLUSION

17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: ZNFH910		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 80 of 82

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Document S/N: OY1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset		Page 81 of 82

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFH910	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1608121352-R1.ZNF	Test Dates: 08/08/16 - 08/18/16	DUT Type: Portable Handset	Page 82 of 82	

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15
Medium: 835 Head Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.886 \text{ S/m}$; $\epsilon_r = 40.228$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 08-10-2016; Ambient Temp: 23.5°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7409; ConvF(10.04, 10.04, 10.04); Calibrated: 5/17/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/11/2016
Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Right Head, Cheek, Mid.ch, 2 Tx slots

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.07 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.492 W/kg
SAR(1 g) = 0.387 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Head Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.886 \text{ S/m}$; $\epsilon_r = 40.228$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 08-10-2016; Ambient Temp: 23.5°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7409; ConvF(10.04, 10.04, 10.04); Calibrated: 5/17/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/11/2016
Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch, Antenna 3

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 29.68 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 1.57 W/kg
SAR(1 g) = 0.734 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used (interpolated):
 $f = 1732.4 \text{ MHz}$; $\sigma = 1.351 \text{ S/m}$; $\epsilon_r = 38.785$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-15-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(5.39, 5.39, 5.39); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1750, Left Head, Cheek, Mid.ch

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.45 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 0.298 W/kg
SAR(1 g) = 0.200 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09395

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium: 1900 Head Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.421 \text{ S/m}$; $\epsilon_r = 40.033$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-08-2016; Ambient Temp: 21.4°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 10/27/2015
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.05 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.234 W/kg

SAR(1 g) = 0.158 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09395


Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.421 \text{ S/m}$; $\epsilon_r = 40.033$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-08-2016; Ambient Temp: 21.4°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 10/27/2015
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch

Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 14.75 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.433 W/kg
SAR(1 g) = 0.286 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.87 \text{ S/m}$; $\epsilon_r = 43.019$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 08-15-2016; Ambient Temp: 23.7°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7409; ConvF(10.73, 10.73, 10.73); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset, Antenna 3**


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.63 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.02 W/kg

SAR(1 g) = 0.832 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09361


Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1
Medium: 835 Head Medium parameters used (interpolated):
 $f = 836.5 \text{ MHz}$; $\sigma = 0.886 \text{ S/m}$; $\epsilon_r = 40.229$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 08-10-2016; Ambient Temp: 23.5°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7409; ConvF(10.04, 10.04, 10.04); Calibrated: 5/17/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn859; Calibrated: 5/11/2016
Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset, Antenna 3**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 31.95 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.66 W/kg
SAR(1 g) = 0.780 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346


Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used (interpolated):
 $f = 1770 \text{ MHz}$; $\sigma = 1.388 \text{ S/m}$; $\epsilon_r = 38.614$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-15-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(5.39, 5.39, 5.39); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 66 (AWS), Left Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 16.77 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 0.494 W/kg
SAR(1 g) = 0.330 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09353


Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used (interpolated):
 $f = 1860 \text{ MHz}$; $\sigma = 1.401 \text{ S/m}$; $\epsilon_r = 40.112$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-08-2016; Ambient Temp: 21.4°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 10/27/2015
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Left Head, Cheek, Low.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 16.95 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.484 W/kg
SAR(1 g) = 0.334 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346


Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1
Medium: 2300 - 2600 Head Medium parameters used:
 $f = 2310 \text{ MHz}$; $\sigma = 1.63 \text{ S/m}$; $\epsilon_r = 39.487$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-15-2016; Ambient Temp: 22.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(4.73, 4.73, 4.73); Calibrated: 10/29/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 10/27/2015
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 30, Left Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$
Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 12.65 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.334 W/kg
SAR(1 g) = 0.203 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1
Medium: 2300 - 2600 Head Medium parameters used (interpolated):
 $f = 2535 \text{ MHz}$; $\sigma = 1.877 \text{ S/m}$; $\epsilon_r = 38.592$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-15-2016; Ambient Temp: 22.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(4.39, 4.39, 4.39); Calibrated: 10/29/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 10/27/2015
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 7, Left Head, Cheek, Mid.ch, QPSK,
20 MHz Bandwidth, 1 RB, 99 RB Offset**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.596 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.246 W/kg

SAR(1 g) = 0.133 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: 2300 - 2600 Head Medium parameters used (interpolated):
 $f = 2437 \text{ MHz}$; $\sigma = 1.765 \text{ S/m}$; $\epsilon_r = 38.999$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-15-2016; Ambient Temp: 22.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(4.53, 4.53, 4.53); Calibrated: 10/29/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 10/27/2015
Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Left Head,
Cheek, Ch 6, 1 Mbps, Primary Antenna**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (8x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.057 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.935 W/kg

SAR(1 g) = 0.389 W/kg



0 dB = 0.513 W/kg = -2.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486

Communication System: UID 0, IEEE 802.11ac; Frequency: 5690 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used (interpolated):
 $f = 5690 \text{ MHz}$; $\sigma = 4.954 \text{ S/m}$; $\epsilon_r = 35.602$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 08-08-2016; Ambient Temp: 20.1°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN3914; ConvF(4.74, 4.74, 4.74); Calibrated: 2/22/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016
Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11ac, U-NII-2C, 80 MHz Bandwidth,
Left Head, Tilt, Ch 138, 29.3 Mbps, Primary Antenna**


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.837 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 0.321 W/kg



0 dB = 0.967 W/kg = -0.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 1.005 \text{ S/m}$; $\epsilon_r = 54.354$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-17-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(6.24, 6.24, 6.24); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.26 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.633 W/kg
SAR(1 g) = 0.503 W/kg



0 dB = 0.552 W/kg = -2.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 1.005 \text{ S/m}$; $\epsilon_r = 54.354$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-17-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(6.24, 6.24, 6.24); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Bottom Edge, Mid.ch, 2 Tx Slots

Area Scan (10x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 28.58 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 1.21 W/kg
SAR(1 g) = 0.719 W/kg



0 dB = 0.876 W/kg = -0.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 1.005 \text{ S/m}$; $\epsilon_r = 54.354$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-17-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(6.24, 6.24, 6.24); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch, Antenna 1

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.26 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 0.614 W/kg
SAR(1 g) = 0.369 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 1.005 \text{ S/m}$; $\epsilon_r = 54.354$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-17-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(6.24, 6.24, 6.24); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Bottom Edge, Mid.ch, Antenna 1

Area Scan (10x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 23.87 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.862 W/kg
SAR(1 g) = 0.503 W/kg



0 dB = 0.621 W/kg = -2.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1732.4 \text{ MHz}$; $\sigma = 1.469 \text{ S/m}$; $\epsilon_r = 52.097$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.9°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 11/11/2015
Phantom: SAM Left; Type: SAM; Serial: 1688
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1750, Body SAR, Back side, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.27 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.926 W/kg
SAR(1 g) = 0.532 W/kg



0 dB = 0.647 W/kg = -1.89 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403


Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1732.4 \text{ MHz}$; $\sigma = 1.469 \text{ S/m}$; $\epsilon_r = 52.097$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.9°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 11/11/2015
Phantom: SAM Left; Type: SAM; Serial: 1688
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1750, Body SAR, Front side, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.72 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 1.12 W/kg
SAR(1 g) = 0.628 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09403

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.565 \text{ S/m}$; $\epsilon_r = 52.557$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3334; ConvF(4.84, 4.84, 4.84); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 3 Tx Slots


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.28 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.614 W/kg

SAR(1 g) = 0.351 W/kg



0 dB = 0.425 W/kg = -3.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09395

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.563 \text{ S/m}$; $\epsilon_r = 52.999$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.80 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.709 W/kg



0 dB = 0.874 W/kg = -0.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09379


Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1
Medium: 750 Body Medium parameters used (interpolated):
 $f = 707.5 \text{ MHz}$; $\sigma = 0.927 \text{ S/m}$; $\epsilon_r = 55.093$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-09-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset, Antenna 1**

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.67 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.407 W/kg
SAR(1 g) = 0.337 W/kg



0 dB = 0.365 W/kg = -4.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09379


Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1
Medium: 750 Body Medium parameters used (interpolated):
 $f = 707.5 \text{ MHz}$; $\sigma = 0.927 \text{ S/m}$; $\epsilon_r = 55.093$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-09-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 12, Body SAR, Right Edge, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset, Antenna 1**

Area Scan (13x14x1): Measurement grid: dx=5mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.38 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.601 W/kg
SAR(1 g) = 0.431 W/kg



0 dB = 0.492 W/kg = -3.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346


Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.5 \text{ MHz}$; $\sigma = 1.005 \text{ S/m}$; $\epsilon_r = 54.355$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-17-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(6.24, 6.24, 6.24); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset, Antenna 1**

Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 21.07 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.642 W/kg
SAR(1 g) = 0.395 W/kg



0 dB = 0.476 W/kg = -3.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346


Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.5 \text{ MHz}$; $\sigma = 1.005 \text{ S/m}$; $\epsilon_r = 54.355$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-17-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(6.24, 6.24, 6.24); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Bottom Edge, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset, Antenna 1**

Area Scan (11x9x1): Measurement grid: dx=5mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.30 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 0.973 W/kg
SAR(1 g) = 0.564 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346


Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1770 \text{ MHz}$; $\sigma = 1.511 \text{ S/m}$; $\epsilon_r = 51.933$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.9°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 11/11/2015
Phantom: SAM Left; Type: SAM; Serial: 1688
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 66 (AWS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.14 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.635 W/kg
SAR(1 g) = 0.368 W/kg



0 dB = 0.445 W/kg = -3.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346


Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1770 \text{ MHz}$; $\sigma = 1.511 \text{ S/m}$; $\epsilon_r = 51.933$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.9°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 11/11/2015
Phantom: SAM Left; Type: SAM; Serial: 1688
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 66 (AWS), Body SAR, Front side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.85 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 1.30 W/kg
SAR(1 g) = 0.722 W/kg



0 dB = 0.847 W/kg = -0.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09379

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.524 \text{ S/m}$; $\epsilon_r = 52.905$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-18-2018; Ambient Temp: 22.1°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3334; ConvF(4.84, 4.84, 4.84); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, Low.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.72 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.921 W/kg



0 dB = 1.10 W/kg = 0.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2300 Body Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.852 \text{ S/m}$; $\epsilon_r = 51.566$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(7.37, 7.37, 7.37); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASYS2, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 30, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.01 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.536 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2300 Body Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.852 \text{ S/m}$; $\epsilon_r = 51.566$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(7.37, 7.37, 7.37); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 30, Body SAR, Front side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.03 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.19 W/kg

SAR(1 g) = 0.598 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1
Medium: 2600 Body Medium parameters used (interpolated):
 $f = 2535 \text{ MHz}$; $\sigma = 2.143 \text{ S/m}$; $\epsilon_r = 50.709$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 7, Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (11x19x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.78 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.40 W/kg

SAR(1 g) = 0.666 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09346


Communication System: UID 0, LTE Band 7; Frequency: 2560 MHz; Duty Cycle: 1:1
Medium: 2600 Body Medium parameters used (interpolated):
 $f = 2560 \text{ MHz}$; $\sigma = 2.177 \text{ S/m}$; $\epsilon_r = 50.625$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 7, Body SAR, Bottom Edge, High ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

Area Scan (11x11x1): Measurement grid: dx=5mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 24.29 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 2.43 W/kg
SAR(1 g) = 1.12 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486


Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used (interpolated):
 $f = 2437 \text{ MHz}$; $\sigma = 2.015 \text{ S/m}$; $\epsilon_r = 51.086$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR,
Ch 6, 1 Mbps, Back Side, Secondary Antenna**

Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 12.23 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 0.552 W/kg
SAR(1 g) = 0.270 W/kg



0 dB = 0.322 W/kg = -4.92 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486


Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used (interpolated):
 $f = 2437 \text{ MHz}$; $\sigma = 2.015 \text{ S/m}$; $\epsilon_r = 51.086$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR,
Ch 6, 1 Mbps, Top Edge, Secondary Antenna**

Area Scan (11x11x1): Measurement grid: dx=5mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 13.13 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.702 W/kg
SAR(1 g) = 0.337 W/kg



0 dB = 0.559 W/kg = -2.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used:

$f = 5260 \text{ MHz}$; $\sigma = 5.524 \text{ S/m}$; $\epsilon_r = 46.993$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-12-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7357; ConvF(4.28, 4.28, 4.28); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-2A, 20 MHz Bandwidth, Body SAR,
Ch 52, 6 Mbps, Back Side, Secondary Antenna**


Area Scan (12x21x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 3.535 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 0.289 W/kg

SAR(1 g) = 0.069 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used:

$f = 5200 \text{ MHz}$; $\sigma = 5.442 \text{ S/m}$; $\epsilon_r = 47.077$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-12-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7357; ConvF(4.28, 4.28, 4.28); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, UNII-1, 20 MHz Bandwidth, Body SAR,
Ch 40, 6 Mbps, Top Side, Secondary Antenna**


Area Scan (10x11x1): Measurement grid: dx=5mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 5.882 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.710 W/kg

SAR(1 g) = 0.200 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486

Communication System: UID 0, Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used (interpolated):
 $f = 2480 \text{ MHz}$; $\sigma = 2.068 \text{ S/m}$; $\epsilon_r = 52.217$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.9°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Bluetooth, Body SAR, Ch 78, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (8x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.202 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.0210 W/kg

SAR(1 g) = 0.009 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486

Communication System: UID 0, IEEE 802.11a; Frequency: 5580 MHz; Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used:
 $f = 5580 \text{ MHz}$; $\sigma = 5.956 \text{ S/m}$; $\epsilon_r = 47.732$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(3.63, 3.63, 3.63); Calibrated: 2/22/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016
Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11a, U-NII-2C, 20 MHz Bandwidth,
Phablet SAR, Ch 116, 6 Mbps, Top Side, Secondary Antenna**


Area Scan (10x12x1): Measurement grid: dx=5mm, dy=10mm

Zoom Scan (9x10x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 32.51 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 31.7 W/kg

SAR(10 g) = 0.788 W/kg



0 dB = 13.8 W/kg = 11.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFH910; Type: Portable Handset; Serial: 09486

Communication System: UID 0, Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used (interpolated):
 $f = 2480 \text{ MHz}$; $\sigma = 2.068 \text{ S/m}$; $\epsilon_r = 52.217$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.9°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/14/2016
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: Bluetooth, Phablet SAR, Ch 78, 1 Mbps, Front Side


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.424 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.359 W/kg

SAR(10 g) = 0.051 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.913 \text{ S/m}$; $\epsilon_r = 42.522$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-15-2016; Ambient Temp: 23.7°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7409; ConvF(10.73, 10.73, 10.73); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.25 W/kg

SAR(1 g) = 1.52 W/kg

Deviation(1 g) = -7.54%



0 dB = 2.02 W/kg = 3.05 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.885 \text{ S/m}$; $\epsilon_r = 40.244$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-10-2016; Ambient Temp: 23.5°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7409; ConvF(10.04, 10.04, 10.04); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.64 W/kg

SAR(1 g) = 1.74 W/kg

Deviation(1 g) = -6.65%



0 dB = 2.34 W/kg = 3.69 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.369 \text{ S/m}$; $\epsilon_r = 38.696$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(5.39, 5.39, 5.39); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.02 W/kg

SAR(1 g) = 3.90 W/kg

Deviation(1 g) = 7.73%



0 dB = 4.83 W/kg = 6.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.442 \text{ S/m}$; $\epsilon_r = 39.958$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 21.4°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(5.03, 5.03, 5.03); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.63 W/kg

SAR(1 g) = 4.22 W/kg

Deviation(1 g) = 5.24%



0 dB = 5.37 W/kg = 7.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2300 MHz; Type: D2300V2; Serial: 1064

Communication System: UID 0, CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: 2300 - 2600 Head Medium parameters used:

$f = 2300$ MHz; $\sigma = 1.613$ S/m; $\epsilon_r = 39.507$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(4.73, 4.73, 4.73); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2300 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 9.73 W/kg

SAR(1 g) = 4.83 W/kg

Deviation(1 g) = 1.47%



0 dB = 6.30 W/kg = 7.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2300 - 2600 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.78 \text{ S/m}$; $\epsilon_r = 38.943$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(4.53, 4.53, 4.53); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.8 W/kg

SAR(1 g) = 5.09 W/kg

Deviation(1 g) = -3.60%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1004

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2300 - 2600 Head Medium parameters used:

$f = 2600$ MHz; $\sigma = 1.941$ S/m; $\epsilon_r = 38.323$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.6°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3333; ConvF(4.39, 4.39, 4.39); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 13.1 W/kg

SAR(1 g) = 5.78 W/kg

Deviation(1 g) = 3.77%



0 dB = 7.75 W/kg = 8.89 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used (interpolated):
 $f = 5250 \text{ MHz}$; $\sigma = 4.481 \text{ S/m}$; $\epsilon_r = 36.202$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.1°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN3914; ConvF(5.07, 5.07, 5.07); Calibrated: 2/22/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016
Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.2 W/kg

SAR(1 g) = 3.83 W/kg

Deviation(1 g) = -7.15%



0 dB = 9.12 W/kg = 9.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.86 \text{ S/m}$; $\epsilon_r = 35.746$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.1°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN3914; ConvF(4.66, 4.66, 4.66); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.1 W/kg

SAR(1 g) = 3.83 W/kg

Deviation(1 g) = -9.35%



0 dB = 9.41 W/kg = 9.74 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head Medium parameters used (interpolated):
 $f = 5750 \text{ MHz}$; $\sigma = 5.03 \text{ S/m}$; $\epsilon_r = 35.498$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.1°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN3914; ConvF(4.74, 4.74, 4.74); Calibrated: 2/22/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016
Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 3.70 W/kg

Deviation(1 g) = -7.50%



0 dB = 9.17 W/kg = 9.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054


Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1
Medium: 750 Body Medium parameters used (interpolated):
 $f = 750 \text{ MHz}$; $\sigma = 0.968 \text{ S/m}$; $\epsilon_r = 54.613$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-09-2016; Ambient Temp: 23.1°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Peak SAR (extrapolated) = 2.47 W/kg
SAR(1 g) = 1.71 W/kg
Deviation(1 g) = -0.12%



0 dB = 1.98 W/kg = 2.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.004 \text{ S/m}$; $\epsilon_r = 54.37$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-17-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(6.24, 6.24, 6.24); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 3.13 W/kg

SAR(1 g) = 1.98 W/kg

Deviation(1 g) = 4.21%



0 dB = 2.39 W/kg = 3.78 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750$ MHz; $\sigma = 1.489$ S/m; $\epsilon_r = 52.018$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-08-2016; Ambient Temp: 20.9°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(4.99, 4.99, 4.99); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2015

Phantom: SAM Left; Type: SAM; Serial: 1688

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.50 W/kg

SAR(1 g) = 3.69 W/kg

Deviation(1 g) = -1.07%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.584 \text{ S/m}$; $\epsilon_r = 52.96$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.37 W/kg

SAR(1 g) = 4.09 W/kg

Deviation(1 g) = 4.60%



0 dB = 5.18 W/kg = 7.14 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used (interpolated):
 $f = 1900 \text{ MHz}$; $\sigma = 1.585 \text{ S/m}$; $\epsilon_r = 52.486$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3334; ConvF(4.84, 4.84, 4.84); Calibrated: 11/17/2015;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1415; Calibrated: 11/11/2015
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Peak SAR (extrapolated) = 7.49 W/kg
SAR(1 g) = 4.22 W/kg
Deviation(1 g) = 7.93%



0 dB = 5.34 W/kg = 7.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2300 MHz; Type: D2300V2; Serial: 1064

Communication System: UID 0, CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: 2300-2600 Body Medium parameters used:

$f = 2300$ MHz; $\sigma = 1.842$ S/m; $\epsilon_r = 51.585$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(7.37, 7.37, 7.37); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

2300 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 9.90 W/kg

SAR(1 g) = 4.95 W/kg

Deviation(1 g) = 8.79%



0 dB = 8.06 W/kg = 9.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2300-2600 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.032$ S/m; $\epsilon_r = 51.051$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.0 W/kg

SAR(1 g) = 5.27 W/kg

Deviation(1 g) = 1.54%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2300-2600 Body Medium parameters used:

$f = 2600$ MHz; $\sigma = 2.238$ S/m; $\epsilon_r = 50.493$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-10-2016; Ambient Temp: 23.6°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 13.2 W/kg

SAR(1 g) = 5.95 W/kg

Deviation(1 g) = 8.38%



0 dB = 10.3 W/kg = 10.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.027$ S/m; $\epsilon_r = 52.369$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.9°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.5 W/kg

SAR(1 g) = 5.11 W/kg; SAR(10 g) = 2.36 W/kg

Deviation(1 g) = 0.59%; Deviation(10 g) = -0.84%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used (interpolated):
 $f = 5250 \text{ MHz}$; $\sigma = 5.515 \text{ S/m}$; $\epsilon_r = 46.983$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-12-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7357; ConvF(4.28, 4.28, 4.28); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/19/2016
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.4 W/kg

SAR(1 g) = 3.97 W/kg

Deviation(1 g) = 2.85%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.945 \text{ S/m}$; $\epsilon_r = 46.456$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-12-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7357; ConvF(3.63, 3.63, 3.63); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.8 W/kg

SAR(1 g) = 4.46 W/kg

Deviation(1 g) = 8.91%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used (interpolated):
 $f = 5750 \text{ MHz}$; $\sigma = 6.205 \text{ S/m}$; $\epsilon_r = 46.083$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-12-2016; Ambient Temp: 21.3°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7357; ConvF(3.77, 3.77, 3.77); Calibrated: 4/19/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/19/2016
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 3.88 W/kg

Deviation(1 g) = 0.65%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.525 \text{ S/m}$; $\epsilon_r = 48.292$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.1 W/kg

SAR(10 g) = 1.05 W/kg

Deviation(10 g) = 0.00%



0 dB = 8.76 W/kg = 9.43 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.975 \text{ S/m}$; $\epsilon_r = 47.645$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(3.63, 3.63, 3.63); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.7 W/kg

SAR(10 g) = 1.14 W/kg

Deviation(10 g) = 6.05%



0 dB = 9.68 W/kg = 9.86 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used (interpolated):
 $f = 5750 \text{ MHz}$; $\sigma = 6.21 \text{ S/m}$; $\epsilon_r = 47.41$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-15-2016; Ambient Temp: 22.0°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/18/2016
Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.2 W/kg

SAR(10 g) = 1.00 W/kg

Deviation(10 g) = -4.31%



0 dB = 8.55 W/kg = 9.32 dBW/kg