

EMI TEST REPORT

FCC CERTIFICATION

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Receipt: June 27, 2016

Date of Issue: July 11, 2016

Test Report No. HCT-E-1607-F014

HCT FRN: 0005866421

FCC ID :

ZNFH918

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN, Bluetooth and RFID
Model Name: LG-H918
Additional Model Name: LGH918, H918, LG-H910PR, LGH910PR, H910PR
Test Port: Micro USB / Earphone Port
Date of Test: July 06, 2016 - July 07, 2016

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By



Jea-Woong Lee
Test Engineer
EMC Team
Certification Division

Reviewed By



Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1607-F014	July 11, 2016	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	5
1.3 Test Facility	5
1.4 Tested System Details.....	6
1.5 Cable Description	7
1.6 Noise Suppression Parts on Cable. (I/O Cable)	7
2. DESCRIPTION OF TEST	8
3. PRELIMINARY TEST	11
3.1 Conducted Emission Test	11
3.2 Radiated Emission Test	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
4.1 Conducted Emission Test	12
4.2 Radiated Emission Test	19
5. LIST OF TEST EQUIPMENT	21
6. CONCLUSION	22

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model	LG-H918
Additional Model	LGH918, H918, LG-H910PR, LGH910PR, H910PR
FCC ID	ZNFH918
EUT Type	Multi-band GSM/EDGE/WCDMA/LTE phone with WLAN, Bluetooth and RFID
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12) 704 MHz to 716 MHz (LTE B17) 1 710 MHz to 1 780 MHz (LTE B66)
RX Frequency	869.20 MHz to 893.80 MHz (GSM850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.40 MHz to 891.60 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 729 MHz to 746 MHz (LTE B12) 734 MHz to 746 MHz (LTE B17) 2 110 MHz to 2 200 MHz (LTE B66)



1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014.

Measurement Facilities	Reg. No.
HCT FRN: 0005866421 Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
HCT FRN: 0005866421 Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-H918	LG ZNFH918		Notebook PC, Earphone
USB cable	EAD63912801	Ningbo Broad	-	EUT, Notebook PC
USB cable	EAD63912803	KSD	-	EUT, Notebook PC
USB cable	EAD63912802	CRESYN	-	EUT, Notebook PC
Earphone EAB629105	02	CRESYN	- EUT	
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	Series PPP009L-E	LITE-ON TECHNOLOGY	- Notebook	PC
Gateway TL-WR747N		TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	- Gateway	
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	16 GB	SanDisk	- EUT	



1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y Y		(P,D)1.2
	Earphone	N/A	Y	(D)1.1
Notebook PC	RJ 45	N/A	N	(D)2.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N N/A		(P)1.8
Gateway DC	in	N N/A		(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y Both	End
	Earphone	N	N/A	Y Both	End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9.66	to 56* 56	to 46*
0.5 to 5	9.56		46
5 to 30	9.60		50

**Decreases with the logarithm of the frequency.*



2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



3. PRELIMINARY TEST

3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

3. 2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable of Worst Case	EAD63912801 (Ningbo Broad)
Kind of Test Site	Shielded Room
Temperature	23.6 °C
Relative Humidity	47.7 %
Test Date	July 07, 2016

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.180000	52.0	9.000	L1	9.6	12.5	64.5
0.188000	58.0	9.000	L1	9.6	6.1	64.1
0.202000	55.7	9.000	L1	9.6	7.9	63.5
0.306000	50.4	9.000	L1	9.6	9.6	60.1
0.336000	52.7	9.000	L1	9.6	6.6	59.3
0.342000	52.8	9.000	L1	9.6	6.4	59.2
0.930000	40.3	9.000	L1	9.7	15.7	56.0
0.940000	41.5	9.000	L1	9.7	14.5	56.0
0.944000	42.8	9.000	L1	9.7	13.2	56.0
0.974000	38.5	9.000	L1	9.7	17.5	56.0
1.072000	40.6	9.000	L1	9.7	15.4	56.0
1.078000	37.3	9.000	L1	9.7	18.7	56.0
8.776000	38.4	9.000	L1	10.0	21.6	60.0
8.844000	39.1	9.000	L1	10.0	20.9	60.0
8.848000	37.9	9.000	L1	10.0	22.1	60.0
8.852000	36.2	9.000	L1	10.0	23.8	60.0
8.888000	38.3	9.000	L1	10.0	21.7	60.0
9.088000	37.0	9.000	L1	10.0	23.0	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.186000	40.5	9.000	L1	9.6	13.7	54.2
0.200000	39.2	9.000	L1	9.6	14.4	53.6
0.270000	30.0	9.000	L1	9.6	21.1	51.1
0.306000	29.9	9.000	L1	9.6	20.2	50.1
0.338000	30.2	9.000	L1	9.6	19.0	49.3
0.406000	24.7	9.000	L1	9.7	23.1	47.7
0.942000	22.3	9.000	L1	9.7	23.7	46.0
0.966000	22.2	9.000	L1	9.7	23.8	46.0
0.978000	21.7	9.000	L1	9.7	24.3	46.0
1.072000	21.7	9.000	L1	9.7	24.3	46.0
2.206000	26.8	9.000	L1	9.8	19.2	46.0
2.550000	28.4	9.000	L1	9.8	17.6	46.0
8.750000	22.1	9.000	L1	10.0	27.9	50.0
8.774000	21.3	9.000	L1	10.0	28.7	50.0
8.844000	20.5	9.000	L1	10.0	29.5	50.0
8.852000	20.0	9.000	L1	10.0	30.0	50.0
8.888000	21.1	9.000	L1	10.0	28.9	50.0
9.110000	22.5	9.000	L1	10.0	27.5	50.0



Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.192000	57.7	9.000	N	9.6	6.3	63.9
0.264000	49.2	9.000	N	9.6	12.1	61.3
0.304000	51.6	9.000	N	9.6	8.5	60.1
0.308000	52.7	9.000	N	9.6	7.3	60.0
0.332000	52.4	9.000	N	9.6	7.0	59.4
0.392000	48.8	9.000	N	9.6	9.3	58.0
0.914000	40.9	9.000	N	9.7	15.1	56.0
0.924000	42.4	9.000	N	9.7	13.6	56.0
2.318000	41.6	9.000	N	9.7	14.4	56.0
2.728000	41.7	9.000	N	9.7	14.3	56.0
2.934000	41.8	9.000	N	9.8	14.2	56.0
2.954000	41.7	9.000	N	9.8	14.3	56.0
8.630000	41.4	9.000	N	9.9	18.6	60.0
8.634000	41.0	9.000	N	9.9	19.0	60.0
8.642000	38.6	9.000	N	9.9	21.4	60.0
8.682000	40.1	9.000	N	10.0	19.9	60.0
8.942000	39.6	9.000	N	10.0	20.4	60.0
9.006000	38.7	9.000	N	10.0	21.3	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.192000	40.8	9.000	N	9.6	13.1	53.9
0.248000	30.5	9.000	N	9.6	21.4	51.8
0.264000	28.8	9.000	N	9.6	22.5	51.3
0.304000	31.4	9.000	N	9.6	18.8	50.1
0.334000	30.6	9.000	N	9.6	18.8	49.4
0.390000	26.5	9.000	N	9.6	21.6	48.1
0.914000	20.3	9.000	N	9.7	25.7	46.0
2.714000	27.5	9.000	N	9.7	18.5	46.0
2.934000	27.4	9.000	N	9.8	18.6	46.0
2.966000	28.3	9.000	N	9.8	17.7	46.0
3.066000	29.0	9.000	N	9.8	17.0	46.0
3.238000	27.6	9.000	N	9.8	18.4	46.0
8.572000	27.5	9.000	N	9.9	22.5	50.0
8.642000	27.2	9.000	N	9.9	22.8	50.0
8.682000	29.3	9.000	N	10.0	20.7	50.0
8.940000	25.4	9.000	N	10.0	24.6	50.0
8.978000	24.9	9.000	N	10.0	25.1	50.0
9.048000	26.2	9.000	N	10.0	23.8	50.0



4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable of Worst Case	EAD63912803 (KSD)
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.1 °C
Relative Humidity	53.9 %
Test Date	July 06, 2016

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
49.358878	32.4	132.0	V	28.0	22.9	7.6	40.0
54.086653	34.5	100.0	V	50.0	22.8	5.5	40.0
240.299880	33.5	100.0	H	350.0	21.7	12.5	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	2.15 GHz
Testing Frequency Range	1 GHz to 10.75 GHz
Operation Mode	Data Communication mode
USB Cable of Worst Case	EAD63912801 (Ningbo Broad)
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.1 °C
Relative Humidity	50.4 %
Test Date	July 07, 2016

Frequency (MHz)	Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1400.050100	48.8	400.0	V	13.0	-8.9	25.2	74.0
1999.448898	51.1	99.7	V	219.0	-8.4	22.9	74.0
2599.148297	48.2	349.8	V	217.0	-5.4	25.8	74.0

Frequency (MHz)	CAverage (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1400.050100	45.9	400.0	V	13.0	-8.9	8.1	54.0
1999.448898	33.3	99.7	V	219.0	-8.4	20.7	54.0
2599.148297	32.2	349.8	V	217.0	-5.4	21.8	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	12.28.2015
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	06.09.2016
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	12.28.2015
<input checked="" type="checkbox"/> Software Ro	hde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	03.30.2016
<input type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17.2014
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9168	255	2 year	03.23.2016
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.27.2016
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP MA	4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T D	T3000/69	N/A	-
<input checked="" type="checkbox"/> Software Ro	hde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	03.30.2016
<input type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4000-XP-ET	48709515	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515	N/A -	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.04.2016
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.07.2016
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.07.2014
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.27.2016
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software Ro	hde & Schwarz	EMC32	-	-	-



6. CONCLUSION

The data collected shows that the **EUT Type: CDMA/GSM/WCDMA/LTE Phone with WLAN, Bluetooth and RFID, Model: LG-H918, FCC ID: ZNFH918** complies with §15.107 and §15.109 of the FCC rules.