

# REPORT

## FCC Certification

**Applicant Name:**

LG Electronics MobileComm U.S.A., Inc.

**Address:**

1000 Sylvan Avenue, Englewood Cliffs NJ 07632

**Date of Issue:**

January 20, 2015

**Test Site/Location:**HCT CO., LTD., 74, Seoicheon-ro 578beon-gil,  
Majang-myeon, Icheon-si, Gyeonggi-do, Korea**Report No.:** HCT-R-1501-F040**HCT FRN:** 0005866421**FCC ID:****ZNFH955P****APPLICANT:****LG Electronics MobileComm U.S.A., Inc.****FCC Model(s):**

LG-H955p

**Additional FCC Model(s):**H955P, LGH955P, LG-H955p, H955p, LGH955p, LG-H955AR, H955AR, LGH955AR,  
LG-H955ar, H955ar, LGH955ar**EUT Type:**

Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/LTE Phone with Bluetooth, WLAN, NFC

**FCC Classification:**

Licensed Portable Transmitter Held to Ear (PCE)

**FCC Rule Part(s):**

§24, §2

| Mode<br>(MHz)     | Tx Frequency<br>(MHz) | Emission<br>Designator | Modulation | ERP               |                     |
|-------------------|-----------------------|------------------------|------------|-------------------|---------------------|
|                   |                       |                        |            | Max. Power<br>(W) | Max. Power<br>(dBm) |
| LTE – Band2 (1.4) | 1850.7 - 1909.3       | 1M09G7D                | QPSK       | 0.463             | 26.66               |
|                   |                       | 1M09W7D                | 16QAM      | 0.467             | 26.69               |
| LTE – Band2 (3)   | 1851.5 - 1908.5       | 2M70G7D                | QPSK       | 0.456             | 26.59               |
|                   |                       | 2M71W7D                | 16QAM      | 0.475             | 26.77               |
| LTE – Band2 (5)   | 1852.5 - 1907.5       | 4M50G7D                | QPSK       | 0.466             | 26.68               |
|                   |                       | 4M51W7D                | 16QAM      | 0.462             | 26.65               |
| LTE – Band2 (10)  | 1855.0 - 1905.0       | 8M98G7D                | QPSK       | 0.493             | 26.93               |
|                   |                       | 8M96W7D                | 16QAM      | 0.481             | 26.82               |
| LTE – Band2 (15)  | 1857.5 - 1902.5       | 13M5G7D                | QPSK       | 0.424             | 26.27               |
|                   |                       | 13M5W7D                | 16QAM      | 0.422             | 26.25               |
| LTE – Band2 (20)  | 1860.0 - 1900.0       | 18M0G7D                | QPSK       | 0.418             | 26.21               |
|                   |                       | 18M0W7D                | 16QAM      | 0.424             | 26.27               |

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

**HCT CO., LTD.** Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998.21 U.S. C.853(a)

  
**Report prepared by**  
**: Kwon Jeong**  
**Test engineer of RF Team**  
**Approved by**  
**: Kyoung Houn Seo**  
**Manager of RF Team**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

| TEST REPORT NO. | DATE             | DESCRIPTION             |
|-----------------|------------------|-------------------------|
| HCT-R-1501-F040 | January 20, 2015 | - First Approval Report |
|                 |                  |                         |
|                 |                  |                         |
|                 |                  |                         |
|                 |                  |                         |

# **Table of Contents**

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION .....</b>                              | <b>5</b>  |
| <b>2. INTRODUCTION .....</b>                                     | <b>6</b>  |
| 2.1. EUT DESCRIPTION.....                                        | 6         |
| 2.2. MEASURING INSTRUMENT CALIBRATION.....                       | 6         |
| 2.3. TEST FACILITY .....                                         | 6         |
| <b>3. DESCRIPTION OF TESTS .....</b>                             | <b>7</b>  |
| 3.1 ERP/EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS..... | 7         |
| 3.2 FREQUENCY RANGE .....                                        | 7         |
| 3.3 PEAK-AVERAGE RATIO .....                                     | 8         |
| 3.4 OCCUPIED BANDWIDTH. ....                                     | 10        |
| 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....     | 11        |
| 3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE ..... | 12        |
| <b>4. LIST OF TEST EQUIPMENT .....</b>                           | <b>13</b> |
| <b>5. SUMMARY OF TEST RESULTS .....</b>                          | <b>14</b> |
| <b>6. SAMPLE CALCULATION .....</b>                               | <b>15</b> |
| <b>7. TEST DATA .....</b>                                        | <b>16</b> |
| 7.1 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT (Band 2).....     | 16        |
| 7.2 RADIATED SPURIOUS EMISSIONS .....                            | 20        |
| 7.2.1 RADIATED SPURIOUS EMISSIONS (1.4 MHz Band 2 LTE) .....     | 20        |
| 7.2.2 RADIATED SPURIOUS EMISSIONS (3 MHz Band 2 LTE).....        | 21        |
| 7.2.3 RADIATED SPURIOUS EMISSIONS (5 MHz Band 2 LTE).....        | 22        |
| 7.2.4 RADIATED SPURIOUS EMISSIONS (10 MHz Band 2 LTE).....       | 23        |
| 7.2.5 RADIATED SPURIOUS EMISSIONS (15 MHz Band 2 LTE).....       | 24        |
| 7.2.6 RADIATED SPURIOUS EMISSIONS (20 MHz Band 2 LTE).....       | 25        |
| 7.3 PEAK-TO-AVERAGE RATIO .....                                  | 26        |
| 7.4 OCCUPIED BANDWIDTH .....                                     | 27        |
| 7.5 CONDUCTED SPURIOUS EMISSIONS .....                           | 28        |
| 7.5.1 BAND EDGE.....                                             | 28        |
| 7.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE ..... | 29        |
| 7.6.1 FREQUENCY STABILITY (1.4 MHz Band 2 LTE).....              | 29        |
| 7.6.2 FREQUENCY STABILITY (3 MHz Band 2 LTE).....                | 30        |

---

|                                                     |    |
|-----------------------------------------------------|----|
| 7.6.3 FREQUENCY STABILITY (5 MHz Band 2 LTE) .....  | 31 |
| 7.6.4 FREQUENCY STABILITY (10 MHz Band 2 LTE) ..... | 32 |
| 7.6.5 FREQUENCY STABILITY (15 MHz Band 2 LTE) ..... | 33 |
| 7.6.6 FREQUENCY STABILITY (20 MHz Band 2 LTE) ..... | 34 |
| 8. TEST PLOTS.....                                  | 35 |

# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

**Applicant Name:** LG Electronics MobileComm U.S.A., Inc.

**Address:** 1000 Sylvan Avenue, Englewood Cliffs NJ 07632

**FCC ID:** ZNFH955P

**Application Type:** Certification

**FCC Classification:** Licensed Portable Transmitter Held to Ear (PCE)

**FCC Rule Part(s):** §24, §2

**EUT Type:** Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/LTE Phone with Bluetooth, WLAN, NFC

**FCC Model(s):** LG-H955p

**Additional FCC Model(s):** H955P, LGH955P, LG-H955p, H955p, LGH955p, LG-H955AR, H955AR, LGH955AR, LG-H955ar, H955ar, LGH955ar

**Tx Frequency:** 1850.7 MHz – 1909.3 MHz (LTE – Band2 (1.4 MHz))  
1851.5 MHz – 1908.5 MHz (LTE – Band2 (3 MHz))  
1852.5 MHz – 1907.5 MHz (LTE – Band2 (5 MHz))  
1855.0 MHz – 1905.0 MHz (LTE – Band2 (10 MHz))  
1857.5 MHz – 1902.5 MHz (LTE – Band2 (15 MHz))  
1860.0 MHz – 1900.0 MHz (LTE – Band2 (20 MHz))

**Max. RF Output Power:**

|                    |                              |
|--------------------|------------------------------|
| Band 2 (1.4 MHz) : | 0.463 W (QPSK) (26.66 dBm)   |
|                    | 0.467 W (16-QAM) (26.69 dBm) |
| Band 2 (3 MHz) :   | 0.456 W (QPSK) (26.59 dBm)   |
|                    | 0.475 W (16-QAM) (26.77 dBm) |
| Band 2 (5 MHz) :   | 0.466 W (QPSK) (26.68 dBm)   |
|                    | 0.462 W (16-QAM) (26.65 dBm) |
| Band 2 (10 MHz) :  | 0.493 W (QPSK) (26.93 dBm)   |
|                    | 0.481 W (16-QAM) (26.82 dBm) |
| Band 2 (15 MHz) :  | 0.424 W (QPSK) (26.27 dBm)   |
|                    | 0.422 W (16-QAM) (26.25 dBm) |
| Band 2 (20 MHz) :  | 0.418 W (QPSK) (26.21 dBm)   |
|                    | 0.424 W (16-QAM) (26.27 dBm) |

**Emission Designator(s):**

|                    |                                   |
|--------------------|-----------------------------------|
| Band 2 (1.4 MHz) : | 1M09G7D (QPSK) / 1M09W7D (16-QAM) |
| Band 2 (3 MHz) :   | 2M70G7D (QPSK) / 2M71W7D (16-QAM) |
| Band 2 (5 MHz) :   | 4M50G7D (QPSK) / 4M51W7D (16-QAM) |
| Band 2 (10 MHz) :  | 8M98G7D (QPSK) / 8M96W7D (16-QAM) |
| Band 2 (15 MHz) :  | 13M5G7D (QPSK) / 13M5W7D (16-QAM) |
| Band 2 (20 MHz) :  | 18M0G7D (QPSK) / 18M0W7D (16-QAM) |

**Date(s) of Tests:** December 11, 2014 ~ January 06, 2015

**Antenna Specification**

Manufacturer: AT & C Co., Ltd.

Antenna type: Internal Antenna

Peak Gain: Band 2 : -1.04 dBi

## **2. INTRODUCTION**

### **2.1. EUT DESCRIPTION**

The LG Electronics MobileComm U.S.A., Inc. LG-H955p Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/LTE Phone with Bluetooth, WLAN, NFC consists of LTE 2.

### **2.2. MEASURING INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **2.3. TEST FACILITY**

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea.

### 3. DESCRIPTION OF TESTS

#### 3.1 ERP/EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS

##### ERP/EIRP

Note: ERP(Effective Radiated Power), EIRP(Equivalent Isotropic Radiated Power)

##### Test Procedure

Radiated emission measurements are performed in the Fully-anechoic chamber. The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-C-2004 Clause 2.2.17. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission. The level and position of the maximized emission is recorded with the spectrum analyzer using a positive peak detector.

A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.


The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

##### Radiated spurious emissions

: Frequency Range : 30 MHz ~ 10<sup>th</sup> Harmonics of highest channel fundamental frequency.

#### 3.2 FREQUENCY RANGE

§ 24.229: PCS – Mobile Frequency Blocks



### 3.3 PEAK-AVERAGE RATIO.

#### Test Procedure

Peak to Average Power Ratio is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 5.7.

#### - Section 5.7.1 CCDF Procedure

- a) Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- b) Set the number of counts to a value that stabilizes the measured CCDF curve;
- c) Set the measurement interval as follows:
  - 1) for continuous transmissions, set to 1 ms,
  - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- d) Record the maximum PAPR level associated with a probability of 0.1%.

#### - Section 5.7.2 Alternate Procedure

Use one of the procedures presented in 5.1 to measure the total peak power and record as  $P_{Pk}$ . Use one of the applicable procedures presented 5.2 to measure the total average power and record as  $P_{Avg}$ . Determine the P.A.R. from:  $P.A.R_{(dB)} = P_{Pk (dBm)} - P_{Avg (dBm)}$  ( $P_{Avg}$  = Average Power + Duty cycle Factor)

#### 5.1.1 Peak power measurements with a spectrum/signal analyzer or EMI receiver

The following procedure can be used to determine the total peak output power.

- a) Set the RBW  $\geq$  OBW.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Set span  $\geq 2 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Ensure that the number of measurement points  $\geq$  span/RBW.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the peak amplitude level.



### **5.2.2 Procedures for use with a spectrum/signal analyzer when EUT cannot be configured to transmit continuously and sweep triggering/signal gating cannot be properly implemented**

If the EUT cannot be configured to transmit continuously (burst duty cycle < 98%), then one of the following procedures can be used. The selection of the applicable procedure will depend on the characteristics of the measured burst duty cycle.

Measure the burst duty cycle with a spectrum/signal analyzer or EMC receiver can be used in zero-span mode if the response time and spacing between bins on the sweep are sufficient to permit accurate measurement of the burst on/off time of the transmitted signal.

#### **5.2.2.2 Constant burst duty cycle**


If the measured burst duty cycle is constant (i.e., duty cycle variations are less than  $\pm 2$  percent), then:

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (power averaging).
- g) Set sweep trigger to "free run".
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
- j) Add  $10 \log (1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission).

For example, add  $10 \log (1/0.25) = 6$  dB if the duty cycle is a constant 25%.

### 3.4 OCCUPIED BANDWIDTH.

#### Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

#### Test Procedure

OBW is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 4.2..

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

### 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

#### Test Procedure

Spurious and harmonic emissions at antenna terminal is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 6.0.

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the -13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 30 MHz to 10<sup>th</sup> Harmonics. A display line was placed at -13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.


- Band Edge Requirement : In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13 dBm.

**NOTES:** The analyzer plot offsets were determined by below conditions.

- For LTE Band 2, total offset 27.4 dBm = 20 dBm attenuator + 6 dBm Divider + 1.4 dBm RF cables.

### 3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

#### Test Set-up



\* Nominal Operating Voltage

#### Test Procedure

Frequency stability is tested in accordance with ANSI/TIA-603-C-2004 section 2.2.2

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from the end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block(LTE Band2).

#### Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

## 4. LIST OF TEST EQUIPMENT

| Manufacture       | Model/ Equipment                            | Serial Number          | Calibration Interval | Calibration Due |
|-------------------|---------------------------------------------|------------------------|----------------------|-----------------|
| Agilent           | N1921A/ Power Sensor                        | MY45241059             | Annual               | 07/09/2015      |
| Agilent           | N1911A/ Power Meter                         | MY45100523             | Annual               | 01/24/2015      |
| MITEQ             | AMF-6D-001180-35-20P/AMP                    | 1081666                | Annual               | 09/04/2015      |
| Wainwright        | WHK1.2/15G-10EF/H.P.F                       | 4                      | Annual               | 06/17/2015      |
| Wainwright        | WRCJV2400/2483.5-2370/2520-60/12SS / B.R.F. | 1                      | Annual               | 06/17/2015      |
| Wainwright        | WHK3.3/18G-10EF/H.P.F                       | 2                      | Annual               | 06/17/2015      |
| Hewlett Packard   | 11667B / Power Splitter                     | 10545                  | Annual               | 02/22/2015      |
| Hewlett Packard   | 11667B / Power Splitter                     | 11275                  | Annual               | 05/19/2015      |
| Digital           | EP-3010/ Power Supply                       | 3110117                | Annual               | 10/29/2015      |
| Schwarzbeck       | UHAP/ Dipole Antenna                        | 557                    | Biennial             | 03/05/2015      |
| Schwarzbeck       | UHAP/ Dipole Antenna                        | 558                    | Biennial             | 05/03/2015      |
| Korea Engineering | KR-1005L / Chamber                          | KRAC05063-3CH          | Annual               | 10/29/2015      |
| Schwarzbeck       | BBHA 9120D/ Horn Antenna                    | 147                    | Biennial             | 09/01/2016      |
| Schwarzbeck       | BBHA 9120D/ Horn Antenna                    | 1151                   | Biennial             | 10/05/2015      |
| Schwarzbeck       | BBHA 9170/ Horn Antenna(15~40GHz)           | BBHA9170541            | Biennial             | 07/05/2015      |
| Agilent           | E4440A/Spectrum Analyzer                    | US45303008             | Annual               | 04/09/2015      |
| WEINSCHL          | ATTENUATOR                                  | BR0592                 | Annual               | 10/22/2015      |
| REOHDE&SCHWARZ    | FSV40/Spectrum Analyzer                     | 1307.9002K40-100931-NK | Annual               | 06/09/2015      |
| Agilent           | 8960 (E5515C)/ Base Station                 | MY48360222             | Annual               | 08/26/2015      |
| Anritsu Corp.     | MT8820C/Wideband Radio Communication Tester | 6200863156             | Annual               | 04/01/2015      |

## 5. SUMMARY OF TEST RESULTS

| FCC Part Section(s) | Test Description                                                 | Test Limit                                                                           | Test Condition | Test Result |
|---------------------|------------------------------------------------------------------|--------------------------------------------------------------------------------------|----------------|-------------|
| 2.1049              | Occupied Bandwidth                                               | N/A                                                                                  | CONDUCTED      | PASS        |
| 2.1051, 24.238(a)   | Band Edge / Spurious and Harmonic Emissions at Antenna Terminal. | $< 43 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions |                | PASS        |
| 2.1046              | *Conducted Output Power                                          | N/A                                                                                  |                | PASS        |
| 24.232(d)           | Peak- to- Average Ratio                                          | $< 13 \text{ dB}$                                                                    |                | PASS        |
| 2.1055, 24.235      | Frequency stability / variation of ambient temperature           | Emission must remain in band                                                         |                | PASS        |
| 24.232(c)           | Equivalent Isotropic Radiated Power                              | $< 2 \text{ Watts max. EIRP}$                                                        | RADIATED       | PASS        |
| 2.1053, 24.238(a)   | Radiated Spurious and Harmonic Emissions                         | $< 43 + 10\log_{10}(P[\text{Watts}])$ for all out-of band emissions                  |                | PASS        |

\*See SAR Report

## 6. SAMPLE CALCULATION

### A. EIRP Sample Calculation

| Mode      | Ch./ Freq. |            | Measured<br>Level(dBm) | Substitute<br>LEVEL(dBm) | Ant. Gain<br>(dBi) | C.L  | Pol. | EIRP  |       |
|-----------|------------|------------|------------------------|--------------------------|--------------------|------|------|-------|-------|
|           | channel    | Freq.(MHz) |                        |                          |                    |      |      | W     | dBm   |
| LTE Band2 | 18607      | 1850.7     | -15.45                 | 19.20                    | 10.04              | 1.83 | H    | 0.551 | 27.41 |

**EIRP = SubstituteLEVEL(dBm) + Ant. Gain – CL(Cable Loss)**

- 1) The EUT mounted on a wooden tripod is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power(EIRP).

### B. Emission Designator

#### **QPSK Modulation(For example)**

**Emission Designator = 4M48G7D**

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

#### **16QAM Modulation(For example)**

**Emission Designator = 4M48W7D**

LTE BW = 4.48 MHz

W = main carrier modulated in a combination of two

or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

## 7. TEST DATA

### 7.1 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT (Band 2)

| Freq<br>(MHz) | Band<br>Width<br>(MHz) | Modulation | Measured<br>Level (dBm) | Substitute<br>Level (dBm) | Ant.<br>Gain(dBi) | C.L  | Pol | EIRP  |       |
|---------------|------------------------|------------|-------------------------|---------------------------|-------------------|------|-----|-------|-------|
|               |                        |            |                         |                           |                   |      |     | W     | dBm   |
| 1850.7        | 1.4                    | QPSK       | -17.60                  | 17.05                     | 10.04             | 1.83 | H   | 0.336 | 25.26 |
|               |                        | 16-QAM     | -17.24                  | 17.41                     | 10.04             | 1.83 | H   | 0.365 | 25.62 |
| 1880.0        |                        | QPSK       | -16.50                  | 18.47                     | 10.04             | 1.85 | H   | 0.463 | 26.66 |
|               |                        | 16-QAM     | -16.47                  | 18.50                     | 10.04             | 1.85 | H   | 0.467 | 26.69 |
| 1909.3        |                        | QPSK       | -16.96                  | 18.06                     | 10.05             | 1.88 | H   | 0.420 | 26.23 |
|               |                        | 16-QAM     | -16.88                  | 18.14                     | 10.05             | 1.88 | H   | 0.428 | 26.31 |

Equivalent Isotropic Radiated Power Output Data (1.4 MHz Band 2 LTE)

Note: Worst case is 1 resource block.

| Freq<br>(MHz) | Band<br>Width<br>(MHz) | Modulation | Measured<br>Level (dBm) | Substitute<br>Level (dBm) | Ant.<br>Gain(dBi) | C.L  | Pol | EIRP  |       |
|---------------|------------------------|------------|-------------------------|---------------------------|-------------------|------|-----|-------|-------|
|               |                        |            |                         |                           |                   |      |     | W     | dBm   |
| 1851.5        | 3                      | QPSK       | -16.78                  | 17.87                     | 10.04             | 1.83 | H   | 0.406 | 26.08 |
|               |                        | 16-QAM     | -16.69                  | 17.96                     | 10.04             | 1.83 | H   | 0.414 | 26.17 |
| 1880.0        |                        | QPSK       | -16.57                  | 18.40                     | 10.04             | 1.85 | H   | 0.456 | 26.59 |
|               |                        | 16-QAM     | -16.39                  | 18.58                     | 10.04             | 1.85 | H   | 0.475 | 26.77 |
| 1908.5        |                        | QPSK       | -17.48                  | 17.54                     | 10.05             | 1.88 | H   | 0.372 | 25.71 |
|               |                        | 16-QAM     | -17.29                  | 17.73                     | 10.05             | 1.88 | H   | 0.389 | 25.90 |

Equivalent Isotropic Radiated Power Output Data (3 MHz Band 2 LTE)

Note: Worst case is 1 resource block.



| Freq<br>(MHz) | Band<br>Width<br>(MHz) | Modulation | Measured<br>Level (dBm) | Substitute<br>Level (dBm) | Ant.<br>Gain(dBi) | C.L  | Pol | EIRP  |       |
|---------------|------------------------|------------|-------------------------|---------------------------|-------------------|------|-----|-------|-------|
|               |                        |            |                         |                           |                   |      |     | W     | dBm   |
| 1852.5        | 5                      | QPSK       | -16.50                  | 18.15                     | 10.04             | 1.83 | H   | 0.433 | 26.36 |
|               |                        | 16-QAM     | -16.80                  | 17.85                     | 10.04             | 1.83 | H   | 0.404 | 26.06 |
| 1880.0        |                        | QPSK       | -16.48                  | 18.49                     | 10.04             | 1.85 | H   | 0.466 | 26.68 |
|               |                        | 16-QAM     | -16.51                  | 18.46                     | 10.04             | 1.85 | H   | 0.462 | 26.65 |
| 1907.5        |                        | QPSK       | -17.01                  | 18.01                     | 10.05             | 1.88 | H   | 0.415 | 26.18 |
|               |                        | 16-QAM     | -16.90                  | 18.12                     | 10.05             | 1.88 | H   | 0.426 | 26.29 |

**Equivalent Isotropic Radiated Power Output Data (5 MHz Band 2 LTE)**

Note: Worst case is 1 resource block.

| Freq<br>(MHz) | Band<br>Width<br>(MHz) | Modulation | Measured<br>Level (dBm) | Substitute<br>Level (dBm) | Ant.<br>Gain(dBi) | C.L  | Pol | EIRP  |       |
|---------------|------------------------|------------|-------------------------|---------------------------|-------------------|------|-----|-------|-------|
|               |                        |            |                         |                           |                   |      |     | W     | dBm   |
| 1855.0        | 10                     | QPSK       | -16.90                  | 17.91                     | 10.04             | 1.83 | H   | 0.409 | 26.12 |
|               |                        | 16-QAM     | -16.84                  | 17.97                     | 10.04             | 1.83 | H   | 0.415 | 26.18 |
| 1880.0        |                        | QPSK       | -16.84                  | 18.13                     | 10.04             | 1.85 | H   | 0.429 | 26.32 |
|               |                        | 16-QAM     | -16.75                  | 18.22                     | 10.04             | 1.85 | H   | 0.438 | 26.41 |
| 1905.0        |                        | QPSK       | -16.26                  | 18.76                     | 10.05             | 1.88 | H   | 0.493 | 26.93 |
|               |                        | 16-QAM     | -16.37                  | 18.65                     | 10.05             | 1.88 | H   | 0.481 | 26.82 |

**Equivalent Isotropic Radiated Power Output Data (10 MHz Band 2 LTE)**

Note: Worst case is 1 resource block.

| Freq<br>(MHz) | Band<br>Width<br>(MHz) | Modulation | Measured<br>Level (dBm) | Substitute<br>Level (dBm) | Ant.<br>Gain(dBi) | C.L  | Pol | EIRP  |       |
|---------------|------------------------|------------|-------------------------|---------------------------|-------------------|------|-----|-------|-------|
|               |                        |            |                         |                           |                   |      |     | W     | dBm   |
| 1857.5        | 15                     | QPSK       | -17.02                  | 17.79                     | 10.04             | 1.83 | H   | 0.398 | 26.00 |
|               |                        | 16-QAM     | -16.99                  | 17.82                     | 10.04             | 1.83 | H   | 0.401 | 26.03 |
| 1880.0        |                        | QPSK       | -16.89                  | 18.08                     | 10.04             | 1.85 | H   | 0.424 | 26.27 |
|               |                        | 16-QAM     | -16.91                  | 18.06                     | 10.04             | 1.85 | H   | 0.422 | 26.25 |
| 1902.5        |                        | QPSK       | -17.37                  | 17.41                     | 10.05             | 1.87 | H   | 0.362 | 25.59 |
|               |                        | 16-QAM     | -17.24                  | 17.54                     | 10.05             | 1.87 | H   | 0.373 | 25.72 |

**Equivalent Isotropic Radiated Power Output Data (15 MHz Band 2 LTE)**

Note: Worst case is 1 resource block.

| Freq<br>(MHz) | Band<br>Width<br>(MHz) | Modulation | Measured<br>Level (dBm) | Substitute<br>Level (dBm) | Ant.<br>Gain(dBi) | C.L  | Pol | EIRP  |       |
|---------------|------------------------|------------|-------------------------|---------------------------|-------------------|------|-----|-------|-------|
|               |                        |            |                         |                           |                   |      |     | W     | dBm   |
| 1860.0        | 20                     | QPSK       | -16.81                  | 18.00                     | 10.04             | 1.83 | H   | 0.418 | 26.21 |
|               |                        | 16-QAM     | -16.75                  | 18.06                     | 10.04             | 1.83 | H   | 0.424 | 26.27 |
| 1880.0        |                        | QPSK       | -17.51                  | 17.46                     | 10.04             | 1.85 | H   | 0.367 | 25.65 |
|               |                        | 16-QAM     | -17.34                  | 17.63                     | 10.04             | 1.85 | H   | 0.382 | 25.82 |
| 1900.0        |                        | QPSK       | -17.14                  | 17.64                     | 10.05             | 1.87 | H   | 0.382 | 25.82 |
|               |                        | 16-QAM     | -17.02                  | 17.76                     | 10.05             | 1.87 | H   | 0.393 | 25.94 |

**Equivalent Isotropic Radiated Power Output Data ( 20 MHz Band 2 LTE)**

Note: Worst case is 1 resource block.

#### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. Turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading.

The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is x plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

## 7.2 RADIATED SPURIOUS EMISSIONS

### 7.2.1 RADIATED SPURIOUS EMISSIONS (1.4 MHz Band 2 LTE)

- ☐ OPERATING FREQUENCY : 1880.00 MHz  
☐ MEASURED OUTPUT POWER: 26.69 dBm = 0.467 W  
☐ MODULATION SIGNAL: 1.4 MHz 16-QAM  
☐ DISTANCE: 3 meters  
☐ LIMIT:  $43 + 10 \log_{10}(W) =$  39.69 dBc

| Ch                | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L  | Pol | EIRP (dBm) | dBc   |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|------------|-------|
| 18607<br>(1850.7) | 3,701.40   | -56.61               | 12.32           | -58.39                 | 2.64 | H   | -48.71     | 75.40 |
|                   | 5,552.10   | -43.48               | 13.02           | -39.94                 | 3.39 | H   | -30.31     | 57.00 |
|                   | 7,402.80   | -58.77               | 11.06           | -46.36                 | 4.08 | H   | -39.38     | 66.07 |
| 18900<br>(1880.0) | 3,760.00   | -56.33               | 12.29           | -58.03                 | 2.67 | H   | -48.41     | 75.10 |
|                   | 5,640.00   | -43.33               | 13.12           | -39.92                 | 3.51 | H   | -30.31     | 57.00 |
|                   | 7,520.00   | -58.63               | 11.09           | -47.11                 | 4.38 | H   | -40.40     | 67.09 |
| 19193<br>(1909.3) | 3,818.60   | -58.80               | 12.28           | -59.89                 | 2.70 | H   | -50.31     | 77.00 |
|                   | 5,727.90   | -39.51               | 13.06           | -35.89                 | 3.57 | H   | -26.40     | 53.09 |
|                   | 7,637.20   | -55.54               | 11.38           | -43.62                 | 4.04 | H   | -36.28     | 62.97 |

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
  2. We are performed all frequency to 10<sup>th</sup> harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
  3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
  4. Worst case is 1 resource block.

## 7.2.2 RADIATED SPURIOUS EMISSIONS (3 MHz Band 2 LTE)

|                                   |                     |
|-----------------------------------|---------------------|
| ▣ OPERATING FREQUENCY :           | 1880.00 MHz         |
| ▣ MEASURED OUTPUT POWER:          | 26.77 dBm = 0.475 W |
| ▣ MODULATION SIGNAL:              | 3 MHz 16-QAM        |
| ▣ DISTANCE:                       | 3 meters            |
| ▣ LIMIT: $43 + 10 \log_{10}(W) =$ | 39.77 dBc           |

| Ch                | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L  | Pol | EIRP (dBm) | dBc   |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|------------|-------|
| 18615<br>(1851.5) | 3,703.00   | -58.40               | 12.32           | -60.18                 | 2.64 | H   | -50.50     | 77.27 |
|                   | 5,554.50   | -41.76               | 13.02           | -38.22                 | 3.39 | H   | -28.59     | 55.36 |
|                   | 7,406.00   | -54.71               | 11.05           | -42.27                 | 4.10 | H   | -35.32     | 62.09 |
| 18900<br>(1880.0) | 3,760.00   | -55.53               | 12.29           | -57.23                 | 2.67 | H   | -47.61     | 74.38 |
|                   | 5,640.00   | -38.94               | 13.12           | -35.53                 | 3.51 | H   | -25.92     | 52.69 |
|                   | 7,520.00   | -59.57               | 11.09           | -48.05                 | 4.38 | H   | -41.34     | 68.11 |
| 19185<br>(1908.5) | 3,817.00   | -55.29               | 12.28           | -56.38                 | 2.70 | H   | -46.80     | 73.57 |
|                   | 5,725.50   | -40.57               | 13.06           | -36.95                 | 3.57 | H   | -27.46     | 54.23 |
|                   | 7,634.00   | -57.16               | 11.36           | -45.50                 | 4.09 | H   | -38.23     | 65.00 |

### NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. We are performed all frequency to 10<sup>th</sup> harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

4. Worst case is 1 resource block.

### 7.2.3 RADIATED SPURIOUS EMISSIONS (5 MHz Band 2 LTE)

- ☐ OPERATING FREQUENCY : 1880.00 MHz  
☐ MEASURED OUTPUT POWER: 26.68 dBm = 0.466 W  
☐ MODULATION SIGNAL: 5 MHz QPSK  
☐ DISTANCE: 3 meters  
☐ LIMIT:  $43 + 10 \log_{10}(W) =$  39.68 dBc

| Ch                | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L  | Pol | EIRP (dBm) | dBc   |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|------------|-------|
| 18625<br>(1852.5) | 3,705.00   | -56.12               | 12.31           | -57.86                 | 2.67 | H   | -48.22     | 74.90 |
|                   | 5,557.50   | -42.41               | 13.04           | -39.05                 | 3.41 | H   | -29.42     | 56.10 |
|                   | 7,410.00   | -56.93               | 11.05           | -44.92                 | 4.13 | H   | -38.00     | 64.68 |
| 18900<br>(1880.0) | 3,760.00   | -59.18               | 12.29           | -60.88                 | 2.67 | H   | -51.26     | 77.94 |
|                   | 5,640.00   | -39.31               | 13.12           | -35.90                 | 3.51 | H   | -26.29     | 52.97 |
|                   | 7,520.00   | -59.49               | 11.09           | -47.97                 | 4.38 | H   | -41.26     | 67.94 |
| 19175<br>(1907.5) | 3,815.00   | -56.83               | 12.28           | -57.92                 | 2.70 | H   | -48.34     | 75.02 |
|                   | 5,722.50   | -40.59               | 13.05           | -37.18                 | 3.59 | H   | -27.72     | 54.40 |
|                   | 7,630.00   | -59.15               | 11.36           | -47.49                 | 4.09 | H   | -40.22     | 66.90 |

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
  2. We are performed all frequency to 10<sup>th</sup> harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
  3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
  4. Worst case is 1 resource block.

#### 7.2.4 RADIATED SPURIOUS EMISSIONS (10 MHz Band 2 LTE)

|                                   |                     |
|-----------------------------------|---------------------|
| ▣ OPERATING FREQUENCY :           | 1905.00 MHz         |
| ▣ MEASURED OUTPUT POWER:          | 26.93 dBm = 0.493 W |
| ▣ MODULATION SIGNAL:              | 10 MHz QPSK         |
| ▣ DISTANCE:                       | 3 meters            |
| ▣ LIMIT: $43 + 10 \log_{10}(W) =$ | 39.93 dBc           |

| Ch                | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L  | Pol | EIRP (dBm) | dBc   |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|------------|-------|
| 18650<br>(1855.0) | 3,710.00   | -59.07               | 12.31           | -60.80                 | 2.70 | H   | -51.19     | 78.12 |
|                   | 5,565.00   | -42.32               | 13.05           | -38.96                 | 3.42 | H   | -29.33     | 56.26 |
|                   | 7,420.00   | -56.93               | 11.05           | -44.81                 | 4.17 | H   | -37.93     | 64.86 |
| 18900<br>(1880.0) | 3,760.00   | -57.78               | 12.29           | -59.48                 | 2.67 | H   | -49.86     | 76.79 |
|                   | 5,640.00   | -40.14               | 13.12           | -36.73                 | 3.51 | H   | -27.12     | 54.05 |
|                   | 7,520.00   | -59.38               | 11.09           | -47.86                 | 4.38 | H   | -41.15     | 68.08 |
| 19150<br>(1905.0) | 3,810.00   | -59.88               | 12.29           | -61.28                 | 2.68 | H   | -51.67     | 78.60 |
|                   | 5,715.00   | -38.34               | 13.08           | -34.97                 | 3.56 | H   | -25.45     | 52.38 |
|                   | 7,620.00   | -56.24               | 11.33           | -44.56                 | 3.99 | H   | -37.22     | 64.15 |

**NOTES:** 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. We are performed all frequency to 10<sup>th</sup> harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

4. Worst case is 1 resource block.

## 7.2.5 RADIATED SPURIOUS EMISSIONS (15 MHz Band 2 LTE)

- ☐ OPERATING FREQUENCY : 1880.00 MHz  
☐ MEASURED OUTPUT POWER: 26.27 dBm = 0.424 W  
☐ MODULATION SIGNAL: 15 MHz QPSK  
☐ DISTANCE: 3 meters  
☐ LIMIT:  $43 + 10 \log_{10}(W) =$  39.27 dBc

| Ch                | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L  | Pol | EIRP (dBm) | dBc   |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|------------|-------|
| 18675<br>(1857.5) | 3,715.00   | -55.99               | 12.31           | -57.74                 | 2.68 | H   | -48.11     | 74.38 |
|                   | 5,572.50   | -41.87               | 13.05           | -38.50                 | 3.43 | H   | -28.88     | 55.15 |
|                   | 7,430.00   | -59.66               | 11.04           | -47.61                 | 4.30 | H   | -40.87     | 67.14 |
| 18900<br>(1880.0) | 3,760.00   | -56.04               | 12.29           | -57.74                 | 2.67 | H   | -48.12     | 74.39 |
|                   | 5,640.00   | -39.54               | 13.12           | -36.13                 | 3.51 | H   | -26.52     | 52.79 |
|                   | 7,520.00   | -58.77               | 11.09           | -47.25                 | 4.38 | H   | -40.54     | 66.81 |
| 19125<br>(1902.5) | 3,805.00   | -55.04               | 12.29           | -56.42                 | 2.66 | H   | -46.79     | 73.06 |
|                   | 5,707.50   | -39.18               | 13.11           | -35.70                 | 3.54 | H   | -26.13     | 52.40 |
|                   | 7,610.00   | -59.70               | 11.31           | -48.25                 | 3.97 | H   | -40.91     | 67.18 |

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
  2. We are performed all frequency to 10<sup>th</sup> harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
  3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
  4. Worst case is 1 resource block.



## 7.2.6 RADIATED SPURIOUS EMISSIONS (20 MHz Band 2 LTE)

|                                   |                     |
|-----------------------------------|---------------------|
| ▣ OPERATING FREQUENCY :           | 1860.00 MHz         |
| ▣ MEASURED OUTPUT POWER:          | 26.27 dBm = 0.424 W |
| ▣ MODULATION SIGNAL:              | 20 MHz 16-QAM       |
| ▣ DISTANCE:                       | 3 meters            |
| ▣ LIMIT: $43 + 10 \log_{10}(W) =$ | 39.27 dBc           |

| Ch                | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L  | Pol | EIRP (dBm) | dBc   |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|------------|-------|
| 18700<br>(1860.0) | 3,720.00   | -57.50               | 12.31           | -59.26                 | 2.67 | H   | -49.62     | 75.89 |
|                   | 5,580.00   | -41.93               | 13.04           | -38.67                 | 3.44 | H   | -29.07     | 55.34 |
|                   | 7,440.00   | -59.80               | 11.04           | -47.37                 | 4.24 | H   | -40.57     | 66.84 |
| 18900<br>(1880.0) | 3,760.00   | -58.60               | 12.29           | -60.30                 | 2.67 | H   | -50.68     | 76.95 |
|                   | 5,640.00   | -41.06               | 13.12           | -37.65                 | 3.51 | H   | -28.04     | 54.31 |
|                   | 7,520.00   | -59.65               | 11.09           | -48.13                 | 4.38 | H   | -41.42     | 67.69 |
| 19100<br>(1900.0) | 3,800.00   | -58.11               | 12.30           | -59.52                 | 2.64 | H   | -49.86     | 76.13 |
|                   | 5,700.00   | -41.73               | 13.13           | -38.34                 | 3.47 | H   | -28.68     | 54.95 |
|                   | 7,600.00   | -60.35               | 11.29           | -48.64                 | 4.12 | H   | -41.47     | 67.74 |

### NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. We are performed all frequency to 10<sup>th</sup> harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

4. Worst case is 1 resource block.

### 7.3 PEAK-TO-AVERAGE RATIO

| Band   | Band Width | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Data ( dB ) |
|--------|------------|-----------------|------------|---------------------|-----------------------|-------------|
| Band 2 | 1.4 MHz    | 1880.0          | QPSK       | 6                   | 0                     | 6.02        |
|        |            |                 | 16-QAM     | 6                   | 0                     | 5.32        |
|        | 3 MHz      |                 | QPSK       | 15                  | 0                     | 5.14        |
|        |            |                 | 16-QAM     | 15                  | 0                     | 5.96        |
|        | 5 MHz      |                 | QPSK       | 25                  | 0                     | 4.96        |
|        |            |                 | 16-QAM     | 25                  | 0                     | 5.72        |
|        | 10 MHz     |                 | QPSK       | 50                  | 0                     | 5.00        |
|        |            |                 | 16-QAM     | 50                  | 0                     | 5.77        |
|        | 15 MHz     |                 | QPSK       | 75                  | 0                     | 4.90        |
|        |            |                 | 16-QAM     | 75                  | 0                     | 5.70        |
|        | 20 MHz     |                 | QPSK       | 100                 | 0                     | 5.74        |
|        |            |                 | 16-QAM     | 100                 | 0                     | 4.96        |

- Plots of the EUT's Peak- to- Average Ratio are shown Page 42 ~ 47

## 7.4 OCCUPIED BANDWIDTH

| Band   | Band Width | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Data ( MHz ) |
|--------|------------|-----------------|------------|---------------------|-----------------------|--------------|
| Band 2 | 1.4 MHz    | 1880.0          | QPSK       | 6                   | 0                     | 1.0899       |
|        |            |                 | 16-QAM     | 6                   | 0                     | 1.0948       |
|        | 3 MHz      |                 | QPSK       | 15                  | 0                     | 2.6995       |
|        |            |                 | 16-QAM     | 15                  | 0                     | 2.7075       |
|        | 5 MHz      |                 | QPSK       | 25                  | 0                     | 4.4962       |
|        |            |                 | 16-QAM     | 25                  | 0                     | 4.5076       |
|        | 10 MHz     |                 | QPSK       | 50                  | 0                     | 8.9805       |
|        |            |                 | 16-QAM     | 50                  | 0                     | 8.9641       |
|        | 15 MHz     |                 | QPSK       | 75                  | 0                     | 13.4730      |
|        |            |                 | 16-QAM     | 75                  | 0                     | 13.4700      |
|        | 20 MHz     |                 | QPSK       | 100                 | 0                     | 17.9500      |
|        |            |                 | 16-QAM     | 100                 | 0                     | 18.0070      |

- Plots of the EUT's Occupied Bandwidth are shown Page 36 ~ 41.

## 7.5 CONDUCTED SPURIOUS EMISSIONS

| Band   | Band Width (MHz) | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Frequency of Maximum Harmonic (GHz) | Maximum Data [dBm] |
|--------|------------------|-----------------|------------|---------------------|-----------------------|-------------------------------------|--------------------|
| Band 2 | 1.4              | 1850.7          | QPSK       | 1                   | 0                     | 6.999780                            | -26.58             |
|        |                  | 1880.0          | QPSK       | 1                   | 0                     | 6.974850                            | -25.37             |
|        |                  | 1909.3          | QPSK       | 1                   | 0                     | 6.962890                            | -26.22             |
|        | 3                | 1851.5          | QPSK       | 1                   | 0                     | 6.936470                            | -25.64             |
|        |                  | 1880.0          | QPSK       | 1                   | 0                     | 6.443450                            | -26.61             |
|        |                  | 1908.5          | QPSK       | 1                   | 0                     | 6.982830                            | -25.53             |
|        | 5                | 1852.5          | QPSK       | 1                   | 0                     | 6.957410                            | -25.71             |
|        |                  | 1880.0          | QPSK       | 1                   | 0                     | 6.969870                            | -26.30             |
|        |                  | 1907.5          | QPSK       | 1                   | 0                     | 6.985320                            | -25.81             |
|        | 10               | 1855.0          | QPSK       | 1                   | 0                     | 6.993800                            | -26.62             |
|        |                  | 1880.0          | QPSK       | 1                   | 0                     | 7.628390                            | -26.61             |
|        |                  | 1905.0          | QPSK       | 1                   | 0                     | 6.911540                            | -26.69             |
|        | 15               | 1857.5          | QPSK       | 1                   | 0                     | 6.995290                            | -25.82             |
|        |                  | 1880.0          | QPSK       | 1                   | 0                     | 6.916530                            | -26.23             |
|        |                  | 1902.5          | QPSK       | 1                   | 0                     | 6.982330                            | -25.12             |
|        | 20               | 1860.0          | QPSK       | 1                   | 0                     | 6.370170                            | -26.65             |
|        |                  | 1880.0          | QPSK       | 1                   | 0                     | 6.925000                            | -25.86             |
|        |                  | 1900.0          | QPSK       | 1                   | 0                     | 6.963390                            | -26.67             |

- Plots of the EUT's Conducted Spurious Emissions are shown Page 66 ~ 83.

### 7.5.1 BAND EDGE


- Plots of the EUT's Band Edge are shown Page 48 ~ 65.

## 7.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

### 7.6.1 FREQUENCY STABILITY (1.4 MHz Band 2 LTE)

|                      |                 |
|----------------------|-----------------|
| OPERATING FREQUENCY: | 1880,000,000 Hz |
| CHANNEL:             | 18900 (1.4 MHz) |
| REFERENCE VOLTAGE:   | 3.8 VDC         |
| DEVIATION LIMIT:     | -               |


| Voltage (%)    | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm    |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100%           | 3.80        | +20(Ref)   | 1880 000 005   | 0                    | 0.000 000     | 0.000  |
| 100%           |             | -30        | 1879 999 997   | -7.70                | 0.000 000     | -0.004 |
| 100%           |             | -20        | 1879 999 996   | -8.70                | 0.000 000     | -0.005 |
| 100%           |             | -10        | 1880 000 014   | 9.10                 | 0.000 000     | 0.005  |
| 100%           |             | 0          | 1879 999 999   | -6.50                | 0.000 000     | -0.003 |
| 100%           |             | +10        | 1879 999 999   | -5.90                | 0.000 000     | -0.003 |
| 100%           |             | +30        | 1880 000 013   | 8.00                 | 0.000 000     | 0.004  |
| 100%           |             | +40        | 1879 999 999   | -6.00                | 0.000 000     | -0.003 |
| 100%           |             | +50        | 1879 999 994   | -10.80               | -0.000 001    | -0.006 |
| 115%           | 4.35        | +20        | 1879 999 998   | -7.20                | 0.000 000     | -0.004 |
| Batt. Endpoint | 3.00        | +20        | 1879 999 998   | -6.80                | 0.000 000     | -0.004 |



## 7.6.2 FREQUENCY STABILITY (3 MHz Band 2 LTE)

☐ OPERATING FREQUENCY: 1880,000,000 Hz  
☐ CHANNEL: 18900 (3 MHz)  
☐ REFERENCE VOLTAGE: 3.8 VDC  
☐ DEVIATION LIMIT: -


| Voltage (%)    | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm    |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100%           | 3.80        | +20(Ref)   | 1880 000 008   | 0                    | 0.000 000     | 0.000  |
| 100%           |             | -30        | 1880 000 004   | -3.20                | 0.000 000     | -0.002 |
| 100%           |             | -20        | 1880 000 002   | -5.80                | 0.000 000     | -0.003 |
| 100%           |             | -10        | 1880 000 000   | -7.50                | 0.000 000     | -0.004 |
| 100%           |             | 0          | 1880 000 000   | -7.30                | 0.000 000     | -0.004 |
| 100%           |             | +10        | 1879 999 998   | -9.30                | 0.000 000     | -0.005 |
| 100%           |             | +30        | 1879 999 999   | -8.20                | 0.000 000     | -0.004 |
| 100%           |             | +40        | 1880 000 001   | -6.30                | 0.000 000     | -0.003 |
| 100%           |             | +50        | 1880 000 016   | 8.00                 | 0.000 000     | 0.004  |
| 115%           | 4.35        | +20        | 1879 999 998   | -9.90                | -0.000 001    | -0.005 |
| Batt. Endpoint | 3.00        | +20        | 1880 000 000   | -7.70                | 0.000 000     | -0.004 |



### 7.6.3 FREQUENCY STABILITY (5 MHz Band 2 LTE)

- ☐ OPERATING FREQUENCY: 1880,000,000 Hz  
☐ CHANNEL: 18900 (5 MHz)  
☐ REFERENCE VOLTAGE: 3.8 VDC  
☐ DEVIATION LIMIT: -


| Voltage (%)    | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm    |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100%           | 3.80        | +20(Ref)   | 1880 000 005   | 0                    | 0.000 000     | 0.000  |
| 100%           |             | -30        | 1879 999 997   | -7.80                | 0.000 000     | -0.004 |
| 100%           |             | -20        | 1879 999 996   | -8.70                | 0.000 000     | -0.005 |
| 100%           |             | -10        | 1879 999 996   | -8.40                | 0.000 000     | -0.004 |
| 100%           |             | 0          | 1879 999 999   | -5.40                | 0.000 000     | -0.003 |
| 100%           |             | +10        | 1879 999 997   | -7.60                | 0.000 000     | -0.004 |
| 100%           |             | +30        | 1879 999 998   | -6.70                | 0.000 000     | -0.004 |
| 100%           |             | +40        | 1879 999 996   | -9.20                | 0.000 000     | -0.005 |
| 100%           |             | +50        | 1879 999 998   | -6.40                | 0.000 000     | -0.003 |
| 115%           | 4.35        | +20        | 1880 000 011   | 6.40                 | 0.000 000     | 0.003  |
| Batt. Endpoint | 3.00        | +20        | 1879 999 999   | -5.70                | 0.000 000     | -0.003 |



#### 7.6.4 FREQUENCY STABILITY (10 MHz Band 2 LTE)

- ☐ OPERATING FREQUENCY: 1880,000,000 Hz  
☐ CHANNEL: 18900 (10 MHz)  
☐ REFERENCE VOLTAGE: 3.8 VDC  
☐ DEVIATION LIMIT: -

| Voltage (%)    | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm    |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100%           | 3.80        | +20(Ref)   | 1879 999 991   | 0                    | 0.000 000     | 0.000  |
| 100%           |             | -30        | 1879 999 984   | -6.50                | 0.000 000     | -0.003 |
| 100%           |             | -20        | 1879 999 984   | -6.30                | 0.000 000     | -0.003 |
| 100%           |             | -10        | 1879 999 984   | -6.90                | 0.000 000     | -0.004 |
| 100%           |             | 0          | 1879 999 985   | -6.20                | 0.000 000     | -0.003 |
| 100%           |             | +10        | 1879 999 983   | -7.60                | 0.000 000     | -0.004 |
| 100%           |             | +30        | 1879 999 987   | -4.20                | 0.000 000     | -0.002 |
| 100%           |             | +40        | 1879 999 984   | -6.80                | 0.000 000     | -0.004 |
| 100%           |             | +50        | 1879 999 985   | -5.50                | 0.000 000     | -0.003 |
| 115%           | 4.35        | +20        | 1879 999 981   | -9.50                | -0.000 001    | -0.005 |
| Batt. Endpoint | 3.00        | +20        | 1879 999 984   | -7.00                | 0.000 000     | -0.004 |






### 7.6.5 FREQUENCY STABILITY (15 MHz Band 2 LTE)

- ☐ OPERATING FREQUENCY: 1880,000,000 Hz  
☐ CHANNEL: 18900 (15 MHz)  
☐ REFERENCE VOLTAGE: 3.8 VDC  
☐ DEVIATION LIMIT: -


| Voltage (%)    | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm    |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100%           | 3.80        | +20(Ref)   | 1880 000 007   | 0                    | 0.000 000     | 0.000  |
| 100%           |             | -30        | 1879 999 998   | -9.10                | 0.000 000     | -0.005 |
| 100%           |             | -20        | 1879 999 999   | -8.00                | 0.000 000     | -0.004 |
| 100%           |             | -10        | 1879 999 999   | -7.60                | 0.000 000     | -0.004 |
| 100%           |             | 0          | 1880 000 000   | -6.90                | 0.000 000     | -0.004 |
| 100%           |             | +10        | 1879 999 999   | -7.80                | 0.000 000     | -0.004 |
| 100%           |             | +30        | 1880 000 000   | -6.50                | 0.000 000     | -0.003 |
| 100%           |             | +40        | 1880 000 001   | -5.80                | 0.000 000     | -0.003 |
| 100%           |             | +50        | 1879 999 997   | -9.40                | 0.000 000     | -0.005 |
| 115%           | 4.35        | +20        | 1880 000 000   | -6.20                | 0.000 000     | -0.003 |
| Batt. Endpoint | 3.00        | +20        | 1880 000 001   | -5.70                | 0.000 000     | -0.003 |



### 7.6.6 FREQUENCY STABILITY (20 MHz Band 2 LTE)

- ☐ OPERATING FREQUENCY: 1880,000,000 Hz  
☐ CHANNEL: 18900 (20 MHz)  
☐ REFERENCE VOLTAGE: 3.8 VDC  
☐ DEVIATION LIMIT: -

| Voltage (%)    | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm    |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100%           | 3.80        | +20(Ref)   | 1880 000 005   | 0                    | 0.000 000     | 0.000  |
| 100%           |             | -30        | 1879 999 999   | -5.90                | 0.000 000     | -0.003 |
| 100%           |             | -20        | 1880 000 000   | -5.10                | 0.000 000     | -0.003 |
| 100%           |             | -10        | 1879 999 997   | -7.80                | 0.000 000     | -0.004 |
| 100%           |             | 0          | 1879 999 997   | -7.80                | 0.000 000     | -0.004 |
| 100%           |             | +10        | 1879 999 999   | -5.80                | 0.000 000     | -0.003 |
| 100%           |             | +30        | 1879 999 998   | -6.50                | 0.000 000     | -0.003 |
| 100%           |             | +40        | 1879 999 997   | -8.00                | 0.000 000     | -0.004 |
| 100%           |             | +50        | 1879 999 999   | -6.00                | 0.000 000     | -0.003 |
| 115%           | 4.35        | +20        | 1879 999 999   | -5.50                | 0.000 000     | -0.003 |
| Batt. Endpoint | 3.00        | +20        | 1879 999 996   | -8.50                | 0.000 000     | -0.005 |




## 8. TEST PLOTS


BAND 2. Occupied Bandwidth Plot (1.4M BW Ch.18900 QPSK RB 6\_0)




BAND 2. Occupied Bandwidth Plot (1.4M BW Ch.18900 16QAM RB 6\_0)




BAND 2. Occupied Bandwidth Plot (3M BW Ch.18900 QPSK RB 15\_0)



BAND 2. Occupied Bandwidth Plot (3M BW Ch.18900 16QAM RB 15\_0)




BAND 2. Occupied Bandwidth Plot (5M BW Ch.18900 16QAM RB 25\_0)




BAND 2. Occupied Bandwidth Plot (5M BW Ch.18900 QPSK RB 25\_0)




BAND 2. Occupied Bandwidth Plot (10M BW Ch.18900 QPSK RB 50\_0)




BAND 2. Occupied Bandwidth Plot (10M BW Ch.18900 16QAM RB 50\_0)



BAND 2. Occupied Bandwidth Plot (15M BW Ch.18900 QPSK RB 75\_0)



BAND 2. Occupied Bandwidth Plot (15M BW Ch.18900 16QAM RB 75\_0)







BAND 2. Occupied Bandwidth Plot (20M BW Ch.18900 QPSK RB 100\_0)




BAND 2. Occupied Bandwidth Plot (20M BW Ch.18900 16QAM RB 100\_0)




BAND 2. PAR Plot (1.4M BW Ch.18900 QPSK RB 6\_0)




BAND 2. PAR Plot (1.4M BW Ch.18900 16QAM RB 6\_0)




BAND 2. PAR Plot (3M BW Ch.18900 QPSK RB 15\_0)




BAND 2. PAR Plot (3M BW Ch.18900 16QAM RB 15\_0)




BAND 2. PAR Plot (5M BW Ch.18900 QPSK RB 25\_0)




BAND 2. PAR Plot (5M BW Ch.18900 16QAM RB 25\_0)




BAND 2. PAR Plot (10M BW Ch.18900 QPSK RB 50\_0)




BAND 2. PAR Plot (10M BW Ch.18900 16QAM RB 50\_0)




BAND 2. PAR Plot (15M BW Ch.18900 QPSK RB 75\_0)




BAND 2. PAR Plot (15M BW Ch.18900 16QAM RB 75\_0)




BAND 2. PAR Plot (20M BW Ch.18900 QPSK RB 100\_0)




BAND 2. PAR Plot (20M BW Ch.18900 16QAM RB 100\_0)



BAND 2. Lower Band Edge Plot (1.4M BW Ch.18607 QPSK\_RB1\_Offset 0) -1



BAND 2. Lower Band Edge Plot (1.4M BW Ch.18607 QPSK\_RB6\_Offset 0) -2







BAND 2. Lower Extended Band Edge Plot (1.4M BW Ch.18607 QPSK\_RB6\_0) -3



BAND 2. Lower Band Edge Plot (3M BW Ch.18615 QPSK\_RB1\_Offset 0) -1




BAND 2. Lower Band Edge Plot (3M BW Ch.18615 QPSK\_RB15\_Offset 0) -2




BAND 2. Lower Extended Band Edge Plot (3M BW Ch.18615 QPSK\_RB15\_0) -3



BAND 2. Lower Band Edge Plot (5M BW Ch.18625 QPSK\_RB1\_Offset 0) -1




BAND 2. Lower Band Edge Plot (5M BW Ch.18625 QPSK\_RB25\_Offset 0) -2




BAND 2. Lower Extended Band Edge Plot (5M BW Ch.18625 QPSK\_RB25\_0) -3



BAND 2. Lower Band Edge Plot (10M BW Ch.18650 QPSK\_RB1\_Offset 0) -1




BAND 2. Lower Band Edge Plot (10M BW Ch.18650 QPSK\_RB50\_Offset 0) -2




BAND 2. Lower Extended Band Edge Plot (10M BW Ch.18650 QPSK\_RB50\_0) -3




BAND 2. Lower Band Edge Plot (15M BW Ch.18675 QPSK\_RB75\_Offset 0) -1




BAND 2. Lower Band Edge Plot (15M BW Ch.18675 QPSK\_RB75\_Offset 0) -2



BAND 2. Lower Extended Band Edge Plot (15M BW Ch.18675 QPSK\_RB75\_0) -3




BAND 2. Lower Band Edge Plot (20M BW Ch.18700 QPSK\_RB1\_Offset 0) -1





BAND 2. Lower Band Edge Plot (20M BW Ch.18700 QPSK\_RB100\_Offset 0) -2




BAND 2. Lower Extended Band Edge Plot (20M BW Ch.18700 QPSK\_RB100\_0) -3






BAND 2. Upper Band Edge Plot (1.4M BW Ch.19193 QPSK\_RB1\_Offset 5) -1




BAND 2. Upper Band Edge Plot (1.4M BW Ch.19193 QPSK\_RB6\_Offset 0) -2




BAND 2. Upper Extended Band Edge Plot (1.4M BW Ch.19193 QPSK\_RB6\_0) -3




BAND 2. Upper Band Edge Plot (3M BW Ch.19185 QPSK\_RB1\_Offset 14) -1




BAND 2. Upper Band Edge Plot (3M BW Ch.19185 QPSK\_RB15\_Offset 0) -2




BAND 2. Upper Extended Band Edge Plot (3M BW Ch.19185 QPSK\_RB15 0) -3




BAND 2. Upper Band Edge Plot (5M BW Ch.19175 QPSK\_RB1\_Offset 24) -1




BAND 2. Upper Band Edge Plot (5M BW Ch.19175 QPSK\_RB25\_Offset 0) -2



BAND 2. Upper Extended Band Edge Plot (5M BW Ch.19175 QPSK\_RB25\_0) -3



BAND 2. Upper Band Edge Plot (10M BW Ch.19150 QPSK\_RB1\_Offset 49) -1



The screenshot displays an Agilent Spectrum Analyzer interface. The main plot shows a signal that transitions from a higher power level to a lower one at a frequency of 1.910 GHz. The signal is represented by a yellow trace, and the noise floor is indicated by a green line at -13.00 dBm. The plot is set to a center frequency of 1.910000 GHz with a span of 8.000 MHz. The resolution bandwidth (Res BW) is 100 kHz, and the video bandwidth (VBW) is 300 kHz. The sweep time is 1.00 s (1001 pts). The signal is identified as Mkr1 at 1.910 000 GHz with a power of -26.800 dBm. The interface includes various control panels for frequency, span, and resolution, as well as a status bar at the bottom.

Agilent Spectrum Analyzer - Swept SA

REF: 50.0 AC SENSE: 20 dB

ALIGN: AUTO

DATE: 14:03 AM Dec 31, 2014

FNO: Far Trig: Free Run #Avg Type: Pwr(RMS) #Attenu: 20 dB

IF Gain: Low

Avg Hold: 1/1

TRACE: 2 3 4 5 6

TYPE: MATH

DET: A N N N N N

Ref Offset 27.4 dB

Ref 25.00 dBm

Mkr1 1.910 000 GHz

-26.800 dBm

10 dB/div

Log

15.0

5.00

-5.00

-15.0

-25.0

-35.0

-45.0

-55.0

-65.0

-13.00 dBm

1

Center 1.910000 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 8.000 MHz

#Sweep 1.00 s (1001 pts)

MSG STATUS

Frequency

Auto Tune

Center Freq

1.910000000 GHz

Start Freq

1.906000000 GHz

Stop Freq

1.914000000 GHz

CF Step

800.000 kHz

Auto

Man

Freq Offset

0 Hz

Agilent Spectrum Analyzer - Channel Power


Center Freq: 1.911500000 GHz  
 Trig: Free Run  
 Avg/Hold: 100/100  
 Radio Std: None  
 Radio Device: BTS

Ref Offset: 27.4 dB  
 Ref: 30.00 dBm

Center 1.912 GHz  
 Res BW 75 kHz  
 VBW 750 kHz  
 Span 8 MHz  
 Sweep 1.733 ms

Channel Power: -19.66 dBm / 1 MHz  
 Power Spectral Density: -79.66 dBm / Hz

BAND 2. Upper Band Edge Plot (15M BW Ch.19125 QPSK\_RB1\_Offset 74) -1




BAND 2. Upper Band Edge Plot (15M BW Ch.19125 QPSK\_RB75\_Offset 0) -2






BAND 2. Upper Extended Band Edge Plot (15M BW Ch.19125 QPSK\_RB75\_0) -3




BAND 2. Upper Band Edge Plot (20M BW Ch.19100 QPSK\_RB1\_Offset 99) -1






BAND 2. Upper Band Edge Plot (20M BW Ch.19100 QPSK\_RB100\_Offset 0) -2



BAND 2. Upper Extended Band Edge Plot (20M BW Ch.19100 QPSK\_RB100\_0) -3




BAND 2. Conducted Spurious (18607ch\_1.4MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious (18607ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_1 (18900ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_2 (18900ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_1 (19193ch\_1.4MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (19193ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious (18615ch\_3MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious (18615ch\_3MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_1 (18900ch\_3MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_2 (18900ch\_3MHz\_QPSK\_RB 1\_0)






BAND 2. Conducted Spurious\_1 (19185ch\_3MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_2 (19185ch\_3MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious (18625ch\_5MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious (18625ch\_5MHz\_QPSK\_RB 1\_0)






BAND 2. Conducted Spurious\_1 (18900ch\_5MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (18900ch\_5MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_1 (19175ch\_5MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (19175ch\_5MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_1 (18650ch\_10MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (18650ch\_10MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_1 (18900ch\_10MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (18900ch\_10MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_1 (19150ch\_10MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (19150ch\_10MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_1 (18675ch\_15MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_2 (18675ch\_15MHz\_QPSK\_RB 1\_0)






AND 2. Conducted Spurious\_1 (18900ch\_15MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (18900ch\_15MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_1 (19125ch\_15MHz\_QPSK\_RB 1\_0)




BAND 2. Conducted Spurious\_2 (19125ch\_15MHz\_QPSK\_RB 1\_0)






BAND 2. Conducted Spurious\_1 (18700ch\_20MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (18700ch\_20MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_1 (18900ch\_20MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (18900ch\_20MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_1 (19100ch\_20MHz\_QPSK\_RB 1\_0)



BAND 2. Conducted Spurious\_2 (19100ch\_20MHz\_QPSK\_RB 1\_0)

