

DASY5 Validation Report for Body TSL

Date: 03.25.2019

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 908

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 53.78$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.79, 7.79, 7.79) @ 2450 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0; Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.51 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 27.1 W/kg

SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.91 W/kg

Maximum value of SAR (measured) = 21.4 W/kg



0 dB = 21.4 W/kg = 13.30 dBW/kg



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China


Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





D2450V2, Serial No. 908 Extended Dipole Calibrations

Referring to KDB 865664 D01 v01r02, if dipoles are verified in return loss ($< -20\text{dB}$, within 20% of prior calibration), and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended.

2450V2 – serial no. 908


2450V2 – serial no. 908												
2450 Head							2450 Body					
Date of Measurement	Return-Loss (dB)	Delta (%)	Real Impedance (ohm)	Delta (ohm)	Imaginary Impedance (ohm)	Delta (ohm)	Return-Loss (dB)	Delta (%)	Real Impedance (ohm)	Delta (ohm)	Imaginary Impedance (ohm)	Delta (ohm)
2019.3.25	-21.6		57.3		5.2		-24.1		52.6		5.8	
2020.3.24	-22.7	-0.05	57.5	-0.18	2.4	2.81	-26.1	-0.08	55.01	-2.40	1.493	4.32

<Justification of the extended calibration>


The return loss is $< -20\text{dB}$, within 20% of prior calibration; the impedance is within 5 ohm of prior calibration. Therefore the verification result should support extended calibration.

Dipole Verification Data> D2450V2, serial no. 908

2450MHz – Head



2450MHz – Body





In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client

Sporton

Certificate No: **Z18-60490**

CALIBRATION CERTIFICATE

Object **D2600V2 - SN: 1061**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **December 7, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102196	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Power sensor NRV-Z5	100596	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Reference Probe EX3DV4	SN 7514	27-Aug-18(SPEAG,No.EX3-7514_Aug18)	Aug-19
DAE4	SN 1555	20-Aug-18(SPEAG,No.DAE4-1555_Aug18)	Aug-19
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-18 (CTTL, No.J18X00560)	Jan-19
Network Analyzer E5071C	MY46110673	24-Jan-18 (CTTL, No.J18X00561)	Jan-19

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: December 10, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.2.1495
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2600 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.0	1.96 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.1 $\pm$ 6 %	1.93 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	14.3 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	57.7 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	6.45 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	25.9 mW / g $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.5	2.16 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	51.0 $\pm$ 6 %	2.18 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	---	---

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	13.7 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	54.2 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	6.11 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	24.3 mW / g $\pm$ 18.7 % (k=2)



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Appendix(Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.8Ω- 7.00jΩ
Return Loss	- 23.1dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	45.6Ω- 5.41jΩ
Return Loss	- 22.8dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.012 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

DASY5 Validation Report for Head TSL

Date: 12.06.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1061

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.926$ S/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(6.92, 6.92, 6.92) @ 2600 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 103.5 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 31.0 W/kg


SAR(1 g) = 14.3 W/kg; SAR(10 g) = 6.45 W/kg

Maximum value of SAR (measured) = 24.7 W/kg





Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 12.06.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1061

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.181$ S/m; $\epsilon_r = 51.03$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(7.06, 7.06, 7.06) @ 2600 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.11 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 29.3 W/kg

SAR(1 g) = 13.7 W/kg; SAR(10 g) = 6.11 W/kg

Maximum value of SAR (measured) = 23.4 W/kg





In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China


Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





D2600V2, Serial No. 1061 Extended Dipole Calibrations

Referring to KDB 865664 D01 v01r02, if dipoles are verified in return loss ($< -20\text{dB}$, within 20% of prior calibration), and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended.


2600V2 – serial no. 1061												
	2600 Head						2600 Body					
Date of Measurement	Return-Loss (dB)	Delta (%)	Real Impedance (ohm)	Delta (ohm)	Imaginary Impedance (ohm)	Delta (ohm)	Return-Loss (dB)	Delta (%)	Real Impedance (ohm)	Delta (ohm)	Imaginary Impedance (ohm)	Delta (ohm)
2018.12.07	-23.1		49.8		-7		-22.8		45.6		-5.41	
2019.11.27	-23.0	0.00	48.9	0.90	-6.83	0.17	-22.6	0.01	44.6	1	-5.29	0.12

<Justification of the extended calibration>


The return loss is $< -20\text{dB}$, within 20% of prior calibration; the impedance is within 5 ohm of prior calibration. Therefore the verification result should support extended calibration.

Dipole Verification Data> D2600V2, serial no. 1061

2600MHz – Head



2600MHz – Body





In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

Client : **Sporton**

Certificate No: **Z19-60486**

CALIBRATION CERTIFICATE

Object **DAE4 - SN: 656**

Calibration Procedure(s) **FF-Z11-002-01**
Calibration Procedure for the Data Acquisition Electronics (DAEx)

Calibration date: **December 17, 2019**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22 ± 3) $^{\circ}\text{C}$ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Process Calibrator 753	1971018	24-Jun-19 (CTTL, No.J19X05126)	Jun-20

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: December 18, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g

CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2512

Fax: +86-10-62304633-2504

E-mail: ttl@chinattl.com

[Http://www.chinattl.cn](http://www.chinattl.cn)

Glossary:

DAE

data acquisition electronics

Connector angle

information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters:

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.



In Collaboration with

s p e a g

CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2512

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

Http://www.chinattl.cn

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 μ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	404.164 $\pm$ 0.15% (k=2)	404.676 $\pm$ 0.15% (k=2)	404.945 $\pm$ 0.15% (k=2)
Low Range	3.95208 $\pm$ 0.7% (k=2)	3.96430 $\pm$ 0.7% (k=2)	3.93942 $\pm$ 0.7% (k=2)

Connector Angle

Connector Angle to be used in DASY system	314° $\pm$ 1 °
---	----------------



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Sporton**

Certificate No: **ES3-3293_Nov19**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3293**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v7
Calibration procedure for dosimetric E-field probes**

Calibration date: **November 25, 2019**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	03-Apr-19 (No. 217-02892/02893)	Apr-20
Power sensor NRP-Z91	SN: 103244	03-Apr-19 (No. 217-02892)	Apr-20
Power sensor NRP-Z91	SN: 103245	03-Apr-19 (No. 217-02893)	Apr-20
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-19 (No. 217-02894)	Apr-20
DAE4	SN: 660	07-Oct-19 (No. DAE4-660_Oct19)	Oct-20
Reference Probe ES3DV2	SN: 3013	31-Dec-18 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-19)	In house check: Oct-20

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			
Issued: November 26, 2019			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3293

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.09	0.90	0.71	± 10.1 %
DCP (mV) ^B	105.6	104.0	109.8	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	197.9	±3.5 %	± 4.7 %
		Y	0.0	0.0	1.0		199.0		
		Z	0.0	0.0	1.0		206.6		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 5).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3293**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-4.6
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3293

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^H (mm)	Unc (k=2)
750	41.9	0.89	6.56	6.56	6.56	0.80	1.23	± 12.0 %
835	41.5	0.90	6.39	6.39	6.39	0.80	1.26	± 12.0 %
900	41.5	0.97	6.23	6.23	6.23	0.72	1.30	± 12.0 %
1450	40.5	1.20	5.89	5.89	5.89	0.48	1.49	± 12.0 %
1750	40.1	1.37	5.53	5.53	5.53	0.55	1.38	± 12.0 %
1900	40.0	1.40	5.32	5.32	5.32	0.67	1.30	± 12.0 %
2000	40.0	1.40	5.25	5.25	5.25	0.50	1.55	± 12.0 %
2300	39.5	1.67	4.89	4.89	4.89	0.63	1.42	± 12.0 %
2450	39.2	1.80	4.60	4.60	4.60	0.80	1.33	± 12.0 %
2600	39.0	1.96	4.39	4.39	4.39	0.75	1.41	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-8 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head})
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$





Appendix E. Conducted RF Output Power Table

The detailed power table are shown as follows.

GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame Average Power (dBm)			Tune-up Limit (dBm)
	128	189	251		128	189	251	
	Frequency (MHz)	824.2	836.4	848.6	(dBm)	824.2	836.4	848.6
GSM 1 Tx slot	32.62	32.70	32.85	33.70	23.62	23.70	23.85	24.70
GPRS 1 Tx slot	32.64	32.71	32.88	33.70	23.64	23.71	23.88	24.70
GPRS 2 Tx slots	31.44	31.57	31.24	32.50	25.44	25.57	25.24	26.50
GPRS 3 Tx slots	29.62	29.81	29.55	30.50	25.36	25.55	25.29	26.24
GPRS 4 Tx slots	27.76	27.97	28.03	29.00	24.76	24.97	25.03	26.00
EDGE 1 Tx slot	26.62	26.76	26.88	27.50	17.82	17.76	17.88	18.50
EDGE 2 Tx slots	24.66	24.59	24.73	25.50	18.66	18.59	18.73	19.50
EDGE 3 Tx slots	22.39	22.17	22.44	23.50	18.13	17.91	18.18	19.24
EDGE 4 Tx slots	21.39	21.05	21.33	22.50	18.39	18.05	18.33	19.50

GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame Average Power (dBm)			Tune-up Limit (dBm)
	512	661	810		512	661	810	
	Frequency (MHz)	1522.2	1620	1722.5	1522.2	1620	1722.5	
GSM 1 Tx slot	29.36	29.44	29.59	30.70	20.36	20.44	20.59	21.70
GPRS 1 Tx slot	28.38	28.48	28.50	30.70	20.38	20.48	20.50	21.70
GPRS 2 Tx slots	27.55	27.88	27.73	28.50	21.55	21.89	21.73	22.50
GPRS 3 Tx slots	23.48	23.24	23.44	24.50	19.22	18.98	19.18	20.24
GPRS 4 Tx slots	23.32	23.10	22.91	24.00	20.32	20.10	19.91	21.00
EDGE 1 Tx slot	25.39	25.28	25.47	26.00	16.39	16.28	16.47	17.00
EDGE 2 Tx slots	23.85	23.78	23.84	24.50	17.85	17.78	17.84	18.50
EDGE 3 Tx slots	19.64	19.60	19.66	20.50	15.38	15.34	15.40	16.24
EDGE 4 Tx slots	19.22	19.04	19.08	20.00	16.22	16.04	16.08	17.00

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
Tx Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Frequency (MHz)		9562	9600	9538		1537	1638	1738		4367	4407	4458	
3GPP Rel 99	AMR 12.2Kbps	24.17	24.08	23.94	24.20	22.87	22.89	22.98	23.70	24.56	24.66	24.69	24.70
3GPP Rel 99	RM-C 12.2Kbps	24.18	24.11	23.95	24.20	22.88	22.91	22.99	23.70	24.57	24.67	24.68	24.70
3GPP Rel 6	HSDPA Subtest-1	22.88	22.75	22.69	23.20	21.33	21.42	21.49	22.70	23.24	23.15	23.18	23.70
3GPP Rel 6	HSDPA Subtest-2	22.87	22.77	22.68	23.20	21.31	21.39	21.47	22.70	23.22	23.11	23.16	23.70
3GPP Rel 6	HSDPA Subtest-3	22.35	22.28	22.22	22.70	20.75	20.91	20.99	22.20	22.74	22.67	22.63	23.20
3GPP Rel 6	HSDPA Subtest-4	22.34	22.24	22.19	22.70	20.71	20.90	20.98	22.20	22.73	22.66	22.62	23.20
3GPP Rel 6	DC-HSDPA Subtest-1	22.87	22.75	22.68	23.20	21.32	21.41	21.48	22.70	23.24	23.11	23.14	23.70
3GPP Rel 8	DC-HSDPA Subtest-2	22.87	22.74	22.64	23.20	21.29	21.39	21.48	22.70	23.22	23.09	23.12	23.70
3GPP Rel 8	DC-HSDPA Subtest-3	22.35	22.25	22.23	22.70	20.74	20.91	20.99	22.20	22.74	22.59	22.63	23.20
3GPP Rel 8	DC-HSDPA Subtest-4	22.34	22.22	22.19	22.70	20.68	20.90	20.97	22.20	22.73	22.56	22.62	23.20
3GPP Rel 6	HSUPA Subtest-1	22.87	22.77	22.69	23.20	21.28	21.41	21.48	22.70	23.23	23.07	23.17	23.70
3GPP Rel 6	HSUPA Subtest-2	20.81	20.75	20.65	21.20	20.23	20.39	20.40	20.70	21.20	21.05	21.15	21.70
3GPP Rel 6	HSUPA Subtest-3	21.88	21.74	21.66	22.20	20.29	20.41	20.48	21.70	22.30	22.15	22.17	22.70
3GPP Rel 6	HSUPA Subtest-4	20.87	20.73	20.63	21.20	19.30	19.41	19.48	20.70	21.28	21.15	21.17	21.70
3GPP Rel 6	HSUPA Subtest-5	22.85	22.74	22.69	23.20	21.30	21.38	21.45	22.70	23.11	23.05	23.03	23.70

Band 2 (1900MHz Band) Part 24E									
BW (MHz)	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)	
Channel				18700	18800	19100			
Frequency (MHz)				1860	1880	1900			
20	QPSK	1	0	23.73	24.00	23.89	24.2	0	
20	QPSK	1	49	24.02	24.00	24.08			
20	QPSK	1	99	23.65	23.98	23.91	23.2	1	
20	QPSK	50	0	23.11	23.12	22.94			
20	QPSK	50	24	22.96	23.09	23.01	23.7	0.5	
20	QPSK	50	50	23.01	22.93	22.96			
20	QPSK	100	0	22.91	23.00	22.97	22.7	1.5	
20	16QAM	1	0	22.68	22.85	22.77			
20	16QAM	1	49	22.68	23.03	23.02	21.7	2.5	
20	16QAM	1	99	22.56	23.00	22.77			
20	16QAM	50	0	22.27	22.08	22.04	22.7	0.5	
20	16QAM	50	24	22.07	22.08	22.05			
20	16QAM	50	50	22.02	22.02	22.03	21.7	1.5	
20	16QAM	100	0	22.13	22.12	22.12			
20	64QAM	1	0	22.15	21.75	22.02	22.7	1.5	
20	64QAM	1	49	22.15	21.76	22.10			
20	64QAM	1	99	21.68	21.86	21.98	21.7	2.5	
20	64QAM	50	0	21.21	21.21	21.22			
20	64QAM	50	24	21.31	21.32	21.25	20.7	3	
20	64QAM	50	50	21.27	21.26	21.27			
20	64QAM	100	0	21.13	21.31	21.18			
Channel				18675	18800	19125	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1867.5	1880	1902.5			
15	QPSK	1	0	23.97	23.94	23.95	24.2	0	
15	QPSK	1	37	23.98	23.93	23.97			
15	QPSK	1	74	23.15	23.75	23.83	23.2	1	
15	QPSK	36	0	23.15	23.09	22.95			
15	QPSK	36	20	23.12	22.90	23.00	23.7	0.5	
15	QPSK	36	36	22.87	23.07	22.91			
15	QPSK	75	0	23.09	22.96	22.95	22.7	1.5	
15	16QAM	1	0	22.95	22.68	22.88			
15	16QAM	1	37	23.15	23.01	23.02	22.7	0.5	
15	16QAM	1	74	22.65	22.25	21.74			
15	16QAM	36	0	22.00	22.06	22.16	21.7	1.5	
15	16QAM	36	20	22.06	21.89	22.03			
15	16QAM	36	36	21.91	22.21	21.80	22.7	0.5	
15	16QAM	75	0	22.22	22.07	22.14			
15	64QAM	1	0	21.97	21.84	22.02	22.7	1.5	
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	64QAM	36	20	21.47	21.10	21.38	21.7	1.5	
15	64QAM	36	36	21.44	21.50	21.36			
15	64QAM	75	0	21.28	21.22	21.11	20.7	3	
15	64QAM	1	0	21.97	21.84	22.02			
15	64QAM	1	37	22.07	21.77	21.96			
15	64QAM	1	74	21.68	21.86	21.97	21.7	2.5	
15	64QAM	36	0	21.43	21.29	21.21			
15	6								

Band 7 (2600MHz Band) Part 27										
BW (MHz)	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)		
Channel				25650	21100	21550				
Frequency (MHz)				2510	2535	2560				
20	QPSK	1	0	22.77	22.91	22.78	23.7	0		
20	QPSK	1	48	22.87	22.87	22.87				
20	QPSK	1	96	22.72	22.86	22.78				
20	QPSK	50	0	22.15	22.23	22.21	22.7	1		
20	QPSK	50	24	21.98	22.13	22.17				
20	QPSK	50	50	21.94	22.09	22.20				
20	QPSK	100	0	21.99	22.18	22.17	22.7	1		
20	16QAM	1	0	21.87	21.92	22.01				
20	16QAM	1	48	22.13	22.06	22.16				
20	16QAM	1	96	21.98	22.13	22.14	21.7	2		
20	16QAM	50	0	21.25	21.13	21.20				
20	16QAM	50	24	21.17	21.26	21.11				
20	16QAM	50	50	21.09	21.17	21.20	21.7	2		
20	16QAM	100	0	21.11	21.15	21.13				
20	16QAM	1	0	21.26	21.18	21.11				
20	64QAM	1	48	21.41	21.12	21.58	21.7	2		
20	64QAM	1	96	21.08	21.24	21.40				
20	64QAM	50	0	20.11	20.20	20.19				
20	64QAM	50	24	20.06	20.08	20.25	20.7	3		
20	64QAM	50	50	20.08	20.25	20.27				
20	64QAM	100	0	20.00	20.15	20.14				
Channel				20625	21100	21375				
Frequency (MHz)				2107.5	2535	2562.5				
15	QPSK	1	0	22.82	22.54	22.51	23.7	0		
15	QPSK	1	37	22.78	22.87	22.78				
15	QPSK	1	74	22.76	22.77	22.81				
15	QPSK	36	0	22.08	22.05	22.10	22.7	1		
15	QPSK	36	20	22.07	22.10	22.15				
15	QPSK	36	39	21.94	22.08	22.07				
15	QPSK	75	0	22.00	21.99	22.08	22.7	1		
15	16QAM	1	0	21.82	21.83	21.67				
15	16QAM	1	37	21.99	21.86	21.88				
15	16QAM	1	74	22.06	21.95	21.98	21.7	2		
15	16QAM	36	0	21.06	21.05	21.08				
15	16QAM	36	20	21.15	21.13	21.23				
15	16QAM	36	39	21.03	21.15	21.15	21.7	2		
15	16QAM	75	0	20.88	21.18	21.15				
15	64QAM	1	0	20.86	21.13	20.74				
15	64QAM	1	37	20.79	21.03	21.10	21.7	2		
15	64QAM	1	74	20.85	21.06	21.16				
15	64QAM	36	0	20.16	20.04	20.16				
15	64QAM	36	20	20.20	20.17	20.22	20.7	3		
15	64QAM	36	39	20.03	20.13	20.31				
15	64QAM	75	0	19.97	20.05	20.14				
Channel				20800	21100	21400				
Frequency (MHz)				2505	2535	2560				
10	QPSK	1	0	22.48	22.70	22.76	23.7	0		
10	QPSK	1	25	22.85	22.77	22.86				
10	QPSK	1	49	22.68	22.72	22.76				
10	QPSK	25	0	21.89	22.04	22.12	22.7	1		
10	QPSK	25	12	22.02	22.05	22.14				
10	QPSK	25	25	21.92	22.07	22.09				
10	QPSK	50	0	21.96	21.99	22.11	22.7	1		
10	16QAM	1	0	21.64	22.01	21.89				
10	16QAM	1	25	21.99	21.95	22.05				
10	16QAM	1	49	21.60	21.78	21.64	21.7	2		
10	16QAM	25	0	20.93	20.90	21.19				
10	16QAM	25	12	21.09	21.13	21.25				
10	16QAM	25	25	20.99	21.05	21.16	21.7	2		
10	16QAM	50	0	20.94	20.98	21.06				
10	64QAM	1	0	20.54	20.74	20.55				
10	64QAM	1	25	20.95	20.89	20.87	21.7	2		
10	64QAM	1	49	20.55	20.81	20.86				
10	64QAM	25	0	19.96	20.09	20.18				
10	64QAM	25	12	20.01	20.29	20.19	20.7	3		
10	64QAM	25	25	20.00	20.12	20.16				
10	64QAM	50	0	20.12	20.04	20.16				
Channel				20775	21100	21425				
Frequency (MHz)				2502.5	2535	2567.5				
5	QPSK	1	0	22.42	22.56	22.77	23.7	0		
5	QPSK	1	12	22.70	22.90	22.86				
5	QPSK	1	24	22.55	22.75	22.72				
5	QPSK	12	0	21.83	21.93	21.91	22.7	1		
5	QPSK	12	7	21.81	21.98	22.02				
5	QPSK	12	13	21.77	21.91	21.90				
5	QPSK	25	0	21.79	21.86	21.90	22.7	1		
5	16QAM	1	0	21.47	21.48	21.44				
5	16QAM	1	12	21.61	21.77	21.53				
5	16QAM	1	24	21.44	21.89	21.89	21.7	2		
5	16QAM	12	0	20.89	20.79	21.07				
5	16QAM	12	7	20.66	20.86	21.00				
5	16QAM	12	13	20.74	20.80	20.87	21.7	2		
5	16QAM	25	0	20.66	20.93	20.98				
5	64QAM	1	0	20.42	20.53	20.50				
5	64QAM	1	12	20.60	20.53	20.67	21.7	2		
5	64QAM	1	24	20.44	20.50	20.44				
5	64QAM	12	0	19.89	19.87	19.84				
5	64QAM	12	7	19.75	19.84	19.86	20.7	3		
5	64QAM	12	13	19.71	19.86	19.86				
5	64QAM	25	0	19.74	20.02	19.87				

Band 12 (700MHz Low Band)										
Part 27F(only on channel required)										
BW (MHz)	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)		
Channel				23060	23065	23130				
Frequency (MHz)				704	707.5	711				
10	QPSK	1	0	23.30	23.51	23.20	24.7	0		
10	QPSK	1	25	23.41	23.35	23.19				
10	QPSK	1	49	23.07	23.05	23.06				
10	QPSK	25	0	22.23	22.39	22.34	23.7	1		
10	QPSK	25	12	22.29	22.33	22.38				
10	QPSK	25	25	22.25	22.33	22.38				
10	QPSK	50	0	22.34	22.42	22.41	23.7	1		
10	16QAM	1	0	21.89	21.73	21.87				
10	16QAM	1	25	21.98	21.98	21.81				
10	16QAM	1	49	21.77	21.82	21.84	22.7	2		
10	16QAM	25	0	21.18	21.22	21.44				
10	16QAM	25	12	21.23	21.32	21.49				
10	16QAM	25	25	21.21	21.39	21.38	22.7	2		
10	16QAM	50	0	21.26	21.37	21.43				
10	64QAM	1	0	20.96	21.16	21.24				
10	64QAM	1	25	21.04	21.42	21.42	22.7	2		
10	64QAM	1	49	20.99	21.41	21.21				
10	64QAM	25	0	20.50	20.38	20.72				
10	64QAM	25	12	20.47	20.54	20.77	21.7	3		
10	64QAM	25	25	20.56	20.54	20.78				
10	64QAM	50	0	20.54	20.51	20.60				
Channel				23060	23065	23135	Tune-up limit (dBm)	MPR (dB)		
Frequency (MHz)				701.5	707.5	711.5				
5	QPSK	1	0	23.04	23.13	23.28	24.7	0		
5	QPSK	1	12	23.40	23.18	23.46				
5	QPSK	1	24	23.13	23.24	23.32				
5	QPSK	12	0	22.29	22.29	22.32	23.7	1		
5	QPSK	12	7	22.33	22.33	22.33				
5	QPSK	12	13	22.21	22.37	22.33				
5	QPSK	25	0	22.31	22.29	22.37	23.7	1		
5	16QAM	1	0	22.09	22.35	22.21				
5	16QAM	1	12	22.40	22.00	22.29				
5	16QAM	1	24	22.10	21.90	21.62	22.7	2		
5	16QAM	12	0	21.15	21.28	21.42				
5	16QAM	12	7	21.29	21.21	21.42				
5	16QAM	12	13	21.14	21.33	21.47	22.7	2		
5	16QAM	25	0	21.19	21.30	21.57				
5	64QAM	1	0	21.02	21.09	21.14				
5	64QAM	1	12	21.26	21.35	21.38	22.7	2		
5	64QAM	1	24	21.06	20.91	21.09				
5	64QAM	12	0	20.39	20.28	20.54				
5	64QAM	12	7	20.37	20.37	20.58	21.7	3		
5	64QAM	12	13	20.32	20.56	20.58				
5	64QAM	25	0	20.52	20.58	20.60				
Channel				23065	23065	23165	Tune-up limit (dBm)	MPR (dB)		
Frequency (MHz)				700.5	707.5	714.5				
3	QPSK	1	0	23.41	23.11	23.40	24.7	0		
3	QPSK	1	8	23.34	23.04	23.32				
3	QPSK	1	14	23.40	23.29	23.15				
3	QPSK	8	0	22.22	22.24	22.68	23.7	1		
3	QPSK	8	4	22.33	22.46	22.47				
3	QPSK	8	7	22.47	22.32	22.32				
3	QPSK	15	0	22.34	22.32	22.47	23.7	1		
3	16QAM	1	0	21.75	22.00	22.26				
3	16QAM	1	8	21.74	22.15	22.06				
3	16QAM	1	14	21.90	22.01	22.07	22.7	1		
3	16QAM	8	0	21.31	21.22	21.48				
3	16QAM	8	4	21.44	21.38	21.48				
3	16QAM	8	7	21.55	21.59	21.33	22.7	2		
3	16QAM	15	0	21.40	21.48	21.24				
3	64QAM	1	0	21.25	21.49	21.17				
3	64QAM	1	8	21.22	21.13	21.11	22.7	2		
3	64QAM	1	14	21.30	21.28	21.02				
3	64QAM	8	0	20.56	20.56	20.76				
3	64QAM	8	4	20.51	20.56	20.69	21.7	3		
3	64QAM	8	7	20.63	20.64	20.54				
3	64QAM	15	0	20.48	20.47	20.55				
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)		
Frequency (MHz)				669.7	707.5	716.3				
1.4	QPSK	1	0	23.47	23.37	23.42	24.7	0		
1.4	QPSK	1	3	23.40	23.44	23.36				
1.4	QPSK	1	5	23.29	23.51	23.32				
1.4	QPSK	3	0	23.33	23.45	23.44	23.7	1		
1.4	QPSK	3	1	23.19	23.49	23.50				
1.4	QPSK	3	3	23.48	23.48	23.34				
1.4	QPSK	6	0	22.35	22.27	22.38	23.7	1		
1.4	16QAM	1	0	22.31	22.26	21.98				
1.4	16QAM	1	3	22.11	22.24	21.87				
1.4	16QAM	3	0	21.96	21.96	21.81	23.7	1		
1.4	16QAM	3	1	22.21	22.37	22.17				
1.4	16QAM	3	3	22.50	22.29	22.40				
1.4	16QAM	3	3	22.56	22.12	22.22	22.7	2		
1.4	16QAM	6	0	20.95	21.45	21.15				
1.4	64QAM	1	0	21.42	21.61	21.16				
1.4	64QAM	1	3	21.17	21.42	21.38	22.7	2		
1.4	64QAM	1	5	21.19	21.46	21.35				
1.4	64QAM	3	0	21.34	21.71	21.45				
1.4	64QAM	3	1	21.55	21.77	21.55	21.7	3		
1.4	64QAM	3	3	21.58	21.49	21.60				
1.4	64QAM	6	0	20.33	20.53	20.50				

Band 17 (700MHz Band) Part 27E(only on channel required)									
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. Freq.	Power Middle Ch. Freq.	Power High Ch. Freq.	Tune-up limit (dBm)	MPR (dB)	
Channel				709	710	711			
Frequency (MHz)				23.16	23.49	23.45			
10	QPSK	1	0	23.16	23.49	23.45	24.7	0	
10	QPSK	1	25	23.44	23.42	23.44			
10	QPSK	1	49	23.18	23.13	23.11			
10	QPSK	25	0	22.37	22.38	22.33	23.7	1	
10	QPSK	25	12	22.37	22.33	22.28			
10	QPSK	25	25	22.37	22.30	22.28			
10	QPSK	50	0	22.40	22.41	22.31	23.7	1	
10	16QAM	1	0	21.76	21.95	21.70			
10	16QAM	1	25	21.95	21.74	21.79			
10	16QAM	1	49	21.85	21.71	21.70	22.7	2	
10	16QAM	25	0	21.39	21.38	21.41			
10	16QAM	25	12	21.52	21.62	21.48			
10	16QAM	25	25	21.39	21.47	21.43	22.7	2	
10	16QAM	50	0	21.30	21.31	21.35			
10	64QAM	1	0	21.08	21.39	21.09			
10	64QAM	1	25	21.22	21.32	21.52	22.7	2	
10	64QAM	1	49	21.31	21.09	21.09			
10	64QAM	25	0	20.84	20.45	20.57			
10	64QAM	25	12	20.68	20.61	20.73	21.7	3	
10	64QAM	25	25	20.70	20.55	20.58			
10	64QAM	50	0	20.55	20.62	20.48			
Channel				23755	23790	23825	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				706.5	710	713.5			
5	QPSK	1	0	23.08	23.22	23.00	24.7	0	
5	QPSK	1	12	23.24	23.46	23.32			
5	QPSK	1	24	23.06	23.27	22.96			
5	QPSK	12	0	22.29	22.28	22.27	23.7	1	
5	QPSK	12	7	22.28	22.28	22.27			
5	QPSK	12	13	22.30	22.28	22.27			
5	QPSK	25	0	22.33	22.22	22.22	23.7	1	
5	16QAM	1	0	21.93	22.20	22.36			
5	16QAM	1	12	21.97	22.25	22.39			
5	16QAM	1	24	22.11	22.41	22.21	22.7	2	
5	16QAM	12	0	21.43	21.55	21.46			
5	16QAM	12	7	21.51	21.37	21.52			
5	16QAM	12	13	21.43	21.40	21.48	22.7	2	
5	16QAM	25	0	21.45	21.39	21.30			
5	64QAM	1	0	20.78	20.88	20.94			
5	64QAM	1	12	21.20	21.18	21.05	22.7	2	
5	64QAM	1	24	21.24	20.90	20.76			
5	64QAM	12	0	20.47	20.58	20.37			
5	64QAM	12	7	20.54	20.66	20.38	21.7	3	
5	64QAM	12	13	20.62	20.63	20.51			
5	64QAM	25	0	20.67	20.54	20.54			

Band 66									
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. Freq.	Power Middle Ch. Freq.	Power High Ch. Freq.	Tune-up limit (dBm)	MPR (dB)	
Channel				133072	133232	133572			
Frequency (MHz)				1720	1745	1770			
20	QPSK	1	0	23.17	23.51	23.07	23.7	0	
20	QPSK	1	49	23.27	23.36	23.31			
20	QPSK	1	99	23.27	23.17	23.14			
20	QPSK	50	0	22.46	22.58	22.41			
20	QPSK	50	24	22.43	22.45	22.39	22.7	1	
20	QPSK	50	50	22.38	22.28	22.18			
20	QPSK	100	0	22.39	22.40	22.34			
20	16QAM	1	0	22.23	22.13	21.89			
20	16QAM	1	49	22.34	22.30	22.10	22.7	1	
20	16QAM	1	99	22.38	22.03	22.08			
20	16QAM	50	0	21.47	21.49	21.25			
20	16QAM	50	24	21.37	21.39	21.24	21.7	2	
20	16QAM	50	50	21.33	21.28	21.09			
20	16QAM	100	0	21.34	21.33	21.23			
20	64QAM	1	0	21.28	21.37	21.41	21.7	2	
20	64QAM	1	49	21.26	21.16	21.44			
20	64QAM	1	99	21.16	21.13	21.01			
20	64QAM	50	0	20.68	20.56	20.68			
20	64QAM	50	24	20.67	20.62	20.56	20.7	3	
20	64QAM	50	50	20.64	20.50	20.38			
20	64QAM	100	0	20.58	20.48	20.36			
Channel				133047	133232	133597	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1717.5	1745	1772.5			
15	QPSK	1	0	23.11	23.32	23.25	23.7	0	
15	QPSK	1	37	23.35	23.10	23.10			
15	QPSK	1	74	23.04	22.90	22.97			
15	QPSK	36	0	22.25	22.39	22.40			
15	QPSK	36	20	22.31	22.18	22.20	22.7	1	
15	QPSK	36	39	22.33	22.16	22.22			
15	QPSK	75	0	22.22	22.24	22.24			
15	16QAM	1	0	21.91	21.85	21.52			
15	16QAM	1	37	21.83	21.75	21.71	22.7	1	
15	16QAM	1	74	21.66	21.55	21.52			
15	16QAM	36	0	21.23	21.21	21.25			
15	16QAM	36	20	21.34	21.28	21.20	21.7	2	
15	16QAM	36	39	21.39	21.18	21.11			
15	16QAM	75	0	21.28	21.23	21.01			
15	64QAM	1	0	21.33	21.41	21.26	21.7	2	
15	64QAM	1	37	20.97	21.13	20.92			
15	64QAM	1	74	21.10	21.00	21.13			
15	64QAM	36	0	20.44	20.52	20.35			
15	64QAM	36	20	20.45	20.42	20.23	20.7	3	
15	64QAM	36	39	20.50	20.40	20.21			
15	64QAM	75	0	20.38	20.36	20.32			
Channel				133022	133232	133622	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1715	1745	1775			
10	QPSK	1	0	23.00	23.22	23.15	23.7	0	
10	QPSK	1	25	23.25	22.99	22.99			
10	QPSK	1	49	22.85	22.80	22.86			
10	QPSK	25	0	22.14	22.29	22.30			
10	QPSK	25	12	22.12	22.08	21.96	22.7	1	
10	QPSK	25	25	22.22	22.05	22.11			
10	QPSK	50	0	22.03	22.14	22.05			
10	16QAM	1	0	21.80	21.66	21.33			
10	16QAM	1	25	21.64	21.65	21.60	22.7	1	
10	16QAM	1	49	21.56	21.44	21.33			
10	16QAM	25	0	21.22	21.12	21.06			
10	16QAM	25	12	21.15	21.18	21.09	21.7	2	
10	16QAM	25	25	21.28	21.08	21.01			
10	16QAM	50	0	21.09	21.12	20.82			
10	64QAM	1	0	21.22	21.22	21.15	21.7	2	
10	64QAM	1	25	20.78	21.02	20.73			
10	64QAM	1	49	20.59	20.81	21.03			
10	64QAM	25	0	20.34	20.41	20.24			
10	64QAM	25	12	20.28	20.32	20.04	20.7	3	
10	64QAM	25	25	20.39	20.29	20.10			
10	64QAM	50	0	20.28	20.25	20.22			
Channel				131987	132222	132647	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1712.5	1745	1777.5			
5	QPSK	1	0	22.89	22.95	22.94	23.7	0	
5	QPSK	1	12	23.15	22.88	22.88			
5	QPSK	1	24	22.78	22.75	22.75			
5	QPSK	12	0	22.03	22.17	22.20			
5	QPSK	12	7	21.83	21.98	21.77	22.7	1	
5	QPSK	12	13	22.11	21.94	22.00			
5	QPSK	25	0	21.84	22.04	21.86	22.7	1	
5	16QAM	1	0	21.69	21.47	21.41			
5	16QAM	1	12	21.45	21.55	21.49			
5	16QAM	1	24	21.16	21.33	21.31			
5	16QAM	12	0	21.11	21.20	20.87	21.7	2	
5	16QAM	12	7	20.96	21.08	20.98			
5	16QAM	12	13	21.17	20.98	20.91			
5	16QAM	25	0	20.90	21.01	20.63	21.7	2	
5	64QAM	1	0	21.11	21.03	21.04			
5	64QAM	1	12	20.79	20.91	20.75			
5	64QAM	1	24	20.88	20.97	20.93			
5	64QAM	12	0	20.28	20.30	20.07	20.7	3	
5	64QAM	12	7	20.07	20.22	19.85			
5	64QAM	12	13	20.28	20.18	19.99			
5	64QAM	25	0	20.18	20.14	20.12			
Channel				131987	132222	132657	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1711.5	1745	1778.5			
3	QPSK	1	0	22.78	22.85	22.84	23.7	0	
3	QPSK	1	8	23.05	22.77	22.77			
3	QPSK	1	16	22.59	22.56	22.64			
3	QPSK	8	0	21.52	21.67	21.10			
3	QPSK	8	4	21.74	21.88	21.74	22.7	1	
3	QPSK	8	7	22.00	21.83	21.89			
3	QPSK	15	0	21.65	21.94	21.67	22.7	1	
3	16QAM	1	0	21.58	21.28	21.22			
3	16QAM	1	8	21.26	21.45	21.38			
3	16QAM	1	16	21.36	21.12	21.12			
3	16QAM	8	0	21.08	21.24	20.87	21.7	2	
3	16QAM	8	4	20.77	20.98	20.87			
3	16QAM	8	7	21.06	20.88	20.81			
3	16QAM	15	0	20.71	20.90	20.44	21.7	2	
3	64QAM	1	0	21.00	20.84	20.93			
3	64QAM	1	8	20.60	20.80	20.56			
3	64QAM	1	16	20.17	20.78	20.83			
3	64QAM	8	0	20.14	20.19	20.07	20.7	3	
3	64QAM	8	4	19.88	20.12	19.86			
3	64QAM	8	7	20.17	20.07	19.88			
3	64QAM	15	0	20.08	20.03	20.02			
Channel				131919	132222	133666	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1710.7	1745	1779.3			
1.4	QPSK	1	0	22.92	23.00	22.99	23.7	0	
1.4	QPSK	1	3	23.02	22.91	22.91			
1.4	QPSK	1	5	22.65	22.62	22.78			
1.4	QPSK	3	0	22.89	22.91	22.76			
1.4	QPSK	3	1	22.89	22.87	22.87	22.7	1	
1.4	QPSK	3	3	22.77	22.89	22.78			
1.4	QPSK	6	0	21.71	22.09	21.73	22.7	1	
1.4	16QAM	1	0	21.72	21.34	21.26			
1.4	16QAM	1	3	21.32	21.60	21.52			
1.4	16QAM	1	5	21.51	21.36	21.38			
1.4	16QAM	3	0	21.77	22.01	21.76	21.7	2	
1.4	16QAM	3	1	21.78	21.34	21.77			
1.4	16QAM	3	3	21.77	21.78	21.67			
1.4	64QAM	6	0	20.77	21.04	20.88	21.7	2	
1.4	64QAM	1	0	21.14	20.90	21.07			
1.4	64QAM	1	3	20.66	20.94	20.77			
1.4	64QAM	1	5	20.91	20.94	20.98			
1.4	64QAM	3	0	20.92	20.89	20.81	21.7	2	
1.4	64QAM	3	1	21.00	20.98	20.91			
1.4	64QAM	3	3	20.88	20.82	20.98			
1.4	64QAM	6	0	20.23	20.17	20.17	20.7	3	

Band 38(only on channel required)								
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch / Freq	Power Middle Ch / Freq	Power High Ch / Freq	Tune-up limit (dBm)	MPR (dB)
Channel				37850	38000	38150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2580	2595	2610		
20	QPSK	1	0	23.73	23.92	23.71	24.7	0
20	QPSK	1	49	23.87	23.67	23.83		
20	QPSK	1	99	23.87	23.66	23.71		
20	QPSK	50	0	22.99	23.00	23.00	23.7	1
20	QPSK	50	24	22.97	22.91	22.92		
20	QPSK	50	50	22.97	22.96	22.76		
20	QPSK	100	0	22.91	22.98	22.71	23.7	1
20	16QAM	1	0	22.30	22.24	22.52		
20	16QAM	1	49	22.35	22.54	22.44		
20	16QAM	1	99	22.47	22.40	22.23	22.7	2
20	16QAM	50	0	21.88	21.87	21.86		
20	16QAM	50	24	21.84	21.86	21.80		
20	16QAM	50	50	22.04	21.85	21.73	22.7	2
20	16QAM	100	0	21.95	21.82	21.86		
20	64QAM	1	0	21.46	21.54	21.73		
20	64QAM	1	49	21.61	21.83	21.88	21.7	3
20	64QAM	1	99	21.59	21.67	21.41		
20	64QAM	50	0	21.63	21.51	21.51		
20	64QAM	50	24	21.58	21.59	21.52	21.7	3
20	64QAM	50	50	21.58	21.64	21.27		
20	64QAM	100	0	21.60	21.61	21.40		
Channel				37825	38000	38175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2577.5	2595	2612.5		
15	QPSK	1	0	23.60	23.76	23.61	24.7	0
15	QPSK	1	37	23.56	23.66	23.67		
15	QPSK	1	74	23.67	23.84	23.80		
15	QPSK	36	0	22.77	22.87	22.95	23.7	1
15	QPSK	36	20	22.97	22.78	22.96		
15	QPSK	36	39	22.73	22.95	22.86		
15	QPSK	75	0	22.68	22.91	22.72	23.7	1
15	16QAM	1	0	22.56	22.41	22.49		
15	16QAM	1	37	22.85	22.19	22.57		
15	16QAM	1	74	22.38	22.27	22.21	22.7	2
15	16QAM	36	0	21.85	21.77	21.71		
15	16QAM	36	20	21.82	21.94	21.86		
15	16QAM	36	39	21.83	21.90	21.80	22.7	2
15	16QAM	75	0	21.86	21.93	21.68		
15	64QAM	1	0	21.76	21.74	21.71		
15	64QAM	1	37	21.80	21.84	21.71	21.7	3
15	64QAM	1	74	21.74	21.44	21.47		
15	64QAM	36	0	21.41	21.51	21.44		
15	64QAM	36	20	21.39	21.57	21.52	21.7	3
15	64QAM	36	39	21.48	21.48	21.32		
15	64QAM	75	0	21.62	21.65	21.30		
Channel				37800	38000	38200	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2575	2595	2615		
10	QPSK	1	0	23.75	23.84	23.77	24.7	0
10	QPSK	1	25	23.91	23.86	23.83		
10	QPSK	1	49	23.70	23.77	23.59		
10	QPSK	25	0	22.78	22.78	22.93	23.7	1
10	QPSK	25	12	22.90	22.97	22.86		
10	QPSK	25	25	22.78	22.94	22.66		
10	QPSK	50	0	22.84	23.00	22.67	23.7	1
10	16QAM	1	0	22.24	22.35	22.33		
10	16QAM	1	25	22.23	22.31	22.27		
10	16QAM	1	49	22.24	22.14	22.10	22.7	2
10	16QAM	25	0	22.01	22.04	21.88		
10	16QAM	25	12	21.90	22.03	21.97		
10	16QAM	25	25	21.93	21.92	21.81	22.7	2
10	16QAM	50	0	21.90	21.88	21.59		
10	64QAM	1	0	21.55	21.75	21.51		
10	64QAM	1	25	21.69	22.00	21.96	21.7	3
10	64QAM	1	49	21.62	21.56	21.53		
10	64QAM	25	0	21.41	21.49	21.36		
10	64QAM	25	12	21.62	21.67	21.53	21.7	3
10	64QAM	25	25	21.67	21.63	21.27		
10	64QAM	50	0	21.43	21.42	21.36		
Channel				37775	38000	38225	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2572.5	2595	2617.5		
5	QPSK	1	0	23.66	23.54	23.55	24.7	0
5	QPSK	1	12	23.71	23.74	23.73		
5	QPSK	1	24	23.51	23.48	23.47		
5	QPSK	12	0	22.86	22.86	22.73	23.7	1
5	QPSK	12	7	22.69	22.76	22.88		
5	QPSK	12	13	22.72	22.72	22.79		
5	QPSK	25	0	22.72	22.84	22.66	23.7	1
5	16QAM	1	0	22.23	22.40	22.21		
5	16QAM	1	12	22.48	22.70	22.86		
5	16QAM	1	24	22.42	22.33	22.21	22.7	2
5	16QAM	12	0	21.70	21.70	21.54		
5	16QAM	12	7	21.81	21.66	21.63		
5	16QAM	12	13	21.68	21.72	21.66	22.7	2
5	16QAM	25	0	21.91	21.72	21.57		
5	64QAM	1	0	21.47	21.68	21.41		
5	64QAM	1	12	21.80	21.71	21.79	21.7	2
5	64QAM	1	24	21.51	21.53	21.51		
5	64QAM	12	0	21.34	21.30	21.15		
5	64QAM	12	7	21.38	21.47	21.25	21.7	3
5	64QAM	12	13	21.38	21.34	21.26		
5	64QAM	25	0	21.48	21.40	21.31		

2.4GHz WLAN	Ant 1					
2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11b 1Mbps	1	2412	15.95	17.00	97.59
		6	2437	16.07	17.00	
		11	2462	16.16	17.00	
	802.11g 6Mbps	1	2412	12.42	13.00	87.04
		6	2437	15.72	16.50	
		11	2462	12.16	13.00	
	802.11n-HT20 MCS0	1	2412	11.57	12.00	86.27
		6	2437	15.03	16.00	
		11	2462	11.70	12.00	
	802.11n-HT40 MCS0	3	2422	9.96	11.00	86.29
		6	2437	14.17	15.00	
		9	2452	10.48	11.00	

BR / EDR

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	8.76	6.59	6.49
	CH 39	2441	9.36	7.27	7.30
	CH 78	2480	7.75	5.50	5.70
Tune-up Limit			10		

LE

Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
LE	CH 00	2402	0.62
	CH 19	2440	1.30
	CH 39	2480	-0.31
Tune-up Limit			2