



FCC RF Test Report

APPLICANT : LG Electronics USA, Inc.
EQUIPMENT : Mobile Phone
BRAND NAME : LG
MODEL NAME : LM-K410EMW, LMK410EMW, K410EMW
FCC ID : ZNFK410EMW
STANDARD : 47 CFR Part 2, 27(M)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jan. 09, 2020 and completely tested on Feb. 28, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	5
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.7 Testing Location	7
1.8 Test Software	7
1.9 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode	8
2.2 Connection Diagram of Test System	9
2.3 Support Unit used in test configuration and system	9
2.4 Measurement Results Explanation Example	9
2.5 Frequency List of Low/Middle/High Channels	10
3 CONDUCTED TEST ITEMS	11
3.1 Measuring Instruments	11
3.2 Test Setup	11
3.3 Test Result of Conducted Test	11
3.4 Conducted Output Power and ERP/EIRP	12
3.5 Peak-to-Average Ratio	13
3.6 Occupied Bandwidth	14
3.7 Conducted Band Edge	15
3.8 Conducted Spurious Emission	16
3.9 Frequency Stability	17
4 RADIATED TEST ITEMS	18
4.1 Measuring Instruments	18
4.2 Test Setup	18
4.3 Test Result of Radiated Test	18
4.4 Radiated Spurious Emission	19
5 LIST OF MEASURING EQUIPMENT	20
6 UNCERTAINTY OF EVALUATION	21
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG010912B	Rev. 01	Initial issue of report	Mar. 18, 2020



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 7) (Band 38)	EIRP < 2Watt	PASS	
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	N/A	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7) (Band 38)	§27.53(m)(4)	PASS	-
3.8	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7) (Band 38)	< 55+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7) (Band 38)	< 55+10log ₁₀ (P[Watts])	PASS	Under limit 21.72 dB at 7760.000 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

LG Electronics USA, Inc.

1000 Sylvan Ave. Englewood Cliffs, New Jersey, United States 07632

1.2 Manufacturer

LG Electronics USA, Inc.

1000 Sylvan Ave. Englewood Cliffs, New Jersey, United States 07632

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	LG
Model Name	LM-K410EMW, LMK410EMW, K410EMW
FCC ID	ZNFK410EMW
EUT supports Radios application	GSM/WCDMA/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR/EDR/LE GNSS
IMEI Code	conducted: N/A Radiation: 353671110021771/353671110028314
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz
Rx Frequency	LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz
Bandwidth	LTE Band 7 : 5MHz/ 10MHz / 15MHz / 20MHz LTE Band 38 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 7 : 23.04 dBm LTE Band 38 : 22.93 dBm
Antenna Gain	LTE Band 7 : -3.23 dBi LTE Band 38 : -3.23 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 7		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2502.5 ~ 2567.5	4M50G7D	-	0.0925	4M50W7D	-	0.0771
10	2505.0 ~ 2565.0	9M07G7D	0.0056	0.0948	9M07W7D	-	0.0815
15	2507.5 ~ 2562.5	13M5G7D	-	0.0938	13M5W7D	-	0.0783
20	2510.0 ~ 2560.0	18M5G7D	-	0.0957	18M5W7D	-	0.0796
LTE Band 7		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
5	2502.5 ~ 2567.5	4M49W7D		-		0.0769	
10	2505.0 ~ 2565.0	9M05W7D		-		0.0733	
15	2507.5 ~ 2562.5	13M5W7D		-		0.0706	
20	2510.0 ~ 2560.0	18M4W7D		-		0.0724	

LTE Band 38		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2572.5 ~ 2617.5	4M50G7D	-	0.0927	4M51W7D	-	0.0920
10	2575.0 ~ 2615.0	9M01G7D	0.0038	0.0925	9M09W7D	-	0.0929
15	2577.5 ~ 2612.5	13M5G7D	-	0.0927	13M5W7D	-	0.0914
20	2580.0 ~ 2610.0	18M5G7D	-	0.0933	18M5W7D	-	0.0762
LTE Band 38		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
5	2572.5 ~ 2617.5	4M49W7D		-		0.0746	
10	2575.0 ~ 2615.0	9M03W7D		-		0.0740	
15	2577.5 ~ 2612.5	13M5W7D		-		0.0738	
20	2580.0 ~ 2610.0	18M4W7D		-		0.0738	

1.7 Testing Location

<FCC>-KS

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 27(M)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Hal f	Full	L	M	H
Max. Output Power	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	7	-	-				v	v	v	v	v		v	v	v	v
	38	-	-				v	v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	7	-	-	v	v	v	v	v	v	v			v	v	v	v
	38	-	-	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	7	-	-	v	v	v	v	v	v	v	v		v	v		v
	38	-	-	v	v	v	v	v	v	v	v		v	v		v
Conducted Spurious Emission	7	-	-	v	v	v	v	v	v	v	v			v	v	v
	38	-	-	v	v	v	v	v	v	v	v			v	v	v
Frequency Stability	7	-	-		v			v					v		v	
	38	-	-		v			v					v		v	
E.R.P / E.I.R.P	7	-	-	v	v	v	v	v	v	v	v			v	v	v
	38	-	-	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	7	Worst Case												v	v	v
	38	Worst Case												v	v	v
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Fixture	INTEL	NGFF Card Carrier	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.30 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.30 \text{ (dB)} \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 7 and Band 38.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

9. For LTE Band 7, 38, the other 40 dB, and 55 dB have additionally applied same calculation above.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7,38:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.
11. For Band 7, 38
The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [55 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[55 + 10\log(P)]$ (dB)
 $= -25\text{dBm}$.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7, 38

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

13. For Band 7, 38:

The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	Apr. 16, 2019	Feb. 28, 2020	Apr. 15, 2020	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 04, 2019	Feb. 28, 2020	Jul. 03, 2020	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G, MAX 30dB	Apr.16, 2019	Feb. 24, 2020	Apr. 15, 2020	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	May 30, 2019	Feb. 24, 2020	May 29, 2020	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1648	1GHz~18GHz	Mar. 27, 2019	Feb. 24, 2020	Mar. 26, 2020	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Nov. 19, 2019	Feb. 24, 2020	Nov. 20, 2020	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug..06.2019	Feb. 24, 2020	Aug.05.2020	Radiation (03CH04-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2020	Feb. 24, 2020	Jan. 13, 2021	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Aug.16.2019	Feb. 24, 2020	Aug.15.2020	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Apr. 15, 2019	Feb. 24, 2020	Apr. 14, 2020	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 24, 2020	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 24, 2020	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 24, 2020	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.3dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8dB
---	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.78	23.04	22.89
20	1	49		22.81	22.77	22.87
20	1	99		22.54	22.64	22.73
20	50	0		22.11	22.38	21.93
20	50	24		22.22	22.32	22.16
20	50	50		22.06	22.22	22.16
20	100	0		22.10	22.23	21.80
20	1	0	16-QAM	22.02	22.18	22.23
20	1	49		22.24	22.16	22.05
20	1	99		22.14	22.02	22.18
20	50	0		21.27	21.50	21.15
20	50	24		21.41	21.45	21.28
20	50	50		21.27	21.39	21.00
20	100	0		21.20	21.38	20.94
20	1	0	64-QAM	21.83	21.57	21.68
20	1	49		21.61	21.60	21.78
20	1	99		21.57	21.70	21.71
20	50	0		20.57	20.89	20.39
20	50	24		20.78	20.75	20.56
20	50	50		20.63	20.70	20.56
20	100	0		20.54	20.78	20.42
15	1	0	QPSK	22.74	22.81	22.55
15	1	37		22.95	22.83	22.58
15	1	74		22.80	22.63	22.65
15	36	0		22.05	22.18	21.94
15	36	20		22.17	22.15	21.89
15	36	39		22.05	22.00	21.72
15	75	0		22.12	22.20	21.79



15	1	0	16-QAM	22.03	21.81	21.76
15	1	37		22.03	22.17	21.72
15	1	74		22.04	22.05	21.72
15	36	0		20.99	21.08	20.92
15	36	20		21.10	21.08	20.85
15	36	39		21.07	20.98	20.69
15	75	0		21.05	21.15	20.79
15	1	0	64-QAM	21.25	21.36	21.57
15	1	37		21.62	21.72	21.53
15	1	74		21.25	21.53	21.23
15	36	0		20.58	20.68	20.57
15	36	20		20.72	20.79	20.46
15	36	39		20.76	20.64	20.30
15	75	0		20.66	20.69	20.37



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.82	22.79	22.55
10	1	25		23.00	22.81	22.78
10	1	49		22.78	22.72	22.80
10	25	0		22.03	22.15	21.90
10	25	12		22.03	22.09	21.81
10	25	25		22.17	21.98	21.70
10	50	0		22.23	22.25	21.93
10	1	0	16-QAM	22.30	22.01	21.93
10	1	25		22.15	22.34	22.08
10	1	49		22.29	21.93	22.07
10	25	0		21.04	21.11	20.87
10	25	12		21.05	21.14	20.80
10	25	25		21.18	21.03	20.71
10	50	0		21.19	21.25	20.90
10	1	0	64-QAM	21.88	21.58	21.44
10	1	25		21.74	21.78	21.48
10	1	49		21.58	21.60	21.44
10	25	0		20.92	21.02	20.92
10	25	12		21.04	21.01	20.87
10	25	25		21.12	21.05	20.71
10	50	0		21.14	21.15	20.79
5	1	0	QPSK	22.72	22.77	22.65
5	1	12		22.89	22.89	22.68
5	1	24		22.80	22.67	22.66
5	12	0		22.03	22.09	21.84
5	12	7		22.14	22.12	21.82
5	12	13		22.12	22.07	21.92
5	25	0		22.07	22.06	21.85
5	1	0	16-QAM	22.03	22.03	22.04
5	1	12		22.02	22.01	22.02
5	1	24		22.10	21.97	22.01
5	12	0		21.00	21.11	20.79
5	12	7		21.07	21.11	20.86



5	12	13		21.12	21.07	20.70
5	25	0		21.04	21.06	20.79
5	1	0	64-QAM	21.68	21.94	21.77
5	1	12		21.81	22.04	21.89
5	1	24		22.09	21.68	21.88
5	12	0		20.96	20.96	20.68
5	12	7		20.95	21.11	20.69
5	12	13		21.01	20.93	20.63
5	25	0		21.02	21.01	20.68



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.79	22.93	22.87
20	1	49		22.86	22.83	22.89
20	1	99		22.67	22.58	22.57
20	50	0		21.87	21.90	21.81
20	50	24		21.71	21.79	21.89
20	50	50		21.68	21.74	21.80
20	100	0		21.85	21.80	21.88
20	1	0	16-QAM	21.88	21.81	21.89
20	1	49		22.05	21.96	22.00
20	1	99		21.69	21.71	21.78
20	50	0		21.22	21.24	21.28
20	50	24		21.22	21.20	21.33
20	50	50		21.10	21.16	21.24
20	100	0		21.24	21.19	21.32
20	1	0	64-QAM	21.90	21.89	21.91
20	1	49		21.78	21.76	21.78
20	1	99		21.68	21.75	21.82
20	50	0		21.20	21.18	21.18
20	50	24		21.12	21.15	21.23
20	50	50		21.02	21.08	21.22
20	100	0		21.19	21.25	21.31
15	1	0	QPSK	22.79	22.68	22.75
15	1	37		22.85	22.90	22.86
15	1	74		22.60	22.60	22.72
15	36	0		22.78	22.88	22.82
15	36	20		22.83	22.77	22.83
15	36	39		22.67	22.76	22.84
15	75	0		22.63	22.72	22.77
15	1	0	16-QAM	22.79	22.76	22.79
15	1	37		22.81	22.84	22.76
15	1	74		22.64	22.61	22.79
15	36	0		21.25	21.28	21.33
15	36	20		21.21	21.25	21.38



15	36	39		21.18	21.23	21.30
15	75	0		21.15	21.30	21.31
15	1	0	64-QAM	21.79	21.75	21.80
15	1	37		21.80	21.88	21.91
15	1	74		21.63	21.65	21.70
15	36	0		21.28	21.28	21.30
15	36	20		21.22	21.24	21.35
15	36	39		21.17	21.25	21.29
15	75	0		21.21	21.21	21.29



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.85	22.75	22.87
10	1	25		22.68	22.68	22.77
10	1	49		22.73	22.61	22.77
10	25	0		22.89	22.83	22.86
10	25	12		22.67	22.83	22.78
10	25	25		22.75	22.75	22.89
10	50	0		22.74	22.72	22.86
10	1	0	16-QAM	22.88	22.86	22.91
10	1	25		22.72	22.77	22.87
10	1	49		22.77	22.75	22.73
10	25	0		21.40	21.38	21.45
10	25	12		21.35	21.37	21.44
10	25	25		21.23	21.18	21.38
10	50	0		21.33	21.25	21.38
10	1	0	64-QAM	21.84	21.83	21.92
10	1	25		21.74	21.73	21.83
10	1	49		21.77	21.77	21.90
10	25	0		21.34	21.32	21.34
10	25	12		21.26	21.31	21.43
10	25	25		21.22	21.30	21.30
10	50	0		21.24	21.25	21.38
5	1	0	QPSK	22.72	22.55	22.78
5	1	12		22.88	22.85	22.76
5	1	24		22.66	22.67	22.79
5	12	0		22.86	22.75	22.90
5	12	7		22.77	22.75	22.78
5	12	13		22.78	22.79	22.90
5	25	0		22.82	22.79	22.76
5	1	0	16-QAM	22.80	22.77	22.86
5	1	12		22.85	22.84	22.87
5	1	24		22.71	22.69	22.87
5	12	0		21.28	21.21	21.31
5	12	7		21.22	21.29	21.45



5	12	13		21.17	21.22	21.28
5	25	0		21.31	21.25	21.46
5	1	0	64-QAM	21.78	21.65	21.85
5	1	12		21.87	21.93	21.96
5	1	24		21.69	21.67	21.79
5	12	0		21.32	21.22	21.35
5	12	7		21.30	21.30	21.51
5	12	13		21.21	21.15	21.35
5	25	0		21.18	21.22	21.30

**ERP/EIRP**

LTE Band 7 (GT - LC = -3.23 dB) QPSK			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency	2502.5	2535	2567.5
(MHz)			
Conducted Power (dBm)	22.89	22.89	22.68
Conducted Power (Watts)	0.1945	0.1945	0.1854
EIRP(dBm)	19.66	19.66	19.45
EIRP(Watts)	0.0925	0.0925	0.0881

LTE Band 7 (GT - LC = -3.23 dB) QPSK									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
(MHz)									
Conducted Power (dBm)	23.00	22.81	22.78	22.95	22.83	22.58	22.78	23.04	22.89
Conducted Power (Watts)	0.1995	0.1910	0.1897	0.1972	0.1919	0.1811	0.1897	0.2014	0.1945
EIRP(dBm)	19.77	19.58	19.55	19.72	19.60	19.35	19.55	19.81	19.66
EIRP(Watts)	0.0948	0.0908	0.0902	0.0938	0.0912	0.0861	0.0902	0.0957	0.0925



LTE Band 7 (GT - LC = -3.23 dB) 16QAM			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency	2502.5	2535	2567.5
(MHz)			
Conducted Power (dBm)	22.10	21.97	22.01
Conducted Power (Watts)	0.1622	0.1574	0.1589
EIRP(dBm)	18.87	18.74	18.78
EIRP(Watts)	0.0771	0.0748	0.0755

LTE Band 7 (GT - LC = -3.23 dB) 16QAM									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
(MHz)									
Conducted Power (dBm)	22.15	22.34	22.08	22.03	22.17	21.72	22.24	22.16	22.05
Conducted Power (Watts)	0.1641	0.1714	0.1614	0.1596	0.1648	0.1486	0.1675	0.1644	0.1603
EIRP(dBm)	18.92	19.11	18.85	18.80	18.94	18.49	19.01	18.93	18.82
EIRP(Watts)	0.0780	0.0815	0.0767	0.0759	0.0783	0.0706	0.0796	0.0782	0.0762



LTE Band 7 (GT - LC = -3.23 dB) 64QAM			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency	2502.5	2535	2567.5
(MHz)			
Conducted Power (dBm)	22.09	21.68	21.88
Conducted Power (Watts)	0.1618	0.1472	0.1542
EIRP(dBm)	18.86	18.45	18.65
EIRP(Watts)	0.0769	0.0700	0.0733

LTE Band 7 (GT - LC = -3.23 dB) 64QAM									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
(MHz)									
Conducted Power (dBm)	21.88	21.58	21.44	21.62	21.72	21.53	21.83	21.57	21.68
Conducted Power (Watts)	0.1542	0.1439	0.1393	0.1452	0.1486	0.1422	0.1524	0.1435	0.1472
EIRP(dBm)	18.65	18.35	18.21	18.39	18.49	18.30	18.60	18.34	18.45
EIRP(Watts)	0.0733	0.0684	0.0662	0.0690	0.0706	0.0676	0.0724	0.0682	0.0700



LTE Band 38 (GT - LC = -3.23 dB) QPSK			
Bandwidth	5M		
Channel	37775	38000	38225
	(Low)	(Mid)	(High)
Frequency	2572.5	2595	2617.5
(MHz)			
Conducted Power (dBm)	22.86	22.75	22.90
Conducted Power (Watts)	0.1932	0.1884	0.1950
EIRP(dBm)	19.63	19.52	19.67
EIRP(Watts)	0.0918	0.0895	0.0927

LTE Band 38 (GT - LC = -3.23 dB) QPSK									
Bandwidth	10M			15M			20M		
Channel	37800	38000	38200	37825	38000	38175	37850	38000	38150
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency	2575	2595	2615	2577.5	2595	2612.5	2580	2595	2610
(MHz)									
Conducted Power (dBm)	22.89	22.83	22.86	22.85	22.90	22.86	22.79	22.93	22.87
Conducted Power (Watts)	0.1945	0.1919	0.1932	0.1928	0.1950	0.1932	0.1901	0.1963	0.1936
EIRP(dBm)	19.66	19.60	19.63	19.62	19.67	19.63	19.56	19.70	19.64
EIRP(Watts)	0.0925	0.0912	0.0918	0.0916	0.0927	0.0918	0.0904	0.0933	0.0920



LTE Band 38 (GT - LC = -3.23 dB) 16QAM			
Bandwidth	5M		
Channel	37775	38000	38225
	(Low)	(Mid)	(High)
Frequency	2572.5	2595	2617.5
(MHz)			
Conducted Power (dBm)	22.85	22.84	22.87
Conducted Power (Watts)	0.1928	0.1923	0.1936
EIRP(dBm)	19.62	19.61	19.64
EIRP(Watts)	0.0916	0.0914	0.0920

LTE Band 38 (GT - LC = -3.23 dB) 16QAM									
Bandwidth	10M			15M			20M		
Channel	37800	38000	38200	37825	38000	38175	37850	38000	38150
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency	2575	2595	2615	2577.5	2595	2612.5	2580	2595	2610
(MHz)									
Conducted Power (dBm)	22.88	22.86	22.91	22.81	22.84	22.76	22.05	21.96	22.00
Conducted Power (Watts)	0.1941	0.1932	0.1954	0.1910	0.1923	0.1888	0.1603	0.1570	0.1585
EIRP(dBm)	19.65	19.63	19.68	19.58	19.61	19.53	18.82	18.73	18.77
EIRP(Watts)	0.0923	0.0918	0.0929	0.0908	0.0914	0.0897	0.0762	0.0746	0.0753



LTE Band 38 (GT - LC = -3.23 dB) 64QAM			
Bandwidth	5M		
Channel	37775	38000	38225
	(Low)	(Mid)	(High)
Frequency	2572.5	2595	2617.5
(MHz)			
Conducted Power (dBm)	21.87	21.93	21.96
Conducted Power (Watts)	0.1538	0.1560	0.1570
EIRP(dBm)	18.64	18.70	18.73
EIRP(Watts)	0.0731	0.0741	0.0746


LTE Band 38 (GT - LC = -3.23 dB) 64QAM									
Bandwidth	10M			15M			20M		
Channel	37800	38000	38200	37825	38000	38175	37850	38000	38150
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency	2575	2595	2615	2577.5	2595	2612.5	2580	2595	2610
(MHz)									
Conducted Power (dBm)	21.84	21.83	21.92	21.80	21.88	21.91	21.90	21.89	21.91
Conducted Power (Watts)	0.1528	0.1524	0.1556	0.1514	0.1542	0.1552	0.1549	0.1545	0.1552
EIRP(dBm)	18.61	18.60	18.69	18.57	18.65	18.68	18.67	18.66	18.68
EIRP(Watts)	0.0726	0.0724	0.0740	0.0719	0.0733	0.0738	0.0736	0.0735	0.0738




LTE Band 7

Peak-to-Average Ratio


Mode	LTE Band 7 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.00	4.70	4.72	5.57	PASS
Middle CH	4.26	4.93	5.19	5.80	
Highest CH	4.06	4.75	5.16	5.86	
Mode	LTE Band 7 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	5.80	6.03	-	-	PASS
Middle CH	5.54	6.06	-	-	
Highest CH	5.77	5.94	-	-	

LTE Band 7 / 20MHz / QPSK
Lowest Channel / 1RB



Date: 9 JAN 2007 23:11:55

Lowest Channel / Full RB



Date: 9 JAN 2007 23:12:04

Middle Channel / 1RB



Date: 9 JAN 2007 23:12:42

Middle Channel / Full RB


Date: 9 JAN 2007 23:12:33

Highest Channel / 1RB


Date: 9 JAN 2007 23:13:09


Highest Channel / Full RB


Date: 9 JAN 2007 23:13:18




LTE Band 7 / 20MHz / 16QAM


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 7 / 20MHz / 64QAM


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB




**26dB Bandwidth**

Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.84	4.92	9.75	9.69	14.39	14.30	20.22	20.18
Middle CH	-	-	-	-	4.87	4.94	9.87	9.85	14.24	14.51	20.14	20.02
Highest CH	-	-	-	-	4.87	4.87	9.81	9.71	14.24	14.21	20.18	20.18
Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.88	-	9.75	-	14.24	-	20.14	-
Middle CH	-	-	-	-	4.87	-	9.91	-	14.45	-	20.30	-
Highest CH	-	-	-	-	4.90	-	9.83	-	14.33	-	20.18	-




LTE Band 7

Lowest Channel / 5MHz / QPSK




Date: 9 JAN 2007 21:04:20

Lowest Channel / 5MHz / 16QAM




Date: 9 JAN 2007 21:04:40

Middle Channel / 5MHz / QPSK




Date: 9 JAN 2007 21:05:20

Middle Channel / 5MHz / 16QAM




Date: 9 JAN 2007 21:05:00

Highest Channel / 5MHz / QPSK



Date: 9 JAN 2007 21:05:40

Highest Channel / 5MHz / 16QAM




Date: 9 JAN 2007 21:06:00




LTE Band 7

Lowest Channel / 10MHz / QPSK




Date: 9 JAN 2007 21:20:48

Lowest Channel / 10MHz / 16QAM




Date: 9 JAN 2007 21:21:08

Middle Channel / 10MHz / QPSK




Date: 9 JAN 2007 21:21:48

Middle Channel / 10MHz / 16QAM




Date: 9 JAN 2007 21:21:28

Highest Channel / 10MHz / QPSK



Date: 9 JAN 2007 21:22:08

Highest Channel / 10MHz / 16QAM




Date: 9 JAN 2007 21:22:28




LTE Band 7

Lowest Channel / 15MHz / QPSK




Date: 9 JAN 2007 21:37:36

Lowest Channel / 15MHz / 16QAM




Date: 9 JAN 2007 21:37:16

Middle Channel / 15MHz / QPSK




Date: 9 JAN 2007 21:37:56

Middle Channel / 15MHz / 16QAM




Date: 9 JAN 2007 21:38:16

Highest Channel / 15MHz / QPSK



Date: 9 JAN 2007 21:38:56

Highest Channel / 15MHz / 16QAM




Date: 9 JAN 2007 21:38:36




LTE Band 7


Lowest Channel / 20MHz / QPSK




Lowest Channel / 20MHz / 16QAM




Middle Channel / 20MHz / QPSK




Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK




Highest Channel / 20MHz / 16QAM






LTE Band 7

Lowest Channel / 5MHz / 64QAM




Date: 9 JAN 2007 22:10:32

Lowest Channel / 10MHz / 64QAM




Date: 9 JAN 2007 22:18:47

Middle Channel / 5MHz / 64QAM




Date: 9 JAN 2007 22:10:42

Middle Channel / 10MHz / 64QAM




Date: 9 JAN 2007 22:18:57

Highest Channel / 5MHz / 64QAM



Date: 9 JAN 2007 22:10:52

Highest Channel / 10MHz / 64QAM




Date: 9 JAN 2007 22:19:07




LTE Band 7

Lowest Channel / 15MHz / 64QAM




Date: 9 JAN 2007 22:27:01

Lowest Channel / 20MHz / 64QAM




Date: 9 JAN 2007 22:35:15

Middle Channel / 15MHz / 64QAM




Date: 9 JAN 2007 22:27:11

Middle Channel / 20MHz / 64QAM




Date: 9 JAN 2007 22:35:25

Highest Channel / 15MHz / 64QAM



Date: 9 JAN 2007 22:27:21

Highest Channel / 20MHz / 64QAM



Date: 9 JAN 2007 22:35:35


**Occupied Bandwidth**

Mode	LTE Band 7 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.49	4.48	9.05	9.05	13.49	13.40	18.38	18.18
Middle CH	-	-	-	-	4.48	4.50	9.03	9.07	13.46	13.49	18.46	18.34
Highest CH	-	-	-	-	4.50	4.48	9.07	8.97	13.43	13.46	18.50	18.50
Mode	LTE Band 7 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.48	-	9.03	-	13.46	-	18.34	-
Middle CH	-	-	-	-	4.49	-	9.03	-	13.43	-	18.34	-
Highest CH	-	-	-	-	4.49	-	9.05	-	13.43	-	18.38	-




LTE Band 7


Lowest Channel / 5MHz / QPSK




Lowest Channel / 5MHz / 16QAM




Middle Channel / 5MHz / QPSK




Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK




Highest Channel / 5MHz / 16QAM






LTE Band 7


Lowest Channel / 10MHz / QPSK




Lowest Channel / 10MHz / 16QAM




Middle Channel / 10MHz / QPSK




Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK




Highest Channel / 10MHz / 16QAM






LTE Band 7


Lowest Channel / 15MHz / QPSK




Lowest Channel / 15MHz / 16QAM




Middle Channel / 15MHz / QPSK




Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK




Highest Channel / 15MHz / 16QAM






LTE Band 7

Lowest Channel / 20MHz / QPSK




Date: 9 JAN 2007 21:53:55

Lowest Channel / 20MHz / 16QAM




Date: 9 JAN 2007 21:53:35

Middle Channel / 20MHz / QPSK




Date: 9 JAN 2007 21:54:15

Middle Channel / 20MHz / 16QAM




Date: 9 JAN 2007 21:54:34

Highest Channel / 20MHz / QPSK



Date: 9 JAN 2007 21:55:14

Highest Channel / 20MHz / 16QAM




Date: 9 JAN 2007 21:54:54




LTE Band 7


Lowest Channel / 5MHz / 64QAM




Lowest Channel / 10MHz / 64QAM




Middle Channel / 5MHz / 64QAM




Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM




Highest Channel / 10MHz / 64QAM






LTE Band 7


Lowest Channel / 15MHz / 64QAM




Lowest Channel / 20MHz / 64QAM




Middle Channel / 15MHz / 64QAM




Middle Channel / 20MHz / 64QAM



Highest Channel / 15MHz / 64QAM



Highest Channel / 20MHz / 64QAM






Conducted Band Edge




LTE Band 7 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 9 JAN 2007 21:07:09

Highest Band Edge / 1 RB




Date: 9 JAN 2007 21:15:06

Lowest Band Edge / Full RB



Date: 9 JAN 2007 21:10:34

Highest Band Edge / Full RB




Date: 9 JAN 2007 21:11:42




LTE Band 7 / 5MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 9 JAN 2007 21:08:17

Highest Band Edge / 1 RB




Date: 9 JAN 2007 21:13:58

Lowest Band Edge / Full RB



Date: 9 JAN 2007 21:09:25

Highest Band Edge / Full RB




Date: 9 JAN 2007 21:12:50




LTE Band 7 / 5MHz / 64QAM

Lowest Band Edge / 1RB




Date: 9 JAN 2007 22:14:43

Highest Band Edge / 1 RB




Date: 9 JAN 2007 22:16:59

Lowest Band Edge / Full RB



Date: 9 JAN 2007 22:15:51

Highest Band Edge / Full RB




Date: 9 JAN 2007 22:18:07




LTE Band 7 / 10MHz / QPSK


Lowest Band Edge / 1 RB



Highest Band Edge / 1 RB



Lowest Band Edge / Full RB



Highest Band Edge / Full RB

