

FCC BT REPORT

FCC Certification

Applicant Name:

LG Electronics MobileComm U.S.A., Inc.

Date of Issue:

March 16, 2016

Test Site/Location:

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Address:

1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Report No.: HCT-R-1603-F026-1**HCT FRN:** 0005866421**IC Recognition No.:** 5944A-5**FCC ID : ZNFK500N****APPLICANT : LG Electronics MobileComm U.S.A., Inc.****Model(s):** LG-K500n**EUT Type:** Cellular/PCS GSM/WCDMA/LTE Phone with WLAN, Bluetooth and NFC**Max. RF Output Power:** 6.775 dBm (4.759 mW)**Frequency Range:** 2402 MHz - 2480 MHz (Bluetooth)**Modulation type** GFSK(Normal), $\pi/4$ DQPSK and 8DPSK(EDR)**FCC Classification:** FCC Part 15 Spread Spectrum Transmitter**FCC Rule Part(s):** Part 15 subpart C 15.247

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

**Report prepared by**
: Seoul Ki Lee**Test engineer of RF Team****Approved by**
: Sang Jun Lee**Manager of RF Team**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1603-F026	March 07, 2016	- First Approval Report
HCT-R-1603-F026-1	March 16, 2016	- Added information for antenna calibration in section 4.

Table of Contents

1.	GENERAL INFORMATION.....	4
2.	EUT DESCRIPTION.....	4
3.	TEST METHODOLOGY.....	5
3.1	EUT CONFIGURATION	5
3.2	EUT EXERCISE	5
3.3	GENERAL TEST PROCEDURES	5
3.4	DESCRIPTION OF TEST MODES	6
4.	INSTRUMENT CALIBRATION	6
5.	FACILITIES AND ACCREDITATIONS.....	6
5.1	FACILITIES	6
5.2	EQUIPMENT	6
6.	ANTENNA REQUIREMENTS	6
7.	SUMMARY OF TEST RESULTS	7
8.	FCC PART 15.247 REQUIREMENTS	8
8.1	PEAK POWER	8
8.2	BAND EDGES.....	15
8.3	FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)	23
8.4	NUMBER OF HOPPING FREQUENCY	32
8.5	TIME OF OCCUPANCY (DWEIL TIME).....	36
8.6	SPURIOUS EMISSIONS.....	43
8.6.1	CONDUCTED SPURIOUS EMISSIONS	43
8.6.2	RADIATED SPURIOUS EMISSIONS	52
8.6.3	RADIATED RESTRICTED BAND EDGES	69
8.7	POWERLINE CONDUCTED EMISSIONS.....	75
9.	LIST OF TEST EQUIPMENT	80
9.1	LIST OF TEST EQUIPMENT(Conducted Test)	80
9.2	LIST OF TEST EQUIPMENT(Radiated Test)	81

1. GENERAL INFORMATION

Applicant: LG Electronics MobileComm U.S.A., Inc.
Address: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
FCC ID: ZNFK500N
EUT Type: Cellular/PCS GSM/WCDMA/LTE Phone with WLAN, Bluetooth and NFC
Model name(s): LG-K500n
Date(s) of Tests: January 18, 2016 ~ February 04, 2016
Place of Tests: HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea

2. EUT DESCRIPTION

Model Name	LG-K500n
EUT Type	Cellular/PCS GSM/WCDMA/LTE Phone with WLAN, Bluetooth and NFC
Power Supply	DC 3.8 V
Battery Information	Model: BL-T9-LGC Type: Lithium Polymer
Frequency Range	2402 MHz - 2480 MHz (Bluetooth)
Max. RF Output Power:	6.775 dBm (4.759mW)
BT Operating Mode	Normal, EDR, AFH
Modulation Type	GFSK(Normal), $\pi/4$ DQPSK and 8DPSK(EDR)
Modulation Technique	FHSS
Number of Channels	79Channels, Minimum 20 Channels(AFH)
Antenna Specification	Manufacturer: LS Mtron Co., Ltd. Antenna type: INTERNAL ANTENNA Peak Gain : - 0.14 dBi

※ 15.247 Requirements for Bluetooth transmitter

▪ This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:

- 1) This system is hopping pseudo-randomly.
- 2) Each frequency is used equally on the average by each transmitter.
- 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
- 4) The receiver shifts frequencies in synchronization with the transmitted signals.

▪ 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.

▪ 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) is used in the measurement of the **LG Electronics MobileComm U.S.A., Inc.. Cellular/PCS GSM/WCDMA/LTE Phone with WLAN, Bluetooth and NFC FCC ID: ZNFK500N**

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013). To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120 kHz for frequencies below 1 GHz or 1 MHz for frequencies above 1 GHz. For average measurements above 1 GHz, the analyzer was set to peak detector with a reduced VBW setting(RBW = 1 MHz, VBW = 1/T Hz, where T = Pulse width).

Conducted Antenna Terminal

See Section from 7.8.2 to 7.8.8.(ANSI 63.10-2013)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 07, 2015 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

7. SUMMARY OF TEST RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	§15.247(a)(1)(ii) or (iii)	N/A	CONDUCTED	PASS
Occupied Bandwidth	N/A	N/A		N/A
Conducted Maximum Peak Output Power	§15.247(b)(1)	< 1 W if ≥ 75 non-overlapping hopping channels used < 0.125 W if < 75 non-overlapping hopping channels used		PASS
Carrier Frequency Separation	§15.247(a)(1)	>25 kHz or >2/3 of the 20dB BW		PASS
Number of Hopping Frequencies	§15.247(a)(1)(iii)	≥ 15		PASS
Time of Occupancy	§15.247(a)(1)(iii)	<400 ms		PASS
Conducted Spurious Emissions	§15.247(d)	> 20 dB for all out-of band emissions		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	> 20 dB for all out-of band emissions		PASS
AC Power line Conducted Emissions	§15.207(a)	cf. Section 8.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 8.6.2	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.6.3		PASS

8. FCC PART 15.247 REQUIREMENTS


8.1 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 W. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 W.
2. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. This test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.5 in ANSI 63.10-2013)

- 1) Span: approximately 5 times the 20 dB bandwidth, centered on a hopping channel
- 2) RBW > the 20 dB bandwidth of the emission being measured
- 3) VBW ≥ RBW
- 4) Sweep = Auto
- 5) Detector = Peak
- 6) Trace = Max hold

SAMPLE CALCULATION

$$\begin{aligned}\text{Output Power} &= \text{Spectrum Reading Power} + \text{Power Splitter loss} + \text{Cable loss}(2 \text{ ea}) \\ &= 10 \text{ dBm} + 6 \text{ dB} + 1.5 \text{ dB} = 17.5 \text{ dBm}\end{aligned}$$

Note :

1. Spectrum reading values are not plot data. The power results in plot is already including the actual values of loss for the splitter and cable combination.

2. Spectrum offset = Power Splitter loss + Cable loss

3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. Actual value of loss for the splitter and cable combination is 7.36 dB at 2402 MHz and is 7.44 dB at 2480 MHz.

So, 7.4 dB is offset. And the offset gap in the 2.4 GHz range do not affect the conducted peak power final result

TEST RESULTS


No non-compliance noted

Test Data


Channel	Frequency (MHz)	Output Power (GFSK)		Limit (mW)	Result
		(dBm)	(mW)		
Low	2402	5.718	3.731	125	PASS
Mid	2441	6.242	4.209		PASS
High	2480	5.398	3.466		PASS

Channel	Frequency (MHz)	Output Power (8DPSK)		Output Power ($\pi/4$ DQPSK)		Limit (mW)	Result
		(dBm)	(mW)	(dBm)	(mW)		
Low	2402	6.243	4.210	5.796	3.798	125	PASS
Mid	2441	6.775	4.759	6.321	4.286		PASS
High	2480	5.909	3.899	5.442	3.501		PASS


Test Plots (GFSK)
Peak Power (Low-CH)




Test Plots (GFSK)
Peak Power (Mid-CH)




Test Plots (GFSK)
Peak Power (High-CH)




Test Plots (8DPSK)
Peak Power (Low-CH)



Test Plots (8DPSK)
Peak Power (Mid-CH)




Test Plots (8DPSK)
Peak Power (High-CH)




Test Plots ($\pi/4$ DQPSK)

Peak Power (Low-CH)




Test Plots ($\pi/4$ DQPSK)

Peak Power (Mid-CH)



Test Plots ($\pi/4$ DQPSK)
Peak Power (High-CH)




8.2 BAND EDGES

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Configuration



TEST PROCEDURE

This test is performed with hopping off and hopping on.

The Spectrum Analyzer is set to (6.10.4 in ANSI 63.10-2013)

- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: Coupled.
- 5) RBW: 100 kHz
- 6) VBW: 300 kHz
- 7) Detector: Peak
- 8) Trace: Max hold

TEST RESULTS

See attached.

Note :

1. The results in plot is already including the actual values of loss for the splitter and cable combination.
2. Spectrum offset = Power Splitter loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. Actual value of loss for the splitter and cable combination is 7.36 dB at 2402 MHz and is 7.44 dB at 2480 MHz. So, 7.4 dB is offset. And the offset gap in the 2.4 GHz range do not affect the band edge measurement final result.

Test Data


- Without hopping

Outside Frequency Band	GFSK	8DPSK	$\pi/4$ DQPSK	Limit (dBc)	Margin			Result
	(dB)	(dB)	(dB)		GFSK (dBc)	8DPSK (dBc)	$\pi/4$ DQPSK (dBc)	
Lower	56.949	57.143	55.020	20	36.949	37.143	35.020	PASS
Upper	64.584	63.596	63.459		44.584	43.596	43.459	PASS


- With hopping

Outside Frequency Band	GFSK	8DPSK	$\pi/4$ DQPSK	Limit (dBc)	Margin			Result
	(dB)	(dB)	(dB)		GFSK (dBc)	8DPSK (dBc)	$\pi/4$ DQPSK (dBc)	
Lower	61.263	59.883	55.130	20	41.263	39.883	35.130	PASS
Upper	65.617	63.685	64.611		45.617	43.685	44.611	PASS


Test Plots without hopping (GFSK)
Band Edges (Low-CH)



Test Plots without hopping (GFSK)
Band Edges (High-CH)




Test Plots without hopping (8DPSK)
Band Edges (Low-CH)




Test Plots without hopping (8DPSK)
Band Edges (High-CH)




Test Plots without hopping ($\pi/4$ DQPSK)
Band Edges (Low-CH)




Test Plots without hopping ($\pi/4$ DQPSK)
Band Edges (High-CH)



Test Plots with hopping (GFSK)
Band Edges (Low-CH)



Test Plots with hopping (GFSK)
Band Edges (High-CH)



Test Plots with hopping (8DPSK)

Band Edges (Low-CH)




Test Plots with hopping (8DPSK)


Band Edges (High-CH)



Test Plots with hopping ($\pi/4$ DQPSK)
Band Edges (Low-CH)



Test Plots with hopping ($\pi/4$ DQPSK)
Band Edges (High-CH)




8.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)

LIMIT

According to §15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Configuration



TEST PROCEDURE

The Channel Separation test is performed with hopping on. And the 20 dB Bandwidth test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.2 in ANSI 63.10-2013)

- 1) Span: Wide enough to capture the peaks of two adjacent channels
- 2) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3) VBW $\geq$ RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) All the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

TEST RESULTS

No non-compliance noted

Test Data

Channel Separation (kHz)			20dB Bandwidth (kHz)				Limit (kHz)	Result
GFSK	8DPSK	$\pi/4$ DQPSK	Channel	GFSK	8DPSK	$\pi/4$ DQPSK		
1001	998	1001	Low CH	1014	1305	1292	>25 or >2/3 of the 20dB BW	Pass
			Middle CH	1004	1302	1289		
			High CH	1013	1300	1290		

Occupied Bandwidth (99% BW)

99% BW (kHz)			
Channel	GFSK	8DPSK	$\pi/4$ DQPSK
Low CH	906.29	1175.3	1172.7
Middle CH	902.91	1172.4	1168.2
High CH	903.89	1172.6	1173.3

Note : We can not know what use channel in AFH mode. So, we can not test in AFH mode. Also, if the test performs some channel in AFH mode, the test result is not different with normal mode.


Test Plots (GFSK) Channel Separation



Test Plots (8DPSK) Channel Separation




Test Plots ($\pi/4$ DQPSK)
Channel Separation




Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (Low-CH)




Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (Mid-CH)




Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (High-CH)




Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (Low-CH)




Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (Mid-CH)




Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (High-CH)




Test Plots ($\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (Low-CH)




Test Plots ($\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (Mid-CH)



Test Plots ($\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (High-CH)




8.4 NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

Test Configuration



TEST PROCEDURE

The Bluetooth frequency hopping function of the EUT was enabled.

The Spectrum Analyzer is set to (7.8.3 in ANSI 63.10-2013)

- 1) Span: the frequency band of operation
- 2) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 3) VBW $\geq$ RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) Allow the trace to stabilize.

TEST RESULTS

No non-compliance noted


Test Data

Result (No. of CH)			Limit	Result
GFSK	8DPSK	$\pi/4$ DQPSK		
79	79	79	>15	Pass

Note : In case of AFH mode, minimum number of hopping channels is 20.


Test Plots (GFSK)

Number of Channels (2.4 GHz - 2.441 GHz)




Test Plots (GFSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




Test Plots (8DPSK)

Number of Channels (2.4 GHz - 2.441 GHz)




Test Plots (8DPSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




Test Plots ($\pi/4$ DQPSK)

Number of Channels (2.4 GHz - 2.441 GHz)



Test Plots ($\pi/4$ DQPSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




8.5 TIME OF OCCUPANCY (DWELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

Test Configuration



TEST PROCEDURE

This test is performed with hopping off.

EUT was set to transmit the longest packet type (DH5)

The Spectrum Analyzer is set to (7.8.4 in ANSI 63.10-2013)

- 1) Span: Zero span, centered on a hopping channel
- 2) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
- 3) Sweep = as necessary to capture the entire dwell time per hopping channel
- 4) Detector: Peak
- 5) Trace: Max hold

The marker-delta function was used to determine the dwell time.

Normal Mode / EDR Mode

DH 5(The longest packet type for GFSK)

CH Mid : $2.890 * (1600/6)/79 * 31.6 = 308.27$ (ms)

2-DH 5(The longest packet type for $\pi/4$ DQPSK)

CH Mid : $2.890 * (1600/6)/79 * 31.6 = 308.27$ (ms)

3-DH 5(The longest packet type for 8DPSK)

CH Mid : $2.885 * (1600/6)/79 * 31.6 = 307.73$ (ms)

AFH Mode

DH 5(The longest packet type for GFSK)

CH Mid : $2.890 * (800/6)/20 * 8.0 = 154.13 \text{ (ms)}$

2-DH 5(The longest packet type for $\pi/4$ DQPSK)

CH Mid : $2.890 * (800/6)/20 * 8.0 = 154.13 \text{ (ms)}$

3-DH 5(The longest packet type for 8DPSK)

CH Mid : $2.885 * (800/6)/20 * 8.0 = 153.9 \text{ (ms)}$

Note :

A DH5 Packet need 5 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 1600/6 hops per second with 79 channels. So the system have each channel 3.3755 times per second and so for 31.6 seconds the system have 106.7 times of appearance.

Each tx-time per appearance of DH5 is 2.892 ms.

Dwell time = Tx-time * 106.7


TEST RESULTS

See the table.


	Channel	GFSK	8DPSK	$\pi/4$ DQPSK
Pulse Time (ms)	Low	2.885	2.890	2.890
	Mid	2.890	2.890	2.885
	High	2.885	2.890	2.885

	Channel	GFSK	8DPSK	$\pi/4$ DQPSK	Period Time (s)	Limit (ms)	Result
Total of Dwell (ms)	Low	307.73	308.27	308.27	31.6	400	PASS
	Mid	308.27	308.27	307.73	31.6		PASS
	High	307.73	308.27	307.73	31.6		PASS


Test Plots (GFSK)
Dwell Time (Low-CH)




Test Plots (GFSK)
Dwell Time (Mid-CH)




Test Plots (GFSK)
Dwell Time (High-CH)




Test Plots (8DPSK)
Dwell Time (Low-CH)



Test Plots (8DPSK)
Dwell Time (Mid-CH)




Test Plots (8DPSK)
Dwell Time (High-CH)




Test Plots ($\pi/4$ DQPSK)

Dwell Time (Low-CH)



Test Plots ($\pi/4$ DQPSK)

Dwell Time (Mid-CH)



8.6 SPURIOUS EMISSIONS


8.6.1 CONDUCTED SPURIOUS EMISSIONS

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer.

The Spectrum Analyzer is set to (7.8.8 in ANSI 63.10-2013)

- 1) Span: 30 MHz to 10 times the operating frequency in GHz.
- 2) RBW: 100 kHz
- 3) VBW: 300 kHz
- 4) Sweep: Coupled
- 5) Detector: Peak

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.

This test is performed with hopping off.

TEST RESULTS

No non-compliance noted.

Note : In order to simplify the report, attached plots were only the worst case channel and data rate.


FACTORS FOR FREQUENCY

Freq(MHz)	Factor(dB)
30	7.18
100	6.35
200	7.04
300	6.58
400	6.26
500	5.95
600	6.17
700	6.34
800	6.72
900	7.08
1000	7.38
2000	7.78
2400*	7.36
2500*	7.44
3000	7.88
4000	8.95
5000	9.57
6000	6.68
7000	9.99
8000	8.34
9000	9.61
10000	10.47
11000	8.96
12000	9.73
13000	8.84
14000	9.50
15000	11.54
16000	8.14
17000	11.73
18000	9.71
19000	10.40
20000	11.69
21000	10.72
22000	12.31
23000	9.85
24000	12.52
25000	11.07
26000	10.50


Note : 1. ** is fundamental frequency range.

2. Factor = Cable loss + Splitter loss

Test Plots (8DPSK)- 30 MHz - 1 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 1 GHz – 3 GHz
Spurious Emission (Mid-CH)




Note : Fundamental maximum level(average mode) is 1.54 dBm. Limit line is 20 dBc down from the fundamental. So, limit is -18.46 dBm.


Test Plots (8DPSK)- 3 GHz - 5 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 5 GHz - 7 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 7 GHz - 9 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 9 GHz - 11 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 11 GHz - 13 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 13 GHz – 15 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)– 15 GHz - 17 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 17 GHz - 19 GHz
Spurious Emission (Mid-CH)




Test Plots (8DPSK)- 19 GHz - 21 GHz
Spurious Emission (Mid-CH)



Test Plots (8DPSK)- 21 GHz - 23 GHz
Spurious Emission (Mid-CH)



Test Plots (8DPSK)- 23 GHz - 25 GHz
Spurious Emission (Mid-CH)




8.6.2 RADIATED SPURIOUS EMISSIONS**LIMIT : §15.247(d), §15.205, §15.209**

1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. Spectrum Setting
 - a. Peak: 1 GHz – 25 GHz, RBW = 1 MHz, VBW $\geq 3 \times$ RBW
 - b. Average: 1 GHz – 25 GHz, RBW = 1 MHz, VBW $\geq 1/\tau$ Hz, where τ = pulse width in seconds.

Note :

1. We are performed the RSE and radiated band edge using standard radiated method.
2. The duty cycle factor for BT mode.

BT Mode	T _{on} (ms)	VBW(1/T) (Hz)	The actual setting value of VBW (Hz)
GFSK	2.885	347	1000
8DPSK	2.890	346	1000
$\pi/4$ DQPSK	2.885	347	1000

TEST RESULTS**9 kHz – 30MHz****Operation Mode:** Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor
5. This test is performed with hopping off.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. This test is performed with hopping off.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Above 1 GHz

Operation Mode: CH Low(GFSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	54.34	-2.96	V	51.38	73.98	22.60	PK
4804	48.30	-2.96	V	45.34	53.98	8.64	AV
7206	48.90	6.88	V	55.78	73.98	18.20	PK
7206	38.35	6.88	V	45.23	53.98	8.75	AV
4804	57.16	-2.96	H	54.2	73.98	19.78	PK
4804	51.33	-2.96	H	48.37	53.98	5.61	AV
7206	49.32	6.88	H	56.2	73.98	17.78	PK
7206	39.30	6.88	H	46.18	53.98	7.80	AV

Operation Mode: CH Low(8DPSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	53.32	-2.96	V	50.36	73.98	23.62	PK
4804	42.47	-2.96	V	39.51	53.98	14.47	AV
7206	47.24	6.88	V	54.12	73.98	19.86	PK
7206	34.50	6.88	V	41.38	53.98	12.60	AV
4804	55.63	-2.96	H	52.67	73.98	21.31	PK
4804	45.06	-2.96	H	42.1	53.98	11.88	AV
7206	47.55	6.88	H	54.43	73.98	19.55	PK
7206	34.85	6.88	H	41.73	53.98	12.25	AV

Operation Mode: CH Low($\pi/4$ DQPSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBUV/m]	Limit [dBUV/m]	Margin [dB]	Measurement Type
4804	52.59	-2.96	V	49.63	73.98	24.35	PK
4804	42.59	-2.96	V	39.63	53.98	14.35	AV
7206	47.61	6.88	V	54.49	73.98	19.49	PK
7206	34.78	6.88	V	41.66	53.98	12.32	AV
4804	55.75	-2.96	H	52.79	73.98	21.19	PK
4804	45.10	-2.96	H	42.14	53.98	11.84	AV
7206	48.09	6.88	H	54.97	73.98	19.01	PK
7206	35.01	6.88	H	41.89	53.98	12.09	AV

※ A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
- Spectrum setting:
 - Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - Average Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
- FYI : Duty Cycle Correction Factor (79 channel hopping)
 - Time to cycle through all channels= $\Delta t = \tau$ [ms] x 79 channels = 229.100 ms, where τ = pulse width
 - $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 1$
 - Worst Case Dwell Time = τ [ms] x $H' = 2.900$ ms
 - Duty Cycle Correction = $20 \log (\text{Worst Case Dwell Time} / 100 \text{ms}) \text{ dB} = -30.752 \text{ dB}$
- Duty Cycle Correction Factor (AFH mode – minimum channel number case - 20 channels)
 - Time to cycle through all channels= $\Delta t = \tau$ [ms] x 20 channels = 58.00 ms, where τ = pulse width
 - $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 2$
 - Worst Case Dwell Time = τ [ms] x $H' = 5.800$ ms

- d. Duty Cycle Correction(AFH) = $20\log (\text{Worst Case Dwell Time}/ 100\text{ms}) \text{ dB} = -24.7314 \text{ dB}$
- e. We applied DCCF in the test result which hopping channel number is 20.
- 8. We have done Normal Mode and EDR Mode test.
- 9. This test is performed with hopping off.
- 10. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH Mid(GFSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	53.96	-2.60	V	51.36	73.98	22.62	PK
4882	46.30	-2.60	V	43.7	53.98	10.28	AV
7323	49.78	6.11	V	55.89	73.98	18.09	PK
7323	39.50	6.11	V	45.61	53.98	8.37	AV
4882	55.95	-2.60	H	53.35	73.98	20.63	PK
4882	49.93	-2.60	H	47.33	53.98	6.65	AV
7323	50.05	6.11	H	56.16	73.98	17.82	PK
7323	40.02	6.11	H	46.13	53.98	7.85	AV

Operation Mode: CH Mid(8DPSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	52.84	-2.60	V	50.24	73.98	23.74	PK
4882	42.66	-2.60	V	40.06	53.98	13.92	AV
7323	48.33	6.11	V	54.44	73.98	19.54	PK
7323	35.04	6.11	V	41.15	53.98	12.83	AV
4882	53.79	-2.60	H	51.19	73.98	22.79	PK
4882	43.96	-2.60	H	41.36	53.98	12.62	AV
7323	48.68	6.11	H	54.79	73.98	19.19	PK
7323	35.21	6.11	H	41.32	53.98	12.66	AV

Operation Mode: CH Mid($\pi/4$ DQPSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBUV/m]	Limit [dBUV/m]	Margin [dB]	Measurement Type
4882	51.86	-2.60	V	49.26	73.98	24.72	PK
4882	42.18	-2.60	V	39.58	53.98	14.40	AV
7323	47.64	6.11	V	53.75	73.98	20.23	PK
7323	35.09	6.11	V	41.2	53.98	12.78	AV
4882	53.67	-2.60	H	51.07	73.98	22.91	PK
4882	43.06	-2.60	H	40.46	53.98	13.52	AV
7323	48.78	6.11	H	54.89	73.98	19.09	PK
7323	35.28	6.11	H	41.39	53.98	12.59	AV

※ A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

Notes:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
- Spectrum setting:
 - Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - Average Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
- FYI : Duty Cycle Correction Factor (79 channel hopping)
 - Time to cycle through all channels= $\Delta t = \tau$ [ms] x 79 channels = 229.100 ms, where τ = pulse width
 - $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 1$
 - Worst Case Dwell Time = τ [ms] x $H' = 2.900$ ms
 - Duty Cycle Correction = $20 \log (\text{Worst Case Dwell Time} / 100 \text{ms}) \text{ dB} = -30.752 \text{ dB}$
- Duty Cycle Correction Factor (AFH mode – minimum channel number case - 20 channels)
 - Time to cycle through all channels= $\Delta t = \tau$ [ms] x 20 channels = 58.00 ms, where τ = pulse width
 - $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 2$
 - Worst Case Dwell Time = τ [ms] x $H' = 5.800$ ms

- d. Duty Cycle Correction(AFH) = $20\log (\text{Worst Case Dwell Time}/ 100\text{ms}) \text{ dB} = -24.7314 \text{ dB}$
- e. We applied DCCF in the test result which hopping channel number is 20.
- 8. We have done Normal Mode and EDR Mode test.
- 9. This test is performed with hopping off.
- 10. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH High(GFSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	53.84	-2.53	V	51.31	73.98	22.67	PK
4960	45.81	-2.53	V	43.28	53.98	10.70	AV
7440	49.03	5.73	V	54.76	73.98	19.22	PK
7440	38.75	5.73	V	44.48	53.98	9.50	AV
4960	54.98	-2.53	H	52.45	73.98	21.53	PK
4960	48.02	-2.53	H	45.49	53.98	8.49	AV
7440	49.64	5.73	H	55.37	73.98	18.61	PK
7440	39.03	5.73	H	44.76	53.98	9.22	AV

Operation Mode: CH High(8DPSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	52.94	-2.53	V	50.41	73.98	23.57	PK
4960	41.15	-2.53	V	38.62	53.98	15.36	AV
7440	47.91	5.73	V	53.64	73.98	20.34	PK
7440	34.53	5.73	V	40.26	53.98	13.72	AV
4960	53.64	-2.53	H	51.11	73.98	22.87	PK
4960	42.23	-2.53	H	39.7	53.98	14.28	AV
7440	48.05	5.73	H	53.78	73.98	20.20	PK
7440	34.85	5.73	H	40.58	53.98	13.40	AV

Operation Mode: CH High ($\pi/4$ DQPSK)

Frequency [MHz]	Reading DBuV	※A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBUV/m]	Limit [dBUV/m]	Margin [dB]	Measurement Type
4960	52.43	-2.53	V	49.90	73.98	24.08	PK
4960	41.55	-2.53	V	39.02	53.98	14.96	AV
7440	47.25	5.73	V	52.98	73.98	21.00	PK
7440	34.66	5.73	V	40.39	53.98	13.59	AV
4960	53.68	-2.53	H	51.15	73.98	22.83	PK
4960	42.47	-2.53	H	39.94	53.98	14.04	AV
7440	47.59	5.73	H	53.32	73.98	20.66	PK
7440	34.83	5.73	H	40.56	53.98	13.42	AV

※ A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN


Notes:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
- Spectrum setting:
 - Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - Average Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
- FYI : Duty Cycle Correction Factor (79 channel hopping)
 - Time to cycle through all channels= $\Delta t = \tau$ [ms] x 79 channels = 229.100 ms, where τ = pulse width
 - $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 1$
 - Worst Case Dwell Time = τ [ms] x $H' = 2.900$ ms
 - Duty Cycle Correction = $20\log (\text{Worst Case Dwell Time} / 100\text{ms}) \text{ dB} = -30.752 \text{ dB}$
- Duty Cycle Correction Factor (AFH mode – minimum channel number case - 20 channels)
 - Time to cycle through all channels= $\Delta t = \tau$ [ms] x 20 channels = 58.00 ms, where τ = pulse width
 - $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 2$
 - Worst Case Dwell Time = τ [ms] x $H' = 5.800$ ms
 - Duty Cycle Correction (AFH) = $20\log (\text{Worst Case Dwell Time} / 100\text{ms}) \text{ dB} = -24.7314 \text{ dB}$

- e. We applied DCCF in the test result which hopping channel number is 20.
- 8. We have done Normal Mode and EDR Mode test.
- 9. This test is performed with hopping off.
- 10. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.


■ **RESULT PLOTS (Worst case : x-H)**

Radiated Spurious Emissions plot – Average Reading (GFSK, Ch. Low 2rd Harmonic)




Date: 29.JAN.2016 11:05:51

Radiated Spurious Emissions plot – Peak Reading (GFSK, Ch. Low 2rd Harmonic)




Date: 29.JAN.2016 11:06:29

Radiated Spurious Emissions plot – Average Reading (8DPSK, Ch. Low 2rd Harmonic)




Date: 29.JAN.2016 11:14:52

Radiated Spurious Emissions plot – Peak Reading (8DPSK, Ch. Low 2rd Harmonic)




Date: 29.JAN.2016 11:14:36

Radiated Spurious Emissions plot – Average Reading ($\pi/4$ DQPSK, Ch. Low 2rd Harmonic)



Date: 29.JAN.2016 11:13:46

Radiated Spurious Emissions plot – Peak Reading ($\pi/4$ DQPSK, Ch. Low 2rd Harmonic)



Date: 29.JAN.2016 11:14:17

8.6.3 RADIATED RESTRICTED BAND EDGES

Test Requirements and limit, §15.247(d), §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode	Normal(GFSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78

Frequency [MHz]	Reading dBuV	※ A.F.+CL [dB]	Ant. Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.88	31.31	H	0	57.19	73.98	16.79	PK
2390.0	12.46	31.31	H	-24.73	19.04	53.98	34.94	AV
2390.0	25.58	31.31	V	0	56.89	73.98	17.09	PK
2390.0	12.38	31.31	V	-24.73	18.96	53.98	35.02	AV
2483.5	34.69	31.37	H	0	66.06	73.98	7.92	PK
2483.5	31.79	31.37	H	-24.73	38.43	53.98	15.55	AV
2483.5	32.55	31.37	V	0	63.92	73.98	10.06	PK
2483.5	29.52	31.37	V	-24.73	36.16	53.98	17.82	AV

Operation Mode	EDR(8DPSK)
Operating Frequency	2402 MHz , 2480 MHz
Channel No	CH 0, CH 78

Frequency [MHz]	Reading dBuV	※ A.F.+CL [dB]	Ant. Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.72	31.31	H	0	57.03	73.98	16.95	PK
2390.0	12.35	31.31	H	-24.73	18.93	53.98	35.05	AV
2390.0	25.49	31.31	V	0	56.80	73.98	17.18	PK
2390.0	12.40	31.31	V	-24.73	18.98	53.98	35.00	AV
2483.5	34.41	31.37	H	0	65.78	73.98	8.20	PK
2483.5	30.04	31.37	H	-24.73	36.68	53.98	17.30	AV
2483.5	32.71	31.37	V	0	64.08	73.98	9.90	PK
2483.5	27.75	31.37	V	-24.73	34.39	53.98	19.59	AV

Operation Mode	EDR(π /4DQPSK)
Operating Frequency	2402 MHz , 2480 MHz
Channel No	CH 0, CH 78

Frequency [MHz]	Reading dBuV	※ A.F.+CL [dB]	Ant. Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.64	31.31	H	0	56.95	73.98	17.03	PK
2390.0	12.39	31.31	H	-24.73	18.97	53.98	35.01	AV
2390.0	25.36	31.31	V	0	56.67	73.98	17.31	PK
2390.0	12.24	31.31	V	-24.73	18.82	53.98	35.16	AV
2483.5	34.78	31.37	H	0	66.15	73.98	7.83	PK
2483.5	30.05	31.37	H	-24.73	36.69	53.98	17.29	AV
2483.5	32.90	31.37	V	0	64.27	73.98	9.71	PK
2483.5	27.52	31.37	V	-24.73	34.16	53.98	19.82	AV


※ A·F: ANTENNA FACTOR
 C·L: CABLE LOSS
 AMP GAIN: AMPLIFIER GAIN

Notes:

1. Frequency range of measurement = 2483.5 MHz ~ 2500 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss + Duty Cycle Correction Factor
3. Spectrum setting:
 - a. Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - b. Average Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
4. FYI : Duty Cycle Correction Factor (79 channel hopping)
 - a. Time to cycle through all channels= $\Delta t = \tau$ [ms] x 79 channels = 229.100 ms, where τ = pulse width
 - b. $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 1$
 - c. Worst Case Dwell Time = τ [ms] x $H' = 2.900$ ms
 - d. Duty Cycle Correction = $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$ dB = -30.752 dB
5. Duty Cycle Correction Factor (AFH mode – minimum channel number case - 20 channels)
 - a. Time to cycle through all channels= $\Delta t = \tau$ [ms] x 20 channels = 58.00 ms, where τ = pulse width
 - b. $100 \text{ ms} / \Delta t$ [ms] = $H \rightarrow$ Round up to next highest integer, $H' = 2$
 - c. Worst Case Dwell Time = τ [ms] x $H' = 5.800$ ms
 - d. Duty Cycle Correction (AFH) = $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$ dB = -24.7314 dB
 - e. We applied DCCF in the test result which hopping channel number is 20.
6. We have done Normal Mode, EDR Mode.
7. This test is performed with hopping off.
8. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.


■ **RESULT PLOTS (Worst case : x-H)**

Radiated Restricted Band Edges plot – Average Reading (GFSK, Ch.78)



Date: 29.JAN.2016 12:32:16


Radiated Restricted Band Edges plot – Peak Reading (GFSK, Ch.78)



Date: 29.JAN.2016 12:31:08


Note : Only the worst case plots for Radiated Restricted Band Edges.

Radiated Restricted Band Edges plot – Average Reading (8DPSK, Ch.78)



Date: 29.JAN.2016 12:29:04


Radiated Restricted Band Edges plot – Peak Reading (8DPSK, Ch.78)



Date: 29.JAN.2016 12:28:33


Note : Only the worst case plots for Radiated Restricted Band Edges.

Radiated Restricted Band Edges plot – Average Reading ($\pi/4$ DQPSK, Ch.78)



Date: 29.JAN.2016 12:29:27

Radiated Restricted Band Edges plot – Peak Reading ($\pi/4$ DQPSK, Ch.78)



Date: 29.JAN.2016 12:30:28

Note : Only the worst case plots for Radiated Restricted Band Edges.

8.7 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

RESULT PLOTS

Conducted Emissions (Line 1)

EMI Auto Test(15)


1 / 2

HCT TEST Report

Common Information

EUT: LG-K500N
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: BT MODE
 Operator Name: SK LEE

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	46.1	9.000	Off	N	9.6	19.9	66.0
0.188000	41.1	9.000	Off	N	9.6	23.0	64.1
0.226000	36.6	9.000	Off	N	9.6	26.0	62.6
0.262000	35.0	9.000	Off	N	9.6	26.4	61.4
0.374000	35.4	9.000	Off	N	9.6	23.0	58.4
0.444000	33.3	9.000	Off	N	9.6	23.7	57.0
1.186000	29.7	9.000	Off	N	9.7	26.3	56.0
1.198000	30.9	9.000	Off	N	9.7	25.1	56.0
1.212000	30.2	9.000	Off	N	9.7	25.8	56.0
1.218000	31.0	9.000	Off	N	9.7	25.0	56.0
1.238000	30.4	9.000	Off	N	9.7	25.6	56.0
1.260000	27.6	9.000	Off	N	9.7	28.4	56.0
6.342000	26.4	9.000	Off	N	9.9	33.6	60.0
6.666000	27.1	9.000	Off	N	9.9	32.9	60.0
7.198000	27.3	9.000	Off	N	9.9	32.7	60.0
7.278000	27.4	9.000	Off	N	9.9	32.6	60.0

2/3/2016

9:21:42

EMI Auto Test(15)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
7.358000	26.9	9.000	Off	N	9.9	33.1	60.0
7.496000	27.3	9.000	Off	N	9.9	32.7	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	33.8	9.000	Off	N	9.6	22.2	56.0
0.184000	28.6	9.000	Off	N	9.6	25.7	54.3
0.188000	29.2	9.000	Off	N	9.6	24.9	54.1
0.222000	25.3	9.000	Off	N	9.6	27.4	52.7
0.226000	24.2	9.000	Off	N	9.6	28.4	52.6
0.372000	25.9	9.000	Off	N	9.6	22.6	48.5
1.182000	24.6	9.000	Off	N	9.7	21.4	46.0
1.188000	24.6	9.000	Off	N	9.7	21.4	46.0
1.200000	25.0	9.000	Off	N	9.7	21.0	46.0
1.210000	25.0	9.000	Off	N	9.7	21.0	46.0
1.236000	24.7	9.000	Off	N	9.7	21.3	46.0
1.260000	23.0	9.000	Off	N	9.7	23.0	46.0
6.342000	20.9	9.000	Off	N	9.9	29.1	50.0
6.666000	21.6	9.000	Off	N	9.9	28.4	50.0
7.252000	22.0	9.000	Off	N	9.9	28.0	50.0
7.278000	21.9	9.000	Off	N	9.9	28.1	50.0
7.358000	21.8	9.000	Off	N	9.9	28.2	50.0
7.978000	21.3	9.000	Off	N	9.9	28.7	50.0

2/3/2016

9:21:42

Conducted Emissions (Line 2)

EMI Auto Test(15)


1 / 2

HCT TEST Report

Common Information

EUT: LG-K500N
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: BT MODE
 Operator Name: SK LEE

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	46.0	9.000	Off	L1	9.7	20.0	66.0
0.186000	42.7	9.000	Off	L1	9.6	21.5	64.2
0.222000	38.9	9.000	Off	L1	9.6	23.8	62.7
0.260000	36.8	9.000	Off	L1	9.6	24.6	61.4
0.300000	37.5	9.000	Off	L1	9.6	22.7	60.2
0.408000	37.2	9.000	Off	L1	9.7	20.5	57.7
1.160000	31.7	9.000	Off	L1	9.7	24.3	56.0
1.190000	31.1	9.000	Off	L1	9.7	24.9	56.0
1.198000	32.0	9.000	Off	L1	9.7	24.0	56.0
1.204000	31.2	9.000	Off	L1	9.7	24.8	56.0
1.228000	30.1	9.000	Off	L1	9.7	25.9	56.0
1.232000	31.1	9.000	Off	L1	9.7	24.9	56.0
7.504000	31.6	9.000	Off	L1	10.0	28.4	60.0
7.512000	31.6	9.000	Off	L1	10.0	28.4	60.0
7.834000	31.4	9.000	Off	L1	10.0	28.6	60.0
18.812000	29.7	9.000	Off	L1	10.2	30.3	60.0

2/3/2016

9:31:17

EMI Auto Test(15)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
19.584000	29.3	9.000	Off	L1	10.2	30.7	60.0
19.686000	29.3	9.000	Off	L1	10.2	30.7	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	33.3	9.000	Off	L1	9.7	22.7	56.0
0.188000	28.8	9.000	Off	L1	9.6	25.3	54.1
0.222000	25.5	9.000	Off	L1	9.6	27.2	52.7
0.226000	24.8	9.000	Off	L1	9.6	27.8	52.6
0.298000	27.9	9.000	Off	L1	9.6	22.4	50.3
0.410000	32.1	9.000	Off	L1	9.7	15.5	47.6
1.160000	25.1	9.000	Off	L1	9.7	20.9	46.0
1.190000	24.8	9.000	Off	L1	9.7	21.2	46.0
1.194000	25.8	9.000	Off	L1	9.7	20.2	46.0
1.206000	24.7	9.000	Off	L1	9.7	21.3	46.0
1.230000	24.7	9.000	Off	L1	9.7	21.3	46.0
1.242000	24.2	9.000	Off	L1	9.7	21.8	46.0
7.504000	24.2	9.000	Off	L1	10.0	25.8	50.0
7.512000	24.3	9.000	Off	L1	10.0	25.7	50.0
7.740000	24.1	9.000	Off	L1	10.0	25.9	50.0
7.834000	23.9	9.000	Off	L1	10.0	26.1	50.0
18.812000	20.9	9.000	Off	L1	10.2	29.1	50.0
19.584000	20.0	9.000	Off	L1	10.2	30.0	50.0

2/3/2016

9:31:17

Note : The Worst case of Conducted Emission is standalone mode.

9. LIST OF TEST EQUIPMENT

9.1 LIST OF TEST EQUIPMENT(Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216/ LISN	12/28/2015	Annual	100073
Rohde & Schwarz	ESCI / TEST RECEIVER	12/28/2015	Annual	100584
Agilent	E4440A/ Spectrum Analyzer	03/18/2015	Annual	US45303008
Agilent	N9020A / SIGNAL ANALYZER	06/30/2015	Annual	MY51110085
Agilent	N9030A / SIGNAL ANALYZER	11/24/2015	Annual	MY49431210
Agilent	N1911A/Power Meter	07/09/2015	Annual	MY45100523
Agilent	N1921A /POWER SENSOR	07/09/2015	Annual	MY45241059
Agilent	87300B/Directional Coupler	11/30/2015	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	06/15/2015	Annual	5001
Hewlett Packard	E3632A / DC POWER SUPPLY	03/11/2015	Annual	KR75303962
Agilent	8493C / Attenuator(10 dB)	07/23/2015	Annual	07560
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/11/2015	Annual	100422

9.2 LIST OF TEST EQUIPMENT(Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Schwarzbeck	VULB 9160/ TRILOG Antenna	10/10/2014	Biennial	3368
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
CERNEX	CBL18265035 / POWER AMP	07/27/2015	Annual	22966
Schwarzbeck	BBHA 9120D/ Horn Antenna	05/07/2015	Biennial	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	04/30/2015	Biennial	BBHA9170124
Rohde & Schwarz	FSP / Spectrum Analyzer	01/15/2016	Annual	839117/011
Wainwright Instrument	WHF3.0/18G-10EF / High Pass Filter	06/29/2015	Annual	8
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	06/15/2015	Annual	1
Rohde & Schwarz	LOOP ANTENNA	02/18/2014	Biennial	100179
CERNEX	CBL06185030 / POWER AMP	07/21/2015	Annual	22965
CERNEX	CBLU1183540 / POWER AMP	07/21/2015	Annual	22964
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/11/2015	Annual	100422