

# FCC BT LE REPORT

## FCC Certification

**Applicant Name:**

LG Electronics MobileComm U.S.A., Inc.

**Address:**

1000 Sylvan Avenue, Englewood Cliffs NJ 07632

**Date of Issue:**

July 18, 2016

**Test Site/Location:**

HCT CO., LTD., 74,Seoicheon-ro 578beon-gil,Majang-myeo,Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Report No.:** HCT-R-1607-F007-1**HCT FRN:** 0005866421**IC Recognition No.:** 5944A-5**FCC ID : ZNFK600****APPLICANT : LG Electronics MobileComm U.S.A., Inc.**

**Model(s):** LG-K600  
**Additional Model(s):** LGK600, K600  
**EUT Type:** GSM/WCDMA/LTE Phone with Bluetooth, WLAN, NFC  
**RF Peak Output Power:** 6.450 dBm (4.416 mW)  
**Frequency Range:** 2402 MHz -2480 MHz  
**Modulation type** GFSK  
**FCC Classification:** Digital Transmission System(DTS)  
**FCC Rule Part(s):** Part 15.247

**Engineering Statement:**

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



**Report prepared by**  
**: Seoul Ki Lee**  
**Test Engineer of RF Team**



**Approved by**  
**: Jong Seok Lee**  
**Manager of RF Team**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1607-F007	July 8, 2016	- First Approval Report
HCT-R-1607-F007-1	July 18, 2016	- Added the min and max conditions for data packet length in the report.

# Table of Contents

1. GENERAL INFORMATION .....	4
2. EUT DESCRIPTION .....	4
3. TEST METHODOLOGY .....	5
3.1 EUT CONFIGURATION .....	5
3.2 EUT EXERCISE .....	5
3.3 GENERAL TEST PROCEDURES .....	5
3.4 DESCRIPTION OF TEST MODES .....	5
4. INSTRUMENT CALIBRATION.....	6
5. FACILITIES AND ACCREDITATIONS .....	6
5.1 FACILITIES .....	6
5.2 EQUIPMENT .....	6
6. ANTENNA REQUIREMENTS .....	6
7. MEASUREMENT UNCERTAINTY .....	7
8. SUMMARY TEST OF RESULTS .....	8
9. TEST RESULT .....	9
9.1 DUTY CYCLE.....	9
9.2 6 dB BANDWIDTH MEASUREMENT .....	11
9.3 OUTPUT POWER MEASUREMENT.....	16
9.4 POWER SPECTRAL DENSITY .....	27
9.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS .....	33
9.6 RADIATED MEASUREMENT.....	52
9.6.1 RADIATED SPURIOUS EMISSIONS.....	52
9.6.2 RADIATED RESTRICTED BAND EDGES .....	66
9.7 POWERLINE CONDUCTED EMISSIONS .....	71
10. LIST OF TEST EQUIPMENT .....	76
10.1 LIST OF TEST EQUIPMENT(Conducted Test) .....	76
10.2 LIST OF TEST EQUIPMENT(Radiated Test).....	77

## 1. GENERAL INFORMATION

**Applicant:** LG Electronics MobileComm U.S.A., Inc.  
**Address:** 1000 Sylvan Avenue, Englewood Cliffs NJ 07632  
**FCC ID:** ZNFK600  
**EUT Type:** GSM/WCDMA/LTE Phone with Bluetooth, WLAN, NFC  
**Model (s):** LG-K600  
**Date(s) of Tests:** May 17, 2016 ~ June 22, 2016  
**Place of Tests:** HCT Co., Ltd.  
 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea  
 (IC Recognition No. : 5944A-5)

## 2. EUT DESCRIPTION

<b>Model</b>	LG-K600	
<b>Additional Model(s):</b>	LGK600, K600	
<b>EUT Type</b>	GSM/WCDMA/LTE Phone with Bluetooth, WLAN, NFC	
<b>Power Supply</b>	DC 3.85 V	
<b>Battery Infomation</b>	Model: BL-51YF Type: Li-ion Battery	
<b>Frequency Range</b>	TX: 2402 MHz ~ 2480 MHz RX: 2402 MHz ~ 2480 MHz	
<b>Max. RF Output Power</b>	Peak	Data packet length (Min)_6.450 dBm (4.416 mW) / Data packet length (Max)_6.393 dBm (4.358 mW)
	Average	Data packet length (Min)_6.260 dBm (4.227 mW) / Data packet length (Max)_6.250 dBm (4.217 mW)
<b>BT Operating Mode</b>	BT _Low Energy Mode	
<b>Modulation Type</b>	GFSK	
<b>Number of Channels</b>	40 Channels	
<b>Antenna Specification</b>	Manufacturer: Ace Technology Antenna type: INTERNAL ANTENNA Peak Gain : -1.47 dBi	

### **3. TEST METHODOLOGY**

FCC KDB 558074 D01 DTS Meas Guidance v03r05 dated April 8, 2016 entitled "Guidance for Performing Compliance Measurements on Digital Transmission Systems(DTS) and the measurement procedure described in ANSI C63.10(Version : 2013) 'the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices'.

#### **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **3.2 EUT EXERCISE**

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### **3.3 GENERAL TEST PROCEDURES**

#### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013)

#### **Conducted Antenna Terminal**

See Section from 9.1 to 9.2.(KDB 558074 v03r05)

### **3.4 DESCRIPTION OF TEST MODES**

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

## 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 07, 2015 (Registration Number: 90661)

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 6. ANTENNA REQUIREMENTS

### According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

\* The antennas of this E.U.T are permanently attached.

\*The E.U.T Complies with the requirement of §15.203

## 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	6.07

## 8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	CONDUCTED	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 8.7		PASS
Radiated Spurious Emissions	§15.205, 15.209	cf. Section 8.6.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.6.2		PASS


## 9. TEST RESULT

### 9.1 DUTY CYCLE

#### ■ TEST PROCEDURE

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value. Set  $VBW \geq RBW$ . Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

#### ■ TEST CONFIGURATION



#### ■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074 v03r05.

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if  $T \leq 6.25$  microseconds. ( $50/6.25 = 8$ )

The zero-span method was used because all measured T data are  $> 6.25$  microseconds and both RBW and VBW are  $> 50/T$ .

1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz ( $\geq$  RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep  $> 100$
6. Trace mode = Clear write
7. Measure  $T_{total}$  and  $T_{on}$
8. Calculate Duty Cycle =  $T_{on} / T_{total}$  and Duty Cycle Factor =  $10 \cdot \log(1/\text{Duty Cycle})$


Data packet length (Min)

LE Mode	T <sub>on</sub>	T <sub>total</sub>	Duty Cycle	Duty Cycle Factor (dB)
	(ms)	(ms)		
	0.3901	0.6245	0.6247	2.04


Data packet length (Max)

LE Mode	T <sub>on</sub>	T <sub>total</sub>	Duty Cycle	Duty Cycle Factor
	(ms)	(ms)		
	2.1350	2.5000	0.8540	0.69

RESULT PLOTS\_ Data packet length (Min)



RESULT PLOTS\_ Data packet length (Max)




### 9.2 6 dB BANDWIDTH MEASUREMENT

#### Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6 dB bandwidth is 500 kHz.

#### ■ TEST CONFIGURATION



#### ■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.1 in KDB 558074 v03r05)

RBW = 100 kHz

VBW ≥ 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

Note : We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

#### ■ TEST RESULT\_ Data packet length (Min)


Mode	Channel	6 dB Bandwidth (kHz)	Limit (kHz)	Pass/Fail
BT LE	0	<b>718.0</b>	> 500	Pass
	19	<b>722.4</b>		Pass
	39	<b>712.7</b>		Pass

#### ■ TEST RESULT\_ Data packet length (Max)

Mode	Channel	6 dB Bandwidth (kHz)	Limit (kHz)	Pass/Fail
BT LE	0	<b>676.2</b>	> 500	Pass
	19	<b>672.9</b>		Pass
	39	<b>675.2</b>		Pass

▣ RESULT PLOTS\_Min


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)




**6 dB Bandwidth plot (High-CH 39)**



▣ RESULT PLOTS\_Max


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)



**6 dB Bandwidth plot (High-CH 39)**




### 9.3 OUTPUT POWER MEASUREMENT

#### Test Requirements and limit, §15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of a Spectrum Analyzer. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

#### ■ TEST CONFIGURATION



#### ■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We use the spectrum analyzer's integrated band power measurement function.

This EUT TX condition is actual operating mode by BT LE mode test program.

The Spectrum Analyzer is set to

- Peak Power ( Procedure 9.1.1 in KDB 558074 v03r05)
  - RBW  $\geq$  DTS Bandwidth
  - VBW  $\geq 3 \times$  RBW
  - SPAN  $\geq 3 \times$  RBW
  - Detector Mode = Peak
  - Sweep = auto couple
  - Trace Mode = max hold
  - Allow trace to fully stabilize.
  - Use peak marker function to determine the peak amplitude level
  
- Average Power ( Procedure 9.2.2.4 in KDB 558074 v03r05)
  - Measure the duty cycle
  - Set span to at least 1.5 times the OBW
  - RBW = 1-5 % of the OBW, not to exceed 1 MHz.
  - VBW  $\geq 3 \times$  RBW.
  - Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
  - Sweep time = auto.
  - Detector = RMS(i.e., power averaging)
  - Do not use sweep triggering. Allow the sweep to "free run".

Trace average at least 100 traces in power averaging(RMS) mode.

Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges.

Add  $10 \log (1/x)$ , where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

#### ■ Sample Calculation

Output Power = Reading Value + ATT loss + Cable loss(1 ea) + Duty Cycle Factor

Output Power = 10 dBm + 10 dB + 0.8 dB + 0.2 dB = 21.0 dBm

Note :

1. Spectrum reading values are not plot data. The power results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.7 dB is offset for 2.4 GHz Band.

■ TEST RESULTS-Peak

Conducted Output Power Measurements\_ Data packet length (Min)

LE Mode		Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.		
2402	0	4.792	30
2440	19	6.450	30
2480	39	4.513	30

Conducted Output Power Measurements\_ Data packet length (Max)

LE Mode		Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.		
2402	0	4.760	30
2440	19	6.393	30
2480	39	4.452	30

■ TEST RESULTS-Average


Conducted Output Power Measurements\_ Data packet length (Min)

LE Mode		Measured Power(dBm)	Duty Cycle Factor (dB)	Measured Power(dBm) + Duty Cycle Factor(dB)	Limit (dBm)
Frequency[MHz]	Channel No.				
2402	0	2.61	2.04	4.65	30
2440	19	4.22	2.04	6.26	30
2480	39	2.27	2.04	4.31	30


Conducted Output Power Measurements\_ Data packet length (Max)

LE Mode		Measured Power(dBm)	Duty Cycle Factor (dB)	Measured Power(dBm) + Duty Cycle Factor(dB)	Limit (dBm)
Frequency[MHz]	Channel No.				
2402	0	3.87	0.69	4.55	30
2440	19	5.57	0.69	6.25	30
2480	39	3.51	0.69	4.19	30


▣ RESULT PLOTS-Peak\_Data packet length (Min)  
Conducted Output Power (Low-CH 0)




Conducted Output Power (Mid-CH 19)




**Conducted Output Power (High-CH 39)**




▣ RESULT PLOTS-Peak\_ Data packet length (Max)  
Conducted Output Power (Low-CH 0)




Conducted Output Power (Mid-CH 19)



**Conducted Output Power (High-CH 39)**



▣ RESULT PLOTS-Average\_ Data packet length (Min)  
Conducted Output Power (Low-CH 0)




Conducted Output Power (Mid-CH 19)




**Conducted Output Power (High-CH 39)**




▣ RESULT PLOTS-Average\_ Data packet length (Max)  
Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)



**Conducted Output Power (High-CH 39)**




## 9.4 POWER SPECTRAL DENSITY

### Test Requirements and limit, §15.247(e)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

**Minimum Standard – The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.**

### ■ TEST CONFIGURATION



### ■ TEST PROCEDURE

We tested according to Procedure 10.2 in KDB 558074 v03 r05

The spectrum analyzer is set to :

Set analyzer center frequency to DTS channel center frequency.

Span = 1.5 times the DTS channel bandwidth.

RBW = 3 kHz ≤ RBW ≤ 100 kHz.

VBW ≥ 3 x RBW.

Sweep = auto couple

Detector = peak

Trace Mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### ■ Sample Calculation

PSD = Reading Value + ATT loss + Cable loss(1 ea)

Output Power = -5 dBm + 10 dB + 0.8 dB = 5.8 dBm

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.7 dB is offset for 2.4 GHz Band.

■ TEST RESULTS

Conducted Power Density Measurements\_ Data packet length (Min)


Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/Fail
2402	0	LE	-9.351	8	Pass
2440	19		-7.534	8	Pass
2480	39		-9.606	8	Pass

Conducted Power Density Measurements\_ Data packet length (Max)


Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/Fail
2402	0	LE	-10.829	8	Pass
2440	19		-9.165	8	Pass
2480	39		-11.088	8	Pass

RESULT PLOTS\_Data packet length (Min)


Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)



**Power Spectral Density (High-CH 39)**




RESULT PLOTS\_ Data packet length (Max)

Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)




**Power Spectral Density (High-CH 39)**



**9.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS****Test Requirements and limit, §15.247(d)**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Limit : 20 dBc****■ TEST CONFIGURATION****■ TEST PROCEDURE**

The transmitter output is connected to the spectrum analyzer. (Procedure 11.0 in KDB 558074 v03r05)

RBW = 100 kHz

VBW  $\geq 3 \times$  RBW

Set span to encompass the spectrum to be examined

Detector = Peak

Trace Mode = max hold

Sweep time = auto couple

Ensure that the number of measurement points  $\geq 2 \times$  Span/RBW

Allow trace to fully stabilize.

Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 10<sup>th</sup> harmonic range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1(KDB558074 v03r05), so the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak

PSD level in 100 kHz (i.e., 20 dBc).

2. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.
3. Spectrum offset = Attenuator loss + Cable loss
4. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.7 dB is offset for 2.4 GHz Band.
5. In case of conducted spurious emissions test, please check factors blow table.
6. In order to simplify the report, attached plots were only the worst case channel and data rate.

**■ FACTORS FOR FREQUENCY**

Freq(MHz)	Factor(dB)
30	11.30
100	9.83
200	10.19
300	10.13
400	10.23
500	10.25
600	10.32
700	10.35
800	10.35
900	10.34
1000	10.39
2000	10.64
2400*	10.65
2500*	10.67
3000	10.68
4000	10.89
5000	11.07
6000	11.06
7000	11.35
8000	11.32
9000	11.48
10000	11.56
11000	11.56
12000	11.68
13000	11.83

14000	11.90
15000	11.98
16000	12.04
17000	12.02
18000	12.08
19000	12.07
20000	12.14
21000	12.17
22000	12.31
23000	12.60
24000	12.34
25000	12.53

Note : 1. \*\* is fundamental frequency range.  
2. Factor = Cable loss + Attenuator loss

▣ RESULT PLOTS\_ Data packet length (Min)  
BandEdge (Low-CH 0)




BandEdge (High-CH 39)




30 MHz ~ 1 GHz

Conducted Spurious Emission (Mid-CH 19)




1 GHz ~ 3 GHz

Conducted Spurious Emission (Mid-CH 19)




3 GHz ~ 5 GHz

Conducted Spurious Emission (Mid-CH 19)




5 GHz ~ 7 GHz

Conducted Spurious Emission (Mid-CH 19)




7 GHz ~ 9 GHz

Conducted Spurious Emission (Mid-CH 19)




9 GHz ~ 11 GHz

Conducted Spurious Emission (Mid-CH 19)




11 GHz ~ 13 GHz

Conducted Spurious Emission (Mid-CH 19)




13 GHz ~ 15 GHz

Conducted Spurious Emission (Mid-CH 19)




15 GHz ~ 17 GHz

Conducted Spurious Emission (Mid-CH 19)




17 GHz ~ 19 GHz

Conducted Spurious Emission (Mid-CH 19)




19 GHz ~ 21 GHz

Conducted Spurious Emission (Mid-CH 19)




21 GHz ~ 23 GHz

Conducted Spurious Emission (Mid-CH 19)



23 GHz ~ 25 GHz

Conducted Spurious Emission (Mid-CH 19)




RESULT PLOTS\_ Data packet length (Max)

BandEdge (Low-CH 0)




BandEdge (High-CH 39)




30 MHz ~ 1 GHz

Conducted Spurious Emission (Mid-CH 19)




1 GHz ~ 3 GHz

Conducted Spurious Emission (Mid-CH 19)




3 GHz ~ 5 GHz

Conducted Spurious Emission (Mid-CH 19)




5 GHz ~ 7 GHz

Conducted Spurious Emission (Mid-CH 19)




7 GHz ~ 9 GHz

Conducted Spurious Emission (Mid-CH 19)




9 GHz ~ 11 GHz

Conducted Spurious Emission (Mid-CH 19)




11 GHz ~ 13 GHz

Conducted Spurious Emission (Mid-CH 19)




13 GHz ~ 15 GHz

Conducted Spurious Emission (Mid-CH 19)




15 GHz ~ 17 GHz

Conducted Spurious Emission (Mid-CH 19)




17 GHz ~ 19 GHz

Conducted Spurious Emission (Mid-CH 19)




19 GHz ~ 21 GHz

Conducted Spurious Emission (Mid-CH 19)




21 GHz ~ 23 GHz

Conducted Spurious Emission (Mid-CH 19)



23 GHz ~ 25 GHz

Conducted Spurious Emission (Mid-CH 19)




**9.6 RADIATED MEASUREMENT.****9.6.1 RADIATED SPURIOUS EMISSIONS.**

Test Requirements and limit, §15.205, §15.209


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

### Test Configuration


#### Below 30 MHz



#### 30 MHz - 1 GHz



**Above 1 GHz**



**TEST PROCEDURE USED**

Method 12.1 in KDB 558074 v03r05

**Spectrum Setting**

- Peak

Peak emission levels are measured by setting the instrument as follows:

RBW = cf. Table 1.

VBW  $\geq 3 \times$  RBW.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes.

(Note that the required measurement time may be longer for low duty cycle applications).

**Table 1 —RBW as a function of frequency**

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- Average (duty cycle < 98%, duty cycle variations are less than ±2%)

Set RBW = 1 MHz

Set VBW ≥ 3 x RBW

Detector = RMS.

Averaging type = power (i.e., RMS).

Sweep time = auto.

Trace mode = average (at least 100 traces).

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.

**Note :**

1. We are performed the RSE and radiated band edge using standard radiated method(RMS).
2. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).
3. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)

**Data packet length (Min)**

LE Mode	T <sub>on</sub> (ms)	T <sub>total</sub> (ms)	Duty Cycle	Duty Cycle Factor (dB)
	0.3901	0.6245	0.6247	2.04

**Data packet length (Max)**

LE Mode	T <sub>on</sub> (ms)	T <sub>total</sub> (ms)	Duty Cycle	Duty Cycle Factor (dB)
	2.1350	2.5000	0.8540	0.69

**TEST RESULTS****9 kHz – 30MHz****Operation Mode:** Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

**Notes:**

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

**TEST RESULTS****Below 1 GHz****Operation Mode:** Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

**Notes:**

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

**Above 1 GHz**

Operation Mode: CH.0\_ Data packet length (Min)

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	49.35	0.00	-1.02	V	48.33	73.98	25.65	PK
4804	36.82	2.04	-1.02	V	37.84	53.98	16.14	AV
7206	46.91	0.00	8.82	V	55.73	73.98	18.25	PK
7206	33.65	2.04	8.82	V	44.51	53.98	9.47	AV
4804	49.09	0.00	-1.02	H	48.07	73.98	25.91	PK
4804	36.76	2.04	-1.02	H	37.78	53.98	16.20	AV
7206	46.77	0.00	8.82	H	55.59	73.98	18.39	PK
7206	33.61	2.04	8.82	H	44.47	53.98	9.51	AV

\*A.F. : Antenna Factor / C.L. : Cable Loss / A.G. : Amplifier Gain / D.F. : Distance Factor

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.0\_ Data packet length (Max)

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	49.45	0.00	-1.02	V	48.43	73.98	25.55	PK
4804	36.88	0.69	-1.02	V	36.545	53.98	17.44	AV
7206	46.82	0.00	8.82	V	55.64	73.98	18.34	PK
7206	33.73	0.69	8.82	V	43.235	53.98	10.75	AV
4804	49.21	0.00	-1.02	H	48.19	73.98	25.79	PK
4804	36.72	0.69	-1.02	H	36.385	53.98	17.60	AV
7206	46.69	0.00	8.82	H	55.51	73.98	18.47	PK
7206	33.64	0.69	8.82	H	43.145	53.98	10.84	AV

\*A.F. : Antenna Factor / C.L. : Cable Loss / A.G. : Amplifier Gain / D.F. : Distance Factor

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.19\_ Data packet length (Min)

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	49.42	0.00	-0.66	V	48.76	73.98	25.22	PK
4882	37.40	2.04	-0.66	V	38.78	53.98	15.20	AV
7323	46.18	0.00	8.05	V	54.23	73.98	19.75	PK
7323	34.00	2.04	8.05	V	44.09	53.98	9.89	AV
4882	48.75	0.00	-0.66	H	48.09	73.98	25.89	PK
4882	37.44	2.04	-0.66	H	38.82	53.98	15.16	AV
7323	45.82	0.00	8.05	H	53.87	73.98	20.11	PK
7323	33.89	2.04	8.05	H	43.98	53.98	10.00	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.19\_ Data packet length (Max)

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	49.10	0.00	-0.66	V	48.44	73.98	25.54	PK
4882	37.42	0.69	-0.66	V	37.445	53.98	16.54	AV
7323	46.23	0.00	8.05	V	54.28	73.98	19.70	PK
7323	33.90	0.69	8.05	V	42.635	53.98	11.35	AV
4882	48.86	0.00	-0.66	H	48.2	73.98	25.78	PK
4882	37.35	0.69	-0.66	H	37.375	53.98	16.61	AV
7323	46.11	0.00	8.05	H	54.16	73.98	19.82	PK
7323	33.92	0.69	8.05	H	42.655	53.98	11.33	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.39\_ Data packet length (Min)

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	50.06	0.00	-0.59	V	49.47	73.98	24.51	PK
4960	37.64	2.04	-0.59	V	39.09	53.98	14.89	AV
7440	46.11	0.00	7.67	V	53.78	73.98	20.20	PK
7440	33.82	2.04	7.67	V	43.53	53.98	10.45	AV
4960	49.48	0.00	-0.59	H	48.89	73.98	25.09	PK
4960	37.65	2.04	-0.59	H	39.1	53.98	14.88	AV
7440	45.56	0.00	7.67	H	53.23	73.98	20.75	PK
7440	33.79	2.04	7.67	H	43.5	53.98	10.48	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor =  $20 \log (\text{test distance} / \text{specific distance})$  (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.39\_ Data packet length (Max)


Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	49.80	0.00	-0.59	V	49.21	73.98	24.77	PK
4960	37.62	0.69	-0.59	V	37.72	53.98	16.27	AV
7440	46.14	0.00	7.67	V	53.81	73.98	20.17	PK
7440	33.85	0.69	7.67	V	42.205	53.98	11.78	AV
4960	49.23	0.00	-0.59	H	48.64	73.98	25.34	PK
4960	37.57	0.69	-0.59	H	37.665	53.98	16.32	AV
7440	45.79	0.00	7.67	H	53.46	73.98	20.52	PK
7440	33.78	0.69	7.67	H	42.135	53.98	11.85	AV

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor =  $20 \log (\text{test distance} / \text{specific distance})$  (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.


■ RESULT PLOTS\_Data packet length (Min) (Worst case : z-V)

**Radiated Spurious Emissions plot – Average Reading (Ch.0 2nd Harmonic)**



Date: 31.MAY.2016 11:42:11


**Radiated Spurious Emissions plot – Peak Reading (Ch.0 2nd Harmonic)**



Date: 31.MAY.2016 12:12:09


■ RESULT PLOTS\_Data packet length (Max) (Worst case : z-V)

**Radiated Spurious Emissions plot – Average Reading (Ch.0 2nd Harmonic)**



Date: 31.MAY.2016 12:11:29

**Radiated Spurious Emissions plot – Peak Reading (Ch.0 2nd Harmonic)**



Date: 31.MAY.2016 12:10:56

**Note : Only the worst case plots for Radiated Spurious Emissions.**

### 9.6.2 RADIATED RESTRICTED BAND EDGES

#### Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode	BT_LE Data packet length (Min)
Operating Frequency	2402 MHz
Channel No.	0

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	15.242	0.00	33.25	H	48.49	73.98	25.49	PK
2390.0	4.138	2.04	33.25	H	39.43	53.98	14.55	AV
2390.0	15.366	0.00	33.25	V	48.62	73.98	25.36	PK
2390.0	4.235	2.04	33.25	V	39.53	53.98	14.46	AV

Operation Mode	BT_LE Data packet length (Max)
Operating Frequency	2402 MHz
Channel No.	0

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	15.239	0.00	33.25	H	48.49	73.98	25.49	PK
2390.0	4.154	0.69	33.25	H	38.09	53.98	15.89	AV
2390.0	15.381	0.00	33.25	V	48.63	73.98	25.35	PK
2390.0	4.336	0.69	33.25	V	38.27	53.98	15.71	AV

**Notes:**

1. Frequency range of measurement = 2310 MHz ~ 2390 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss + Duty Cycle Factor + Distance Factor
3. Distance extrapolation factor =  $20 \log (\text{test distance} / \text{specific distance})$  (dB)
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The radiated restricted band edge measurements are measured with a spectrum analyzer connected to the receive antenna while the EUT is transmitting.

Operation Mode BT\_LE Data packet length (Min)  
 Operating Frequency 2480 MHz  
 Channel No. 39

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	15.397	0.00	33.31	H	48.71	73.98	25.27	PK
2483.5	4.475	2.04	33.31	H	39.83	53.98	14.16	AV
2483.5	15.768	0.00	33.31	V	49.08	73.98	24.90	PK
2483.5	4.518	2.04	33.31	V	39.87	53.98	14.11	AV

Operation Mode BT\_LE Data packet length (Max)  
 Operating Frequency 2480 MHz  
 Channel No. 39


Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	15.361	0.00	33.31	H	48.67	73.98	25.31	PK
2483.5	4.438	0.69	33.31	H	38.43	53.98	15.55	AV
2483.5	15.570	0.00	33.31	V	48.88	73.98	25.10	PK
2483.5	4.486	0.69	33.31	V	38.48	53.98	15.50	AV

**Notes:**


1. Frequency range of measurement = 2483.5 MHz ~ 2500 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss + Duty Cycle Factor + Distance Factor
3. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The radiated restricted band edge measurements are measured with a spectrum analyzer connected to the receive antenna while the EUT is transmitting.

▣ RESULT PLOTS\_Data packet length (Min) (Worst case : z-V)

Radiated Restricted Band Edges plot – Average Reading (Ch.39)




Radiated Restricted Band Edges plot – Peak Reading (Ch.39)




▣ RESULT PLOTS\_Data packet length (Max) (Worst case : z-V)

Radiated Restricted Band Edges plot – Average Reading (Ch.39)



Radiated Restricted Band Edges plot – Peak Reading (Ch.39)



Note : Only the worst case plots for Radiated Restricted Band Edges.

## 9.7 POWERLINE CONDUCTED EMISSIONS

### Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

### Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

▣ RESULT PLOTS

Conducted Emissions (Line 1)

BT LE MODE L1


1 / 2

## HCT TEST Report

### Common Information

EUT: LG-K600  
 Manufacturer: LG  
 Test Site: SHIELD ROOM  
 Operating Conditions: BT LE MODE

FCC CLASS B



— FCC CLASS B\_QP      — FCC CLASS B\_AV      — Preview Result 1-PK+  
 — Preview Result 2-AVG      X Final Result 1-QPK      X Final Result 2-CAV

### Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.496000	39.0	9.000	Off	L1	9.7	17.1	56.1
0.502000	37.6	9.000	Off	L1	9.7	18.4	56.0
0.700000	36.9	9.000	Off	L1	9.7	19.1	56.0
0.730000	37.8	9.000	Off	L1	9.7	18.2	56.0
0.824000	37.6	9.000	Off	L1	9.7	18.4	56.0
0.828000	38.4	9.000	Off	L1	9.7	17.6	56.0
0.912000	38.3	9.000	Off	L1	9.7	17.7	56.0
0.916000	37.0	9.000	Off	L1	9.7	19.0	56.0
0.974000	37.9	9.000	Off	L1	9.7	18.1	56.0
0.984000	38.7	9.000	Off	L1	9.7	17.3	56.0
0.988000	38.7	9.000	Off	L1	9.7	17.3	56.0
1.018000	38.2	9.000	Off	L1	9.7	17.8	56.0
5.198000	30.6	9.000	Off	L1	9.9	29.4	60.0
5.240000	30.2	9.000	Off	L1	9.9	29.8	60.0
5.252000	29.5	9.000	Off	L1	9.9	30.5	60.0
6.570000	29.6	9.000	Off	L1	9.9	30.4	60.0
6.640000	29.2	9.000	Off	L1	9.9	30.8	60.0
6.856000	28.3	9.000	Off	L1	9.9	31.7	60.0

2016-06-01

오전 10:25:00

BT LE MODE L1

2 / 2

**Final Result 2**

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.496000	24.0	9.000	Off	L1	9.7	22.1	46.1
0.502000	23.8	9.000	Off	L1	9.7	22.2	46.0
0.700000	23.8	9.000	Off	L1	9.7	22.2	46.0
0.730000	18.7	9.000	Off	L1	9.7	27.3	46.0
0.822000	25.8	9.000	Off	L1	9.7	20.2	46.0
0.858000	24.1	9.000	Off	L1	9.7	21.9	46.0
0.974000	24.9	9.000	Off	L1	9.7	21.1	46.0
0.982000	26.0	9.000	Off	L1	9.7	20.0	46.0
0.986000	26.3	9.000	Off	L1	9.7	19.7	46.0
1.060000	25.5	9.000	Off	L1	9.7	20.5	46.0
1.160000	24.1	9.000	Off	L1	9.7	21.9	46.0
2.076000	26.3	9.000	Off	L1	9.8	19.7	46.0
5.198000	21.9	9.000	Off	L1	9.9	28.1	50.0
5.240000	19.7	9.000	Off	L1	9.9	30.3	50.0
5.252000	19.2	9.000	Off	L1	9.9	30.8	50.0
6.570000	18.6	9.000	Off	L1	9.9	31.4	50.0
6.640000	18.6	9.000	Off	L1	9.9	31.4	50.0
6.856000	18.0	9.000	Off	L1	9.9	32.0	50.0

2016-06-01

오전 10:25:00

**Conducted Emissions (Line 2)**

BT LE MODE N


1 / 2

**HCT TEST Report**

**Common Information**

EUT: LG-K600  
 Manufacturer: LG  
 Test Site: SHIELD ROOM  
 Operating Conditions: BT LE MODE

FCC CLASS B



— FCC CLASS B\_QP      —×— Final Result 1-QPK      —×— Final Result 2-CAV  
 — Preview Result 2-AVG

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.508000	37.3	9.000	Off	N	9.6	18.7	56.0
0.784000	36.1	9.000	Off	N	9.7	19.9	56.0
0.824000	35.9	9.000	Off	N	9.7	20.1	56.0
0.828000	36.6	9.000	Off	N	9.7	19.4	56.0
0.832000	37.0	9.000	Off	N	9.7	19.0	56.0
0.840000	37.5	9.000	Off	N	9.7	18.5	56.0
0.924000	37.1	9.000	Off	N	9.7	18.9	56.0
0.974000	36.6	9.000	Off	N	9.7	19.4	56.0
0.978000	36.9	9.000	Off	N	9.7	19.1	56.0
1.012000	36.6	9.000	Off	N	9.7	19.4	56.0
1.036000	37.6	9.000	Off	N	9.7	18.4	56.0
1.046000	36.5	9.000	Off	N	9.7	19.5	56.0
15.678000	28.7	9.000	Off	N	10.2	31.3	60.0
15.704000	28.6	9.000	Off	N	10.2	31.4	60.0
15.750000	28.1	9.000	Off	N	10.2	31.9	60.0
17.340000	28.7	9.000	Off	N	10.2	31.3	60.0
17.344000	27.9	9.000	Off	N	10.2	32.1	60.0
17.644000	27.8	9.000	Off	N	10.2	32.2	60.0

2016-06-01

오전 10:11:05

BT LE MODE N

2 / 2

**Final Result 2**

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.784000	23.6	9.000	Off	N	9.7	22.4	46.0
0.796000	24.6	9.000	Off	N	9.7	21.4	46.0
0.812000	26.1	9.000	Off	N	9.7	19.9	46.0
0.828000	24.0	9.000	Off	N	9.7	22.0	46.0
0.832000	24.6	9.000	Off	N	9.7	21.4	46.0
0.840000	25.5	9.000	Off	N	9.7	20.5	46.0
0.924000	24.8	9.000	Off	N	9.7	21.2	46.0
1.010000	24.6	9.000	Off	N	9.7	21.4	46.0
1.016000	26.0	9.000	Off	N	9.7	20.0	46.0
1.032000	26.0	9.000	Off	N	9.7	20.0	46.0
1.036000	25.8	9.000	Off	N	9.7	20.2	46.0
1.048000	24.8	9.000	Off	N	9.7	21.2	46.0
15.704000	19.4	9.000	Off	N	10.2	30.6	50.0
15.708000	19.3	9.000	Off	N	10.2	30.7	50.0
17.340000	19.7	9.000	Off	N	10.2	30.3	50.0
17.344000	19.0	9.000	Off	N	10.2	31.0	50.0
17.376000	18.8	9.000	Off	N	10.2	31.2	50.0
17.738000	17.2	9.000	Off	N	10.2	32.8	50.0

2016-06-01

오전 10:11:05

## 10. LIST OF TEST EQUIPMENT

### 10.1 LIST OF TEST EQUIPMENT(Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	12/28/2015	Annual	100073
Rohde & Schwarz	ESCI / Test Receiver	12/28/2015	Annual	100584
Agilent	N9020A / Signal Analyzer	06/30/2015	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	11/24/2015	Annual	MY49431210
Agilent	N1911A / Power Meter	07/09/2015	Annual	MY45100523
Agilent	N1921A / Power Sensor	03/11/2016	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/30/2015	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	06/14/2016	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	03/09/2016	Annual	KR75303962
Agilent	8493C / Attenuator(10 dB)	07/21/2015	Annual	07560
Rohde & Schwarz	CBT / Bluetooth Tester	05/16/2016	Annual	100422

**10.2 LIST OF TEST EQUIPMENT(Radiated Test)**

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Audix	AM4000 / Antenna Position Tower	N/A	N/A	N/A
Audix	Turn Table	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Rohde & Schwarz	Loop Antenna	02/23/2016	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	04/15/2015	Biennial	255
Schwarzbeck	BBHA 9120D / Horn Antenna	05/07/2015	Biennial	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	09/03/2015	Biennial	BBHA9170541
Rohde & Schwarz	FSP / Spectrum Analyzer	09/24/2015	Annual	100688
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/23/2015	Annual	101068-SZ
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	06/29/2015	Annual	8
Wainwright Instruments	WHFX7.0/18G-8SS / High Pass Filter	05/13/2016	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	07/06/2015	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/26/2016	Annual	2
Agilent	8493C-10 / Attenuator(10 dB)	08/20/2015	Annual	76649
CERNEX	CBLU1183540 / Power Amplifier	07/21/2015	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/21/2015	Annual	22965
CERNEX	CBL18265035 / Power Amplifier	07/27/2015	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	07/09/2015	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	04/01/2016	Annual	3000C000276