

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DREFCC1709-0257
2. Customer
 - Name : LG Electronics MobileComm USA, Inc.
 - Address : 1000 Sylvan Ave. Englewood Cliffs NJ 07632
3. Use of Report : Grant of Certification
4. Product Name / Model Name : Mobile phone / L-01K
5. Test Method Used : ANSI C 63.4:2014
FCC Part 15 Subpart B
(Class B personal computers and peripherals)
6. Date of Test : 2017-09-20
7. Testing Environment : Temperature (24 ~ 26) °C , Humidity (45 ~ 47) % R.H.
8. Test Result : Refer to the attached Test Result

Affirmation	Tested by	Technical Manager
	Name : JinYoung Park (Signature)	Name : MyungJin Song (Signature)

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose.

This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2017. 09. 27.

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

CONTENTS

1. General Remarks	3
2. Test Laboratory	3
3. General Information of EUT	4
4. Test Summary	5
4.1 Applied standards and test results	5
4.2 Test environment and conditions.....	5
4.3 Test result Summary	5
5. Test Set-up and operation mode	6
5.1 Principle of Configuration Selection	6
5.2 Test Operation Mode.....	6
5.3 Support Equipment Used.....	6
6. Test Results : Emission	7
6.1 Conducted Disturbance	7
6.2 Radiated Disturbance	10
Appendix 1	22
List of Test and Measurement Instruments	22
Appendix 2	24
Report Revision History	24

1. General Remarks

This report contains the result of tests performed by:

DT&C Co., Ltd.

42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042

<http://www.dtnc.net>

Tel: +82-31-321-2664 Fax: +82-31-321-1664

2. Test Laboratory

DT&C Co., Ltd. has been accredited / filed / authorized by the agencies listed in the following table;

Certificate	Nation	Agency	Code	Mark
Accreditation	Korea	KOLAS	393	ISO/IEC 17025
Site Filing	USA	FCC	KR0034 101842 678747, 596748, 804488, 165783	Accredited 2.948 Listed
	Canada	IC	5740A-1 5740A-2	Registered
	Japan	VCCI	C-1427 R-1364, R-3385, R-4076, R-4180, T-1442, G-10338, G-754, G-815	Registered
Certification	Korea	KC	KR0034	Designation
	Germany	TUV	CARAT 17 01 89112 004	ISO/IEC 17025

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competent of calibration and testing laboratory".

3. General Information of EUT

Product Name	Mobile phone
Model Name	L-01K
Add Model Name	None
Serial No	None
Type of Sample Tested	Pre-Production
Supplied Power for Test	AC 120 V, 60 Hz
FCC ID	ZNFL01K
Applicant	LG Electronics MobileComm USA, Inc. 1000 Sylvan Ave. Englewood Cliffs NJ 07632
Manufacturer	LG Electronics MobileComm USA, Inc. 1000 Sylvan Ave. Englewood Cliffs NJ 07632

Related Submittal(s) / Grant(s)
Original submittal only.

4. Test Summary

4.1 Applied standards and test results

Test Items	Applied Standards	Results
Conducted Disturbance	ANSI C63.4:2014	C
Radiated Disturbance	ANSI C63.4:2014	C
C=Comply N/C=Not Comply N/T=Not Tested N/A=Not Applicable		

The data in this test report are traceable to the national or international standards.

4.2 Test environment and conditions

Test Items	Test date (YYYY-MM-DD)	Temp (°C)	Humidity (% R.H.)
Conducted Disturbance	2017-09-20	26	45
Radiated Disturbance	2017-09-20	24	47

4.3 Test result Summary

(1) Conducted Emission

Frequency [MHz]	Phase	Result [dB μ V]	Detector	Limit [dB μ V]	Margin [dB]
11.43120	N	44.32	Average	50.00	5.68

(2) Radiated Emission

Frequency [MHz]	Pol.	Result [dB(μ V/m)]	Detector	Limit [dB(μ V/m)]	Margin [dB]
45.763	V	32.42	QP	40.00	7.58

5. Test Set-up and operation mode

5.1 Principle of Configuration Selection

Emission : The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

5.2 Test Operation Mode

- EUT was connected PC by USB cable and continuously operated.
 'READ' & 'WRITE' & 'DELETE' function.

5.3 Support Equipment Used

Unit	Model No.	Serial No.	Manufacturer	CABLE				Back shell	FCC ID
				Connect type	Length (m)	shield	With Ferrite		
KEYBOARD	KB25	N/A	LITEON Technology	USB OUT	1.7	Shield	X	Plastic	-
MOUSE	SM-9023	58Q02855	LG	USB OUT	1.7	Shield	X	Plastic	-
LCD MONITOR	UP2414Qt	CN-0W06C2-7 4445-467-013L	DELL	POWER IN	1.8	Non-shield	X	Plastic	-
				DSUB OUT	1.8	Shield	X	Plastic	
PC	DCNE	861Z8BX	DELL	POWER IN	1.8	Non-shield	X	Plastic	-
				DSUB IN	1.8	Shield	X	Plastic	
				PARALLEL IN	2.0	Shield	X	Plastic	
				SERIAL IN	1.9	Shield	X	Plastic	
				USB IN	1.7	Shield	X	Plastic	
				USB IN	1.7	Shield	X	Plastic	
				USB IN	1.7	Shield	X	Plastic	
				STEREO IN/OUT	2.0	Non-shield	X	Plastic	
SSD 3.0	MU-PT250B	S2WKNPAH70 0337W	SAMSUNG	USB OUT	0.3	Shield	X	Plastic	-
PRINTER	SRP-770	N/A	Bixolon	POWER IN	1.8	Non-shield	X	Plastic	-
				PARALLEL OUT	2.0	Shield	X	Plastic	
				SERIAL OUT	1.9	Shield	X	Plastic	
Headset	COV909	N/A	COSY	STEREO IN/OUT	2.0	Non-shield	X	Plastic	-

6. Test Results : Emission

6.1 Conducted Disturbance

6.1.1 Measurement Procedure

In the range of 0.15 MHz to 30 MHz, the conducted disturbance was measured and set-up was made accordance with **ANSI C63.4**. If the EUT is table top equipment, it was placed on a wooden table with a height of 0.8 m above the reference ground plane and 0.4 m from the conducting wall of the shielded room. Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15 m above the reference ground plane. Connect the EUT's power source lines to the PC power through the LISN. All the other peripherals are connected to the 2nd LISN, if any. Unused measuring port of the LISN was resistively terminated by 50 ohm terminator.

The measuring port of the LISN for EUT was connected to spectrum analyzer. Using conducted emission test software, the emissions were scanned with peak detector mode. After scanning over the frequency range, suspected emissions were selected to perform final measurement. When performing final measurement, the receiver was used which has Quasi-Peak detector and CISPR Average detector. For (0.15 ~ 30) MHz frequency range, Quasi-Peak detector with 10 kHz RBW and 30 kHz VBW was used. By varying the configuration of the test sample and the cable routing it was attempted to maximize the emission. For further description of the configuration refer to the picture of the test set-up.

6.1.2 Limit for Conducted Disturbance

(1) Conducted disturbance at mains ports.

Frequency range (MHz)	Limits dB(μV)			
	Quasi-peak		Average	
	Class A	Class B	Class A	Class B
0.15 to 0.50	79	66 to 56	66	56 to 46
0.50 to 5	73	56	60	46
5 to 30		60		50

Note 1 The lower limit shall apply at the transition frequencies.
 Note 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

- Note) 1. Emission Level = Reading Value + Correction Factor.
 2. Correction Factor = Cable Loss + Insertion Loss of LISN
 3. Margin = Limit - Emission level

Measurement uncertainty :

Expended uncertainty U (95 %, Confidence level, $k = 2$)	2.36 dB
--	---------

Test Result



Results of Conducted Emission

DT&C

Date 2017-09-20

Order No. DTNC1709-06811
Power Supply 120 V 60 Hz
Temp/Humi/Atm 26 °C 45 % R.H. 99.4 kPa
Test Condition PC LINK

LIMIT : CISPR22_B QP
CISPR22_B AV



Results of Conducted Emission

DT&C

Date 2017-09-20

Order No.	DTNC1709-06811
Power Supply	120 V 60 Hz
Temp/Humi/Atm	26 °C 45 % R.H. 99.4 kPa
Test Condition	PC LINK

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.21244	39.63	37.59	0.08	39.71	37.67	63.11	53.11	23.40	15.45	N
2	0.81458	37.27	30.47	0.09	37.36	30.56	56.00	46.00	18.64	15.44	N
3	1.05440	37.95	33.00	0.11	38.06	33.11	56.00	46.00	17.94	12.89	N
4	2.55160	31.34	25.60	0.15	31.49	25.75	56.00	46.00	24.51	20.25	N
5	4.45200	33.85	28.29	0.19	34.04	28.48	56.00	46.00	21.96	17.52	N
6	4.62420	32.82	27.89	0.20	33.02	28.09	56.00	46.00	22.98	17.91	N
7	11.43120	46.46	44.01	0.31	46.77	44.32	60.00	50.00	13.23	5.68	N
8	0.21227	40.87	40.46	0.07	40.94	40.53	63.12	53.12	22.18	12.59	L
9	0.81441	37.38	30.82	0.09	37.47	30.91	56.00	46.00	18.53	15.09	L
10	1.06960	30.35	23.83	0.10	30.45	23.93	56.00	46.00	25.55	22.07	L
11	2.60800	32.79	24.64	0.14	32.93	24.78	56.00	46.00	23.07	21.22	L
12	4.44360	35.86	25.55	0.18	36.04	25.73	56.00	46.00	19.96	20.27	L
13	4.57460	36.87	26.53	0.19	37.06	26.72	56.00	46.00	18.94	19.28	L
14	11.42920	45.87	43.25	0.30	46.17	43.55	60.00	50.00	13.83	6.45	L

6.2 Radiated Disturbance

6.2.1 Measurement Procedure

The radiated disturbance was measured and set-up was made accordance with **ANSI C63.4**.

If the EUT is tabletop equipment, it was placed on a wooden table with a height of 0.8 m above the reference ground plane and 3 m or 10 m away from the interference receiving antenna in the **3m semi-anechoic chamber**. Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15 m above the reference ground plane. Rotate the EUT from (0 - 360)° and position the receiving antenna at heights from (1 - 4) m above the reference ground plane continuously to determine associated with higher emission levels and record them. The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report. For final measurement below 1 GHz frequency range, Quasi-Peak detector with (RBW = 120 kHz Bandwidth) was used. For final measurement above 1 GHz frequency range, Peak detector with (RBW = 1 MHz Bandwidth) and CISPR Average detector with (RBW = 1 MHz Bandwidth) were used. For further description of the configuration refer to the picture of the test set-up.

6.2.2 Limit for Radiated Disturbance

- The test frequency range of Radiated Disturbance measurements are listed below.

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 108	1 000
108 – 500	2 000
500 – 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

(1) Limit for Radiated Emission below 1 000 MHz

Frequency range (MHz)	Class A Equipment (10 m distance)	Class B Equipment (3 m distance)
	Quasi-peak (dB μ V/m)	Quasi-peak (dB μ V/m)
30 to 88	39.1	40
88 to 216	43.5	43.5
216 to 960	46.4	46
960 to 1 000	49.5	54

Note 1 The lower limit shall apply at the transition frequency.
 Note 2 Additional provisions may be required for cases where interference occurs.
 Note 3 According to 15.109(g), as an alternative to the radiated emission limit shown above, digital devices may be shown to comply with the standards(CISPR), Pub. 22 shown as below.

Frequency range (MHz)	Class A Equipment (10 m distance)	Class B Equipment (10 m distance)
	Quasi-peak (dB μ V/m)	Quasi-peak (dB μ V/m)
30 to 230	40	30
230 to 1 000	47	37

(2) Limits for Radiated Emission above 1 000 MHz at a measuring distance of 3 m

Frequency (GHz)	Class A Equipment		Class B Equipment	
	Peak (dB μ V/m)	Average (dB μ V/m)	Peak (dB μ V/m)	Average (dB μ V/m)
1 to 40	80	60	74	54

Note)1. Emission Level = Reading Value + loss - gain + Ant Factor

2. Margin = Limit - Emission level

3. (0.03 ~ 6) GHz : Loss = Cable Loss, Gain = Amp Gain, Ant Factor = Antenna Factor

4. (6 ~ 18) GHz : Loss = Cable Loss, Ant Factor = Antenna Factor - Amp Gain

Measurement uncertainty (10m Chamber) :

Expended uncertainty U (95 %, Confidence level, $k = 2$)	3.50 dB, (30 ~ 1 000) MHz 4.00 dB, (Above 1 GHz)
--	---

Test Result

< 30 MHz ~ 1 GHz >



RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
Power Supply 120 V 60 Hz
Temp/Humi 24 °C 47 % R.H.
Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 6 dB



RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
 Power Supply 120 V 60 Hz
 Temp/Humi 24 °C 47 % R.H.
 Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart B Class B (3m)
 MARGIN: 6 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	75.111	45.70	9.07	1.30	26.81	29.26	40.00	10.74	395	96
2	532.936	42.10	18.36	3.87	26.40	37.93	46.00	8.07	130	350
----- Vertical -----										
3	30.243	42.40	9.35	0.74	26.85	25.64	40.00	14.36	115	235
4	45.763	46.80	11.48	0.98	26.84	32.42	40.00	7.58	290	78
5	48.794	41.10	11.78	1.02	26.84	27.06	40.00	12.94	100	153
6	75.153	45.60	9.06	1.30	26.81	29.15	40.00	10.85	120	23

< (1 ~ 6) GHz _ Peak >



RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
Power Supply 120 V 60 Hz
Temp/Humi 24 °C 47 % R.H.
Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
 Power Supply 120 V 60 Hz
 Temp/Humi 24 °C 47 % R.H.
 Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart.B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1498.125	51.40	28.10	4.15	32.31	51.34	74.0	22.66	100	1
2	1610.625	53.10	28.46	4.21	32.36	53.41	74.0	20.59	100	204
3	1718.750	53.90	29.23	4.42	32.40	55.15	74.0	18.85	100	186
4	2995.625	51.50	32.49	5.88	32.58	57.29	74.0	16.71	100	1
5	3146.250	48.50	32.65	6.10	32.59	54.66	74.0	19.34	100	25
6	3442.500	48.90	32.80	6.72	32.62	55.80	74.0	18.2	100	1
----- Vertical -----										
7	2995.000	49.80	32.49	5.88	32.58	55.59	74.0	18.41	100	358
8	3446.875	47.90	32.80	6.73	32.62	54.81	74.0	19.19	100	176

< (1 ~ 6) GHz _ Average >



RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
Power Supply 120 V 60 Hz
Temp/Humi 24 °C 47 % R.H.
Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
 Power Supply 120 V 60 Hz
 Temp/Humi 24 °C 47 % R.H.
 Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart.B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING CAV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1498.105	40.50	28.10	4.15	32.31	40.44	54.00	13.56	100	12
2	1610.631	38.60	28.46	4.21	32.36	38.91	54.00	15.09	100	235
3	1718.928	39.20	29.23	4.42	32.40	40.45	54.00	13.55	100	192
4	2995.628	36.80	32.49	5.88	32.58	42.59	54.00	11.41	100	12
5	3146.202	36.70	32.65	6.10	32.59	42.86	54.00	11.14	100	32
6	3442.531	37.10	32.80	6.72	32.62	44.00	54.00	10.00	100	215
----- Vertical -----										
7	2995.013	37.50	32.49	5.88	32.58	43.29	54.00	10.71	100	32
8	3446.868	36.80	32.80	6.73	32.62	43.71	54.00	10.29	100	148

< (6 ~ 30) GHz _ Peak >


RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
Power Supply 120 V 60 Hz
Temp/Humi 24 °C 47 % R.H.
Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



* The measurement is performed above 18 GHz up to 30 GHz and not found emissions above 18 GHz.

RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
 Power Supply 120 V 60 Hz
 Temp/Humi 24 °C 47 % R.H.
 Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart.B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	6745.500	43.80	-8.44	9.29	0.00	44.65	74.0	29.35	100	210
2	8997.750	50.00	-6.78	10.33	0.00	53.55	74.0	20.45	100	215
3	9136.500	40.60	-6.70	10.84	0.00	44.74	74.0	29.26	100	215
----- Vertical -----										
4	7785.000	41.70	-7.75	10.30	0.00	44.25	74.0	29.75	100	206
5	8831.250	41.60	-7.02	10.79	0.00	45.37	74.0	28.63	100	206
6	8997.000	53.40	-6.78	10.34	0.00	56.96	74.0	17.04	100	358
7	9130.500	44.70	-6.70	10.81	0.00	48.81	74.0	25.19	100	211
8	11982.750	41.00	-5.51	12.71	0.00	48.20	74.0	25.8	100	358

< (6 ~ 30) GHz _ Average >


RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
Power Supply 120 V 60 Hz
Temp/Humi 24 °C 47 % R.H.
Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



* The measurement is performed above 18 GHz up to 30 GHz and not found emissions above 18 GHz.

RADIATED EMISSION

Date 2017-09-20

Order No. DTNC1709-06811
 Power Supply 120 V 60 Hz
 Temp/Humi 24 °C 47 % R.H.
 Test Condition PC LINK

Memo

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart.B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING CAV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	6745.620	31.50	-8.44	9.29	0.00	32.35	54.00	21.65	100	245
2	8997.778	32.00	-6.78	10.33	0.00	35.55	54.00	18.45	100	246
3	9136.478	30.70	-6.70	10.84	0.00	34.84	54.00	19.16	100	15
----- Vertical -----										
4	7785.031	27.50	-7.75	10.30	0.00	30.05	54.00	23.95	100	175
5	8831.278	28.50	-7.02	10.79	0.00	32.27	54.00	21.73	100	253
6	8997.052	31.60	-6.78	10.34	0.00	35.16	54.00	18.84	100	32
7	9130.657	30.60	-6.70	10.81	0.00	34.71	54.00	19.29	100	175
8	11982.730	26.80	-5.51	12.71	0.00	34.00	54.00	20.00	100	235

List of Test and Measurement Instruments

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment is identified by the Test Laboratory.

1. Conducted Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
<input checked="" type="checkbox"/> MEASUREMENT SOFTWARE	EMI-C VER. 2.00.0143	TSJ	N/A	N/A	N/A
<input checked="" type="checkbox"/> EMI TEST RECEIVER	ESCI	ROHDE & SCHWARZ	100364	2017.02.16	2018.02.16
<input checked="" type="checkbox"/> LISN	NNLK 8121	SCHWARZBECK	06182	2017.04.03	2018.04.03
<input checked="" type="checkbox"/> LISN	LISN1600	TTI	197204	2017.06.07	2018.06.07
<input checked="" type="checkbox"/> SINGLE-PHASE MASTER	4420	NF	3049354420023	2017.09.01	2018.09.01
<input checked="" type="checkbox"/> HIGH PASS FILTER	KFL-007D	KYORITSU	8-2259-4	N/A	N/A
<input checked="" type="checkbox"/> 50 OHM TERMINATOR	CT-01	TME	N/A	2017.01.03	2018.01.03

2. Radiated Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
<input checked="" type="checkbox"/> MEASUREMENT SOFTWARE	EMI-R VER. 2.00.0121	TSJ	N/A	N/A	N/A
<input checked="" type="checkbox"/> EMI TEST RECEIVER	ESU	ROHDE & SCHWARZ	100538	2017.02.03	2018.02.03
<input checked="" type="checkbox"/> TRILOG BROADBAND TEST-ANTENNA <small>NOTE1)</small>	VULB9160	SCHWARZBECK	9160-3339	2017.04.21	2019.04.21
<input checked="" type="checkbox"/> LOW NOISE PRE AMPLIFIER	MLA-100K01-B01-26	TSJ	1252741	2017.02.20	2018.02.20
<input checked="" type="checkbox"/> PRE AMPLIFIER	8449B	AGILENT	3008A01590	2017.02.20	2018.02.20
<input checked="" type="checkbox"/> HORN ANTENNA	3117	ETS-LINDGREN	00152093	2016.02.26	2018.02.26
<input checked="" type="checkbox"/> HORN ANTENNA WITH PREAMPLIFIER	EM-6969	ELECTRO-METRICS	156	2017.01.19	2018.01.19
<input checked="" type="checkbox"/> HORN ANTENNA WITH PREAMPLIFIER	MLA-0618-B03-34	TSJ	1785642	2017.01.19	2018.01.19
<input checked="" type="checkbox"/> EMI TEST RECEIVER	ESU	ROHDE & SCHWARZ	100469	2017.07.06	2018.07.06
<input checked="" type="checkbox"/> LOW NOISE PRE AMPLIFIER	MLA-1840-J02-40	TSJ	13184	2016.10.18	2017.10.18
<input checked="" type="checkbox"/> HORN ANTENNA	SAS-574	A.H.SYSTEMS,INC	155	2017.07.31	2019.07.31

* NOTE1) The measurement antennas were calibrated in accordance to the requirements of C63.5-2006.

Appendix 2

Report Revision History

Revision Date	Description	Revised By	Revision Reviewed By
None	Original	N/A	N/A