



HCT CO., LTD.

CERTIFICATE OF COMPLIANCE FCC Certification

Applicant Name:
LG Electronics MobileComm U.S.A., Inc.

Date of Issue:
June 20, 2012

Address:
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Location:
HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon,
Icheon-si, Kyunggi-Do, Korea

Test Report No.: HCTR1206FR06-1

HCT FRN: 0005866421

FCC ID : ZNFL06D

APPLICANT : LG Electronics MobileComm U.S.A., Inc.

FCC Model(s): L-06D

EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)

Tx Frequency: 1 850.20 - 1 909.80 MHz (GSM1900)

Rx Frequency: 1 930.20 - 1 989.80 MHz (GSM1900)

Max. RF Output Power: 0.964 W EIRP GSM1900 (29.84 dBm)

Emission Designator(s): 247KGXW (GSM1900)

FCC Classification: PCS Licensed Transmitter held to ear (PCE)

FCC Rule Part(s): §24, §2

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)

Report prepared by
: Hyo Sun Kwak

Test engineer of RF Team

Approved by
: Chang Seok Choi

Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1206FR06	June 15, 2012	- First Approval Report
HCTR1206FR06-1	June 20, 2012	- Revised report (Page 9) - Add offset value report page 14, 15

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION.....	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS	6
3.1 EFFECTIVE RADIATED POWER/EQUIVALENT ISOTROPIC RADIATED POWER.....	6
3.2 PEAK- TO- AVERAGE RATIO	7
3.3 OCCUPIED BANDWIDTH.	8
3.4 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	9
3.5 RAIDATED SPURIOUS AND HARMONIC EMISSIONS	10
3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	11
4. LIST OF TEST EQUIPMENT	12
5. SUMMARY OF TEST RESULTS	13
6. SAMPLE CALCULATION	14
7. TEST DATA	15
7.1 CONDUCTED OUTPUT POWER	15
7.2 PEAK-TO-AVERAGE RATIO	15
7.3 OCCUPIED BANDWIDTH	16
7.4 CONDUCTED SPURIOUS EMISSIONS	16
7.4.1 BAND EDGE.....	16
7.5 EQUIVALENT ISOTROPIC RADIATED POWER	17
7.6 RADIATED SPURIOUS EMISSIONS	18
7.6.1 RADIATED SPURIOUS EMISSIONS (GSM1900).....	18
7.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	19
7.7.1 FREQUENCY STABILITY (GSM1900)	19
8. TEST PLOTS.....	20

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: LG Electronics MobileComm U.S.A., Inc.

Address: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632

FCC ID: ZNFL06D

Application Type: Certification

FCC Classification: PCS Licensed Transmitter held to ear (PCE)

FCC Rule Part(s): §24, §2

EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)

FCC Model name(s): L-06D

Tx Frequency: 1 850.20 - 1 909.80 MHz (GSM1900)

Rx Frequency: 1 930.20 - 1 989.80 MHz (GSM1900)

Max. RF Output Power: 0.964 W EIRP GSM1900 (29.84 dBm)

Emission Designator(s): 247KGXW (GSM1900)

Date(s) of Tests: May 07, 2012 ~ May 17, 2012

Antenna Specification
 Manufacturer: Shanghai Amphenol Airwave
 Antenna type: INTERNAL Antenna
 Peak Gain: -4.56 dBi

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

2. INTRODUCTION

2.1. EUT DESCRIPTION

The LG Electronics MobileComm U.S.A., Inc. L-06D PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica) consists of GSM1900 and GPRS A Class12.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY


The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, Korea. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated March 02, 2011 (Registration Number: 90661)

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

3. DESCRIPTION OF TESTS

3.1 EFFECTIVE RADIATED POWER/EQUIVALENT ISOTROPIC RADIATED POWER

Test Set-up



Test Procedure

Radiated emission measurements were performed at an Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters from the receive antenna. A turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D


3.2 PEAK- TO- AVERAGE RATIO

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA and WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. Plots of the EUT's Peak- to- Average Ratio are shown herein.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

3.3 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

Test Procedure

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

3.4 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. The RBW settings used in the testing are greater than 1 % of the occupied bw. The 1 MHz RBW was used to scan from 10 MHz to 10 GHz. (GSM1900 Mode: 10 MHz to 20 GHz). A display line was placed at - 13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

- Band Edge Requirement : According to FCC 24.238(a) specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.


The center frequency of spectrum is the band edge frequency and span is 1MHz RB of the spectrum is 3KHz and VB of the spectrum is 3KHz (GSM)

The center frequency of spectrum is the band edge frequency and span is 5MHz RB of the spectrum is 100KHz and VB of the spectrum is 100KHz(WCDMA)

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

3.5 RAIDATED SPURIOUS AND HARMONIC EMISSIONS

Test Set-up



The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section § 2.948. The Fully-anechoic chamber meets requirements in ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a rotatable platform mounted at three from the antenna mast.

- 1) The unit mounted on a turntable 1.5 m × 1.0 m × 0.80 m is 0.8 meter above test site ground level.
- 2) During the emission test, the turntable is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
- 3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
- 4) The spectrum shall be scanned up to the 10th harmonic of the fundamental frequency.

Test Procedure


The equipment under test is placed on a non-conductive table 3-meters from the receive antenna. A turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
R&S	N9020A	MY51110020	Annual	09/23/2012
Agilent	E9327A/ Power Sensor	MY4442009	Annual	05/02/2013
R&S	CMW500/ Base Station	1201.0002K50_116858	Annual	01/17/2013
MITEQ	AMF-6D-001180-35-20P/AMP	1081666	Annual	09/24/2012
Wainwright	WHK1.2/15G-10EF/H.P.F	2	Annual	05/02/2013
Wainwright	WHK3.3/18G-10EF/H.P.F	1	Annual	05/02/2013
Hewlett Packard	11667B / Power Splitter	10126	Annual	11/04/2012
Digital	EP-3010/ Power Supply	3110117	Annual	11/07/2012
Schwarzbeck	UHAP/ Dipole Antenna	557	Biennial	03/11/2013
Schwarzbeck	UHAP/ Dipole Antenna	558	Biennial	03/11/2013
Korea Engineering	KR-1005L / Chamber	KRAB05063-3CH	Annual	11/07/2012
Schwarzbeck	BBHA 9120D/ Horn Antenna	296	Biennial	02/20/2014
Agilent	E4440A/Spectrum Analyzer	US45303008	Annual	05/02/2013
WEINSCHL	ATTENUATOR	BR0592	Annual	11/07/2012
REOHDE&SCHWARZ	FSP30/Spectrum Analyzer	839117/011	Annual	02/09/2013
Agilent	8960 (E5515C)/ Base Station	GB44400269	Annual	02/10/2013

5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049, 24.238(a)	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 24.238(a)	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions		PASS
2.1046	Conducted Output Power	-		PASS
24.232(d)	Peak- to- Average Ratio	< 13 dB		PASS
2.1055, 24.235	Frequency stability / variation of ambient temperature	< 2.5 ppm		PASS
24.232(c)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS
	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS
2.1053, 24.238(a)	Radiated Spurious and Harmonic Emissions	< 43 + 10log10 (P[Watts]) for all out-of band emissions		PASS

6. SAMPLE CALCULATION

A. EIRP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain	C.L	Pol.	EIRP	
	channel	Freq.(MHz)						W	dBm
GSM1900	512	1,850.20	-14.72	16.89	10.05	1.91	H	0.32	25.02

ERP = SubstituteLEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 0.8 meter above test site ground level.
- 2) During the test , the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power (ERP).

B. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

C. Conducted Output Power and PAR Sample Calculation

Conducted Output Power

$$\begin{aligned} \text{Output Power} &= \text{Reading Value} + \text{Cable loss}(1 \text{ ea}) \\ &= 30 \text{ dBm} + 0.85 \text{ dB} = 30.85 \text{ dBm} \end{aligned}$$

Note: Power values in Base-Station power Measurement function are applied offset.

PAR

$$\begin{aligned} \text{PAR} &= \text{Reading Value} + \text{ATT}(20 \text{ dB}) + \text{Splitter} + \text{Cable loss}(2 \text{ ea}) \\ &= 5 \text{ dBm} + 20 \text{ dB} + 6 \text{ dB} + 1.2 = 32.2 \text{ dBm} \end{aligned}$$

Note: Power values in plots of spectrum analyzer are applied offset.


(where) offset = ATT(20 dB) + Splitter + Cable loss(2 ea)

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

7. TEST DATA

7.1 CONDUCTED OUTPUT POWER

A base station simulator was used to establish communication with the EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Test Result

Band	Channel	Voice	GPRS Data			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)
GSM 1900	512	30.18	30.16	27.84	25.78	24.84
	661	30.08	30.06	27.65	25.73	24.60
	810	29.97	29.96	27.61	25.49	24.46

(GSM Conducted Maximum Output Powers)

Note :

1. We apply to cable loss in base-station for testing conducted output power.
2. Actual offset values are 0.85 dB in GSM1900.

7.2 PEAK-TO-AVERAGE RATIO

- Plots of the EUT's Peak- to- Average Ratio are shown Page 22.

Note :

1. We apply to cable loss, splitter and attenuation for testing PAR.
2. Actual offset values is 27.2 dB in GSM1900.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

7.3 OCCUPIED BANDWIDTH

Band	Channel	Frequency(MHz)	Data (kHz)
GSM1900	512	1850.20	243.6344
	661	1880.00	246.6535
	810	1909.80	241.0980

- Plots of the EUT's Occupied Bandwidth are shown Page 21 ~ 22.

7.4 CONDUCTED SPURIOUS EMISSIONS

Band	Channel	Frequency of Maximum Harmonic (GHz)	Maximum Data (dBm)
GSM1900	512	14.050	-28.75
	661	14.640	-29.61
	810	13.310	-28.84

- Plots of the EUT's Conducted Spurious Emissions are shown Page 25 ~ 27.

7.4.1 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 23 ~ 24.

7.5 EQUIVALENT ISOTROPIC RADIATED POWER

(GSM1900 Mode)

Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
512	1,850.20	-10.27	21.53	10.02	1.71	H	0.964	29.84
661	1,880.00	-10.60	21.38	10.04	1.77	V	0.923	29.65
810	1,909.80	-10.97	21.29	10.05	1.80	V	0.899	29.54

Note: Standard batteries are the only options for this phone. And a peak detector is used.

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported in GSM mode and using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band. This unit was tested with its standard battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is in z plane in GSM1900 (x plane ch 512) mode. Also worst case of detecting Antenna is in vertical polarization in GSM1900 (horizontal polarization) mode.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D

7.6 RADIATED SPURIOUS EMISSIONS

7.6.1 RADIATED SPURIOUS EMISSIONS (GSM1900)

- MEASURED OUTPUT POWER: 29.84 dBm = 0.964 W
- MODULATION SIGNAL: GSM1900
- DISTANCE: 3 meters
- LIMIT: $-(43 + 10 \log_{10}(W)) =$ -42.84 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	EIRP (dBm)	dBc
512 (1850.2)	3,700.40	-45.41	12.36	-47.20	4.87	H	-39.71	-69.55
	5,550.60	-46.53	12.61	-42.98	6.66	H	-37.03	-66.87
	7,400.80	-53.31	10.97	-42.08	6.60	H	-37.71	-67.55
661 (1880.0)	3,760.00	-45.91	12.40	-47.63	4.88	H	-40.11	-69.95
	5,640.00	-47.11	12.65	-43.32	6.54	H	-37.21	-67.05
	7,520.00	-52.96	10.84	-40.58	7.32	H	-37.06	-66.90
810 (1909.8)	3,819.60	-46.28	12.45	-48.51	5.02	V	-41.08	-70.92
	5,729.40	-47.07	12.71	-43.54	6.54	V	-37.37	-67.21
	7,639.20	-51.50	10.87	-38.59	7.78	H	-35.50	-65.34


- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
 2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

7.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

7.7.1 FREQUENCY STABILITY (GSM1900)

OPERATING FREQUENCY: 1880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	1879 999 981	0	0.000 000	0.000
100%		-30	1880 000 005	23.65	0.000 001	0.013
100%		-20	1880 000 004	22.82	0.000 001	0.012
100%		-10	1880 000 006	24.08	0.000 001	0.013
100%		0	1880 000 005	23.14	0.000 001	0.012
100%		+10	1880 000 002	20.16	0.000 001	0.011
100%		+30	1880 000 003	21.48	0.000 001	0.011
100%		+40	1880 000 003	21.10	0.000 001	0.011
100%		+50	1880 000 002	20.35	0.000 001	0.011
115%		4.255	+20	1880 000 003	21.70	0.000 001
Batt. Endpoint	3.400	+20	1880 000 001	19.07	0.000 001	0.010



8. TEST PLOTS

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D


■ GSM1900 MODE (512 CH.) Occupied Bandwidth




■ GSM1900 MODE (661 CH.) Occupied Bandwidth




■ GSM1900 MODE (810 CH.) Occupied Bandwidth




■ GSM1900 MODE (661 CH.) Peak-to-Average Ratio




■ GSM1900 MODE (512 CH.) Block Edge 1




■ GSM1900 MODE (512 CH.) Block Edge 2



■ GSM1900 MODE (810 CH.) Block Edge 1




■ GSM1900 MODE (810 CH.) Block Edge 2




FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1206FR06-1	Date of Issue: June 20, 2012	EUT Type: PCS GSM/GPRS Phone with Bluetooth, WLAN and NFC(Felica)	FCC ID : ZNFL06D


■ GSM1900 MODE (512 CH.) Conducted Spurious Emissions1




■ GSM1900 MODE (512 CH.) Conducted Spurious Emissions2




■ GSM1900 MODE (661 CH) Conducted Spurious Emissions1



■ GSM1900 MODE (661 CH.) Conducted Spurious Emissions2



■ GSM1900 MODE (810 CH.) Conducted Spurious Emissions1



■ GSM1900 MODE (810 CH.) Conducted Spurious Emissions2

