

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Receipt: November 10, 2015**Date of Issue: December 01, 2015****Test Report No. HCT-E-1511-F027-2****HCT FRN: 0005866421****FCC ID :****ZNFL17AG**

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: GSM/WCDMA Phone with Bluetooth4.0+LE, WLAN802.11 b/g/n(2.4GHz)
Model Name: LGL17AG
Additional Model Name: L17AG, LG-L17AG
Test Port: USB / Earphone Port
Date of Test: November 18, 2015 – November 23, 2015

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Gu-Cheol Yoon
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1511-F027	November 26, 2015	Initial Release
HCT-E-1511-F027-1	November 30, 2015	The additional test of USB cable
HCT-E-1511-F027-2	December 01, 2015	The additional model is added.



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	5
1.3 Test Facility	5
1.4 Tested System Details.....	6
1.5 Cable Description	7
1.6 Noise Suppression Parts on Cable. (I/O Cable)	7
2. DESCRIPTION OF TEST	8
3. PRELIMINARY TEST	11
3.1 Conducted Emission Test	11
3. 2 Radiated Emission Test	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
4.1 Conducted Emission Test	12
4.2 Radiated Emission Test	19
5. LIST OF TEST EQUIPMENT	21
6. CONCLUSION	22

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model	LGL17AG
FCC ID	ZNFL17AG
Additional Model	L17AG, LG-L17AG
EUT Type	GSM/WCDMA Phone with Bluetooth4.0+LE, WLAN802.11 b/g/n(2.4GHz)
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 826.40 MHz to 846.60 MHz (WCDMA 850) 1 852.4 MHz to 1 907.6 MHz (WCDMA 1 900)
RX Frequency	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 871.40 MHz to 891.60 MHz (WCDMA 850) 1 932.4 MHz to 1 987.6 MHz (WCDMA 1 900)



1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
HCT FRN: 0005866421 Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
HCT FRN: 0005866421 Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LGL17AG	LG	ZNFL17AG	USB cable, Earphone
USB cable	EAD62377914	CRESYN	-	EUT, Notebook PC
USB cable	EAD62377903	KSD	-	EUT, Notebook PC
USB cable	EAD62377908	LEAGTECH	-	EUT, Notebook PC
USB cable	EAD62377902	Ningbo Broad	-	EUT, Notebook PC
Earphone	EAB62209304	I-SOUND	-	EUT
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	PPP009D	DELTA Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	TL-WR747N	TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	-	Gateway
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	16 GB	Samsung	-	EUT



1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.0
Notebook PC	RJ 45	N/A	N	(D)2.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	EUT End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



3. PRELIMINARY TEST

3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

3. 2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	EAD62377914 (CRESYN) *NOTE: The worst-case emissions are reported.
Kind of Test Site	Shielded Room
Temperature	22.5 °C
Relative Humidity	44.0 %
Test Date	November 18, 2015

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.200000	53.3	9.000	L1	9.6	10.3	63.6
0.214000	47.9	9.000	L1	9.6	15.1	63.0
0.688000	46.3	9.000	L1	9.7	9.7	56.0
0.692000	46.3	9.000	L1	9.7	9.7	56.0
0.800000	45.7	9.000	L1	9.7	10.3	56.0
0.834000	46.4	9.000	L1	9.7	9.6	56.0
0.934000	44.8	9.000	L1	9.7	11.2	56.0
0.956000	44.8	9.000	L1	9.7	11.2	56.0
0.982000	45.6	9.000	L1	9.7	10.4	56.0
1.050000	44.8	9.000	L1	9.7	11.2	56.0
1.108000	45.1	9.000	L1	9.7	10.9	56.0
1.126000	45.3	9.000	L1	9.7	10.7	56.0
6.558000	34.0	9.000	L1	9.9	26.0	60.0
16.558000	33.4	9.000	L1	10.2	26.6	60.0
16.572000	34.1	9.000	L1	10.2	25.9	60.0
19.254000	35.0	9.000	L1	10.3	25.0	60.0
20.876000	35.9	9.000	L1	10.3	24.1	60.0
20.946000	35.9	9.000	L1	10.3	24.1	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.200000	37.1	9.000	L1	9.6	16.5	53.6
0.674000	24.2	9.000	L1	9.7	21.8	46.0
0.688000	23.5	9.000	L1	9.7	22.5	46.0
0.692000	23.6	9.000	L1	9.7	22.4	46.0
0.800000	24.4	9.000	L1	9.7	21.6	46.0
0.834000	27.1	9.000	L1	9.7	18.9	46.0
0.934000	24.3	9.000	L1	9.7	21.7	46.0
0.944000	24.2	9.000	L1	9.7	21.8	46.0
0.956000	25.4	9.000	L1	9.7	20.6	46.0
0.982000	27.5	9.000	L1	9.7	18.5	46.0
1.050000	28.4	9.000	L1	9.7	17.6	46.0
1.108000	30.0	9.000	L1	9.7	16.0	46.0
6.206000	27.0	9.000	L1	9.9	23.0	50.0
16.572000	27.4	9.000	L1	10.2	22.6	50.0
20.734000	29.0	9.000	L1	10.3	21.0	50.0
20.876000	29.1	9.000	L1	10.3	20.9	50.0
20.946000	29.3	9.000	L1	10.3	20.7	50.0
20.952000	28.9	9.000	L1	10.3	21.1	50.0



Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	46.8	9.000	N	9.6	19.1	65.9
0.196000	54.1	9.000	N	9.6	9.7	63.8
0.200000	54.0	9.000	N	9.6	9.6	63.6
0.208000	53.3	9.000	N	9.6	10.0	63.3
0.212000	51.4	9.000	N	9.6	11.7	63.1
0.682000	46.1	9.000	N	9.6	9.9	56.0
0.904000	45.3	9.000	N	9.7	10.7	56.0
0.930000	44.5	9.000	N	9.7	11.5	56.0
0.952000	44.4	9.000	N	9.7	11.6	56.0
0.960000	45.4	9.000	N	9.7	10.6	56.0
0.978000	45.5	9.000	N	9.7	10.5	56.0
1.124000	44.8	9.000	N	9.7	11.2	56.0
6.278000	34.7	9.000	N	9.9	25.3	60.0
6.418000	34.6	9.000	N	9.9	25.4	60.0
19.254000	35.7	9.000	N	10.3	24.3	60.0
19.400000	35.0	9.000	N	10.3	25.0	60.0
21.232000	36.4	9.000	N	10.3	23.6	60.0
21.374000	35.0	9.000	N	10.3	25.0	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.196000	36.5	9.000	N	9.6	17.3	53.8
0.200000	36.9	9.000	N	9.6	16.7	53.6
0.208000	34.9	9.000	N	9.6	18.4	53.3
0.212000	30.6	9.000	N	9.6	22.5	53.1
0.682000	24.0	9.000	N	9.6	22.0	46.0
0.930000	23.8	9.000	N	9.7	22.2	46.0
0.952000	24.1	9.000	N	9.7	21.9	46.0
0.960000	26.8	9.000	N	9.7	19.2	46.0
0.978000	27.2	9.000	N	9.7	18.8	46.0
1.112000	29.9	9.000	N	9.7	16.1	46.0
1.124000	30.2	9.000	N	9.7	15.8	46.0
1.270000	28.8	9.000	N	9.7	17.2	46.0
6.278000	27.1	9.000	N	9.9	22.9	50.0
6.418000	26.7	9.000	N	9.9	23.3	50.0
6.488000	26.3	9.000	N	9.9	23.7	50.0
19.202000	27.4	9.000	N	10.3	22.6	50.0
21.232000	30.3	9.000	N	10.3	19.7	50.0
21.374000	27.0	9.000	N	10.3	23.0	50.0



4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	EAD62377914 (CRESYN) ※NOTE: The worst-case emissions are reported.
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.0 °C
Relative Humidity	44.9 %
Test Date	November 18, 2015

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
56.230541	29.8	133.0	V	132.0	15.6	10.2	40.0
69.037756	29.9	183.0	H	5.0	14.3	10.1	40.0
87.372745	27.6	239.0	H	95.0	11.5	12.4	40.0
602.463006	32.5	237.0	V	173.0	25.5	13.5	46.0
750.027045	38.5	100.0	H	155.0	27.5	7.5	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	1.1 GHz
Testing Frequency Range	1 GHz to 6 GHz
Operation Mode	Data Communication mode
USB Cable Type	EAD62377914 (CRESYN) ※NOTE: The worst-case emissions are reported.
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.4 °C
Relative Humidity	39.1 %
Test Date	November 23, 2015

Frequency (MHz)	Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1328.406814	46.8	144.0	V	13.0	-9.7	27.2	74.0
1400.050100	50.6	193.0	V	41.0	-9.6	23.4	74.0
2656.963928	50.3	100.0	V	28.0	-5.4	23.7	74.0

Frequency (MHz)	CAverage (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1328.406814	26.9	144.0	V	13.0	-9.7	27.1	54.0
1400.050100	48.2	193.0	V	41.0	-9.6	5.8	54.0
2656.963928	31.3	100.0	V	28.0	-5.4	22.7	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	01.13.2015
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	06.11.2015
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	01.13.2015
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.01.2015
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17.2014
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.05.2015
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.01.2015
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.06.2015
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.15.2015
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.07.2014
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.05.2015
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-



6. CONCLUSION

The data collected shows that the **EUT Type: GSM/WCDMA Phone with Bluetooth4.0+LE, WLAN802.11b/g/n(2.4GHz), Model: LGL17AG, FCC ID: ZNFL17AG** complies with §15.107 and §15.109 of the FCC rules.