



PART 27 MEASUREMENT REPORT

Applicant Name:

LG Electronics USA, Inc.
111 Sylvan Avenue, North Building
Englewood Cliffs, NJ 07632
United States

Date of Testing:

4/26 - 5/21/2020

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M2004220073-04-R1.ZNF

FCC ID:

ZNFL355DL

APPLICANT:

LG Electronics USA, Inc.

Application Type:

Certification

Model:

LM-K300QM

Additional Model(s):

LG-L355DL, LMK300QM, LGL355DL, K300QM, L355DL, LG L355DL

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part:

27

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01,
KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised test report (S/N: 1M2004220073-04-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President



FCC ID: ZNFL355DL		PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 1 of 112

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	8
5.0	TEST EQUIPMENT CALIBRATION DATA	9
6.0	SAMPLE CALCULATIONS	10
7.0	TEST RESULTS.....	11
7.1	Summary.....	11
7.2	Occupied Bandwidth	12
7.3	Spurious and Harmonic Emissions at Antenna Terminal	38
7.4	Band Edge Emissions at Antenna Terminal	61
7.5	Conducted Power Output Data	94
7.6	Radiated Power (ERP)	95
7.7	Radiated Spurious Emissions Measurements	99
7.8	Frequency Stability / Temperature Variation	106
8.0	CONCLUSION.....	112

FCC ID: ZNFL355DL	 PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 2 of 112



MEASUREMENT REPORT

FCC Part 27



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	EIRP		ERP		Emission Designator
				Max. Power [W]	Max. Power [dBm]	Max. Power [W]	Max. Power [dBm]	
LTE Band 12	10 MHz	QPSK	704.0 - 711.0	0.094	19.71	0.057	17.56	9M05G7D
		16QAM	704.0 - 711.0	0.074	18.67	0.045	16.52	9M03W7D
		64QAM	704.0 - 711.0	0.058	17.65	0.035	15.50	9M05W7D
	5 MHz	QPSK	701.5 - 713.5	0.097	19.87	0.059	17.72	4M55G7D
		16QAM	701.5 - 713.5	0.073	18.63	0.044	16.48	4M55W7D
		64QAM	701.5 - 713.5	0.060	17.76	0.036	15.61	4M54W7D
	3 MHz	QPSK	700.5 - 714.5	0.093	19.69	0.057	17.54	2M70G7D
		16QAM	700.5 - 714.5	0.072	18.55	0.044	16.40	2M70W7D
		64QAM	700.5 - 714.5	0.060	17.76	0.036	15.61	2M70W7D
	1.4 MHz	QPSK	699.7 - 715.3	0.091	19.60	0.056	17.45	1M09G7D
		16QAM	699.7 - 715.3	0.070	18.47	0.043	16.32	1M10W7D
		64QAM	699.7 - 715.3	0.058	17.61	0.035	15.46	1M10W7D
LTE Band 13	10 MHz	QPSK	782.0	0.089	19.47	0.054	17.32	9M03G7D
		16QAM	782.0	0.073	18.64	0.045	16.49	9M03W7D
		64QAM	782.0	0.058	17.64	0.035	15.49	9M04W7D
	5 MHz	QPSK	779.5 - 784.5	0.091	19.58	0.055	17.43	4M53G7D
		16QAM	779.5 - 784.5	0.073	18.65	0.045	16.50	4M51W7D
		64QAM	779.5 - 784.5	0.058	17.65	0.036	15.50	4M50W7D
LTE Band 71	20 MHz	QPSK	673.0 - 688.0	0.105	20.20	0.064	18.05	18M1G7D
		16QAM	673.0 - 688.0	0.085	19.31	0.052	17.16	18M1W7D
		64QAM	673.0 - 688.0	0.068	18.32	0.041	16.17	18M1W7D
	15 MHz	QPSK	670.5 - 690.5	0.106	20.24	0.064	18.09	13M5G7D
		16QAM	670.5 - 690.5	0.084	19.25	0.051	17.10	13M5W7D
		64QAM	670.5 - 690.5	0.068	18.36	0.042	16.21	13M5W7D
	10 MHz	QPSK	668.0 - 693.0	0.104	20.16	0.063	18.01	9M06G7D
		16QAM	668.0 - 693.0	0.083	19.18	0.050	17.03	9M05W7D
		64QAM	668.0 - 693.0	0.066	18.20	0.040	16.05	9M06W7D
	5 MHz	QPSK	665.5 - 695.5	0.102	20.10	0.062	17.95	4M58G7D
		16QAM	665.5 - 695.5	0.081	19.08	0.049	16.93	4M54W7D
		64QAM	665.5 - 695.5	0.064	18.07	0.039	15.92	4M54W7D

Overview Table (<1GHz Bands)

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	EIRP		Emission Designator
				Max. Power [W]	Max. Power [dBm]	
WCDMA	N/A	Spread Spectrum	1712.4 - 1752.6	0.190	22.78	4M19F9W
LTE Band 66/4	20 MHz	QPSK	1720.0 - 1770.0	0.153	21.86	18M0G7D
		16QAM	1720.0 - 1770.0	0.126	21.02	18M0W7D
		64QAM	1720.0 - 1770.0	0.103	20.11	18M0W7D
	15 MHz	QPSK	1717.5 - 1772.5	0.156	21.92	13M5G7D
		16QAM	1717.5 - 1772.5	0.126	21.00	13M6W7D
		64QAM	1717.5 - 1772.5	0.103	20.13	13M6W7D
	10 MHz	QPSK	1715.0 - 1775.0	0.160	22.03	9M06G7D
		16QAM	1715.0 - 1775.0	0.128	21.09	9M06W7D
		64QAM	1715.0 - 1775.0	0.104	20.16	9M05W7D
	5 MHz	QPSK	1712.5 - 1777.5	0.155	21.91	4M53G7D
		16QAM	1712.5 - 1777.5	0.126	21.02	4M54W7D
		64QAM	1712.5 - 1777.5	0.103	20.12	4M54W7D
	3 MHz	QPSK	1711.5 - 1778.5	0.147	21.69	2M70G7D
		16QAM	1711.5 - 1778.5	0.120	20.81	2M69W7D
		64QAM	1711.5 - 1778.5	0.099	19.94	2M70W7D
	1.4 MHz	QPSK	1710.7 - 1779.3	0.147	21.67	1M10G7D
		16QAM	1710.7 - 1779.3	0.118	20.71	1M10W7D
		64QAM	1710.7 - 1779.3	0.093	19.71	1M10W7D

Overview Table (>1GHz Bands)

FCC ID: ZNFL355DL		PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 3 of 112

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFL355DL	 PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 4 of 112

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFL355DL**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part.

Test Device Serial No.: 09870, 02440, 09979

2.2 Device Capabilities

This device contains the following capabilities:

CDMA, GSM/GPRS/EDGE, WCDMA/HSPA, LTE, WLAN, Bluetooth (1x, EDR, LE)

LTE Band 66 (1710 - 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz). Therefore, test data provided in this report covers Band 4 as well as Band 66.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFL355DL	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	 LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 5 of 112	

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Block C Frequency Range

Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.

3.3 Block A Frequency Range

698-746 MHz band. The following frequencies are available for licensing pursuant to this part in the 698-746 MHz band: (1) Three paired channel blocks of 12 megahertz each are available for assignment as follows:

Block A: 698-704 MHz and 728-734 MHz;
Block B: 704-710 MHz and 734-740 MHz; and
Block C: 710-716 MHz and 740-746 MHz.

3.4 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum

FCC ID: ZNFL355DL	 PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 6 of 112

analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

FCC ID: ZNFL355DL	 PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 7 of 112

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFL355DL	 PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 8 of 112

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX3	Licensed Transmitter Cable Set	10/30/2019	Annual	10/30/2020	LTX3
Agilent	N9038A	MXE EMI Receiver	7/17/2019	Annual	7/17/2020	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	6/12/2019	Annual	6/12/2020	MY52350166
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2019	Biennial	10/10/2021	121034
Espec	ESX-2CA	Environmental Chamber	6/13/2019	Annual	6/13/2020	17620
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	2/22/2019	Biennial	2/22/2021	128338
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			836371/0079
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			112347
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	6/5/2019	Annual	6/5/2020	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/23/2019	Annual	9/23/2020	100348
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/11/2019	Annual	7/11/2020	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/8/2019	Annual	7/8/2020	102133
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	5/19/2018	Biennial	5/19/2020	A051107

Table 5-1. Summary of Test Results

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFL355DL		PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 9 of 112	

6.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

WCDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (–24.80).

FCC ID: ZNFL355DL	 PCTEST Proud to be part of 	PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 10 of 112	

7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFL355DL
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): WCDMA/LTE

Test Condition	Test Description	FCC Part Section(s)	RSS Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Occupied Bandwidth	2.1049	RSS-139(2.3)	N/A	PASS	Section 7.2
	Conducted Band Edge / Spurious Emissions	2.1051, 27.53	RSS-139(6.6)	> 43 + 10log10(P[Watts]) at Band Edge and for all out-of-band emissions	PASS	Sections 7.3, 7.4
	Transmitter Conducted Output Power	2.1046	RSS-139(4.1)	N/A	PASS	See RF Exposure Report
	Frequency Stability	2.1055, 27.54	RSS-139(6.4)	Fundamental emissions stay within authorized frequency block	PASS	Section 7.8
RADIATED	Effective Radiated Power / Equivalent Isotropic Radiated Power (LTE Band 71)	27.50(b)(10)	RSS-130(4.4)	< 3 Watts max. ERP < 5 Watts max. EIRP	PASS	Section 7.6
	Effective Radiated Power / Equivalent Isotropic Radiated Power (LTE Band 12)				PASS	Section 7.6
	Effective Radiated Power / Equivalent Isotropic Radiated Power (LTE Band 13)	27.50(c)(10)	RSS-130(4.4)	< 3 Watts max. ERP < 5 Watts max. EIRP	PASS	Section 7.6
	Equivalent Isotropic Radiated Power (WCDMA)	27.50(d)(4)	RSS-139(6.5)	< 1 Watts max. EIRP	PASS	Section 7.6
	Equivalent Isotropic Radiated Power (LTE Band 4/66)				PASS	Section 7.6
	Radiated Spurious Emissions (LTE Band 13)	2.1053, 27.53(f)	RSS-139(6.6)	< -70 dBW/MHz (for wideband signals) < -80 dBW (for discrete emissions less than 700Hz BW) For all emissions in the band 1559 - 1610 MHz	PASS	Section 7.7
	Radiated Spurious Emissions	2.1053, 27.53	RSS-139(6.6)	> 43 + 10 log10 (P[Watts]) for all out-of-band emissions	PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST 2G/3G Automation Version 4.5, LTE Automation Version 5.3.

FCC ID: ZNFL355DL	 PART 27 MEASUREMENT REPORT		Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 11 of 112

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset	Page 12 of 112	

LTE Band 66/4




Plot 7-1. Occupied Bandwidth Plot (LTE Band 66/4 - 20MHz QPSK - Full RB Configuration)



Plot 7-2. Occupied Bandwidth Plot (LTE Band 66/4 - 20MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 13 of 112




Plot 7-3. Occupied Bandwidth Plot (LTE Band 66/4 - 20MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 66/4 - 15MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 14 of 112




Plot 7-5. Occupied Bandwidth Plot (LTE Band 66/4 - 15MHz 16-QAM - Full RB Configuration)



Plot 7-6. Occupied Bandwidth Plot (LTE Band 66/4 - 15MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 15 of 112




Plot 7-7. Occupied Bandwidth Plot (LTE Band 66/4 - 10MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 66/4 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 16 of 112




Plot 7-9. Occupied Bandwidth Plot (LTE Band 66/4 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 66/4 - 5MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 17 of 112




Plot 7-11. Occupied Bandwidth Plot (LTE Band 66/4 - 5MHz 16-QAM - Full RB Configuration)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 66/4 - 5MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 18 of 112




Plot 7-13. Occupied Bandwidth Plot (LTE Band 66/4 - 3MHz QPSK - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (LTE Band 66/4 - 3MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 19 of 112




Plot 7-15. Occupied Bandwidth Plot (LTE Band 66/4 - 3MHz 64-QAM - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (LTE Band 66/4 - 1.4MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 20 of 112




Plot 7-17. Occupied Bandwidth Plot (LTE Band 66/4 - 1.4MHz 16-QAM - Full RB Configuration)



Plot 7-18. Occupied Bandwidth Plot (LTE Band 66/4 - 1.4MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 21 of 112

LTE Band 12




Plot 7-19. Occupied Bandwidth Plot (LTE Band 12 - 10MHz QPSK - Full RB Configuration)




Plot 7-20. Occupied Bandwidth Plot (LTE Band 12 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 22 of 112




Plot 7-21. Occupied Bandwidth Plot (LTE Band 12 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-22. Occupied Bandwidth Plot (LTE Band 12 - 5MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 23 of 112




Plot 7-23. Occupied Bandwidth Plot (LTE Band 12 - 5MHz 16-QAM - Full RB Configuration)




Plot 7-24. Occupied Bandwidth Plot (LTE Band 12 - 5MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 24 of 112




Plot 7-25. Occupied Bandwidth Plot (LTE Band 12 - 3MHz QPSK - Full RB Configuration)



Plot 7-26. Occupied Bandwidth Plot (LTE Band 12 - 3MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 25 of 112




Plot 7-27. Occupied Bandwidth Plot (LTE Band 12 - 3MHz 64-QAM - Full RB Configuration)



Plot 7-28. Occupied Bandwidth Plot (LTE Band 12 - 1.4MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 26 of 112




Plot 7-29. Occupied Bandwidth Plot (LTE Band 12 – 1.4MHz 16-QAM - Full RB Configuration)



Plot 7-30. Occupied Bandwidth Plot (LTE Band 12 – 1.4MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 27 of 112

LTE Band 13




Plot 7-31. Occupied Bandwidth Plot (LTE Band 13 - 10MHz QPSK - Full RB Configuration)




Plot 7-32. Occupied Bandwidth Plot (LTE Band 13 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 28 of 112




Plot 7-33. Occupied Bandwidth Plot (LTE Band 13 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-34. Occupied Bandwidth Plot (LTE Band 13 - 5MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 29 of 112




Plot 7-35. Occupied Bandwidth Plot (LTE Band 13 - 5MHz 16-QAM - Full RB Configuration)




Plot 7-36. Occupied Bandwidth Plot (LTE Band 13 - 5MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 30 of 112

LTE Band 71




Plot 7-37. Occupied Bandwidth Plot (LTE Band 71 - 20MHz QPSK - Full RB Configuration)




Plot 7-38. Occupied Bandwidth Plot (LTE Band 71 - 20MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 31 of 112




Plot 7-39. Occupied Bandwidth Plot (LTE Band 71 - 20MHz 64-QAM - Full RB Configuration)




Plot 7-40. Occupied Bandwidth Plot (LTE Band 71 - 15MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 32 of 112




Plot 7-41. Occupied Bandwidth Plot (LTE Band 71 - 15MHz 16-QAM - Full RB Configuration)



Plot 7-42. Occupied Bandwidth Plot (LTE Band 71 - 15MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 33 of 112




Plot 7-43. Occupied Bandwidth Plot (LTE Band 71 - 10MHz QPSK - Full RB Configuration)




Plot 7-44. Occupied Bandwidth Plot (LTE Band 71 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 34 of 112




Plot 7-45. Occupied Bandwidth Plot (LTE Band 71 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-46. Occupied Bandwidth Plot (LTE Band 71 - 5MHz QPSK - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 35 of 112




Plot 7-47. Occupied Bandwidth Plot (LTE Band 71 - 5MHz 16-QAM - Full RB Configuration)



Plot 7-48. Occupied Bandwidth Plot (LTE Band 71 - 5MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 36 of 112

WCDMA AWS



Plot 7-49. Occupied Bandwidth Plot (WCDMA, Ch. 1413)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 37 of 112

7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW $\geq$ 100kHz
3. VBW $\geq$ 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 7-2. Test Instrument & Measurement Setup

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 38 of 112

LTE Band 66/4




Plot 7-50. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-51. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 39 of 112




Plot 7-52. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-53. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 40 of 112



Plot 7-54. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-55. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 41 of 112




Plot 7-56. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-57. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 42 of 112




Plot 7-58. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 43 of 112

LTE Band 12




Plot 7-59. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-60. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 44 of 112




Plot 7-61. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-62. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 45 of 112




Plot 7-63. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-64. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 46 of 112




Plot 7-65. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-66. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 47 of 112




Plot 7-67. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 48 of 112

LTE Band 13




Plot 7-68. Conducted Spurious Plot (LTE Band 13 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-69. Conducted Spurious Plot (LTE Band 13 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)


FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 49 of 112




Plot 7-70. Conducted Spurious Plot (LTE Band 13 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 50 of 112

LTE Band 71




Plot 7-71. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-72. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1.ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 51 of 112




Plot 7-73. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-74. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 52 of 112




Plot 7-75. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-76. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 53 of 112




Plot 7-77. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-78. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 54 of 112




Plot 7-79. Conducted Spurious Plot (LTE Band 71 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 55 of 112

WCDMA AWS




Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1312- Low Channel)




Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1312- Low Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 56 of 112




Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1312- Low Channel)




Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1413- Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 57 of 112



Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1413- Mid Channel)




Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1413- Mid Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-R1-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 58 of 112



Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1513- High Channel)



Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 1513- High Channel)

FCC ID: ZNFL355DL	PCTEST Proud to be part of elements	PART 27 MEASUREMENT REPORT	LG	Approved by: Quality Manager
Test Report S/N: 1M2004220073-04-RL-ZNF	Test Dates: 4/26 - 5/21/2020	EUT Type: Portable Handset		Page 59 of 112