



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
http://www.pctestlab.com



## MEASUREMENT REPORT FCC Part 90 Band Class 10 CDMA

**Applicant:**  
LG Electronics MobileComm U.S.A  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States

**Date of Testing:**  
March 24 - 31, 2014  
**Test Site/Location:**  
PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
0Y1403240592.ZNF

<b>FCC ID:</b>	<b>ZNFLS620</b>
<b>APPLICANT:</b>	<b>LG ELECTRONICS MOBILECOMM U.S.A</b>

**Applicant Type:** Certification  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part:** §90.691  
**EUT Type:** Portable Handset  
**Model(s):** LGLS620, LS620  
**Test Device Serial No.:** *identical prototype* [S/N: A0000034DCD786]

Mode	Tx Frequency (MHz)	Emission Designator	ERP/EIRP	
			Max. Power (W)	Max. Power (dBm)
CDMA800 (BC10)	817.9 - 823.1	1M28F9W	0.170	22.30

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
 Randy Ortanez  
 President



FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 1 of 23

# T A B L E O F C O N T E N T S


FCC PART 90 MEASUREMENT REPORT.....	3
1.0 INTRODUCTION .....	4
1.1 SCOPE .....	4
1.2 TESTING FACILITY.....	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION .....	5
2.2 DEVICE CAPABILITIES.....	5
2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....	5
3.0 DESCRIPTION OF TESTS .....	6
3.1 EVALUATION PROCEDURE .....	6
3.2 OCCUPIED BANDWIDTH .....	6
3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	6
3.4 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS .....	7
3.5 FREQUENCY STABILITY / TEMPERATURE VARIATION .....	8
4.0 TEST EQUIPMENT CALIBRATION DATA .....	9
5.0 SAMPLE CALCULATIONS .....	10
6.0 TEST RESULTS.....	11
6.1 SUMMARY.....	11
6.2 EFFECTIVE RADIATED POWER OUTPUT DATA .....	12
6.3 BC10 CDMA RADIATED MEASUREMENTS .....	13
6.4 BC10 CDMA FREQUENCY STABILITY MEASUREMENTS.....	15
7.0 PLOTS OF EMISSIONS.....	17
8.0 CONCLUSION.....	23

<b>FCC ID:</b> ZNFLS620	 <b>Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)</b>	 <b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1403240592.ZNF	<b>Test Dates:</b> March 24 - 31, 2014	<b>EUT Type:</b> Portable Handset	
			Page 2 of 23



# MEASUREMENT REPORT

## BC10 CDMA





### §2.1033 General Information

**APPLICANT:** LG Electronics MobileComm U.S.A  
**APPLICANT ADDRESS:** 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21045 USA  
**BASE MODEL:** LGLS620  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**MODE:** CDMA  
**FREQUENCY TOLERANCE:** ±0.00025 % (2.5 ppm)  
**Test Device Serial No.:** A0000034DCD786     Production     Pre-Production     Engineering  
**DATE(S) OF TEST:** March 24 - 31, 2014  
**TEST REPORT S/N:** 0Y1403240592.ZNF

### Test Facility / Accreditations

Measurements were performed at **PCTEST Engineering Lab. located in Columbia, MD 21045, U.S.A.**



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

<b>FCC ID:</b> ZNFLS620		<b>Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1403240592.ZNF	<b>Test Dates:</b> March 24 - 31, 2014	<b>EUT Type:</b> Portable Handset	Page 3 of 23	

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003/2009 on January 10, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFLS620	PCTEST ENGINEERING LABORATORY, INC.	Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 4 of 23

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFLS620**. The EUT consisted of the following component(s):

Trade Name / Base Model	FCC ID	Description
LG / Model: LGLS620	ZNFLS620	Portable Handset

**Table 2-1. EUT Equipment Description**

**Note:** All data contained in this report is applicable for the device operation in the BC10 (817 – 824 MHz). Test data shown supports the devices compliance with §90.691 of the FCC Rules and Regulation.

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev 0/A (BC0, BC1, BC10), 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE)

### 2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset	Page 5 of 23	

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment Measurements and Performance Standards” (ANSI/TIA-603-C-2004) was used in the measurement of the measurement of the **LG Portable Handset FCC ID: ZNFLS620**.

### 3.2 Occupied Bandwidth

#### §2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers’ “occupied bandwidth” measurement function was used to record the occupied bandwidth in accordance with KDB 971168.

### 3.3 Spurious and Harmonic Emissions at Antenna Terminal

#### §2.1051, §90.691

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic.

Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \text{ Log}_{10}(f/6.1)$  decibels or  $50 + 10 \text{ Log}_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \text{ Log}_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 6 of 23

### 3.4 Radiated Power and Radiated Spurious Emissions

§2.1053, §90.635, §90.691


Radiated spurious emissions are investigated indoors in a semi-anechoic chamber to determine the frequencies producing the worst case emissions. Final measurements for radiated power and radiated spurious emissions are performed on the 3 meter OATS per the guidelines of ANSI/TIA-603-C-2004. The measurement area is situated on an 18 meter x 20 meter galvanized 1/2" hardware cloth as the conducting ground plane. This material is sewn together in sections 4 feet wide and 60 feet long. A total of eighteen sections are required to cover the entire measurement area. Sections are laid across the width of the pad, overlapped 1" and sewn and soldered together at intervals of 3" (7.6 cm.) The terrain of the test site is reasonably flat and level. Power and cable to the test site are buried 18" deep into the ground outside the perimeter of the site. An all-weather non-metallic housing is situated on a 2 x 3 meter area adjacent to the measurement area to house the test equipment. The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Emissions are also investigated with the receive antenna horizontally and vertically polarized. The level of the maximized emission is recorded with the spectrum analyzer using a peak detector with RBW = 1MHz, VBW = 3MHz for emissions greater than 1GHz. For emissions below 1GHz, the spectrum analyzer is set to RBW = 100kHz and VBW = 300kHz.

A half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

The calculated  $P_d$  levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of  $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ .



**Figure 3-1. Diagram of 3-meter Test Range**

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 7 of 23

### 3.5 Frequency Stability / Temperature Variation

#### §2.1055, 90.213(a)

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

*Specification – For Part 90.213, the frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.*

#### Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: ZNFLS620	 <b>Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)</b>		 <b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1403240592.ZNF	<b>Test Dates:</b> March 24 - 31, 2014	<b>EUT Type:</b> Portable Handset	Page 8 of 23

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE2	Radiated Emissions Cable Set (VHF/UHF)	3/29/2013	Annual	3/29/2014	N/A
-	LTx2	Licensed Transmitter Cable Set	1/30/2014	Annual	1/30/2015	N/A
Agilent	8447D	Broadband Amplifier	5/31/2013	Annual	5/31/2014	1937A03348
Agilent	8449B	(1-26.5GHz) Pre-Amplifier	4/17/2013	Annual	4/17/2014	3008A00985
Agilent	E5515C	Wireless Communications Test Set	3/18/2014	Annual	3/18/2015	GB46110872
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/16/2013	Annual	4/16/2014	MY45470194
Agilent	N9020A	MXA Signal Analyzer	10/29/2013	Annual	10/29/2014	US46470561
Agilent	N9038A	MXE EMI Receiver	1/3/2014	Annual	1/3/2015	MY51210133
Anritsu	MA2411B	Pulse Sensor	7/16/2013	Annual	7/16/2014	1315051
Anritsu	ML2495A	Power Meter	7/12/2013	Annual	7/12/2014	1328004
Emco	6502	Active Loop Antenna (10k - 30 MHz)	5/31/2012	Biennial	5/31/2014	267
Espec	ESX-2CA	Environmental Chamber	4/16/2013	Annual	4/16/2014	17620
Mini-Circuits	VHF-1300+	High Pass Filter	1/29/2014	Annual	1/29/2015	30716
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	11/1/2013	Biennial	11/1/2015	91052522TX
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/1/2013	Biennial	11/1/2015	91052523RX
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2014	Biennial	3/5/2016	N/A
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	6/19/2013	Biennial	6/19/2015	A050307
Sunol	DRH-118	Horn Antenna (1-18 GHz)	6/19/2013	Biennial	6/19/2015	A042511
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/28/2014	Biennial	1/28/2016	A051107

**Table 4-1. Test Equipment**

**Note:**

For equipment listed above that has a calibration due date that falls within the test date range, care was taken to ensure that this equipment was utilized prior to the calibration due date.

Radiated tests (reported in Section 6.2 and 6.3 of this report) using "RE2" were performed before the calibration due date of 3/29/2014.

FCC ID: ZNFLS620	 <b>Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)</b>			Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset	Page 9 of 23	

## 5.0 SAMPLE CALCULATIONS

### Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### Spurious Radiated Emission – BC10

**Example: Channel 476 CDMA BC10 Mode 3<sup>rd</sup> Harmonic (2453.70MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is  $8.1$  dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is  $2.0$  dB at  $2453.70$  MHz. So  $6.1$  dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was  $25.501$  dBm so this harmonic was  $25.501$  dBm  $- (-24.80) = 50.3$  dBc.

FCC ID: ZNFLS620	 <b>Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)</b>			Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 10 of 23

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: LG Electronics MobileComm U.S.A  
 FCC ID: ZNFLS620  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): CDMA  
 Band: Band Class 10

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
§2.1051, §90.691	Band Edge / Conducted Spurious Emissions	$< 50 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	CONDUCTED	PASS	Section 7.0
§2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
§90.635	Effective Radiated Power	$< 100$ Watts max. ERP	RADIATED	PASS	Section 6.2
§2.1053, §90.691	Undesirable Emissions	$< 43 + 10\log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Sections 6.3
§2.1055, §90.213	Frequency Stability	$< 2.5$ ppm		PASS	Section 6.4

**Table 6-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

FCC ID: ZNFLS620	 <b>Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)</b> 		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset	Page 11 of 23

## 6.2 Effective Radiated Power Output Data

§90.635

Frequency [MHz]	BC10 [Channel]	Battery Type	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
817.90	Ch. 476	Standard	24.09	-1.79	V	22.30	0.170	50.00	-27.70
823.10	Ch. 684	Standard	23.13	-1.84	V	21.29	0.135	50.00	-28.71

**Table 6-2. Effective Radiated Power Output Data**

### NOTES:

1. This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical setup. The data reported in the table above was measured in this test setup.

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset	Page 12 of 23	

### 6.3 BC10 CDMA Radiated Measurements §2.1053, §90.691

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 817.90 MHz  
 CHANNEL: 476  
 MEASURED OUTPUT POWER: 22.30 dBm = 0.170 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.30 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1635.80	-57.65	8.58	-49.08	V	71.38
2453.70	-57.58	8.78	-48.80	V	71.10
3271.60	-85.32	9.08	-76.23	V	98.53
4089.50	-83.46	9.58	-73.87	V	96.17
4907.40	-83.79	11.28	-72.51	V	94.81

**Table 6-3. Radiated Spurious Data (Ch. 476)**

#### NOTES:

1. This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical setup. The data reported in the table above was measured in this test setup.

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset	Page 13 of 23	

**BC10 CDMA Radiated Measurements (Cont'd)**  
§2.1053, §90.691

**Field Strength of SPURIOUS Radiation**

OPERATING FREQUENCY: 823.10 MHz  
 CHANNEL: 684  
 MEASURED OUTPUT POWER: 21.29 dBm = 0.135 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.29 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1646.20	-59.57	8.51	-51.06	V	72.35
2469.30	-58.42	8.75	-49.66	V	70.95
3292.40	-85.29	9.11	-76.19	V	97.48
4115.50	-83.58	9.71	-73.87	V	95.16
4938.60	-83.62	11.24	-72.37	V	93.66

**Table 6-4. Radiated Spurious Data (Ch. 684)**

**NOTES:**

1. This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical setup. The data reported in the table above was measured in this test setup.

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset	Page 14 of 23	

## 6.4 BC10 CDMA Frequency Stability Measurements

§2.1055, §90.213


OPERATING FREQUENCY: 823,100,000 Hz  
 CHANNEL: 684  
 REFERENCE VOLTAGE: 3.8 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	823,099,983	-17	-0.000002
100 %		- 30	823,099,988	-12	-0.000001
100 %		- 20	823,100,016	16	0.000002
100 %		- 10	823,099,990	-10	-0.000001
100 %		0	823,100,011	11	0.000001
100 %		+ 10	823,099,986	-14	-0.000002
100 %		+ 20	823,099,983	-17	-0.000002
100 %		+ 30	823,099,984	-16	-0.000002
100 %		+ 40	823,099,985	-15	-0.000002
100 %		+ 50	823,099,990	-10	-0.000001
115 %		4.37	+ 20	823,099,980	-20
BATT. ENDPOINT	3.40	+ 20	823,099,976	-24	-0.000003

**Table 6-5. Frequency Stability Data (Ch.684)**

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset	Page 15 of 23	


**BC10 CDMA Frequency Stability Measurements (Cont'd)**  
**§2.1055, §90.213**




**Figure 6-1. Frequency Stability Graph (Ch. 684)**

FCC ID: ZNFLS620	PCTEST ENGINEERING LABORATORY, INC.	Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 16 of 23






Plot 7-3. Channel Edge Plot (Ch. 476)




Plot 7-4. Conducted Spurious Plot (Ch. 684)

FCC ID: ZNFLS620	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 18 of 23




Plot 7-5. Conducted Spurious Plot (Ch. 684)



Plot 7-6. Channel Edge Plot (Ch. 684)

FCC ID: ZNFLS620	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 19 of 23



Plot 7-7. Occupied Bandwidth Plot (Ch. 476)



Plot 7-8. Occupied Bandwidth Plot (Ch. 684)

FCC ID: ZNFLS620	PCTEST ENGINEERING LABORATORY, INC.	Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 20 of 23



Plot 7-9. Inner Extended Band Edge (Ch. 476)



Plot 7-10. Outer Extended Band Edge (Ch. 476)

FCC ID: ZNFLS620	PCTEST ENGINEERING LABORATORY, INC.	Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 21 of 23



Plot 7-11. Inner Extended Band Edge (Ch. 684)



Plot 7-12. Outer Extended Band Edge (Ch. 684)

FCC ID: ZNFLS620	PCTEST ENGINEERING LABORATORY, INC.	Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 22 of 23

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFLS620** complies with all the requirements of Parts 90 of the FCC rules.

FCC ID: ZNFLS620		Part 90 BC10 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1403240592.ZNF	Test Dates: March 24 - 31, 2014	EUT Type: Portable Handset		Page 23 of 23