

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Receipt: January 13, 2015**Date of Issue: February 03, 2015****Test Report No. HCT-E-1502-F005****HCT FRN: 0005866421****FCC ID:****ZNFLS770**

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: CDMA, LTE smart phone with Bluetooth and WLAN
Model Name: LG-LS770
Additional Model Name: LGLS770, LS770
Test Port: USB / Earphone Port
Date of Test: January 26, 2015 - January 27, 2015

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Jeong-Hyun Choi
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1502-F005	February 03, 2015	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Test Facility	5
1.4 Tested System Details.....	6
1.5 Cable Description	7
1.6 Noise Suppression Parts on Cable. (I/O Cable)	7
2. DESCRIPTION OF TEST	8
3. PRELIMINARY TEST	11
3.1 Conducted Emission Test	11
3.2 Radiated Emission Test	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
4.1 Conducted Emission Test	12
4.2 Radiated Emission Test	26
5. LIST OF TEST EQUIPMENT	30
6. CONCLUSION	31

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model	LG-LS770
Additional Model	LGLS770, LS770
FCC ID	ZNFLS770
EUT Type	CDMA, LTE smart phone with Bluetooth and WLAN
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 817.90 MHz to 823.10 MHz (CDMA BC10) 1 850.7 MHz to 1 909.3 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 862.00 MHz to 894.00 MHz (CDMA BC10) 1 930.00 MHz to 1 990.00 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 729 MHz to 746 MHz (LTE B12) 1 925 MHz to 1 990 MHz (LTE B25) 859 MHz to 894 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.



1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-LS770	LG	ZNFLS770	Notebook PC, Earphone
USB cable	EAD62572502	Ningbo Broad	-	EUT, Notebook PC
USB cable	EAD62572501	CRESYN	-	EUT, Notebook PC
Earphone	SGEY0007612	CRESYN	-	EUT
Standard case	-	-	-	EUT
Quick case	CFV-120	YOUNG KWANG	-	EUT
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor
Notebook PC adaptor	PPP009D	Delta Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	8 GB	SanDisk	-	EUT



1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 7

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μ V))	Average (dB(μ V))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a shield room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak (dB($\mu\text{V}/\text{m}$))
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak (dB $\mu\text{V}/\text{m}$)	Average (dB($\mu\text{V}/\text{m}$))
Above 1 000	3	74	54




2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



3. PRELIMINARY TEST

3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

3.2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
EUT Case Type	Standard Case
USB Cable Type	Ningbo Broad (EAD62572502) *NOTE: The worst-case emissions are reported.
Kind of Test Site	Shielded Room
Temperature	20.4 °C
Relative Humidity	26.8 %
Test Date	January 27, 2015

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Spectral Diagrams, Conducted Emission, AC Mains (0.15 - 30)MHz, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.192000	49.9	9.000	L1	9.6	14.0	63.9
0.196000	50.4	9.000	L1	9.6	13.4	63.8
0.200000	50.1	9.000	L1	9.7	13.5	63.6
0.204000	49.5	9.000	L1	9.7	13.9	63.4
0.208000	49.2	9.000	L1	9.7	14.1	63.3
0.212000	48.3	9.000	L1	9.7	14.8	63.1
4.034000	40.4	9.000	L1	9.9	15.6	56.0
4.174000	40.0	9.000	L1	9.9	16.0	56.0
4.242000	41.0	9.000	L1	9.9	15.0	56.0
4.456000	40.3	9.000	L1	9.9	15.7	56.0
4.526000	40.5	9.000	L1	9.9	15.5	56.0
4.666000	40.5	9.000	L1	9.9	15.5	56.0
17.038000	35.3	9.000	L1	10.2	24.7	60.0
19.412000	35.4	9.000	L1	10.3	24.6	60.0
19.536000	35.1	9.000	L1	10.3	24.9	60.0
19.728000	34.9	9.000	L1	10.3	25.1	60.0
19.798000	34.4	9.000	L1	10.3	25.6	60.0
19.866000	34.4	9.000	L1	10.3	25.6	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	27.3	9.000	L1	9.6	28.7	56.0
0.154000	26.1	9.000	L1	9.6	29.7	55.8
0.200000	36.9	9.000	L1	9.7	16.7	53.6
0.208000	35.8	9.000	L1	9.7	17.5	53.3
0.254000	31.9	9.000	L1	9.7	19.7	51.6
0.260000	32.6	9.000	L1	9.7	18.8	51.4
3.676000	31.1	9.000	L1	9.8	14.9	46.0
4.030000	31.9	9.000	L1	9.9	14.1	46.0
4.178000	32.0	9.000	L1	9.9	14.0	46.0
4.232000	33.1	9.000	L1	9.9	12.9	46.0
4.454000	32.8	9.000	L1	9.9	13.2	46.0
4.666000	32.3	9.000	L1	9.9	13.7	46.0
17.038000	27.3	9.000	L1	10.2	22.7	50.0
19.412000	27.5	9.000	L1	10.3	22.5	50.0
19.516000	27.1	9.000	L1	10.3	22.9	50.0
19.756000	26.1	9.000	L1	10.3	23.9	50.0
19.796000	24.8	9.000	L1	10.3	25.2	50.0
19.866000	23.5	9.000	L1	10.3	26.5	50.0



Figure 2: Spectral Diagrams, Conducted Emission, AC Mains (0.15 - 30)MHz, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	42.5	9.000	N	9.6	23.5	66.0
0.192000	51.9	9.000	N	9.6	12.0	63.9
0.196000	51.6	9.000	N	9.6	12.2	63.8
0.204000	52.0	9.000	N	9.6	11.4	63.4
0.210000	51.0	9.000	N	9.6	12.2	63.2
0.216000	43.9	9.000	N	9.6	19.1	63.0
3.890000	40.1	9.000	N	9.8	15.9	56.0
4.104000	40.9	9.000	N	9.8	15.1	56.0
4.316000	40.4	9.000	N	9.8	15.6	56.0
4.460000	39.3	9.000	N	9.9	16.7	56.0
4.598000	40.5	9.000	N	9.9	15.5	56.0
4.670000	39.8	9.000	N	9.9	16.2	56.0
19.534000	34.5	9.000	N	10.3	25.5	60.0
19.736000	34.6	9.000	N	10.3	25.4	60.0
19.948000	34.4	9.000	N	10.3	25.6	60.0
21.366000	33.9	9.000	N	10.3	26.1	60.0
21.506000	33.9	9.000	N	10.3	26.1	60.0
21.646000	34.0	9.000	N	10.3	26.0	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	27.5	9.000	N	9.6	28.5	56.0
0.192000	34.3	9.000	N	9.6	19.6	53.9
0.196000	37.1	9.000	N	9.6	16.7	53.8
0.204000	37.1	9.000	N	9.6	16.3	53.4
0.210000	35.3	9.000	N	9.6	17.9	53.2
0.216000	30.5	9.000	N	9.6	22.5	53.0
3.964000	30.8	9.000	N	9.8	15.2	46.0
4.042000	31.3	9.000	N	9.8	14.7	46.0
4.104000	32.1	9.000	N	9.8	13.9	46.0
4.318000	32.7	9.000	N	9.8	13.3	46.0
4.386000	32.6	9.000	N	9.9	13.4	46.0
4.598000	32.6	9.000	N	9.9	13.4	46.0
19.534000	26.7	9.000	N	10.3	23.3	50.0
19.806000	25.2	9.000	N	10.3	24.8	50.0
21.366000	27.2	9.000	N	10.3	22.8	50.0
21.506000	25.8	9.000	N	10.3	24.2	50.0
21.578000	24.7	9.000	N	10.3	25.3	50.0
21.646000	24.8	9.000	N	10.3	25.2	50.0



The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	CRESYN (EAD62572501) *NOTE: The worst-case emissions are reported.
EUT Case Type	Quick Case
Kind of Test Site	Shielded Room
Temperature	20.4 °C
Relative Humidity	26.8 %
Test Date	January 27, 2015

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 3: Spectral Diagrams, Conducted Emission, AC Mains (0.15 - 30)MHz, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.184000	42.3	9.000	L1	9.6	22.0	64.3
0.188000	42.8	9.000	L1	9.6	21.3	64.1
0.192000	49.0	9.000	L1	9.6	14.9	63.9
0.196000	49.4	9.000	L1	9.6	14.4	63.8
0.202000	48.9	9.000	L1	9.7	14.6	63.5
0.206000	48.8	9.000	L1	9.7	14.6	63.4
4.026000	41.2	9.000	L1	9.9	14.8	56.0
4.310000	41.1	9.000	L1	9.9	14.9	56.0
4.452000	40.8	9.000	L1	9.9	15.2	56.0
4.522000	40.8	9.000	L1	9.9	15.2	56.0
4.592000	40.7	9.000	L1	9.9	15.3	56.0
4.662000	40.4	9.000	L1	9.9	15.6	56.0
16.466000	34.6	9.000	L1	10.2	25.4	60.0
16.744000	35.5	9.000	L1	10.2	24.5	60.0
16.816000	35.4	9.000	L1	10.2	24.6	60.0
16.838000	34.9	9.000	L1	10.2	25.1	60.0
19.434000	35.2	9.000	L1	10.3	24.8	60.0
19.502000	35.6	9.000	L1	10.3	24.4	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	27.1	9.000	L1	9.6	28.9	56.0
0.184000	27.5	9.000	L1	9.6	26.9	54.3
0.192000	33.8	9.000	L1	9.6	20.1	53.9
0.198000	36.2	9.000	L1	9.6	17.5	53.7
0.202000	36.2	9.000	L1	9.7	17.3	53.5
0.206000	35.7	9.000	L1	9.7	17.7	53.4
3.674000	31.5	9.000	L1	9.8	14.5	46.0
3.958000	31.8	9.000	L1	9.9	14.2	46.0
4.026000	32.1	9.000	L1	9.9	13.9	46.0
4.382000	32.8	9.000	L1	9.9	13.2	46.0
4.450000	32.8	9.000	L1	9.9	13.2	46.0
4.522000	32.6	9.000	L1	9.9	13.4	46.0
15.968000	27.3	9.000	L1	10.2	22.7	50.0
16.460000	28.1	9.000	L1	10.2	21.9	50.0
16.600000	27.9	9.000	L1	10.2	22.1	50.0
19.078000	28.2	9.000	L1	10.3	21.8	50.0
19.434000	27.3	9.000	L1	10.3	22.7	50.0
21.480000	25.4	9.000	L1	10.3	24.6	50.0



Figure 4: Spectral Diagrams, Conducted Emission, AC Mains (0.15 - 30)MHz, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.192000	51.0	9.000	N	9.6	12.9	63.9
0.198000	51.1	9.000	N	9.6	12.6	63.7
0.202000	51.0	9.000	N	9.6	12.5	63.5
0.206000	50.4	9.000	N	9.6	13.0	63.4
0.212000	49.0	9.000	N	9.6	14.1	63.1
0.258000	44.6	9.000	N	9.7	16.9	61.5
4.026000	41.0	9.000	N	9.8	15.0	56.0
4.168000	41.2	9.000	N	9.8	14.8	56.0
4.172000	39.9	9.000	N	9.8	16.1	56.0
4.384000	39.6	9.000	N	9.9	16.4	56.0
4.598000	38.4	9.000	N	9.9	17.6	56.0
4.664000	40.0	9.000	N	9.9	16.0	56.0
16.680000	34.4	9.000	N	10.2	25.6	60.0
16.820000	34.8	9.000	N	10.2	25.2	60.0
19.504000	35.3	9.000	N	10.3	24.7	60.0
19.574000	35.5	9.000	N	10.3	24.5	60.0
21.340000	36.0	9.000	N	10.3	24.0	60.0
21.412000	35.5	9.000	N	10.3	24.5	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.192000	34.2	9.000	N	9.6	19.7	53.9
0.198000	36.5	9.000	N	9.6	17.2	53.7
0.202000	36.1	9.000	N	9.6	17.4	53.5
0.206000	35.9	9.000	N	9.6	17.5	53.4
0.212000	33.4	9.000	N	9.6	19.7	53.1
0.258000	32.6	9.000	N	9.7	18.9	51.5
3.888000	30.9	9.000	N	9.8	15.1	46.0
4.028000	31.6	9.000	N	9.8	14.4	46.0
4.384000	32.4	9.000	N	9.9	13.6	46.0
4.520000	32.1	9.000	N	9.9	13.9	46.0
4.598000	31.9	9.000	N	9.9	14.1	46.0
4.664000	31.9	9.000	N	9.9	14.1	46.0
15.968000	26.7	9.000	N	10.2	23.3	50.0
16.538000	27.5	9.000	N	10.2	22.5	50.0
16.714000	27.5	9.000	N	10.2	22.5	50.0
16.820000	27.4	9.000	N	10.2	22.6	50.0
19.574000	26.3	9.000	N	10.3	23.7	50.0
21.412000	28.1	9.000	N	10.3	21.9	50.0



4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
EUT Case Type	Standard Case
USB Cable Type	CRESYN (EAD62572501) *NOTE: The worst-case emissions are reported.
Kind of Test Site	3 m semi anechoic chamber
Temperature	20.5 °C
Relative Humidity	28.4 %
Test Date	January 26, 2015

Frequency (MHz)	Quasi Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
34.887776	24.2	100.0	V	259.0	15.0	15.8	40.0
125.010501	33.4	100.0	V	94.0	15.9	10.1	43.5

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	CRESYN (EAD62572501) *NOTE: The worst-case emissions are reported.
EUT Case Type	Quick Case
Kind of Test Site	3 m semi anechoic chamber
Temperature	20.5 °C
Relative Humidity	28.4 %
Test Date	January 26, 2015

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
125.010501	35.5	100.0	V	88.0	15.9	8.0	43.5
375.012024	38.6	150.0	V	13.0	20.1	7.4	46.0
625.029659	36.9	100.0	V	1.0	25.8	9.1	46.0



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	1.996 GHz
Testing Frequency Range	1 GHz to 10 GHz
Operation Mode	Data Communication mode
USB Cable Type	Ningbo Broad (EAD62572502) *NOTE: The worst-case emissions are reported.
EUT Case Type	Standard Case
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.8 °C
Relative Humidity	28.6 %
Test Date	January 27, 2015

Frequency (MHz)	Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)
1332.915832	47.3	150.0	V	301.0	-9.3	26.7	74.0
1993.837675	56.2	100.0	V	27.0	-7.8	17.8	74.0
2666.282565	49.2	100.0	V	42.0	-4.8	24.8	74.0

Frequency (MHz)	CAverage (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)
1332.915832	30.1	150.0	V	301.0	-9.3	23.9	54.0
1993.837675	37.7	100.0	V	27.0	-7.8	16.3	54.0
2666.282565	33.2	100.0	V	42.0	-4.8	20.8	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	1.996 GHz
Testing Frequency Range	1 GHz to 10 GHz
Operation Mode	Data Communication mode
USB Cable Type	CRESYN (EAD62572501) ※NOTE: The worst-case emissions are reported.
EUT Case Type	Quick Case
Kind of Test Site	3 m semi anechoic chamber
Temperature	20.5 °C
Relative Humidity	28.4 %
Test Date	January 26, 2015

Frequency (MHz)	Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1331.913828	50.0	100.0	V	0.0	-9.3	24.0	74.0
1994.739479	57.1	100.0	V	21.0	-7.8	16.9	74.0
2665.681362	48.4	100.0	V	43.0	-4.8	25.6	74.0

Frequency (MHz)	CAverage (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1331.913828	32.0	100.0	V	0.0	-9.3	22.0	54.0
1994.739479	38.0	100.0	V	21.0	-7.8	16.0	54.0
2665.681362	33.2	100.0	V	43.0	-4.8	20.8	54.0



5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	01.13.2015
<input checked="" type="checkbox"/> LISN	EMCO	3816/2SH	9706-1070	1 year	04.07. 2014
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	01.13.2015
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17. 2014
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18.2014
<input type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9168	185	2 year	04.16. 2013
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.11.2014
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.11. 2014
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.07.2014
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	1151	2 year	07.05.2013
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18. 2014
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170124	2 year	10.30. 2013
<input type="checkbox"/> Power Amplifier	CERNEX	CBL18265035	22966	1 year	07.23. 2014
<input type="checkbox"/> Power Amplifier	CERNEX	CBL26405040	19660	1 year	04.04. 2014
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-



6. CONCLUSION

The data collected shows that the **EUT Type: CDMA, LTE smart phone with Bluetooth and WLAN, FCC ID: ZNFLS770, Model: LG-LS770** complies with §15.107 and §15.109 of the FCC rules.