



HCT CO., LTD.

CERTIFICATION DIVISION

74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA
TEL: +82 31 645 6300 FAX: +82 31 645 6401

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Issue: October 07, 2013

Test Report No.: HCTE1310FE02

Test Site: HCT CO., LTD.

HCT FRN: 0005-8664-21

FCC ID:

ZNFLS995

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B
Equipment Type : Multi-Band CDMA/EVDO/GSM/EDGE/WCDMA/LTE Phone with WLAN,
Bluetooth, and RFID
Model Name : LS995
Additional Model Name : LG-LS995, LGLS995
Port / Connector(s) : USB / Earphone Port
Date of Test : September 30, 2013 - October 02, 2013

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862


Report prepared by
: **Gu-Cheol Yoon**
Test Engineer of EMC Team


Approved by
: **Jin-Pyo Hong**
Manager of EMC Team

DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCTE1310FE02	October 07, 2013	Initial Release

TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Product Description	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Tested System Details.....	5
1.4 Cable Description	6
1.5 Noise Suppression Parts on Cable. (I/O cable)	6
1.6 Test Methodology	7
1.7 Test Facility	7
1.8 Frequency Range of Radiated Measurements	7
2. SYSTEM TEST CONFIGURATION.....	8
2.1 Configuration of Test System.....	8
3. PRELIMINARY TEST	9
3.1 Conducted Emission Test	9
3. 2 Radiated Emission Test	9
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	10
4.1 Conducted Emission Test	10
4.2 Radiated Emission Test	11
5. FIELD STRENGTH CALCULATION	24
6. TEST EQUIPMENT	25
7. CONCLUSION	26

ATTACHMENT: TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Product Description

Equipment Under Test is **EUT type: Multi-Band CDMA/EVDO/GSM/EDGE/WCDMA/LTE Phone with WLAN, Bluetooth, and RFID, Model: LS995** manufactured by **LG Electronics MobileComm U.S.A., Inc.** Its basic purpose is used for communications.

Model Name	LS995
FCC ID	ZNFLS995
Additional Model Name	LG-LS995, LGLS995
EUT Type	Multi-Band CDMA/EVDO/GSM/EDGE/WCDMA/LTE Phone with WLAN, Bluetooth, and RFID
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 826.40 MHz to 846.60 MHz (WCDMA 850) 1 852.4 MHz to 1 907.6 MHz (WCDMA 1 900) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 817.90 MHz to 823.10 MHz (CDMA BC10)
RX Frequency	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 871.40 MHz to 891.60 MHz (WCDMA 850) 1 932.4 MHz to 1 987.6 MHz (WCDMA 1 900) 1 925 MHz to 1 990 MHz (LTE B25) 859 MHz to 894 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 862.00 MHz to 894.00 MHz (CDMA BC10)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LS995	LG	ZNFLS995	Notebook PC Ear-phone
USB cable (USB2.0)	EAD6258801	CRESYN	-	E.U.T Notebook PC
USB cable (USB2.0)	EAD62329305	BROAD	-	E.U.T Notebook PC
USB cable (USB2.0)	EAD62329304	KSD	-	E.U.T Notebook PC
USB cable (USB3.0)	EAD62488701	BROAD	-	E.U.T Notebook PC
Ear-phone	EAB62691101	LG	-	E.U.T
Notebook PC	ProBook6570b	H.P	DoC	EUT, Notebook PC adaptor
Notebook PC adaptor	PPP012D-S	DELTA Electronics (JIANGSU)LTD	-	Notebook PC
Mouse	Serial mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
RJ45 cable	-	-	-	Notebook PC, Gateway

1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB (USB2.0)	Y	Y	(P,D)1.2
	Micro USB (USB3.0)	Y	Y	(P,D)0.1
	Ear-phone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB (USB2.0)	N	N/A	Y	Both End
	Micro USB (USB3.0)	N	N/A	Y	Both End
	Ear-phone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End

1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to EUT distance of 3 m

1.7 Test Facility

Chamber used to collect the test data is located at the 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3m)	90661(Mar. 02, 2011)
Radiated Field strength measurement facility (10m)	90661 (Sep. 03, 2010)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

2. SYSTEM TEST CONFIGURATION

2.1 Configuration of Test System


2.1.1 Conducted Emission Test

EUT was connected to LISN via Notebook PC adaptor and Base Station. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

2.1.2 Radiated Emission Test

Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m semi-anechoic chamber.

[Configuration of Tested System]



Non-Conductive Table
Power Line: 120 VAC

3. PRELIMINARY TEST

3.1 Conducted Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode (USB2.0)
 Data Communication mode (USB3.0)

3. 2 Radiated Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode (USB2.0)
 Data Communication mode (USB3.0)

4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Operation Mode	: Data Communication mode
USB Type (USB2.0)	: EAD6258801 (Cresyn)
Temperature	: 22.7 °C
Humidity Level	: 50.7 %
Test Date	: September 30, 2013

Frequency (MHz)	Transd (dB)	Conductor	Quasi-Peak			Average		
			Limit	Measurement Level	Result Level	Limit	Measurement Level	Result Level
			(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dBuV)
0.150	9.8	H	66	41.7	51.5	56	-	-
0.158	10.0	N	66	38.9	48.9	56	14.7	24.7
0.178	10.0	N	65	34.2	44.2	55	-	-
0.182	9.8	H	64	35.2	45.0	54	14.6	24.4
2.748	9.8	H	56	-	-	46	18.8	28.6
2.884	10.2	N	56	24.6	34.8	46	16.8	27.0

※ **NOTE:** Refer to page 11 to page 14 for details.

1. The worst-case emissions are reported.
2. Line H = Hot, Line N = Neutral
3. Transd = LISN factor + Cable Loss factor


HCT

EMC

EUT: LG-LS995
 Manufacturer: LG
 Operating Condition: DATA MODE (DATA CABLE : CRESYN)
 Test Site: SHIELD ROOM
 Operator: GC YOON
 Test Specification: FCC PART15 B
 Comment: H

SCAN TABLE: "FCC CLASS B(H)"

Short Description:			KN22 CLASS B				
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer	
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
500.0 kHz	5.0 MHz	4.0 kHz	Average	10.0 ms	9 kHz	None	
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average	10.0 ms	9 kHz	None	



MEASUREMENT RESULT: "PHONE_fin_QP"

2013-09-30 2:52 Ω 辛

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	51.50	9.8	66	14.5	---	---
0.182001	45.00	9.8	64	19.4	---	---
0.478001	33.10	9.8	56	23.3	---	---
2.952000	36.30	10.0	56	19.7	---	---
3.152000	36.00	10.1	56	20.0	---	---
3.300000	35.50	10.1	56	20.5	---	---
8.452000	33.40	10.4	60	26.6	---	---
8.852000	31.80	10.4	60	28.2	---	---
9.192000	31.30	10.4	60	28.7	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2013-09-30 2:52 오후

Frequency MHz	Level dB _{μV}	Transd dB	Limit dB _{μV}	Margin dB	Line	PE
0.182001	24.40	9.8	54	30.0	---	---
0.366001	18.20	9.8	49	30.4	---	---
0.486001	19.40	9.8	46	26.8	---	---
0.620000	21.20	9.8	46	24.8	---	---
2.316000	25.20	10.0	46	20.8	---	---
2.748000	28.60	10.0	46	17.4	---	---
8.612000	26.90	10.4	50	23.1	---	---
9.248000	27.60	10.4	50	22.4	---	---
18.244000	28.20	10.9	50	21.8	---	---


HCT

EMC

EUT: LG-LS995
 Manufacturer: LG
 Operating Condition: DATA MODE (DATA CALBLE : CRESYN)
 Test Site: SHIELD ROOM
 Operator: GC YOON
 Test Specification: FCC PART15 B
 Comment: N

SCAN TABLE: "FCC CLASS B(N)"

Short Description:			KN22 CLASS B			
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	4.0 kHz	Average			
			MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

2013-09-30 2:48 오후

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.158001	48.90	10.0	66	16.6	---	---
0.178001	44.20	10.0	65	20.4	---	---
0.500000	36.20	10.0	56	19.8	---	---
0.500000	36.20	10.0	56	19.8	---	---
2.304000	31.30	10.2	56	24.7	---	---
2.884000	34.80	10.2	56	21.2	---	---
8.340000	33.30	10.6	60	26.7	---	---
8.488000	34.00	10.6	60	26.0	---	---
8.680000	33.90	10.6	60	26.1	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2013-09-30 2:48 오후

Frequency MHz	Level dB _{μV}	Transd dB	Limit dB _{μV}	Margin dB	Line	PE
0.158001	24.70	10.0	56	30.8	---	---
0.370001	22.40	10.0	49	26.1	---	---
0.494001	22.40	10.0	46	23.7	---	---
0.656000	20.50	10.0	46	25.5	---	---
2.288000	23.30	10.2	46	22.7	---	---
2.884000	27.00	10.2	46	19.0	---	---
8.476000	26.90	10.6	50	23.1	---	---
18.244000	28.50	11.2	50	21.5	---	---
20.260000	28.20	11.3	50	21.8	---	---

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)

Operation Mode : Data Communication mode

USB Type (USB 3.0) : EAD62488701 (BROAD)

Temperature : 22.7 °C

Humidity Level : 50.7 %

Test Date : September 30, 2013

Frequency	Transd	Conductor	Quasi-Peak			Average		
			Limit	Measurement Level	Result Level	Limit	Measurement Level	Result Level
(MHz)	(dB)		(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dBuV]
0.150	9.8	H	66	42.2	52.0	56	-	-
0.170	9.8	H	65	39.2	49.0	55	19.8	29.6
0.150	10.0	N	66	43.3	53.3	56	20.5	30.5
0.170	10.0	N	65	39.7	49.7	55	-	-
3.040	10.1	H	56	-	-	46	19.6	29.7
23.128	11.4	N	60	-	-	50	22.1	33.5

※ **NOTE:** Refer to page 16 to page 19 for details.

1. Line H = Hot, Line N = Neutral
2. Transd = LISN factor + Cable Loss factor


HCT

EMC

EUT: LG-LS995
 Manufacturer: LG
 Operating Condition: DATA MODE USB 3.0
 Test Site: SHIELD ROOM
 Operator: GC YOON
 Test Specification: FCC PART15 B
 Comment: H

SCAN TABLE: "FCC CLASS B(H)"

Short Description:			KN22 CLASS B			
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	4.0 kHz	Average	10.0 ms	9 kHz	None
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

2013-09-30 3:17 오후

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	52.20	9.8	66	13.8	---	---
0.170001	49.00	9.8	65	16.0	---	---
0.178001	47.00	9.8	65	17.6	---	---
2.276000	33.70	10.0	56	22.3	---	---
2.948000	37.00	10.0	56	19.0	---	---
3.300000	35.80	10.1	56	20.2	---	---
8.620000	34.20	10.4	60	25.8	---	---
8.664000	34.00	10.4	60	26.0	---	---
8.724000	33.80	10.4	60	26.2	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2013-09-30 3:17 오후

Frequency MHz	Level dB _{μV}	Transd dB	Limit dB _{μV}	Margin dB	Line	PE
0.170001	29.60	9.8	55	25.4	---	---
0.178001	27.00	9.8	55	27.6	---	---
0.474001	20.40	9.8	46	26.0	---	---
0.980000	22.20	9.8	46	23.8	---	---
2.276000	26.20	10.0	46	19.8	---	---
3.040000	29.70	10.1	46	16.3	---	---
18.244000	31.40	10.9	50	18.6	---	---
20.260000	31.30	10.9	50	18.7	---	---
23.128000	32.90	11.1	50	17.1	---	---


HCT

EMC

EUT: LG-LS995
 Manufacturer: LG
 Operating Condition: DATA MODE USB 3.0
 Test Site: SHIELD ROOM
 Operator: GC YOON
 Test Specification: FCC PART15 B
 Comment: N

SCAN TABLE: "FCC CLASS B(N)"

Short Description:			KN22 CLASS B				
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer	
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



MEASUREMENT RESULT: "PHONE_fin QP"

2013-09-30 3:21오.후

Frequency MHz	Level dB	Transd dB	Limit dB	Margin dB	Line	PE
0.150001	53.30	10.0	66	12.7	---	---
0.170001	49.70	10.0	65	15.3	---	---
0.182001	46.40	10.0	64	18.0	---	---
0.576000	34.30	10.0	56	21.7	---	---
0.724000	33.20	10.0	56	22.8	---	---
3.172000	35.20	10.3	56	20.8	---	---
8.500000	34.40	10.6	60	25.6	---	---
8.704000	34.60	10.6	60	25.4	---	---
8.828000	34.10	10.6	60	25.9	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2013-09-30 3:21오후

Frequency MHz	Level dB _{μV}	Transd dB	Limit dB _{μV}	Margin dB	Line	PE
0.150001	30.50	10.0	56	25.5	---	---
0.162001	32.50	10.0	55	22.8	---	---
0.426001	21.60	10.0	47	25.7	---	---
0.928000	21.50	10.0	46	24.5	---	---
2.276000	24.90	10.2	46	21.1	---	---
2.872000	28.40	10.2	46	17.6	---	---
20.260000	31.80	11.3	50	18.2	---	---
21.664000	32.60	11.3	50	17.4	---	---
23.128000	33.50	11.4	50	16.5	---	---

4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

-For measurement below 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Quasi-Peak (6 dB Bandwidth: 120 kHz)

Operation Mode : Data Communication mode

USB Type (USB 2.0) : EAD62329305 (BROAD)

Temperature : 25.0 °C

Humidity Level : 54.0 %

Test Date : October 01, 2013

Frequency (MHz)	Reading (dBUV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBUV/m)	Level (dBUV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
58.0	12.73	V	1.0	11.92	3.62	40.0	28.27	11.7
213.7	22.62	H	1.1	10.33	4.38	43.5	37.33	6.2
270.1	22.15	H	1.3	12.43	4.56	46.0	39.14	6.9
328.0	20.47	H	1.1	14.03	4.74	46.0	39.24	6.8
624.0	10.75	V	1.0	19.96	5.51	46.0	36.22	9.8
900.0	4.55	V	1.0	23.38	5.99	46.0	33.92	12.1

※ NOTE:

1. The worst-case emissions are reported.

-For measurement below 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Quasi-Peak (6 dB Bandwidth: 120 kHz)

Operation Mode : Data Communication mode

USB Type (USB 3.0) : EAD62488701 (BROAD)

Temperature : 25.0 °C

Humidity Level : 54.0 %

Test Date : October 01, 2013

Frequency (MHz)	Reading (dBuV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBuV/m)	Level (dBuV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
125.0	9.69	V	1.0	12.01	4.02	43.5	25.72	17.8
214.1	21.48	H	1.5	10.35	4.39	43.5	36.22	7.3
270.1	18.43	V	1.0	12.43	4.56	46.0	35.42	10.6
335.9	17.79	V	1.5	14.21	4.77	46.0	36.77	9.2
624.0	8.77	V	1.3	19.96	5.51	46.0	34.24	11.8
900.0	3.57	V	1.2	23.38	5.99	46.0	32.94	13.1

-For measurement above 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Peak mode: Peak (RBW: 1 MHz, VBW: 1 MHz)
 : Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)

Operation Mode : Data Communication mode

USB Type (USB 2.0) : EAD62329305 (BROAD)

Temperature : 23.7 °C

Humidity Level : 60.0 %

Test Date : October 02, 2013

Frequency (GHz)	Peak			POL	Average		
	Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)		Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2.2405	53.10	74	20.9	V	36.60	54	17.4
2.5428	51.40	74	22.6	V	30.00	54	24.0

※ **NOTE:**

1. The worst-case emissions are reported.
2. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. Test was measured by 12 GHz.

-For measurement above 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Peak mode: Peak (RBW: 1 MHz, VBW: 1 MHz)
 : Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)

Operation Mode : Data Communication mode

USB Type (USB 3.0) : EAD62488701 (BROAD)

Temperature : 23.7 °C

Humidity Level : 60.0 %

Test Date : October 02, 2013

Frequency (GHz)	Peak			POL	Average		
	Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)		Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2.2405	54.10	74	19.9	V	38.00	54	16.0
2.4928	49.20	74	24.8	H	35.90	54	18.1
3.1190	51.40	74	22.6	V	32.00	54	22.0

※ NOTE:

1. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. Test was measured by 12 GHz.

5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

[Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	μ V/m	dB μ V/m
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>Next CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	2014.04.25
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	2014.06.23
<input type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	2014.07.03
<input checked="" type="checkbox"/> LISN	EMCO	3816/2SH	9706-1070	1 year	2014.04.26
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	2014.02.06
<input type="checkbox"/> Attenuator	Rohde & Schwarz	ESH3-Z2	357.8810.352	1 year	2014.07.03
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	2014.12.17
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Turn Table	HD GmbH	2090	9702/1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
<input type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9168	185	2 year	2015.04.16
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Turn Table	HD GmbH	2090	9702/1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21690	1 year	2014.07.12
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	2014.12.13

7. CONCLUSION

The data collected shows that the **EUT type: Multi-Band CDMA/EVDO/GSM/EDGE/WCDMA/LTE Phone with WLAN, Bluetooth, and RFID, FCC ID: ZNFLS995, Model: LS995** complies with §15.107 and §15.109 of the FCC rules.