

# TEST REPORT

of

FCC Part 15 Subpart E §15.407  
FCC ID: ZNFP940

Equipment Under Test : Cellular/PCS GSM/GPRS/EDGE and PCS  
WCDMA/HSUPA Phone with Bluetooth, WLAN and NFC

Model Name : LG-P940

Serial No. : N/A

Applicant : LG Electronics mobileComm U.S.A.,Inc.

Manufacturer : LG Electronics mobileComm U.S.A.,Inc.

Date of Test(s) : 2011.09.06 ~ 2011.10.24

Date of Issue : 2011.10.24

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date

2011.10.24

Wonsuk Kim

Approved By:



Date

2011.10.24

Charles Kim

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

---

## Table of contents

1. General information -----	3
2. Transmitter radiated spurious emissions and conducted spurious emission ----	6
3. 26 Bandwidth -----	28
4. Output power -----	39
5. Peak power spectral density -----	42
6. Peak excursion -----	53
7. Transmitter AC Power line conducted emission-----	64
8. DFS (Dynamic Frequency Selection)-----	68

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 1. General information

### 1.1. Testing laboratory

SGS Korea Co., Ltd.(Gunpo Laboratory)

- 705, Dongchun-Dong Sooji-Gu, Yongin-Shi, Kyungki-Do, South Korea.
- Wireless Div. 2FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040

[www.kr.sgs.com/ee](http://www.kr.sgs.com/ee)

Phone No. : +82 +31 428 5700

Fax No. : +82 +31 427 2371

### 1.2 Details of applicant

Applicant : LG Electronics mobileComm U.S.A.,Inc.  
 Address : 10101 Old Grove Road, San Diego, CA 92131  
 Contact Person : An, Hee-Ju  
 Phone No. : +82 +10 2846 2750

### 1.3 Description of EUT

<b>Kind of Product</b>	Cellular/PCS GSM/GPRS/EDGE and PCS WCDMA/HSUPA Phone with Bluetooth, WLAN and NFC
<b>Model Name</b>	LG-P940
<b>Serial Number</b>	N/A
<b>Power Supply</b>	DC 3.7 V (Li-Ion Battery)
<b>Frequency Range</b>	2 412 MHz ~ 2 462 MHz (11b/g/n) 5 180 MHz ~ 5 240 MHz (11a/n – Non DFS) 5 260 MHz ~ 5 320 MHz (11a/n – DFS) 5 500 MHz ~ 5 700 MHz (11a/n – DFS)
<b>Modulation Technique</b>	DSSS, OFDM
<b>Number of Channels</b>	11 channel(11b/g/n), 4 channel(11a/n – Non DFS), 4 channel (11a/n - DFS_ 5 260 MHz ~ 5 320 MHz), 11 channel (11a/n - DFS_ 5 500 MHz ~ 5 700 MHz)
<b>Antenna Type</b>	Fixed type
<b>Antenna Gain</b>	-3.43 dB i(11b/g/n), -1.55 dB i(11a/n – Non DFS), -1.30 dB i(11a/n -DFS)

### 1.4. Description of test mode

- EUT is SLAVE without DFS and TPC.

802.11a & (Non-DFS) mode:

We found out the test mode with the highest power level after we analyze all the data rates. So we choose 6 Mbps data rate (worst case) as a representative.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 1.5. Test equipment list

Equipment	Manufacturer	Model	S/N	Cal Due.
Signal Generator	R & S	SMR40	100272	Jul. 15, 2012
Spectrum Analyzer	R & S	FSP40	100007	Jul. 14, 2012
Spectrum Analyzer	Agilent	E4440A	MY43362142	May. 18, 2012
Attenuator	Agilent	8494B	MY42141937	Apr. 01, 2012
High Pass Filter	Wainwright	WHK3.0/18G-10SS	344	Jul. 07, 2012
DC power Supply	Agilent	U8002A	MY49030063	Jan. 05, 2012
Preamplifier	H.P.	8447F	2944A03909	Jul. 04, 2012
Preamplifier	R & S	SCU 18	10117	Mar. 23, 2012
Test Receiver	R & S	ESU26	100109	Feb. 21, 2012
Two-Line V-Network	R & S	ENV216	100190	Jan. 06, 2012
Test Receiver	R & S	ESHS10	863365/018	Apr. 27, 2012
Bilog Antenna	SCHWARZBECK MESSELEKTRONIK	VULB9163	396	Apr. 27, 2013
Horn Antenna	R & S	HF 907	100019	Jul. 29, 2012
Horn Antenna	SCHWARZBECK	BBH 9120D	BBHA9170431	Mar. 17, 2012
Antenna Master	EMCO	1050	N.C.R.	N.C.R.
Turn Table	Daeil EMC	DI-1500	N.C.R.	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N.C.R.	N.C.R.

### ► Support equipment

Description	Manufacturer	Model	Serial Number
Access Point( master)	Cisco	AIR-AP1242AG-K-K9	FHK1034407S
Notebook	IBM	T43	2669CC8

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 1.7. Summary of test result

The EUT has been tested according to the following specifications:

Applied standard : FCC Part15 subpart E		
Standard section	Test Item	Result
15.205(a) 15.209(a) 15.407(b)(1)	Transmitter radiated spurious emissions and Conducted spurious emission	Complied
15.407(a)(1)	Output power	Complied
15.407(a)(1)	Peak power spectral density	Complied
15.407(a)(1)	Peak excursion	Complied
15.207	Transmitter AC power line conducted emission	Complied
15.407(h)	DFS -Channel closing transmission time -Channel move time -Non occupied period	Complied

## 1.8. Test report revision

Revision	Report number	Description
0	F690501/RF-RTL004980	Initial
1	F690501/RF-RTL004980-1	The band(5745-5825) is deleted
2	F690501/RF-RTL004980-2	Retest for density and conducted spurious


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 2. Transmitter radiated spurious emissions and conducted spurious emission


### 2.1. Test setup

#### 2.1.1. Transmitter radiated spurious emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 40 GHz Emissions.



#### 2.1.2. Conducted spurious emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 2.2. Limit

For transmitters operating in the 5.15 ~ 5.25 GHz band : all emissions outside of the 5.15 ~ 5.35 GHz band shall not exceed an EIRP of -27 dB m

For transmitters operating in the 5.25–5.35 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of -27 dB m/MHz. Devices operating in the 5.25–5.35 GHz band that generate emissions in the 5.15–5.25 GHz band must meet all applicable technical requirements for operation in the 5.15–5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dB m/MHz in the 5.15–5.25 GHz band.

For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of -27 dB m/MHz.

## 2.3. Test procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

### 2.3.1. Test procedures for radiated spurious emissions

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### ■ Note

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) or Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

### 2.3.2. Test procedures for conducted spurious emissions

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW=1 MHz, VBW=1 MHz.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 2.4. Test result

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 49 % R.H.

### 2.4.1. Spurious radiated emission

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions are not reported much lower than the prescribed limits.

Radiated emissions			Ant	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect mode	Pol.	AF (dB/m)	Amp gain+CL (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
Below 1 000.00	Not detected	-	-	-	-	-	-	-

▣ Remark:

1. All spurious emission at channels are almost the same below 1 GHz, so that the channel was chosen at representative in final test.
2. Actual = Reading + AF + AMP + CL
3. To get a maximum emission level from the EUT, the EUT was moved throughout the X, Y and Z planes. The worst case is Z.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 2.4.2. Spurious radiated emission for above 1 GHz

### 802.11a (Non-DFS)

#### A. Low Channel (5 180 MHz)

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 150.00*	28.36	Peak	V	34.80	8.24	-9.5	61.90	74.00	12.10
5 150.00*	14.91	Average	V	34.80	8.24	-9.5	48.45	54.00	5.55
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 356.31	53.01	Peak	V	38.00	-32.58	-9.5	48.93	74.00	25.07
Above 10 400.00	Not Detected	-	-	-	-	-	-	-	-

#### B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 437.84	49.69	Peak	V	38.00	-33.65	-9.5	44.54	74.00	29.46
Above 10 500.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**C. High Channel (5 240 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 350.00*	26.71	Peak	V	34.80	8.36	-9.5	60.37	74.00	13.63
5 350.00*	15.62	Average	V	34.80	8.36	-9.5	49.28	54.00	4.72
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 479.44	50.25	Peak	V	38.00	-33.29	-9.5	45.46	74.00	28.54
Above 10 500.00	Not Detected	-	-	-	-	-	-	-	-

**802.11a (DFS)**
**A. Low Channel (5 260 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 519.92	50.31	Peak	V	38.00	-33.02	-9.5	45.79	74.00	28.21
Above 10 600.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**B. Middle Channel (5 300 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 595.75	49.19	Peak	V	38.00	-33.68	-9.5	44.01	74.00	29.99
Above 10 600.00	Not Detected	-	-	-	-	-	-	-	-

**C. High Channel (5 320 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 350.00*	27.91	Peak	V	34.80	8.36	-9.5	61.57	74.00	12.43
5 350.00*	15.64	Average	V	34.80	8.36	-9.5	49.30	54.00	4.70
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 635.83	50.42	Peak	V	38.10	-33.36	-9.5	45.66	74.00	28.34
Above 10 700.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**802.11a (DFS)**
**A. Low Channel (5 500 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 460.00*	26.34	Peak	V	34.80	8.18	-9.5	59.82	74.00	14.18
5 460.00*	14.95	Average	V	34.80	8.18	-9.5	48.43	54.00	5.57
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 997.44	50.05	Peak	V	38.30	-32.87	-9.5	45.98	74.00	28.02
Above 11 000.00	Not Detected	-	-	-	-	-	-	-	-

**B. Middle Channel (5 600 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
11 196.96	48.65	Peak	V	38.40	-32.76	-9.5	44.79	74.00	29.21
Above 11 200.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**C. High Channel (5 700 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
11 373.43	48.69	Peak	V	38.50	-32.99	-9.5	44.70	74.00	29.30
Above 11 400.00	Not Detected	-	-	-	-	-	-	-	-

**802.11n (Non-DFS)**
**A. Low Channel (5 180 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 150.00*	28.21	Peak	V	34.80	8.24	-9.5	61.75	74.00	12.25
5 150.00*	15.10	Average	V	34.80	8.24	-9.5	48.64	54.00	5.36
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 357.92	50.51	Peak	V	38.00	-32.59	-9.5	46.44	74.00	27.56
Above 10 400.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 443.21	49.20	Peak	V	38.00	-33.75	-9.5	43.95	74.00	30.05
Above 10 500.00	Not Detected	-	-	-	-	-	-	-	-

## C. High Channel (5 240 MHz)

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 350.00*	26.90	Peak	V	34.80	8.36	-9.5	60.56	74.00	13.44
5 350.00*	15.60	Average	V	34.80	8.36	-9.5	49.26	54.00	4.74
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 482.48	48.11	Peak	V	38.00	-33.23	-9.5	43.38	74.00	30.62
Above 10 500.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**802.11n (DFS)**

## A. Low Channel (5 260 MHz)

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 518.64	47.88	Peak	V	38.00	-33.01	-9.5	43.37	74.00	30.63
Above 10 600.00	Not Detected	-	-	-	-	-	-	-	-

## B. Middle Channel (5 300 MHz)

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 596.15	46.02	Peak	V	38.00	-33.69	-9.5	40.83	74.00	33.17
Above 10 600.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**C. High Channel (5 320 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 350.00*	27.89	Peak	V	34.80	8.36	-9.5	61.55	74.00	12.45
5 350.00*	15.62	Average	V	34.80	8.36	-9.5	49.28	54.00	4.72
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 637.20	46.68	Peak	V	38.10	-33.35	-9.5	41.93	74.00	32.07
Above 10 700.00	Not Detected	-	-	-	-	-	-	-	-

**802.11n (DFS)**
**A. Low Channel (5 500 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
5 460.00*	26.90	Peak	V	34.80	8.18	-9.5	59.58	74.00	14.42
5 460.00*	14.93	Average	V	34.80	8.18	-9.5	47.61	54.00	6.39
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
10 998.96	45.62	Peak	V	38.30	-32.88	-9.5	41.54	74.00	32.46
Above 11 000.00	Not Detected	-	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**B. Middle Channel (5 600 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
11 201.44	45.41	Peak	V	38.40	-32.78	-9.5	41.53	74.00	32.47
Above 11 300.00	Not Detected	-	-	-	-	-	-	-	-

**C. High Channel (5 700 MHz)**

Radiated Emissions			Ant	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB uV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+ CL (dB)	Dis. (dB)	Actual (dB uV/m)	Limit (dB uV/m)	Margin (dB)
11 397.84	41.71	Peak	V	38.50	-32.98	-9.5	37.73	74.00	36.27
Above 11 400.00	Not Detected	-	-	-	-	-	-	-	-

**▣ Remarks**


1. "\*" means the restricted band.
2. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental Frequency.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using peak/average detector mode.
4. Average test would be performed if the peak result were greater than the average limit.
5. To get a maximum emission level from the EUT, the EUT was moved throughout the X, Y and Z planes. The worst case is Z.
6. Spurious emission above 5 GHz measured 1 m away from EUT.  
Distance remuneration is -9.5 dB. Ref.) 20 log (1/3) = -9.5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


### 2.4.3. Spurious RF Conducted Emissions: Plot of Spurious RF Conducted Emission

#### 802.11a (Non-DFS)

Low Channel (5 180 MHz)




Middle Channel (5 220 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 240 MHz)




## 802.11a (DFS)

### Low Channel (5 260 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 300 MHz)




## High Channel (5 320 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11a (DFS)

### Low Channel (5 500 MHz)




### Middle Channel (5 600 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 700 MHz)




## 802.11n (Non-DFS)

### Low Channel (5 180 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 220 MHz)




## High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11n (DFS)

### Low Channel (5 260 MHz)




### Middle Channel (5 300 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 320 MHz)




## 802.11n (DFS)

## Low Channel (5 500 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 600 MHz)



## High Channel (5 700 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

### 3. 26 dB bandwidth

#### 3.1. Test setup



#### 3.2. Limit

None; for reporting purpose only

#### 3.3. Test procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100 kHz, VBW = RBW, Span = 100 MHz, Sweep = auto.
4. Repeat until all the rest channels are investigated.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 3.4. Test result

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 49 % R.H.

Mode : 11a

Operating mode	Frequency(MHz)	26 dB bandwidth(MHz)
Non - DFS	5 180	18.60
	5 220	18.60
	5 240	18.60
DFS	5 260	18.80
	5 300	18.60
	5 320	18.60
DFS	5 500	18.60
	5 600	18.60
	5 700	18.40


Mode : 11n

Operating mode	Frequency(MHz)	26 dB bandwidth(MHz)
Non - DFS	5 180	19.00
	5 220	18.80
	5 240	18.80
DFS	5 260	19.00
	5 300	19.00
	5 320	19.00
DFS	5 500	18.80
	5 600	19.00
	5 700	18.80


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 802.11a (Non-DFS)

### Low Channel (5 180 MHz)




### Middle Channel (5 220 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 240 MHz)




## 802.11a (DFS)

### Low Channel (5 260 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 300 MHz)




## High Channel (5 320 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11a (DFS)

### Low Channel (5 500 MHz)




### Middle Channel (5 600 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 700 MHz)




## 802.11n (Non-DFS)

### Low Channel (5 180 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 220 MHz)




## High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11n (DFS)

### Low Channel (5 260 MHz)




### Middle Channel (5 300 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 320 MHz)




## 802.11n (DFS)

### Low Channel (5 500 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 600 MHz)




## High Channel (5 700 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 4. Output power

### 4.1. Test setup



### 4.2. Limit

For the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or  $4 \text{ dBm} + 10 \log B$ , where B is the 26-dB emission bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 4.3. Test procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to power sensor

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 4.4. Test result

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 49 % R.H.

Limit  
 Mode : 11a

Frequency (MHz)	Fixed Limit (dB m)	B (MHz)	4+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
5 180	17	18.60	16.70	-2.37	16.70
5 220	17	18.60	16.70	-2.37	16.70
5 240	17	18.60	16.70	-2.37	16.70

Frequency (MHz)	Fixed Limit (dB m)	B (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
5 260	24	18.80	23.74	-2.37	23.74
5 300	24	18.60	23.70	-2.37	23.70
5 320	24	18.60	23.70	-2.37	23.70
5 500	24	18.60	23.70	-2.37	23.70
5 600	24	18.60	23.70	-2.37	23.70
5 700	24	18.40	23.65	-2.37	23.65

Mode : 11n

Frequency (MHz)	Fixed Limit (dB m)	B (MHz)	4+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
5 180	17	19.00	16.79	-2.37	16.79
5 220	17	18.80	16.74	-2.37	16.74
5 240	17	18.80	16.74	-2.37	16.74

Frequency (MHz)	Fixed Limit (dB m)	B (MHz)	11+10LogB (dB m)	Antenna gain (dB i)	Limit (dB)
5 260	24	19.00	23.79	-2.37	23.79
5 300	24	19.00	23.79	-2.37	23.79
5 320	24	19.00	23.79	-2.37	23.79
5 500	24	18.80	23.74	-2.37	23.74
5 600	24	19.00	23.79	-2.37	23.79
5 700	24	18.80	23.74	-2.37	23.74

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Results

Mode : 11a

Frequency (MHz)	Output power (dB m)	Limit (dB m)	Margin (dB)
5 180	11.73	16.70	4.97
5 220	12.27	16.70	4.43
5 240	12.01	16.70	4.69

Frequency (MHz)	Output power (dB m)	Limit (dB m)	Margin (dB)
5 260	11.97	23.74	11.77
5 300	11.98	23.70	11.72
5 320	11.85	23.70	11.85
5 500	11.12	23.70	12.58
5 600	10.95	23.70	12.75
5 700	10.77	23.65	12.88

Mode : 11n

Frequency (MHz)	Output power (dB m)	Limit (dB m)	Margin (dB)
5 180	10.59	16.79	6.2
5 220	11.02	16.74	5.72
5 240	10.83	16.74	5.91

Frequency (MHz)	Output power (dB m)	Limit (dB m)	Margin (dB)
5 260	10.87	23.79	12.92
5 300	10.90	23.79	12.89
5 320	10.71	23.79	13.08
5 500	10.09	23.74	13.65
5 600	9.87	23.79	13.92
5 700	9.72	23.74	14.02

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 5. Peak power spectral density

### 5.1. Test setup



### 5.2. Limit

For the 5.15-5.25 GHz band, the peak power spectral density shall not exceed 4 dBm in any 1 MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The maximum antenna gain is less than or equal to 6 dB i, therefore the limit is 4 dB m.

For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the peak power spectral density shall not exceed 11 dB m in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dB i are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB i.

### 5.3. Test procedure

1. Place the EUT on the table and set it in transmitting mode  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 1 MHz, VBW = 3 MHz, Span = 20 MHz.
3. Record the max reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 5.4. Test result

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 49 % R.H.

Mode : 11a

Operating mode	Frequency (MHz)	PPSD (dB m)	Limit (dB m)	Margin (dB)
Non - DFS	5 180	0.18	4	3.82
	5 220	0.84		3.16
	5 240	0.20		3.80
DFS	5 260	0.05	11	10.95
	5 300	0.51		10.49
	5 320	0.06		10.94
DFS	5 500	-0.56		11.56
	5 600	-1.09		12.09
	5 700	-1.39		12.39

Mode : 11n

Operating mode	Frequency (MHz)	PPSD (dB m)	Limit (dB m)	Margin (dB)
Non - DFS	5 180	-1.32	4	5.32
	5 220	-0.92		4.92
	5 240	-1.01		5.01
DFS	5 260	-1.10	11	12.10
	5 300	-0.94		11.94
	5 320	-1.32		12.32
DFS	5 500	-1.70		12.70
	5 600	-1.83		13.20
	5 700	-2.70		13.70


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11a (Non-DFS)

Low Channel (5 180 MHz)




Middle Channel (5 220 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 240 MHz)




## 802.11a (DFS)

### Low Channel (5 260 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

### Middle Channel (5 300 MHz)



### High Channel (5 320 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11a (DFS)

Low Channel (5 500 MHz)




Middle Channel (5 600 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 700 MHz)




## 802.11n (Non-DFS)

### Low Channel (5 180 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel (5 220 MHz)




High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

### 802.11a (DFS)

Low Channel (5 260 MHz)



Middle Channel (5 300 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel (5 320 MHz)



802.11a (DFS)

Low Channel (5 500 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel (5 600 MHz)



High Channel (5 700 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 6. Peak excursion

### 6.1. Test setup



### 6.2. Limit

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the peak transmit power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less. The maximum antenna

### 6.3. Test procedure

1. Place the EUT on the table and set it in transmitting mode  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as ;  
RBW = 1 MHz, VBW = 3 MHz, Span = 30 MHz, Detector mode: average, Trace 1: Max hold & View
3. Set the spectrum analyzer as ;  
RBW = 1 MHz, VBW = 3 MHz, Span = 30 MHz, Detector mode: peak, Trace 2: Max hold
4. Record the max reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 6.4. Test result

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 49 % R.H.

Mode : 11a

Operating mode	Frequency (MHz)	Peak excursion (dB)	Limit (dB)	Margin (dB)
Non - DFS	5 180	8.77	13	4.23
	5 220	9.54		3.46
	5 240	8.80		4.20
DFS	5 260	9.93		3.07
	5 300	9.88		3.12
	5 320	9.14		3.86
DFS	5 500	9.15		3.85
	5 600	8.66		4.34
	5 700	9.37		3.63


Mode : 11n

Operating mode	Frequency (MHz)	Peak excursion (dB)	Limit (dB)	Margin (dB)
Non - DFS	5 180	8.01	13	4.99
	5 220	9.17		3.83
	5 240	8.84		4.16
DFS	5 260	9.47		3.53
	5 300	9.25		3.75
	5 320	9.34		3.66
DFS	5 500	8.17		4.83
	5 600	9.08		3.92
	5 700	9.28		3.72


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11a (Non-DFS)

### Low Channel (5 180 MHz)




### Middle Channel (5 220 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



## Middle Channel (5 300 MHz)




## High Channel (5 320 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11a (DFS)

### Low Channel (5 500 MHz)




### Middle Channel (5 600 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 700 MHz)




## 802.11n (Non-DFS)

### Low Channel (5 180 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 220 MHz)




## High Channel (5 240 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 802.11n (DFS)

### Low Channel (5 260 MHz)




### Middle Channel (5 300 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## High Channel (5 320 MHz)




## 802.11n (DFS)

### Low Channel (5 500 MHz)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Middle Channel (5 600 MHz)




## High Channel (5 700 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 7. Transmitter AC power line conducted emission

### 7.1. Test setup



### 7.2. Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 – 0.50	66-56*	56-46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

▣ Decreases with the logarithm of the frequency.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

### 7.3. Test procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

1. The test procedure is performed in a 6.5 m × 3.6 m × 3.6 m (L×W×H) shielded room. The EUT along with its peripherals were placed on a 1.0 m(W)× 1.5 m(L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 7.4. Test result (Worst case configuration\_802.11a (5 300 MHz))

The following table shows the highest levels of conducted emissions on both phase of Hot and Neutral line.

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 49 % R.H.  
 Frequency range : 0.15 MHz – 30 MHz  
 Measured Bandwidth : 9 kHz

Freq. (MHz)	Level (dB uV)		Line	Limit (dB uV)		Margin (dB)	
	Q-Peak	Average		Q-Peak	Average	Q-Peak	Average
0.42	42.90	30.90	H	57.55	47.55	14.65	16.65
0.54	44.70	34.30	H	56.00	46.00	11.30	11.70
0.95	41.90	31.40	H	56.00	46.00	14.10	14.60
2.25	38.70	29.30	H	56.00	46.00	17.30	16.70
10.48	32.50	20.20	H	60.00	50.00	27.50	29.80
23.98	11.40	7.10	H	60.00	50.00	48.60	42.90
0.27	38.20	24.50	N	61.12	51.12	22.92	26.62
0.42	41.60	32.30	N	57.55	47.55	15.95	15.25
0.89	36.60	26.40	N	56.00	46.00	19.40	19.60
2.18	35.60	23.60	N	56.00	46.00	20.40	22.40
13.32	37.50	23.40	N	60.00	50.00	22.50	26.60
27.25	10.20	5.60	N	60.00	50.00	49.80	44.40


■ Note

Line ( H ) : Hot  
 Line ( N ) : Neutral

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*


### Plot of conducted power line

Test mode: (Hot)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Test mode: (Neutral)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 8. DFS (Dynamic Frequency Selection)

### 8.1. System overview

#### 8.1.1. Set up of EUT



#### ► Support equipment

Description	Manufacturer	Model	Cal Due.
Spectrum analyzer	R&S	FSV30	Mar. 31, 2012
Vector signal generator	R&S	SMBV100A	Jul. 20, 2012
Access Point( master)	Cisco	AIR-AP1242AG-K-K9	N / A
Notebook	IBM	T43	N / A
Splitter / Combiner	Mini-Circuits	ZFSC-2-10G	Oct. 30, 2012
Attenuator	Agilent	8494B	Apr. 01, 2012

The radar signal generation equipment consists of a vector signal generator

The signal monitoring equipment consists of a spectrum analyzer set to display 8001 bins on the horizontal axis. The time domain resolution is 2 msec/bin with a 16 second sweep time, meeting the 10 second short pulse reporting criteria. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold.

The Slave is tested separately for compliance with the Channel Shutdown requirements, for the situation when the Slave device vacates the channel in response to detection of a radar by the Master.

All tests were performed at a channel center frequency of 5 500 MHz. Measurements were performed using conducted test methods.

### 8.2 Limit

§15.407 (h) and FCC 06-96 APPENDIX "COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350 MHz AND 5470-5725 MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 8.1.1. Set up of EUT

**Table 1: Applicability of DFS requirements prior to use of a channel**

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client (with radar detection)
Non-Occupancy Period	Yes	Yes	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
Uniform Spreading	Yes	Not required	Not required

**Table 2: Applicability of DFS requirements during normal operation**

Requirement	Operational Mode		
	Master	Client (without DFS)	Client (with DFS)
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes

**Table 3: Interference Threshold values, Master or Client incorporating In-Service Monitoring**

Maximum Transmit Power	Value (see note)
≥ 200 milliwatt	-64 dBm
< 200 milliwatt	-62 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

**Table 4: DFS Response requirement values**

Parameter	Value
Non-occupancy period	30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds
Channel Closing Transmission Time	200 milliseconds + approx. 60 milliseconds over remaining 10 second period

The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:  
 For the Short pulse radar Test Signals this instant is the end of the Burst. For the Frequency Hopping radar Test Signal, this instant is the end of the last radar burst generated. For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission. The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate channel changes (an aggregate of approximately 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

**Table 5 – Short Pulse Radar Test Waveforms**

Radar Type	Pulse Width (Microseconds)	PRI (Microseconds)	Pulses	Minimum Percentage of Successful Detection	Minimum Trials
1	1	1428	18	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

**Table 6 – Long Pulse Radar Test Signal**

Radar Waveform	Bursts	Pulses per Burst	Pulse Width (µsec)	Chirp Width (MHz)	PRI (µsec)	Minimum Percentage of Successful Detection	Minimum Trials
5	8-20	1-3	50-100	5-20	1000-2000	80%	30

**Table 7 – Frequency Hopping Radar Test Signal**

Radar Waveform	Pulse Width (µsec)	PRI (µsec)	Burst Length (ms)	Pulses per Hop	Hopping Rate (kHz)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	300	9	.333	70%	30

## 8.2. Description of EUT

The EUT operates over the 5 250 MHz ~ 5 350 MHz (11a – DFS), 5 470 MHz ~ 5725 MHz (11a – DFS) range.

The gain antenna assembly utilized with the master has a gain of 2.50 dB i.


The rated output power of the master unit is <200 milliwatt. Therefore the required interference threshold level is -62 dB m. After correction for antenna gain and procedure adjustments the required conducted threshold at the antenna port is -62 +2.5 = -59.50 dB m

The calibrated conducted DFS Detection Threshold level is set to - 59 dB m


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## PLOTS OF RADAR WAVEFORMS AND WLAN TRAFFIC

### Plot of radar waveform type 1



### Plot of LAN traffic



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

The reference maker is set at the end of Last radar pulse.

The delta maker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time= (Number of analyzer bins showing transmission)\*(dwell time per bin)

The observation period over which the aggregated time is calculated begins at (Reference Maker) and ends no earlier than (Reference Maker +10 sec)

### **8.3. Test result**


Channel Move Time (sec)	Limit (sec)
5.86	10

Aggregate channel closing transmission time (msec)	Limit (msec)
292	1000


2 \* 146 = 292 msec

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

**Plot of channel move time**




**Plot of aggregate channel closing transmission time**



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

**Plot of Non-occupancy period**



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*