



**MEASUREMENT REPORT
 FCC Part 90**

Applicant Name:
 LG Electronics USA, Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 01/14/20 - 02/13/20
Test Site/Location:
 PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
 1M2001130006 - 04.ZNF

FCC ID:	ZNFQ730TM
APPLICANT:	LG Electronics USA, Inc.

Application Type: Certification
Model: LM-Q730TM
Additional Model(s): LM-Q730MM, LMQ730TM, LMQ730MM, Q730TM, Q730MM
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part: §2.1049, §22(H), §90(S)
Test Procedure(s): ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortanez
 President




FCC ID: ZNFQ730TM	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 1 of 47

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS	10
7.1	Summary	10
7.2	Occupied Bandwidth	11
7.3	Spurious and Harmonic Emissions at Antenna Terminal	21
7.4	Band Edge Emissions at Antenna Terminal	27
7.5	Conducted Power Output Data	34
7.6	Radiated Power (ERP)	35
7.7	Radiated Spurious Emissions Measurements	37
7.8	Frequency Stability / Temperature Variation	42
8.0	CONCLUSION.....	47

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Approved by: Quality Manager
			Page 2 of 47



MEASUREMENT REPORT

FCC Part 22(H) & 90



Mode	Tx Frequency (MHz)	Measurement	Max. Power (W)	Max. Power (dBm)	Emission Designator	Modulation
CDMA800 (BC10)	817.9 - 823.1	Conducted	0.321	25.07	1M28F9W	CDMA
LTE Band 26	814.7 - 823.3	Conducted	0.318	25.02	1M09G7D	QPSK
LTE Band 26	814.7 - 823.3	Conducted	0.258	24.11	1M08W7D	16-QAM
LTE Band 26	814.7 - 823.3	Conducted	0.204	23.10	1M08W7D	64-QAM
LTE Band 26	815.5 - 822.5	Conducted	0.324	25.10	2M68G7D	QPSK
LTE Band 26	815.5 - 822.5	Conducted	0.251	24.00	2M68W7D	16-QAM
LTE Band 26	815.5 - 822.5	Conducted	0.205	23.11	2M69W7D	64-QAM
LTE Band 26	816.5 - 821.5	Conducted	0.331	25.20	4M48G7D	QPSK
LTE Band 26	816.5 - 821.5	Conducted	0.258	24.12	4M48W7D	16-QAM
LTE Band 26	816.5 - 821.5	Conducted	0.208	23.18	4M49W7D	64-QAM
LTE Band 26	819	Conducted	0.327	25.15	8M97G7D	QPSK
LTE Band 26	819	Conducted	0.257	24.10	9M01W7D	16-QAM
LTE Band 26	819	Conducted	0.200	23.01	8M99W7D	64-QAM
LTE Band 26	821.5	Conducted	0.326	25.13	13M5G7D	QPSK
LTE Band 26	821.5	Conducted	0.258	24.12	13M5W7D	16-QAM
LTE Band 26	821.5	Conducted	0.204	23.10	13M5W7D	64-QAM
LTE Band 26	821.5	ERP	0.049	16.93	13M5G7D	QPSK
LTE Band 26	821.5	ERP	0.040	16.04	13M5W7D	16-QAM
LTE Band 26	821.5	ERP	0.028	14.54	13M5W7D	64-QAM

EUT Overview

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 3 of 47	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 4 of 47	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFQ730TM**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 22(H) and 90(S).

Test Device Serial No.: 03429, 03304, 03312

2.2 Device Capabilities

This device contains the following capabilities:

800/850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFQ730TM	 MEASUREMENT REPORT (CERTIFICATION)		 Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 5 of 47

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Power and Radiated Spurious Emissions \$2.1053, \$90.635, \$90(S)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10 \log_{10}(\text{Power}_{\text{[Watts]}})$ specified in 90(S).

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

FCC ID: ZNFQ730TM	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 6 of 47	

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 7 of 47	

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX1	Licensed Transmitter Cable Set	6/4/2019	Annual	6/4/2020	LTX1
-	LTX5	Licensed Transmitter Cable Set	6/5/2019	Annual	6/5/2020	LTX5
Agilent	N9020A	MXA Signal Analyzer	4/20/2019	Annual	4/20/2020	US46470561
Agilent	N9038A	MXE EMI Receiver	7/17/2019	Annual	7/17/2020	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	6/12/2019	Annual	6/12/2020	MY52350166
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	5/10/2019	Annual	5/10/2020	441112
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/9/2018	Biennial	8/9/2020	135427
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	2/14/2019	Biennial	2/14/2021	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	2/22/2019	Biennial	2/22/2021	128338
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Mini-Circuits	PWR-SEN-4RMS	USB Power Sensor	4/20/2019	Annual	4/20/2020	11210140001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11403100002
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			100976
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	6/5/2019	Annual	6/5/2020	100342
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/11/2019	Annual	7/11/2020	102134
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	4/30/2018	Biennial	4/30/2020	9105-2403
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	N/A
Sunol	DRH-118	Horn Antenna (1-18GHz)	10/3/2019	Biennial	10/3/2021	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	4/19/2018	Biennial	4/19/2020	A051107

Table 5-1. Test Equipment

Notes:

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 8 of 47	

6.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission – BC10

Example: Channel 476 CDMA BC10 Mode 3rd Harmonic (2453.70MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 2453.70 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc.

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz
 W = Amplitude/Angle Modulated
 7 = Quantized/Digital Info
 D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 9 of 47	

7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFQ730TM
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): CDMA / EvDO / LTE
 Band: Band Class 10 / Band 26

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 90(S).691(a)	Conducted Band Edge / Spurious Emissions	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions except > 50 + 10 log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge (Band 26)		PASS	Sections 7.3, 7.4
2.1055 90.213	Frequency Stability	< 2.5 ppm		PASS	Section 7.8
2.1046 90.635	Conducted Power	< 100 Watts		PASS	Section 7.5
22.913(a.2)	Effective Radiated Power (Band 26)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
2.1053 90(S).691(a)	Radiated Spurious Emissions	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions except > 50 + 10 log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 4.2.

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 10 of 47	

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 11 of 47	

CDMA BC10




Plot 7-1. Occupied Bandwidth Plot (CDMA/EvDO, Ch. 476)




Plot 7-2. Occupied Bandwidth Plot (CDMA/EvDO, Ch. 684)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 12 of 47

LTE Band 26




Plot 7-3. Occupied Bandwidth Plot (LTE Band 26 – 15MHz QPSK - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26 – 15MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 13 of 47




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26 – 15MHz 64-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 26 - 10MHz QPSK - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 14 of 47




Plot 7-7. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 16-QAM - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 15 of 47




Plot 7-9. Occupied Bandwidth Plot (LTE Band 26 - 5MHz QPSK - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 16 of 47




Plot 7-11. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 64-QAM - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (LTE Band 26 - 3MHz QPSK - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 17 of 47



Plot 7-13. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 16-QAM - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 18 of 47




Plot 7-15. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-16. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 19 of 47



Plot 7-17. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 64-QAM - Full RB Configuration)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 20 of 47

7.3 Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §90(S).691(a)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW \geq 100kHz
3. VBW \geq 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 21 of 47	




Plot 7-20. Conducted Spurious Plot (CDMA/EvDO, Ch. 476)




Plot 7-21. Conducted Spurious Plot (CDMA/EvDO, Ch. 684)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 23 of 47




Plot 7-22. Conducted Spurious Plot (CDMA/EvDO, Ch. 684)




Plot 7-23. Conducted Spurious Plot (CDMA/EvDO, Ch. 684)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 24 of 47

LTE Band 26




Plot 7-24. Conducted Spurious Plot (LTE Band 26 – 10MHz QPSK Size 1, RB Offset 0- Mid Channel)



Plot 7-25. Conducted Spurious Plot (LTE Band 26 – 10MHz QPSK Size 1, RB Offset 0- Mid Channel)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 25 of 47



Plot 7-26. Conducted Spurious Plot (LTE Band 26 – 10MHz QPSK Size 1, RB Offset 0- Mid Channel)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 26 of 47

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §90(S).691(a)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by greater than 37.5 kHz is $43 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by up to and including 37.5 kHz is $50 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 27 of 47	

Test Notes

For channel edge emission, the signal analyzer's "ACP" measurement capability is used.


Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFQ730TM	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 28 of 47

CDMA BC10




Plot 7-27. Channel Edge Plot (CDMA BC10 - Ch. 476)




Plot 7-28. Channel Edge Plot (CDMA BC10 - Ch. 684)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 29 of 47

LTE Band 26




Plot 7-29. Channel Edge Plot (LTE Band 26 – 1.4MHz QPSK – Low Channel)




Plot 7-30. Channel Edge Plot (LTE Band 26 – 1.4MHz QPSK – High Channel)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 30 of 47




Plot 7-31. Channel Edge Plot (LTE Band 26 – 3.0MHz QPSK – Low Channel)



Plot 7-32. Channel Edge Plot (LTE Band 26 – 3.0MHz QPSK – High Channel)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 31 of 47




Plot 7-33. Channel Edge Plot (LTE Band 26 – 5MHz QPSK – Low Channel)




Plot 7-34. Channel Edge Plot (LTE Band 26 – 5MHz QPSK – High Channel)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 32 of 47



Plot 7-35. Channel Edge Plot (LTE Band 26 – 10MHz QPSK – Mid Channel)



Plot 7-36. Channel Edge Plot (LTE Band 26 – 15MHz QPSK – Mid Channel)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 33 of 47

7.5 Conducted Power Output Data

§2.1046 §90.635

Frequency [MHz]	BC10 [Channel]	Battery Type	Cond. PWR [dBm]	Cond. PWR [Watts]	Cond. PWR Limit [dBm]	Margin [dB]
817.90	476	Standard	25.03	0.318	50.00	-24.97
823.10	684	Standard	25.07	0.321	50.00	-24.93

Table 7-2. CDMA BC10 Conducted Power Output Data

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Cond. PWR [dBm]	Cond. PWR [Watts]	Cond. PWR Limit [dBm]	Margin [dB]
814.70	1.4	QPSK	24.59	0.288	50.00	-25.41
823.30	1.4	QPSK	25.02	0.318	50.00	-24.98
814.70	1.4	16-QAM	23.75	0.237	50.00	-26.25
823.30	1.4	16-QAM	24.11	0.258	50.00	-25.89
814.70	1.4	64-QAM	22.68	0.185	50.00	-27.32
823.30	1.4	64-QAM	23.10	0.204	50.00	-26.90
815.50	3	QPSK	24.57	0.286	50.00	-25.43
822.50	3	QPSK	25.10	0.324	50.00	-24.90
815.50	3	16-QAM	23.82	0.241	50.00	-26.18
822.50	3	16-QAM	24.00	0.251	50.00	-26.00
815.50	3	64-QAM	22.69	0.186	50.00	-27.31
822.50	3	64-QAM	23.11	0.205	50.00	-26.89
816.50	5	QPSK	24.44	0.278	50.00	-25.56
821.50	5	QPSK	25.20	0.331	50.00	-24.80
816.50	5	16-QAM	23.76	0.238	50.00	-26.24
821.50	5	16-QAM	24.12	0.258	50.00	-25.88
816.50	5	64-QAM	22.60	0.182	50.00	-27.40
821.50	5	64-QAM	23.18	0.208	50.00	-26.82
819.00	10	QPSK	25.15	0.327	50.00	-24.85
819.00	10	16-QAM	24.10	0.257	50.00	-25.90
819.00	10	64-QAM	23.01	0.200	50.00	-26.99
821.50	15	QPSK	25.13	0.326	50.00	-24.87
821.50	15	16-QAM	24.12	0.258	50.00	-25.88
821.50	15	64-QAM	23.1	0.204	50.00	-26.90

Table 7-3. LTE Band 26 Conducted Power Output Data

NOTES:

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
2. This unit was tested with its standard battery.

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 34 of 47	

7.6 Radiated Power (ERP)

§22.913(a.2) §90.542(a)(7)

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFQ730TM	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 35 of 47

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Radiated Test Setup <1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
821.50	15	QPSK	H	223	48	1 / 74	12.38	6.70	16.93	0.049	38.45	-21.52
821.50	15	16-QAM	H	223	48	1 / 74	11.49	6.70	16.04	0.040	38.45	-22.41
821.50	15	64-QAM	H	223	48	1 / 74	9.99	6.70	14.54	0.028	38.45	-23.91
821.50	15	QPSK	V	138	176	1 / 74	10.22	6.70	14.77	0.030	38.45	-23.68

Table 7-37. ERP Data (Band 26)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 36 of 47

7.7 Radiated Spurious Emissions Measurements

§2.1053 §90(S).691(a)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFQ730TM	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 37 of 47

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup < 1GHz




Figure 7-6. Test Instrument & Measurement Setup >1 GHz


FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 38 of 47

Test Notes

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. This unit was tested with its standard battery.
4. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
5. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFQ730TM	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 39 of 47

CDMA BC10



Plot 7-38. Radiated Spurious Plot (CDMA BC10)

Frequency (MHz):	817.9
Modulation:	CDMA BC10

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1635.8	H	105	38	-76.10	-0.90	30.00	-65.25	-13.00	-52.25
2453.7	H	142	219	-77.08	3.42	33.34	-61.92	-13.00	-48.92
3271.6	H	-	-	-78.48	4.64	33.16	-62.09	-13.00	-49.09
4089.5	H	-	-	-79.53	6.29	33.76	-61.50	-13.00	-48.50

Table 7-4. CDMA BC10 Radiated Spurious Data (Ch. 476)


Frequency (MHz):	823.1
Modulation:	CDMA BC10

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1646.2	H	100	45	-75.92	-0.83	30.25	-65.00	-13.00	-52.00
2469.3	H	114	41	-77.65	3.14	32.49	-62.77	-13.00	-49.77
3292.4	H	-	-	-78.54	4.45	32.91	-62.34	-13.00	-49.34
4115.5	H	-	-	-79.51	6.39	33.88	-61.37	-13.00	-48.37

Table 7-5. CDMA BC10 Radiated Spurious Data (Ch. 684)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 40 of 47

LTE Band 26



Plot 7-39. Radiated Spurious Plot (Band 26)

OPERATING FREQUENCY: 821.50 MHz
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 15.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1643.00	H	194	295	-71.80	8.91	-62.89	-49.9
2464.50	H	329	7	-67.98	9.61	-58.37	-45.4
3286.00	H	-	-	-74.05	9.56	-64.48	-51.5
4107.50	H	-	-	-74.45	10.14	-64.31	-51.3

Table 7-6. Radiated Spurious Data (LTE Band 26 – Mid Channel)

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset		Page 41 of 47

7.8 Frequency Stability / Temperature Variation

§2.1055 §90.213

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 42 of 47	

Frequency Stability / Temperature Variation
§2.1055, §90.213

OPERATING FREQUENCY: 817,900,000 Hz
 CHANNEL: 476
 REFERENCE VOLTAGE: 4.00 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.00	- 30	817,900,214	214	0.0000262
100 %		- 20	817,900,290	290	0.0000355
100 %		- 10	817,899,716	-284	-0.0000347
100 %		0	817,900,041	41	0.0000050
100 %		+ 10	817,900,100	100	0.0000122
100 %		+ 20	817,900,207	207	0.0000253
100 %		+ 30	817,899,958	-42	-0.0000051
100 %		+ 40	817,899,974	-26	-0.0000032
100 %		+ 50	817,899,980	-20	-0.0000024
BATT. ENDPOINT		2.90	+ 20	817,900,001	1

Table 7-7. CDMA BC10 Frequency Stability Data

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 43 of 47	

Frequency Stability / Temperature Variation
\$2.1055, \$90.213




Figure 7-7. CDMA BC10 Frequency Stability Chart

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 44 of 47	

Frequency Stability / Temperature Variation
§2.1055, §90.213

OPERATING FREQUENCY: 819,000,000 Hz
 CHANNEL: 26740
 REFERENCE VOLTAGE: 4.00 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.00	- 30	818,999,632	-368	-0.0000449
100 %		- 20	818,999,800	-200	-0.0000244
100 %		- 10	818,999,731	-269	-0.0000328
100 %		0	819,000,149	149	0.0000182
100 %		+ 10	818,999,905	-95	-0.0000116
100 %		+ 20	819,000,022	22	0.0000027
100 %		+ 30	818,999,890	-110	-0.0000134
100 %		+ 40	818,999,780	-220	-0.0000269
100 %		+ 50	818,999,824	-176	-0.0000215
BATT. ENDPOINT		2.90	+ 20	818,999,949	-51

Table 7-8. LTE Band 26 Frequency Stability Data

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 45 of 47	

Frequency Stability / Temperature Variation
\$2.1055, \$90.213




Table 7-9. LTE Band 26 Frequency Stability Chart

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 46 of 47

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFQ730TM** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: ZNFQ730TM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M2001130006 - 04.ZNF	Test Dates: 01/14/20 - 02/13/20	EUT Type: Portable Handset	Page 47 of 47	