

EMI TEST REPORT FCC CERTIFICATION

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Receipt: November 08, 2016

Date of Issue: December 02, 2016

Test Report No. HCT-E-1612-F001

HCT FRN: 0005866421

FCC ID :

ZNFUS215

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: Portable Handset
Model Name: LG-US215
Additional Model Name: LGUS215, US215
Date of Test: November 29, 2016 - December 01, 2016

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By



Yeong-Moo Kim
Test Engineer
EMC Team
Certification Division

Reviewed By



Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1612-F001	December 02, 2016	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	5
1.3 Test Facility	5
1.4 Calibration of Measuring Instrument	5
1.5 Tested System Details.....	6
1.6 Cable Description	7
1.7 Noise Suppression Parts on Cable. (I/O Cable)	7
2. MEASUREMENT UNCERTAINTY	8
3. DESCRIPTION OF TEST	9
3.1 Measurement of Conducted Emission.....	9
3.2 Measurement of Radiated Measurements	10
4. PRELIMINARY TEST	12
4.1 Conducted Emission Test	12
4. 2 Radiated Emission Test	12
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	13
5.1 Conducted Emission Test	13
5.2 Radiated Emission Test	20
6. LIST OF TEST EQUIPMENT	22
7. CONCLUSION	23

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFUS215
Model	LG-US215
Additional Model	LGUS215, US215
EUT Type	Portable Handset
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12) 1 850 MHz to 1 915 MHz (LTE B25) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz band)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 729 MHz to 746 MHz (LTE B12) 1 930 MHz to 1 995 MHz (LTE B25) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz band)



1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014.

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661 (July 07, 2015)
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	

1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipments, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-US215	LG	ZNFUS215	Notebook PC, Earphone
USB Cable	EAD62377927	Ningbo Broad	-	EUT, Notebook PC
USB Cable	EAD62377923	CRESYN	-	EUT, Notebook PC
USB Cable	EAD62377921	LEAGTECH	-	EUT, Notebook PC
USB Cable	EAD62377922	KSD	-	EUT, Notebook PC
Earphone	EAB62808715	Goertek	-	EUT
Notebook PC	ProBook6560b	HP	DoC	Gateway , Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	Series PPP009L-E	LITE-On Technology	-	Notebook PC
Gateway	TL-WR747N	TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	-	Gateway
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	EVO+UHS-1 microSDXC U1	SAMSUNG	-	EUT



1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)2.0
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	Both End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	± 1.82 dB ($k = 2$)
Radiated Emissions (30 MHz to 1 GHz)	± 5.06 dB ($k = 2$)
Radiated Emissions (1 GHz to 6 GHz)	± 5.0 dB ($k = 2$)
Radiated Emissions (6 GHz to 18 GHz)	± 5.4 dB ($k = 2$)



3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

3.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

4.2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
Worst Case USB Cable	KSD (EAD62377922)
Kind of Test Site	Shielded Room
Temperature	23.2 °C
Relative Humidity	26.6 %
Test Date	December 01, 2016

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	44.8	9.000	L1	9.7	21.2	66.0
0.156000	43.8	9.000	L1	9.7	21.9	65.7
0.160000	45.0	9.000	L1	9.7	20.5	65.5
0.170000	44.9	9.000	L1	9.7	20.1	65.0
0.176000	42.9	9.000	L1	9.7	21.8	64.7
0.182000	42.4	9.000	L1	9.7	22.0	64.4
1.084000	31.3	9.000	L1	9.8	24.7	56.0
4.272000	28.5	9.000	L1	9.9	27.5	56.0
4.346000	28.6	9.000	L1	9.9	27.4	56.0
4.378000	28.9	9.000	L1	9.9	27.1	56.0
4.406000	28.8	9.000	L1	9.9	27.2	56.0
4.440000	28.7	9.000	L1	9.9	27.3	56.0
9.458000	29.1	9.000	L1	10.1	30.9	60.0
9.552000	29.4	9.000	L1	10.1	30.6	60.0
9.662000	29.7	9.000	L1	10.1	30.3	60.0
9.700000	30.0	9.000	L1	10.1	30.0	60.0
9.822000	29.3	9.000	L1	10.1	30.7	60.0
9.908000	29.3	9.000	L1	10.1	30.7	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	25.9	9.000	L1	9.7	30.0	55.9
0.156000	25.8	9.000	L1	9.7	29.8	55.7
0.164000	29.6	9.000	L1	9.7	25.7	55.3
0.176000	30.5	9.000	L1	9.7	24.2	54.7
0.180000	29.4	9.000	L1	9.7	25.1	54.5
0.186000	27.3	9.000	L1	9.7	26.9	54.2
1.056000	25.5	9.000	L1	9.8	20.5	46.0
4.346000	20.4	9.000	L1	9.9	25.6	46.0
4.378000	20.6	9.000	L1	9.9	25.4	46.0
4.406000	20.1	9.000	L1	9.9	25.9	46.0
4.432000	20.2	9.000	L1	9.9	25.8	46.0
4.440000	20.2	9.000	L1	9.9	25.8	46.0
9.552000	22.7	9.000	L1	10.1	27.3	50.0
9.700000	23.0	9.000	L1	10.1	27.0	50.0
9.710000	22.8	9.000	L1	10.1	27.2	50.0
9.770000	22.5	9.000	L1	10.1	27.5	50.0
9.780000	22.7	9.000	L1	10.1	27.3	50.0
9.822000	22.3	9.000	L1	10.1	27.7	50.0



Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	45.6	9.000	N	9.7	20.4	66.0
0.158000	44.3	9.000	N	9.7	21.2	65.6
0.162000	44.0	9.000	N	9.7	21.4	65.4
0.166000	43.8	9.000	N	9.7	21.4	65.2
0.180000	43.4	9.000	N	9.7	21.1	64.5
0.186000	42.7	9.000	N	9.7	21.5	64.2
1.072000	31.6	9.000	N	9.7	24.4	56.0
2.738000	31.1	9.000	N	9.8	24.9	56.0
2.948000	31.6	9.000	N	9.8	24.4	56.0
3.074000	31.2	9.000	N	9.8	24.8	56.0
3.108000	31.0	9.000	N	9.8	25.0	56.0
3.160000	30.8	9.000	N	9.8	25.2	56.0
9.290000	34.9	9.000	N	10.0	25.1	60.0
9.304000	34.9	9.000	N	10.0	25.1	60.0
9.342000	35.2	9.000	N	10.0	24.8	60.0
9.408000	35.1	9.000	N	10.0	24.9	60.0
9.640000	34.4	9.000	N	10.0	25.6	60.0
9.656000	34.6	9.000	N	10.0	25.4	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	25.1	9.000	N	9.7	30.9	56.0
0.158000	22.9	9.000	N	9.7	32.7	55.6
0.170000	29.1	9.000	N	9.7	25.8	55.0
0.180000	31.4	9.000	N	9.7	23.1	54.5
0.186000	30.4	9.000	N	9.7	23.8	54.2
0.192000	28.4	9.000	N	9.7	25.5	53.9
1.054000	25.0	9.000	N	9.7	21.0	46.0
1.092000	25.1	9.000	N	9.7	20.9	46.0
2.958000	23.4	9.000	N	9.8	22.6	46.0
3.062000	23.1	9.000	N	9.8	22.9	46.0
3.108000	22.8	9.000	N	9.8	23.2	46.0
3.160000	22.7	9.000	N	9.8	23.3	46.0
9.268000	27.3	9.000	N	10.0	22.7	50.0
9.290000	27.4	9.000	N	10.0	22.6	50.0
9.304000	27.4	9.000	N	10.0	22.6	50.0
9.342000	27.5	9.000	N	10.0	22.5	50.0
9.360000	27.8	9.000	N	10.0	22.2	50.0
9.408000	27.5	9.000	N	10.0	22.5	50.0



5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
Worst Case USB Cable	KSD (EAD62377922)
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.2 °C
Relative Humidity	26.5 %
Test Date	November 29, 2016

Frequency (MHz)	Quasi Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
30.154867	23.2	144.0	V	75.0	21.3	16.8	40.0
54.116000	31.6	100.0	V	97.0	22.8	8.4	40.0
58.808800	34.4	350.0	H	152.0	22.5	5.6	40.0
63.502400	35.8	400.0	H	152.0	22.0	4.2	40.0
68.200000	30.4	400.0	H	161.0	21.4	9.6	40.0
265.573600	30.2	100.0	H	297.0	22.6	15.8	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	2 480 MHz
Upper Frequency of Measurement Range	1 GHz to 12.4 GHz
Worst Case USB Cable	KSD (EAD62377922)
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.2 °C
Relative Humidity	26.5 %
Test Date	November 30, 2016

Frequency (MHz)	Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1000.272500	47.1	362.4	V	26.0	-13.9	26.9	74.0
1399.990000	51.2	362.2	V	195.0	-12.8	22.8	74.0
1543.900000	46.8	355.7	V	26.0	-12.5	27.2	74.0
1999.305000	54.1	100.0	V	206.0	-12.2	19.9	74.0
2666.135000	46.0	111.4	V	156.0	-9.1	28.0	74.0
5974.745000	44.1	311.6	V	155.0	-2.4	29.9	74.0

Frequency (MHz)	CAverage (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1000.272500	39.9	362.4	V	26.0	-13.9	14.1	54.0
1399.990000	48.0	362.2	V	195.0	-12.8	6.0	54.0
1543.900000	22.2	355.7	V	26.0	-12.5	31.8	54.0
1999.305000	29.0	100.0	V	206.0	-12.2	25.0	54.0
2666.135000	23.0	111.4	V	156.0	-9.1	31.0	54.0
5974.745000	28.1	311.6	V	155.0	-2.4	25.9	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	12.28.2015
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	06.09.2016
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	12.28.2015
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	03.30.2016
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESIB26	100298	1 year	02.11.2016
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9168	255	2 year	04.15.2015
<input checked="" type="checkbox"/> 6dB Attenuator	HP	8491A	24257	2 year	04.15.2015
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.27.2016
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	03.30.2016
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESIB26	100298	1 year	02.11.2016
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
<input type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4000-XP-ET	48709515	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.04.2016
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.07.2016
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170541	2 year	09.03.2015
<input type="checkbox"/> Power Amplifier	CERNEX	CBL18265035	22966	1 year	07.11.2016
<input type="checkbox"/> Power Amplifier	CERNEX	CBL26405040	19660	1 year	07.15.2016
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	1300	2 year	08.25.2016
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.27.2016
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-



7. CONCLUSION

The data collected shows that the **EUT Type: Portable Handset, Model: LG-US215, FCC ID: ZNFUS215** complies with §15.107 and §15.109 of the FCC rules.