



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

http://www.pctest.com



MEASUREMENT REPORT GSM / GPRS / CDMA / WCDMA

Applicant Name:

LG Electronics USA, Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

6/20/2018-8/2/2018

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1806200130-02-R1.ZNF

FCC ID:

ZNFV405UA

APPLICANT:

LG Electronics USA, Inc.

Application Type:

Certification

Model:

LM-V405UA

Additional Model(s):

LMV405UA, LM-V405TA, LMV405TA, LM-V405MA, LMV405MA,
LM-V405QA, LMV405QA, LM-V405QA5, LMV405QA5, LM-V405QA6,
LMV405QA6

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

22, 24, & 27


Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01,
KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1806200130-02-R1.ZNF) supersedes and replaces the previously issued test report (S/N: 1M1806200130-02-R1.ZNF) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President




FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 1 of 106	

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Cellular - Base Frequency Blocks	6
3.3	Cellular - Mobile Frequency Blocks	6
3.4	PCS - Base Frequency Blocks	6
3.5	PCS - Mobile Frequency Blocks	7
3.6	AWS - Base Frequency Blocks	7
3.7	AWS - Mobile Frequency Blocks	7
3.8	Radiated Measurements	8
4.0	MEASUREMENT UNCERTAINTY	9
5.0	TEST EQUIPMENT CALIBRATION DATA	10
6.0	SAMPLE CALCULATIONS	11
7.0	TEST RESULTS	12
7.1	Summary	12
7.2	Occupied Bandwidth	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal	19
7.4	Band Edge Emissions at Antenna Terminal	55
7.5	Peak-Average Ratio	67
7.6	Radiated Power (ERP/EIRP)	70
7.7	Radiated Spurious Emissions Measurements	75
7.8	Frequency Stability / Temperature Variation	91
8.0	CONCLUSION	106

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Approved by: Quality Manager
			Page 2 of 106



MEASUREMENT REPORT

GSM / GPRS / CDMA / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
GPRS850	22H	824.2 - 848.8	0.622	27.94	1.021	30.09	242KGXW
EDGE850	22H	824.2 - 848.8	0.176	22.46	0.289	24.61	244KG7W
CDMA850	22H	824.70 - 848.31	0.100	20.01	0.164	22.16	1M28F9W
WCDMA850	22H	826.4 - 846.6	0.080	19.03	0.131	21.18	4M16F9W
WCDMA1700	27	1712.4 - 1752.6			0.174	22.40	4M14F9W
GPRS1900	24E	1850.2 - 1909.8			1.112	30.46	241KGXW
EDGE1900	24E	1850.2 - 1909.8			0.380	25.80	243KG7W
CDMA1900	24E	1851.25 - 1908.75			0.273	24.36	1M28F9W
WCDMA1900	24E	1852.4 - 1907.6			0.328	25.16	4M13F9W

EUT Overview

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 3 of 106	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 4 of 106	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFV405UA**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

Test Device Serial No.: 00799, 00823, 00971

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ac WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 5 of 106	


3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks




BLOCK 1: 869 – 880 MHz (A* Low + A)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks




BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)


BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)


FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 6 of 106	

3.5 PCS - Mobile Frequency Blocks




- BLOCK 1: 1850 – 1865 MHz (A)
- BLOCK 2: 1865 – 1870 MHz (D)
- BLOCK 3: 1870 – 1885 MHz (B)
- BLOCK 4: 1885 – 1890 MHz (E)
- BLOCK 5: 1890 – 1895 MHz (F)
- BLOCK 6: 1895 – 1910 MHz (C)

3.6 AWS - Base Frequency Blocks



- BLOCK 1: 2110 – 2120 MHz (A)
- BLOCK 2: 2120 – 2130 MHz (B)
- BLOCK 3: 2130 – 2135 MHz (C)
- BLOCK 4: 2135 – 2140 MHz (D)
- BLOCK 5: 2140 – 2145 MHz (E)
- BLOCK 6: 2145 – 2155 MHz (F)

3.7 AWS - Mobile Frequency Blocks



- BLOCK 1: 1710 – 1720 MHz (A)
- BLOCK 2: 1720 – 1730 MHz (B)
- BLOCK 3: 1730 – 1735 MHz (C)
- BLOCK 4: 1735 – 1740 MHz (D)
- BLOCK 5: 1740 – 1745 MHz (E)
- BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 7 of 106

3.8 Radiated Measurements

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [dBm] = P_g [dBm] - \text{cable loss} [dB] + \text{antenna gain} [dBd/dBi]$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g [dBm] - \text{cable loss} [dB]$.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 8 of 106	

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 9 of 106

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx3	Licensed Transmitter Cable Set	1/23/2018	Annual	7/23/2018	LTx3
Agilent	N9020A	MXA Signal Analyzer	1/24/2018	Annual	1/24/2019	US46470561
Agilent	N9038A	MXE EMI Receiver	6/11/2018	Annual	6/11/2019	MY51210133
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/23/2016	Biennial	8/23/2018	135427
Espec	ESX-2CA	Environmental Chamber	3/28/2018	Annual	3/28/2019	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	12/1/2016	Biennial	12/1/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/28/2018	Biennial	3/28/2020	128337
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/30/2018	Annual	3/30/2019	11401010036
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Mini-Circuits	PWR-SEN-4RMS	USB Power Sensor	3/30/2018	Annual	3/30/2019	11210140001
Mini-Circuits	TVA-11-422	RF Power Amp	N/A			QA1303002
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11403100002
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			107826
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	1/24/2018	Annual	7/24/2018	100040
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/31/2017	Annual	7/31/2018	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/11/2017	Annual	8/11/2018	103200
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/2/2018	Annual	7/2/2019	102131
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	6/18/2018	Annual	6/18/2019	102134
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	4/19/2018	Biennial	4/19/2020	A051107

Table 5-1. Test Equipment

Notes:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 10 of 106	

6.0 SAMPLE CALCULATIONS

GPRS Emission Designator

Emission Designator = 250KGXW

GPRS BW = 250 kHz
 G = Phase Modulation
 X = Cases not otherwise covered
 W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 W = Combination (Audio/Data)

CDMA Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 11 of 106

7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFV405UA
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM / GPRS / CDMA / WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	RSS-Gen (4.6.1) RSS-133(2.3) RSS-139(2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Conducted Band Edge / Spurious Emissions	> 43 + log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	RSS-132(5.4) RSS-133(4.1) RSS-139(4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a)(5)	RSS-132(5.4)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	RSS-133(6.4)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d)(4)	RSS-139(6.5)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Radiated Spurious Emissions	> 43 + log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 12 of 106	

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 13 of 106	




Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 14 of 106




Plot 7-3. Occupied Bandwidth Plot (PCS GPRS Mode)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 15 of 106




Plot 7-5. Occupied Bandwidth Plot (Cellular CDMA Mode)




Plot 7-6. Occupied Bandwidth Plot (PCS CDMA Mode)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 16 of 106




Plot 7-7. Occupied Bandwidth Plot (Cellular WCDMA Mode)



Plot 7-8. Occupied Bandwidth Plot (AWS WCDMA Mode)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 17 of 106



Plot 7-9. Occupied Bandwidth Plot (PCS WCDMA Mode)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 18 of 106

7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Per 24.238(b), 27.53(h)(3), and RSS-133(6.5), RSS-139(6.5), compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 19 of 106

Cellular GPRS Mode




Plot 7-10. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 20 of 106




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-13. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 21 of 106




Plot 7-14. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)




Plot 7-15. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 22 of 106




Plot 7-16. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)



Plot 7-17. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)


FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 23 of 106




Plot 7-18. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 24 of 106

PCS GPRS Mode




Plot 7-19. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-20. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 25 of 106




Plot 7-21. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-22. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 26 of 106




Plot 7-23. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)




Plot 7-24. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 27 of 106




Plot 7-25. Conducted Spurious Plot (PCS GPRS Mode - High Channel)



Plot 7-26. Conducted Spurious Plot (PCS GPRS Mode - High Channel)


FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 28 of 106




Plot 7-27. Conducted Spurious Plot (PCS GPRS Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 29 of 106

Cellular CDMA Mode




Plot 7-28. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)




Plot 7-29. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 30 of 106




Plot 7-30. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)




Plot 7-31. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 31 of 106




Plot 7-32. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)




Plot 7-33. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 32 of 106




Plot 7-34. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)



Plot 7-35. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)


FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 33 of 106




Plot 7-36. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 34 of 106

PCS CDMA Mode




Plot 7-37. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)




Plot 7-38. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 35 of 106




Plot 7-39. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)




Plot 7-40. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 36 of 106




Plot 7-41. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)




Plot 7-42. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 37 of 106




Plot 7-43. Conducted Spurious Plot (PCS CDMA Mode - High Channel)



Plot 7-44. Conducted Spurious Plot (PCS CDMA Mode - High Channel)


FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 38 of 106




Plot 7-45. Conducted Spurious Plot (PCS CDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 39 of 106

Cellular WCDMA Mode




Plot 7-46. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-47. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 40 of 106




Plot 7-48. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-49. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 41 of 106




Plot 7-50. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)




Plot 7-51. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 42 of 106




Plot 7-52. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)



Plot 7-53. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)


FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 43 of 106




Plot 7-54. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 44 of 106

AWS WCDMA Mode




Plot 7-55. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)




Plot 7-56. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 45 of 106




Plot 7-57. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)




Plot 7-58. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 46 of 106




Plot 7-59. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)




Plot 7-60. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 47 of 106




Plot 7-61. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)



Plot 7-62. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)


FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 48 of 106




Plot 7-63. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 49 of 106

PCS WCDMA Mode




Plot 7-64. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-65. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 50 of 106




Plot 7-66. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-67. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 51 of 106




Plot 7-68. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)




Plot 7-69. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 52 of 106




Plot 7-70. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)



Plot 7-71. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 53 of 106



Plot 7-72. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 54 of 106

7.4 Band Edge Emissions at Antenna Terminal

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

Test Notes


Per 22.917(b), 24.238(b), 27.53(h)(3), and RSS-132(5.5), RSS-133(6.5), RSS-139(6.5), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 55 of 106

Cellular GPRS Mode




Plot 7-73. Band Edge Plot (Cellular GPRS Mode - Low Channel)




Plot 7-74. Band Edge Plot (Cellular GPRS Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 56 of 106

PCS GPRS Mode




Plot 7-75. Band Edge Plot (PCS GPRS Mode - Low Channel)




Plot 7-76. 4MHz Span Plot (PCS GPRS Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 57 of 106




Plot 7-77. Band Edge Plot (PCS GPRS Mode - High Channel)




Plot 7-78. 4MHz Span Plot (PCS GPRS Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 58 of 106

Cellular CDMA Mode




Plot 7-79. Band Edge Plot (Cellular CDMA Mode - Low Channel)




Plot 7-80. Band Edge Plot (Cellular CDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 59 of 106

PCS CDMA Mode



Plot 7-81. Band Edge Plot (PCS CDMA Mode - Low Channel)




Plot 7-82. 4MHz Span Plot (PCS CDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 60 of 106

Cellular WCDMA Mode




Plot 7-85. Band Edge Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-86. Band Edge Plot (Cellular WCDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 62 of 106

AWS WCDMA Mode



Plot 7-87. Band Edge Plot (AWS WCDMA Mode - Low Channel)




Plot 7-88. 4MHz Span Plot (AWS WCDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 63 of 106



Plot 7-89. Band Edge Plot (AWS WCDMA Mode - High Channel)




Plot 7-90. 4MHz Span Plot (AWS WCDMA Mode - High Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 64 of 106

PCS WCDMA Mode



Plot 7-91. Band Edge Plot (PCS WCDMA Mode - Low Channel)



Plot 7-92. 4MHz Span Plot (PCS WCDMA Mode - Low Channel)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 65 of 106

7.5 Peak-Average Ratio

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 67 of 106




Plot 7-95. Peak-Average Ratio Plot (PCS GPRS Mode)




Plot 7-96. Peak-Average Ratio Plot (PCS CDMA Mode)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 68 of 106



Plot 7-97. Peak-Average Ratio Plot (AWS WCDMA Mode)



Plot 7-98. Peak-Average Ratio Plot (PCS WCDMA Mode)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 69 of 106

7.6 Radiated Power (ERP/EIRP)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”. Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 70 of 106	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 71 of 106	

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: ZNFV405UA	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 72 of 106

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.20	GPRS850	H	150	8	27.87	1.50	27.22	0.527	38.45	-11.23	29.37	0.864	40.61	-11.24
836.60	GPRS850	H	150	80	28.59	1.50	27.94	0.622	38.45	-10.51	30.09	1.021	40.61	-10.52
848.80	GPRS850	H	150	355	27.35	1.50	26.70	0.468	38.45	-11.75	28.85	0.768	40.61	-11.76
836.60	GPRS850	V	150	238	27.37	1.50	26.72	0.470	38.45	-11.73	28.87	0.771	40.61	-11.74
836.60	EDGE850	H	150	80	23.11	1.50	22.46	0.176	38.45	-15.99	24.61	0.289	40.61	-16.00
836.60	GPRS850 (WCP)	H	150	238	26.41	1.50	25.76	0.377	38.45	-12.69	27.91	0.618	40.61	-12.70

Table 7-2. ERP/EIRP (Cellular GPRS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
824.70	CDMA850	H	150	96	20.49	1.50	19.84	38.45	-18.61	21.99	40.61	-18.62
836.52	CDMA850	H	150	89	20.66	1.50	20.01	38.45	-18.44	22.16	40.61	-18.45
848.31	CDMA850	H	150	89	19.26	1.50	18.61	38.45	-19.84	20.76	40.61	-19.85
836.52	CDMA850	V	150	27	18.02	1.50	17.37	38.45	-21.08	19.52	40.61	-21.09
836.52	CDMA850 (WCP)	H	150	346	20.19	1.50	19.54	38.45	-18.91	21.69	40.61	-18.92

Table 7-3. ERP/EIRP (Cellular CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850(WCP)	H	150	353	19.02	1.50	18.37	0.069	38.45	-20.08	20.52	0.113	40.61	-20.09
836.60	WCDMA850(WCP)	H	150	355	19.50	1.50	18.85	0.077	38.45	-19.60	21.00	0.126	40.61	-19.61
846.60	WCDMA850(WCP)	H	150	357	19.68	1.50	19.03	0.080	38.45	-19.42	21.18	0.131	40.61	-19.43
846.60	WCDMA850(WCP)	V	150	238	19.19	1.50	18.54	0.071	38.45	-19.91	20.69	0.117	40.61	-19.92
846.60	WCDMA850	H	150	103	17.93	1.50	17.28	0.053	38.45	-21.17	19.43	0.088	40.61	-21.18

Table 7-4. ERP/EIRP (Cellular WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700 (WCP)	H	150	345	16.45	5.55	22.00	0.158	30.00	-8.00
1732.60	WCDMA1700 (WCP)	H	150	346	16.99	5.41	22.40	0.174	30.00	-7.60
1752.60	WCDMA1700 (WCP)	H	150	349	17.07	5.27	22.34	0.171	30.00	-7.66
1732.60	WCDMA1700 (WCP)	V	150	3245	15.19	5.41	20.60	0.115	30.00	-9.40
1732.60	WCDMA1700	H	150	359	16.22	5.41	21.63	0.145	30.00	-8.37

Table 7-5. EIRP (AWS WCDMA)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 73 of 106	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	H	150	351	25.64	4.82	30.46	1.112	33.01	-2.55
1880.00	GPRS1900	H	150	352	24.53	4.74	29.27	0.845	33.01	-3.74
1909.80	GPRS1900	H	150	321	24.41	4.68	29.09	0.810	33.01	-3.92
1850.20	GPRS1900	V	150	237	23.80	4.82	28.62	0.728	33.01	-4.39
1850.20	EDGE1900	H	150	351	20.98	4.82	25.80	0.380	33.01	-7.21
1850.20	GPRS1900 (WCP)	H	150	239	22.08	4.82	26.90	0.490	33.01	-6.11

Table 7-6. EIRP (PCS GPRS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	V	150	356	19.14	4.82	23.96	0.249	33.01	-9.05
1880.00	CDMA1900	V	150	315	19.62	4.74	24.36	0.273	33.01	-8.65
1908.75	CDMA1900	V	150	359	17.94	4.68	22.62	0.183	33.01	-10.39
1880.00	CDMA1900	H	150	0	19.23	4.74	23.97	0.249	33.01	-9.04
1880.00	CDMA1900 (WCP)	V	150	358	19.59	4.74	24.33	0.271	33.01	-8.68

Table 7-7. EIRP (PCS CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900 (WCP)	H	150	357	18.79	4.81	23.60	0.229	33.01	-9.41
1880.00	WCDMA1900 (WCP)	H	150	346	20.42	4.74	25.16	0.328	33.01	-7.85
1907.60	WCDMA1900 (WCP)	H	150	352	17.43	4.68	22.11	0.163	33.01	-10.90
1880.00	WCDMA1900 (WCP)	V	150	238	16.86	4.74	21.60	0.145	33.01	-11.41
1880.00	WCDMA1900	H	150	355	19.46	4.74	24.20	0.263	33.01	-8.81

Table 7-8. EIRP (PCS WCDMA)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 74 of 106	

7.7 Radiated Spurious Emissions Measurements

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points \geq 2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFV405UA	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 75 of 106

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 6) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 7) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 8) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 76 of 106

Cellular GPRS Mode

OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1648.40	H	256	209	-54.35	9.01	-45.34	-32.3
2472.60	H	141	252	-49.66	9.12	-40.54	-27.5
3296.80	H	266	191	-67.69	9.37	-58.32	-45.3
4121.00	H	326	17	-69.18	9.83	-59.34	-46.3
4945.20	H	-	-	-72.44	11.24	-61.20	-48.2
5769.40	H	-	-	-71.81	11.36	-60.45	-47.4

Table 7-9. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	196	354	-54.12	8.85	-45.27	-32.3
2509.80	H	102	253	-47.86	9.17	-38.69	-25.7
3346.40	H	-	-	-69.45	9.36	-60.09	-47.1
4183.00	H	107	45	-66.02	10.19	-55.82	-42.8
5019.60	H	-	-	-72.16	11.09	-61.06	-48.1
5856.20	H	-	-	-71.17	11.32	-59.84	-46.8

Table 7-10. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 77 of 106	

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	149	134	-52.50	8.67	-43.83	-30.8
2546.40	H	140	244	-53.17	9.28	-43.89	-30.9
3395.20	H	229	148	-67.03	9.46	-57.57	-44.6
4244.00	H	111	39	-67.02	10.48	-56.54	-43.5
5092.80	H	-	-	-70.60	10.88	-59.71	-46.7
5941.60	H	-	-	-70.64	11.23	-59.41	-46.4

Table 7-11. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	149	6	-54.52	8.85	-45.67	-32.7
2509.80	H	243	252	-54.21	9.17	-45.04	-32.0
3346.40	H	-	-	-69.79	9.36	-60.43	-47.4
4183.00	H	132	8	-64.80	10.19	-54.60	-41.6
5019.60	H	-	-	-72.20	11.09	-61.10	-48.1
5856.20	H	-	-	-70.82	11.32	-59.49	-46.5

Table 7-12. Radiated Spurious Data with WCP (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 78 of 106	

Cellular CDMA Mode

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1649.40	H	123	1	-73.26	9.30	-63.95	-51.0
2474.10	H	342	132	-67.29	8.64	-58.66	-45.7
3298.80	H	-	-	-76.01	8.24	-67.77	-54.8

Table 7-13. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.04	H	11	334	-75.97	9.45	-66.52	-53.5
2509.56	H	384	135	-68.49	8.50	-59.99	-47.0
3346.08	H	-	-	-74.26	8.71	-65.55	-52.5

Table 7-14. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 79 of 106

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1696.62	H	203	21	-76.74	9.59	-67.14	-54.1
2544.93	H	153	55	-71.41	8.42	-62.99	-50.0
3393.24	H	-	-	-75.37	9.03	-66.35	-53.3

Table 7-15. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.04	H	158	197	-77.10	9.45	-67.65	-54.6
2509.56	H	128	330	-69.60	8.50	-61.10	-48.1
3346.08	H	-	-	-74.41	8.71	-65.70	-52.7

Table 7-16. Radiated Spurious Data with WCP (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 80 of 106

Cellular WCDMA Mode

OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	212	69	-72.38	5.80	-66.58	-53.6
2479.20	H	392	275	-70.62	5.73	-64.89	-51.9
3305.60	H	-	-	-73.47	7.86	-65.61	-52.6

Table 7-17. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 4183
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	265	74	-70.00	5.73	-64.28	-51.3
2509.80	H	138	202	-69.73	5.77	-63.96	-51.0
3346.40	H	-	-	-73.46	7.91	-65.56	-52.6

Table 7-18. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 81 of 106	

OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	145	70	-70.19	5.66	-64.53	-51.5
2539.80	H	130	205	-68.43	5.88	-62.55	-49.6
3386.40	H	-	-	-74.21	7.96	-66.26	-53.3

Table 7-19. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	198	162	-73.22	5.66	-67.56	-54.6
2539.80	H	189	316	-68.47	5.88	-62.59	-49.6
3386.40	H	-	-	-74.27	7.96	-66.32	-53.3

Table 7-20. Radiated Spurious Data with WCP (Cellular WCDMA Mode – Ch. 4233)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 82 of 106

AWS WCDMA Mode

OPERATING FREQUENCY: 1712.40 MHz
 CHANNEL: 1312
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3424.80	H	112	219	-51.28	8.11	-43.17	-30.2
5137.20	H	112	227	-39.04	10.24	-28.80	-15.8
6849.60	H	384	130	-48.29	11.36	-36.93	-23.9
8562.00	H	363	202	-47.74	13.06	-34.69	-21.7
10274.40	H	112	186	-49.29	13.11	-36.18	-23.2
11986.80	H	114	183	-62.55	13.14	-49.42	-36.4

Table 7-21. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)

OPERATING FREQUENCY: 1732.60 MHz
 CHANNEL: 1413
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3465.20	H	114	318	-51.00	8.33	-42.67	-29.7
5197.80	H	114	226	-39.31	10.27	-29.03	-16.0
6930.40	H	363	231	-45.67	11.42	-34.25	-21.2
8663.00	H	396	210	-47.16	13.09	-34.07	-21.1
10395.60	H	118	184	-47.68	13.12	-34.56	-21.6
12128.20	H	118	177	-61.68	13.14	-48.54	-35.5

Table 7-22. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1413)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 83 of 106

OPERATING FREQUENCY: 1752.60 MHz
 CHANNEL: 1513
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3505.20	H	260	200	-54.13	8.52	-45.62	-32.6
5257.80	H	115	296	-39.76	10.29	-29.46	-16.5
7010.40	H	372	292	-46.01	11.50	-34.51	-21.5
8763.00	H	400	367	-49.19	13.12	-36.07	-23.1
10515.60	H	111	243	-47.04	13.15	-33.89	-20.9
12268.20	H	113	242	-59.81	13.21	-46.60	-33.6

Table 7-23. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)

OPERATING FREQUENCY: 1732.60 MHz
 CHANNEL: 1413
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3465.20	H	113	92	-54.92	8.33	-46.59	-33.6
5197.80	H	123	280	-40.70	10.27	-30.42	-17.4
6930.40	H	112	252	-48.56	11.42	-37.14	-24.1
8663.00	H	135	228	-51.11	13.09	-38.02	-25.0
10395.60	H	118	203	-54.49	13.12	-41.37	-28.4
12128.20	H	343	285	-63.35	13.14	-50.21	-37.2

Table 7-24. Radiated Spurious Data with WCP (AWS WCDMA Mode – Ch. 1413)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 84 of 106

PCS GPRS Mode

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	H	400	39	-35.14	8.30	-26.84	-13.8
5550.60	H	111	315	-39.81	10.52	-29.29	-16.3
7400.80	H	114	10	-32.26	11.91	-20.35	-7.4
9251.00	H	113	2	-36.23	13.41	-22.82	-9.8
11101.20	H	343	323	-38.87	13.37	-25.50	-12.5
12951.40	H	111	43	-44.10	13.36	-30.74	-17.7
14801.60	H	113	335	-52.91	14.05	-38.86	-25.9

Table 7-25. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	400	39	-34.15	9.37	-24.79	-11.8
5640.00	H	111	315	-36.43	11.17	-25.26	-12.3
7520.00	H	114	10	-31.79	11.11	-20.68	-7.7
9400.00	H	113	2	-34.73	11.57	-23.16	-10.2
11280.00	H	343	323	-38.05	12.72	-25.33	-12.3
13160.00	H	111	43	-44.00	13.15	-30.86	-17.9
15040.00	H	113	335	-52.99	13.52	-39.47	-26.5

Table 7-26. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 85 of 106

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3819.60	H	400	39	-32.62	9.30	-23.32	-10.3
5729.40	H	111	315	-34.27	11.39	-22.88	-9.9
7639.20	H	114	10	-32.62	11.33	-21.28	-8.3
9549.00	H	113	2	-34.70	11.79	-22.92	-9.9
11458.80	H	343	323	-39.66	12.82	-26.85	-13.8
13368.60	H	111	43	-43.70	12.78	-30.91	-17.9
15278.40	H	113	335	-55.71	14.90	-40.82	-27.8

Table 7-27. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	H	120	152	-36.74	8.30	-28.44	-15.4
5550.60	H	112	37	-34.50	10.52	-23.98	-11.0
7400.80	H	117	80	-35.90	11.91	-23.99	-11.0
9251.00	H	361	355	-38.70	13.41	-25.29	-12.3
11101.20	H	113	59	-44.84	13.37	-31.47	-18.5
12951.40	H	119	80	-53.16	13.36	-39.80	-26.8
14801.60	H	321	65	-53.89	14.05	-39.84	-26.8

Table 7-28. Radiated Spurious Data with WCP (PCS GPRS Mode – Ch. 512)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 86 of 106

PCS CDMA Mode

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3702.50	H	130	34	-45.58	8.31	-37.28	-24.3
5553.75	H	115	32	-42.08	10.53	-31.55	-18.5
7405.00	H	124	11	-39.77	11.92	-27.86	-14.9
9256.25	H	130	10	-44.87	13.41	-31.47	-18.5
11107.50	H	111	355	-48.07	13.37	-34.70	-21.7
12958.75	H	113	43	-55.28	13.37	-41.91	-28.9

Table 7-29. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 600
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	129	40	-44.15	8.46	-35.70	-22.7
5640.00	H	114	34	-42.14	10.60	-31.54	-18.5
7520.00	H	146	8	-41.58	12.11	-29.47	-16.5
9400.00	H	114	3	-45.23	13.35	-31.88	-18.9
11280.00	H	118	359	-49.36	13.43	-35.93	-22.9
13160.00	H	114	43	-55.59	13.75	-41.85	-28.8

Table 7-30. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 87 of 106

OPERATING FREQUENCY: 1908.75 MHz
 CHANNEL: 1175
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3817.50	H	122	30	-43.10	8.56	-34.54	-21.5
5726.25	H	327	31	-41.79	10.64	-31.15	-18.1
7635.00	H	119	358	-45.26	12.19	-33.07	-20.1
9543.75	H	114	1	-45.39	13.30	-32.10	-19.1
11452.50	H	112	359	-49.57	13.46	-36.11	-23.1
13361.25	H	114	41	-57.61	13.83	-43.78	-30.8

Table 7-31. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 600
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	132	345	-45.15	8.46	-36.70	-23.7
5640.00	H	112	234	-39.15	10.60	-28.55	-15.5
7520.00	H	129	325	-50.82	12.11	-38.71	-25.7
9400.00	H	385	139	-47.89	13.35	-34.54	-21.5
11280.00	H	319	174	-52.53	13.43	-39.10	-26.1
13160.00	H	113	205	-62.64	13.75	-48.90	-35.9

Table 7-32. Radiated Spurious Data with WCP (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 88 of 106

PCS WCDMA Mode

OPERATING FREQUENCY: 1852.40 MHz
 CHANNEL: 9262
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3704.80	H	113	207	-47.03	8.31	-38.72	-25.7
5557.20	H	122	221	-47.22	10.54	-36.68	-23.7
7409.60	H	130	205	-48.99	11.92	-37.07	-24.1
9262.00	H	113	191	-47.04	13.41	-33.64	-20.6
11114.40	H	115	183	-54.38	13.38	-41.00	-28.0
12966.80	H	113	223	-59.28	13.39	-45.89	-32.9

Table 7-33. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	136	219	-43.62	8.46	-35.17	-22.2
5640.00	H	130	209	-46.93	10.60	-36.33	-23.3
7520.00	H	333	198	-51.90	12.11	-39.79	-26.8
9400.00	H	111	188	-47.12	13.35	-33.77	-20.8
11280.00	H	114	181	-55.95	13.43	-42.52	-29.5
13160.00	H	111	223	-60.59	13.75	-46.85	-33.8

Table 7-34. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 89 of 106

OPERATING FREQUENCY: 1907.60 MHz
 CHANNEL: 9538
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3815.20	H	131	215	-42.40	8.56	-33.84	-20.8
5722.80	H	122	137	-43.73	10.63	-33.10	-20.1
7630.40	H	340	192	-55.07	12.18	-42.89	-29.9
9538.00	H	112	186	-48.20	13.29	-34.90	-21.9
11445.60	H	113	193	-60.07	13.47	-46.60	-33.6
13353.20	H	114	223	-61.34	13.83	-47.51	-34.5

Table 7-35. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	141	25	-42.93	8.46	-34.48	-21.5
5640.00	H	129	310	-46.23	10.60	-35.63	-22.6
7520.00	H	121	120	-61.41	12.11	-49.30	-36.3
9400.00	H	394	197	-54.05	13.35	-40.70	-27.7
11280.00	H	308	212	-62.53	13.43	-49.10	-36.1
13160.00	H	114	175	-66.42	13.75	-52.68	-39.7

Table 7-36. Radiated Spurious Data with WCP (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 90 of 106

7.8 Frequency Stability / Temperature Variation

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, RSS-132, and RSS-133, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24, Part 27, and RSS-139, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 91 of 106	

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 190
 REFERENCE VOLTAGE: 4.20 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.20	+ 20 (Ref)	836,600,063	63	0.0000075
100 %		- 30	836,599,848	-152	-0.0000182
100 %		- 20	836,600,092	92	0.0000110
100 %		- 10	836,600,168	168	0.0000201
100 %		0	836,599,879	-121	-0.0000145
100 %		+ 10	836,599,655	-345	-0.0000412
100 %		+ 20	836,600,035	35	0.0000042
100 %		+ 30	836,600,078	78	0.0000093
100 %		+ 40	836,600,006	6	0.0000007
100 %		+ 50	836,600,381	381	0.0000455
BATT. ENDPOINT	3.54	+ 20	836,599,903	-97	-0.0000116

Table 7-37. Frequency Stability Data (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 92 of 106	

Frequency Stability / Temperature Variation




Figure 7-8. Frequency Stability Graph (Cellular GPRS Mode – Ch. 190)

<p>FCC ID: ZNFV405UA</p>		<p>MEASUREMENT REPORT (CERTIFICATION)</p>		<p>Approved by: Quality Manager</p>
<p>Test Report S/N: 1M1806200130-02-R1.ZNF</p>	<p>Test Dates: 6/20/2018-8/2/2018</p>	<p>EUT Type: Portable Handset</p>	<p>Page 93 of 106</p>	

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 836,520,000 Hz
 CHANNEL: 384
 REFERENCE VOLTAGE: 4.20 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.20	+ 20 (Ref)	836,519,952	-48	-0.0000057
100 %		- 30	836,519,965	-35	-0.0000042
100 %		- 20	836,520,148	148	0.0000177
100 %		- 10	836,520,350	350	0.0000418
100 %		0	836,520,018	18	0.0000022
100 %		+ 10	836,520,235	235	0.0000281
100 %		+ 20	836,519,804	-196	-0.0000234
100 %		+ 30	836,520,155	155	0.0000185
100 %		+ 40	836,520,189	189	0.0000226
100 %		+ 50	836,520,060	60	0.0000072
BATT. ENDPOINT	3.54	+ 20	836,520,232	232	0.0000277

Table 7-38. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 94 of 106	

Frequency Stability / Temperature Variation




Figure 7-9. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 95 of 106

Frequency Stability / Temperature Variation

OPERATING FREQUENCY:	836,600,000	Hz
CHANNEL:	4183	
REFERENCE VOLTAGE:	4.20	VDC
DEVIATION LIMIT:	± 0.00025 % or 2.5 ppm	

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.20	+ 20 (Ref)	836,600,128	128	0.0000153
100 %		- 30	836,600,123	123	0.0000147
100 %		- 20	836,599,918	-82	-0.0000098
100 %		- 10	836,600,250	250	0.0000299
100 %		0	836,600,156	156	0.0000186
100 %		+ 10	836,600,317	317	0.0000379
100 %		+ 20	836,599,993	-7	-0.0000008
100 %		+ 30	836,599,749	-251	-0.0000300
100 %		+ 40	836,599,995	-5	-0.0000006
100 %		+ 50	836,599,837	-163	-0.0000195
BATT. ENDPOINT	3.54	+ 20	836,600,001	1	0.0000001

Table 7-39. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 96 of 106	

Frequency Stability / Temperature Variation




Figure 7-10. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 97 of 106

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,732,600,000 Hz
 CHANNEL: 1413
 REFERENCE VOLTAGE: 4.20 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.20	+ 20 (Ref)	1,732,600,493	493	0.0000285
100 %		- 30	1,732,600,375	375	0.0000216
100 %		- 20	1,732,600,143	143	0.0000083
100 %		- 10	1,732,600,028	28	0.0000016
100 %		0	1,732,600,082	82	0.0000047
100 %		+ 10	1,732,599,573	-427	-0.0000246
100 %		+ 20	1,732,599,803	-197	-0.0000114
100 %		+ 30	1,732,599,910	-90	-0.0000052
100 %		+ 40	1,732,599,974	-26	-0.0000015
100 %		+ 50	1,732,599,799	-201	-0.0000116
BATT. ENDPOINT	3.54	+ 20	1,732,600,469	469	0.0000271

Table 7-40. Frequency Stability Data (AWS WCDMA Mode – Ch. 1413)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 98 of 106	

Frequency Stability / Temperature Variation




Figure 7-11. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1413)

<p>FCC ID: ZNFV405UA</p>		<p>MEASUREMENT REPORT (CERTIFICATION)</p>	<p>Approved by: Quality Manager</p>
<p>Test Report S/N: 1M1806200130-02-R1.ZNF</p>	<p>Test Dates: 6/20/2018-8/2/2018</p>	<p>EUT Type: Portable Handset</p>	<p>Page 99 of 106</p>

Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 4.20 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.20	+ 20 (Ref)	1,880,000,176	176	0.0000094
100 %		- 30	1,880,000,081	81	0.0000043
100 %		- 20	1,880,000,027	27	0.0000014
100 %		- 10	1,879,999,838	-162	-0.0000086
100 %		0	1,880,000,008	8	0.0000004
100 %		+ 10	1,880,000,103	103	0.0000055
100 %		+ 20	1,880,000,236	236	0.0000126
100 %		+ 30	1,880,000,116	116	0.0000062
100 %		+ 40	1,879,999,773	-227	-0.0000121
100 %		+ 50	1,880,000,130	130	0.0000069
BATT. ENDPOINT	3.54	+ 20	1,879,999,797	-203	-0.0000108

Table 7-41. Frequency Stability Data (PCS GPRS Mode – Ch. 661)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 100 of 106	

Frequency Stability / Temperature Variation




Figure 7-12. Frequency Stability Graph (PCS GPRS Mode – Ch. 661)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 101 of 106

Frequency Stability / Temperature Variation

OPERATING FREQUENCY:	1,880,000,000	Hz
CHANNEL:	600	
REFERENCE VOLTAGE:	4.20	VDC
DEVIATION LIMIT:	± 0.00025 % or 2.5 ppm	

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.20	+ 20 (Ref)	1,880,000,026	26	0.0000014
100 %		- 30	1,880,000,233	233	0.0000124
100 %		- 20	1,880,000,233	233	0.0000124
100 %		- 10	1,880,000,246	246	0.0000131
100 %		0	1,880,000,251	251	0.0000134
100 %		+ 10	1,880,000,389	389	0.0000207
100 %		+ 20	1,880,000,355	355	0.0000189
100 %		+ 30	1,879,999,841	-159	-0.0000085
100 %		+ 40	1,879,999,690	-310	-0.0000165
100 %		+ 50	1,879,999,928	-72	-0.0000038
BATT. ENDPOINT	3.54	+ 20	1,880,000,154	154	0.0000082

Table 7-42. Frequency Stability Data (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 102 of 106	

Frequency Stability / Temperature Variation




Figure 7-13. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset		Page 103 of 106

Frequency Stability / Temperature Variation

OPERATING FREQUENCY:	1,880,000,000	Hz
CHANNEL:	9400	
REFERENCE VOLTAGE:	4.20	VDC
DEVIATION LIMIT:	± 0.00025 % or 2.5 ppm	

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.20	+ 20 (Ref)	1,879,999,891	-109	-0.0000058
100 %		- 30	1,879,999,858	-142	-0.0000076
100 %		- 20	1,879,999,939	-61	-0.0000032
100 %		- 10	1,880,000,070	70	0.0000037
100 %		0	1,880,000,288	288	0.0000153
100 %		+ 10	1,879,999,961	-39	-0.0000021
100 %		+ 20	1,880,000,449	449	0.0000239
100 %		+ 30	1,880,000,055	55	0.0000029
100 %		+ 40	1,880,000,386	386	0.0000205
100 %		+ 50	1,879,999,998	-2	-0.0000001
BATT. ENDPOINT	3.54	+ 20	1,880,000,150	150	0.0000080

Table 7-43. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 104 of 106	

Frequency Stability / Temperature Variation




Figure 7-14. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

<p>FCC ID: ZNFV405UA</p>		<p>MEASUREMENT REPORT (CERTIFICATION)</p>	<p>Approved by: Quality Manager</p>
<p>Test Report S/N: 1M1806200130-02-R1.ZNF</p>	<p>Test Dates: 6/20/2018-8/2/2018</p>	<p>EUT Type: Portable Handset</p>	<p>Page 105 of 106</p>

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFV405UA** complies with all the requirements of Part 22, 24, & 27 of the FCC Rules.

FCC ID: ZNFV405UA		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1806200130-02-R1.ZNF	Test Dates: 6/20/2018-8/2/2018	EUT Type: Portable Handset	Page 106 of 106	