

EMI TEST REPORT FCC CERTIFICATION

Applicant:

LG Electronics USA, Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632
United States

Date of Issue: August 06, 2018

Test Report No. HCT-EM-1807-FI004-R1

Test Site: HCT CO., LTD.

FCC ID :

ZNFV405UA

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
ANSI C63.4-2014

EUT Type: Multi-band CDMA/EVDO/GSM/EDGE/WCDMA/LTE Phone with
WLAN, Bluetooth and RFID

Model Name: LM-V405UA

Additional Model Name: LMV405UA, LM-V405TA, LMV405TA, LM-V405MA,
LMV405MA, LM-V405QA, LMV405QA, LM-V405QA5,
LMV405QA5, LM-V405QA6, LMV405QA6

TA Information: Model Name: MCS-H06WP, Manufacturer: PNTELECOM

Date of Test: June 28, 2018 to July 04, 2018

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By



Wook Yi
Test Engineer
EMC Team
Certification Division

Reviewed



Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



REVISION HISTORY

The revision history for this document is shown in table.

Report No.	Issue Date	Description
HCT-EM-1807-FI004	July 05, 2018	Initial Release
HCT-EM-1807-FI004-R1	August 06, 2018	Deleted the ISED



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s)	4
1.3 Test Facility	6
1.4 Calibration of Measuring Instrument	6
1.5 Tested System Details	7
1.6 Cable Description	7
1.7 Noise Suppression Parts on Cable. (I/O Cable)	7
2. MEASUREMENT UNCERTAINTY	8
3. DESCRIPTION OF TEST	9
3.1 Measurement of Conducted Emission.....	9
3.2 Measurement of Radiated Measurements	10
4. PRELIMINARY TEST	13
4.1 Conducted Emission Test	13
4.2 Radiated Emission Test	13
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	14
5.1 Conducted Emission Test	14
5.2 Radiated Emission Test	21
6. LIST OF TEST EQUIPMENT.....	25
7. CONCLUSION.....	26
8. APPENDIX A. TEST SETUP PHOTOGRAPHS	27



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFV405UA
Model	LM-V405UA
Additional Model	LMV405UA, LM-V405TA, LMV405TA, LM-V405MA, LMV405MA, LM-V405QA, LMV405QA, LM-V405QA5, LMV405QA5, LM-V405QA6, LMV405QA6
EUT Type	Multi-band CDMA/EVDO/GSM/EDGE/WCDMA/LTE Phone with WLAN, Bluetooth and RFID
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 817.90 MHz to 823.10 MHz (CDMA BC10) 824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 2 496 MHz to 2 570 MHz (LTE B7) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 788 MHz to 798 MHz (LTE B14) 704 MHz to 716 MHz (LTE B17) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 305 MHz to 2 315 MHz (LTE B30) 2 496 MHz to 2 690 MHz (LTE B41) 1 710 MHz to 1 780 MHz (LTE B66) 663 MHz to 698 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3) 13.56 MHz (RFID)



RX Frequency	<p>869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 862.00 MHz to 894.00 MHz (CDMA BC10) 869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.40 MHz to 891.60 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 2 516 MHz to 2 690 MHz (LTE B7) 729 MHz to 746 MHz (LTE B12) 746 MHz to 756 MHz (LTE B13) 758 MHz to 768 MHz (LTE B14) 734 MHz to 746 MHz (LTE B17) 1 925 MHz to 1 990 MHz (LTE B25) 859 MHz to 894 MHz (LTE B26) 717 MHz to 728 MHz (LTE B29) 2 350 MHz to 2 360 MHz (LTE B30) 2 496 MHz to 2 690 MHz (LTE B41) 5 150 MHz to 5 925 MHz (LTE B46) 2 110 MHz to 2 200 MHz (LTE B66) 617 MHz to 652 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3) 13.56 MHz (RFID)</p>
--------------	---



1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	

1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID/ DoC
EUT	LM-V405UA	LG	ZNFV405UA
Data cable	EAD64746101	Ningbo Broad	-
Earphone	EAB63728244	CRESYN	-
Travel adaptor	MCS-H06WP	PNTELECOM	-
Micro SD card	SAMSUNG EVO+ microSDXC CLASS10 UHS-I (256 GB)	SAMSUNG	-
Wireless charger	EP-PN920	SAMSUNG	-

1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	USB type C	Y	Y	(P)1.0
	Earphone	N/A	Y	(D)1.2
Wireless charger	Micro USB	Y	N	(D)1.5

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	USB type C	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Wireless charger	Micro USB	N	N/A	Y	Both End



2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	1.82 dB ($k = 2$)
3 m Radiated Emissions (30 MHz to 1 GHz)	5.20 dB ($k = 2$)
3 m Radiated Emissions (1 GHz to 18 GHz)	5.24 dB ($k = 2$)
3 m Radiated Emissions (18 GHz to 40 GHz)	5.40 dB ($k = 2$)



3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



3.3 Configuration of Tested System



Wireless Charging Mode



Non-Conductive Table
Power Line: 120 VAC, 60 Hz



4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

- Operation Mode:** Camera (Front) & MP3 mode
 Camera (Rear) & FM Radio mode
 Idle mode

NOTE. *The worst-case emissions are reported.*

4. 2 Radiated Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

- Operation Mode:** Camera (Front) & MP3 mode
 Camera (Rear) & FM Radio mode
 Idle mode

NOTE. *The worst-case emissions are reported.*

- Wireless charging mode



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

Rule Part / Standard	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Worst Case of Operation Mode	Camera (Rear) & FM Radio mode
Kind of Test Site	Shielded Room
Temperature	24.1 °C
Relative Humidity	47.9 %
Test Date	June 28, 2018


- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Conducted Emission, AC Main Port, Line (L1)

FCC CLASS B_Exten Cable





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.156000	31.3	9.000	L1	9.7	34.4	65.7
0.166000	30.8	9.000	L1	9.7	34.4	65.2
0.438000	32.3	9.000	L1	9.7	24.8	57.1
0.446000	32.5	9.000	L1	9.7	24.5	56.9
0.450000	32.7	9.000	L1	9.7	24.2	56.9
0.472000	33.1	9.000	L1	9.7	23.4	56.5
1.100000	37.2	9.000	L1	9.8	18.8	56.0
1.122000	37.2	9.000	L1	9.8	18.8	56.0
1.142000	37.9	9.000	L1	9.8	18.1	56.0
1.146000	38.1	9.000	L1	9.8	17.9	56.0
1.152000	37.8	9.000	L1	9.8	18.2	56.0
1.170000	36.1	9.000	L1	9.8	19.9	56.0
8.338000	28.7	9.000	L1	10.1	31.3	60.0
9.456000	29.3	9.000	L1	10.1	30.7	60.0
9.510000	28.9	9.000	L1	10.1	31.1	60.0
9.756000	29.5	9.000	L1	10.2	30.5	60.0
10.936000	28.0	9.000	L1	10.2	32.0	60.0
10.998000	29.3	9.000	L1	10.2	30.7	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	18.5	9.000	L1	9.7	37.3	55.8
0.166000	20.8	9.000	L1	9.7	34.3	55.2
0.354000	23.4	9.000	L1	9.7	25.5	48.9
0.438000	24.8	9.000	L1	9.7	22.3	47.1
0.444000	26.1	9.000	L1	9.7	20.9	47.0
0.452000	26.4	9.000	L1	9.7	20.4	46.8
1.098000	30.8	9.000	L1	9.8	15.2	46.0
1.136000	31.6	9.000	L1	9.8	14.4	46.0
1.142000	31.2	9.000	L1	9.8	14.8	46.0
1.148000	30.9	9.000	L1	9.8	15.1	46.0
1.152000	30.8	9.000	L1	9.8	15.2	46.0
1.170000	29.8	9.000	L1	9.8	16.2	46.0
8.338000	18.4	9.000	L1	10.1	31.6	50.0
9.756000	19.5	9.000	L1	10.2	30.5	50.0
9.978000	19.4	9.000	L1	10.2	30.6	50.0
10.244000	19.6	9.000	L1	10.2	30.4	50.0
10.936000	19.2	9.000	L1	10.2	30.8	50.0
11.112000	19.2	9.000	L1	10.2	30.8	50.0



Figure 2: Conducted Emission, AC Main Port, Line (N)

FCC CLASS B_Exten Cable





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.3	9.000	N	9.7	37.7	66.0
0.154000	28.6	9.000	N	9.7	37.2	65.8
0.170000	27.5	9.000	N	9.7	37.5	65.0
0.444000	33.2	9.000	N	9.7	23.8	57.0
0.452000	33.5	9.000	N	9.7	23.4	56.8
0.474000	30.2	9.000	N	9.7	26.3	56.4
1.116000	38.3	9.000	N	9.8	17.8	56.0
1.136000	39.2	9.000	N	9.8	16.8	56.0
1.140000	38.3	9.000	N	9.8	17.7	56.0
1.146000	38.8	9.000	N	9.8	17.2	56.0
1.156000	38.8	9.000	N	9.8	17.2	56.0
1.162000	37.9	9.000	N	9.8	18.1	56.0
26.268000	30.9	9.000	N	10.8	29.1	60.0
26.368000	30.6	9.000	N	10.9	29.4	60.0
26.656000	30.9	9.000	N	10.9	29.1	60.0
26.756000	31.1	9.000	N	10.9	28.9	60.0
26.892000	30.9	9.000	N	10.9	29.1	60.0
26.918000	30.8	9.000	N	10.9	29.2	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	15.4	9.000	N	9.7	40.4	55.8
0.174000	15.2	9.000	N	9.7	39.6	54.8
0.444000	24.4	9.000	N	9.7	22.6	47.0
0.450000	24.7	9.000	N	9.7	22.2	46.9
0.462000	25.0	9.000	N	9.7	21.7	46.7
0.472000	23.8	9.000	N	9.7	22.7	46.5
1.116000	31.8	9.000	N	9.8	14.2	46.0
1.146000	31.8	9.000	N	9.8	14.2	46.0
1.156000	31.3	9.000	N	9.8	14.7	46.0
1.162000	31.3	9.000	N	9.8	14.7	46.0
1.168000	30.7	9.000	N	9.8	15.3	46.0
1.172000	30.6	9.000	N	9.8	15.4	46.0
26.268000	16.5	9.000	N	10.8	33.5	50.0
26.602000	16.3	9.000	N	10.9	33.7	50.0
26.656000	16.5	9.000	N	10.9	33.5	50.0
26.756000	16.8	9.000	N	10.9	33.2	50.0
26.892000	16.6	9.000	N	10.9	33.4	50.0
26.992000	16.6	9.000	N	10.9	33.4	50.0



5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Worst Case of Operation Mode	Camera (Rear) & FM Radio mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.5 °C
Relative Humidity	47.1 %
Test Date	June 29, 2018

Frequency (MHz)	Quasi Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
40.051200	23.4	99.8	V	70.0	19.7	16.6	40.0
87.240000	20.6	225.0	H	306.0	14.7	19.4	40.0
137.988800	19.1	99.8	V	312.0	19.5	24.4	43.5
162.512000	18.6	225.0	H	256.0	20.0	24.9	43.5
330.710400	20.6	125.2	H	105.0	21.3	25.4	46.0
850.820000	30.4	125.0	H	78.0	30.7	15.6	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



Rule Part / Standard	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Wireless charging mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	24.7 °C
Relative Humidity	47.5 %
Test Date	July 04, 2018

Frequency (MHz)	Quasi Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
46.172800	20.9	99.9	V	0.0	20.1	19.1	40.0
54.096800	24.1	99.8	V	53.0	20.1	15.9	40.0
78.350400	17.1	325.2	H	99.0	16.0	22.9	40.0
114.562400	20.9	175.0	V	1.0	17.2	22.6	43.5
370.480000	20.9	99.8	H	95.0	22.3	25.1	46.0
620.211200	27.7	308.9	V	295.0	27.7	18.3	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	5 925 MHz
Tested Frequency Range	1 GHz to 30 GHz
Worst Case of Operation Mode	Camera (Rear) & FM Radio mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	24.0 °C
Relative Humidity	43.9 %
Test Date	July 02, 2018

Frequency (MHz)	Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1725.430000	30.9	99.7	H	75.0	-27.7	43.1	74.0
2765.300000	33.5	248.4	H	118.0	-23.6	40.5	74.0
3600.520000	40.6	349.9	V	289.0	-22.0	33.4	74.0
6621.020000	39.2	113.6	V	63.0	-14.6	34.8	74.0
7823.975000	42.6	99.8	V	341.0	-12.0	31.4	74.0
9638.600000	43.7	149.9	V	4.0	-10.6	30.3	74.0

Frequency (MHz)	CAverage (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1725.430000	17.5	99.7	H	75.0	-27.7	36.5	54.0
2765.300000	20.3	248.4	H	118.0	-23.6	33.7	54.0
3600.520000	29.2	349.9	V	289.0	-22.0	24.8	54.0
6621.020000	26.0	113.6	V	63.0	-14.6	28.0	54.0
7823.975000	29.1	99.8	V	341.0	-12.0	24.9	54.0
9638.600000	30.3	149.9	V	4.0	-10.6	23.7	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



Rule Part / Standard	FCC PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	5 925 MHz
Tested Frequency Range	1 GHz to 30 GHz
Operation Mode	Wireless charging mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	24.7 °C
Relative Humidity	47.5 %
Test Date	July 04, 2018

Frequency (MHz)	Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1399.260000	30.2	138.5	V	204.0	-28.6	43.8	74.0
3080.315000	34.0	249.7	H	26.0	-22.8	40.0	74.0
5518.105000	36.6	248.4	V	37.0	-17.5	37.4	74.0
7667.650000	41.9	249.5	H	39.0	-12.1	32.1	74.0
8939.470000	42.8	321.7	H	109.0	-11.4	31.2	74.0
9740.820000	42.9	149.9	V	218.0	-10.3	31.1	74.0

Frequency (MHz)	CAverage (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
1399.260000	17.4	138.5	V	204.0	-28.6	36.6	54.0
3080.315000	21.0	249.7	H	26.0	-22.8	33.0	54.0
5518.105000	23.7	248.4	V	37.0	-17.5	30.3	54.0
7667.650000	29.3	249.5	H	39.0	-12.1	24.7	54.0
8939.470000	29.9	321.7	H	109.0	-11.4	24.1	54.0
9740.820000	29.6	149.9	V	218.0	-10.3	24.4	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.25.2018
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	102245	1 year	12.20.2017
<input type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	05.03.2018
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.54.0	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB 9168	760	2 year	04.06.2017
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO 3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	INNCO Systems	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	INNCO Systems	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
<input checked="" type="checkbox"/> Low Noise Amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.06.2018
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	2 year	12.05.2017
<input checked="" type="checkbox"/> Power Amplifier	TESTEK	TK-PA1840H	170030-L	1 year	12.20.2017
<input type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	06.25.2018
<input type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-



7. CONCLUSION

The data collected shows that the **EUT Type: Multi-band CDMA/EVDO/GSM/EDGE/WCDMA /LTE Phone with WLAN, Bluetooth and RFID, Model: LM-V405UA** complies with §15.107 and §15.109 of the FCC rules.



8. APPENDIX A. TEST SETUP PHOTOGRAPHS

Please refer to Appendix A