

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Receipt: January 26, 2015

Date of Issue: March 13, 2015

Test Report No. HCT-E-1502-F024-1

HCT FRN: 0005866421

FCC ID:

ZNFV495

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: Potable tablet
Model Name: LG-V495
Additional Model Name: VS495, LG-VS495, LGVS495
Test Port: USB / Earphone Port
Date of Test: February 09, 2015 - February 17, 2015

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By



Kyoung-Hee Yoon
Test Engineer
EMC Team
Certification Division

Reviewed By



Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1502-F024	February 23, 2015	Initial Release
HCT-E-1502-F024-1	March 13, 2015	The EUT Type name is changed.



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Test Facility	5
1.4 Tested System Details.....	6
1.5 Cable Description	7
1.6 Noise Suppression Parts on Cable. (I/O Cable)	7
2. DESCRIPTION OF TEST	8
3. PRELIMINARY TEST	11
3.1 Conducted Emission Test	11
3. 2 Radiated Emission Test	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
4.1 Conducted Emission Test	12
4.2 Radiated Emission Test	19
5. LIST OF TEST EQUIPMENT	21
6. CONCLUSION	22

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model	LG-V495
FCC ID	ZNFV495
Additional Model	VS495, LG-VS495, LGVS495
EUT Type	Potable tablet
TX Frequency	1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850.7 MHz to 1 909.3 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 2 496 MHz to 2570 MHz (LTE B7) 699 MHz to 716 MHz (LTE B12) 704 MHz to 716 MHz (LTE B17) 1 850 MHz to 1 915 MHz (LTE B25)
RX Frequency	1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.40 MHz to 891.60 MHz (WCDMA B5) 1 930.00 MHz to 1 990.00 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 2 516 MHz to 2690 MHz (LTE B7) 729 MHz to 746 MHz (LTE B12) 734 MHz to 746 MHz (LTE B17) 1 925 MHz to 1 990 MHz (LTE B25)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.



1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-V495	LG	ZNFV495	Notebook PC, Earphone
USB cable	EAD62572502	Ningbo Broad	-	EUT, Notebook PC
USB cable	EAD62572501	CRESYN	-	EUT, Notebook PC
USB cable	EAD62572503	KSD	-	EUT, Notebook PC
Earphone	EAB62209201	I-SOUND	-	EUT
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	8 GB	SanDisk	-	EUT



1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End

※NOTE: This tablet device does not contain the minimum number of ports required for personal computer testing per ANSI C63.4, but the EUT is attached to a computer through its only available port, which represents worst case emissions. All other aspects of ANSI C63.4 testing requirements were maintained.



2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 7

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a 3 m shield room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V}/\text{m}$)	Quasi-Peak ($\text{dB}(\mu\text{V})/\text{m}$)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ($\text{dB}(\mu\text{V})/\text{m}$)	Average ($\text{dB}(\mu\text{V})/\text{m}$)
Above 1 000	3	74	54




2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



3. PRELIMINARY TEST

3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

3.2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	CRESYN (EAD62572501) *NOTE: The worst-case emissions are reported.
Kind of Test Site	Shielded Room
Temperature	20.5 / 20.0 °C
Relative Humidity	30.9 / 25.9 %
Test Date	February 16, 2015 / February 17, 2015

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)





QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	47.3	9.000	L1	9.6	18.6	65.9
0.158000	44.2	9.000	L1	9.6	21.4	65.6
0.194000	56.1	9.000	L1	9.6	7.8	63.9
0.200000	55.4	9.000	L1	9.7	8.2	63.6
0.204000	54.9	9.000	L1	9.7	8.5	63.4
0.208000	54.2	9.000	L1	9.7	9.1	63.3
3.896000	38.0	9.000	L1	9.9	18.0	56.0
4.110000	38.7	9.000	L1	9.9	17.3	56.0
4.316000	38.2	9.000	L1	9.9	17.8	56.0
4.524000	37.8	9.000	L1	9.9	18.2	56.0
4.676000	38.3	9.000	L1	9.9	17.7	56.0
4.712000	37.4	9.000	L1	9.9	18.6	56.0
17.768000	32.3	9.000	L1	10.3	27.7	60.0
17.782000	32.4	9.000	L1	10.3	27.6	60.0
17.926000	32.0	9.000	L1	10.3	28.0	60.0
18.134000	32.5	9.000	L1	10.3	27.5	60.0
18.208000	31.4	9.000	L1	10.3	28.6	60.0
18.490000	29.7	9.000	L1	10.3	30.3	60.0




CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.4	9.000	L1	9.6	27.6	56.0
0.158000	24.7	9.000	L1	9.6	30.9	55.6
0.192000	34.4	9.000	L1	9.6	19.5	53.9
0.196000	38.1	9.000	L1	9.6	15.7	53.8
0.202000	38.3	9.000	L1	9.7	15.2	53.5
0.210000	35.7	9.000	L1	9.7	17.5	53.2
3.896000	28.5	9.000	L1	9.9	17.5	46.0
4.316000	30.0	9.000	L1	9.9	16.0	46.0
4.524000	30.4	9.000	L1	9.9	15.6	46.0
4.610000	29.9	9.000	L1	9.9	16.1	46.0
4.676000	30.4	9.000	L1	9.9	15.6	46.0
4.712000	30.1	9.000	L1	9.9	15.9	46.0
17.716000	25.1	9.000	L1	10.3	24.9	50.0
17.768000	25.1	9.000	L1	10.3	24.9	50.0
17.782000	25.8	9.000	L1	10.3	24.2	50.0
18.134000	23.7	9.000	L1	10.3	26.3	50.0
18.208000	23.3	9.000	L1	10.3	26.7	50.0
18.490000	20.7	9.000	L1	10.3	29.3	50.0



Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)





QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	45.6	9.000	N	9.6	20.4	66.0
0.192000	51.7	9.000	N	9.6	12.2	63.9
0.196000	52.5	9.000	N	9.6	11.3	63.8
0.202000	52.2	9.000	N	9.6	11.3	63.5
0.208000	51.4	9.000	N	9.6	11.9	63.3
0.212000	50.1	9.000	N	9.6	13.0	63.1
4.036000	39.0	9.000	N	9.8	17.0	56.0
4.048000	37.8	9.000	N	9.8	18.2	56.0
4.460000	38.9	9.000	N	9.9	17.1	56.0
4.602000	38.7	9.000	N	9.9	17.3	56.0
4.612000	37.5	9.000	N	9.9	18.5	56.0
4.674000	38.1	9.000	N	9.9	17.9	56.0
18.122000	30.8	9.000	N	10.3	29.2	60.0
19.684000	31.9	9.000	N	10.3	28.1	60.0
19.752000	32.4	9.000	N	10.3	27.6	60.0
21.588000	32.7	9.000	N	10.3	27.3	60.0
21.804000	32.5	9.000	N	10.3	27.5	60.0
21.948000	30.1	9.000	N	10.3	29.9	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	26.6	9.000	N	9.6	29.4	56.0
0.192000	32.3	9.000	N	9.6	21.6	53.9
0.196000	35.5	9.000	N	9.6	18.3	53.8
0.202000	35.5	9.000	N	9.6	18.0	53.5
0.206000	34.9	9.000	N	9.6	18.5	53.4
0.212000	32.2	9.000	N	9.6	20.9	53.1
4.036000	29.6	9.000	N	9.8	16.4	46.0
4.110000	30.0	9.000	N	9.8	16.0	46.0
4.460000	30.6	9.000	N	9.9	15.4	46.0
4.530000	30.4	9.000	N	9.9	15.6	46.0
4.602000	30.2	9.000	N	9.9	15.8	46.0
4.612000	30.1	9.000	N	9.9	15.9	46.0
17.772000	23.2	9.000	N	10.3	26.8	50.0
18.122000	21.6	9.000	N	10.3	28.4	50.0
19.608000	24.7	9.000	N	10.3	25.3	50.0
21.450000	26.0	9.000	N	10.3	24.0	50.0
21.806000	22.6	9.000	N	10.3	27.4	50.0
21.948000	21.5	9.000	N	10.3	28.5	50.0



4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
USB Cable Type	CRESYN (EAD62572501) ※NOTE: The worst-case emissions are reported.
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.6 °C
Relative Humidity	26.1 %
Test Date	February 09, 2015

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)
85.228858	29.0	350.0	H	231.0	11.6	11.0	40.0
170.359920	34.3	174.0	H	68.0	16.5	9.2	43.5
265.570421	36.3	123.0	H	306.0	16.8	9.7	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	1.2 GHz
Testing Frequency Range	1 GHz to 6 GHz
Operation Mode	Data Communication mode
USB Cable Type	KSD (EAD62572503) *NOTE: The worst-case emissions are reported.
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.6 °C
Relative Humidity	26.1 %
Test Date	February 09, 2015

Frequency (MHz)	Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)
1331.312626	49.8	100.0	V	28.0	-9.3	24.2	74.0
1995.140281	57.5	100.0	V	28.0	-7.8	16.5	74.0
2588.827656	49.6	238.0	V	30.0	-4.9	24.4	74.0

Frequency (MHz)	CAverage (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)
1331.312626	31.8	100.0	V	28.0	-9.3	22.2	54.0
1995.140281	38.6	100.0	V	28.0	-7.8	15.4	54.0
2588.827656	33.4	238.0	V	30.0	-4.9	20.6	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	01.13.2015
<input checked="" type="checkbox"/> LISN	EMCO	3816/2SH	9706-1070	1 year	04.07. 2014
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	01.13.2015
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17 2014
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18.2014
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.11.2014
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.11. 2014
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	12.13. 2012
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	1151	2 year	07.05.2013
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18. 2014
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170124	2 year	10.30. 2013
<input type="checkbox"/> Power Amplifier	CERNEX	CBL18265035	22966	1 year	07.23. 2014
<input type="checkbox"/> Power Amplifier	CERNEX	CBL26405040	19660	1 year	04.04. 2014
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-



6. CONCLUSION

The data collected shows that the **EUT Type: Potable tablet, FCC ID: ZNFV495, Model: LG-V495** complies with §15.107 and §15.109 of the FCC rules.