



## MEASUREMENT REPORT FCC Part 22, 24, & 27 LTE

**Applicant Name:**  
 LG Electronics MobileComm U.S.A  
 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632  
 United States

**Date of Testing:**  
 03/17 - 03/31/2015  
**Test Site/Location:**  
 PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
 OY1503160567.ZNF

<b>FCC ID :</b>	<b>ZNFVK815</b>
<b>APPLICANT:</b>	<b>LG ELECTRONICS MOBILECOMM U.S.A</b>

**Application Type:** Class II Permissive Change  
**FCC Classification:** PCS Licensed Transmitter (PCB)  
**FCC Rule Part(s):** §2; §22; §24; §27  
**Test Procedure(s):** ANSI/TIA-603-C-2004, KDB 971168 v02r02  
**EUT Type:** Portable Tablet  
**Model(s):** LG-VK815, LGVK815, VK815, LG-AK815, LGAK815, AK815  
**Test Device Serial No.:** *identical prototype* [S/N: ERP/EIRP]  
**Class II Permissive Change:** Please see FCC change document  
**Original Grant Date:** 03/24/2015

Mode	Tx Frequency (MHz)	Modulation	ERP/EIRP	
			Max. Power (W)	Max. Power (dBm)
LTE Band 13	779.5 - 784.5	QPSK	0.066	18.20
LTE Band 13	779.5 - 784.5	16QAM	0.052	17.20
LTE Band 13	782	QPSK	0.066	18.20
LTE Band 13	782	16QAM	0.055	17.40
LTE Band 5	824.7 - 848.3	QPSK	0.071	18.51
LTE Band 5	824.7 - 848.3	16QAM	0.059	17.71
LTE Band 5	825.5 - 847.5	QPSK	0.085	19.31
LTE Band 5	825.5 - 847.5	16QAM	0.070	18.42
LTE Band 5	826.5 - 846.5	QPSK	0.089	19.49
LTE Band 5	826.5 - 846.5	16QAM	0.070	18.44
LTE Band 5	829 - 844	QPSK	0.094	19.74
LTE Band 5	829 - 844	16QAM	0.073	18.66
LTE Band 4	1710.7 - 1754.3	QPSK	0.423	26.26
LTE Band 4	1710.7 - 1754.3	16QAM	0.315	24.99
LTE Band 4	1711.5 - 1753.5	QPSK	0.566	27.53
LTE Band 4	1711.5 - 1753.5	16QAM	0.394	25.96
LTE Band 4	1712.5 - 1752.5	QPSK	0.530	27.25
LTE Band 4	1712.5 - 1752.5	16QAM	0.408	26.11
LTE Band 4	1715 - 1750	QPSK	0.462	26.64
LTE Band 4	1715 - 1750	16QAM	0.356	25.51
LTE Band 4	1717.5 - 1747.5	QPSK	0.453	26.56
LTE Band 4	1717.5 - 1747.5	16QAM	0.350	25.45
LTE Band 4	1720 - 1745	QPSK	0.465	26.68
LTE Band 4	1720 - 1745	16QAM	0.370	25.68
LTE Band 2	1850.7 - 1909.3	QPSK	0.251	23.99
LTE Band 2	1850.7 - 1909.3	16QAM	0.209	23.21
LTE Band 2	1851.5 - 1908.5	QPSK	0.294	24.68
LTE Band 2	1851.5 - 1908.5	16QAM	0.229	23.61
LTE Band 2	1852.5 - 1907.5	QPSK	0.249	23.96
LTE Band 2	1852.5 - 1907.5	16QAM	0.179	22.54
LTE Band 2	1855 - 1905	QPSK	0.250	23.99
LTE Band 2	1855 - 1905	16QAM	0.190	22.78
LTE Band 2	1857.5 - 1902.5	QPSK	0.268	24.29
LTE Band 2	1857.5 - 1902.5	16QAM	0.233	23.67
LTE Band 2	1860 - 1900	QPSK	0.267	24.26
LTE Band 2	1860 - 1900	16QAM	0.224	23.49

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
 Randy Ortanez  
 President




<b>FCC ID:</b> ZNFVK815		<b>FCC Pt. 22, 24, &amp; 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> OY1503160567.ZNF	<b>Test Dates:</b> 03/17 - 03/31/2015	<b>EUT Type:</b> Portable Tablet	Page 1 of 25	

# T A B L E O F C O N T E N T S

FCC PART 22, 24, & 27 MEASUREMENT REPORT .....		3
1.0 INTRODUCTION .....		4
1.1 SCOPE .....		4
1.2 TESTING FACILITY .....		4
2.0 PRODUCT INFORMATION .....		5
2.1 EQUIPMENT DESCRIPTION .....		5
2.2 DEVICE CAPABILITIES .....		5
2.3 TEST CONFIGURATION .....		5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....		5
2.5 LABELING REQUIREMENTS .....		5
3.0 DESCRIPTION OF TESTS .....		6
3.1 MEASUREMENT PROCEDURE .....		6
3.1 BLOCK C FREQUENCY RANGE .....		6
3.2 CELLULAR - BASE FREQUENCY BLOCKS .....		6
3.3 CELLULAR - MOBILE FREQUENCY BLOCKS .....		6
3.4 PCS - BASE FREQUENCY BLOCKS .....		7
3.5 PCS - MOBILE FREQUENCY BLOCKS .....		7
3.6 AWS - BASE FREQUENCY BLOCKS .....		7
3.7 AWS - MOBILE FREQUENCY BLOCKS .....		7
3.8 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS .....		8
4.0 TEST EQUIPMENT CALIBRATION DATA .....		9
5.0 SAMPLE CALCULATIONS .....		10
6.0 TEST RESULTS .....		11
6.1 SUMMARY .....		11
6.2 RADIATED POWER (ERP/EIRP) .....		12
6.3 RADIATED SPURIOUS EMISSIONS MEASUREMENTS .....		17
7.0 CONCLUSION .....		25

FCC ID: ZNFVK815		<b>FCC Pt. 22, 24, &amp; 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1503160567.ZNF	<b>Test Dates:</b> 03/17 - 03/31/2015	<b>EUT Type:</b> Portable Tablet	Page 2 of 25	



# MEASUREMENT REPORT

## FCC Part 22, 24, & 27




### §2.1033 General Information

**APPLICANT:** LG Electronics MobileComm U.S.A  
**APPLICANT ADDRESS:** 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22; §24; §27  
**BASE MODEL:** LG-VK815  
**FCC ID:** ZNFVK815  
**FCC CLASSIFICATION:** PCS Licensed Transmitter (PCB)  
**FREQUENCY TOLERANCE:** ±0.00025 % (2.5 ppm)  
**Test Device Serial No.:** ERP/EIRP  Production  Pre-Production  Engineering  
**DATE(S) OF TEST:** 03/17 - 03/31/2015  
**TEST REPORT S/N:** 0Y1503160567.ZNF

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 3 of 25	

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet		Page 4 of 25

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Tablet FCC ID: ZNFVK815**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

### 2.2 Device Capabilities

This device contains the following capabilities:

Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n UNII, Bluetooth (1x, EDR, LE)

### 2.3 Test Configuration

The LG Portable Tablet FCC ID: ZNFVK815 was tested per the guidance of ANSI/TIA-603-C-2004 and KDB 971168 v02r02. See Section 6.0 of this test report for a description of the radiated emissions tests.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.5 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 5 of 25	

## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168) were used in the measurement of the **LG Portable Tablet FCC ID: ZNFVK815**.

### 3.1 Block C Frequency Range

#### §27.5(b)(3)

Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.

### 3.2 Cellular - Base Frequency Blocks

#### §22.905




**BLOCK 1:** 869 – 880 MHz (A\* Low + A)  
**BLOCK 2:** 880 – 890 MHz (B)

**BLOCK 3:** 890 – 891.5 MHz (A\* High)  
**BLOCK 4:** 891.5 – 894 MHz (B\*)

### 3.3 Cellular - Mobile Frequency Blocks

#### §22.905




**BLOCK 1:** 824 – 835 MHz (A\* Low + A)  
**BLOCK 2:** 835 – 845 MHz (B)

**BLOCK 3:** 845 – 846.5 MHz (A\* High)  
**BLOCK 4:** 846.5 – 849 MHz (B\*)

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 6 of 25	

### 3.4 PCS - Base Frequency Blocks


§24.229



- BLOCK 1: 1930 – 1945 MHz (A)
- BLOCK 2: 1945 – 1950 MHz (D)
- BLOCK 3: 1950 – 1965 MHz (B)
- BLOCK 4: 1965 – 1970 MHz (E)
- BLOCK 5: 1970 – 1975 MHz (F)
- BLOCK 6: 1975 – 1990 MHz (C)

### 3.5 PCS - Mobile Frequency Blocks


§24.229



- BLOCK 1: 1850 – 1865 MHz (A)
- BLOCK 2: 1865 – 1870 MHz (D)
- BLOCK 3: 1870 – 1885 MHz (B)
- BLOCK 4: 1885 – 1890 MHz (E)
- BLOCK 5: 1890 – 1895 MHz (F)
- BLOCK 6: 1895 – 1910 MHz (C)

### 3.6 AWS - Base Frequency Blocks


§27.5(h)



- BLOCK 1: 2110 – 2120 MHz (A)
- BLOCK 2: 2120 – 2130 MHz (B)
- BLOCK 3: 2130 – 2135 MHz (C)
- BLOCK 4: 2135 – 2140 MHz (D)
- BLOCK 5: 2140 – 2145 MHz (E)
- BLOCK 6: 2145 – 2155 MHz (F)

### 3.7 AWS - Mobile Frequency Blocks

§27.5(h)



- BLOCK 1: 1710 – 1720 MHz (A)
- BLOCK 2: 1720 – 1730 MHz (B)
- BLOCK 3: 1730 – 1735 MHz (C)
- BLOCK 4: 1735 – 1740 MHz (D)
- BLOCK 5: 1740 – 1745 MHz (E)
- BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet		Page 7 of 25

### 3.8 Radiated Power and Radiated Spurious Emissions

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(b.10) §27.50(d.4) §27.53(f) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A 3/4" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss} \text{ [dB]} + \text{antenna gain} \text{ [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss} \text{ [dB]}$ .

The calculated  $P_d$  levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of  $43 + 10\log_{10}(\text{Power} \text{ [Watts]})$ .

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 8 of 25	

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	10/16/2014	Annual	10/16/2015	N/A
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	10/24/2014	Annual	10/24/2015	N/A
Agilent	8447D	Broadband Amplifier	5/30/2014	Annual	5/30/2015	2443A01900
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Emco	3115	Horn Antenna (1-18GHz)	1/30/2014	Biennial	1/30/2016	9704-5182
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/8/2014	Biennial	4/8/2016	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/12/2014	Biennial	3/12/2016	128337
K & L	13SH10-1000/U1000	N Type High Pass Filter	12/1/2014	Annual	12/1/2015	1
K & L	11SH10-3075/U18000	High Pass Filter	12/1/2014	Annual	12/1/2015	2
Mini-Circuits	SSG-4000HP	USB Synthesized Signal Generator	N/A			11208010032
Mini-Circuits	PWR-SENS-4RMS	USB Power Sensor	3/11/2015	Annual	3/11/2016	11210140001
Mini-Circuits	TVA-11-422	RF Power Amp	N/A			QA1303002
Rhode & Schwarz	TS-PR18	Pre-Amplifier	3/5/2015	Annual	3/5/2016	101622
Rohde & Schwarz	CMW500	Radio Communication Tester	10/3/2014	Annual	10/3/2015	100976
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/5/2015	Annual	3/5/2016	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/3/2015	Annual	3/3/2016	100040
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	3/12/2015	Annual	3/12/2016	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	5/21/2014	Annual	5/21/2015	100348
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/21/2013	Biennial	11/21/2015	9105-2404
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/28/2014	Biennial	1/28/2016	A051107
VWR	62344-734	Thermometer with Clock	2/20/2014	Biennial	2/20/2016	140140336

**Table 4-1. Test Equipment**

**Note:**

1. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 9 of 25	

## 5.0 SAMPLE CALCULATIONS

### Spurious Radiated Emission – LTE Band

#### Example: Middle Channel LTE Mode 2<sup>nd</sup> Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is  $8.1$  dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is  $2.0$  dB at  $1564$  MHz. So  $6.1$  dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was  $25.501$  dBm so this harmonic was  $25.501$  dBm  $- (-24.80)$ .

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 10 of 25	

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: LG Electronics MobileComm U.S.A  
 FCC ID: ZNFVK815  
 FCC Classification: PCS Licensed Transmitter (PCB)  
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
<b>TRANSMITTER MODE (TX)</b>					
22.913(a.2)	Effective Radiated Power (Band 5,)	< 7 Watts max. ERP	RADIATED	PASS	Section 6.2
27.50(b.10)	Effective Radiated Power (Band 13)	< 3 Watts max. ERP		PASS	Section 6.2
24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	< 2 Watts max. EIRP		PASS	Section 6.2
27.50(d.4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP		PASS	Section 6.2
2.1053 22.917(a) 24.238(a) 27.53(c) 27.53(h)	Undesirable Emissions	> 43 + 10log <sub>10</sub> (P[Watts]) for all out-of-band emissions		PASS	Section 6.3
27.53(f)	Undesirable Emissions (Band 13)	< -70 dBW/MHz (for wideband signals) < -80 dBW (for discrete emissions less than 700Hz BW) For all emissions in the band 1559 – 1610 MHz		PASS	Section 6.3

**Table 6-1. Summary of Test Results**

**Note:**

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 11 of 25	

**6.2 Radiated Power (ERP/EIRP)**  
§22.913(a.2) §24.232(c.2) §27.50(b.10) §27.50(d.4)

**Test Overview**

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

**Test Procedures Used**

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17


**Test Settings**

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”.
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet		Page 12 of 25

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-1. Test Instrument & Measurement Setup**

### Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	Ant. Pol. [H/V]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
779.50	5	QPSK	Standard	1 / 24	15.49	2.47	V	17.96	34.77	-16.81
782.00	5	QPSK	Standard	1 / 24	15.69	2.51	V	18.20	34.77	-16.57
784.50	5	QPSK	Standard	1 / 24	15.39	2.56	V	17.95	34.77	-16.82
779.50	5	16QAM	Standard	1 / 24	14.73	2.47	V	17.20	34.77	-17.57
782.00	5	16QAM	Standard	1 / 24	14.65	2.51	V	17.16	34.77	-17.61
784.50	5	16QAM	Standard	1 / 24	14.50	2.56	V	17.06	34.77	-17.71
782.00	10	QPSK	Standard	1 / 49	15.69	2.51	V	18.20	34.77	-16.57
782.00	10	16QAM	Standard	1 / 49	14.89	2.51	V	17.40	34.77	-17.37

**Table 6-2. ERP Data (Band 13)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 13 of 25	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	Ant. Pol. [H/V]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
824.70	1.4	QPSK	Standard	1 / 5	15.30	2.98	V	18.28	38.45	-20.17
836.50	1.4	QPSK	Standard	1 / 5	14.86	3.04	V	17.90	38.45	-20.55
848.30	1.4	QPSK	Standard	1 / 5	15.41	3.10	V	18.51	38.45	-19.94
824.70	1.4	16-QAM	Standard	1 / 5	14.35	2.98	V	17.33	38.45	-21.12
836.50	1.4	16-QAM	Standard	1 / 5	13.62	3.04	V	16.66	38.45	-21.79
848.30	1.4	16-QAM	Standard	1 / 5	14.61	3.10	V	17.71	38.45	-20.74
825.50	3	QPSK	Standard	1 / 14	14.60	2.98	V	17.58	38.45	-20.87
836.50	3	QPSK	Standard	1 / 14	15.35	3.04	V	18.39	38.45	-20.06
847.50	3	QPSK	Standard	1 / 14	16.21	3.10	V	19.31	38.45	-19.14
825.50	3	16-QAM	Standard	1 / 14	13.71	2.98	V	16.69	38.45	-21.76
836.50	3	16-QAM	Standard	1 / 14	14.24	3.04	V	17.28	38.45	-21.17
847.50	3	16-QAM	Standard	1 / 14	15.32	3.10	V	18.42	38.45	-20.03
826.50	5	QPSK	Standard	1 / 24	15.06	2.99	V	18.05	38.45	-20.40
836.50	5	QPSK	Standard	1 / 24	15.62	3.04	V	18.66	38.45	-19.79
846.50	5	QPSK	Standard	1 / 24	16.40	3.09	V	19.49	38.45	-18.96
826.50	5	16-QAM	Standard	1 / 24	14.08	2.99	V	17.07	38.45	-21.38
836.50	5	16-QAM	Standard	1 / 24	14.53	3.04	V	17.57	38.45	-20.88
846.50	5	16-QAM	Standard	1 / 24	15.35	3.09	V	18.44	38.45	-20.01
829.00	10	QPSK	Standard	1 / 49	16.53	3.00	V	19.53	38.45	-18.92
836.50	10	QPSK	Standard	1 / 49	15.79	3.04	V	18.83	38.45	-19.62
844.00	10	QPSK	Standard	1 / 49	16.66	3.08	V	19.74	38.45	-18.71
829.00	10	16-QAM	Standard	1 / 49	15.61	3.00	V	18.61	38.45	-19.84
836.50	10	16-QAM	Standard	1 / 49	14.92	3.04	V	17.96	38.45	-20.49
844.00	10	16-QAM	Standard	1 / 49	15.58	3.08	V	18.66	38.45	-19.79

**Table 6-3. ERP Data (Band 5)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 14 of 25	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	Standard	1 / 5	16.98	9.28	V	26.26	30.000	-3.74
1732.50	1.4	QPSK	Standard	1 / 3	16.82	9.00	V	25.82	30.000	-4.18
1754.30	1.4	QPSK	Standard	1 / 0	16.70	8.72	V	25.42	30.000	-4.58
1710.70	1.4	16-QAM	Standard	1 / 5	15.71	9.28	V	24.99	30.000	-5.01
1732.50	1.4	16-QAM	Standard	1 / 3	15.92	9.00	V	24.92	30.000	-5.08
1754.30	1.4	16-QAM	Standard	1 / 0	15.54	8.72	V	24.26	30.000	-5.74
1711.50	3	QPSK	Standard	1 / 7	18.26	9.27	V	27.53	30.000	-2.47
1732.50	3	QPSK	Standard	1 / 0	17.45	9.00	V	26.45	30.000	-3.55
1753.50	3	QPSK	Standard	1 / 0	16.70	8.73	V	25.43	30.000	-4.57
1711.50	3	16-QAM	Standard	1 / 7	16.69	9.27	V	25.96	30.000	-4.04
1732.50	3	16-QAM	Standard	1 / 0	16.34	9.00	V	25.34	30.000	-4.66
1753.50	3	16-QAM	Standard	1 / 0	15.54	8.73	V	24.27	30.000	-5.73
1712.50	5	QPSK	Standard	1 / 12	17.99	9.26	V	27.25	30.000	-2.75
1732.50	5	QPSK	Standard	1 / 12	17.11	9.00	V	26.11	30.000	-3.89
1752.50	5	QPSK	Standard	1 / 24	16.29	8.74	V	25.03	30.000	-4.97
1712.50	5	16-QAM	Standard	1 / 12	16.85	9.26	V	26.11	30.000	-3.89
1732.50	5	16-QAM	Standard	1 / 12	16.22	9.00	V	25.22	30.000	-4.78
1752.50	5	16-QAM	Standard	1 / 24	15.68	8.74	V	24.42	30.000	-5.58
1715.00	10	QPSK	Standard	1 / 0	17.42	9.22	V	26.64	30.000	-3.36
1732.50	10	QPSK	Standard	1 / 49	17.09	9.00	V	26.09	30.000	-3.91
1750.00	10	QPSK	Standard	1 / 49	16.80	8.77	V	25.57	30.000	-4.43
1715.00	10	16-QAM	Standard	1 / 0	16.29	9.22	V	25.51	30.000	-4.49
1732.50	10	16-QAM	Standard	1 / 49	15.86	9.00	V	24.86	30.000	-5.14
1750.00	10	16-QAM	Standard	1 / 49	15.74	8.77	V	24.51	30.000	-5.49
1717.50	15	QPSK	Standard	1 / 0	17.37	9.19	V	26.56	30.000	-3.44
1732.50	15	QPSK	Standard	1 / 74	17.30	9.00	V	26.30	30.000	-3.70
1747.50	15	QPSK	Standard	1 / 74	16.85	8.80	V	25.65	30.000	-4.35
1717.50	15	16-QAM	Standard	1 / 0	16.16	9.19	V	25.35	30.000	-4.65
1732.50	15	16-QAM	Standard	1 / 74	16.45	9.00	V	25.45	30.000	-4.55
1747.50	15	16-QAM	Standard	1 / 74	15.77	8.80	V	24.57	30.000	-5.43
1720.00	20	QPSK	Standard	1 / 0	17.52	9.16	V	26.68	30.000	-3.32
1732.50	20	QPSK	Standard	1 / 99	17.25	9.00	V	26.25	30.000	-3.75
1745.00	20	QPSK	Standard	1 / 99	16.90	8.83	V	25.73	30.000	-4.27
1720.00	20	16-QAM	Standard	1 / 0	16.52	9.16	V	25.68	30.000	-4.32
1732.50	20	16-QAM	Standard	1 / 99	16.56	9.00	V	25.56	30.000	-4.44
1745.00	20	16-QAM	Standard	1 / 99	15.82	8.83	V	24.65	30.000	-5.35

**Table 6-4. EIRP Data (Band 4)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 15 of 25	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.70	1.4	QPSK	Standard	1 / 0	14.71	8.34	V	23.05	33.01	-9.96
1880.00	1.4	QPSK	Standard	1 / 5	15.29	8.46	V	23.75	33.01	-9.26
1909.30	1.4	QPSK	Standard	1 / 0	15.35	8.64	V	23.99	33.01	-9.02
1850.70	1.4	16-QAM	Standard	1 / 0	13.61	8.34	V	21.95	33.01	-11.06
1880.00	1.4	16-QAM	Standard	1 / 5	14.75	8.46	V	23.21	33.01	-9.80
1909.30	1.4	16-QAM	Standard	1 / 0	14.16	8.64	V	22.80	33.01	-10.21
1851.50	3	QPSK	Standard	1 / 0	14.72	8.35	V	23.07	33.01	-9.94
1880.00	3	QPSK	Standard	1 / 7	16.12	8.46	V	24.58	33.01	-8.43
1908.50	3	QPSK	Standard	1 / 0	16.05	8.63	V	24.68	33.01	-8.33
1851.50	3	16-QAM	Standard	1 / 0	13.61	8.35	V	21.96	33.01	-11.05
1880.00	3	16-QAM	Standard	1 / 7	15.15	8.46	V	23.61	33.01	-9.40
1908.50	3	16-QAM	Standard	1 / 0	14.93	8.63	V	23.56	33.01	-9.45
1852.50	5	QPSK	Standard	1 / 12	14.70	8.35	V	23.05	33.01	-9.96
1880.00	5	QPSK	Standard	1 / 0	15.50	8.46	V	23.96	33.01	-9.05
1907.50	5	QPSK	Standard	1 / 0	14.62	8.62	V	23.24	33.01	-9.77
1852.50	5	16-QAM	Standard	1 / 12	13.47	8.35	V	21.82	33.01	-11.19
1880.00	5	16-QAM	Standard	1 / 0	14.08	8.46	V	22.54	33.01	-10.47
1907.50	5	16-QAM	Standard	1 / 0	13.70	8.62	V	22.32	33.01	-10.69
1855.00	10	QPSK	Standard	1 / 25	14.97	8.36	V	23.33	33.01	-9.68
1880.00	10	QPSK	Standard	1 / 0	15.53	8.46	V	23.99	33.01	-9.02
1905.00	10	QPSK	Standard	1 / 0	14.72	8.59	V	23.31	33.01	-9.70
1855.00	10	16-QAM	Standard	1 / 25	13.17	8.36	V	21.53	33.01	-11.48
1880.00	10	16-QAM	Standard	1 / 0	14.32	8.46	V	22.78	33.01	-10.23
1905.00	10	16-QAM	Standard	1 / 0	14.06	8.59	V	22.65	33.01	-10.36
1857.50	15	QPSK	Standard	1 / 37	15.11	8.37	V	23.48	33.01	-9.53
1880.00	15	QPSK	Standard	1 / 37	15.83	8.46	V	24.29	33.01	-8.72
1902.50	15	QPSK	Standard	1 / 74	14.99	8.56	V	23.55	33.01	-9.46
1857.50	15	16-QAM	Standard	1 / 37	14.25	8.37	V	22.62	33.01	-10.39
1880.00	15	16-QAM	Standard	1 / 37	15.21	8.46	V	23.67	33.01	-9.34
1902.50	15	16-QAM	Standard	1 / 74	14.30	8.56	V	22.86	33.01	-10.15
1860.00	20	QPSK	Standard	1 / 50	14.10	8.38	V	22.48	33.01	-10.53
1880.00	20	QPSK	Standard	1 / 50	15.10	8.46	V	23.56	33.01	-9.45
1900.00	20	QPSK	Standard	1 / 99	15.73	8.53	V	24.26	33.01	-8.75
1860.00	20	16-QAM	Standard	1 / 50	13.37	8.38	V	21.75	33.01	-11.26
1880.00	20	16-QAM	Standard	1 / 50	14.37	8.46	V	22.83	33.01	-10.18
1900.00	20	16-QAM	Standard	1 / 99	14.96	8.53	V	23.49	33.01	-9.52

**Table 6-5. EIRP Data (Band 2)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 16 of 25	

### 6.3 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) §24.238(a) §27.53(c) §27.53(f) §27.53(h)

#### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

#### Test Procedures Used

KDB 971168 v02r02 – Section 5.8


ANSI/TIA-603-C-2004 – Section 2.2.12

#### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq 2 \times$  span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-2. Test Instrument & Measurement Setup**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet		Page 17 of 25

**Test Notes**

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

OPERATING FREQUENCY: 779.50 MHz  
 CHANNEL: 23205  
 MEASURED OUTPUT POWER: 17.96 dBm = 0.062 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  30.96 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
2338.50	-57.55	3.63	-53.92	V	71.9
3118.00	-58.94	5.13	-53.81	V	71.8

**Table 6-6. Radiated Spurious Data (Band 13 – Low Channel)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 18 of 25	

OPERATING FREQUENCY: 782.00 MHz  
 CHANNEL: 23230  
 MEASURED OUTPUT POWER: 18.20 dBm = 0.066 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  31.20 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
2346.00	-57.60	3.63	-53.97	V	72.2
3128.00	-58.23	5.17	-53.06	V	71.3

Table 6-7. Radiated Spurious Data (Band 13 – Mid Channel)

OPERATING FREQUENCY: 784.50 MHz  
 CHANNEL: 23255  
 MEASURED OUTPUT POWER: 17.95 dBm = 0.062 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 5.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  30.95 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
2353.50	-57.92	3.62	-54.29	V	72.2
3138.00	-58.27	5.21	-53.07	V	71.0

Table 6-8. Radiated Spurious Data (Band 13 – High Channel)

OPERATING FREQUENCY: 782.00 MHz  
 CHANNEL: 23230  
 MEASURED OUTPUT POWER: 18.20 dBm = 0.066 W  
 MODULATION SIGNAL: QPSK  
 DISTANCE: 3 meters  
 NARROWBAND EMISSION LIMIT: -50 dBm  
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	Margin [dB]
1564.00	-61.85	3.69	-58.17	V	-18.2

Table 6-9. Radiated Spurious Data (Band 13 – 1559-1610MHz Band)

OPERATING FREQUENCY: 829.00 MHz  
 CHANNEL: 20450  
 MEASURED OUTPUT POWER: 19.53 dBm = 0.090 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 10.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  32.53 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1658.00	-60.43	3.56	-56.88	V	76.4
2487.00	-56.30	3.52	-52.78	V	72.3
3316.00	-58.07	5.68	-52.38	V	71.9

Table 6-10. Radiated Spurious Data (Band 5 – Low Channel)

OPERATING FREQUENCY: 836.50 MHz  
 CHANNEL: 20525  
 MEASURED OUTPUT POWER: 18.83 dBm = 0.076 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 10.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  31.83 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1673.00	-57.76	3.50	-54.26	V	73.1
2509.50	-57.28	3.53	-53.75	V	72.6
3346.00	-58.05	5.77	-52.29	V	71.1

**Table 6-11. Radiated Spurious Data (Band 5 – Mid Channel)**

OPERATING FREQUENCY: 844.00 MHz  
 CHANNEL: 20600  
 MEASURED OUTPUT POWER: 19.74 dBm = 0.094 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 10.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  32.74 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1688.00	-58.70	3.44	-55.26	V	75.0
2532.00	-56.93	3.58	-53.35	V	73.1
3376.00	-59.94	5.85	-54.10	V	73.8

**Table 6-12. Radiated Spurious Data (Band 5 – High Channel)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet	Page 21 of 25	

OPERATING FREQUENCY: 1711.50 MHz  
 CHANNEL: 19965  
 MEASURED OUTPUT POWER: 27.53 dBm = 0.566 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 3.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  40.53 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3423.00	-51.49	8.15	-43.34	H	70.9
5134.50	-58.25	10.26	-47.99	H	75.5
6846.00	-58.85	11.38	-47.47	H	75.0

**Table 6-13. Radiated Spurious Data (Band 4 – Low Channel)**

OPERATING FREQUENCY: 1732.50 MHz  
 CHANNEL: 20175  
 MEASURED OUTPUT POWER: 26.45 dBm = 0.441 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 3.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  39.45 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3465.00	-50.12	8.29	-41.83	H	68.3
5197.50	-56.87	10.35	-46.53	H	73.0
6930.00	-56.91	11.49	-45.42	H	71.9

**Table 6-14. Radiated Spurious Data (Band 4 – Mid Channel)**

OPERATING FREQUENCY: 1753.50 MHz  
 CHANNEL: 20385  
 MEASURED OUTPUT POWER: 25.43 dBm = 0.349 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 3.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  38.43 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3507.00	-48.52	8.41	-40.11	H	65.5
5260.50	-57.04	10.36	-46.68	H	72.1
7014.00	-57.33	11.57	-45.76	H	71.2

**Table 6-15. Radiated Spurious Data (Band 4 – High Channel)**

OPERATING FREQUENCY: 1851.50 MHz  
 CHANNEL: 18615  
 MEASURED OUTPUT POWER: 23.07 dBm = 0.203 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 3.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.07 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3703.00	-46.35	8.40	-37.95	H	61.0
5554.50	-56.96	10.56	-46.40	H	69.5
7406.00	-56.26	12.05	-44.21	H	67.3

**Table 6-16. Radiated Spurious Data (Band 2 – Low Channel)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet		Page 23 of 25

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 18900  
 MEASURED OUTPUT POWER: 24.58 dBm = 0.287 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 3.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  37.58 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3760.00	-46.60	8.38	-38.22	H	62.8
5640.00	-54.92	10.70	-44.23	H	68.8
7520.00	-57.45	12.10	-45.35	H	69.9

**Table 6-17. Radiated Spurious Data (Band 2 – Mid Channel)**

OPERATING FREQUENCY: 1908.50 MHz  
 CHANNEL: 19185  
 MEASURED OUTPUT POWER: 24.68 dBm = 0.294 W  
 MODULATION SIGNAL: QPSK  
 BANDWIDTH: 3.0 MHz  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  37.68 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3817.00	-46.88	8.40	-38.48	H	63.2
5725.50	-54.81	10.76	-44.05	H	68.7
7634.00	-56.06	12.21	-43.85	H	68.5

**Table 6-18. Radiated Spurious Data (Band 2 – High Channel)**

FCC ID: ZNFVK815		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1503160567.ZNF	Test Dates: 03/17 - 03/31/2015	EUT Type: Portable Tablet		Page 24 of 25

## 7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Tablet FCC ID: ZNFVK815** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules for LTE operation only.

FCC ID: ZNFVK815		<b>FCC Pt. 22, 24, &amp; 27 LTE MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1503160567.ZNF	<b>Test Dates:</b> 03/17 - 03/31/2015	<b>EUT Type:</b> Portable Tablet	Page 25 of 25	