



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com



MEASUREMENT REPORT FCC Part 22, 24

Applicant Name:
LG Electronics MobileComm U.S.A
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:
February 21, 2014
Test Site/Location:
PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
0Y1402170440.ZNF

| | |
|-------------------|--|
| FCC ID: | ZNFVN280 |
| APPLICANT: | LG ELECTRONICS MOBILECOMM U.S.A |

Application Type: Class II Permissive Change
Model(s): LG-VN280, LG-AN280, LG-UN280, LG-VN280PP, LG-AN280PP, LGUN280PP, LG280
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2 §22(H) §24(E)
Test Procedure(s): ANSI/TIA-603-C-2004, KDB 971168 v02r01
Test Device Serial No.: *identical prototype* [S/N: A0000034ADEBBE]
Class II Permissive Change: Please see FCC change documents.
Original Grant Date: January 16, 2014

| Mode | Tx Frequency (MHz) | ERP/EIRP | |
|----------|--------------------|----------------|------------------|
| | | Max. Power (W) | Max. Power (dBm) |
| CDMA850 | 824.70 - 848.31 | 0.095 | 19.77 |
| CDMA1900 | 1851.25 - 1908.75 | 0.420 | 26.23 |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortañez
 President




| | | | | | |
|---|---|--------------------------------------|--|---|--|
| FCC ID: ZNFVN280 |  | | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | | Page 1 of 19 | |

T A B L E O F C O N T E N T S


| | |
|--|----|
| FCC PART 22, 24 MEASUREMENT REPORT | 3 |
| 1.0 INTRODUCTION | 4 |
| 1.1 SCOPE | 4 |
| 1.2 TESTING FACILITY | 4 |
| 2.0 PRODUCT INFORMATION | 5 |
| 2.1 EQUIPMENT DESCRIPTION | 5 |
| 2.2 DEVICE CAPABILITIES | 5 |
| 2.3 TEST CONFIGURATION | 5 |
| 2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS | 5 |
| 3.0 DESCRIPTION OF TESTS | 6 |
| 3.1 EVALUATION PROCEDURE | 6 |
| 3.2 CELLULAR - BASE FREQUENCY BLOCKS | 6 |
| 3.3 CELLULAR - MOBILE FREQUENCY BLOCKS | 6 |
| 3.4 PCS - BASE FREQUENCY BLOCKS | 6 |
| 3.5 PCS - MOBILE FREQUENCY BLOCKS | 7 |
| 3.6 RADIATED MEASUREMENTS | 8 |
| 4.0 TEST EQUIPMENT CALIBRATION DATA | 9 |
| 5.0 SAMPLE CALCULATIONS | 10 |
| 6.0 TEST RESULTS | 11 |
| 6.1 SUMMARY | 11 |
| 6.2 RADIATED POWER (ERP/EIRP) | 12 |
| 6.3 RADIATED SPURIOUS EMISSIONS MEASUREMENTS | 14 |
| 7.0 CONCLUSION | 19 |

| | | | |
|---|--|---|--|
| FCC ID: ZNFVN280 |  FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 2 of 19 |



MEASUREMENT REPORT

FCC Part 22, 24




§2.1033 General Information

APPLICANT: LG Electronics MobileComm U.S.A
APPLICANT ADDRESS: 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632, United States
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2 §22(H) §24(E)
BASE MODEL: LG-VN280
FCC ID: ZNFVN280
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
MODE: CDMA
FREQUENCY TOLERANCE: ±0.00025 % (2.5 ppm)
Test Device Serial No.: A0000034ADEBBE Production Pre-Production Engineering
DATE(S) OF TEST: February 21, 2014
TEST REPORT S/N: 0Y1402170440.ZNF

Test Facility / Accreditations

Measurements were performed at **PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



| | | | |
|---|--|---|--|
| FCC ID: ZNFVN280 |  FCC Pt. 22, 24 CDMA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 3 of 19 |

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on January 10, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

| | | | | |
|--------------------------------------|---|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 4 of 19 | |

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFVN280**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA (BC0, BC1), Bluetooth (1x, EDR)

2.3 Test Configuration

The LG Portable Handset FCC ID: ZNFVN280 was tested per the guidance of ANSI/TIA-603-C-2004 and KDB 971168 v02r01. See Section 6.0 of this test report for a description of the radiated emissions test.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

| | | | | |
|--------------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVN280 |  FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) | |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 5 of 19 | |

3.0 DESCRIPTION OF TESTS


3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 v02r01) were used in the measurement of the **LG Portable Handset FCC ID: ZNFVN280**.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

| | | | | |
|--------------------------------------|---|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 6 of 19 | |

3.5 PCS - Mobile Frequency Blocks

§24.229



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 6: 1895 – 1910 MHz (C)

| | | | | |
|--------------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVN280 |  FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) | |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | | Page 7 of 19 |

3.6 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) RSS-132(4.4) RSS-132(4.5.1) RSS-133(6.4) RSS-133(6.5.1)

Radiated spurious emissions are investigated indoors in a semi-anechoic chamber to determine the frequencies producing the worst case emissions. Final measurements for radiated power and radiated spurious emissions are performed on the 3 meter OATS per the guidelines of ANSI/TIA-603-C-2004. The measurement area is situated on an 18 meter x 20 meter galvanized 1/2" hardware cloth as the conducting ground plane. This material is sewn together in sections 4 feet wide and 60 feet long. A total of eighteen sections are required to cover the entire measurement area. Sections are laid across the width of the pad, overlapped 1" and sewn and soldered together at intervals of 3" (7.6 cm.) The terrain of the test site is reasonably flat and level. Power and cable to the test site are buried 18" deep into the ground outside the perimeter of the site. An all-weather non-metallic housing is situated on a 2 x 3 meter area adjacent to the measurement area to house the test equipment. The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Emissions are also investigated with the receive antenna horizontally and vertically polarized. The level of the maximized emission is recorded with the spectrum analyzer using a peak detector with RBW = 1MHz, VBW = 3MHz for emissions greater than 1GHz. For emissions below 1GHz, the spectrum analyzer is set to RBW = 100kHz and VBW = 300kHz.

A half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$ specified in 22.917(a) and 24.238(a)




Figure 3-1. Diagram of 3-meter Test Range

| | | | | | |
|--------------------------------------|---|-------------------------------|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 8 of 19 | | |

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|---------------|-----------|--|------------|--------------|------------|---------------|
| - | RE1 | Radiated Emissions Cable Set (UHF/EHF) | 3/29/2013 | Annual | 3/29/2014 | N/A |
| - | RE2 | Radiated Emissions Cable Set (VHF/UHF) | 3/29/2013 | Annual | 3/29/2014 | N/A |
| Agilent | 8447D | Broadband Amplifier | 5/31/2013 | Annual | 5/31/2014 | 1937A03348 |
| Agilent | 8449B | (1-26.5GHz) Pre-Amplifier | 4/17/2013 | Annual | 4/17/2014 | 3008A00985 |
| Agilent | 8648D | (9kHz-4GHz) Signal Generator | 10/28/2013 | Annual | 10/28/2014 | 3613A00315 |
| Agilent | E4448A | PSA (3Hz-50GHz) Spectrum Analyzer | 4/18/2013 | Annual | 4/18/2014 | US42510244 |
| Agilent | E5515C | Wireless Communications Test Set | 10/10/2013 | Annual | 10/10/2014 | GB46110872 |
| Agilent | E8257D | (250kHz-20GHz) Signal Generator | 4/16/2013 | Annual | 4/16/2014 | MY45470194 |
| Agilent | N9038A | MXE EMI Receiver | 1/3/2014 | Annual | 1/3/2015 | MY51210133 |
| Anritsu | ML2495A | Power Meter | 10/31/2013 | Annual | 10/31/2014 | 941001 |
| Anritsu | MA2411B | Pulse Sensor | 11/13/2013 | Annual | 11/13/2014 | 846215 |
| Com-Power | AL-130 | 9kHz - 30MHz Loop Antenna | 6/26/2013 | Annual | 6/26/2014 | 121034 |
| Emco | 3115 | Horn Antenna (1-18GHz) | 1/30/2014 | Biennial | 1/30/2016 | 9704-5182 |
| Emco | 6502 | Active Loop Antenna (10k - 30 MHz) | 5/31/2012 | Biennial | 5/31/2014 | 267 |
| ETS Lindgren | 3117 | 1-18 GHz DRG Horn (Medium) | 7/24/2013 | Biennial | 7/24/2015 | 125518 |
| ETS Lindgren | 3160-09 | 18-26.5 GHz Standard Gain Horn | 5/30/2012 | Biennial | 5/30/2014 | 135427 |
| ETS Lindgren | 3164-08 | Quad Ridge Horn Antenna | 11/7/2012 | Biennial | 11/7/2014 | 128338 |
| K & L | 11SH10 | Band Pass Filter | N/A | Annual | N/A | 1300/4000 |
| K & L | 11SH10 | Band Pass Filter | N/A | Annual | N/A | 4000/12000 |
| Mini-Circuits | VHF-1300+ | High Pass Filter | 1/29/2014 | Annual | 1/29/2015 | 30716 |
| Mini-Circuits | VHF-3100+ | High Pass Filter | 1/29/2014 | Annual | 1/29/2015 | 31144 |
| Schwarzbeck | UHA 9105 | Dipole Antenna (400 - 1GHz) Tx | 11/1/2013 | Biennial | 11/1/2015 | 91052522TX |
| Schwarzbeck | UHA 9105 | Dipole Antenna (400 - 1GHz) Rx | 11/1/2013 | Biennial | 11/1/2015 | 91052523RX |
| Seekonk | NC-100 | Torque Wrench (8" lb) | 3/5/2012 | Triennial | 3/5/2015 | N/A |
| Sunol | DRH-118 | Horn Antenna (1 - 18GHz) | 6/19/2013 | Biennial | 6/19/2015 | A050307 |
| Sunol | JB5 | Bi-Log Antenna (30M - 5GHz) | 1/28/2014 | Biennial | 1/28/2016 | A051107 |
| Sunol | DRH-118 | Horn Antenna (1-18 GHz) | 6/19/2013 | Biennial | 6/19/2015 | A042511 |

Table 4-1. Test Equipment

| | | | | |
|--------------------------------------|---|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 9 of 19 | |

5.0 SAMPLE CALCULATIONS

CDMA Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

| | | | | |
|--------------------------------------|---|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 10 of 19 | |

6.0 TEST RESULTS

6.1 Summary

Company Name: LG Electronics MobileComm U.S.A
 FCC ID: ZNFVN280
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): CMDA

| FCC Part Section(s) | Test Description | Test Limit | Test Condition | Test Result | Reference |
|----------------------------------|-------------------------------------|---|----------------|-------------|-------------|
| TRANSMITTER MODE (TX) | | | | | |
| 22.913(a.2) | Effective Radiated Power | < 7 Watts max. ERP | RADIATED | PASS | Section 6.2 |
| 24.232(c) | Equivalent Isotropic Radiated Power | < 2 Watts max. EIRP | | PASS | Section 6.2 |
| 2.1053 22.917(a) 24.238(a) | Radiated Spurious Emissions | > 43 + log ₁₀ (P[Watts]) for all out-of-band emissions | | PASS | Section 6.3 |

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

| | | | | | |
|--------------------------------------|---|-------------------------------|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | | Page 11 of 19 | |

6.2 Radiated Power (ERP/EIRP)

§22.913(a)(2) RSS-132(4.4) [SRSP-503(5.1.3)]

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r01 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”.
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

| | | | | | |
|--------------------------------------|---|-------------------------------|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | | Page 12 of 19 | |

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-1. Test Instrument & Measurement Setup

Test Notes

- 1) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 2) This unit was tested with its standard battery.
- 3) The data reported in the table above was measured in this test setup.

| Frequency [MHz] | Mode | Battery Type | Substitute Level [dBm] | Antenna Gain [dBd] | EUT Pol [H/V] | ERP [dBm] | ERP [Watts] | ERP Limit [dBm] | Margin [dB] |
|-----------------|---------|--------------|------------------------|--------------------|---------------|-----------|-------------|-----------------|-------------|
| 824.70 | CDMA850 | Standard | 20.89 | -1.85 | V | 19.04 | 0.080 | 38.45 | -19.41 |
| 836.52 | CDMA850 | Standard | 21.53 | -1.94 | V | 19.59 | 0.091 | 38.45 | -18.86 |
| 848.31 | CDMA850 | Standard | 21.81 | -2.04 | V | 19.77 | 0.095 | 38.45 | -18.68 |

Table 6-2. ERP (Cellular CDMA)

| Frequency [MHz] | Mode | Battery Type | Substitute Level [dBm] | Antenna Gain [dBi] | EUT Pol [H/V] | EIRP [dBm] | EIRP [Watts] | EIRP Limit [dBm] | Margin [dB] |
|-----------------|----------|--------------|------------------------|--------------------|---------------|------------|--------------|------------------|-------------|
| 1851.25 | CDMA1900 | Standard | 18.07 | 8.16 | V | 26.23 | 0.420 | 33.01 | -6.78 |
| 1880.00 | CDMA1900 | Standard | 16.78 | 8.23 | V | 25.01 | 0.317 | 33.01 | -8.00 |
| 1908.75 | CDMA1900 | Standard | 17.49 | 8.31 | V | 25.80 | 0.380 | 33.01 | -7.21 |

Table 6-3. EIRP (PCS CDMA)

| | | | | | |
|--------------------------------------|---|-------------------------------|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 13 of 19 | | |

6.3 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) RSS-132(4.5.1)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r01 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-2. Test Instrument & Measurement Setup

| | | | | |
|--------------------------------------|---|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | | Page 14 of 19 |

Test Notes

- 1) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 2) This unit was tested with its standard battery.
- 3) The data reported in the table above was measured in this test setup.
- 4) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
- 5) Emissions below 18GHz were measured at a 3 meter test distance.

| | | | | |
|---|--|--------------------------------------|---|--|
| FCC ID: ZNFVN280 |  FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) | |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 15 of 19 | |

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MEASURED OUTPUT POWER: 19.04 dBm = 0.080 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 32.04 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | EUT POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|---------------|-------|
| 1649.40 | -37.56 | 6.34 | -31.22 | V | 50.3 |
| 2474.10 | -53.64 | 6.59 | -47.04 | V | 66.1 |
| 3298.80 | -83.14 | 6.97 | -76.17 | V | 95.2 |
| 4123.50 | -81.51 | 7.61 | -73.90 | V | 92.9 |
| 4948.20 | -81.41 | 9.08 | -72.33 | V | 91.4 |

Table 6-4. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MEASURED OUTPUT POWER: 19.59 dBm = 0.091 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 32.59 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | EUT POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|---------------|-------|
| 1673.04 | -40.59 | 6.19 | -34.40 | V | 54.0 |
| 2509.56 | -53.64 | 6.58 | -47.06 | V | 66.7 |
| 3346.08 | -83.35 | 7.16 | -76.19 | V | 95.8 |
| 4182.60 | -82.08 | 7.99 | -74.08 | V | 93.7 |
| 5019.12 | -80.96 | 8.98 | -71.99 | V | 91.6 |

Table 6-5. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

| | | | | | |
|--------------------------------------|---|-------------------------------|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 16 of 19 | | |

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MEASURED OUTPUT POWER: 19.77 dBm = 0.095 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 32.77 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | EUT POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|---------------|-------|
| 1696.62 | -39.32 | 6.04 | -33.28 | V | 53.1 |
| 2544.93 | -51.85 | 6.71 | -45.14 | V | 64.9 |
| 3393.24 | -83.56 | 7.35 | -76.21 | V | 96.0 |
| 4241.55 | -82.40 | 8.26 | -74.14 | V | 93.9 |
| 5089.86 | -80.33 | 8.84 | -71.49 | V | 91.3 |

Table 6-6. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MEASURED OUTPUT POWER: 26.23 dBm = 0.420 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 39.23 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | EUT POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|---------------|-------|
| 3702.50 | -51.11 | 9.92 | -41.18 | V | 67.4 |
| 5553.75 | -80.48 | 11.11 | -69.36 | V | 95.6 |
| 7405.00 | -75.52 | 10.75 | -64.78 | V | 91.0 |
| 9256.25 | -74.87 | 12.31 | -62.56 | V | 88.8 |
| 11107.50 | -72.36 | 12.90 | -59.46 | V | 85.7 |

Table 6-7. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

| | | | | | |
|--------------------------------------|---|-------------------------------|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  | | FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 17 of 19 | | |

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MEASURED OUTPUT POWER: 25.01 dBm = 0.317 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 38.01 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | EUT POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|---------------|-------|
| 3760.00 | -48.59 | 9.70 | -38.89 | V | 63.9 |
| 5640.00 | -80.61 | 11.25 | -69.36 | V | 94.4 |
| 7520.00 | -75.77 | 10.99 | -64.78 | V | 89.8 |
| 9400.00 | -74.82 | 12.26 | -62.56 | V | 87.6 |
| 11280.00 | -72.41 | 12.95 | -59.46 | V | 84.5 |

Table 6-8. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

OPERATING FREQUENCY: 1908.75 MHz
 CHANNEL: 1175
 MEASURED OUTPUT POWER: 25.80 dBm = 0.380 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 38.80 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | EUT POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|---------------|-------|
| 3817.50 | -39.57 | 9.49 | -30.08 | V | 55.9 |
| 5726.25 | -80.66 | 11.30 | -69.36 | V | 95.2 |
| 7635.00 | -75.99 | 11.22 | -64.78 | V | 90.6 |
| 9543.75 | -74.90 | 12.34 | -62.56 | V | 88.4 |
| 11452.50 | -72.57 | 13.11 | -59.46 | V | 85.3 |

Table 6-9. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFVN280** complies with all the requirements of Parts 2, 22, 24 of the FCC rules.

| | | | |
|--------------------------------------|--|---|---------------------------------|
| FCC ID: ZNFVN280 |  FCC Pt. 22, 24 CMDA MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1402170440.ZNF | Test Dates: February 21, 2014 | EUT Type: Portable Handset | Page 19 of 19 |