

HEARING AID COMPATIBILITY

Applicant Name:

LG Electronics MobileComm U.S.A. Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

01/21/2015 - 01/25/2015

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1601110077-R1.ZNF

FCC ID:

ZNFVS425

APPLICANT:

LG ELECTRONICS MOBILECOMM U.S.A. INC.

Scope of Test:

Audio Band Magnetic Testing (T-Coil)

Application Type:

Certification

FCC Rule Part(s):

CFR §20.19(b)

HAC Standard:

ANSI C63.19-2011

EUT Type:

Portable Handset

Model(s):

VS425, LGVS425, LG-VS425

Test Device Serial No.:

Pre-Production Sample [S/N: 01799]

C63.19-2011 HAC Category:

T3 (SIGNAL TO NOISE CATEGORY)

Note: This revised Test Report (S/N: 0Y1601110077-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: 0Y1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 1 of 74 |

TABLE OF CONTENTS

| | | |
|-----|---|----|
| 1. | INTRODUCTION | 3 |
| 2. | TEST SITE LOCATION | 4 |
| 3. | EUT DESCRIPTION | 5 |
| 4. | ANSI C63.19-2011 PERFORMANCE CATEGORIES | 6 |
| 5. | METHOD OF MEASUREMENT | 8 |
| 6. | VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION | 18 |
| 7. | FCC 3G MEASUREMENTS | 20 |
| 8. | TEST SUMMARY | 22 |
| 9. | MEASUREMENT UNCERTAINTY | 43 |
| 10. | EQUIPMENT LIST | 44 |
| 11. | TEST DATA | 45 |
| 12. | CALIBRATION CERTIFICATES | 62 |
| 13. | CONCLUSION | 69 |
| 14. | REFERENCES | 70 |
| 15. | TEST SETUP PHOTOGRAPHS | 72 |

| | | | | |
|---|--|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  <small>ENGINEERING LABORATORY, INC.</small> | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 2 of 74 |

1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid *in-vitu*

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 3 of 74 |

2. TEST SITE LOCATION

I. Introduction

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC (See Figure 2-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in Stonewood Business Center, Guilford Industrial Park, Columbia, Maryland. The site address is 7185 Oakland Mills Road, Columbia, MD 21046. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 10' 24" N latitude and 76° 49' 50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory.



Figure 2-1
Map of the Greater Baltimore and Metropolitan Washington, D.C. area

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 4 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

3. EUT DESCRIPTION



FCC ID: ZNFVS425
 Applicant: LG Electronics MobileComm U.S.A. Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States
 Model(s): VS425, LGVS425, LG-VS425
 Serial Number: 01799
 HW Version: Rev. 1.0
 SW Version: VS4250LA
 Antenna: Internal Antenna
 HAC Test Configurations: Cellular CDMA, 1013, 384, 777, BT Off, WLAN Off, LTE Off
 PCS CDMA, 25, 600, 1175, BT Off, WLAN Off, LTE Off
 GSM 850, 128, 190, 251, BT Off, WLAN Off, LTE Off
 GSM 1900, 512, 661, 810, BT Off, WLAN Off, LTE Off
 UMTS V, 4132, 4183, 4233, BT Off, WLAN Off, LTE Off
 UMTS II, 9262, 9400, 9538, BT Off, WLAN Off, LTE Off
 LTE FDD B2; BW's: 20MHz, 15MHz, 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off
 LTE FDD B4; BW's: 20MHz, 15MHz, 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off
 LTE FDD B5; BW's: 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off
 LTE FDD B13; BW's: 10MHz, 5MHz; BT Off, WLAN Off
 * Note: LTE test channels for different bands and bandwidths can be found in Sect. 8.II
 EUT Type: Portable Handset

| Air-Interface | Band (MHz) | Type Transport | HAC Tested | Simultaneous But Not Tested | Voice over Digital Transport OTT Capability | WiFi Low Power | Additional GSM Power Reduction |
|--|------------|-----------------|--|------------------------------|---|----------------|--------------------------------|
| GSM | 850 | VO | Yes | Yes: WiFi or BT | N/A | N/A | No |
| | 1900 | VO | Yes | Yes: WiFi or BT | N/A | N/A | No |
| | GPRS/EDGE | DT | No | Yes: WiFi or BT | Yes | N/A | No |
| UMTS | 850 | VD | Yes | Yes: WiFi or BT | N/A | N/A | N/A |
| | 1900 | VD | Yes | Yes: WiFi or BT | N/A | N/A | N/A |
| | HSPA | DT | No | Yes: WiFi or BT | Yes | N/A | N/A |
| CDMA | 835 | VO | Yes | Yes: WiFi or BT | N/A | N/A | N/A |
| | 1900 | VO | Yes | Yes: WiFi or BT | N/A | N/A | N/A |
| | EVDO | DT | No | Yes: WiFi or BT | Yes | N/A | N/A |
| LTE (FDD) | 780 (B13) | VD ¹ | Yes | Yes: WiFi or BT | Yes | N/A | N/A |
| | 850 (B5) | | | | | | |
| | 1700 (B4) | | | | | | |
| | 1900 (B2) | | | | | | |
| WiFi | 2450 | DT | No | Yes: CDMA, GSM, UMTS, or LTE | Yes | N/A | N/A |
| BT | 2450 | DT | No | Yes: CDMA, GSM, UMTS, or LTE | N/A | N/A | N/A |
| Type Transport VO = Voice Only DT = Digital Data - Not intended for CMRS Service VD = CMRS and Data Transport | | | Notes: 1. The 3GPP VoLTE CMRS service is defined by GSMA in PRD IR.92 for IP Voice Service and Digital Transport. | | | | |

Table 3-1: ZNFVS425 HAC Air Interfaces

| | | | | |
|----------------------------------|--|-------------------------------|--|---------------------------------|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 5 of 74 |

4. ANSI C63.19-2011 PERFORMANCE CATEGORIES

I. MAGNETIC COUPLING

Axial and Radial Field Intensity

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be ≥ -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 4-1
Magnetic field frequency response for Wireless Devices with an axial field ≤ -15 dB(A/m) at 1 kHz




Figure 4-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds -15 dB(A/m) at 1 kHz

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 6 of 74 |

Signal Quality

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

| Category | Telephone RF Parameters |
|----------|---|
| | Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB] |
| T1 | 0 to 10 dB |
| T2 | 10 to 20 dB |
| T3 | 20 to 30 dB |
| T4 | > 30 dB |

Table 4-1
Magnetic Coupling Parameters

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 7 of 74 |

5. METHOD OF MEASUREMENT

I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 5-1
Validation Setup with Helmholtz Coil




Figure 5-2
T-Coil Test Setup

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 8 of 74 |

II. Scanning Mechanism

Manufacturer: TEM
 Accuracy: ± 0.83 cm/meter
 Minimum Step Size: 0.1 mm
 Maximum speed: 6.1 cm/sec
 Line Voltage: 115 VAC
 Line Frequency: 60 Hz
 Material Composite: Delrin (Acetal)
 Data Control: Parallel Port
 Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm
 Dimensions: 36" x 25" x 38"
 Operating Area: 36" x 49" x 55"
 Reflections: < -20 dB (in anechoic chamber)




Figure 5-3
RF Near-Field Scanner

III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T
 Active Frequency Range: 100 Hz – 8 kHz
 Stimulus Type: Male and Female, no spaces
 Single Sample Duration: 20.96 seconds
 Activity Level: 100%




Figure 5-4
Spectral Characteristic of full P.50





Figure 5-5
Temporal Characteristic of full P.50

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 9 of 74 |

ABM1 Measurement Block Diagram:



ABM2 Measurement Block Diagram:




Figure 5-6 Magnetic Measurement Processing Steps

IV. Test Procedure

1. Ambient Noise Check per C63.19 §7.3.1
 - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
 - b. “A-weighting” and Half-Band Integration was applied to the measurements.
 - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

$$-18 - 30 - 10 = -58 \text{ dBA/m}$$
2. Measurement System Validation(See Figure 5-1)
 - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
 - b. ABM1 Validation
 The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N\left(\frac{V}{R}\right)}{r\sqrt{1.25^3}}$$

Where H_c = magnetic field strength in amperes per meter
 N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.13m; R=10.193Ω and using V=29mV:

$$H_c = \frac{20 \cdot \left(\frac{0.029}{10.193}\right)}{0.13 \cdot \sqrt{1.25^3}} = 0.316 \text{ A/m} \approx -10 \text{ dB(A/m)}$$

Therefore a pure tone of 1kHz was applied into the coils such that 29mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of -10 dB(A/m) in the center of the Helmholtz coil which was used to validate the probe measurement at -10dB(A/m). This was verified to be within ± 0.5 dB of the -10dB(A/m) value (see Page 41).

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 10 of 74 |

c. Frequency Response Validation

The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:




Figure 5-7 Frequency Response Validation

d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

**Table 5-1
ABM2 Frequency Response Validation**

| f (Hz) | HBI, A - Measured (dB re 1kHz) | HBI, A - Theoretical (dB re 1kHz) | dB Var. |
|--------|--------------------------------|-----------------------------------|---------|
| 100 | -16.180 | -16.170 | -0.010 |
| 125 | -13.257 | -13.250 | -0.007 |
| 160 | -10.347 | -10.340 | -0.007 |
| 200 | -8.017 | -8.010 | -0.007 |
| 250 | -5.925 | -5.920 | -0.005 |
| 315 | -4.045 | -4.040 | -0.005 |
| 400 | -2.405 | -2.400 | -0.005 |
| 500 | -1.212 | -1.210 | -0.002 |
| 630 | -0.349 | -0.350 | 0.001 |
| 800 | 0.071 | 0.070 | 0.001 |
| 1000 | 0.000 | 0.000 | 0.000 |
| 1250 | -0.503 | -0.500 | -0.003 |
| 1600 | -1.513 | -1.510 | -0.003 |
| 2000 | -2.778 | -2.780 | 0.002 |
| 2500 | -4.316 | -4.320 | 0.004 |
| 3150 | -6.166 | -6.170 | 0.004 |
| 4000 | -8.322 | -8.330 | 0.008 |
| 5000 | -10.573 | -10.590 | 0.017 |
| 6300 | -13.178 | -13.200 | 0.022 |
| 8000 | -16.241 | -16.270 | 0.029 |
| 10000 | -19.495 | -19.520 | 0.025 |

| | | | | |
|----------------------------------|--|-------------------------------|--|---------------------------------|
| FCC ID: ZNFVS425 | PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 11 of 74 |




Figure 5-8
ABM2 Frequency Response Validation

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 5-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:




Figure 5-9
ABM2 Validation Block Diagram

The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 5-2
ABM2 Power Sum Validation

| WN Input (dBV) | Power Sum (dBV) | Multimeter-Full (dBV) | Dev (dB) |
|----------------|-----------------|-----------------------|----------|
| -60 | -60.36 | -60.2 | 0.16 |
| -50 | -50.19 | -50.13 | 0.06 |
| -40 | -40.14 | -40.03 | 0.11 |
| -30 | -30.13 | -30.01 | 0.12 |
| -20 | -20.12 | -20 | 0.12 |
| -10 | -10.14 | -10 | 0.14 |

| | | | | |
|----------------------------------|--|-------------------------------|--|---------------------------------|
| FCC ID: ZNFVS425 | PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 12 of 74 |




Figure 5-10
ABM2 Power Sum Validation

3. Measurement Test Setup

a. Fine scan above the WD (TEM)

- i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below:




Figure 5-11
Measurement Distance

- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 5-15 after a T-coil orientation was fully measured with the SoundCheck system.

b. Speech Signal Setup to Base Station Simulator

- i. C63.19 Table 7-1 states audio reference input levels for various technologies:

| Standard | Technology | Input Level (dBm0) |
|-----------------|---------------------|--------------------|
| TIA/EIA/IS-2000 | CDMA | -18 |
| J-STD-007 | GSM (217) | -16 |
| T1/T1P1/3GPP | UMTS (WCDMA) | -16 |
| iDEN™ | TDMA (22 and 11 Hz) | -18 |


| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 13 of 74 |

The CMU200 audio levels were determined using base station simulator manufacturer calibration procedures resulting in the below corresponding voltages relative to handset test point level (in dBm0):

**Table 5-3
CMU200 Voltage Input Levels for Audio**

| dBm0 Ref. | Input Voltage | | Notes |
|-----------|---------------|-----------|---|
| 3.14 dBm0 | 1052.0 mV | 0.4 dBV | From CDMA2K "DECODER CAL". (What is needed through Encoder for FS) |
| -18 dBm0 | 92.260 mV | -20.7 dBV | For 8k Enhanced (Low) |
| dBm0 Ref. | Voltage | | Notes |
| 3.14 dBm0 | 990.5 mV | -0.08 dBV | From GSM "DECODER CAL". (What is needed through Encoder for FS) |
| -16 dBm0 | 109.4 mV | -19.2 dBV | For Speechcod/Handset Low |
| dBm0 Ref. | Voltage | | Notes |
| 3.14 dBm0 | 1068.5 mV | 0.58 dBV | From UMTS "DECODER CAL". (What is needed through Encoder for FS) |
| -16 dBm0 | 118.0 mV | -18.6 dBV | For Handset Low |

- ii. See Section 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE) testing.
- c. Real-Time Analyzer (RTA)
 - i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.
- d. WD Radio Configuration Selection
 - i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 7 for more information regarding worst-case configurations for CDMA and UMTS. LTE configuration information can be found in Section 6):



**Figure 5-12
Vocoder Analysis for ABM Noise for GSM**

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 14 of 74 | |

4. Signal Quality Data Analysis
 - a. Narrow-band Magnetic Intensity
 - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.
 - b. Frequency Response
 - i. The appropriate frequency response curve was measured to curves in Figure 4-1 or Figure 4-2 between 300 – 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
 - ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 5-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
 - iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.
 - c. Signal Quality Index
 - i. Ensuring the WD was at maximum RF power, maximum volume, backlight on, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz – 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
 - ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
 - iii. This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

V. Test Setup




Figure 5-13
Audio Magnetic Field Test Setup

VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to inaccessible RF ports.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 15 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS were tested for T-coil. See Table 3-1 for more details regarding which modes were tested.

According to the April 2013 TCB workshop slides, WIFI and other OTT data services are outside the current definition of a managed CMRS service and are currently not required to be evaluated.

VIII. Wireless Device Channels and Frequencies

1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band.


**Table 5-4
Center Channels and Frequencies**

| Test frequencies & associated channels | |
|--|-----------------|
| Channel | Frequency (MHz) |
| Cellular 850 | |
| 384 (CDMA) | 836.52 |
| 190 (GSM) | 836.60 |
| 4183 (UMTS) | 836.60 |
| PCS 1900 | |
| 600 (CDMA) | 1880 |
| 661 (GSM) | 1880 |
| 9400 (UMTS) | 1880 |

2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. See Tables 8-12 through 8-21 for LTE bandwidths and channels.

IX. RF Emission Effect on T-coil Measurements



**Figure 5-14
High power RF Emissions Effect with HAC Dipole on the T-coil Probe System 10mm between dipole maximum and magnetic probe**

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 16 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

X. Test Flow

The flow diagram below was followed (From C63.19):




Figure 5-15
C63.19 T-Coil Signal Test Process

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 17 of 74 |

6. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoLTE T-coil Testing

1. Equipment Setup

The general test setup used for VoLTE is shown below (adopted from FCC KDB 285076 D02). The callbox used when performing VoLTE T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1
Test Setup for VoLTE T-Coil Measurements

2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for LTE T-coil testing, -16dBm0 shall be used for the normal speech input level. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE connection.

* http://c63.org/documents/misc/posting/new_interpretations.htm

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 18 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

II. DUT Configuration for VoLTE T-coil Testing

1. Radio Configuration

An investigation was performed on the worst-case LTE Band and bandwidth combination to determine the modulation and RB configuration to be used for testing. 16QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

| Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | ABM1 [dB(A/m)] | ABM2 [dB(A/m)] | SNNR [dB] |
|-----------------|---------|-----------------|------------|---------|-----------|----------------|----------------|-----------|
| 1880.0 | 18900 | 20 | QPSK | 1 | 0 | 3.07 | -27.99 | 31.06 |
| 1880.0 | 18900 | 20 | QPSK | 1 | 50 | 3.02 | -27.40 | 30.42 |
| 1880.0 | 18900 | 20 | QPSK | 1 | 99 | 2.95 | -27.08 | 30.03 |
| 1880.0 | 18900 | 20 | QPSK | 50 | 0 | 3.04 | -27.93 | 30.97 |
| 1880.0 | 18900 | 20 | QPSK | 50 | 25 | 3.07 | -29.92 | 32.99 |
| 1880.0 | 18900 | 20 | QPSK | 50 | 50 | 3.09 | -30.10 | 33.19 |
| 1880.0 | 18900 | 20 | QPSK | 100 | 0 | 3.10 | -30.22 | 33.32 |
| 1880.0 | 18900 | 20 | 16QAM | 1 | 0 | 2.94 | -25.92 | 28.86 |
| 1880.0 | 18900 | 20 | 16QAM | 1 | 50 | 3.24 | -25.69 | 28.93 |
| 1880.0 | 18900 | 20 | 16QAM | 1 | 99 | 3.04 | -26.40 | 29.44 |
| 1880.0 | 18900 | 20 | 16QAM | 50 | 0 | 2.97 | -28.62 | 31.59 |
| 1880.0 | 18900 | 20 | 16QAM | 50 | 25 | 3.02 | -28.34 | 31.36 |
| 1880.0 | 18900 | 20 | 16QAM | 50 | 50 | 3.05 | -27.75 | 30.80 |
| 1880.0 | 18900 | 20 | 16QAM | 100 | 0 | 3.12 | -27.21 | 30.33 |

Figure 6-2
LTE SNNR by Radio Configuration

2. Codec Configuration

An investigation was performed on the worst-case LTE Band and bandwidth combination to determine the audio codec configuration to be used for testing. The NB AMR 12.2kbps setting was used for the audio codec on the CMW500 for VoLTE T-coil testing. See below table for ABM1 and ABM2 comparisons between different codecs and codec data rates:

| Codec Setting: | WB AMR 12.65kbps | NB AMR 12.2kbps | Orientation | Channel |
|--|------------------|-----------------|-------------|-----------------------|
| ABM1 Pre-test (dBA/m) | 5.21 | 4.95 | Radial | 18900 (LTE B2, 20MHz) |
| ABM2 Pre-test (dBA/m) (A-weight, Half-Band Int.) | -27.38 | -25.68 | | |
| S+N/N (dB) | 32.59 | 30.63 | | |

Table 6-1
FCC 4G ABM Measurements for ZNFVS425

- Mute on; Backlight on; Max Volume; Max Contrast
- TPC = "Max Power"




Figure 6-3
Audio Band Magnetic Curve Measurement Block Diagram

| | | | | |
|----------------------------------|--|-------------------------------|--|---------------------------------|
| FCC ID: ZNFVS425 | PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 19 of 74 |

7. FCC 3G MEASUREMENTS

I. CDMA Test Configurations

Radio Configuration 1, Service Option 3 (thick, green data curve) was used for the testing as the worst-case configuration for the handset due to vocoder gating from the EVRC logic. See below plot for ABM noise comparison between operational field service options and radio configurations for a CDMA2000 handset:




Figure 7-1
CDMA Audio Band Magnetic Noise

II. UMTS Test Configurations

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:



Figure 7-2
UMTS Audio Band Magnetic Noise

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 20 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M

12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

III. ABM Measurements

**Table 7-1
FCC 3G ABM Measurements for ZNFVS425 (CDMA)**


| Codec Setting: | RC1/SO3 | RC3/SO3 | RC4/SO3 | Orientation | Channel |
|---|---------|---------|---------|-------------|---------|
| ABM1 Pre-test (dBA/m) | 3.08 | 3.34 | 2.92 | Axial | 1175 |
| ABM2 Pre-test (dBA/m) (A-weight, Half-Band Int.) | -21.80 | -44.32 | -44.18 | | |
| S+N/N (dB) | 24.88 | 47.66 | 47.10 | | |

- Mute on; Backlight on; Max Volume; Max Contrast
- Power Control Bits = "All Up"

**Table 7-2
FCC 3G ABM Measurements for ZNFVS425 (UMTS)**

| Codec Setting: | AMR 12.2kbps | AMR 7.95kbps | AMR 4.75kbps | Orientation | Channel |
|---|--------------|--------------|--------------|-------------|---------|
| ABM1 Pre-test (dBA/m) | 6.25 | 6.29 | 6.08 | Radial | 9538 |
| ABM2 Pre-test (dBA/m) (A-weight, Half-Band Int.) | -37.66 | -37.93 | -39.98 | | |
| S+N/N (dB) | 43.91 | 44.22 | 46.06 | | |

- Mute on; Backlight on; Max Volume; Max Contrast
- TPC="All 1s"



**Figure 7-3
Audio Band Magnetic Curve Measurement Block Diagram**

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 21 of 74 |

8. TEST SUMMARY

I. T-Coil Test Summary

Table 8-1
Table of Results for CDMA

| C63.19 Sec. | Mode | Band | Test Description | Minimum Limit* | Measured | Verdict |
|-------------|------|----------|-------------------------------|----------------|--------------|------------------|
| | | | | <i>dBa/m</i> | <i>dBa/m</i> | <i>PASS/FAIL</i> |
| 8.3.1 | CDMA | Cellular | Intensity, Axial | -18 | 2.9 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 3.6 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 28.5 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 29.1 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 1.9 | PASS |
| 8.3.1 | CDMA | PCS | Intensity, Axial | -18 | 2.8 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 3.7 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 24.3 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 24.4 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 1.9 | PASS |

Note: The above summary table represents the worst-case numerical values according to configurations in Table 8-9.

Table 8-2
Table of Results for GSM

| C63.19 Sec. | Mode | Band | Test Description | Minimum Limit* | Measured | Verdict |
|-------------|------|----------|-------------------------------|----------------|--------------|------------------|
| | | | | <i>dBa/m</i> | <i>dBa/m</i> | <i>PASS/FAIL</i> |
| 8.3.1 | GSM | Cellular | Intensity, Axial | -18 | 7.0 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 6.3 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 36.3 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 22.2 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | GSM | PCS | Intensity, Axial | -18 | 6.9 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 6.4 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 38.6 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 24.9 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |

Note: The above summary table represents the worst-case numerical values according to configurations in Table 8-10.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 22 of 74 |

Table 8-3
Table of Results for UMTS

| C63.19 Sec. | Mode | Band | Test Description | Minimum Limit* | Measured | Verdict |
|-------------|------|----------|-------------------------------|----------------|--------------|------------------|
| | | | | <i>dBA/m</i> | <i>dBA/m</i> | <i>PASS/FAIL</i> |
| 8.3.1 | UMTS | Cellular | Intensity, Axial | -18 | 7.1 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 6.3 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 48.7 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 44.3 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | UMTS | PCS | Intensity, Axial | -18 | 7.1 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 6.3 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 49.0 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 43.5 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |

Note: The above summary table represents the worst-case numerical values according to configurations in Table 8-11.

Table 8-4
Table of Results for LTE B13

| C63.19 Sec. | Mode | BW/Band | Test Description | Minimum Limit* | Measured | Verdict |
|-------------|------|-------------------|-------------------------------|----------------|--------------|------------------|
| | | | | <i>dBA/m</i> | <i>dBA/m</i> | <i>PASS/FAIL</i> |
| 8.3.1 | LTE | 5MHz/ Band 13 | Intensity, Axial | -18 | 8.5 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 40.1 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 33.8 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 10MHz/ Band 13 | Intensity, Axial | -18 | 8.5 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.9 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 37.2 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 31.8 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |

Note: The above summary table represents the worst-case numerical values according to configurations in Table 8-12.

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 23 of 74 |

Table 8-5
Table of Results for LTE B5

| C63.19 Sec. | Mode | BW/Band | Test Description | Minimum Limit* | Measured | Verdict |
|-------------|------|-------------------|-------------------------------|----------------|--------------|------------------|
| | | | | <i>dBa/m</i> | <i>dBa/m</i> | <i>PASS/FAIL</i> |
| 8.3.1 | LTE | 1.4MHz/ Band 5 | Intensity, Axial | -18 | 8.5 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.7 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 38.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 32.9 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 3MHz/ Band 5 | Intensity, Axial | -18 | 8.7 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.9 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 40.4 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 33.4 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 5MHz/ Band 5 | Intensity, Axial | -18 | 8.8 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 42.1 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 34.7 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 10MHz/ Band 5 | Intensity, Axial | -18 | 8.4 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 40.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 33.9 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |

Note: The above summary table represents the worst-case numerical values according to configurations in Tables 8-13 and 8-14.

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 24 of 74 | |

Table 8-6
Table of Results for LTE B4

| C63.19 Sec. | Mode | BW/Band | Test Description | Minimum Limit* | Measured | Verdict |
|-------------|------|-------------------|-------------------------------|----------------|--------------|------------------|
| | | | | <i>dBA/m</i> | <i>dBA/m</i> | <i>PASS/FAIL</i> |
| 8.3.1 | LTE | 1.4MHz/ Band 4 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 36.4 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 31.4 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 3MHz/ Band 4 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 37.5 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 31.6 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 5MHz/ Band 4 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.6 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 39.3 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 33.7 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 10MHz/ Band 4 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 37.4 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 32.0 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 15MHz/ Band 4 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.7 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 35.2 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 30.1 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 20MHz/ Band 4 | Intensity, Axial | -18 | 8.3 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 35.9 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 30.1 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |

Note: The above summary table represents the worst-case numerical values according to configurations in Tables 8-15 through 8-17.

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 25 of 74 |

Table 8-7
Table of Results for LTE B2

| C63.19 Sec. | Mode | BW/Band | Test Description | Minimum Limit* | Measured | Verdict |
|-------------|------|-------------------|-------------------------------|----------------|--------------|------------------|
| | | | | <i>dBA/m</i> | <i>dBA/m</i> | <i>PASS/FAIL</i> |
| 8.3.1 | LTE | 1.4MHz/ Band 2 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.9 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 34.6 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 31.3 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 3MHz/ Band 2 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.9 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 35.6 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 32.2 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 5MHz/ Band 2 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.8 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 37.7 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 33.9 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 10MHz/ Band 2 | Intensity, Axial | -18 | 8.2 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.9 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 35.2 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 31.5 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 15MHz/ Band 2 | Intensity, Axial | -18 | 8.0 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.9 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 34.0 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 31.5 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |
| 8.3.1 | LTE | 20MHz/ Band 2 | Intensity, Axial | -18 | 8.1 | PASS |
| 8.3.1 | | | Intensity, Radial | -18 | 4.7 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Axial | 20 | 35.3 | PASS |
| 8.3.4 | | | Signal-to-Noise/Noise, Radial | 20 | 30.0 | PASS |
| 8.3.2 | | | Frequency Response, Axial | 0 | 2.0 | PASS |

Note: The above summary table represents the worst-case numerical values according to configurations in Tables 8-18 through 8-21.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 26 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

**Table 8-8
Consolidated Tabled Results**

| | | Freq. Response Margin | | Magnetic Intensity Verdict | | FCC SNNR Verdict | | C63.19-2011 RATING |
|------|----------|-----------------------|--------|----------------------------|--------|------------------|--------|--------------------|
| | | Axial | Radial | Axial | Radial | Axial | Radial | |
| CDMA | Cellular | PASS | NA | PASS | PASS | PASS | PASS | T3 |
| | PCS | PASS | NA | PASS | PASS | PASS | PASS | |
| GSM | Cellular | PASS | NA | PASS | PASS | PASS | PASS | T3 |
| | PCS | PASS | NA | PASS | PASS | PASS | PASS | |
| UMTS | Cellular | PASS | NA | PASS | PASS | PASS | PASS | T4 |
| | PCS | PASS | NA | PASS | PASS | PASS | PASS | |
| LTE | B13 | PASS | NA | PASS | PASS | PASS | PASS | T4 |
| | B5 | PASS | NA | PASS | PASS | PASS | PASS | |
| | B4 | PASS | NA | PASS | PASS | PASS | PASS | |
| | B2 | PASS | NA | PASS | PASS | PASS | PASS | |

Note: Result shown is for T-coil category only.

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 27 of 74 |

II. Raw Handset Data

**Table 8-9
Raw Data Results for CDMA**

| | Volume | Cellular Band | | | | | |
|------------------------------------|---------|------------------------|----------|--------|-----------|----------|--------|
| | | Axial | | | Radial | | |
| | | 1013 | 384 | 777 | 1013 | 384 | 777 |
| ABM1, dBA/m | Maximum | 2.91 | 3.27 | 2.90 | 3.58 | 3.62 | 3.73 |
| ABM2, dBA/m | | -25.90 | -26.56 | -25.57 | -25.53 | -26.28 | -25.50 |
| Ambient Noise, dBA/m | | -63.40 | -63.40 | -63.40 | -63.26 | -63.26 | -63.26 |
| Freq. Response Margin (dB) | | 1.88 | 2.00 | 2.00 | N/A | N/A | N/A |
| S+N/N (dB) | | 28.81 | 29.83 | 28.47 | 29.11 | 29.90 | 29.23 |
| S+N/N per orientation (dB) | | 28.47 | | | 29.11 | | |
| C63.19-2011 Rating per orientation | | T3 | | | T3 | | |
| | | | | | | | |
| | Volume | PCS Band | | | | | |
| | | Axial | | | Radial | | |
| | | 25 | 600 | 1175 | 25 | 600 | 1175 |
| ABM1, dBA/m | Maximum | 2.97 | 2.82 | 2.82 | 3.68 | 3.73 | 3.75 |
| ABM2, dBA/m | | -24.12 | -23.37 | -21.45 | -24.09 | -22.53 | -20.66 |
| Ambient Noise, dBA/m | | -63.40 | -63.40 | -63.40 | -63.26 | -63.26 | -63.26 |
| Freq. Response Margin (dB) | | 1.94 | 1.91 | 1.93 | N/A | N/A | N/A |
| S+N/N (dB) | | 27.09 | 26.19 | 24.27 | 27.77 | 26.26 | 24.41 |
| S+N/N per orientation (dB) | | 24.27 | | | 24.41 | | |
| C63.19-2011 Rating per orientation | | T3 | | | T3 | | |
| T-coil Coordinates (cm) | | [x,y] from bottom left | 1.7, 1.3 | | | 1.3, 2.5 | |

Notes:

1. Power Configuration: Power Control Bits = "All Up"
2. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
3. Vocoder Configuration: RC1/SO3 (CDMA - EVRC)
4. 'Radial' orientation refers to radial transverse.
5. Speech Signal: ITU-T P.50 Artificial Voice
6. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 28 of 74 |

**Table 8-10
Raw Data Results for GSM**

| | Volume | Cellular Band | | | | | |
|------------------------------------|------------------------|---------------|--------|--------|-----------|--------|--------|
| | | Axial | | | Radial | | |
| | | 128 | 190 | 251 | 128 | 190 | 251 |
| ABM1, dBA/m | Maximum | 7.06 | 7.19 | 7.02 | 6.38 | 6.31 | 6.41 |
| ABM2, dBA/m | | -31.05 | -30.05 | -29.24 | -17.33 | -16.48 | -15.81 |
| Ambient Noise, dBA/m | | -63.40 | -63.40 | -63.40 | -63.26 | -63.26 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | 2.00 | 2.00 | N/A | N/A | N/A |
| S+N/N (dB) | | 38.11 | 37.24 | 36.26 | 23.71 | 22.79 | 22.22 |
| S+N/N per orientation (dB) | | 36.26 | | | 22.22 | | |
| C63.19-2011 Rating per orientation | | T4 | | | T3 | | |
| | | | | | | | |
| | Volume | PCS Band | | | | | |
| | | Axial | | | Radial | | |
| | | 512 | 661 | 810 | 512 | 661 | 810 |
| ABM1, dBA/m | Maximum | 7.04 | 6.93 | 7.00 | 6.45 | 6.45 | 6.41 |
| ABM2, dBA/m | | -31.97 | -31.80 | -31.61 | -18.63 | -18.64 | -18.44 |
| Ambient Noise, dBA/m | | -63.40 | -63.40 | -63.40 | -63.26 | -63.26 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | 2.00 | 2.00 | N/A | N/A | N/A |
| S+N/N (dB) | | 39.01 | 38.73 | 38.61 | 25.08 | 25.09 | 24.85 |
| S+N/N per orientation (dB) | | 38.61 | | | 24.85 | | |
| C63.19-2011 Rating per orientation | | T4 | | | T3 | | |
| | | | | | | | |
| T-coil Coordinates (cm) | [x,y] from bottom left | 1.7, 1.3 | | | 1.3, 2.5 | | |

Notes:

1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
2. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
3. Vocoder Configuration: EFR (GSM);
4. 'Radial' orientation refers to radial transverse.
5. Speech Signal: ITU-T P.50 Artificial Voice
6. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 29 of 74 |

**Table 8-11
Raw Data Results for UMTS**

| | Volume | Cellular Band | | | | | |
|------------------------------------|------------------------|---------------|--------|--------|-----------|--------|--------|
| | | Axial | | | Radial | | |
| | | 4132 | 4183 | 4233 | 4132 | 4183 | 4233 |
| ABM1, dBA/m | Maximum | 7.09 | 7.18 | 7.19 | 6.34 | 6.39 | 6.27 |
| ABM2, dBA/m | | -41.61 | -41.82 | -41.57 | -38.18 | -38.33 | -38.07 |
| Ambient Noise, dBA/m | | -63.40 | -63.40 | -63.40 | -63.26 | -63.26 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | 2.00 | 2.00 | N/A | N/A | N/A |
| S+N/N (dB) | | 48.70 | 49.00 | 48.76 | 44.52 | 44.72 | 44.34 |
| S+N/N per orientation (dB) | | 48.70 | | | 44.34 | | |
| C63.19-2011 Rating per orientation | | T4 | | | T4 | | |
| | Volume | PCS Band | | | | | |
| | | Axial | | | Radial | | |
| | | 9262 | 9400 | 9538 | 9262 | 9400 | 9538 |
| ABM1, dBA/m | Maximum | 7.16 | 7.14 | 7.18 | 6.28 | 6.28 | 6.26 |
| ABM2, dBA/m | | -41.81 | -44.51 | -44.49 | -38.16 | -38.01 | -37.20 |
| Ambient Noise, dBA/m | | -63.40 | -63.40 | -63.40 | -63.26 | -63.26 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | 2.00 | 2.00 | N/A | N/A | N/A |
| S+N/N (dB) | | 48.97 | 51.65 | 51.67 | 44.44 | 44.29 | 43.46 |
| S+N/N per orientation (dB) | | 48.97 | | | 43.46 | | |
| C63.19-2011 Rating per orientation | | T4 | | | T4 | | |
| T-coil Coordinates (cm) | [x,y] from bottom left | 1.7, 1.3 | | | 1.3, 2.5 | | |

Notes:

1. Power Configuration: TPC="All 1s";
2. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
3. Vocoder Configuration: AMR 12.2 kbps (UMTS);
4. 'Radial' orientation refers to radial transverse.
5. Speech Signal: ITU-T P.50 Artificial Voice
6. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 30 of 74 |

**Table 8-12
Raw Data Results for LTE B13 (5MHz and 10MHz BW's)**

| | Volume | 5MHz BW | |
|------------------------------------|------------------------|-----------|-----------|
| | | Axial | Radial |
| | | 23230 | 23230 |
| ABM1, dBA/m | Maximum | 8.54 | 4.79 |
| ABM2, dBA/m | | -31.54 | -29.03 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 40.08 | 33.82 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| | Volume | 10MHz BW | |
| | | Axial | Radial |
| | | 23230 | 23230 |
| ABM1, dBA/m | Maximum | 8.47 | 4.87 |
| ABM2, dBA/m | | -28.71 | -26.89 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 37.18 | 31.76 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| T-coil Coordinates (cm) | [x,y] from bottom left | 1.7, 1.3 | 1.3, 2.5 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 31 of 74 |

**Table 8-13
Raw Data Results for LTE B5 (1.4MHz and 3MHz BW's)**

| | | 1.4MHz BW | |
|------------------------------------|---------|------------------------|-----------|
| | | Axial | Radial |
| Volume | | 20525 | 20525 |
| ABM1, dBA/m | Maximum | 8.53 | 4.74 |
| ABM2, dBA/m | | -30.23 | -28.12 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 38.76 | 32.86 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| | | 3MHz BW | |
| | | Axial | Radial |
| Volume | | 20525 | 20525 |
| ABM1, dBA/m | Maximum | 8.68 | 4.87 |
| ABM2, dBA/m | | -31.67 | -28.49 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 40.35 | 33.36 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| T-coil Coordinates (cm) | | [x,y] from bottom left | 1.7, 1.3 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 32 of 74 |

**Table 8-14
Raw Data Results for LTE B5 (5MHz and 10MHz BW's)**

| | Volume | 5MHz BW | |
|------------------------------------|---------|------------------------|-----------|
| | | Axial | Radial |
| | | 20525 | 20525 |
| ABM1, dBA/m | Maximum | 8.76 | 4.83 |
| ABM2, dBA/m | | -33.29 | -29.87 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 42.05 | 34.70 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| | Volume | 10MHz BW | |
| | | Axial | Radial |
| | | 20525 | 20525 |
| ABM1, dBA/m | Maximum | 8.42 | 4.80 |
| ABM2, dBA/m | | -32.35 | -29.12 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 40.77 | 33.92 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| T-coil Coordinates (cm) | | [x,y] from bottom left | 1.7, 1.3 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 33 of 74 |

**Table 8-15
Raw Data Results for LTE B4 (1.4MHz and 3MHz BW's)**

| | | 1.4MHz BW | |
|------------------------------------|---------|------------------------|-----------|
| | | Axial | Radial |
| Volume | | 20175 | 20175 |
| ABM1, dBA/m | Maximum | 8.17 | 4.78 |
| ABM2, dBA/m | | -28.25 | -26.66 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 36.42 | 31.44 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| | | 3MHz BW | |
| | | Axial | Radial |
| Volume | | 20175 | 20175 |
| ABM1, dBA/m | Maximum | 8.21 | 4.83 |
| ABM2, dBA/m | | -29.24 | -26.72 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 37.45 | 31.55 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| T-coil Coordinates (cm) | | [x,y] from bottom left | 1.7, 1.3 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 34 of 74 |

**Table 8-16
Raw Data Results for LTE B4 (5MHz and 10MHz BW's)**

| | Volume | 5MHz BW | |
|------------------------------------|------------------------|-----------|-----------|
| | | Axial | Radial |
| | | 20175 | 20175 |
| ABM1, dBA/m | Maximum | 8.24 | 4.64 |
| ABM2, dBA/m | | -31.10 | -29.01 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 39.34 | 33.65 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| | Volume | 10MHz BW | |
| | | Axial | Radial |
| | | 20175 | 20175 |
| ABM1, dBA/m | Maximum | 8.22 | 4.77 |
| ABM2, dBA/m | | -29.16 | -27.27 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 37.38 | 32.04 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| T-coil Coordinates (cm) | [x,y] from bottom left | 1.7, 1.3 | 1.3, 2.5 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 35 of 74 |

**Table 8-17
Raw Data Results for LTE B4 (15MHz and 20MHz BW's)**

| | | 15MHz BW | |
|------------------------------------|---------|------------------------|-----------|
| | | Axial | Radial |
| Volume | | 20175 | 20175 |
| ABM1, dBA/m | Maximum | 8.20 | 4.65 |
| ABM2, dBA/m | | -27.03 | -25.42 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 35.23 | 30.07 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| | | 20MHz BW | |
| | | Axial | Radial |
| Volume | | 20175 | 20175 |
| ABM1, dBA/m | Maximum | 8.34 | 4.8 |
| ABM2, dBA/m | | -27.54 | -25.33 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 35.88 | 30.13 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| T-coil Coordinates (cm) | | [x,y] from bottom left | 1.7, 1.3 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 36 of 74 |

**Table 8-18
Raw Data Results for LTE B2 (1.4MHz and 3MHz BW's)**

| | | 1.4MHz BW | |
|------------------------------------|---------|------------------------|-----------|
| | | Axial | Radial |
| Volume | | 18900 | 18900 |
| ABM1, dBA/m | Maximum | 8.23 | 4.89 |
| ABM2, dBA/m | | -26.37 | -26.44 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 34.60 | 31.33 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | 3MHz BW | |
| Volume | | 18900 | 18900 |
| | | Axial | Radial |
| ABM1, dBA/m | Maximum | 8.18 | 4.90 |
| ABM2, dBA/m | | -27.37 | -27.30 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 35.55 | 32.20 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| T-coil Coordinates (cm) | | [x,y] from bottom left | 1.7, 1.3 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 37 of 74 | |

**Table 8-19
Raw Data Results for LTE B2 (5MHz and 10MHz BW's)**

| | Volume | 5MHz BW | |
|------------------------------------|------------------------|-----------|-----------|
| | | Axial | Radial |
| | | 18900 | 18900 |
| ABM1, dBA/m | Maximum | 8.23 | 4.83 |
| ABM2, dBA/m | | -29.44 | -29.11 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 37.67 | 33.94 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| | Volume | 10MHz BW | |
| | | Axial | Radial |
| | | 18900 | 18900 |
| ABM1, dBA/m | Maximum | 8.17 | 4.92 |
| ABM2, dBA/m | | -27.02 | -26.55 |
| Ambient Noise, dBA/m | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | N/A |
| S+N/N (dB) | | 35.19 | 31.47 |
| C63.19-2011 Rating per orientation | | T4 | T4 |
| | | | |
| T-coil Coordinates (cm) | [x,y] from bottom left | 1.7, 1.3 | 1.3, 2.5 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 38 of 74 |

**Table 8-20
Raw Data Results for LTE B2 (15MHz and 20MHz BW's)**

| | | Volume | 15MHz BW | |
|------------------------------------|------------------------|---------|-----------|-----------|
| | | | Axial | Radial |
| | | | 18900 | 18900 |
| ABM1, dBA/m | | | 8.00 | 4.93 |
| ABM2, dBA/m | | | -26.02 | -26.60 |
| Ambient Noise, dBA/m | | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | Maximum | 2.00 | N/A |
| S+N/N (dB) | | | 34.02 | 31.53 |
| C63.19-2011 Rating per orientation | | | T4 | T4 |
| | | Volume | 20MHz BW | |
| | | | Axial | Radial |
| | | | 18900 | 18900 |
| ABM1, dBA/m | | | 8.11 | 4.75 |
| ABM2, dBA/m | | | -27.22 | -25.26 |
| Ambient Noise, dBA/m | | | -63.40 | -63.26 |
| Freq. Response Margin (dB) | | Maximum | 2.00 | N/A |
| S+N/N (dB) | | | 35.33 | 30.01 |
| C63.19-2011 Rating per orientation | | | T4 | T4 |
| T-coil Coordinates (cm) | [x,y] from bottom left | | 1.7, 1.3 | 1.3, 2.5 |

Notes:

1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.
8. The worst case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 2 at 15MHz is the worst case for the Axial probe orientation. LTE Band 2 at 20MHz bandwidth is the worst case for the Radial probe orientation. Please see Table 8-21 for additional tests on the low and high channels for the Axial and Radial probe orientations.

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 39 of 74 |

**Table 8-21
Raw Data Results for Worst Case LTE Band/BW Combinations by Probe Orientation**


| | Volume | Band 2 | | | Band 2 | | |
|------------------------------------|---------|------------------------|----------|--------|-----------|----------|--------|
| | | 15MHz | | | 20MHz | | |
| | | Axial | | | Radial | | |
| | | 18675 | 18900 | 19125 | 18700 | 18900 | 19100 |
| ABM1, dBA/m | Maximum | 8.38 | 8.00 | 8.32 | 4.72 | 4.75 | 4.81 |
| ABM2, dBA/m | | -29.72 | -26.02 | -28.79 | -26.27 | -25.26 | -26.47 |
| Ambient Noise, dBA/m | | -63.40 | -63.40 | -63.40 | -63.26 | -63.26 | -63.26 |
| Freq. Response Margin (dB) | | 2.00 | 2.00 | 2.00 | N/A | N/A | N/A |
| S+N/N (dB) | | 38.10 | 34.02 | 37.11 | 30.99 | 30.01 | 31.28 |
| S+N/N per orientation (dB) | | 34.02 | | | 30.01 | | |
| C63.19-2011 Rating per orientation | | T4 | | | T4 | | |
| T-coil Coordinates (cm) | | [x,y] from bottom left | 1.7, 1.3 | | | 1.3, 2.5 | |

Notes:


1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
4. Vocoder Configuration: NB AMR 12.2kbps
5. 'Radial' orientation refers to radial transverse.
6. Speech Signal: ITU-T P.50 Artificial Voice
7. User Hearing aid Mode (**Phone→Call Settings→Hearing aids**) as well as Noise suppression Mode (**Phone→Call Settings→Noise suppression**) were set to ON for Frequency Response compliance.
8. The worst case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 2 at 20MHz bandwidth is the worst case for the Radial probe orientation. LTE Band 2 at 15MHz is the worst case for the Axial probe orientation.

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 40 of 74 |

III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -18 dBm0 for CDMA. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE. This measurement was taken in the axial configuration above the maximum location.

IV. T-Coil Validation Test Results

Table 8-22
Helmholtz Coil Validation Table of Results

| Item | Target | Result | Verdict |
|---------------------------------|--------------|--------|-------------|
| Axial | | | |
| Magnetic Intensity, -10 dBA/m | -10 ± 0.5 dB | -9.661 | PASS |
| Environmental Noise | < -58 dBA/m | -63.40 | PASS |
| Frequency Response, from limits | > 0 dB | 0.70 | PASS |
| Radial | | | |
| Magnetic Intensity, -10 dBA/m | -10 ± 0.5 dB | -9.814 | PASS |
| Environmental Noise | < -58 dBA/m | -63.26 | PASS |
| Frequency Response, from limits | > 0 dB | 0.80 | PASS |

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 41 of 74 |

V. ABM1 Magnetic Field Distribution Scan Overlays




Figure 8-1
T-Coil Scan Overlay Magnetic Field Distributions

Notes:

1. Final measurement locations are indicated by a cursor on the contour plots.
2. See Test Setup Photographs for actual WD overlay.

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 42 of 74 | |

9. MEASUREMENT UNCERTAINTY

**Table 9-1
Uncertainty Estimation Table**

| Contribution | Data +/- % | Data +/- dB | Data Type | Probability distribution | Divisor | Standard uncertainty | Standard Uncertainty (dB) |
|--|------------|-------------|---------------|--------------------------|---------|----------------------|---------------------------|
| ABM Noise | 7.0% | 0.29 | Std. Dev. | Normal k=1 | 1.00 | 7.0% | |
| RF Reflections | 4.7% | 0.20 | Specification | Rectangular | 1.73 | 2.7% | |
| Reference Signal Level | 12.2% | 0.50 | Specification | Rectangular | 1.73 | 7.0% | |
| Positioning Accuracy | 10.0% | 0.41 | Uncertainty | Rectangular | 1.73 | 5.8% | |
| Probe Coil Sensitivity | 12.2% | 0.50 | Specification | Rectangular | 1.73 | 7.0% | |
| Probe Linearity | 2.4% | 0.10 | Std. Dev. | Normal k=1 | 1.00 | 2.4% | |
| Cable Loss | 2.8% | 0.12 | Specification | Rectangular | 1.73 | 1.6% | |
| Frequency Analyzer | 5.0% | 0.21 | Specification | Rectangular | 1.73 | 2.9% | |
| System Repeatability | 5.0% | 0.21 | Std. Dev. | Normal k=1 | 1.00 | 5.0% | |
| WD Repeatability | 9.0% | 0.37 | Std. Dev. | Normal k=1 | 1.00 | 9.0% | |
| Positioner Accuracy | 1.0% | 0.04 | Specification | Rectangular | 1.73 | 0.6% | |
| Combined standard uncertainty, u_c (k=1) | | | | | | 17.7% | 0.71 |
| Expanded uncertainty (k=2), 95% confidence level | | | | | | 35.3% | 1.31 |

Notes:

1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
2. All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 43 of 74 |

10. EQUIPMENT LIST

**Table 10-1
Equipment List**

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|-----------------|---------------------|-------------------------------------|------------|--------------|------------|-------------------|
| Listen | SoundCheck | Acoustic Analyzer System | 1/27/2015 | Annual | 1/27/2016 | 04-06-5876-SC2850 |
| Listen | SoundConnect | Microphone Power Supply | 11/13/2015 | Annual | 11/13/2016 | PS2612 |
| NI | 4474 | Data Acquisition Card | N/A | | N/A | N/A |
| Rohde & Schwarz | CMU200 | Base Station Simulator | 3/23/2015 | Annual | 3/23/2016 | 836371/0079 |
| Rohde & Schwarz | CMU200 | Base Station Simulator | 12/2/2015 | Annual | 12/2/2016 | 833855/0010 |
| Rohde & Schwarz | CMW500 | Radio Communication tester | 5/5/2015 | Annual | 5/5/2016 | 140144 |
| TEM | Radial T-Coil Probe | Radial T-Coil Probe | 11/17/2015 | Annual | 11/17/2016 | TEM-1130 |
| TEM | Axial T-Coil Probe | Axial T-Coil Probe | 11/17/2015 | Annual | 11/17/2016 | TEM-1124 |
| TEM | Helmholtz Coil | Helmholtz Coil | 12/22/2015 | Annual | 12/22/2016 | SBI 1052 |
| TEM | | HAC System Controller with Software | N/A | | N/A | N/A |
| TEM | | HAC Positioner | N/A | | N/A | N/A |

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 44 of 74 |

11. TEST DATA

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 45 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.



PCTEST Hearing-Aid Compatibility Facility

DUT: HH Coil - SN: SBI 1052


Type: HH Coil
Serial: SBI 1052

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015
- Helmholtz Coil – SN: SBI 1052; Calibrated: 12/22/2015

Noise Spectrum



Frequency Response



Results

| | | | | |
|-----------------------------|-----------|---|------------------|--------------|
| Verification 1kHz Intensity | -9.661 dB | ✓ | Max/Min | -9.5/-10.5 |
| Verification ABM2 | -63.4 dB | ✓ | Maximum | -58.0 |
| Frequency Response Margin | 700m dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 46 of 74 |



PCTEST Hearing-Aid Compatibility Facility

DUT: HH Coil – SN: SBI 1052


Type: HH Coil
Serial: SBI 1052

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015
- Helmholtz Coil – SN: SBI 1052; Calibrated: 12/22/2015

Noise Spectrum



Frequency Response



Results

| | | | | |
|-----------------------------|-----------|---|------------------|--------------|
| Verification 1kHz Intensity | -9.814 dB | ✓ | Max/Min | -9.5/-10.5 |
| Verification ABM2 | -63.26 dB | ✓ | Maximum | -58.0 |
| Frequency Response Margin | 800m dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 47 of 74 |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015


Test Configuration:

- Mode: Cellular CDMA
- Channel: 777
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

| | | | | |
|-------------------------|-----------|---|------------------|--------------|
| ABM1 | 2.9 dB | ✓ | Minimum | -18.0 |
| ABM2 | -25.57 dB | ✓ | Maximum | 0 |
| SNNR | 28.47 dB | ✓ | Minimum | 20 |
| Aligned Response - P.50 | 2 dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 48 of 74 | |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015


Test Configuration:

- Mode: PCS CDMA
- Channel: 1175
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

| | | | | |
|-------------------------|-----------|---|------------------|--------------|
| ABM1 | 2.82 dB | ✓ | Minimum | -18.0 |
| ABM2 | -21.45 dB | ✓ | Maximum | 0.0 |
| SNNR | 24.27 dB | ✓ | Minimum | 20.0 |
| Aligned Response - P.50 | 1.93 dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 49 of 74 |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015


Test Configuration:

- Mode: GSM850
- Channel: 251
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

| | | | | |
|-------------------------|-----------|---|------------------|--------------|
| ABM1 | 7.02 dB | ✓ | Minimum | -18.0 |
| ABM2 | -29.24 dB | ✓ | Maximum | 0.0 |
| SNNR | 36.26 dB | ✓ | Minimum | 20.0 |
| Aligned Response - P.50 | 2 dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 50 of 74 | |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015


Test Configuration:

- Mode: GSM1900
- Channel: 810
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

| | | | | |
|-------------------------|-----------|---|------------------|--------------|
| ABM1 | 7 dB | ✓ | Minimum | -18.0 |
| ABM2 | -31.61 dB | ✓ | Maximum | 0 |
| SNNR | 38.61 dB | ✓ | Minimum | 20 |
| Aligned Response - P.50 | 2 dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 51 of 74 |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015


Test Configuration:

- Mode: UMTS Band V
- Channel: 4132
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

| | | | | |
|-------------------------|-----------|---|------------------|--------------|
| ABM1 | 7.09 dB | ✓ | Minimum | -18.0 |
| ABM2 | -41.61 dB | ✓ | Maximum | 0.0 |
| SNNR | 48.7 dB | ✓ | Minimum | 20.0 |
| Aligned Response - P.50 | 2 dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 52 of 74 |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015


Test Configuration:

- Mode: UMTS Band II
- Channel: 9262
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

| | | | | |
|-------------------------|----------|---|------------------|--------------|
| ABM1 | 7.16 dB | ✓ | Minimum | -18.0 |
| ABM2 | -41.8 dB | ✓ | Maximum | 0.0 |
| SNNR | 48.97 dB | ✓ | Minimum | 20.0 |
| Aligned Response - P.50 | 2 dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 53 of 74 | |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 11/17/2015


Test Configuration:

- Mode: LTE Band 2
- Bandwidth: 15MHz
- Channel: 18900
- Speech Signal: ITU-T P.50 Artificial Voice

Noise Spectrum



Frequency Response



Results

| | | | | |
|-------------------------|-----------|---|------------------|--------------|
| ABM1 | 8 dB | ✓ | Minimum | -18.0 |
| ABM2 | -26.02 dB | ✓ | Maximum | 0.0 |
| SNNR | 34.02 dB | ✓ | Minimum | 20.0 |
| Aligned Response - P.50 | 2 dB | ✓ | Tolerance curves | Aligned Data |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 54 of 74 |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015

Test Configuration:

- Mode: Cellular CDMA
- Channel: 1013

Noise Spectrum



Results

| | | | | |
|------|-----------|---|---------|-------|
| ABM1 | 3.58 dB | ✓ | Minimum | -18.0 |
| ABM2 | -25.53 dB | ✓ | Maximum | 0.0 |
| SNNR | 29.11 dB | ✓ | Minimum | 20.0 |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 55 of 74 | |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015

Test Configuration:

- Mode: PCS CDMA
- Channel: 1175

Noise Spectrum



Results

| | | | | |
|------|-----------|---|---------|-------|
| ABM1 | 3.75 dB | ✓ | Minimum | -18.0 |
| ABM2 | -20.66 dB | ✓ | Maximum | 0.0 |
| SNNR | 24.41 dB | ✓ | Minimum | 20.0 |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 56 of 74 | |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015

Test Configuration:

- Mode: GSM850
- Channel: 251

Noise Spectrum



Results

| | | | | |
|------|-----------|---|---------|-------|
| ABM1 | 6.41 dB | ✓ | Minimum | -18.0 |
| ABM2 | -15.81 dB | ✓ | Maximum | 0.0 |
| SNNR | 22.22 dB | ✓ | Minimum | 20.0 |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 57 of 74 |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015

Test Configuration:

- Mode: GSM1900
- Channel: 810

Noise Spectrum



Results

| | | | | |
|------|-----------|---|---------|-------|
| ABM1 | 6.41 dB | ✓ | Minimum | -18.0 |
| ABM2 | -18.45 dB | ✓ | Maximum | 0.0 |
| SNNR | 24.85 dB | ✓ | Minimum | 20.0 |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 58 of 74 | |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015

Test Configuration:

- Mode: UMTS Band V
- Channel: 4233

Noise Spectrum



Results

| | | | | |
|------|-----------|---|---------|-------|
| ABM1 | 6.27 dB | ✓ | Minimum | -18.0 |
| ABM2 | -38.07 dB | ✓ | Maximum | 0.0 |
| SNNR | 44.34 dB | ✓ | Minimum | 20.0 |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|--|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 59 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015

Test Configuration:

- Mode: UMTS Band II
- Channel: 9538

Noise Spectrum



Results

| | | | | |
|------|-----------|---|---------|-------|
| ABM1 | 6.26 dB | ✓ | Minimum | -18.0 |
| ABM2 | -37.21 dB | ✓ | Maximum | 0.0 |
| SNNR | 43.46 dB | ✓ | Minimum | 20.0 |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 60 of 74 | |



PCTEST Hearing-Aid Compatibility Facility

DUT: ZNFVS425

Type: Portable Handset
Serial: 01799

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 11/17/2015

Test Configuration:

- Mode: LTE Band 2
- Bandwidth: 20MHz
- Channel: 18900

Noise Spectrum



Results

| | | | | |
|------|-----------|---|---------|-------|
| ABM1 | 4.75 dB | ✓ | Minimum | -18.0 |
| ABM2 | -25.26 dB | ✓ | Maximum | 0.0 |
| SNNR | 30.01 dB | ✓ | Minimum | 20.0 |

PCTEST 2016

| | | | | |
|---|---|--------------------------------------|---------------|--|
| FCC ID: ZNFVS425 | | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 61 of 74 | |

12. CALIBRATION CERTIFICATES

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 62 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

West Caldwell Calibration Laboratories Inc.

Certificate of Calibration

for

AXIAL T COIL PROBE

Manufactured by: TEM CONSULTING
Model No: AXIAL T COIL PROBE
Serial No: TEM-1124
Calibration Recall No: 25880

Submitted By:

Customer: ANDREW HARWELL
Company: PCTEST ENGINEERING LAB
Address: 6660-B DOBBIN ROAD
COLUMBIA MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No. AXIAL T C TEM

Upon receipt for Calibration, the instrument was found to be:

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2008 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

Calibration Date: 17-Nov-15

Certificate No: 25880 - 3

QA Doc. #1051 Rev. 2.0 10/1/01

Certificate Page 1 of 1

FC
Felix Christopher (QA Mgr.)
ISO/IEC 17025:2005

West Caldwell
Calibration
Laboratories, Inc.
uncompromised calibration
1575 State Route 96, Victor, NY 14564, U.S.A.



Calibration Lab. Cert. # 1533.01

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 63 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.



1575 State Route 96, Victor NY 14564

ISO/IEC 17025: 2005



Calibration Lab. Cert. # 1533.01

REPORT OF CALIBRATION

TEM Consulting LP Axial T Coil Probe

for
Model No.: Axial T Coil Probe

Serial No.: TEM-1124

Company : PC Test Engineering Lab.

I. D. No: XXXX


| | | | |
|--|--------|-------------------------------------|-------------------------------|
| Calibration results: | | Before data: | After data: |
| Probe Sensitivity measured with Helmholtz Coil | | Before & after data same: ...X..... | |
| <i>Helmholtz Coil;</i> | | | |
| the number of turns on each coil; | 10 | No. | |
| the radius of each coil, in meters; | 0.204 | m | |
| the current in the coils, in amperes.; | 0.09 | A | |
| <i>Helmholtz Coil Constant;</i> | | Laboratory Environment: | |
| 7.09 | | A/m/V | Ambient Temperature: 21.7 °C |
| <i>Helmholtz Coil magnetic field;</i> | | Ambient Humidity: 28.1 % RH | |
| 6.05 | | A/m | Ambient Pressure: 100.8 kPa |
| Probe Sensitivity at 1000 Hz. | | Calibration Date: 17-Nov-15 | |
| was | -60.07 | dBV/A/m | Re-calibration Due: 17-Nov-16 |
| | 0.992 | mV/A/m | Report Number: 25880 -3 |
| Probe resistance | 902 | Ohms | Control Number: 25880 |

The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers: 683/284413-14

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure :

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures

intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 17-Nov-2015

Measurements performed by: *[Signature]*

Calibrated on WCCL system type 9700

Felix Christopher

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

| | | | | |
|----------------------------------|--|-------------------------------|--|---------------------------------|
| FCC ID: ZNFVS425 | PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 64 of 74 |

HCATEMC_TEM-1124_Nov-17-2015

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564
Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Axial T Coil Probe for Model No.: Axial T Coil Probe Serial No.: TEM-1124
Company : PC Test Engineering Lab.

| Test | Function | Tolerance | Measured values | | |
|-------|--------------------------|-----------------------|-----------------|--------|---------|
| | | | Before | Out | Remarks |
| 1.0 | Probe Sensitivity at | 1000 Hz. dBV/A/m | -60.07 | | |
| 2.0 | Probe Level Linearity | Ref. (0 dB) | 6 | 6.06 | |
| | | | 0 | 0.00 | |
| | | | -6 | -6.03 | |
| | | | -12 | -12.06 | |
| 3.0 | Probe Frequency Response | Ref. (0 dB) | 100 | -19.8 | |
| | | | 126 | -18.0 | |
| | | | 158 | -16.0 | |
| | | | 200 | -13.9 | |
| | | | 251 | -12.0 | |
| | | | 316 | -9.9 | |
| | | | 398 | -8.0 | |
| | | | 501 | -6.0 | |
| | | | 631 | -4.0 | |
| | | | 794 | -2.0 | |
| | | | 1000 | 0.0 | |
| | | | 1259 | 2.0 | |
| | | | 1585 | 4.0 | |
| | | | 1995 | 6.0 | |
| | | | 2512 | 7.9 | |
| | | | 3162 | 9.9 | |
| | | | 3981 | 11.9 | |
| 5012 | 13.9 | | | | |
| 6310 | 15.9 | | | | |
| 7943 | 18.0 | | | | |
| 10000 | 20.1 | | | | |

| Instruments used for calibration: | | | Date of Cal. | Traceability No. | Due Date |
|-----------------------------------|--------|--------------|--------------|------------------|------------|
| HP | 34401A | S/N 36064102 | 1-Oct-2015 | 287708 | 1-Oct-2016 |
| HP | 34401A | S/N 36102471 | 1-Oct-2015 | 287708 | 1-Oct-2016 |
| HP | 33120A | S/N 36043716 | 1-Oct-2015 | 287708 | 1-Oct-2016 |
| B&K | 2133 | S/N 1583254 | 1-Oct-2015 | 683/284413-14 | 1-Oct-2016 |

Cal. Date: 17-Nov-2015 Tested by: Felix Christopher
Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc. Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 65 of 74 |

West Caldwell Calibration Laboratories Inc.

Certificate of Calibration

for

RADIAL T COIL PROBE

Manufactured by: TEM CONSULTING
Model No: RADIAL T COIL PROBE
Serial No: TEM-1130
Calibration Recall No: 25880

Submitted By:

Customer: ANDREW HARWELL
Company: PCTEST ENGINEERING LAB
Address: 6660-B DOBBIN ROAD
COLUMBIA MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No. RADIAL T TEM

Upon receipt for Calibration, the instrument was found to be:

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2008 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

Calibration Date: 17-Nov-15

FC
Felix Christopher (QA Mgr.)

Certificate No: 25880 - 2

ISO/IEC 17025:2005

QA Doc. #1051 Rev. 2.0 10/1/01

Certificate Page 1 of 1

West Caldwell
Calibration
Laboratories, Inc.
uncompromised calibration
1575 State Route 96, Victor, NY 14564, U.S.A.



Calibration Lab. Cert. # 1533.01

| | | | | |
|----------------------------------|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 66 of 74 |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M

12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.



ISO/IEC 17025: 2005



Calibration Lab. Cert. # 1533.01

REPORT OF CALIBRATION

TEM Consulting LP Radial T Coil Probe

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

Company : PC Test Engineering Lab.

I. D. No: XXXX


| Calibration results: | | Before data: | After data: |
|---|----------------|-------------------------------------|-------------------|
| Probe Sensitivity measured with Helmholtz Coil | | | |
| <i>Helmholtz Coil;</i> | | Before & after data same: ...X..... | |
| the number of turns on each coil; | 10 No. | Laboratory Environment: | |
| the radius of each coil, in meters; | 0.204 m | Ambient Temperature: | 21.7 °C |
| the current in the coils, in amperes.; | 0.09 A | Ambient Humidity: | 28.1 % RH |
| <i>Helmholtz Coil Constant;</i> | 7.09 A/m/V | Ambient Pressure: | 100.8 kPa |
| <i>Helmholtz Coil magnetic field;</i> | 5.98 A/m | Calibration Date: | 17-Nov-15 |
| Probe Sensitivity at | 1000 Hz. | Re-calibration Due: | 17-Nov-16 |
| was | -60.41 dBV/A/m | Report Number: | 25880 -2 |
| | 0.954 mV/A/m | Control Number: | 25880 |
| Probe resistance | 903 Ohms | | |

The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers: 683/284413-14

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : **Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC**

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSS Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 17-Nov-2015

Measurements performed by: *[Signature]*

Calibrated on WCCL system type 9700

Felix Christopher

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

| | | | | |
|----------------------------------|--|-------------------------------|--|---------------------------------|
| FCC ID: ZNFVS425 | PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT | | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 67 of 74 |

HCRTEM_Cal-1130_Nov-17-2015

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564
Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Radial T Coil Probe for Model No.: Radial T Coil Probe Serial No.: TEM-1130
Company : PC Test Engineering Lab.

| Test | Function | Tolerance | Measured values | | |
|-------|--------------------------|-----------------------|-----------------|--------|---------|
| | | | Before | Out | Remarks |
| 1.0 | Probe Sensitivity at | 1000 Hz. dBV/A/m | -60.41 | | |
| 2.0 | Probe Level Linearity | Ref. (0 dB) | 6 dB | 6.05 | |
| | | | 0 | 0.00 | |
| | | | -6 | -6.03 | |
| | | | -12 | -12.05 | |
| 3.0 | Probe Frequency Response | Ref. (0 dB) | 100 Hz | -20.0 | |
| | | | 126 | -17.9 | |
| | | | 158 | -15.9 | |
| | | | 200 | -13.9 | |
| | | | 251 | -11.9 | |
| | | | 316 | -10.0 | |
| | | | 398 | -8.0 | |
| | | | 501 | -6.0 | |
| | | | 631 | -4.0 | |
| | | | 794 | -2.0 | |
| | | | 1000 | 0.0 | |
| | | | 1259 | 2.0 | |
| | | | 1585 | 4.0 | |
| | | | 1995 | 6.0 | |
| | | | 2512 | 7.9 | |
| | | | 3162 | 9.9 | |
| | | | 3981 | 11.9 | |
| 5012 | 13.9 | | | | |
| 6310 | 15.9 | | | | |
| 7943 | 18.0 | | | | |
| 10000 | 20.2 | | | | |

| Instruments used for calibration: | | S/N | Date of Cal. | Traceability No. | Due Date |
|-----------------------------------|--------|----------|--------------|------------------|------------|
| HP | 34401A | 36064102 | 1-Oct-2015 | ,287708 | 1-Oct-2016 |
| HP | 34401A | 36102471 | 1-Oct-2015 | ,287708 | 1-Oct-2016 |
| HP | 33120A | 36043716 | 1-Oct-2015 | ,287708 | 1-Oct-2016 |
| B&K | 2133 | 1583254 | 1-Oct-2015 | 683/284413-14 | 1-Oct-2016 |

Cal. Date: 17-Nov-2015 Tested by: Felix Christopher
Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEM_C

| | | | | |
|----------------------------------|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | | Page 68 of 74 |

13. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 69 of 74 | |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

14. REFERENCES

1. ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
2. FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v04," October 31, 2013
3. FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v01r01," October 31, 2013
4. FCC Public Notice DA 06-1215, *Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard*, June 6, 2006
5. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
6. Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
7. Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," *Wireless Telephones and Hearing Aids: New Challenges for Audiology*, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
8. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices," IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
9. Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, *Ear and Hearing* 7:257-265, 1986.
11. Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells," U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
12. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
13. EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
15. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.

| | | | | |
|----------------------------------|--|-------------------------------|--|---------------------------------|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  LG | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 70 of 74 | |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

17. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
19. Joyner, K. H., et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
20. Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Construction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.
22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
25. Ma, M. A., Sreenivashiah, I. , and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1040, July 1981.
26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
28. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

| | | | | |
|---|---|--------------------------------------|---|--|
| FCC ID: ZNFVS425 |  PCTEST ENGINEERING LABORATORY, INC. | HAC (T-COIL) TEST REPORT |  | Reviewed by: Quality Manager |
| Filename: OY1601110077-R1.ZNF | Test Dates: 01/21/2015 - 01/25/2015 | EUT Type: Portable Handset | Page 71 of 74 | |

© 2016 PCTEST Engineering Laboratory, Inc.

REV 3.1.M
12/9/2015

© 2016 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.