

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Issue: March 18, 2014

Test Report No.: HCT-E-1403-F017

Test Site: HCT CO., LTD.
HCT FRN: 0005-8664-21

FCC ID:

ZNFVS450PP

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B
Equipment Type : CDMA Phone with Bluetooth4.0, WLAN2.4GHz 802.11b/g/n
Model Name : LG-VS450PP
Additional Model Name : LGVVS450PP, VS450PP, LGL41C, LG-AS750
Port / Connector(s) : USB / Earphone Port
Date of Test : February 27, 2014 - March 04, 2014

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4/2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denial the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By



Dong-Hyun Park
Test Engineer
EMC Team
Certification Division

Reviewed By



Sang-Jun Lee
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1403-F017	March 18, 2014	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Product Description	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Tested System Details.....	5
1.4 Cable Description	6
1.5 Noise Suppression Parts on Cable. (I/O cable)	6
1.6 Test Methodology	7
1.7 Test Facility	7
1.8 Frequency Range of Radiated Measurements	7
2. SYSTEM TEST CONFIGURATION.....	8
2.1 Configuration of Test System	8
3. PRELIMINARY TEST	9
3.1 Conducted Emission Test	9
3.2 Radiated Emission Test	9
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	10
4.1 Conducted Emission Test	10
4.2 Radiated Emission Test	10
5. FIELD STRENGTH CALCULATION	17
6. TEST EQUIPMENT	18
7. CONCLUSION	19

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Product Description

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model Name	LG-VS450PP
Additional Model Name	LGVS450PP, VS450PP, LGL41C, LG-AS750
FCC ID	ZNFVS450PP
EUT Type	CDMA Phone with Bluetooth4.0, WLAN2.4GHz 802.11b/g/n
TX Frequency	824.70 MHz to 848.31 MHz (CDMA 850) 1 851.25 MHz to 1 908.75 MHz (CDMA 1 900)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA 850) 1 931.25 MHz to 1 988.75 MHz (CDMA 1 900)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.



1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-VS450PP	LG	ZNFVS450PP	Notebook PC Ear-phone
USB cable	EAD62432101	Ningbo Broad	-	E.U.T Notebook PC
Ear-phone	EAB62209201	I-SOUND	-	E.U.T
Notebook PC	ProBook6560b	H.P	DoC	EUT Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (JIANGSU)LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Serial Mouse	Serial 2 Button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	8GB	SanDisk	-	E.U.T



1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Ear-phone	N/A	N	(D)1.1
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Ear-phone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to EUT distance of 3 m.

1.7 Test Facility

Chamber used to collect the test data is located at the 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4/2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3m)	90661 (June 21, 2011)
Radiated Field strength measurement facility (10m)	90661 (June 21, 2011)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



2. SYSTEM TEST CONFIGURATION

2.1 Configuration of Test System


2.1.1 Conducted Emission Test

EUT was connected to LISN via Notebook PC adaptor and Base Station. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

2.1.2 Radiated Emission Test

Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m semi-anechoic chamber.

[Configuration of Tested System]



Power Line: 120 VAC



3. PRELIMINARY TEST

3.1 Conducted Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode

3.2 Radiated Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Operation Mode	: Data Communication mode
Temperature	: 21.7°C
Humidity Level	: 29.4 %
Test Date	: March 04, 2014

Frequency (MHz)	Transd (dB)	Conductor	Quasi-Peak			Average		
			Limit	Measurement Level	Result Level	Limit	Measurement Level	Result Level
			(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dBuV)
0.1950	9.7	L1	63.8	39.0	48.7	53.8	25.1	34.8
0.1950	9.7	N	63.8	40.5	50.2	53.8	-	-
4.1720	10.1	L1	56.0	-	-	46.0	20.5	30.6
4.5995	10.1	N	56.0	-	-	46.0	19.8	29.9

※ **NOTE:** Refer to page 11 to page 14 for details.

1. Conductor H = L1, Conductor N = Neutral
 2. Transducer = LISN Factor + Cable Loss Factor
 3. Result Level = Measurement Level + Transducer Factor
- * 'Result Level' in above table is same as the 'Quasi-Peak' and 'Average' of the test data



EMI Auto Test(1)


1/2

HCT TEST Report

Common Information

EUT: LG-VS450PP
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: DATA MODE
 Operator Name:

FCC CLASS B



— FCCCLASS B_QP — FCCCLASS B_AV — Preview Result 1-PK*
 — Preview Result 2-AVG X Final Result 1-CPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	47.5	9.000	Off	L1	9.7	18.5	66.0
0.172500	44.2	9.000	Off	L1	9.7	20.6	64.8
0.181500	43.2	9.000	Off	L1	9.7	21.2	64.4
0.195000	48.7	9.000	Off	L1	9.7	15.1	63.8
0.208500	47.4	9.000	Off	L1	9.7	15.9	63.3
0.226500	38.8	9.000	Off	L1	9.7	23.8	62.6
3.821000	39.2	9.000	Off	L1	10.0	16.8	56.0
4.032500	38.9	9.000	Off	L1	10.1	17.1	56.0
4.316000	38.8	9.000	Off	L1	10.1	17.2	56.0
4.388000	38.7	9.000	Off	L1	10.1	17.3	56.0
4.599500	38.5	9.000	Off	L1	10.1	17.5	56.0
4.671500	37.9	9.000	Off	L1	10.1	18.1	56.0
15.710000	33.0	9.000	Off	L1	10.7	27.0	60.0
16.137500	32.5	9.000	Off	L1	10.8	27.5	60.0
16.421000	32.8	9.000	Off	L1	10.8	27.2	60.0
17.195000	32.1	9.000	Off	L1	10.8	27.9	60.0

3/4/2014

2:33:19



EMI Auto Test(1)

2 / 2

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
19.323500	33.1	9.000	Off	L1	10.9	26.9	60.0
20.813000	35.1	9.000	Off	L1	10.9	24.9	60.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.154500	27.8	9.000	Off	L1	9.7	28.0	55.8
0.163500	27.6	9.000	Off	L1	9.7	27.7	55.3
0.181500	27.8	9.000	Off	L1	9.7	26.6	54.4
0.195000	34.8	9.000	Off	L1	9.7	19.0	53.8
0.204000	34.8	9.000	Off	L1	9.7	18.6	53.4
0.267000	31.6	9.000	Off	L1	9.7	19.6	51.2
3.677000	29.8	9.000	Off	L1	10.0	16.2	46.0
3.731000	29.8	9.000	Off	L1	10.0	16.2	46.0
3.888500	29.6	9.000	Off	L1	10.0	16.4	46.0
4.163000	29.5	9.000	Off	L1	10.1	16.5	46.0
4.172000	30.6	9.000	Off	L1	10.1	15.4	46.0
4.599500	30.1	9.000	Off	L1	10.1	15.9	46.0
15.710000	25.3	9.000	Off	L1	10.7	24.7	50.0
16.137500	25.5	9.000	Off	L1	10.8	24.5	50.0
16.421000	25.3	9.000	Off	L1	10.8	24.7	50.0
17.195000	23.8	9.000	Off	L1	10.8	26.2	50.0
19.323500	25.2	9.000	Off	L1	10.9	24.8	50.0
20.385500	26.9	9.000	Off	L1	10.9	23.1	50.0

3/4/2014

2:33:19



EMI Auto Test(1)


1 / 2

HCT TEST Report

Common Information

EUT: LG-VS450PP
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: DATA MODE
 Operator Name:

FCC CLASS B



— FCCCLASS B_QP
 — FCCCLASS B_AV
 — Preview Result 1-PK+
— Preview Result 2-AVG
 X Final Result 1-QPK
 X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154500	46.9	9.000	Off	N	9.7	18.9	65.8
0.168000	44.9	9.000	Off	N	9.7	20.2	65.1
0.186000	43.1	9.000	Off	N	9.7	21.1	64.2
0.195000	50.2	9.000	Off	N	9.7	13.6	63.8
0.213000	46.6	9.000	Off	N	9.7	16.5	63.1
0.258000	43.1	9.000	Off	N	9.7	18.4	61.5
3.857000	38.1	9.000	Off	N	10.1	17.9	56.0
3.960500	38.9	9.000	Off	N	10.1	17.1	56.0
3.974000	38.4	9.000	Off	N	10.1	17.6	56.0
4.032500	38.8	9.000	Off	N	10.1	17.2	56.0
4.104500	39.1	9.000	Off	N	10.1	16.9	56.0
4.320500	37.9	9.000	Off	N	10.1	18.1	56.0
19.170500	33.0	9.000	Off	N	10.8	27.0	60.0
19.674500	31.4	9.000	Off	N	10.8	28.6	60.0
20.255000	33.6	9.000	Off	N	10.8	26.4	60.0
20.880500	35.1	9.000	Off	N	10.8	24.9	60.0

3/4/2014

2:39:59



EMI Auto Test(1)

2 / 2

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
21.015500	35.2	9.000	Off	N	10.8	24.8	60.0
21.231500	34.8	9.000	Off	N	10.8	25.2	60.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.150000	29.0	9.000	Off	N	9.7	27.0	56.0
0.163500	27.6	9.000	Off	N	9.7	27.7	55.3
0.177000	27.8	9.000	Off	N	9.7	26.8	54.6
0.199500	35.3	9.000	Off	N	9.7	18.3	53.6
0.208500	34.5	9.000	Off	N	9.7	18.8	53.3
0.258000	32.4	9.000	Off	N	9.7	19.1	51.5
3.857000	29.1	9.000	Off	N	10.1	16.9	46.0
3.974000	28.8	9.000	Off	N	10.1	17.2	46.0
4.032500	29.3	9.000	Off	N	10.1	16.7	46.0
4.104500	29.6	9.000	Off	N	10.1	16.4	46.0
4.320500	29.8	9.000	Off	N	10.1	16.2	46.0
4.599500	29.9	9.000	Off	N	10.1	16.1	46.0
15.579500	24.4	9.000	Off	N	10.7	25.6	50.0
19.170500	25.3	9.000	Off	N	10.8	24.7	50.0
19.674500	22.0	9.000	Off	N	10.8	28.0	50.0
20.768000	27.9	9.000	Off	N	10.8	22.1	50.0
20.880500	27.8	9.000	Off	N	10.8	22.2	50.0
21.231500	27.8	9.000	Off	N	10.8	22.2	50.0

3/4/2014

2:39:59



4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

-For measurement below 1 GHz

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak (6 dB Bandwidth: 120 kHz)
Operation Mode	: Data Communication mode
Temperature	: 20.3°C
Humidity Level	: 27.7 %
Test Date	: March 03, 2014

Frequency (MHz)	Reading (dBuV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBuV/m)	Level (dBuV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
288.0	19.48	H	1.2	13.02	4.50	46.0	37.0	9.0
375.0	17.94	H	1.0	15.08	4.79	46.0	37.8	8.2
625.0	12.44	V	1.0	19.97	5.39	46.0	37.8	8.2



-For measurement above 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Peak mode: Peak (RBW: 1 MHz, VBW: 1 MHz)
: Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)

Temperature : 19.6°C

Humidity Level : 24.2 %

Test Date : February 27, 2014

Frequency (GHz)	Peak			POL	Average		
	Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)		Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1.33040	50.5	74	23.5	V	32.7	54	21.3
1.99760	55.3	74	18.7	V	38.3	54	15.7
2.66420	52.4	74	21.6	V	34.3	54	19.7

※ **NOTE:**

1. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. Test was measured by 12 GHz.



5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

[Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	μ V/m	dB μ V/m
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0



6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>Next CAL Date</u>
<u>Conducted Emission</u>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	2015.01.24
<input checked="" type="checkbox"/> LISN	EMCO	3816/2SH	9706-1070	1 year	2014.04.26
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	2015.01.29
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	2014.06.23
<input type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	2014.07.03
<input type="checkbox"/> Attenuator	Rohde & Schwarz	ESH3-Z2	357.8810.352	1 year	2014.07.03
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	2014.12.17
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Turn Table	HD GmbH	2090	9702/1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
<input type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9168	185	2 year	2015.04.16
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Turn Table	HD GmbH	2090	9702/1224	N/A	-
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21690	1 year	2014.07.12
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	2014.12.13
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-



7. CONCLUSION

The data collected shows that the **EUT type: CDMA Phone with Bluetooth4.0, WLAN2.4GHz 802.11b/g/n, FCC ID: ZNFVS450PP, Model: LG-VS450PP** complies with §15.107 and §15.109 of the FCC rules.