



FCC CFR47 PART 15 SUBPART C

**BLUETOOTH LOW ENERGY
CERTIFICATION TEST REPORT**

FOR

CDMA/ LTE Phone + Bluetooth, and DTS b/g/n

MODEL NUMBER: LG-VS810PP, VS810PP, LGVS810PP

FCC ID: ZNFVS810PP

REPORT NUMBER: 14U18508-E3

ISSUE DATE: AUGUST 25, 2014

Prepared for

**LG ELECTRONICS MOBILECOMM U.S.A., INC
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS,
NEW JERSEY, 07632, U.S.A**

Prepared by

**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	08/25/14	Initial Issue	D. Corona

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>5</i>
4.2. <i>SAMPLE CALCULATION</i>	<i>5</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>5</i>
5. EQUIPMENT UNDER TEST.....	6
5.1. <i>DESCRIPTION OF EUT</i>	<i>6</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>6</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>6</i>
5.4. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>7</i>
5.5. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>8</i>
6. TEST AND MEASUREMENT EQUIPMENT	10
7. SUMMARY	11
8. ANTENNA PORT TEST RESULTS	12
8.1. <i>6 dB BANDWIDTH.....</i>	<i>12</i>
8.2. <i>99% BANDWIDTH.....</i>	<i>16</i>
8.3. <i>OUTPUT POWER.....</i>	<i>20</i>
8.4. <i>AVERAGE POWER.....</i>	<i>24</i>
8.5. <i>POWER SPECTRAL DENSITY</i>	<i>25</i>
8.6. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	<i>29</i>
9. RADIATED TEST RESULTS.....	36
9.1. <i>LIMITS AND PROCEDURE.....</i>	<i>36</i>
9.2. <i>TRANSMITTER ABOVE 1 GHz.....</i>	<i>37</i>
9.3. <i>WORST-CASE BELOW 1 GHz.....</i>	<i>50</i>
10. AC POWER LINE CONDUCTED EMISSIONS	53
11. SETUP PHOTOS	58

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S.A., INC
EUT DESCRIPTION: CDMA/LTE Phone + Bluetooth, and DTS b/g/n.
MODEL: LG-VS810PP, VS810PP, and LGVS810PP
SERIAL NUMBER: 18 (Conducted), 22 (Radiated)
DATE TESTED: August 8-16, 2014

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



DAN CORONIA
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.

STEVEN TRAN
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
<input checked="" type="checkbox"/> Chamber A	<input type="checkbox"/> Chamber D
<input type="checkbox"/> Chamber B	<input type="checkbox"/> Chamber E
<input type="checkbox"/> Chamber C	<input type="checkbox"/> Chamber F
	<input type="checkbox"/> Chamber G
	<input checked="" type="checkbox"/> Chamber H

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a CDMA//LTE Phone + Bluetooth, DTS b/g/n.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402-2480	BLE	1.00	1.26

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes PIFA antenna, with a maximum gain of 0.12 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	LG	VS-810PP	RA481001374	N/A
Headset	LG	VS-810PP	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C00986	4/1/2015
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4440A	C01179	2/26/2015
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	8/8/2015
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	5/8/2015
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	10/22/2014
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	N/A	3/6/2015
Antenna, Horn, 18 GHz	ETS	3117	C01022	2/21/2015
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00589	12/17/2014
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/2014
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/2014
LISN, 30 MHz	FCC	50/250-25-2	C00626	1/14/2015

7. SUMMARY

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	RSS-210 A8.2(a)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	0.673 MHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-84.33 dBm
15.247	RSS-210 A8.4	TX conducted output power	<30dBm		Pass	1.0 dBm
15.247	RSS-210 A8.2	PSD	<8dBm		Pass	-19.07 dBm
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	49.30 dBuV
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	42.89 dBuV/m

8. ANTENNA PORT TEST RESULTS

8.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.


TEST PROCEDURE


Reference to KDB 558074 D01 DTS Meas Guidance v03r02: The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.


RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.673	0.5
Middle	2440	0.737	0.5
High	2480	0.677	0.5

6 dB BANDWIDTH PLOTS







8.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.


TEST PROCEDURE


Reference to KDB558074 D01 DTS Meas Guidance v03r01: The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.


RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0625
Middle	2440	1.0715
High	2480	1.0379

99% BANDWIDTH PLOTS







8.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.


TEST PROCEDURE


Peak power is measured using KDB 558074 D01 DTS Meas Guidance v03r02 under section 9.1.1 utilizing spectrum analyzer.


RESULTS

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	0.2	30	-29.810
Middle	2440	1.0	30	-29.020
High	2480	-0.5	30	-30.480

OUTPUT POWER PLOTS







8.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.2 dB (including 10 dB pad and 0.2 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	-0.5
Middle	2440	0.4
High	2480	-1.1

8.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


TEST PROCEDURE


Power Spectral Density was performed utilizing the “Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v03r01, April 9, 2013


RESULTS

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-20.11	8	-28.11
Middle	2440	-19.07	8	-27.07
High	2480	-20.76	8	-28.76

POWER SPECTRAL DENSITY PLOTS







8.6. CONDUCTED SPURIOUS EMISSIONS LIMITS

FCC §15.247 (d)

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


RESULTS

SPURIOUS EMISSIONS, LOW CHANNEL

LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL

MID CHANNEL REFERENCE




MID CHANNEL SPURIOUS




SPURIOUS EMISSIONS, HIGH CHANNEL

HIGH CHANNEL BANDEDGE



HIGH CHANNEL SPURIOUS



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4 - 2009. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor = $10 \log(1/x)$. For this sample: $DCF = 10 \log(1/0.622) = 2.06 \text{ dB}$ (Spectrum Analyzer round it up to 2.1 dB)

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz

RESTRICTED BANDEGE (LOW CHANNEL)

LOW CHANNEL RESTRICTED, HORIZONTAL PEAK AND AVERAGE PLOT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	DCCF	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.46	PK	32.1	-23.1		49.46	-	-	74	-24.54	231	127	H
2	* 2.385	43.11	PK	32.1	-23.1		52.11	-	-	74	-21.89	231	127	H
3	* 2.39	30.84	RMS	32.1	-23.1	2.1	41.94	54	-12.06	-	-	231	127	H
4	* 2.388	31.31	RMS	32.1	-23.1	2.1	42.41	54	-11.59	-	-	231	127	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

LOW CHANNEL RESTRICTED, VERTICAL PEAK AND AVERAGE PLOT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DCCF	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.38	42.88	PK	32.1	-23.1	-	51.88	-	-	74	-22.12	256	132	V
4	* 2.385	31.22	RMS	32.1	-23.1	2.1	42.32	54	-11.68	-	-	256	132	V
1	* 2.39	40.77	PK	32.1	-23.1	-	49.77	-	-	74	-24.23	256	132	V
3	* 2.39	30.32	RMS	32.1	-23.1	2.1	41.42	54	-12.58	-	-	256	132	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

RESTRICTED BANDEDGE (HIGH CHANNEL)

HIGH CHANNEL RESTRICTED, HORIZONTAL PEAK AND AVERAGE PLOT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DCCF	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.36	PK	32.3	-22.8	-	49.86	-	-	74	-24.14	0	130	H
3	* 2.484	30.65	RMS	32.3	-22.8	2.1	42.25	54	-11.75	-	-	0	130	H
2	2.547	42.76	PK	32.4	-22.7	-	52.46	-	-	74	-21.54	0	130	H
4	2.562	30.99	RMS	32.4	-22.7	2.1	42.79	54	-11.21	-	-	0	130	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

HIGH CHANNEL RESTRICTED, VERTICAL PEAK AND AVERAGE PLOT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DCCF	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.04	PK	32.3	-22.8	-	50.54	-	-	74	-23.46	252	133	V
3	* 2.484	30.75	RMS	32.3	-22.8	2.1	42.35	54	-11.65	-	-	252	133	V
4	2.531	30.99	RMS	32.4	-22.6	2.1	42.89	54	-11.11	-	-	252	133	V
2	2.56	42.91	PK	32.4	-22.7	-	52.61	-	-	74	-21.39	252	133	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection


HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fitr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.906	33.02	PK	31.3	-23.2	0	41.12	-	-	-	-	0-360	200	H
2	1.953	33.59	PK	31.4	-23.2	0	41.79	-	-	-	-	0-360	100	V
3	3.011	33.15	PK	33	-31.1	0	35.05	-	-	-	-	0-360	100	V
4	6.57	31.03	PK	35.6	-28.7	0	37.93	-	-	-	-	0-360	200	H
5	7.118	30.89	PK	35.6	-28	0	38.49	-	-	-	-	0-360	200	V
6	9.607	29.07	PK	36.7	-25.2	0	40.57	-	-	-	-	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fitr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1.953	31.78	MAv1	31.4	-23.2	2.06	42.04	-	-	-	-	54	107	V
1.955	43.33	PK2	31.4	-23.2	0	51.53	-	-	-	-	54	107	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak


MAv1 - KDB558074 Option 1 Maximum RMS Average

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fitr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.773	33	PK	29.9	-23.3	0	39.6	-	-	-	-	0-360	200	H
2	2.1	32.82	PK	31.5	-23	0	41.32	-	-	-	-	0-360	200	V
3	3.013	31.78	PK	33	-31.1	0	33.68	-	-	-	-	0-360	200	H
4	5.612	29.61	PK	34.7	-29.3	0	35.01	-	-	-	-	0-360	100	H
5	5.772	30.85	PK	34.9	-30.3	0	35.45	-	-	-	-	0-360	100	V
6	10.154	27.32	PK	37	-25.2	0	39.12	-	-	-	-	0-360	100	V

PK - Peak detector


Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/ Fitr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2.1	31.33	MAV1	31.5	-23	2.06	41.89	-	-	-	-	55	170	V
2.101	43.94	PK2	31.5	-23	0	52.44	-	-	-	-	55	170	V

PK2 - KDB558074 Method: Maximum Peak


MAV1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fitr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.001	34.51	PK	31.6	-23.2	0	42.91	-	-	-	-	0-360	100	H
2	2.066	33.07	PK	31.6	-23	0	41.67	-	-	-	-	0-360	100	V
3	3.485	32.56	PK	33	-31.1	0	34.46	-	-	-	-	0-360	200	V
4	6.323	31.11	PK	35.4	-29.3	0	37.21	-	-	-	-	0-360	100	H
5	9.245	30.12	PK	36.3	-26.9	0	39.52	-	-	-	-	0-360	200	V
6	9.748	27.53	PK	36.9	-25.7	0	38.73	-	-	-	-	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fitr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1.999	31.54	MAv1	31.6	-23.2	2.06	42	-	-	-	-	334	192	H
2.002	43.62	PK2	31.6	-23.2	0	52.02	-	-	-	-	334	192	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average


9.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	SS JB3 SN A051314-1	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	* 117.72	35.18	PK	16.3	-29.9	21.58	43.52	-21.94	0-360	201	H
5	* 243.2	38.1	PK	14.6	-28.9	23.8	46.02	-22.22	0-360	100	H
1	49.5075	50.54	PK	10.9	-30.8	30.64	40	-9.36	0-360	100	V
2	61.025	47.97	PK	10.8	-30.6	28.17	40	-11.83	0-360	100	V
3	80.0225	37.98	PK	10.4	-30.3	18.08	40	-21.92	0-360	100	V
6	806.1	31.26	PK	24.4	-26.2	29.46	46.02	-16.56	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.


TEST PROCEDURE

ANSI C63.4 - 2009

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT




LINE 1 RESULTS

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.177	40.32	PK	1.1	0	41.42	64.6	-23.18	-	-
2	.177	19.2	Av	1.1	0	20.3	-	-	54.6	-34.3
3	.3345	38.97	PK	.5	0	39.47	59.3	-19.83	-	-
4	.3345	28.2	Av	.5	0	28.7	-	-	49.3	-20.6
5	.6315	30.88	PK	.3	0	31.18	56	-24.82	-	-
6	.6315	15.91	Av	.3	0	16.21	-	-	46	-29.79
7	1.275	29.87	PK	.2	.1	30.17	56	-25.83	-	-
8	1.275	16.38	Av	.2	.1	16.68	-	-	46	-29.32
9	2.3235	29.75	PK	.2	.1	30.05	56	-25.95	-	-
10	2.3235	11.56	Av	.2	.1	11.86	-	-	46	-34.14
11	7.8315	33.48	PK	.2	.1	33.78	60	-26.22	-	-
12	7.8315	18.27	Av	.2	.1	18.57	-	-	50	-31.43
13	26.232	34.33	PK	.3	.3	34.93	60	-25.07	-	-
14	26.232	17.66	Av	.3	.3	18.26	-	-	50	-31.74

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBUV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBUV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
15	.177	43.84	PK	1.2	0	45.04	64.6	-19.56	-	-
16	.177	19.83	Av	1.2	0	21.03	-	-	54.6	-33.57
17	.3345	36.93	PK	.5	0	37.43	59.3	-21.87	-	-
18	.3345	29.41	Av	.5	0	29.91	-	-	49.3	-19.39
19	.8655	26.06	PK	.3	0	26.36	56	-29.64	-	-
20	.8655	13.33	Av	.3	0	13.63	-	-	46	-32.37
21	2.7195	27.18	PK	.2	.1	27.48	56	-28.52	-	-
22	2.7195	14.29	Av	.2	.1	14.59	-	-	46	-31.41
23	6.6885	31.01	PK	.2	.1	31.31	60	-28.69	-	-
24	6.6885	16.69	Av	.2	.1	16.99	-	-	50	-33.01
25	24.711	28.39	PK	.3	.2	28.89	60	-31.11	-	-
26	24.711	10.98	Av	.3	.2	11.48	-	-	50	-38.52