



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
http://www.pctestlab.com



## MEASUREMENT REPORT FCC Part 22 & 24

**Applicant Name:**  
LG Electronics MobileComm U.S.A  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States

**Date of Testing:**  
5/18 - 5/26/2016, 6/23/2016  
**Test Site/Location:**  
PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
0Y1605160926.ZNF

<b>FCC ID:</b>	<b>ZNFVS835</b>
<b>APPLICANT:</b>	<b>LG ELECTRONICS MOBILECOMM U.S.A</b>

**Application Type:** Certification  
**Model(s):** LG-VS835, LGVS835, VS835  
**EUT Type:** Portable Handset  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part(s):** §2 §22(H) §24(E)  
**Test Procedure(s):** ANSI/TIA-603-D-2010, KDB 971168 v02r02  
**Test Device Serial No.:** *identical prototype* [S/N: 02006, 02014, ]

Mode	Tx Frequency (MHz)	Emission Designator	ERP/EIRP	
			Max. Power (W)	Max. Power (dBm)
GPRS850	824.2 - 848.8	244KGXW	1.312	31.18
EDGE850	824.2 - 848.8	240KG7W	0.449	26.52
GPRS1900	1850.2 - 1909.8	243KGXW	1.233	30.91
EDGE1900	1850.2 - 1909.8	247KG7W	0.504	27.02
CDMA850	824.70 - 848.31	1M27F9W	0.171	22.32
CDMA1900	1851.25 - 1908.75	1M27F9W	0.315	24.99
WCDMA850	826.4 - 846.6	4M18F9W	0.148	21.71
WCDMA1900	1852.4 - 1907.6	4M17F9W	0.203	23.07

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortañez  
President




<b>FCC ID:</b> ZNFVS835		<b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/26/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset		Page 1 of 88

# T A B L E O F C O N T E N T S


FCC PART 22 & 24 MEASUREMENT REPORT .....		3
1.0 INTRODUCTION .....		4
1.1 Scope.....		4
1.2 Testing Facility .....		4
2.0 PRODUCT INFORMATION.....		5
2.1 Equipment Description .....		5
2.2 Device Capabilities .....		5
2.3 Test Configuration.....		5
2.4 EMI Suppression Device(s)/Modifications .....		5
3.0 DESCRIPTION OF TESTS .....		6
3.1 Evaluation Procedure.....		6
3.2 Cellular - Base Frequency Blocks .....		6
3.3 Cellular - Mobile Frequency Blocks.....		6
3.4 PCS - Base Frequency Blocks .....		6
3.5 PCS - Mobile Frequency Blocks .....		7
3.6 Radiated Measurements .....		7
4.0 MEASUREMENT UNCERTAINTY .....		8
5.0 TEST EQUIPMENT CALIBRATION DATA .....		9
6.0 SAMPLE CALCULATIONS .....		10
7.0 TEST RESULTS .....		11
7.1 Summary.....		11
7.2 Occupied Bandwidth .....		12
7.3 Spurious and Harmonic Emissions at Antenna Terminal .....		17
7.4 Band Edge Emissions at Antenna Terminal.....		45
7.5 Peak-Average Ratio.....		56
7.6 Radiated Power (ERP/EIRP) .....		59
7.7 Radiated Spurious Emissions Measurements.....		64
7.8 Frequency Stability / Temperature Variation .....		75
8.0 CONCLUSION.....		88

<b>FCC ID:</b> ZNFVS835		<b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/26/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset	Page 2 of 88	



# MEASUREMENT REPORT

## FCC Part 22 & 24




### §2.1033 General Information

**APPLICANT:** LG Electronics MobileComm U.S.A  
**APPLICANT ADDRESS:** 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA  
**FCC RULE PART(S):** §2 §22(H) §24(E)  
**BASE MODEL:** LG-VS835  
**FCC ID:** ZNFVS835  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**MODE:** CDMA / GSM / GPRS / WCDMA  
**FREQUENCY TOLERANCE:** ±0.00025 % (2.5 ppm)  
**Test Device Serial No.:** 02006, 02014       Production     Pre-Production     Engineering  
**DATE(S) OF TEST:** 5/18 - 5/26/2016  
**TEST REPORT S/N:** 0Y1605160926.ZNF

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



<b>FCC ID:</b> ZNFVS835		<b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/26/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset	Page 3 of 88	

# 1.0 INTRODUCTION


## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.



**Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area**

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 4 of 88

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFVS835**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, (BC0, BC1), 850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n UNII, Bluetooth (1x, EDR, LE)

### 2.3 Test Configuration

The LG Portable Handset FCC ID: ZNFVS835 was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

### 2.4 EMI Suppression Device(s)/Modifications


No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 5 of 88	



### 3.5 PCS - Mobile Frequency Blocks

§24.229



**BLOCK 1: 1850 – 1865 MHz (A)**

**BLOCK 4: 1885 – 1890 MHz (E)**

**BLOCK 2: 1865 – 1870 MHz (D)**

**BLOCK 5: 1890 – 1895 MHz (F)**

**BLOCK 3: 1870 – 1885 MHz (B)**

**BLOCK 6: 1895 – 1910 MHz (C)**

### 3.6 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2014. For measurements above 1GHz, absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, a 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

Radiated power and radiated spurious emissions levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-D-2010.

FCC ID: ZNFVS835	 <b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 7 of 88

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFVS835	 FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 8 of 88

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX3	Licensed Transmitter Cable Set	7/12/2015	Annual	7/12/2016	LTX3
-	RE3	Radiated Emissions Cable Set	11/18/2015	Annual	11/18/2016	RE3
Agilent	E5515C	Wireless Communications Test Set	1/29/2016	Biennial	1/29/2018	GB46310798
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	2/26/2016	Annual	2/26/2017	441119
Espec	ESX-2CA	Environmental Chamber	3/4/2016	Annual	3/4/2017	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	10/22/2014	Biennial	10/22/2016	128338
K & L	11SH10-3075/U18000	High Pass Filter	7/18/2015	Annual	7/18/2016	11SH10-3075/U18000-2
K & L	13SH10-1000/U1000	N Type High Pass Filter	7/18/2015	Annual	7/18/2016	13SH10-1000/U1000-1
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/4/2016	Annual	3/4/2017	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rhode & Schwarz	TS-PR18	Pre-Amplifier	3/7/2016	Annual	3/7/2017	101622
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			107826
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/17/2015	Annual	7/17/2016	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	6/2/2015	Annual	6/2/2016	103200
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	3/30/2016	Biennial	3/30/2018	9105-2403
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

**Table 5-1. Test Equipment**

**Note:**

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 9 of 88	

## 6.0 SAMPLE CALCULATIONS

### GPRS Emission Designator

**Emission Designator = 250KGXW**

GPRS BW = 250 kHz  
 G = Phase Modulation  
 X = Cases not otherwise covered  
 W = Combination (Audio/Data)

### EDGE Emission Designator

**Emission Designator = 250KG7W**

EDGE BW = 250 kHz  
 G = Phase Modulation  
 7 = Quantized/Digital Info  
 W = Combination (Audio/Data)

### CDMA Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### WCDMA Emission Designator

**Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### Spurious Radiated Emission

**Example: Spurious emission at 3700.40 MHz**

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was 25.50 dBm so this harmonic was  $25.50$  dBm  $- (-24.80) = 50.3$  dBc.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 10 of 88	

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: LG Electronics MobileComm U.S.A  
 FCC ID: ZNFVS835  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): CDMA / GSM / GPRS / WCDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
<b>TRANSMITTER MODE (TX)</b>					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a)	Conducted Band Edge / Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24)		PASS	Section 7.8
22.913(a.2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a)	Radiated Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.2.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 11 of 88	

## 7.2 Occupied Bandwidth

§2.1049

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used


KDB 971168 v02r02 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**


### Test Notes

None.

FCC ID: ZNFVS835	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 12 of 88	




Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode – Ch. 190)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 13 of 88




Plot 7-3. Occupied Bandwidth Plot (PCS GPRS Mode – Ch. 661)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 14 of 88




**Plot 7-5. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)**




**Plot 7-6. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)**

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 15 of 88



Plot 7-7. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4183)



Plot 7-8. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 16 of 88

### 7.3 Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §22.917(a) §24.238(a)

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

#### Test Procedure Used


KDB 971168 v02r02 – Section 6.0

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**


#### Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 17 of 88	




**Plot 7-9. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)**




**Plot 7-10. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)**

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 18 of 88




Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 19 of 88




Plot 7-13. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)




Plot 7-14. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 20 of 88




Plot 7-15. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)




Plot 7-16. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 21 of 88




Plot 7-17. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)




Plot 7-18. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 22 of 88




Plot 7-19. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)




Plot 7-20. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 23 of 88




Plot 7-21. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)




Plot 7-22. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 24 of 88




Plot 7-23. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)




Plot 7-24. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 25 of 88




Plot 7-25. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)




Plot 7-26. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 26 of 88




Plot 7-27. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-28. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 27 of 88




Plot 7-29. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-30. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset		Page 28 of 88




Plot 7-31. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-32. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 29 of 88




Plot 7-33. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-34. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 30 of 88




Plot 7-35. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-36. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset		Page 31 of 88




Plot 7-37. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-38. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 32 of 88




Plot 7-39. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)



Plot 7-40. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 33 of 88




Plot 7-41. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-42. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 34 of 88




Plot 7-43. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)




Plot 7-44. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 35 of 88




Plot 7-45. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-46. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 36 of 88




Plot 7-47. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-48. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 37 of 88




Plot 7-49. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)




Plot 7-50. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 38 of 88






Plot 7-53. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-54. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 40 of 88




Plot 7-55. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-56. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 41 of 88




Plot 7-57. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-58. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 42 of 88




Plot 7-59. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-60. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 43 of 88



Plot 7-61. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-62. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 44 of 88

## 7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a)

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 v02r02 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq$  1% of the emission bandwidth
4. VBW  $\geq$  3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq$  2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**


### Test Notes

Per 22.917(b), 24.238(b), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 45 of 88




Plot 7-63. Band Edge Plot (Cellular GPRS Mode – Ch. 128)




Plot 7-64. Band Edge Plot (Cellular GPRS Mode – Ch. 251)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 46 of 88




Plot 7-65. Band Edge Plot (PCS GPRS Mode – Ch. 512)




Plot 7-66. 4MHz Span Plot (PCS GPRS Mode – Ch. 512)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 47 of 88




Plot 7-67. Band Edge Plot (PCS GPRS Mode – Ch. 810)



Plot 7-68. 4MHz Span Plot (PCS GPRS Mode – Ch. 810)

FCC ID: ZNFVS835	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 48 of 88






Plot 7-71. Band Edge Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-72. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset		Page 50 of 88




Plot 7-73. Band Edge Plot (PCS CDMA Mode – Ch. 25)



Plot 7-74. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 51 of 88




Plot 7-75. Band Edge Plot (PCS CDMA Mode – Ch. 1175)



Plot 7-76. 4MHz Span Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 52 of 88




Plot 7-77. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-78. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 53 of 88





Plot 7-81. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-82. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 55 of 88

## 7.5 Peak-Average Ratio

### §24.232(d)

#### Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

#### Test Procedure Used


KDB 971168 v02r02 – Section 5.7.1

#### Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-4. Test Instrument & Measurement Setup**


#### Test Notes

None

FCC ID: ZNFVS835	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 56 of 88	




Plot 7-83. Peak-Average Ratio Plot (PCS GPRS Mode – Ch. 661)




Plot 7-84. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 57 of 88



Plot 7-85. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)



Plot 7-86. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset		Page 58 of 88

## 7.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c)

### Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using horizontally and vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".  
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize


FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset	Page 59 of 88	

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Radiated Test Setup <1GHz**



**Figure 7-6. Radiated Test Setup >1GHz**

FCC ID: ZNFVS835	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset		Page 60 of 88

**Test Notes**

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 61 of 88	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.20	GPRS850	H	215	181	25.66	5.00	30.66	1.165	38.45	-7.79
836.60	GPRS850	H	208	194	26.02	5.16	31.18	1.312	38.45	-7.27
848.80	GPRS850	H	225	200	24.58	5.31	29.89	0.975	38.45	-8.56
836.60	EDGE850	H	208	194	21.36	5.16	26.52	0.449	38.45	-11.93
836.60	GPRS850	V	224	38	25.22	5.00	30.22	1.052	38.45	-8.23

**Table 7-2. ERP (Cellular GPRS/EDGE)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.70	CDMA850	H	207	10	16.65	5.01	21.66	0.147	38.45	-16.79
836.52	CDMA850	H	221	27	17.16	5.16	22.32	0.171	38.45	-16.13
848.31	CDMA850	H	220	370	16.03	5.30	21.33	0.136	38.45	-17.12
836.52	CDMA850	V	139	350	16.33	5.00	21.33	0.136	38.45	-17.12

**Table 7-3. ERP (Cellular CDMA)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	197	216	16.24	5.03	21.27	0.134	38.45	-17.18
836.60	WCDMA850	H	211	214	16.15	5.16	21.31	0.135	38.45	-17.14
846.60	WCDMA850	H	359	209	16.43	5.28	21.71	0.148	38.45	-16.74
846.60	WCDMA850	V	210	189	15.63	5.04	20.67	0.117	38.45	-17.78

**Table 7-4. ERP (Cellular WCDMA)**

<b>FCC ID:</b> ZNFVS835	 <b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/26/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset	Page 62 of 88

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	H	100	268	21.56	9.35	30.91	1.233	33.01	-2.10
1880.00	GPRS1900	H	100	261	20.58	9.27	29.85	0.967	33.01	-3.16
1909.80	GPRS1900	H	102	267	20.29	9.25	29.54	0.899	33.01	-3.47
1850.20	EDGE1900	H	100	268	17.75	9.27	27.02	0.504	33.01	-5.99
1850.20	GPRS1900	V	115	247	19.92	9.21	29.13	0.818	33.01	-3.88

**Table 7-5. EIRP (PCS GPRS/EDGE)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	H	110	85	15.64	9.35	24.99	0.315	33.01	-8.02
1880.00	CDMA1900	H	102	81	14.36	9.27	23.63	0.231	33.01	-9.38
1908.75	CDMA1900	H	102	81	14.47	9.25	23.72	0.235	33.01	-9.29
1851.25	CDMA1900	V	100	144	12.90	9.21	22.11	0.163	33.01	-10.90

**Table 7-6. EIRP (PCS CDMA)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	100	154	13.73	9.34	23.07	0.203	33.01	-9.94
1880.00	WCDMA1900	H	132	124	13.71	9.27	22.98	0.199	33.01	-10.03
1907.60	WCDMA1900	H	108	154	13.28	9.24	22.52	0.179	33.01	-10.49
1852.40	WCDMA1900	V	111	206	12.31	9.22	21.53	0.142	33.01	-11.48

**Table 7-7. EIRP (PCS WCDMA)**

FCC ID: ZNFV835	 <b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 63 of 88

## 7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) 24.238(a)

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset	Page 64 of 88	

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-7. Test Instrument & Measurement Setup**

## Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 6) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 7) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 8) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFVS835	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 65 of 88

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MEASURED OUTPUT POWER: 30.66 dBm = 1.165 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  43.66 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1648.40	H	104	36	-53.88	6.69	-47.18	77.8
2472.60	H	101	144	-41.59	7.51	-34.08	64.7
3296.80	H	-	-	-59.71	7.36	-52.35	83.0
4121.00	H	100	0	-48.87	8.07	-40.80	71.5
4945.20	H	-	-	-60.17	8.74	-51.43	82.1
5769.40	H	100	139	-55.16	9.33	-45.84	76.5
6593.60	H	-	-	-59.68	9.93	-49.75	80.4

**Table 7-8. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MEASURED OUTPUT POWER: 31.18 dBm = 1.312 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  44.18 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	100	38	-52.68	6.70	-45.98	77.2
2509.80	H	100	94	-40.71	7.63	-33.08	64.3
3346.40	H	-	-	-60.33	7.52	-52.81	84.0
4183.00	H	100	177	-51.23	8.23	-43.00	74.2
5019.60	H	-	-	-59.98	8.75	-51.23	82.4
5856.20	H	100	193	-57.07	9.41	-47.66	78.8
6692.80	H	-	-	-58.20	9.57	-48.63	79.8

**Table 7-9. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)**

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MEASURED OUTPUT POWER: 29.89 dBm = 0.975 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  42.89 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1697.60	H	100	15	-43.37	6.70	-36.68	66.6
2546.40	H	100	99	-49.25	7.60	-41.66	71.5
3395.20	H	-	-	-60.57	7.68	-52.90	82.8
4244.00	H	100	190	-56.85	8.41	-48.44	78.3
5092.80	H	-	-	-59.69	8.62	-51.07	81.0
5941.60	H	-	-	-57.74	9.32	-48.42	78.3
6790.40	H	-	-	-57.81	9.47	-48.33	78.2

**Table 7-10. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)**

OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013  
 MEASURED OUTPUT POWER: 21.66 dBm = 0.147 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.66 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1649.40	H	100	16	-65.71	6.70	-59.01	80.7
2474.10	H	100	96	-57.96	7.52	-50.44	72.1
3298.80	H	-	-	-60.60	7.36	-53.24	74.9

**Table 7-11. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)**

OPERATING FREQUENCY: 836.52 MHz  
 CHANNEL: 384  
 MEASURED OUTPUT POWER: 22.32 dBm = 0.171 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.32 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.04	H	128	88	-63.69	6.70	-56.99	79.3
2509.56	H	100	95	-58.13	7.63	-50.50	72.8
3346.08	H	-	-	-61.00	7.51	-53.48	75.8

**Table 7-12. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)**

OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 777  
 MEASURED OUTPUT POWER: 21.33 dBm = 0.136 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.33 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1696.62	H	100	42	-62.00	6.70	-55.30	76.6
2544.93	H	100	44	-61.06	7.60	-53.47	74.8
3393.24	H	-	-	-60.51	7.67	-52.84	74.2

**Table 7-13. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)**

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MEASURED OUTPUT POWER: 21.27 dBm = 0.134 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.27 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1652.80	H	100	0	-71.58	6.70	-64.89	86.2
2479.20	H	-	-	-70.60	7.54	-63.06	84.3

**Table 7-14. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 4183  
 MEASURED OUTPUT POWER: 21.31 dBm = 0.135 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.31 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	100	89	-69.50	6.70	-62.80	84.1
2509.80	H	-	-	-70.27	7.63	-62.64	84.0

**Table 7-15. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)**

OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MEASURED OUTPUT POWER: 21.71 dBm = 0.148 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.71 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1693.20	H	100	297	-69.15	6.70	-62.46	84.2
2539.80	H	-	-	-69.96	7.60	-62.36	84.1

**Table 7-16. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)**

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 30.91 dBm = 1.233 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  43.91 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3700.40	H	168	246	-27.73	9.53	-18.20	49.1
5550.60	H	170	154	-51.95	11.01	-40.94	71.9
7400.80	H	135	141	-50.73	10.94	-39.78	70.7
9251.00	H	-	-	-55.26	11.52	-43.74	74.7

**Table 7-17. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MEASURED OUTPUT POWER: 29.85 dBm = 0.967 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  42.85 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	111	213	-26.84	9.39	-17.46	48.4
5640.00	H	126	230	-47.36	11.22	-36.13	67.0
7520.00	H	123	264	-47.59	11.10	-36.49	67.4
9400.00	H	-	-	-53.39	11.54	-41.85	72.8

**Table 7-18. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)**

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MEASURED OUTPUT POWER: 29.54 dBm = 0.899 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  42.54 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3819.60	H	156	284	-25.85	9.32	-16.53	47.4
5729.40	H	156	279	-48.34	11.37	-36.98	67.9
7639.20	H	153	267	-46.93	11.33	-35.59	66.5
9549.00	H	-	-	-52.20	11.78	-40.42	71.3

**Table 7-19. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)**

OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 25  
 MEASURED OUTPUT POWER: 24.99 dBm = 0.315 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  37.99 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3702.50	H	100	343	-47.21	9.52	-37.68	62.7
5553.75	H	-	-	-56.46	11.02	-45.44	70.4

**Table 7-20. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 600  
 MEASURED OUTPUT POWER: 23.63 dBm = 0.231 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.63 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	107	319	-44.00	9.39	-34.62	59.6
5640.00	H	-	-	-56.26	11.22	-45.03	70.0

**Table 7-21. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)**

OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175  
 MEASURED OUTPUT POWER: 23.72 dBm = 0.235 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.72 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3817.50	H	106	317	-40.33	9.32	-31.01	56.0
5726.25	H	-	-	-57.58	11.36	-46.22	71.2

**Table 7-22. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)**

OPERATING FREQUENCY: 1852.40 MHz  
 CHANNEL: 9262  
 MEASURED OUTPUT POWER: 23.07 dBm = 0.203 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.07 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3704.80	H	100	67	-51.89	9.52	-42.37	65.4
5557.20	H	-	-	-55.56	11.03	-44.53	67.6

**Table 7-23. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 9400  
 MEASURED OUTPUT POWER: 22.98 dBm = 0.199 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.98 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	100	333	-51.22	9.39	-41.84	64.9
5640.00	H	-	-	-56.83	11.22	-45.60	68.7

**Table 7-24. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)**

OPERATING FREQUENCY: 1907.60 MHz  
 CHANNEL: 9538  
 MEASURED OUTPUT POWER: 22.52 dBm = 0.179 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.52 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3815.20	H	107	320	-48.37	9.32	-39.05	62.1
5722.80	H	-	-	-56.60	11.35	-45.25	68.3

**Table 7-25. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)**

## 7.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.235

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 22, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency. For Part 24 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.***

### Test Procedure Used

ANSI/TIA-603-D-2010

### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes

None

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 75 of 88	

## Frequency Stability / Temperature Variation

§2.1055 §22.355

OPERATING FREQUENCY: 836,600,000 Hz  
 CHANNEL: 190  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,600,074	74	0.0000088
100 %		- 30	836,599,877	-123	-0.0000147
100 %		- 20	836,600,046	46	0.0000055
100 %		- 10	836,599,755	-245	-0.0000293
100 %		0	836,600,042	42	0.0000050
100 %		+ 10	836,599,961	-39	-0.0000047
100 %		+ 20	836,599,929	-71	-0.0000085
100 %		+ 30	836,599,937	-63	-0.0000075
100 %		+ 40	836,599,653	-347	-0.0000415
100 %		+ 50	836,599,849	-151	-0.0000180
BATT. ENDPOINT	3.45	+ 20	836,599,771	-229	-0.0000274

**Table 7-26. Frequency Stability Data (Cellular GPRS Mode – Ch. 190)**

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 76 of 88	

**Frequency Stability / Temperature Variation**

§2.1055 §22.355



**Figure 7-8. Frequency Stability Graph (Cellular GPRS Mode – Ch. 190)**

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset	Page 77 of 88	

## Frequency Stability / Temperature Variation

§2.1055 §22.355

OPERATING FREQUENCY: 836,520,000 Hz  
 CHANNEL: 384  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,520,007	7	0.0000008
100 %		- 30	836,519,908	-92	-0.0000110
100 %		- 20	836,519,901	-99	-0.0000118
100 %		- 10	836,520,012	12	0.0000014
100 %		0	836,519,854	-146	-0.0000175
100 %		+ 10	836,519,909	-91	-0.0000109
100 %		+ 20	836,520,159	159	0.0000190
100 %		+ 30	836,520,361	361	0.0000432
100 %		+ 40	836,519,986	-14	-0.0000017
100 %		+ 50	836,519,974	-26	-0.0000031
BATT. ENDPOINT		3.45	+ 20	836,520,204	204

Table 7-27. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 78 of 88	

**Frequency Stability / Temperature Variation**

§2.1055 §22.355



**Figure 7-9. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)**

<b>FCC ID:</b> ZNFVS835	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>	<b>LG</b>	<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/28/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset		Page 79 of 88

## Frequency Stability / Temperature Variation

§2.1055 §22.355


OPERATING FREQUENCY: 836,600,000 Hz  
 CHANNEL: 4183  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,600,041	41	0.0000049
100 %		- 30	836,599,956	-44	-0.0000053
100 %		- 20	836,600,046	46	0.0000055
100 %		- 10	836,599,972	-28	-0.0000033
100 %		0	836,599,967	-33	-0.0000039
100 %		+ 10	836,599,754	-246	-0.0000294
100 %		+ 20	836,599,863	-137	-0.0000164
100 %		+ 30	836,600,200	200	0.0000239
100 %		+ 40	836,599,747	-253	-0.0000302
100 %		+ 50	836,600,146	146	0.0000175
BATT. ENDPOINT	3.45	+ 20	836,599,716	-284	-0.0000339

**Table 7-28. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)**

**Frequency Stability / Temperature Variation**

§2.1055 §22.355



**Figure 7-10. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)**

<p>FCC ID: ZNFVS835</p>		<p>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</p>		<p>Reviewed by: Quality Manager</p>
<p>Test Report S/N: 0Y1605160926.ZNF</p>	<p>Test Dates: 5/18 - 5/28/2016, 6/23/2016</p>	<p>EUT Type: Portable Handset</p>	<p>Page 81 of 88</p>	

## Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 661  
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,879,999,759	-241	-0.0000128
100 %		- 30	1,879,999,792	-208	-0.0000111
100 %		- 20	1,880,000,016	16	0.0000009
100 %		- 10	1,880,000,265	265	0.0000141
100 %		0	1,880,000,029	29	0.0000015
100 %		+ 10	1,879,999,711	-289	-0.0000154
100 %		+ 20	1,880,000,376	376	0.0000200
100 %		+ 30	1,879,999,961	-39	-0.0000021
100 %		+ 40	1,880,000,169	169	0.0000090
100 %		+ 50	1,879,999,675	-325	-0.0000173
BATT. ENDPOINT	3.45	+ 20	1,880,000,132	132	0.0000070

**Table 7-29. Frequency Stability Data (PCS GPRS Mode – Ch. 661)**


**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 82 of 88	

**Frequency Stability / Temperature Variation**

§2.1055 §24.235



**Figure 7-11. Frequency Stability Graph (PCS GPRS Mode – Ch. 661)**

<b>FCC ID:</b> ZNFV835	<b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/26/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset	Page 83 of 88

## Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 600  
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,339	339	0.0000180
100 %		- 30	1,880,000,316	316	0.0000168
100 %		- 20	1,880,000,375	375	0.0000199
100 %		- 10	1,880,000,040	40	0.0000021
100 %		0	1,879,999,963	-37	-0.0000020
100 %		+ 10	1,880,000,355	355	0.0000189
100 %		+ 20	1,879,999,943	-57	-0.0000030
100 %		+ 30	1,879,999,889	-111	-0.0000059
100 %		+ 40	1,879,999,904	-96	-0.0000051
100 %		+ 50	1,879,999,787	-213	-0.0000113
BATT. ENDPOINT		3.45	+ 20	1,879,999,773	-227

Table 7-30. Frequency Stability Data (PCS CDMA Mode – Ch. 600)


**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset	Page 84 of 88	

**Frequency Stability / Temperature Variation**

**§2.1055 §24.235**



**Figure 7-12. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)**

<b>FCC ID:</b> ZNFVS835	<b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/26/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset	Page 85 of 88

## Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 9400  
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,879,999,968	-32	-0.0000017
100 %		- 30	1,880,000,263	263	0.0000140
100 %		- 20	1,880,000,134	134	0.0000071
100 %		- 10	1,879,999,983	-17	-0.0000009
100 %		0	1,880,000,277	277	0.0000147
100 %		+ 10	1,879,999,859	-141	-0.0000075
100 %		+ 20	1,880,000,278	278	0.0000148
100 %		+ 30	1,879,999,854	-146	-0.0000078
100 %		+ 40	1,880,000,134	134	0.0000071
100 %		+ 50	1,880,000,011	11	0.0000006
BATT. ENDPOINT		3.45	+ 20	1,879,999,779	-221

Table 7-31. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)


**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFVS835	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/28/2016, 6/23/2016	EUT Type: Portable Handset	Page 86 of 88	

**Frequency Stability / Temperature Variation**

**§2.1055 §24.235**



**Figure 7-13. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)**

<b>FCC ID:</b> ZNFV835	<b>FCC Pt. 22 &amp; 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1605160926.ZNF	<b>Test Dates:</b> 5/18 - 5/28/2016, 6/23/2016	<b>EUT Type:</b> Portable Handset	Page 87 of 88

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFVS835** complies with all the requirements of Parts 22 & 24 of the FCC rules.

FCC ID: ZNFVS835		FCC Pt. 22 & 24 CDMA / GSM / GPRS / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1605160926.ZNF	Test Dates: 5/18 - 5/26/2016, 6/23/2016	EUT Type: Portable Handset		Page 88 of 88