



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
http://www.pctestlab.com



## MEASUREMENT REPORT FCC Part 22, 24, & 27

**Applicant Name:**  
LG Electronics MobileComm U.S.A.  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States

**Date of Testing:**  
1/20-2/18/2016  
**Test Site/Location:**  
PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
0Y1601180117-R2.ZNF

<b>FCC ID:</b>	<b>ZNFVS987</b>
<b>APPLICANT:</b>	<b>LG ELECTRONICS MOBILECOMM U.S.A.</b>

**Application Type:** Certification  
**Model(s):** LG-VS987, LG-US992, LG-RS988, LG-VS987T, LG-VS987G, LG-VS987P, LGVS987, VS987, LGUS992, US992, LGRS988, RS988, LG-RS988L, LGRS988L, RS988L  
**EUT Type:** Portable Handset  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part(s):** §2 §22(H) §24(E) §27(L)  
**Test Procedure(s):** ANSI/TIA-603-C-2004, KDB 971168 v02r02  
**Test Device Serial No.:** *identical prototype* [S/N: 03738, 03746, 03720]

Mode	Tx Frequency (MHz)	Emission Designator	ERP/EIRP	
			Max. Power (W)	Max. Power (dBm)
GSM850	824.2 - 848.8	240KGXW	2.453	33.90
EDGE850	824.2 - 848.8	243KG7W	0.624	27.95
GSM1900	1850.2 - 1909.8	246KGXW	0.773	28.88
EDGE1900	1850.2 - 1909.8	244KG7W	0.235	23.71
CDMA850	824.70 - 848.31	1M27F9W	0.204	23.10
CDMA1900	1851.25 - 1908.75	1M27F9W	0.068	18.31
WCDMA850	826.4 - 846.6	4M14F9W	0.311	24.93
WCDMA1700	1712.4 - 1752.6	4M13F9W	0.179	22.53
WCDMA1900	1852.4 - 1907.6	4M16F9W	0.319	25.04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 0Y1601180117-R2.ZNF) supersedes and replaces the previously issued test report (S/N: 0Y1601180117-R1.ZNF) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortanez  
President




<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 1 of 104	

# T A B L E O F C O N T E N T S


FCC PART 22, 24, & 27 MEASUREMENT REPORT .....		3
1.0 INTRODUCTION .....		4
1.1 Scope.....		4
1.2 Testing Facility .....		4
2.0 PRODUCT INFORMATION.....		5
2.1 Equipment Description .....		5
2.2 Device Capabilities .....		5
2.3 Test Configuration.....		5
2.4 EMI Suppression Device(s)/Modifications .....		5
3.0 DESCRIPTION OF TESTS .....		6
3.1 Evaluation Procedure.....		6
3.2 Cellular - Base Frequency Blocks .....		6
3.3 Cellular - Mobile Frequency Blocks.....		6
3.4 PCS - Base Frequency Blocks .....		6
3.5 PCS - Mobile Frequency Blocks .....		7
3.6 AWS - Base Frequency Blocks .....		7
3.7 AWS - Mobile Frequency Blocks.....		7
3.8 Radiated Measurements .....		8
4.0 MEASUREMENT UNCERTAINTY .....		9
5.0 TEST EQUIPMENT CALIBRATION DATA .....		10
6.0 SAMPLE CALCULATIONS .....		11
7.0 TEST RESULTS .....		12
7.1 Summary.....		12
7.2 Occupied Bandwidth .....		13
7.3 Spurious and Harmonic Emissions at Antenna Terminal .....		19
7.4 Band Edge Emissions at Antenna Terminal.....		52
7.5 Peak-Average Ratio .....		65
7.6 Radiated Power (ERP/EIRP) .....		68
7.7 Radiated Spurious Emissions Measurements.....		73
7.8 Frequency Stability / Temperature Variation .....		89
8.0 CONCLUSION.....		104

<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 2 of 104	



# MEASUREMENT REPORT

## FCC Part 22, 24, & 27




### §2.1033 General Information

**APPLICANT:** LG Electronics MobileComm U.S.A.  
**APPLICANT ADDRESS:** 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA  
**FCC RULE PART(S):** §2 §22(H) §24(E) §27(L)  
**BASE MODEL:** LG-VS987  
**FCC ID:** ZNFVS987  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**MODE:** GSM/ CDMA / WCDMA  
**FREQUENCY TOLERANCE:** ±0.00025 % (2.5 ppm)  
**Test Device Serial No.:** 03738, 03746, 03720       Production     Pre-Production     Engineering  
**DATE(S) OF TEST:** 1/20-2/18/2016  
**TEST REPORT S/N:** 0Y1601180117-R2.ZNF

### Test Facility / Accreditations

Measurements were performed at **PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 3 of 104	

# 1.0 INTRODUCTION


## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.



**Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area**

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 4 of 104	

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFVS987**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

For PCS Band CDMA, this device employs an antenna switching mechanism that allows the EUT's uplink transmission to switch entirely from the main antenna to the diversity antenna. Both antennas cannot transmit simultaneously so dual transmission conditions were not investigated. The diversity transmit antenna transmits at a lower power level than the main antenna. Test data for the diversity antenna's EIRP are reported herein.

This EUT supports a Camera Module accessory (Model: CBG-700) that can be installed on the EUT. Additional ERP/EIRP and spurious emission measurements were performed with a Camera Module accessory installed on the EUT to ensure compliance. The worst case radiated emissions data is reported herein.

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

### 2.3 Test Configuration

The LG Portable Handset FCC ID: ZNFVS987 was tested per the guidance of ANSI/TIA-603-C-2004 and KDB 971168 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 5 of 104

### 3.0 DESCRIPTION OF TESTS


#### 3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 v02r02) were used in the measurement of the **LG Portable Handset FCC ID: ZNFVS987**.

Deviation from Measurement Procedure.....None

#### 3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A\* Low + A)


BLOCK 3: 890 – 891.5 MHz (A\* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B\*)

#### 3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A\* Low + A)


BLOCK 3: 845 – 846.5 MHz (A\* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B\*)

#### 3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: ZNFVS987	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 6 of 104

### 3.5 PCS - Mobile Frequency Blocks

§24.229



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)


BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

### 3.6 AWS - Base Frequency Blocks

§27.5(h)



BLOCK 1: 2110 – 2120 MHz (A)

BLOCK 4: 2135 – 2140 MHz (D)

BLOCK 2: 2120 – 2130 MHz (B)


BLOCK 5: 2140 – 2145 MHz (E)

BLOCK 3: 2130 – 2135 MHz (C)

BLOCK 6: 2145 – 2155 MHz (F)

### 3.7 AWS - Mobile Frequency Blocks

§27.5(h)



BLOCK 1: 1710 – 1720 MHz (A)

BLOCK 4: 1735 – 1740 MHz (D)

BLOCK 2: 1720 – 1730 MHz (B)

BLOCK 5: 1740 – 1745 MHz (E)

BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 7 of 104

### 3.8 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(d)(10) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A 3/4" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss} \text{ [dB]} + \text{antenna gain} \text{ [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss} \text{ [dB]}$ .

Radiated power levels are investigated with the receive antenna vertically polarized while radiated spurious emissions levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-C-2004.

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 8 of 104

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 9 of 104	

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx3	Licensed Transmitter Cable Set	6/12/2015	Annual	6/12/2016	LTx3
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	4/28/2015	Annual	4/28/2016	RE1
Agilent	8447D	Broadband Amplifier	6/12/2015	Annual	6/12/2016	2443A01900
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/24/2015	Annual	3/24/2016	MYS2350166
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
Com-Power	PAM-118A	Pre-Amplifier	4/10/2015	Annual	4/10/2016	551042
Emco	3115	Horn Antenna (1-18GHz)	3/30/2014	Biennial	3/30/2016	9704-5182
Espec	ESX-2CA	Environmental Chamber	3/17/2015	Annual	3/17/2016	17620
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	10/22/2014	Biennial	10/22/2016	128338
K & L	11SH10-3075/U18000	High Pass Filter	7/18/2015	Annual	7/18/2016	11SH10-3075/U18000-2
K & L	13SH10-1000/U1000	N Type High Pass Filter	7/18/2015	Annual	7/18/2016	13SH10-1000/U1000-2
Mini-Circuits	PWR-SENS-4RMS	USB Power Sensor	3/11/2015	Annual	3/11/2016	11210140001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Mini-Circuits	TVA-11-422	RF Power Amp	N/A			QA1303002
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			107826
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	3/12/2015	Annual	3/12/2016	100342
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/5/2015	Annual	3/5/2016	100071
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	2/21/2014	Biennial	2/21/2016	9105-2404
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/28/2014	Biennial	3/28/2016	A051107

**Table 5-1. Test Equipment**

**Note:**

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 10 of 104	

## 6.0 SAMPLE CALCULATIONS

### GSM Emission Designator

**Emission Designator = 250KGXW**

GSM BW = 250 kHz  
 G = Phase Modulation  
 X = Cases not otherwise covered  
 W = Combination (Audio/Data)

### EDGE Emission Designator

**Emission Designator = 250KG7W**

EDGE BW = 250 kHz  
 G = Phase Modulation  
 7 = Quantized/Digital Info  
 W = Combination (Audio/Data)

### CDMA Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### WCDMA Emission Designator

**Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### Spurious Radiated Emission

**Example: Spurious emission at 3700.40 MHz**

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was 25.50 dBm so this harmonic was  $25.50$  dBm  $- (-24.80) = 50.3$  dBc.

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 11 of 104	

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: LG Electronics MobileComm U.S.A.  
 FCC ID: ZNFVS987  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): GSM/ CDMA / WCDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
<b>TRANSMITTER MODE (TX)</b>					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	Conducted Band Edge / Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a.2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d.4)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	Radiated Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.2.

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 12 of 104	

## 7.2 Occupied Bandwidth

§2.1049

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used


KDB 971168 v02r02 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**


### Test Notes

None.

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 13 of 104




Plot 7-1. Occupied Bandwidth Plot (Cellular GSM Mode – Ch. 190)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 14 of 104




Plot 7-3. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 15 of 104




Plot 7-5. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-6. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 16 of 104




Plot 7-7. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4183)



Plot 7-8. Occupied Bandwidth Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 17 of 104



Plot 7-9. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 18 of 104

### 7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h)

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

#### Test Procedure Used


KDB 971168 v02r02 – Section 6.0

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**


#### Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24, Part 27. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 19 of 104




Plot 7-10. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-11. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 20 of 104




Plot 7-12. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-13. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 21 of 104




Plot 7-14. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)




Plot 7-15. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 22 of 104






Plot 7-18. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)




Plot 7-19. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 24 of 104




Plot 7-20. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-21. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 25 of 104




Plot 7-22. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-23. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 26 of 104




Plot 7-24. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-25. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 27 of 104




Plot 7-26. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)




Plot 7-27. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 28 of 104




Plot 7-28. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-29. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 29 of 104




Plot 7-30. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-31. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 30 of 104




Plot 7-32. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-33. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 31 of 104




Plot 7-34. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-35. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 32 of 104




Plot 7-36. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)



Plot 7-37. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset			Page 33 of 104




Plot 7-38. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-39. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 34 of 104




Plot 7-40. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-41. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 35 of 104




Plot 7-42. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)



Plot 7-43. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 36 of 104




Plot 7-44. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)




Plot 7-45. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 37 of 104




Plot 7-46. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-47. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 38 of 104




Plot 7-48. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-49. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 39 of 104




Plot 7-50. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)




Plot 7-51. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 40 of 104




Plot 7-52. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-53. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 41 of 104




Plot 7-54. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-55. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/CDMA/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 42 of 104




Plot 7-56. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-57. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 43 of 104




Plot 7-58. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-59. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 44 of 104




Plot 7-60. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-61. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 45 of 104




Plot 7-62. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)




Plot 7-63. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 46 of 104




Plot 7-64. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-65. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 47 of 104




Plot 7-66. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-67. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 48 of 104




Plot 7-68. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-69. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 49 of 104



Plot 7-70. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-71. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 50 of 104



## 7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h)

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 v02r02 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq$  1% of the emission bandwidth
4. VBW  $\geq$  3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq$  2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**


### Test Notes

Per 22.917(b), 24.238(b), 27.53(h)(3), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 52 of 104




Plot 7-73. Band Edge Plot (Cellular GSM Mode – Ch. 128)




Plot 7-74. Band Edge Plot (Cellular GSM Mode – Ch. 251)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 53 of 104




Plot 7-75. Band Edge Plot (PCS GSM Mode – Ch. 512)




Plot 7-76. 4MHz Span Plot (PCS GSM Mode – Ch. 512)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 54 of 104




Plot 7-77. Band Edge Plot (PCS GSM Mode – Ch. 810)




Plot 7-78. 4MHz Span Plot (PCS GSM Mode – Ch. 810)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 55 of 104




Plot 7-79. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)



Plot 7-80. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 56 of 104




Plot 7-81. Band Edge Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-82. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 57 of 104




Plot 7-83. Band Edge Plot (PCS CDMA Mode – Ch. 25)




Plot 7-84. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 58 of 104




Plot 7-85. Band Edge Plot (PCS CDMA Mode – Ch. 1175)




Plot 7-86. 4MHz Span Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 59 of 104




Plot 7-87. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-88. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 60 of 104




Plot 7-89. Band Edge Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-90. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset			Page 61 of 104



Plot 7-91. Band Edge Plot (AWS WCDMA Mode – Ch. 1862)




Plot 7-92. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1862)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 62 of 104



Plot 7-93. Band Edge Plot (PCS WCDMA Mode – Ch. 9262)



Plot 7-94. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 63 of 104



Plot 7-95. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-96. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 64 of 104

## 7.5 Peak-Average Ratio

### §24.232(d)

#### Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

#### Test Procedure Used


KDB 971168 v02r02 – Section 5.7.1

#### Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-4. Test Instrument & Measurement Setup**


#### Test Notes

None

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 65 of 104		




**Plot 7-97. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)**




**Plot 7-98. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)**

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 66 of 104



Plot 7-99. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)



Plot 7-100. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 67 of 104

## 7.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c) 27.50(d.4)

### Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".  
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize


FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 68 of 104

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Radiated Test Setup <1GHz**



**Figure 7-6. Radiated Test Setup >1GHz**

<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 69 of 104	

### Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

Frequency [MHz]	Mode	Module	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.20	GSM850	Standard	H	1.81	76	29.02	4.27	33.29	2.131	38.45	-5.17
836.60	GSM850	Standard	H	1.69	65	29.41	4.46	33.87	2.440	38.45	-4.58
848.80	GSM850	Standard	H	1.71	75	29.24	4.66	33.90	2.453	38.45	-4.55
848.80	EDGE850	Standard	H	1.71	75	23.29	4.66	27.95	0.624	38.45	-10.50
848.80	GSM850	Camera	H	2.70	29	26.33	5.03	30.99	1.255	38.45	-7.46

**Table 7-2. ERP (Cellular GSM)**

<b>FCC ID:</b> ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset			Page 70 of 104

Frequency [MHz]	Mode	Module	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.70	CDMA850	Standard	H	1.94	72	18.05	4.27	22.32	0.171	38.45	-16.13
836.52	CDMA850	Standard	H	1.93	75	18.31	4.46	22.77	0.189	38.45	-15.68
848.31	CDMA850	Standard	H	1.94	72	18.45	4.65	23.10	0.204	38.45	-15.35
848.31	CDMA850	Camera	H	2.67	43	17.71	5.02	22.36	0.172	38.45	-16.09

**Table 7-3. ERP (Cellular CDMA)**

Frequency [MHz]	Mode	Module	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	Standard	H	1.74	72	18.77	4.30	23.07	0.203	38.45	-15.38
836.60	WCDMA850	Standard	H	1.69	67	19.47	4.46	23.93	0.247	38.45	-14.52
846.60	WCDMA850	Standard	H	1.74	71	19.28	4.62	23.90	0.246	38.45	-14.55
836.60	WCDMA850	Camera	V	1.37	176	20.47	4.46	24.93	0.311	38.45	-13.52

**Table 7-4. ERP (Cellular WCDMA)**

Frequency [MHz]	Mode	Module	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	Standard	H	1.12	313	12.72	9.45	22.17	0.165	30.00	-7.83
1732.60	WCDMA1700	Standard	H	1.12	313	12.28	9.41	21.69	0.148	30.00	-8.31
1752.60	WCDMA1700	Standard	H	1.12	313	12.46	9.38	21.84	0.153	30.00	-8.16
1712.40	WCDMA1700	Camera	H	1.22	338	13.08	9.65	22.53	0.179	30.00	-7.47

**Table 7-5. EIRP (AWS WCDMA)**

Frequency [MHz]	Mode	Module	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GSM1900	Standard	H	1.55	327	18.19	9.24	27.43	0.554	33.01	-5.58
1880.00	GSM1900	Standard	H	1.72	323	15.71	9.21	24.92	0.311	33.01	-8.09
1909.80	GSM1900	Standard	H	1.72	329	14.64	9.25	23.89	0.245	33.01	-9.12
1850.20	EDGE1900	Standard	H	1.55	327	14.47	9.24	23.71	0.235	33.01	-9.30
1850.20	GSM1900	Camera	V	1.78	94	19.67	9.21	28.88	0.773	33.01	-4.13

**Table 7-6. EIRP (PCS GSM)**

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 71 of 104		

Frequency [MHz]	Mode	Module	Antenna	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	Standard	Main	H	1.12	326	8.86	9.24	18.10	0.065	33.01	-14.91
1880.00	CDMA1900	Standard	Main	H	1.12	326	6.99	9.21	16.20	0.042	33.01	-16.81
1908.75	CDMA1900	Standard	Main	H	1.12	326	6.62	9.24	15.86	0.039	33.01	-17.15
1851.25	CDMA1900	Standard	Diversity	H	1.34	84	7.69	9.24	16.93	0.049	33.01	-16.08
1851.25	CDMA1900	Camera	Main	H	1.12	326	13.60	9.54	18.31	0.068	33.01	-14.70

**Table 7-7. EIRP (PCS CDMA)**

Frequency [MHz]	Mode	Module	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	Standard	H	1.16	329	14.38	9.24	23.62	0.230	33.01	-9.39
1880.00	WCDMA1900	Standard	H	1.12	320	14.84	9.21	24.05	0.254	33.01	-8.96
1907.60	WCDMA1900	Standard	H	1.08	329	14.19	9.23	23.42	0.220	33.01	-9.59
1880.00	WCDMA1900	Camera	H	2.44	336	15.83	9.27	25.04	0.319	33.01	-7.97

**Table 7-8. EIRP (PCS WCDMA)**

<b>FCC ID:</b> ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset		Page 72 of 104	

## 7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) 24.238(a) 27.53(h)

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 v02r02 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 73 of 104

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-7. Test Instrument & Measurement Setup**

## Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 6) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 7) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 74 of 104	

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MEASURED OUTPUT POWER: 33.29 dBm = 2.131 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  46.29 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1648.40	H	1.29	247	-56.59	6.56	-50.03	83.3
2472.60	H	1.17	224	-48.42	7.29	-41.12	74.4
3296.80	H	1.19	211	-57.62	7.37	-50.26	83.5
4121.00	H	-	-	-57.79	8.02	-49.77	83.1

**Table 7-9. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MEASURED OUTPUT POWER: 33.87 dBm = 2.440 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  46.87 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	1.01	242	-48.01	6.55	-41.45	75.3
2509.80	H	1.12	222	-49.53	7.34	-42.19	76.1
3346.40	H	1.02	215	-58.79	7.44	-51.35	85.2
4183.00	H	-	-	-57.71	8.20	-49.51	83.4

**Table 7-10. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)**

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MEASURED OUTPUT POWER: 33.90 dBm = 2.453 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  46.90 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1697.60	H	1.04	250	-46.20	6.55	-39.65	73.6
2546.40	H	1.02	250	-49.37	7.36	-42.00	75.9
3395.20	H	1.01	260	-58.30	7.51	-50.79	84.7
4244.00	H	-	-	-57.48	8.40	-49.08	83.0

**Table 7-11. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)**

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MEASURED OUTPUT POWER: 33.90 dBm = 2.453 W  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  46.90 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1697.60	H	1.65	16	-45.82	6.55	-39.28	73.2
2546.40	H	1.71	332	-43.22	7.36	-35.86	69.8
3395.20	H	1.78	5	-58.42	7.51	-50.91	84.8
4244.00	H	-	-	-57.83	8.40	-49.43	83.3

**Table 7-12. Radiated Spurious Data with Camera Module (Cellular GSM Mode – Ch. 251)**

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 76 of 104	

OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013  
 MEASURED OUTPUT POWER: 22.32 dBm = 0.171 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.32 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1649.40	H	1.06	350	-56.66	6.56	-50.10	72.4
2474.10	H	2.25	0	-54.21	7.30	-46.91	69.2
3298.80	H	-	-	-59.50	7.37	-52.13	74.5

**Table 7-13. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)**

OPERATING FREQUENCY: 836.52 MHz  
 CHANNEL: 384  
 MEASURED OUTPUT POWER: 22.77 dBm = 0.189 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.77 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.04	H	1.09	340	-52.74	6.55	-46.19	69.0
2509.56	H	2.53	10	-54.50	7.34	-47.15	69.9
3346.08	H	-	-	-60.47	7.44	-53.03	75.8

**Table 7-14. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)**

OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 777  
 MEASURED OUTPUT POWER: 23.10 dBm = 0.204 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.10 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1696.62	H	1.10	341	-50.60	6.55	-44.05	67.1
2544.93	H	2.18	331	-56.63	7.36	-49.27	72.4
3393.24	H	-	-	-59.48	7.51	-51.97	75.1

Table 7-15. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 777  
 MEASURED OUTPUT POWER: 23.10 dBm = 0.204 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.10 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1696.62	H	1.75	7	-53.52	6.55	-46.97	70.1
2544.93	H	1.68	131	-42.13	7.36	-34.77	57.9
3393.24	H	-	-	-60.36	7.51	-52.85	75.9

Table 7-16. Radiated Spurious Data with Camera Module (Cellular CDMA Mode – Ch. 777)

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MEASURED OUTPUT POWER: 23.07 dBm = 0.203 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.07 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1652.80	H	2.84	180	-59.94	6.56	-53.38	76.5
2479.20	H	-	-	-63.67	7.30	-56.37	79.4

**Table 7-17. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 4183  
 MEASURED OUTPUT POWER: 23.93 dBm = 0.247 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.93 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	2.67	180	-57.24	6.55	-50.68	74.6
2509.80	H	-	-	-62.99	7.34	-55.65	79.6

**Table 7-18. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)**

OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MEASURED OUTPUT POWER: 23.90 dBm = 0.246 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.90 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1693.20	H	2.56	179	-56.49	6.55	-49.95	73.8
2539.80	H	-	-	-63.34	7.36	-55.98	79.9

**Table 7-19. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)**

OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MEASURED OUTPUT POWER: 23.90 dBm = 0.246 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.91 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1693.20	V	2.11	203	-54.62	6.58	-48.03	71.9
2539.80	V	-	-	-53.63	7.37	-46.26	70.2

**Table 7-20. Radiated Spurious Data with Camera Module (Cellular WCDMA Mode – Ch. 4233)**

OPERATING FREQUENCY: 1712.40 MHz  
 CHANNEL: 1312  
 MEASURED OUTPUT POWER: 22.17 dBm = 0.165 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.17 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3424.80	H	2.08	123	-53.91	9.68	-44.23	66.4
5137.20	H	-	-	-56.23	10.68	-45.55	67.7

**Table 7-21. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)**

OPERATING FREQUENCY: 1732.60 MHz  
 CHANNEL: 1413  
 MEASURED OUTPUT POWER: 21.69 dBm = 0.148 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.69 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.20	H	2.01	138	-51.66	9.71	-41.95	64.1
5197.80	H	-	-	-55.71	10.59	-45.12	67.3

**Table 7-22. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1413)**

OPERATING FREQUENCY: 1752.60 MHz  
 CHANNEL: 1513  
 MEASURED OUTPUT POWER: 21.84 dBm = 0.153 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.84 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.20	H	2.00	128	-49.48	9.73	-39.75	61.9
5257.80	H	-	-	-55.87	10.64	-45.23	67.4

**Table 7-23. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)**

OPERATING FREQUENCY: 1752.60 MHz  
 CHANNEL: 1513  
 MEASURED OUTPUT POWER: 21.84 dBm = 0.153 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  34.85 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.20	H	2.52	234	-57.16	8.40	-48.75	70.9
5257.80	H	-	-	-57.50	10.36	-47.14	69.3

**Table 7-24. Radiated Spurious Data with Camera Module (AWS WCDMA Mode – Ch. 1513)**

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 27.43 dBm = 0.554 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  40.43 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3700.40	H	1.33	19	-43.59	9.44	-34.15	61.6
5550.60	H	1.64	10	-49.59	10.78	-38.80	66.2
7400.80	H	-	-	-52.00	10.69	-41.32	68.7

Table 7-25. Radiated Spurious Data (PCS GSM Mode – Ch. 512)

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MEASURED OUTPUT POWER: 24.92 dBm = 0.311 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  37.92 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	1.31	10	-46.43	9.28	-37.15	64.6
5640.00	H	1.34	343	-51.67	11.03	-40.64	68.1
7520.00	H	-	-	-52.73	10.97	-41.76	69.2

Table 7-26. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MEASURED OUTPUT POWER: 23.89 dBm = 0.245 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  36.89 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3819.60	H	1.43	342	-46.46	9.19	-37.27	64.7
5729.40	H	-	-	-54.72	11.28	-43.43	70.9

**Table 7-27. Radiated Spurious Data (PCS GSM Mode – Ch. 810)**

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 28.88 dBm = 0.773 W  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  41.88 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3700.40	V	1.20	0	-56.55	8.39	-48.16	75.6
5550.60	V	-	-	-57.06	10.54	-46.52	74.0

**Table 7-28. Radiated Spurious Data with Camera Module (PCS GSM Mode – Ch. 512)**

OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 25  
 MEASURED OUTPUT POWER: 20.74 dBm = 0.119 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  33.74 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3702.50	H	1.72	41	-45.28	9.43	-35.85	56.6
5553.75	H	1.85	350	-52.25	10.79	-41.46	62.2
7405.00	H	-	-	-51.92	10.70	-41.22	62.0

**Table 7-29. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 600  
 MEASURED OUTPUT POWER: 18.84 dBm = 0.077 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  31.84 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	1.66	7	-45.37	9.28	-36.09	56.8
5640.00	H	-	-	-54.54	11.03	-43.51	64.2

**Table 7-30. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)**

OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175  
 MEASURED OUTPUT POWER: 18.50 dBm = 0.071 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  31.50 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3817.50	H	1.66	7	-50.97	9.19	-41.78	62.5
5726.25	H	1.65	8	-53.82	11.28	-42.54	63.3
7635.00	H	-	-	-51.98	11.17	-40.81	61.6

**Table 7-31. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)**

OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 25  
 MEASURED OUTPUT POWER: 20.74 dBm = 0.119 W  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  33.76 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3702.50	H	1.91	336	-55.30	9.43	-45.87	64.0
5553.75	H	1.58	65	-46.54	10.79	-35.75	53.9
7405.00	H	-	-	-52.02	10.70	-41.32	59.4

**Table 7-32. Radiated Spurious Data with Camera Module (PCS CDMA Mode – Ch. 25)**

OPERATING FREQUENCY: 1852.40 MHz  
 CHANNEL: 9262  
 MEASURED OUTPUT POWER: 23.62 dBm = 0.230 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.62 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3704.80	H	1.97	348	-51.80	9.43	-42.38	66.0
5557.20	H	-	-	-52.92	10.80	-42.12	65.7

**Table 7-33. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 9400  
 MEASURED OUTPUT POWER: 24.05 dBm = 0.254 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  37.05 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	1.94	357	-54.31	9.28	-45.03	68.6
5640.00	H	-	-	-54.07	11.03	-43.04	66.7

**Table 7-34. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)**

OPERATING FREQUENCY: 1907.60 MHz  
 CHANNEL: 9538  
 MEASURED OUTPUT POWER: 23.42 dBm = 0.220 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.42 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3815.20	H	1.71	325	-50.25	9.19	-41.06	64.7
5722.80	H	-	-	-54.72	11.27	-43.45	67.1

**Table 7-35. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)**

OPERATING FREQUENCY: 1907.60 MHz  
 CHANNEL: 9538  
 MEASURED OUTPUT POWER: 23.42 dBm = 0.220 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.42 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3815.20	H	2.21	358	-53.53	8.40	-45.14	68.8
5722.80	H	-	-	-56.21	10.76	-45.45	69.1

**Table 7-36. Radiated Spurious Data with Camera Module (PCS WCDMA Mode – Ch. 9538)**

## 7.8 Frequency Stability / Temperature Variation

\$2.1055 \$22.355 \$24.235 \$27.54

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 22, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.***

### Test Procedure Used

ANSI/TIA-603-C-2004

### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes

None

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 89 of 104

## Frequency Stability / Temperature Variation

§2.1055 §22.355


OPERATING FREQUENCY: 836,600,000 Hz  
 CHANNEL: 190  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,600,308	308	0.0000368
100 %		- 30	836,600,131	131	0.0000157
100 %		- 20	836,599,771	-229	-0.0000274
100 %		- 10	836,599,912	-88	-0.0000105
100 %		0	836,600,022	22	0.0000026
100 %		+ 10	836,599,897	-103	-0.0000123
100 %		+ 20	836,600,011	11	0.0000013
100 %		+ 30	836,599,680	-320	-0.0000383
100 %		+ 40	836,600,179	179	0.0000214
100 %		+ 50	836,600,072	72	0.0000086
BATT. ENDPOINT	3.45	+ 20	836,599,878	-122	-0.0000146

Table 7-37. Frequency Stability Data (Cellular GSM Mode – Ch. 190)

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 90 of 104	

**Frequency Stability / Temperature Variation**  
**§2.1055 §22.355**



**Figure 7-8. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)**

<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 91 of 104	

## Frequency Stability / Temperature Variation

§2.1055 §22.355


OPERATING FREQUENCY: 836,520,000 Hz  
 CHANNEL: 384  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,519,956	-44	-0.000053
100 %		- 30	836,519,719	-281	-0.0000336
100 %		- 20	836,519,770	-230	-0.0000275
100 %		- 10	836,520,018	18	0.0000022
100 %		0	836,520,186	186	0.0000222
100 %		+ 10	836,520,060	60	0.0000072
100 %		+ 20	836,519,973	-27	-0.0000032
100 %		+ 30	836,520,304	304	0.0000363
100 %		+ 40	836,520,449	449	0.0000537
100 %		+ 50	836,520,009	9	0.0000011
BATT. ENDPOINT		3.45	+ 20	836,520,173	173

Table 7-38. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 92 of 104	

**Frequency Stability / Temperature Variation**  
**§2.1055 §22.355**



**Figure 7-9. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)**

<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 93 of 104	

## Frequency Stability / Temperature Variation

§2.1055 §22.355

OPERATING FREQUENCY: 836,600,000 Hz  
 CHANNEL: 4183  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,600,066	66	0.0000079
100 %		- 30	836,600,069	69	0.0000082
100 %		- 20	836,599,941	-59	-0.0000071
100 %		- 10	836,599,841	-159	-0.0000190
100 %		0	836,600,204	204	0.0000244
100 %		+ 10	836,599,665	-335	-0.0000400
100 %		+ 20	836,599,778	-222	-0.0000265
100 %		+ 30	836,599,822	-178	-0.0000213
100 %		+ 40	836,600,103	103	0.0000123
100 %		+ 50	836,600,074	74	0.0000088
BATT. ENDPOINT		3.45	+ 20	836,600,139	139

Table 7-39. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 94 of 104

**Frequency Stability / Temperature Variation**

§2.1055 §22.355




Figure 7-10. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 95 of 104	

## Frequency Stability / Temperature Variation

§2.1055 §27.54

OPERATING FREQUENCY: 1,732,600,000 Hz  
 CHANNEL: 1413  
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,732,599,810	-190	-0.0000110
100 %		- 30	1,732,600,133	133	0.0000077
100 %		- 20	1,732,600,017	17	0.0000010
100 %		- 10	1,732,599,982	-18	-0.0000010
100 %		0	1,732,599,753	-247	-0.0000143
100 %		+ 10	1,732,599,961	-39	-0.0000023
100 %		+ 20	1,732,600,100	100	0.0000058
100 %		+ 30	1,732,599,962	-38	-0.0000022
100 %		+ 40	1,732,600,078	78	0.0000045
100 %		+ 50	1,732,599,922	-78	-0.0000045
BATT. ENDPOINT	3.45	+ 20	1,732,599,923	-77	-0.0000044

Table 7-40. Frequency Stability Data (AWS WCDMA Mode – Ch. 1412)


**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 96 of 104	

**Frequency Stability / Temperature Variation**

**§2.1055 §27.54**



**Figure 7-11. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1412)**

<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 97 of 104	

## Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 661  
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,879,999,767	-233	-0.0000124
100 %		- 30	1,880,000,041	41	0.0000022
100 %		- 20	1,879,999,758	-242	-0.0000129
100 %		- 10	1,879,999,869	-131	-0.0000070
100 %		0	1,880,000,035	35	0.0000019
100 %		+ 10	1,879,999,679	-321	-0.0000171
100 %		+ 20	1,879,999,916	-84	-0.0000045
100 %		+ 30	1,879,999,823	-177	-0.0000094
100 %		+ 40	1,879,999,814	-186	-0.0000099
100 %		+ 50	1,880,000,037	37	0.0000020
BATT. ENDPOINT		3.45	+ 20	1,879,999,701	-299

Table 7-41. Frequency Stability Data (PCS GSM Mode – Ch. 661)


**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 98 of 104	

**Frequency Stability / Temperature Variation**

**§2.1055 §24.235**



**Figure 7-12. Frequency Stability Graph (PCS GSM Mode – Ch. 661)**

<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 99 of 104	

## Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 600  
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,879,999,777	-223	-0.0000119
100 %		- 30	1,880,000,028	28	0.0000015
100 %		- 20	1,880,000,051	51	0.0000027
100 %		- 10	1,879,999,898	-102	-0.0000054
100 %		0	1,879,999,791	-209	-0.0000111
100 %		+ 10	1,880,000,199	199	0.0000106
100 %		+ 20	1,879,999,930	-70	-0.0000037
100 %		+ 30	1,879,999,936	-64	-0.0000034
100 %		+ 40	1,880,000,091	91	0.0000048
100 %		+ 50	1,879,999,966	-34	-0.0000018
BATT. ENDPOINT	3.45	+ 20	1,879,999,920	-80	-0.0000043

Table 7-42. Frequency Stability Data (PCS CDMA Mode – Ch. 600)


**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFVS987	 FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset	Page 100 of 104	

**Frequency Stability / Temperature Variation**

**§2.1055 §24.235**



**Figure 7-13. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)**

<b>FCC ID:</b> ZNFVS987	 <b>FCC Pt. 22, 24, &amp; 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b> 		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 101 of 104

## Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY:	1,880,000,000	Hz
CHANNEL:	9400	
REFERENCE VOLTAGE:	3.85	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,014	14	0.0000007
100 %		- 30	1,880,000,070	70	0.0000037
100 %		- 20	1,879,999,904	-96	-0.0000051
100 %		- 10	1,879,999,916	-84	-0.0000045
100 %		0	1,879,999,999	-1	-0.0000001
100 %		+ 10	1,880,000,103	103	0.0000055
100 %		+ 20	1,880,000,171	171	0.0000091
100 %		+ 30	1,880,000,184	184	0.0000098
100 %		+ 40	1,880,000,194	194	0.0000103
100 %		+ 50	1,880,000,383	383	0.0000204
BATT. ENDPOINT	3.45	+ 20	1,879,999,788	-212	-0.0000113


**Table 7-43. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)**

**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFVS987			FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1601180117-R2.ZNF	Test Dates: 1/20-2/18/2016	EUT Type: Portable Handset		Page 102 of 104	

**Frequency Stability / Temperature Variation**  
**§2.1055 §24.235**



**Figure 7-14. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)**

<b>FCC ID:</b> ZNFVS987		FCC Pt. 22, 24, & 27 GSM/ CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 103 of 104	

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFVS987** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules.

<b>FCC ID:</b> ZNFVS987	 <b>FCC Pt. 22, 24, &amp; 27 GSM / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1601180117-R2.ZNF	<b>Test Dates:</b> 1/20-2/18/2016	<b>EUT Type:</b> Portable Handset	Page 104 of 104