

# EMI TEST REPORT

## FCC CERTIFICATION

**Applicant:**

**LG Electronics MobileComm U.S.A., Inc.**  
**1000 Sylvan Avenue, Englewood Cliffs NJ 07632**  
**United States**

**Date of Receipt: June 07, 2018**

**Date of Issue: June 19, 2018**

**Test Report No. HCT-EM-1806-FC007**

**FCC ID :**

**ZNFX410PM**

Rule Part(s) / Standard(s) : FCC CFR 47 PART 15 Subpart B Class B  
FCC Classification : JAB (Part 15B – Class B Digital Device)  
EUT Type : Multi-band GSM/WCDMA/LTE/CDMA Phone with BT and WLAN  
Model Name : LM-X410PM  
Additional Model Name : LMX410PM, X410PM  
TA Information: : Model Name: MCS-V01WD, Manufacturer: DONGDO  
Date of Test : June 08, 2018 – June 12, 2018

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)  
I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.  
HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

**Tested By**



**Wook Yi**  
**Test Engineer**  
**EMC Team**  
**Certification Division**

**Reviewed By**



**Jeong-Hyun Choi**  
**Technical Manager**  
**EMC Team**  
**Certification Division**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



## REVISION HISTORY

*The revision history for this document is shown in table.*

Report No.	Issue Date	Information About Changes
HCT-EM-1806-FC007	June 19, 2018	Initial Release



## TABLE OF CONTENTS

	<b>PAGE</b>
1. GENERAL INFORMATION .....	4
1.1 Description of EUT .....	4
1.2 Related Submittal(s) / Grant(s) .....	4
1.3 Test Facility .....	5
1.4 Calibration of Measuring Instrument .....	5
1.5 Tested System Details .....	6
1.6 Cable Description .....	6
1.7 Noise Suppression Parts on Cable. (I/O Cable) .....	6
2. MEASUREMENT UNCERTAINTY .....	7
3. DESCRIPTION OF TEST .....	8
3.1 Measurement of Conducted Emission.....	8
3.2 Measurement of Radiated Measurements .....	10
4. PRELIMINARY TEST .....	11
4.1 Conducted Emission Test .....	11
4.2 Radiated Emission Test .....	11
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY .....	12
5.1 Conducted Emission Test .....	12
5.2 Radiated Emission Test .....	19
6. LIST OF TEST EQUIPMENT.....	21
7. CONCLUSION.....	22
8. APPENDIX A_ TEST SETUP PHOTOGRAPHS .....	23



## 1. GENERAL INFORMATION

### 1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFX410PM
Model	LM-X410PM
Additional Model	LMX410PM, X410PM
EUT Type	Multi-band GSM/WCDMA/LTE/CDMA Phone with BT and WLAN
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 817.90 MHz to 823.10 MHz (CDMA BC10) 824.2 MHz to 848.8 MHz (GSM 850) 1 850.2 MHz to 1 909.8 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.4 MHz to 846.6 MHz (WCDMA B5) 1 850.7 MHz to 1 909.3 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 2 402 MHz to 2 480 MHz ( Bluetooth) 2 412 MHz to 2 462 MHz ( WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 862.00 MHz to 894.00 MHz (CDMA BC10) 869 MHz to 894 MHz (CDMA BC0) 1 930 MHz to 1 990 MHz (CDMA BC1) 869.2 MHz to 893.8 MHz (GSM 850) 1 930.2 MHz to 1 989.8 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.4 MHz to 891.6 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 729 MHz to 746 MHz (LTE B12) 746 MHz to 756 MHz (LTE B13)



RX Frequency	1 925 MHz to 1 990 MHz (LTE B25) 859 MHz to 894 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 2 402 MHz to 2 480 MHz ( Bluetooth) 2 412 MHz to 2 462 MHz ( WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3)
--------------	---

### 1.2 Related Submittal(s) / Grant(s)

Original submittal only.

### 1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	

### 1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipments, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



## 1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer	FCC ID / DoC
EUT	LM-X410PM	-	LG	ZNFX410PM
Data cable	EAD62377922	-	KSD	-
Earphone	EAB64168741	-	CRESYN	-
Travel adaptor	MCS-V01WD	-	DONGDO	-
Micro SD card	SAMSUNG EVO +microSDX CLASS10 UHS-1 (256 GB)	-	SAMSUNG	-

## 1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	N/A	(P)1.0
	Earphone	N/A	Y	(D)1.2

\* The marked “(D)” means the data cable and “(P)” means the power cable.

## 1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End



## 2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	1.82 dB ( $k = 2$ )
Radiated Emissions (30 MHz to 1 GHz)	5.20 dB ( $k = 2$ )
Radiated Emissions (1 GHz to 18 GHz)	5.24 dB ( $k = 2$ )
Radiated Emissions (18 GHz to 40 GHz)	5.40 dB ( $k = 2$ )



### 3. DESCRIPTION OF TEST

#### 3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).  
 If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).  
 Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

#### [ Conducted Emission Limits ]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

*\*Decreases with the logarithm of the frequency.*



### 3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

#### [ Radiated Emission Limits ]

Frequency (MHz)	Antenna Distance (m)	Field Strength ( $\mu\text{V}/\text{m}$ )	Quasi-Peak ( $\text{dB}(\mu\text{V})/\text{m}$ )
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ( $\text{dB}(\mu\text{V})/\text{m}$ )	Average ( $\text{dB}(\mu\text{V})/\text{m}$ )
Above 1 000	3	74	54




### 3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

### 3.3 Configuration of Tested System



**Non-Conductive Table**  
Power Line: 120 VAC



## 4. PRELIMINARY TEST

### 4.1 Conducted Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

- Operation Mode:**  Camera (Front) & MP3 mode  
 Camera (Rear) & FM Radio mode  
 Idle mode

**NOTE.** *The worst-case emissions are reported.*

### 4.2 Radiated Emission Test

It was tested the following operating mode, after connecting all peripheral devices.

- Operation Mode:**  Camera (Front) & MP3 mode  
 Camera (Rear) & FM Radio mode  
 Idle mode

**NOTE.** *The worst-case emissions are reported.*



## 5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

### 5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Worst Case of Operation Mode	Camera (Rear) & FM Radio mode
Kind of Test Site	Shielded Room
Temperature	24.6 °C
Relative Humidity	44.8 %
Test Date	June 12, 2018

#### ***- Calculation Formula:***

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Conducted Emission, AC Main Port, Line (L1)





### QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.414000	38.7	9.000	L1	9.7	18.9	57.6
0.428000	39.6	9.000	L1	9.7	17.7	57.3
0.432000	40.5	9.000	L1	9.7	16.7	57.2
0.444000	38.5	9.000	L1	9.7	18.5	57.0
0.460000	38.5	9.000	L1	9.7	18.2	56.7
0.466000	37.1	9.000	L1	9.7	19.4	56.6
1.092000	42.5	9.000	L1	9.8	13.5	56.0
1.100000	42.9	9.000	L1	9.8	13.1	56.0
1.106000	42.3	9.000	L1	9.8	13.7	56.0
1.116000	42.1	9.000	L1	9.8	13.9	56.0
1.120000	41.9	9.000	L1	9.8	14.1	56.0
1.132000	41.7	9.000	L1	9.8	14.3	56.0
14.332000	37.5	9.000	L1	10.2	22.5	60.0
14.848000	37.7	9.000	L1	10.3	22.3	60.0
15.270000	37.7	9.000	L1	10.3	22.3	60.0
18.340000	36.8	9.000	L1	10.3	23.2	60.0
18.482000	37.3	9.000	L1	10.3	22.7	60.0
18.796000	37.1	9.000	L1	10.3	22.9	60.0




### CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.356000	21.6	9.000	L1	9.7	27.2	48.8
0.416000	29.3	9.000	L1	9.7	18.2	47.5
0.424000	30.7	9.000	L1	9.7	16.7	47.4
0.438000	30.7	9.000	L1	9.7	16.4	47.1
0.472000	30.7	9.000	L1	9.7	15.8	46.5
0.824000	25.1	9.000	L1	9.7	20.9	46.0
1.084000	35.7	9.000	L1	9.8	10.3	46.0
1.092000	35.5	9.000	L1	9.8	10.5	46.0
1.100000	35.7	9.000	L1	9.8	10.3	46.0
1.116000	35.7	9.000	L1	9.8	10.3	46.0
1.120000	35.5	9.000	L1	9.8	10.5	46.0
1.134000	35.4	9.000	L1	9.8	10.6	46.0
12.934000	27.1	9.000	L1	10.2	22.9	50.0
14.848000	28.0	9.000	L1	10.3	22.0	50.0
15.270000	28.2	9.000	L1	10.3	21.8	50.0
18.058000	26.3	9.000	L1	10.3	23.7	50.0
18.482000	26.4	9.000	L1	10.3	23.6	50.0
19.156000	25.6	9.000	L1	10.4	24.4	50.0



Figure 2: Conducted Emission, AC Main Port, Line (N)





### QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.402000	35.8	9.000	N	9.7	22.0	57.8
0.444000	40.4	9.000	N	9.7	16.6	57.0
0.450000	36.8	9.000	N	9.7	20.1	56.9
0.466000	36.4	9.000	N	9.7	20.2	56.6
0.480000	36.2	9.000	N	9.7	20.1	56.3
0.494000	33.4	9.000	N	9.7	22.7	56.1
1.090000	41.4	9.000	N	9.8	14.6	56.0
1.100000	42.2	9.000	N	9.8	13.8	56.0
1.112000	42.0	9.000	N	9.8	14.0	56.0
1.126000	42.1	9.000	N	9.8	13.9	56.0
1.140000	42.0	9.000	N	9.8	14.0	56.0
1.164000	40.0	9.000	N	9.8	16.0	56.0
11.518000	32.7	9.000	N	10.3	27.3	60.0
12.088000	32.9	9.000	N	10.3	27.1	60.0
13.442000	33.2	9.000	N	10.4	26.8	60.0
13.504000	32.7	9.000	N	10.4	27.3	60.0
14.010000	33.4	9.000	N	10.4	26.6	60.0
14.490000	33.6	9.000	N	10.4	26.4	60.0



## CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.400000	25.6	9.000	N	9.7	22.3	47.9
0.432000	30.5	9.000	N	9.7	16.7	47.2
0.442000	30.8	9.000	N	9.7	16.2	47.0
0.450000	30.9	9.000	N	9.7	16.0	46.9
0.470000	30.1	9.000	N	9.7	16.4	46.5
0.500000	27.5	9.000	N	9.7	18.5	46.0
1.080000	35.1	9.000	N	9.8	10.9	46.0
1.088000	35.1	9.000	N	9.8	10.9	46.0
1.096000	35.4	9.000	N	9.8	10.6	46.0
1.102000	35.6	9.000	N	9.8	10.4	46.0
1.110000	35.2	9.000	N	9.8	10.8	46.0
1.140000	35.2	9.000	N	9.8	10.8	46.0
11.518000	23.6	9.000	N	10.3	26.4	50.0
12.088000	23.5	9.000	N	10.3	26.5	50.0
13.442000	23.2	9.000	N	10.4	26.8	50.0
14.010000	23.5	9.000	N	10.4	26.5	50.0
14.490000	23.6	9.000	N	10.4	26.4	50.0
15.526000	24.3	9.000	N	10.5	25.7	50.0



## 5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

### -For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Worst Case of Operation Mode	Camera (Rear) & FM Radio mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.5 °C
Relative Humidity	44.3 %
Test Date	June 08, 2018

Frequency (MHz)	Quasi Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
44.948800	24.2	99.9	V	17.0	20.0	15.8	40.0
71.375200	16.8	274.7	H	315.0	17.7	23.2	40.0
98.672800	15.9	274.7	H	316.0	15.4	27.6	43.5
165.987200	18.6	99.8	V	30.0	19.8	24.9	43.5
640.611200	27.9	99.9	V	114.0	28.0	18.1	46.0
902.948800	31.0	274.7	V	199.0	31.2	15.0	46.0

### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



## -For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	5 825 MHz
Tested Frequency Range	1 GHz to 30 GHz
Worst Case of Operation Mode	Camera (Rear) & FM Radio mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.1 / 22.8 °C
Relative Humidity	44.0 / 43.8 %
Test Date	June 11 / June 12, 2018

Frequency (MHz)	Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1614.695000	30.8	159.5	H	333.0	-28.0	43.2	74.0
3117.300000	33.1	124.7	V	0.0	-22.7	40.9	74.0
4448.035000	35.5	99.8	V	271.0	-19.8	38.5	74.0
6580.715000	39.2	189.4	V	12.0	-14.7	34.8	74.0
8212.000000	41.7	99.7	V	295.0	-12.0	32.3	74.0
9609.065000	43.5	219.4	V	40.0	-10.6	30.5	74.0

Frequency (MHz)	CAverage (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1614.695000	17.3	159.5	H	333.0	-28.0	36.7	54.0
3117.300000	20.8	124.7	V	0.0	-22.7	33.2	54.0
4448.035000	22.5	99.8	V	271.0	-19.8	31.5	54.0
6580.715000	26.1	189.4	V	12.0	-14.7	27.9	54.0
8212.000000	29.0	99.7	V	295.0	-12.0	25.0	54.0
9609.065000	30.4	219.4	V	40.0	-10.6	23.6	54.0

### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



## 6. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.20.2017
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	06.27.2017
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	102245	1 year	12.20.2017
<input type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	07.18.2017
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.54.0	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB 9168	760	2 year	04.06.2017
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO 3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	INNCO Systems	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-
-For measurement above 1 GHz					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU40	100524	1 year	08.16.2017
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	INNCO Systems	CO 3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	INNCO Systems	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
<input checked="" type="checkbox"/> Low Noise Amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.06.2018
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	2 year	12.05.2017
<input checked="" type="checkbox"/> Power Amplifier	TESTEK	TK-PA1840H	170030-L	1 year	12.20.2017
<input type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	06.28.2017
<input type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	1300	2 year	06.30.2017
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU26	100241	1 year	08.16.2017
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-



## 7. CONCLUSION

The data collected shows that the **EUT Type: Multi-band GSM/WCDMA/LTE/CDMA Phone with BT and WLAN, FCC ID: ZNFX410PM, Model: LM-X410PM** complies with §15.107 and §15.109 of the FCC rules.



## 8. APPENDIX A. TEST SETUP PHOTOGRAPHS

Please refer to Appendix A