



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
http://www.pctest.com



## MEASUREMENT REPORT GSM / GPRS / CDMA / WCDMA

**Applicant Name:**  
LG Electronics MobileComm U.S.A  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States

**Date of Testing:**  
Jan 22 - Feb 09, 2018  
**Test Site/Location:**  
PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
1M1801190006-02.ZNF

<b>FCC ID:</b>	<b>ZNFX410UM</b>
<b>APPLICANT:</b>	<b>LG Electronics MobileComm U.S.A</b>

**Application Type:** Certification  
**Model:** LM-X410UM  
**Additional Model(s):** LMX410UM, X410UM, LM-X410ULML, LMX410ULML, X410ULML  
**EUT Type:** Portable Handset  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part(s):** 22 & 24  
**Test Procedure(s):** ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1801190006-02.ZNF) supersedes and replaces the previously issued test report (S/N: 1M1801190006-02.ZNF) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortanez  
President




<b>FCC ID:</b> ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 1 of 82	

# TABLE OF CONTENTS


1.0	INTRODUCTION .....	4
1.1	Scope .....	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities.....	5
2.3	Test Configuration .....	5
2.4	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Cellular - Base Frequency Blocks .....	6
3.3	Cellular - Mobile Frequency Blocks.....	6
3.4	PCS - Base Frequency Blocks .....	6
3.5	PCS - Mobile Frequency Blocks.....	7
3.6	Radiated Measurements .....	8
4.0	MEASUREMENT UNCERTAINTY .....	9
5.0	TEST EQUIPMENT CALIBRATION DATA .....	10
6.0	SAMPLE CALCULATIONS .....	11
7.0	TEST RESULTS.....	12
7.1	Summary.....	12
7.2	Occupied Bandwidth .....	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal .....	18
7.4	Band Edge Emissions at Antenna Terminal .....	49
7.5	Peak-Average Ratio .....	60
7.6	Radiated Power (ERP/EIRP).....	63
7.7	Radiated Spurious Emissions Measurements.....	68
8.0	CONCLUSION.....	82

<b>FCC ID:</b> ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 2 of 82	



## MEASUREMENT REPORT

### GSM / GPRS / CDMA / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
GSM850	22H	824.2 - 848.8	1.447	31.61	2.374	33.76	242KGXW
EDGE850	22H	824.2 - 848.8	0.453	26.56	0.744	28.71	242KG7W
CDMA850	22H	824.70 - 848.31	0.172	22.36	0.282	24.51	1M28F9W
WCDMA850	22H	826.4 - 846.6	0.172	22.35	0.282	24.50	4M16F9W
GSM1900	24E	1850.2 - 1909.8			1.070	30.29	243KGXW
EDGE1900	24E	1850.2 - 1909.8			0.524	27.20	244KG7W
CDMA1900	24E	1851.25 - 1908.75			0.304	24.82	1M29F9W
WCDMA1900	24E	1852.4 - 1907.6			0.333	25.22	4M17F9W

**EUT Overview**

<b>FCC ID:</b> ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 3 of 82	

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

## 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

## 1.3 Test Facility / Accreditations

**Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

<b>FCC ID:</b> ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 4 of 82	

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFX410UM**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

**Test Device Serial No.:** 01259, 1242, 00772

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A (BC0, BC1), 850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE)

### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

<b>FCC ID:</b> ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 5 of 82	


## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

### 3.2 Cellular - Base Frequency Blocks




BLOCK 1: 869 – 880 MHz (A\* Low + A)

BLOCK 3: 890 – 891.5 MHz (A\* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B\*)

### 3.3 Cellular - Mobile Frequency Blocks




BLOCK 1: 824 – 835 MHz (A\* Low + A)

BLOCK 3: 845 – 846.5 MHz (A\* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B\*)

### 3.4 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)


BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 6 of 82

### 3.5 PCS - Mobile Frequency Blocks



**BLOCK 1: 1850 – 1865 MHz (A)**

**BLOCK 4: 1885 – 1890 MHz (E)**

**BLOCK 2: 1865 – 1870 MHz (D)**

**BLOCK 5: 1890 – 1895 MHz (F)**

**BLOCK 3: 1870 – 1885 MHz (B)**

**BLOCK 6: 1895 – 1910 MHz (C)**

<b>FCC ID:</b> ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 7 of 82	

### 3.6 Radiated Measurements

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: ZNFX410UM	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		<b>Approved by:</b> Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset	Page 8 of 82

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 9 of 82	

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	1/6/2018	Annual	1/6/2019	LTx1
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	8/28/2017	Annual	8/28/2018	MY49432391
Agilent	N5183A	MXG Analog Signal Generator	2/24/2016	Biennial	2/24/2018	MY50141900
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/27/2017	Annual	3/27/2018	MY52350166
Emco	6502	Active Loop Antenna (10k - 30 MHz)	8/9/2016	Biennial	8/9/2018	2936
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/23/2016	Biennial	8/23/2018	135427
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/11/2017	Annual	5/11/2018	100040
Rohde & Schwarz	CMW500	Radio Communication Tester	10/13/2017	Annual	10/13/2018	102060
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/31/2017	Annual	7/31/2018	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/11/2017	Annual	8/11/2018	103200
Rohde & Schwarz	TC-TA18	Cross-Pol Antenna 400MHz-18GHz	10/30/2017	Annual	10/30/2018	101058
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102135
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102134
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107
Sunol	DRH-118	Horn Antenna (1-18 GHz)	8/11/2017	Biennial	8/11/2019	A042511

**Table 5-1. Test Equipment**

FCC ID: ZNFX410UM	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset	Page 10 of 82

## 6.0 SAMPLE CALCULATIONS

### GPRS Emission Designator

**Emission Designator = 250KGXW**

GPRS BW = 250 kHz  
 G = Phase Modulation  
 X = Cases not otherwise covered  
 W = Combination (Audio/Data)

### CDMA Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### WCDMA Emission Designator

**Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### Spurious Radiated Emission

**Example: Spurious emission at 3700.40 MHz**

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm - (-24.80) = 50.3 dBC.

FCC ID: ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset	Page 11 of 82	

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: LG Electronics MobileComm U.S.A  
 FCC ID: ZNFX410UM  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): GSM / GPRS / EDGE / CDMA / WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	RSS-Gen (4.6.1) RSS-133(2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5)	Conducted Band Edge / Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	RSS-132(5.4) RSS-133(6.4)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	RSS-132(5.4) RSS-133(4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
22.913(a)(2)	RSS-132(5.4)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	RSS-133(6.4)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5)	Radiated Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: ZNFX410UM	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset	Page 12 of 82

## 7.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used


KDB 971168 D01 v03 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**


### Test Notes

Some plots below show a VBW slightly less than 3xRBW. However it has been determined that this does not impact the measurement since the VBW is very close to 3xRBW.

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 13 of 82




**Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode)**




**Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode)**

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	<b>MEASUREMENT REPORT (CERTIFICATION)</b>	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 14 of 82




Plot 7-3. Occupied Bandwidth Plot (PCS GPRS Mode)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode)

FCC ID: ZNFX410UM	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>MEASUREMENT REPORT</b> (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 15 of 82



Plot 7-5. Occupied Bandwidth Plot (Cellular CDMA Mode)



Plot 7-6. Occupied Bandwidth Plot (PCS CDMA Mode)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 16 of 82



Plot 7-7. Occupied Bandwidth Plot (Cellular WCDMA Mode)



Plot 7-8. Occupied Bandwidth Plot (PCS WCDMA Mode)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 17 of 82

## 7.3 Spurious and Harmonic Emissions at Antenna Terminal

### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 D01 v03 – Section 6.0

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**

### Test Notes


Per 24.238(b), and RSS-133(6.5), compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 18 of 82






Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 20 of 82




Plot 7-13. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)




Plot 7-14. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 21 of 82




Plot 7-15. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)



Plot 7-16. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)


FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 22 of 82




**Plot 7-17. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)**

<b>FCC ID:</b> ZNFX410UM	<b>MEASUREMENT REPORT (CERTIFICATION)</b>			<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 23 of 82	

**PCS GPRS Mode**




**Plot 7-18. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)**




**Plot 7-19. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 24 of 82




Plot 7-20. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-21. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 25 of 82




Plot 7-22. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)




Plot 7-23. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 26 of 82




Plot 7-24. Conducted Spurious Plot (PCS GPRS Mode - High Channel)



Plot 7-25. Conducted Spurious Plot (PCS GPRS Mode - High Channel)


FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 27 of 82




**Plot 7-26. Conducted Spurious Plot (PCS GPRS Mode - High Channel)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 28 of 82

# Cellular CDMA Mode




Plot 7-27. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)




Plot 7-28. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 29 of 82




Plot 7-29. Conducted Spurious Plot (Cellular CDMA Mode - Low Channel)




Plot 7-30. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 30 of 82




Plot 7-31. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)




Plot 7-32. Conducted Spurious Plot (Cellular CDMA Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 31 of 82




Plot 7-33. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)



Plot 7-34. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 32 of 82




**Plot 7-35. Conducted Spurious Plot (Cellular CDMA Mode - High Channel)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 33 of 82

**PCS CDMA Mode**




**Plot 7-36. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)**



**Plot 7-37. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)**

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 34 of 82




Plot 7-38. Conducted Spurious Plot (PCS CDMA Mode - Low Channel)




Plot 7-39. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 35 of 82




Plot 7-40. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)




Plot 7-41. Conducted Spurious Plot (PCS CDMA Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 36 of 82




Plot 7-42. Conducted Spurious Plot (PCS CDMA Mode - High Channel)



Plot 7-43. Conducted Spurious Plot (PCS CDMA Mode - High Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 37 of 82




**Plot 7-44. Conducted Spurious Plot (PCS CDMA Mode - High Channel)**

<b>FCC ID:</b> ZNFX410UM	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 38 of 82	

**Cellular WCDMA Mode**




**Plot 7-45. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)**



**Plot 7-46. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)**

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 39 of 82




Plot 7-47. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-48. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 40 of 82




Plot 7-49. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)




Plot 7-50. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 41 of 82




Plot 7-51. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)



Plot 7-52. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)


FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 42 of 82




**Plot 7-53. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 43 of 82

**PCS WCDMA Mode**




**Plot 7-54. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)**



**Plot 7-55. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 44 of 82




Plot 7-56. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-57. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 45 of 82




Plot 7-58. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)




Plot 7-59. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 46 of 82




Plot 7-60. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)



Plot 7-61. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 47 of 82



Plot 7-62. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 48 of 82

## 7.4 Band Edge Emissions at Antenna Terminal

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

**The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.**

### Test Procedure Used


KDB 971168 D01 v03 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3.  $RBW \geq 1\%$  of the emission bandwidth
4.  $VBW \geq 3 \times RBW$
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span}/RBW$
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**

### Test Notes


Per 22.917(b), 24.238(b), and RSS-132(5.5), RSS-133(6.5), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 49 of 82

# Cellular GPRS Mode




Plot 7-63. Band Edge Plot (Cellular GPRS Mode - Low Channel)




Plot 7-64. Band Edge Plot (Cellular GPRS Mode - High Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 50 of 82




**Plot 7-65. Band Edge Plot (PCS GPRS Mode - Low Channel)**




**Plot 7-66. 4MHz Span Plot (PCS GPRS Mode - Low Channel)**

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 51 of 82




Plot 7-67. Band Edge Plot (PCS GPRS Mode - High Channel)




Plot 7-68. 4MHz Span Plot (PCS GPRS Mode - High Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 52 of 82

## Cellular CDMA Mode




Plot 7-69. Band Edge Plot (Cellular CDMA Mode - Low Channel)



Plot 7-70. 4MHz Span Plot (Cellular CDMA Mode - Low Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 53 of 82



Plot 7-71. Band Edge Plot (Cellular CDMA Mode - High Channel)




Plot 7-72. 4MHz Span Plot (Cellular CDMA Mode - High Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 54 of 82



**Plot 7-73. Band Edge Plot (PCS CDMA Mode - Low Channel)**




**Plot 7-74. 4MHz Span Plot (PCS CDMA Mode - Low Channel)**

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 55 of 82



Plot 7-75. Band Edge Plot (PCS CDMA Mode - High Channel)



Plot 7-76. 4MHz Span Plot (PCS CDMA Mode - High Channel)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 56 of 82

**Cellular WCDMA Mode**




**Plot 7-77. Band Edge Plot (Cellular WCDMA Mode - Low Channel)**




**Plot 7-78. Band Edge Plot (Cellular WCDMA Mode - High Channel)**

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 57 of 82

# PCS WCDMA Mode



Plot 7-79. Band Edge Plot (PCS WCDMA Mode - Low Channel)




Plot 7-80. 4MHz Span Plot (PCS WCDMA Mode - Low Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 58 of 82



Plot 7-81. Band Edge Plot (PCS WCDMA Mode - High Channel)



Plot 7-82. 4MHz Span Plot (PCS WCDMA Mode - High Channel)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 59 of 82

## 7.5 Peak-Average Ratio

### Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

### Test Procedure Used


KDB 971168 D01 v03 – Section 5.7.1

### Test Settings

1. The signal analyzer’s CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal “RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-4. Test Instrument & Measurement Setup**


### Test Notes

None

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 60 of 82




Plot 7-83. Peak-Average Ratio Plot (PCS GPRS Mode)




Plot 7-84. Peak-Average Ratio Plot (PCS EDGE Mode)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 61 of 82



Plot 7-85. Peak-Average Ratio Plot (PCS CDMA Mode)



Plot 7-86. Peak-Average Ratio Plot (PCS WCDMA Mode)

FCC ID: ZNFX410UM	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 62 of 82

## 7.6 Radiated Power (ERP/EIRP)

### Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v03 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”. Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize


FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 63 of 82

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Radiated Test Setup <1GHz**



**Figure 7-6. Radiated Test Setup >1GHz**

FCC ID: ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>	 <b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 64 of 82

**Test Notes**

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
824.20	GSM850	H	150	5	31.40	1.50	30.74	38.45	-7.71	32.89	40.61	-7.71
836.60	GSM850	H	150	1	31.80	1.50	31.15	38.45	-7.30	33.30	40.61	-7.30
848.80	GSM850	H	150	3	32.26	1.50	<b>31.61</b>	38.45	-6.85	<b>33.76</b>	40.61	-6.85
848.80	GSM850	V	150	353	31.47	1.50	30.82	38.45	-7.63	32.97	40.61	-7.64
848.80	EDGE850	H	150	3	27.21	1.50	<b>26.56</b>	38.45	-11.89	<b>28.71</b>	40.61	-11.89

**Table 7-2. ERP/EIRP (Cellular GPRS)**

FCC ID: ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset		Page 65 of 82	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
824.70	CDMA850	H	150	355	21.54	1.50	20.89	38.45	-17.56	23.04	40.61	-17.57
836.52	CDMA850	H	150	0	22.25	1.50	21.60	38.45	-16.85	23.75	40.61	-16.86
848.31	CDMA850	H	150	8	23.01	1.50	<b>22.36</b>	38.45	-16.09	<b>24.51</b>	40.61	-16.10
848.31	CDMA850	V	150	355	22.84	1.50	22.19	38.45	-16.26	24.34	40.61	-16.27

Table 7-3. ERP/EIRP (Cellular CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	150	353	21.38	1.50	20.73	38.45	-17.72	22.88	40.61	-17.73
836.60	WCDMA850	H	150	6	22.50	1.50	21.85	38.45	-16.60	24.00	40.61	-16.61
846.60	WCDMA850	H	150	1	23.00	1.50	<b>22.35</b>	38.45	-16.10	<b>24.50</b>	40.61	-16.11
846.60	WCDMA850	V	150	350	21.86	1.50	21.21	38.45	-17.24	23.36	40.61	-17.25

Table 7-4. ERP/EIRP (Cellular WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.20	GSM1900	H	150	3	24.55	4.82	29.37	33.01	-3.64
1880.00	GSM1900	H	150	3	24.43	4.74	29.17	33.01	-3.84
1909.80	GSM1900	H	150	3	25.61	4.68	<b>30.29</b>	33.01	-2.72
1909.80	GSM1900	V	150	238	19.82	4.86	24.68	33.01	-8.33
1909.80	EDGE1900	H	150	3	22.52	4.68	<b>27.20</b>	33.01	-5.81

Table 7-5. EIRP (PCS GPRS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	V	150	344	18.88	4.79	23.67	33.01	-9.34
1880.00	CDMA1900	V	150	268	18.41	4.84	23.25	33.01	-9.76
1908.75	CDMA1900	V	150	81	19.96	4.86	<b>24.82</b>	33.01	-8.19
1908.75	CDMA1900	H	150	3	18.22	4.68	22.90	33.01	-10.11

Table 7-6. EIRP (PCS CDMA)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 66 of 82

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	150	5	18.75	4.81	23.56	33.01	-9.45
1880.00	WCDMA1900	H	150	343	19.67	4.74	24.41	33.01	-8.60
1907.60	WCDMA1900	H	150	0	20.54	4.68	<b>25.22</b>	33.01	-7.79
1907.60	WCDMA1900	V	150	272	18.45	4.68	23.13	33.01	-9.88

**Table 7-7. EIRP (PCS WCDMA)**

FCC ID: ZNFX410UM	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset	Page 67 of 82

## 7.7 Radiated Spurious Emissions Measurements

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v03 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFX410UM	 <b>MEASUREMENT REPORT (CERTIFICATION)</b> 		<b>Approved by:</b> Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset	Page 68 of 82

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-7. Test Instrument & Measurement Setup**

**Test Notes**

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) For CDMA mode, this device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 6) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 7) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 8) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 69 of 82

### Cellular GPRS Mode

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1648.40	H	150	353	-60.10	4.81	-55.29	-42.3
2472.60	H	150	12	-46.75	4.99	-41.76	-28.8
3296.80	H	-	-	-60.54	6.24	-54.30	-41.3

**Table 7-8. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	150	290	-53.69	4.86	-48.83	-35.8
2509.80	H	150	306	-46.60	5.10	-41.50	-28.5
3346.40	H	-	-	-60.63	6.25	-54.38	-41.4

**Table 7-9. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 70 of 82

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	150	353	-59.67	4.91	-54.76	-41.8
2546.40	H	150	40	-48.82	5.28	-43.54	-30.5
3395.20	H	-	-	-60.38	6.39	-53.99	-41.0

Table 7-10. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 71 of 82

### Cellular CDMA Mode

OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1649.40	H	150	6	-69.14	4.81	-64.33	-51.3
2474.10	H	150	16	-63.89	4.99	-58.90	-45.9
3298.80	H	-	-	-66.83	6.25	-60.58	-47.6

**Table 7-11. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)**

OPERATING FREQUENCY: 836.52 MHz  
 CHANNEL: 384  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.04	H	150	353	-67.49	4.86	-62.63	-49.6
2509.56	H	150	335	-62.21	5.10	-57.11	-44.1
3346.08	H	-	-	-66.78	6.25	-60.52	-47.5

**Table 7-12. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 72 of 82

OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 777  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1696.62	H	150	6	-63.42	4.91	-58.51	-45.5
2544.93	H	150	342	-60.19	5.27	-54.92	-41.9
3393.24	H	-	-	-66.84	6.39	-60.45	-47.5

Table 7-13. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 73 of 82

### Cellular WCDMA Mode

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	150	347	-68.87	4.82	-64.05	-51.0
2479.20	H	-	-	-65.53	5.01	-60.52	-47.5
3305.60	H	-	-	-66.94	6.25	-60.69	-47.7

**Table 7-14. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 4183  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	-	-	-69.52	4.86	-64.66	-51.7
2509.80	H	150	308	-65.51	5.10	-60.41	-47.4
3346.40	H	-	-	-66.80	6.25	-60.54	-47.5

**Table 7-15. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 74 of 82

OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	150	1	-65.11	4.90	-60.20	-47.2
2539.80	H	-	-	-66.11	5.25	-60.86	-47.9
3386.40	H	-	-	-67.12	6.36	-60.76	-47.8

Table 7-16. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 75 of 82

### PCS GPRS Mode

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	V	150	21	-55.74	6.76	-48.98	-36.0
5550.60	V	150	44	-53.52	8.43	-45.09	-32.1
7400.80	V	-	-	-52.89	8.26	-44.63	-31.6

**Table 7-17. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	V	-	-	-58.14	6.84	-51.30	-38.3
5640.00	V	150	192	-54.71	8.52	-46.20	-33.2
7520.00	V	-	-	-53.11	8.44	-44.66	-31.7

**Table 7-18. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset	Page 76 of 82	

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MODULATION SIGNAL: GSM (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3819.60	V	-	-	-59.86	7.00	-52.86	-39.9
5729.40	V	133	57	-54.52	8.58	-45.95	-32.9
7639.20	V	-	-	-54.90	8.56	-46.33	-33.3

Table 7-19. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 77 of 82	

### PCS CDMA Mode

OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 25  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3702.50	H	150	35	-56.82	6.76	-50.05	-37.1
5553.75	H	-	-	-66.41	8.44	-57.97	-45.0
7405.00	H	-	-	-62.88	8.27	-54.61	-41.6

**Table 7-20. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 600  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	150	36	-52.13	6.84	-45.29	-32.3
5640.00	H	-	-	-65.89	8.52	-57.37	-44.4
7520.00	H	-	-	-61.96	8.44	-53.52	-40.5

**Table 7-21. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)**

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 78 of 82

OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175  
 MODULATION SIGNAL: CDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3817.50	H	79	27	-55.70	6.99	-48.71	-35.7
5726.25	H	-	-	-66.47	8.58	-57.90	-44.9
7635.00	H	-	-	-63.29	8.56	-54.74	-41.7

Table 7-22. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 79 of 82

### PCS WCDMA Mode

OPERATING FREQUENCY: 1852.40 MHz  
 CHANNEL: 9262  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3704.80	H	150	275	-63.85	6.77	-57.09	-44.1
5557.20	H	-	-	-66.57	8.44	-58.13	-45.1
7409.60	H	-	-	-62.95	8.28	-54.67	-41.7

Table 7-23. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 9400  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	150	32	-58.14	6.84	-51.30	-38.3
5640.00	H	-	-	-66.09	8.52	-57.58	-44.6
7520.00	H	-	-	-62.37	8.44	-53.93	-40.9

Table 7-24. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 80 of 82

OPERATING FREQUENCY: 1907.60 MHz  
 CHANNEL: 9538  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3815.20	H	150	33	-59.14	6.98	-52.15	-39.2
5722.80	H	-	-	-66.66	8.58	-58.08	-45.1
7630.40	H	-	-	-63.37	8.55	-54.82	-41.8

Table 7-25. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFX410UM		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1801190006-02.ZNF	Test Dates: Jan 22 - Feb 09, 2018	EUT Type: Portable Handset		Page 81 of 82

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFX410UM** complies with all the requirements of Part 22 & 24 of the FCC Rules.

FCC ID: ZNFX410UM		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1801190006-02.ZNF	<b>Test Dates:</b> Jan 22 - Feb 09, 2018	<b>EUT Type:</b> Portable Handset	Page 82 of 82	