

# **SAR Test Report**

Product Name: mobile phone

Model No. : X85

FCC ID : ZO6FCCX85001

Applicant: XPX Technology Limited

Address: Flat B8 F8, Kin Tak Fung Ind Bldg, 174 Wai Yip

St, Kwun Tong Kowloon, HongKong

Date of Receipt: 18/06/2011

Date of Test : 06/07/2011

Issued Date : 06/07/2011

Report No. : 116S050R-HP-US-P03V01

Report Version: V2.2

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quie Tek Corporation.



# **Test Report Certification**

Issued Date: 06/07/2011

Report No: 116S050R-HP-US-P03V01

# QuieTek

Product Name : mobile phone

Applicant : XPX Technology Limited

Address : Flat B8 F8, Kin Tak Fung Ind Bldg, 174 Wai Yip St, Kwun

Tong Kowloon, HongKong

Manufacturer : Yuanfenn Industrial Dalang Lonhua

Address : 4&5 FL Area B, Yuanfenn Industrial Zone, Dalang Lonhua

Model No. : X85

FCC ID : ZO6FCCX85001

Brand Name : XPX mobile phone

EUT Voltage : DC 3.7V

Applicable Standard FCC Oet65 Supplement C June 2001

IEEE Std. 1528-2003,47CFR § 2.1093

Test Result : Max. SAR Measurement (1g)

Head: 0.424 W/kg Body: 1.130 W/kg

Wi-Fi: 0.012 W/kg

Performed Location : Suzhou EMC Laboratory

No.99 Hongye Rd., Suzhou Industrial Park Loufeng

Hi-Tech Development Zone., Suzhou, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098

FCC Registration Number: 800392

Documented By : Alice Wi

(Engineering ADM: Alice Ni)

Reviewed By : Lobin Wa

(Senior Engineer: Robin Wu)

Approved By : Marlinchen

(Engineering Supervisor: Marlin Chen)



#### **Laboratory Information**

We, **QuieTek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C. : BSMI, NCC, TAF

Germany : TUV Rheinland

Norway : Nemko, DNV

USA : FCC, NVLAP

Japan : VCCI

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site: <a href="http://www.quietek.com/tw/ctg/cts/accreditations.htm">http://www.quietek.com/tw/ctg/cts/accreditations.htm</a>
The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site: <a href="http://www.quietek.com/">http://www.quietek.com/</a>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

#### **HsinChu Testing Laboratory:**







#### **LinKou Testing Laboratory:**







#### Suzhou (China) Testing Laboratory:









## TABLE OF CONTENTS

Description	Page
1. General Information	6
1.1. EUT Description	6
1.2. Test Environment	7
2. SAR Measurement System	8
2.1. DASY5 System Description	8
2.1.1. Applications	9
2.1.2. Area Scans	9
2.1.3. Zoom Scan (Cube Scan Averaging)	9
2.1.4. Uncertainty of Inter-/Extrapolation and Averaging	9
2.2. DASY5 E-Field Probe	10
2.2.1. Isotropic E-Field Probe Specification	10
2.3. Boundary Detection Unit and Probe Mounting Device .	11
2.4. DATA Acquisition Electronics (DAE) and Measuremen	t Server11
2.5. Robot	12
2.6. Light Beam Unit	12
2.7. Device Holder	13
2.8. SAM Twin Phantom	13
3. Tissue Simulating Liquid	14
3.1. The composition of the tissue simulating liquid	14
3.2. Tissue Calibration Result	15
3.3. Tissue Dielectric Parameters for Head and Body Phan	toms17
4. SAR Measurement Procedure	18
4.1. SAR System Validation	18
4.1.1. Validation Dipoles	18
4.1.2. Validation Result	19
4.2. SAR Measurement Procedure	21
5. SAR Exposure Limits	22
6. Test Equipment List	23
7. Measurement Uncertainty	29
8. Conducted Power Measurement	30
9. Test Results	31



9.1.	SAR Test Results Summary	31
Append	dix A. SAR System Validation Data	37
Append	dix B. SAR measurement Data	42
Append	dix C. Test Setup Photographs & EUT Photographs	71
Append	dix D. Probe Calibration Data	77
Append	dix E. Dipole Calibration Data	84
Append	dix F. DAE Calibration Data	111



## 1. General Information

## 1.1. EUT Description

Product Name	mobile phone
Model No.	X85
IMEI 1	352273017386340
IMEI 2	352751019523267
IMEI 3	358570010103893
Hardware Version	T18_PCB_V1.2
Software Version	T18_X85-1_320X240_TRISIM_12864_FJU_MArEnFrPeP
T = 5	oSpTu_V01.03B05
Tx Frequency Range	GSM 850: 824~849MHz
	PCS 1900: 1850~1910MHz
	Wi-Fi: 2412~2462MHz
Rx Frequency Range	GSM 850: 869~894MHz
	PCS 1900: 1930~1990MHz
	Wi-Fi: 2412~2462MHz
Antenna Type	Internal
GPRS Type	Class B
GPRS Class	10
Type of Modulation	GMSK
Device Category	Portable
Peak Antenna Gain	2dBi
Max. Output Power	GSM850: 31.94dBm <sim 1=""></sim>
(Avg. Burst Power)	PCS1900: 26.73dBm <sim 1=""></sim>
	Wi-Fi: 20.49dBm
Max. Output Power	GSM850: 35.59 dBm- ERP
(Radiated)	PCS1900: 31.54 dBm- EIRP
Headset Model Number	N/A
Battery	Rated Voltage and Capacitance: 3.7V 750mAh 2.78Wh
Adapter	Input: AC 90-240V 50/60Hz, 0.2A
	Output: DC 5V, 500mA



#### 1.2. Test Environment


Ambient conditions in the laboratory:

Items	Required	Actual
Temperature (°C)	18-25	21.5± 2
Humidity (%RH)	30-70	52



#### 2. SAR Measurement System

## 2.1. DASY5 System Description



The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.



#### 2.1.1. Applications

Predefined procedures and evaluations for automated compliance testing with all worldwide standards, e.g., IEEE 1528, OET 65, IEC 62209-1, IEC 62209-2, EN 50360, EN 50383 and others.

#### 2.1.2. Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm<sup>2</sup> step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE 1528-2003, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan).

#### 2.1.3. Zoom Scan (Cube Scan Averaging)

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications utilize a physical step of 7x7x7 (5mmx5mmx5mm) providing a volume of 30mm in the X & Y axis, and 30mm in the Z axis.

#### 2.1.4. Uncertainty of Inter-/Extrapolation and Averaging

In order to evaluate the uncertainty of the interpolation, extrapolation and averaged SAR calculation algorithms of the Postprocessor, DASY5 allows the generation of measurement grids which are artificially predefined by analytically based test functions. Therefore, the grids of area scans and zoom scans can be filled with uncertainty test data, according to the SAR benchmark functions of IEEE 1528. The three analytical functions shown in equations as below are used to describe the possible range of the expected SAR distributions for the tested handsets. The field gradients are covered by the spatially flat distribution f1, the spatially steep distribution f3 and f2 accounts for H-field cancellation on the phantom/tissue surface.



$$f_1(x, y, z) = Ae^{-\frac{z}{2a}}\cos^2\left(\frac{\pi}{2}\frac{\sqrt{x'^2 + y'^2}}{5a}\right)$$

$$f_2(x, y, z) = Ae^{-\frac{z}{a}}\frac{a^2}{a^2 + x'^2}\left(3 - e^{-\frac{2z}{a}}\right)\cos^2\left(\frac{\pi}{2}\frac{y'}{3a}\right)$$

$$f_3(x, y, z) = A\frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2}\left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a+2z)^2}\right)$$

#### 2.2. DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 62209-1, IEC 62209, etc.) under ISO 17025. The calibration data are in Appendix D.

#### 2.2.1. Isotropic E-Field Probe Specification

Model	EX3DV4
Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g. DGBE)
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μW/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



#### 2.3. Boundary Detection Unit and Probe Mounting Device

The DASY probes use a precise connector and an additional holder for the probe, consisting of a plastic tube and a flexible silicon ring to center the probe. The connector at the DAE is flexibly mounted and held in the default position with magnets and springs. Two switching systems in the connector mount detect frontal and lateral probe collisions and trigger the necessary software response.



#### 2.4. DATA Acquisition Electronics (DAE) and Measurement Server

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit.

Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE4 is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chipdisk and 128MB RAM. The necessary circuits for communication with the DAE electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.





#### 2.5. Robot

The DASY5 system uses the high precision robots TX90 XL type out of the newer series from Stäubli SA (France). For the 6-axis controller DASY5 system, the CS8C robot controller version from Stäubli is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- ➢ 6-axis controller



#### 2.6. Light Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.





#### 2.7. Device Holder

The DASY5 device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY5 device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon r = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



#### 2.8. SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left head
- Right head
- Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.



## 3. Tissue Simulating Liquid

## 3.1. The composition of the tissue simulating liquid

INGREDIENT	835MHz	835MHz	1900MHz	1900MHz	2450MHz
(% Weight)	Head	Body	Head	Body	Body
Water	40.45	52.4	54.90	40.5	73.2
Salt	1.45	1.40	0.18	0.50	0.04
Sugar	57.6	45.0	0.00	58.0	0.00
HEC	0.40	1.00	0.00	0.50	0.00
Preventol	0.10	0.20	0.00	0.50	0.00
DGBE	0.00	0.00	44.92	0.00	26.7



#### 3.2. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY5 Dielectric Probe Kit and Agilent Vector Network Analyzer E5071C

Head Tissue Simulant Measurement					
Frequency	Description	Dielectric Parameters		Tissue Temp.	
[MHz]	Description	ε <sub>r</sub>	σ [s/m]	[°C]	
835 MHz	Reference result	42.54	0.91	N/A	
	± 5% window	40.41 to 44.67	0.86 to 0.96	IN/A	
	06-07-2011	41.12	0.89	21.0	

Body Tissue Simulant Measurement					
Frequency	Description	Dielectric Parameters		Tissue Temp.	
[MHz]	Description	ε <sub>r</sub>	σ [s/m]	[°C]	
835 MHz	Reference result	55.2	0.97	N/A	
	± 5% window	52.44 to 57.96	0.92 to 1.02	IN/A	
	06-07-2011	54.54	1.00	21.0	
				•	

Head Tissue Simulant Measurement					
Frequency	Description	Dielectric Parameters		Tissue Temp.	
[MHz]	Description	ε <sub>r</sub>	σ [s/m]	[°C]	
1900 MHz	Reference result	39.9	1.42	N/A	
	± 5% window	37.91 to 41.90	1.35 to 1.49	IN/A	
	06-07-2011	38.98	1.45	21.0	

Body Tissue Simulant Measurement						
Frequency	Description	Dielectric Parameters		Tissue Temp.		
[MHz]	Description	ε <sub>r</sub>	ஏ [s/m]	[°C]		
1900 MHz	Reference result	53.3	1.52	N/A		
	± 5% window	50.64 to 55.97	1.44 to 1.60	IN/A		
	06-07-2011	51.77	1.52	21.0		
				•		



Body Tissue Simulant Measurement					
Frequency	Description	Dielectric Parameters		Tissue Temp.	
[MHz]	Description	ε <sub>r</sub>	σ [s/m]	[°C]	
2450MHz	Reference result	52.7	1.95	N/A	
	± 5% window	50.07 to 55.34	1.85 to 2.05	IN/A	
	06-07-2011	50.89	1.96	21.0	



#### 3.3. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Target Frequency	He	ad	Во	dy
(MHz)	$\epsilon_{r}$	σ (S/m)	ε <sub>r</sub>	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00


( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho$  = 1000 kg/m³)



#### 4. SAR Measurement Procedure

#### 4.1. SAR System Validation

## 4.1.1. Validation Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles.

Frequency	L (mm)	h (mm)	d (mm)
835MHz	161.0	89.8	3.6
1900MHz	68.0	39.5	3.6
2450MHz	51.5	30.4	3.6



#### 4.1.2. Validation Result

System Perf	ormance Check	at 835MHz	&1900MHz for Head	

Validation Kit: D835V2-SN 4d094

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
835 MHz	Reference result ± 10% window	9.70 8.73 to 10.67	6.30 5.67 to 6.93	N/A
	06-07-2011	9.92	6.48	21.0

#### Validation Kit: D1900V2-SN 5d121

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
1900 MHz	Reference result ± 10% window	39.8 35.82 to 43.78	21.1 18.99 to 23.21	N/A
	06-07-2011	42.00	21.48	21.0

Note: All SAR values are normalized to 1W forward power.

## System Performance Check at 835MHz &1900MHz for Body

#### Validation Kit: D835V2-SN 4d094

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
835 MHz	Reference result ± 10% window	9.90 8.91 to 10.89	6.53 5.88 to 7.18	N/A
	06-07-2011	9.80	6.32	21.0

#### Validation Kit: D1900V2-SN 5d121

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
1900 MHz	Reference result ± 10% window	41.4 37.26 to 45.54	22.3 20.07 to 24.53	N/A
	06-07-2011	39.36	20.44	21.0

Note: All SAR values are normalized to 1W forward power.



## System Performance Check at 2450MHz for Body

Validation Dipole: D2450V2, SN: 839

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]	
2450 MHz	Reference result ± 10% window	51.6 46.44 to 56.76	24.2 21.78 to 26.62	N/A	
	06-07-2011	50.40	23.32	21.0	

Note: All SAR values are normalized to 1W forward power.



#### 4.2. SAR Measurement Procedure

The ALSAS-10U calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

σ: represents the simulated tissue conductivity

p: represents the tissue density

The EUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm<sup>2</sup>) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm<sup>3</sup>).



## 5. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 "Uncontrolled Environments" limits. These limits apply to a location which is deemed as "Uncontrolled Environment" which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled
	Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	1.60 W/kg
Spatial Average SAR (whole body)	0.08 W/kg
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	4.00 W/kg



## 6. Test Equipment List

Instrument	Manufacturer	Model No.	Serial No.	Cali. Due Date
Stäubli Robot TX60L	Stäubli	TX60L	F10/5C90A1/A/01	only once
Controller	Stäubli	SP1	S-0034	only once
Dipole Validation Kits	Speag	D835V2	4d094	2012.03.15
Dipole Validation Kits	Speag	D1900V2	5d121	2012.03.23
Dipole Validation Kits	Speag	D2450V2	839	2012.04.10
SAM Twin Phantom	Speag	SAM	TP-1561/1562	N/A
Device Holder	Speag	SD 000 H01 HA	N/A	N/A
Data	Speag	DAE4	1220	2012.12.03
Acquisition Electronic				
E-Field Probe	Speag	EX3DV4	3710	2012.02.25
SAR Software	Speag	DASY5	V5.2 Build 162	N/A
Power Amplifier	Mini-Circuit	ZVA-183-S+	N657400950	N/A
Directional Coupler	Agilent	778D	20160	N/A
Universal Radio	R&S	CMU 200	117088	2011.07.12
Communication Tester				
Vector Network	Agilent	E5071C	MY48367267	2012.04.10
Signal Generator	Agilent	E4438C	MY49070163	2012.04.23
Power Meter	Anritsu	ML2495A	0905006	2012.01.12
Wide Bandwidth Sensor	Anritsu	MA2411B	0846014	2012.01.12

Note: Per KDB 450824 D02 requirements for dipole calibration, QuieTek Lab has adopted two years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:


- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss is within 20% of calibrated measurement (Show below);
- 4. Impedance is within  $5\Omega$  of calibrated measurement (Show below).




#### Impedance Plot for D835V2

#### 835 Head

Calibrated impedance: 52.2  $\Omega$ ; Measured impedance: 50.322  $\Omega$  (within  $5\Omega$ )




Calibrated return loss: -29.4 dB; Measured impedance: -27.246 dB (within 20%)






#### 835 Body

Calibrated impedance: 48.0  $\Omega$ ; Measured impedance: 48.611  $\Omega$  (within  $5\Omega$ )



Calibrated return loss: -25.5 dB; Measured impedance: -26.333 dB (within 20%)







#### Impedance Plot for D1900V2

#### 1900 Head

Calibrated impedance: 50.6  $\Omega$ ; Measured impedance: 51.610  $\Omega$  (within  $5\Omega$ )




Calibrated return loss: -22.7 dB; Measured impedance: -23.651 dB (within 20%)






#### 1900 Body

Calibrated impedance: 46.1  $\Omega$ ; Measured impedance: 45.692  $\Omega$  (within  $5\Omega$ )



Calibrated return loss: -21.5 dB; Measured impedance: -19.090 dB (within 20%)







#### Impedance Plot for D2450V2

#### 2450 Body

Calibrated impedance: 50.0  $\Omega$ ; Measured impedance: 50.36  $\Omega$  (within  $5\Omega$ )



Calibrated return loss: -40.8 dB; Measured impedance: -42.22 dB (within 20%)





# 7. Measurement Uncertainty

DASY5 Uncertainty								
Error Description	Uncert.	Prob.	Div.	(Ci)	(Ci)	Std.	Std.	(Vi)
	value	Dist.		1g	10g	Unc.	Unc.	Veff
						(1g)	(10g)	
Measurement System		•	•	•	•			•
Probe Calibration	±5.5%	N	1	1	1	±5.5%	±5.5%	∞
Axial Isotropy	±4.7%	R	√3	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	√3	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Readout Electronics	±0.3%	N	1	1	1	±0.3%	±0.3%	∞
Response Time	±0.8%	R	√3	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	√3	1	1	±1.5%	±1.5%	∞
RF Ambient Noise	±3.0%	R	√3	1	1	±1.7%	±1.7%	∞
RF Ambient Reflections	±3.0%	R	√3	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.4%	R	√3	1	1	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	√3	1	1	±1.7%	±1.7%	∞
Max. SAR Eval.	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Test Sample Related								•
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	√3	1	1	±2.9%	±2.9%	∞
Phantom and Setup								
Phantom Uncertainty	±4.0%	R	√3	1	1	±2.3%	±2.3%	∞
Liquid Conductivity	±5.0%	R	/2	0.64	0.43	±1.8%	±1.2%	∞
(target)	13.076	IX.	√3	0.04	0.43	11.076	11.2/0	
Liquid Conductivity	±2.5%	N	1	0.64	0.43	±1.6%	±1.1%	∞
(meas.)	12.070	14	<b>'</b>	0.04	0.40	11.070	11.170	
Liquid Permittivity	±5.0%	R	√3	0.6	0.49	±1.7%	±1.4%	∞
(target)	10.070	1	V 3	0.0	0.40	11.770	11.470	
Liquid Permittivity	±2.5%	N	1	0.6	0.49	±1.5%	±1.2%	∞
(meas.)	070						/0	
Combined Std. Uncertain	inty					±10.7%	±10.5%	387
Expanded STD Uncertain	inty					±21.5%	±21.0%	



## 8. Conducted Power Measurement

Mode	Frequency (MHz)	Avg. Burst Power	Duty Cycle	Frame Power
		(dBm)	Factor (dB)	(dBm)
Maximum Power <s< td=""><td>IM 1&gt;</td><td></td><td></td><td></td></s<>	IM 1>			
	824.2	31.62	-9	22.62
GSM850	836.4	31.80	-9	22.80
	848.8	31.94	-9	22.94
	1850.2	26.28	-9	17.28
PCS1900	1880.0	26.55	-9	17.55
	1909.8	26.73	-9	17.73
	824.2	31.49	-6	25.49
GPRS850(2 Slot)	836.4	31.68	-6	25.68
	848.8	31.82	-6	25.82
	1850.2	26.20	-6	20.20
GPRS1900(2 Slot)	1880.0	26.51	-6	20.51
	1909.8	26.18	-6	20.18
Maximum Power <s< td=""><td>IM 2&gt;</td><td></td><td></td><td></td></s<>	IM 2>			
GSM850	836.4	31.79	-9	22.79
PCS1900	1880.0	26.53	-9	17.53
Maximum Power <s< td=""><td>IM 3&gt;</td><td></td><td></td><td></td></s<>	IM 3>			
GSM850	836.4	31.78	-9	22.78
PCS1900	1880.0	26.52	-9	17.52

Note: All SAR testing was done in SIM 1.

#### Wi-Fi output power

Test Mode	Channel No.	Frequency	Conducted Power
		(MHz)	(dBm)
	01	2412	20.45
802.11b	06	2437	20.27
	11	2462	20.09
	01	2412	20.46
802.11g	06	2437	20.49
	11	2462	20.41
	01	2412	18.79
802.11n(20MHz)	06	2437	18.51
	11	2462	18.40

Note: the output power was based on peak detector.



#### 9. Test Results

#### 9.1. SAR Test Results Summary

#### 9.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE1528, and Body SAR was performed with the device 15mm from the phantom. Body SAR was also performed with the headset attached and without.

#### 9.1.2. Body SAR with Headset

Testing with the headset was performed at the position and channels that resulted in the highest body SAR. This testing was performed with GPRS transmitting with 2 uplink timeslots. This operation mode represents the maximum SAR situation, when downloading data via GPRS and listening to music by headset. SAR without the headset attached was significantly higher than with the headset, and also was verified several times and confirmed, so the final test data shown were the worst case without headset.

In the Body SAR test result table, body-worn means display of device down, body-front means display of device up.

#### 9.1.3. Operation Mode

This is a multislot class 10 device capable of 2 uplink timeslots. During the head SAR test, the device was transmitting with 1 uplink timeslot; during the body SAR test, it was transmitting with 2 uplink timeslots. Additionally, this device doesn't support dual transfer mode (DTM).

The final SAR test was done with continuous transmission setting by RF test tool on the phone.

Evaluation mode: 802.11b, 802.11g.

Additionally, this device doesn't support simultaneous transmission between Wi-Fi and GSM.

#### 9.1.4. Co-located SAR

Reference document: KDB 447498 and KDB 648474, KDB 248227.

WWAN/BT, BT Max peak power is less than Pref and the WWAN SAR value is less than 1.2W/kg, so no Simultaneous SAR needed.

WWAN/WLAN, Sum of WWAN and WLAN SAR is less than 1.6W/kg.

WLAN/BT, BT standalone SAR is not needed caused its power is less than Pref.

Simultaneous SAR is not needed because sum of SAR is less then 1.6 W/kg.



#### 9.1.5. Test Result

SAR MEASUREMENT

Ambient Temperature (°C): 21.5 ±2 Relative Humidity (%): 52

Liquid Temperature (°C): 21.0 ±2 Depth of Liquid (cm):>15

Product: mobile phone

Test Mode: GSM850 <SIM 1>

Test Antenna		Freque	ency	Frame Power	Power Drift	SAR 1g	Limit	
Position Head	Position	Channel	MHz	(dBm)	(<±0.2)	(W/kg)	(W/kg)	
Left-Cheek	Fixed	128	824.2	22.62			1.6	
Left-Cheek	Fixed	189	836.4	22.80	-0.066	0.314	1.6	
Left-Cheek	Fixed	251	848.8	22.94			1.6	
Left-Tilted	Fixed	189	836.4	22.80	-0.077	0.273	1.6	
Right-Cheek	Fixed	128	824.2	22.62			1.6	
Right-Cheek	Fixed	189	836.4	22.80	-0.216	0.317	1.6	
Right-Cheek	Fixed	251	848.8	22.94			1.6	
Right-Tilted	Fixed	189	836.4	22.80	-0.076	0.306	1.6	
Test Mode: G	SM850 <si< td=""><td>M 2&gt;</td><td></td><td></td><td></td><td></td><td></td></si<>	M 2>						
Right-Cheek	Fixed	251	848.8	22.79	-0.048	0.315	1.6	
Test Mode: G	SM850 <si< td=""><td>M 3&gt;</td><td></td><td></td><td></td><td></td><td></td></si<>	M 3>						
Right-Cheek	Fixed	251	848.8	22.78	-0.115	0.291	1.6	



SAR MEASUREMENT	REMENT	JRI	SI	Α	ИE	١ ١	AR	S
-----------------	--------	-----	----	---	----	-----	----	---

Ambient Temperature (°C): 21.5 ±2 Relative Humidity (%): 52

Liquid Temperature (°C): 21.0 ±2 Depth of Liquid (cm):>15

Product: mobile phone

Test Mode: GSM850

Test Position	Antenna	Frequency		Frame Power	Power Drift	SAR 1g	Limit			
Body Positi	Position	Channel	MHz	(dBm)	(<±0.2)	(W/kg)	(W/kg)			
Body-worn	Fixed	128	824.2	22.62			1.6			
Body-worn	Fixed	189	836.4	22.80	0.038	0.472	1.6			
Body-worn	Fixed	251	848.8	22.94			1.6			
Body-front	Fixed	189	836.4	22.80	-0.090	0.150	1.6			
Test Mode: GPR	Test Mode: GPRS850 2slot									
Body-worn	Fixed	128	824.2	25.49	-0.192	0.758	1.6			
Body-worn	Fixed	189	836.4	25.68	-0.193	0.986	1.6			
Body-worn	Fixed	251	848.8	25.82	-0.142	1.130	1.6			
Body-front	Fixed	189	836.4	25.68	-0.107	0.365	1.6			
Body-worn (With Headset)	Fixed	189	836.4	25.68	-0.144	0.757	1.6			



SAR MEASUREMENT

Ambient Temperature (°C): 21.5 ±2 Relative Humidity (%): 52

Liquid Temperature (°C): 21.0 ±2 Depth of Liquid (cm):>15

Product: mobile phone

Test Mode: PCS1900 <SIM 1>

rest Mode. I Go 1900 Kolivi Iz										
Test Position Head	Antenna Position	Frequ Channel	ency MHz	Frame Power (dBm)	Power Drift (<±0.2)	SAR 1g (W/kg)	Limit (W/kg)			
Left-Cheek	Fixed	512	1850.2	17.28			1.6			
Left-Cheek	Fixed	661	1880.0	17.55	0.101	0.382	1.6			
Left-Cheek	Fixed	810	1909.8	17.73			1.6			
Left-Tilted	Fixed	661	1880.0	17.55	0.105	0.422	1.6			
Right-Cheek	Fixed	512	1850.2	17.28			1.6			
Right-Cheek	Fixed	661	1880.0	17.55	0.178	0.412	1.6			
Right-Cheek	Fixed	810	1909.8	17.73			1.6			
Right-Tilted	Fixed	661	1880.0	17.55	0.105	0.424	1.6			
Test Mode: Po	Test Mode: PCS1900 <sim 2=""></sim>									
Right-Tilted	Fixed	661	1880.0	17.53	0.113	0.371	1.6			
Test Mode: Po	CS1900 <s< td=""><td>3&gt;</td><td></td><td></td><td></td><td></td><td></td></s<>	3>								
Right-Tilted	Fixed	661	1880.0	17.52	0.128	0.403	1.6			



#### SAR MEASUREMENT

Ambient Temperature (°C): 21.5 ±2 Relative Humidity (%): 52

Liquid Temperature (°C): 21.0 ±2 Depth of Liquid (cm):>15

Product: mobile phone

Test Mode: PCS1900

	_			_	_		_		
Test Position	Antenna	Frequ	uency	Frame	Power Drift (<±0.2)	SAR 1g (W/kg)	Limit (W/kg)		
Body Positi	Position	Channel	MHz	Power (dBm)					
Body-worn	Fixed	512	1850.2	17.28			1.6		
Body-worn	Fixed	661	1880.0	17.55	0.251	0.178	1.6		
Body-worn	Fixed	810	1909.8	17.73			1.6		
Body-front	Fixed	661	1880.0	17.55	0.072	0.110	1.6		
Test Mode: GPRS1900 2slot									
Body-worn	Fixed	512	1850.2	20.20			1.6		
Body-worn	Fixed	661	1880.0	20.51	0.192	0.293	1.6		
Body-worn	Fixed	810	1909.8	20.18			1.6		
Body-front	Fixed	661	1880.0	20.51	-0.106	0.234	1.6		
Body-worn (With Headset)	Fixed	661	1880.0	20.51	-0.169	0.222	1.6		



SAR MEASUREMENT	
Ambient Temperature (°C): 21.5 ±2	Relative Humidity (%): 52
Liquid Temperature (°C) : 21.0 ±2	Depth of Liquid (cm):>15

Product: GSM Mobile Phone

Test Mode: 802.11g

Test Position	Antenna	Frequency		Conducted	Power Drift	SAR 1g	Limit
Body	Position	Channel	MHz	Power (dBm)	(<±0.2)	(W/kg)	(W/kg )
Body-worn	Fixed	6	2437	20.49	-0.170	0.012	1.6
Body-front	Fixed	6	2437	20.49	0.187	0.004	1.6



### Appendix A. SAR System Validation Data

Date/Time: 06-07-2011

Test Laboratory: QuieTek Lab System Check Head 835MHz

**DUT: Dipole 835 MHz D835V2; Type: D835V2** 

Communication System: CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

• Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/System Check GSM850 Head/Area Scan (6x19x1): Measurement grid: dx=10mm, dy=10mm, Maximum value of SAR (measured) = 2.55 mW/g

Configuration/System Check GSM850 Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 55 V/m; Power Drift = -0.059 dB

Peak SAR (extrapolated) = 3.71 W/kg

**SAR(1 g) = 2.48 mW/g; SAR(10 g) = 1.62 mW/g** Maximum value of SAR (measured) = 2.67 mW/g



0 dB = 2.67 mW/g



Test Laboratory: QuieTek Lab System Check Body 835MHz

**DUT: Dipole 835 MHz D835V2; Type: D835V2** 

Communication System: CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz;  $\sigma = 1$  mho/m;  $\epsilon r = 54.5$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59


Configuration/System Check GSM835 Body/Area Scan (8x16x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 2.58 mW/g

Configuration/System Check GSM835 Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 51.8 V/m; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 3.72 W/kg

**SAR(1 g) = 2.45 mW/g; SAR(10 g) = 1.58 mW/g** Maximum value of SAR (measured) = 2.64 mW/g



0 dB = 2.64 mW/g



Test Laboratory: QuieTek Lab System Check Head 1900MHz

#### DUT: Dipole 1900 MHz D1900V2; Type: D1900V2

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle: 1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz;  $\sigma = 1.45$  mho/m;  $\epsilon r = 39$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59


# Configuration/System Check PCS1900 Head/Area Scan (6X85x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 11.4 mW/g

Configuration/System Check PCS1900 Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 88.4 V/m; Power Drift = 0.069 dB

Peak SAR (extrapolated) = 19.8 W/kg

**SAR(1 g) = 10.5 mW/g; SAR(10 g) = 5.37 mW/g** Maximum value of SAR (measured) = 11.9 mW/g



0 dB = 11.9 mW/g



Test Laboratory: QuieTek Lab System Check Body 1900MHz

#### DUT: Dipole 1900 MHz D1900V2; Type: D1900V2

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle: 1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon r = 51.8$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

- Probe: EX3DV4 SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59


# Configuration/System Check PCS1900 Body/Area Scan (7X85x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 10.8 mW/g

Configuration/System Check PCS1900 Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 84.4 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 17.9 W/kg

**SAR(1 g) = 9.84 mW/g; SAR(10 g) = 5.11 mW/g** Maximum value of SAR (measured) = 11.1 mW/g



0 dB = 11.1 mW/g



Test Laboratory: QuieTek Lab System Check Body 2450MHz

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2

Communication System: CW; Communication System Band: D2450 (2450.0 MHz); Duty Cycle: 1:1;

Frequency: 2450 MHz; Medium parameters used: f = 2450 MHz;  $\sigma = 1.96$  mho/m;  $\epsilon r = 50.9$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

- Probe: EX3DV4 SN3710; ConvF(7, 7, 7); Calibrated: 05/03/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 09/03/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/Body 2450MHz/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (measured) = 12.7 mW/g

Configuration/Body 2450MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,

dz=5mm, Reference Value = 85.6 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 25.4 W/kg

**SAR(1 g) = 12.6 mW/g; SAR(10 g) = 5.83 mW/g** Maximum value of SAR (measured) = 14.5 mW/g



0 dB = 14.5 mW/g



### **Appendix B. SAR measurement Data**

Date/Time: 06-07-2011

Test Laboratory: QuieTek Lab GSM850 Mid Touch-Left

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\rho = 1000$  kg/m3; Phantom section: Left Section

Ambient temperature (°C): 21.5, Liquid temperature (°C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Left/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.298 mW/g

Configuration/GSM850 Mid Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 15 V/m; Power Drift = -0.066 dB

Peak SAR (extrapolated) = 0.428 W/kg

SAR(1 g) = 0.314 mW/g; SAR(10 g) = 0.224 mW/g Maximum value of SAR (measured) = 0.336 mW/g



0 dB = 0.336 mW/g



Test Laboratory: QuieTek Lab

GSM850 Mid Tilt-Left

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\rho = 1000$  kg/m3; Phantom section: Left Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Tilt-Left/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.287 mW/g

Configuration/GSM850 Mid Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16.9 V/m; Power Drift = -0.077 dB

Peak SAR (extrapolated) = 0.367 W/kg

SAR(1 g) = 0.273 mW/g; SAR(10 g) = 0.192 mW/g Maximum value of SAR (measured) = 0.292 mW/g



0 dB = 0.292 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Touch-Right

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\rho = 1000$  kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.336 mW/g

Configuration/GSM850 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16.4 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.571 W/kg

**SAR(1 g) = 0.317 mW/g; SAR(10 g) = 0.214 mW/g** Maximum value of SAR (measured) = 0.337 mW/g



0 dB = 0.337 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Tilt-Right

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\rho = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\epsilon = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\epsilon = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\epsilon = 0.89$  mho/m;  $\epsilon = 0.89$  mho/m

= 1000 kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Tilt-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.322 mW/g

Configuration/GSM850 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16 V/m; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 0.501 W/kg

**SAR(1 g) = 0.306 mW/g; SAR(10 g) = 0.204 mW/g** Maximum value of SAR (measured) = 0.328 mW/g



0 dB = 0.328 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Touch-Right <SIM 2>

DUT: mobile phone ; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 41.1$ ;  $\rho = 1000$  kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.305 mW/g

Configuration/GSM850 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 15.2 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 0.620 W/kg

**SAR(1 g) = 0.315 mW/g; SAR(10 g) = 0.199 mW/g** Maximum value of SAR (measured) = 0.339 mW/g



0 dB = 0.339 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Touch-Right <SIM 3>

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty

Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma$  = 0.89 mho/m;  $\epsilon r$  = 41.1;  $\rho$ 

= 1000 kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.301 mW/g

Configuration/GSM850 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 15.8 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 0.536 W/kg

**SAR(1 g) = 0.291 mW/g; SAR(10 g) = 0.199 mW/g** Maximum value of SAR (measured) = 0.309 mW/g



0 dB = 0.309 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Body-Back

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 1$  mho/m;  $\epsilon r = 54.5$ ;  $\rho = 1$ 

1000 kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.444 mW/g

Configuration/GSM850 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 13.6 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 0.630 W/kg

**SAR(1 g) = 0.472 mW/g; SAR(10 g) = 0.340 mW/g** Maximum value of SAR (measured) = 0.495 mW/g



0 dB = 0.495 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Body-Front

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 1$  mho/m;  $\epsilon r = 54.5$ ;  $\rho = 1$ 

1000 kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Body-Front/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.159 mW/g

Configuration/GSM850 Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 8.22 V/m; Power Drift = -0.090 dB

Peak SAR (extrapolated) = 0.210 W/kg

**SAR(1 g) = 0.150 mW/g; SAR(10 g) = 0.108 mW/g** Maximum value of SAR (measured) = 0.158 mW/g



0 dB = 0.158 mW/g



Test Laboratory: QuieTek Lab
GPRS850 Low Body-Back(2up)
DUT: mobile phone; Type: X85

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 824.2 MHz; Medium parameters used: f = 824.2 MHz;  $\sigma = 0.99$  mho/m;  $\epsilon r = 54.6$ ;  $\rho = 1000$ 

kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Low Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.730 mW/g

Configuration/GPRS850 Low Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16.5 V/m; Power Drift = -0.192 dB

Peak SAR (extrapolated) = 1.82 W/kg

**SAR(1 g) = 0.758 mW/g; SAR(10 g) = 0.548 mW/g** Maximum value of SAR (measured) = 0.784 mW/g



0 dB = 0.784 mW/g



Test Laboratory: QuieTek Lab GPRS850 Mid Body-Back(2up) DUT: mobile phone; Type: X85

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 1$  mho/m;  $\epsilon r = 54.5$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Mid Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.984 mW/g

Configuration/GPRS850 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 18.8 V/m; Power Drift = -0.193 dB

Peak SAR (extrapolated) = 1.33 W/kg

**SAR(1 g) = 0.986 mW/g; SAR(10 g) = 0.712 mW/g** Maximum value of SAR (measured) = 1.04 mW/g



0 dB = 1.04 mW/g



Test Laboratory: QuieTek Lab GPRS850 High Body-Back(2up) **DUT: mobile phone ; Type: X85** 

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 848.6 MHz; Medium parameters used: f = 848.6 MHz;  $\sigma = 1.01$  mho/m;  $\epsilon r = 54.4$ ;  $\rho = 1000$ 

kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 High Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 1.07 mW/g

Configuration/GPRS850 High Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 19.4 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 1.56 W/kg


**SAR(1 g) = 1.13 mW/g; SAR(10 g) = 0.808 mW/g** Maximum value of SAR (measured) = 1.18 mW/g



0 dB = 1.18 mW/g



#### **Z-Axis Plot**





Test Laboratory: QuieTek Lab
GPRS850 Mid Body-Front(2up)
DUT: mobile phone; Type: X85

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 1$  mho/m;  $\epsilon r = 54.5$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Mid Body-Front/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.398 mW/g

Configuration/GPRS850 Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 12.9 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 0.489 W/kg

**SAR(1 g) = 0.365 mW/g; SAR(10 g) = 0.264 mW/g** Maximum value of SAR (measured) = 0.383 mW/g



0 dB = 0.383 mW/g



Test Laboratory: QuieTek Lab

GPRS850 Mid Body-Back(2up) (With Headset)

DUT: mobile phone; Type: X85

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 1$  mho/m;  $\epsilon r = 54.5$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Mid Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.740 mW/g

Configuration/GPRS850 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 17.1 V/m; Power Drift = -0.144 dB

Peak SAR (extrapolated) = 1.54 W/kg

**SAR(1 g) = 0.757 mW/g; SAR(10 g) = 0.513 mW/g** Maximum value of SAR (measured) = 0.765 mW/g



0 dB = 0.765 mW/g



Test Laboratory: QuieTek Lab PCS 1900 Mid Touch-Left

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.43$  mho/m;  $\epsilon r = 39$ ;

ρ = 1000 kg/m3; Phantom section: Left Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Touch-Left/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.385 mW/g

Configuration/PCS1900 Mid Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 0.658 W/kg

**SAR(1 g) = 0.382 mW/g; SAR(10 g) = 0.226 mW/g** Maximum value of SAR (measured) = 0.401 mW/g



0 dB = 0.401 mW/g



Test Laboratory: QuieTek Lab

PCS 1900 Mid Tilt-Left

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.43$  mho/m;  $\epsilon r = 39$ ;

ρ = 1000 kg/m3; Phantom section: Left Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Left/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.360 mW/g

Configuration/PCS1900 Mid Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16.7 V/m; Power Drift = 0.105 dB

Peak SAR (extrapolated) = 0.717 W/kg

**SAR(1 g) = 0.422 mW/g; SAR(10 g) = 0.242 mW/g** Maximum value of SAR (measured) = 0.451 mW/g



0 dB = 0.451 mW/g



Test Laboratory: QuieTek Lab PCS 1900 Mid Touch-Right

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.43$  mho/m;  $\epsilon r = 39$ ;

ρ = 1000 kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Touch-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.320 mW/g

Configuration/PCS1900 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 12.3 V/m; Power Drift = 0.178 dB

Peak SAR (extrapolated) = 0.793 W/kg

**SAR(1 g) = 0.412 mW/g; SAR(10 g) = 0.216 mW/g** Maximum value of SAR (measured) = 0.458 mW/g



0 dB = 0.458 mW/g



Test Laboratory: QuieTek Lab
PCS 1900 Mid Tilt-Right

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.43$  mho/m;  $\epsilon r = 39$ ;

 $\rho$  = 1000 kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.336 mW/g

Configuration/PCS1900 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 14.1 V/m; Power Drift = 0.105 dB

Peak SAR (extrapolated) = 0.826 W/kg


**SAR(1 g) = 0.424 mW/g; SAR(10 g) = 0.226 mW/g** Maximum value of SAR (measured) = 0.457 mW/g



0 dB = 0.457 mW/g



#### **Z-Axis Plot**





Test Laboratory: QuieTek Lab
PCS 1900 Mid Tilt-Right <SIM 2> **DUT: mobile phone ; Type: X85** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.43$  mho/m;  $\epsilon r = 39$ ;

ρ = 1000 kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.278 mW/g

Configuration/PCS1900 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 12.7 V/m; Power Drift = 0.113 dB

Peak SAR (extrapolated) = 0.691 W/kg

**SAR(1 g) = 0.371 mW/g; SAR(10 g) = 0.203 mW/g** Maximum value of SAR (measured) = 0.415 mW/g



0 dB = 0.415 mW/g



Test Laboratory: QuieTek Lab
PCS 1900 Mid Tilt-Right <SIM 3> **DUT: mobile phone ; Type: X85** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.43$  mho/m;  $\epsilon r = 39$ ;

 $\rho$  = 1000 kg/m3; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Right/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.327 mW/g

Configuration/PCS1900 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 13.4 V/m; Power Drift = 0.128 dB

Peak SAR (extrapolated) = 0.774 W/kg

**SAR(1 g) = 0.403 mW/g; SAR(10 g) = 0.216 mW/g** Maximum value of SAR (measured) = 0.439 mW/g



0 dB = 0.439 mW/g



Test Laboratory: QuieTek Lab PCS1900 Mid Body-Back

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.5$  mho/m;  $\epsilon r = 51.8$ ;

 $\rho$  = 1000 kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.170 mW/g

Configuration/PCS1900 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 9.68 V/m; Power Drift = 0.151 dB

Peak SAR (extrapolated) = 0.293 W/kg

**SAR(1 g) = 0.178 mW/g; SAR(10 g) = 0.107 mW/g** Maximum value of SAR (measured) = 0.194 mW/g



0 dB = 0.194 mW/g



Test Laboratory: QuieTek Lab PCS1900 Mid Body-Front

DUT: mobile phone; Type: X85

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.5$  mho/m;  $\epsilon r = 51.8$ ;

 $\rho$  = 1000 kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Body-Front/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.111 mW/g

Configuration/PCS1900 Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 7.16 V/m; Power Drift = 0.072 dB

Peak SAR (extrapolated) = 0.183 W/kg

**SAR(1 g) = 0.110 mW/g; SAR(10 g) = 0.065 mW/g** Maximum value of SAR (measured) = 0.120 mW/g



0 dB = 0.120 mW/g



Test Laboratory: QuieTek Lab GPRS1900 Mid Body-Back(2up) **DUT: mobile phone ; Type: X85** 

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: PCS1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.5$  mho/m;  $\epsilon r = 51.8$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS1900 Mid Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.274 mW/g

Configuration/GPRS1900 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 12.4 V/m; Power Drift = 0.192 dB

Peak SAR (extrapolated) = 0.483 W/kg

**SAR(1 g) = 0.293 mW/g; SAR(10 g) = 0.177 mW/g** Maximum value of SAR (measured) = 0.310 mW/g



0 dB = 0.310 mW/g



Test Laboratory: QuieTek Lab GPRS1900 Mid Body-Front(2up) **DUT: mobile phone ; Type: X85** 

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: PCS1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma$  = 1.5 mho/m;  $\epsilon$ r = 51.8;  $\rho$  = 1000 kg/m3;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

• Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS1900 Mid Body-Front/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.225 mW/g

Configuration/GPRS1900 Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 10.4 V/m; Power Drift = -0.106 dB

Peak SAR (extrapolated) = 0.587 W/kg

**SAR(1 g) = 0.234 mW/g; SAR(10 g) = 0.133 mW/g** Maximum value of SAR (measured) = 0.230 mW/g



0 dB = 0.230 mW/g



Test Laboratory: QuieTek Lab

GPRS1900 Mid Body-Back(2up) (With Headset)

DUT: mobile phone; Type: X85

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: PCS1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.5$  mho/m;  $\epsilon r = 51.8$ ;  $\rho = 1000$  kg/m3;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS1900 Mid Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.184 mW/g

Configuration/GPRS1900 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 9.77 V/m; Power Drift = -0.169 dB

Peak SAR (extrapolated) = 0.548 W/kg

**SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.122 mW/g** Maximum value of SAR (measured) = 0.210 mW/g



0 dB = 0.210 mW/g



Test Laboratory: QuieTek Lab 802.11g 2437MHz Body-Back

DUT: mobile phone; Type: X85

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1.0; Frequency: 2437

MHz; Medium parameters used: f = 2437 MHz;  $\sigma$  = 1.94 mho/m;  $\epsilon$ r = 50.9;  $\rho$  = 1000 kg/m3; Phantom

section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.702, 4.126, 4.265); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

• Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/802.11g Mid Body-Back/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.00755 mW/g

Configuration/802.11g Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 0.377 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 0.022 W/kg


SAR(1 g) = 0.012 mW/g; SAR(10 g) = 0.0091 mW/g Maximum value of SAR (measured) = 0.012 mW/g



0 dB = 0.012 mW/g



#### **Z-Axis Plot**





Test Laboratory: QuieTek Lab 802.11g 2437MHz Body-Front

DUT: mobile phone; Type: X85

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1.0; Frequency: 2437

MHz; Medium parameters used: f = 2437 MHz;  $\sigma$  = 1.94 mho/m;  $\epsilon$ r = 50.9;  $\rho$  = 1000 kg/m3; Phantom

section: Flat Section

Ambient temperature ( $^{\circ}$ ): 21.5, Liquid temperature ( $^{\circ}$ ): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.702, 4.126, 4.265); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/802.11g Mid Body-Front/Area Scan (6x9x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.005 mW/g

Configuration/802.11g Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 0.467 V/m; Power Drift = 0.187 dB

Peak SAR (extrapolated) = 0.019 W/kg

**SAR(1 g) = 0.004 mW/g; SAR(10 g) = 0.002 mW/g** Maximum value of SAR (measured) = 0.004 mW/g



0 dB = 0.004 mW/g



# **Appendix C. Test Setup Photographs & EUT Photographs**

# **Test Setup Photographs**




Left-Cheek Touch




Left-Tilt 15°





Right-Cheek Touch



Right-Tilt 15°





Body SAR Back 15mm



Body SAR Front 15mm





Body SAR Back 15mm with Headset



# Depth of the liquid in the phantom – Zoom in


Note: The position used in the measurements were according to IEEE 1528 - 2003





# **EUT Photographs**

## (1) EUT Photo



## (2) EUT Photo



## (3) EUT Photo

