
FCC Test Report

Report No.: AGC129110901F2A

FCC ID : ZOJKROME

PRODUCT DESIGNATION : GSM Mobile Phone

BRAND NAME : MOBO

TEST MODEL : KROME

CLIENT : MOBO USA CORP

DATE OF ISSUE : Sep. 27, 2011

STANDARD(S) : FCC Part 22H & 24E Rules

Attestation of Global Compliance Co., Ltd.

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

VERIFICATION OF COMPLIANCE


| | |
|----------------------|---|
| Applicant: | MOBO USA CORP 6000 NW 97 AV unit 14 Miami Florida 33178 USA |
| Manufacturer: | More Union International Co.,Ltd Floor 9 ,Honglong Building , 2057 Nanhai Dadao , Nanshan District Shenzhen China |
| Product Description: | GSM Mobile Phone |
| Brand Name: | MOBO |
| Model Name: | KROME |
| FCC ID: | ZOJKROME |
| Report Number: | AGC129110901F2A |
| Date of Test: | Sep.24, 2011 to Sep.25, 2011 |

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2003 and TIA/EIA 603. The sample tested as described in this report is in compliance with the FCC Rules Part 22H and 24E


The test results of this report relate only to the tested sample identified in this report.

Tested By :



Curoky Chen Sep.27, 2011

Reviewed By :



Forrest Lei Sep.27, 2011

Approved By:



Solger Zhang Sep.27, 2011

TABLE OF CONTENTS

| | |
|---|-----------|
| 1. GENERAL INFORMATION | 4 |
| 1.1 PRODUCT DESCRIPTION | 4 |
| 1.2 RELATED SUBMITTAL(S) / GRANT (S)..... | 4 |
| 1.3 TEST METHODOLOGY..... | 4 |
| 1.4 TEST FACILITY | 5 |
| 1.5 MEASUREMENT INSTRUMENTS | 5 |
| 1.6 SPECIAL ACCESSORIES | 5 |
| 1.7 EQUIPMENT MODIFICATIONS | 5 |
| 2. SYSTEM TEST CONFIGURATION..... | 6 |
| 2.1 EUT CONFIGURATION | 6 |
| 2.2 EUT EXERCISE..... | 6 |
| 2.3 GENERAL TECHNICAL REQUIREMENTS..... | 6 |
| 2.4 CONFIGURATION OF EUT SYSTEM..... | 6 |
| 3. SUMMARY OF TEST RESULTS..... | 7 |
| 4. DESCRIPTION OF TEST MODES | 7 |
| 5. OUTPUT POWER..... | 8 |
| 5.1 CONDUCTED OUTPUT POWER..... | 8 |
| 5.2 RADIATED OUTPUT POWER..... | 10 |
| 6. SPURIOUS EMISSION..... | 12 |
| 6.1 CONDUCTED SPURIOUS EMISSION..... | 12 |
| 6.2 RADIATED SPURIOUS EMISSION..... | 14 |
| 7. CONDUCTED EMISSION..... | 17 |
| 7.1 MEASUREMENT METHOD..... | 18 |
| 7.2 PROVISIONS APPLICABLE..... | 18 |

| | |
|---|-----------|
| 7.3 MEASUREMENT RESULT | 18 |
| 8. FREQUENCY STABILITY | 21 |
| 8.1 MEASUREMENT METHOD..... | 21 |
| 8.2 PROVISIONS APPLICABLE..... | 21 |
| 8.3 MEASUREMENT RESULT | 22 |
| 9. OCCUPIED BANDWIDTH | 24 |
| 9.1 MEASUREMENT METHOD..... | 24 |
| 9.2 PROVISIONS APPLICABLE..... | 24 |
| 9.3 MEASUREMENT RESULT | 24 |
| 10. EMISSION BANDWIDTH | 25 |
| 10.1 MEASUREMENT METHOD..... | 25 |
| 10.2 PROVISIONS APPLICABLE..... | 25 |
| 10.3 MEASUREMENT RESULT | 25 |
| 11. BAND EDGE..... | 26 |
| 11.1 MEASUREMENT METHOD..... | 26 |
| 11.2 PROVISIONS APPLICABLE..... | 26 |
| 11.3 MEASUREMENT RESULT | 26 |
| APPENDIX I TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION..... | 27 |
| APPENDIX II TEST PLOTS FOR OCCUPIED BANDWIDTH (99%) | 35 |
| APPENDIX III TEST PLOTS FOR BAND EDGES | 39 |
| APPENDIX IV PHOTOGRAPHS OF TEST SETUP | 42 |
| APPENDIX V PHOTOGRAPHS OF EUT | 44 |

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

| | |
|---|---|
| Product Designation: | GSM Mobile Phone |
| FCC ID: | ZOJKROME |
| Frequency Bands: | GSM 850: 824.2- 848.8MHz PCS 1900: 1850.2-1909.8MHz |
| Antenna: | Integrated Antenna |
| Power Supply: | DC3.7V by Built-in Li-ion Battery |
| Battery parameter: | 750MAH / 3.7V |
| Adapter Input: | AC100-240V, 50-60Hz |
| Adapter Output: | DC5V, 500mA |
| Output Power: | 31.25Bm Maximum ERP measured for GSM 850 for SIM1 33.96Bm Maximum Conducted Power for GSM 850 for SIM1 28.74Bm Maximum EIRP measured for GSM 1900 for SIM1 30.95Bm Maximum Conducted Power for GSM 1900 for SIM1 |
| Dual SIM Card | The result for SIM1 is the worst case which was only recorded |
| GPRS Class | 12 |
| Extreme Vol. Limits: | DC3.4 V to 4.2 V (Nominal DC3.7 V) |
| Extreme Temp. Tolerance | -10°C to +50°C |
| <p>** Note: The High Voltage 4.2V and Low Voltage 3.4V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.</p> <p>Other function have been performed according to verification procedure except for Bluetooth and MS function.</p> <p>SIM1 can not transmit with SIM2 simultaneously</p> | |

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: ZOJKROME** filing to comply with the FCC Part 22H and 24E requirements.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2003; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located at:

Attestation of Global Compliance Co., Ltd.

1F., No.2 Building, Huafeng No.1 Technical Industrial Park, Sanwei, Xixiang, Baoan District, Shenzhen

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.

FCC register No.: 259865

1.5 MEASUREMENT INSTRUMENTS

| NAME OF EQUIPMENT | MANUFACTURER | MODEL | SERIAL NUMBER | NEXT CAL. DATE |
|----------------------|-------------------|-------------|---------------|----------------|
| SPECTRUM ANALYZER | AGILENT | E4440A | US44300399 | 2012.6.26 |
| TEST RECEIVER | R&S | ESCI | A0304218 | 2012.6.26 |
| COMMUNICATION TESTER | AGILENT | 8960 | 3104A03367 | 2012.6.26 |
| COMMUNICATION TESTER | R&S | CMU200 | A0304247 | 2012.6.26 |
| TEST RECEIVER | R&S | FCKL1528 | A0304230 | 2012.6.26 |
| LISN | SCHWARZBECK | NSLK8127 | A0304233 | 2012.6.26 |
| CLIMATE CHAMBER | ALBATROSS | -- | -- | 2012.6.26 |
| Loop Antenna | Daze | ZN30900N | SEL0097 | 2012.6.26 |
| Biological Antenna | A.H. Systems Inc. | SAS-521-4 | N/A | 2012.6.26 |
| Horn Antenna | EM | EM-AH-10180 | N/A | 2012.6.26 |

1.6 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

1.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

| Item Number | Item Description | | FCC Rules |
|-------------|--------------------------|----------------------------|--------------------------|
| 1 | Output Power | Conducted | 22.913(a) / 24.232 (b) |
| | | Radiated | |
| 2 | Spurious Emission | Conducted Emission | 2.1051 / 22.917 / 24.238 |
| | | Radiated Spurious Emission | |
| 3 | Mains Conducted Emission | | 15.107 / 15.207 |
| 4 | Frequency Stability | | 2.1055 /24.235 |
| 5 | Occupied Bandwidth | | 2.1049 (h)(i) |
| 6 | Emission Bandwidth | | 22.917(b) / 24.238 (b) |
| 7 | Band Edge | | 22.917(b) / 24.238 (b) |

2.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System



Table 2-1 Equipment Used in EUT System

| Item | Equipment | Model No. | ID or Specification | Note |
|------|------------------|-----------|---------------------|-----------|
| 1 | GSM Mobile Phone | KROME | FCC ID: ZOJKROME | EUT |
| 2 | ADAPTER | N/A | 5V / 500mA | Accessory |
| 3 | BATTERY | N/A | 750 mAh /3.7V | Accessory |
| 4 | EARPHONE | N/A | N/A | Accessory |
| 5 | USB Cable | N/A | N/A | Accessory |

Note: All the accessories have been used during the test, the earphone and adapter could not connect to mobile phone at the same time. the following "EUT" in setup diagram means EUT system.

3. SUMMARY OF TEST RESULTS

| Item Number | Item Description | | FCC Rules | Result |
|-------------|--------------------------|-----------------------------|--------------------------|--------|
| 1 | Output Power | Conducted Output Power | 22.913(a) / 24.232 (b) | Pass |
| | | Radiated Output Power | | |
| 2 | Spurious Emission | Conducted Spurious Emission | 2.1051 / 22.917 / 24.238 | Pass |
| | | Radiated Spurious Emission | | |
| 3 | Mains Conducted Emission | | 15.107 / 15.207 | Pass |
| 4 | Frequency Stability | | 2.1055 / 24.235 | Pass |
| 5 | Occupied Bandwidth | | 2.1049 (h)(i) | Pass |
| 6 | Emission Bandwidth | | 22.917(b) / 24.238 (b) | Pass |
| 7 | Band Edge | | 22.917(b) / 24.238 (b) | Pass |

4. DESCRIPTION OF TEST MODES

During the testing, the EUT (GSM Dual Band GPRS Digital Mobile Phone) was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.

Note: GSM and GPRS modes have been tested during the test. the worst condition (GSM) be recorded in the test report if no other modes test data.

5. OUTPUT POWER

5.1 Conducted Output Power

5.1.1 MEASUREMENT METHOD

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes(GSM, GPRS,) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

5.1.2 PROVISIONS APPLICABLE

| Conducted Output Power Limits for GSM 850 MHZ | | | |
|---|------------|--------------------|---------------|
| Mode | Power Step | Nominal Peak Power | Tolerance(dB) |
| GSM | 5 | 33 dBm (2W) | ±1 |
| GPRS | 3 | 33 dBm (2W) | ±1 |

| Conducted Output Power Limits for PCS 1900 MHZ | | | |
|--|------------|--------------------|---------------|
| Mode | Power Step | Nominal Peak Power | Tolerance(dB) |
| GSM | 0 | 30 dBm (1W) | ±1 |
| GPRS | 3 | 30 dBm (1W) | ±1 |

5.1.3 MEASUREMENT RESULT

| Mode | Frequency | Reference Power (dBm) | Measured Result | | Conclusion |
|--------------|-----------|-----------------------|------------------|----------------|------------|
| | | | Peak Power (dBm) | Tolerance (dB) | |
| GSM(SIM1) | 824.2 | 33 | 33.96 | 0.96 | Pass |
| | 836.6 | 33 | 33.89 | 0.89 | Pass |
| | 848.8 | 33 | 33.51 | 0.51 | Pass |
| GPRS 1 slot | 824.2 | 33 | 33.53 | 0.53 | Pass |
| | 836.6 | 33 | 33.64 | 0.64 | Pass |
| | 848.8 | 33 | 33.40 | 0.40 | Pass |
| GPRS 2 slots | 824.2 | 30 | 29.58 | -0.42 | Pass |
| | 836.6 | 30 | 29.84 | -0.16 | Pass |
| | 848.8 | 30 | 29.33 | -0.67 | Pass |
| GPRS 3 slots | 824.2 | 28.22 | 27.85 | -0.37 | Pass |
| | 836.6 | 28.22 | 28.17 | -0.05 | Pass |
| | 848.8 | 28.22 | 27.71 | -0.51 | Pass |
| GPRS 4 slots | 824.2 | 27 | 26.55 | -0.45 | Pass |
| | 836.6 | 27 | 26.84 | -0.16 | Pass |
| | 848.8 | 27 | 26.39 | -0.61 | Pass |

| | | | | | |
|-----------|-------|----|-------|------|------|
| GSM(SIM2) | 824.2 | 33 | 33.60 | 0.60 | Pass |
| | 836.6 | 33 | 33.56 | 0.56 | Pass |
| | 848.8 | 33 | 33.17 | 0.17 | Pass |

| Conducted Output Power for PCS 1900 MHZ | | | | | |
|---|-----------|-----------------------|------------------|----------------|------------|
| Mode | Frequency | Reference Power (dBm) | Result | | Conclusion |
| | | | Peak Power (dBm) | Tolerance (dB) | |
| GSM(SIM1) | 1850.2 | 30 | 30.89 | 0.89 | Pass |
| | 1880.0 | 30 | 30.95 | 0.95 | Pass |
| | 1909.8 | 30 | 30.60 | 0.60 | Pass |
| GPRS 1slot | 1850.2 | 30 | 30.69 | 0.69 | Pass |
| | 1880.0 | 30 | 30.83 | 0.83 | Pass |
| | 1909.8 | 30 | 30.62 | 0.62 | Pass |
| GPRS 2 slots | 1850.2 | 27 | 26.79 | -0.21 | Pass |
| | 1880.0 | 27 | 26.88 | -0.12 | Pass |
| | 1909.8 | 27 | 26.61 | -0.39 | Pass |
| GPRS 3 slots | 1850.2 | 25.22 | 24.99 | -0.23 | Pass |
| | 1880.0 | 25.22 | 25.20 | -0.02 | Pass |
| | 1909.8 | 25.22 | 24.81 | -0.41 | Pass |
| GPRS 4 slots | 1850.2 | 24 | 23.60 | -0.4 | Pass |
| | 1880.0 | 24 | 23.95 | -0.05 | Pass |
| | 1909.8 | 24 | 23.42 | -0.58 | Pass |
| GSM(SIM2) | 1850.2 | 30 | 30.45 | 0.45 | Pass |
| | 1880.0 | 30 | 30.62 | 0.62 | Pass |
| | 1909.8 | 30 | 30.28 | 0.28 | Pass |

5.2 Radiated Output Power

5.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were applied.

- 1 In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as $AR_{pl}=P_{in} + 2.15 - P_r$. The AR_{pl} is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: $Power=PM_{ea}+AR_{pl}$
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- 6 Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step 1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi..}$

5.2.2 PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

| Radiated Power Limits for GSM 850 MHZ (ERP) | | |
|---|------------|--------------------|
| Mode | Power Step | Nominal Peak Power |
| GSM | 5 | <=38.45 dBm (7W) |
| GPRS | 3 | <=38.45 dBm (7W) |

| Radiated Power Limits for PCS 1900 MHZ (E.I.R.P.) | | |
|---|------------|--------------------|
| Mode | Power Step | Nominal Peak Power |
| GSM | 0 | <=33 dBm (2W) |
| GPRS | 3 | <=33 dBm (2W) |

5.2.3 MEASUREMENT RESULT

| Radiated Power (ERP) for GSM 850 MHZ | | | | | |
|---|-----------|------------|-------------------------|-------------------------------|------------|
| Mode | Frequency | Power Step | Result | | Conclusion |
| | | | Max. Peak ERP (dBm) | Polarization Of Max. ERP | |
| GSM | 824.2 | 5 | 31.25 | Horizontal | Pass |
| | 836.6 | 5 | 31.21 | Horizontal | Pass |
| | 848.8 | 5 | 31.19 | Horizontal | Pass |
| GPRS 1 slot | 824.2 | 3 | 30.97 | Horizontal | Pass |
| | 836.6 | 3 | 31.16 | Horizontal | Pass |
| | 848.8 | 3 | 30.95 | Horizontal | Pass |
| GPRS 2 slots | 824.2 | 3 | Less than 27 dBm | Horizontal | Pass |
| | 836.6 | 3 | | Horizontal | Pass |
| | 848.8 | 3 | | Horizontal | Pass |
| GPRS 3 slots | 824.2 | 2 | | Horizontal | Pass |
| | 836.6 | 2 | | Horizontal | Pass |
| | 848.8 | 2 | | Horizontal | Pass |
| GPRS 4 slots | 824.2 | 2 | | Horizontal | Pass |
| | 836.6 | 2 | | Horizontal | Pass |
| | 848.8 | 2 | | Horizontal | Pass |
| Radiated Power (E.I.R.P) for PCS 1900 MHZ | | | | | |
| Mode | Frequency | Power Step | Result | | Conclusion |
| | | | Max. Peak E.I.R.P.(dBm) | Polarization Of Max. E.I.R.P. | |
| GSM | 1850.2 | 0 | 28.74 | Horizontal | Pass |
| | 1880.0 | 0 | 28.64 | Horizontal | Pass |
| | 1909.8 | 0 | 28.67 | Horizontal | Pass |
| GPRS 1slot | 1850.2 | 3 | 28.66 | Horizontal | Pass |
| | 1880.0 | 3 | 28.63 | Horizontal | Pass |
| | 1909.8 | 3 | 28.67 | Horizontal | Pass |
| GPRS 2 slots | 1850.2 | 3 | Less than 27 dBm | Horizontal | Pass |
| | 1880.0 | 3 | | Horizontal | Pass |
| | 1909.8 | 3 | | Horizontal | Pass |
| GPRS 3 slots | 1850.2 | 2 | | Horizontal | Pass |
| | 1880.0 | 2 | | Horizontal | Pass |
| | 1909.8 | 2 | | Horizontal | Pass |
| GPRS 4 slots | 1850.2 | 2 | | Horizontal | Pass |
| | 1880.0 | 2 | | Horizontal | Pass |
| | 1909.8 | 2 | | Horizontal | Pass |

6. SPURIOUS EMISSION

6.1 CONDUCTED SPURIOUS EMISSION

6.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.

2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

| Typical Channels for testing of GSM 850 MHz | |
|---|-----------------|
| Channel | Frequency (MHz) |
| 128 | 824.2 |
| 190 | 836.6 |
| 251 | 848.8 |

| Typical Channels for testing of PCS 1900 MHz | |
|--|-----------------|
| Channel | Frequency (MHz) |
| 512 | 1850.2 |
| 661 | 1880.0 |
| 810 | 1909.8 |

6.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

6.1.3 MEASUREMENT RESULT

| Conducted Spurious Emission for GSM 850 MHz | | | | | | |
|---|---------------------------|----------------|---------------------------|----------------|---------------------------|----------------|
| Harmonic | Tx ch. 128 Freq. (MHz) | Level (dBm) | Tx ch. 190 Freq. (MHz) | Level (dBm) | Tx ch. Freq. (MHz) 251 | Level (dBm) |
| 2 | 1648.4 | B.I.N.F | 1673.2 | B.I.N.F | 1697.6 | B.I.N.F |
| 3 | 2472.6 | B.I.N.F | 2509.8 | B.I.N.F | 2546.4 | B.I.N.F |
| 4 | 3296.8 | B.I.N.F | 3346.4 | B.I.N.F | 3395.2 | B.I.N.F |
| 5 | 4121 | B.I.N.F | 4183 | B.I.N.F | 4244 | B.I.N.F |
| 6 | 4945.2 | B.I.N.F | 5019.6 | B.I.N.F | 5092.8 | B.I.N.F |
| 7 | 5769.4 | B.I.N.F | 5856.2 | B.I.N.F | 5941.6 | B.I.N.F |
| 8 | 6593.6 | B.I.N.F | 6692.8 | B.I.N.F | 6790.4 | B.I.N.F |
| 9 | 7417.8 | B.I.N.F | 7529.4 | B.I.N.F | 7639.2 | B.I.N.F |
| 10 | 8242 | B.I.N.F | 8366 | B.I.N.F | 8488 | B.I.N.F |

● B.I.N.F: Below Instruments Noise floor

| Conducted Spurious Emission for PCS 1900 MHz | | | | | | |
|--|---------------------------|----------------|---------------------------|----------------|---------------------------|----------------|
| Harmonic | Tx ch. 512 Freq. (MHz) | Level (dBm) | Tx ch. 661 Freq. (MHz) | Level (dBm) | Tx ch. 810 Freq. (MHz) | Level (dBm) |
| 2 | 3700.4 | B.I.N.F | 3760 | B.I.N.F | 3819.6 | B.I.N.F |
| 3 | 5550.6 | B.I.N.F | 5640 | B.I.N.F | 5729.4 | B.I.N.F |
| 4 | 7400.8 | B.I.N.F | 7520 | B.I.N.F | 7639.2 | B.I.N.F |
| 5 | 9251.0 | B.I.N.F | 9400 | B.I.N.F | 9549.0 | B.I.N.F |
| 6 | 11101.2 | B.I.N.F | 11280 | B.I.N.F | 11458.8 | B.I.N.F |
| 7 | 12951.4 | B.I.N.F | 13160 | B.I.N.F | 13368.6 | B.I.N.F |
| 8 | 14801.6 | B.I.N.F | 15040 | B.I.N.F | 15278.4 | B.I.N.F |
| 9 | 16651.8 | B.I.N.F | 16920 | B.I.N.F | 17188.2 | B.I.N.F |
| 10 | 18502.0 | B.I.N.F | 18800 | B.I.N.F | 19098.0 | B.I.N.F |

● B.I.N.F: Below Instruments Noise floor

Note: Below 30MHZ no Spurious found and The GSM modes is the worst condition.


6.2 Radiated Spurious Emission

6.2.1 MEASUREMENT METHOD


The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GSM, GPRS) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

The procedure of radiated spurious emissions is as follows:

- Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, $RSE = Rx(\text{dBuV}) + CL(\text{dB}) + SA(\text{dB}) + Gain(\text{dBi}) - 107$ (dBuV to dBm) The SA is calibrated using following setup.



- EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{RPL} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: $\text{Power} = P_{\text{Mea}} + A_{RPL}$

6.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a IMOBOOnsee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43 + 10\log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

6.2.3 MEASUREMENT RESULT

| The Worst Test Results for Channel 128 / 824.2 MHz | | | | | |
|--|------------|------------------------|------------------------|------------|------------|
| Frequency(MHz) | Power(dBm) | A _{Rpl} (dBm) | P _{Mea} (dBm) | Limit(dBm) | Polarity |
| 1648.00 | -36.83 | -4.08 | -40.91 | -13.00 | Horizontal |
| 1967.72 | -36.68 | -3.09 | -39.77 | -13.00 | Vertical |
| 2717.49 | -36.79 | 2.46 | -34.33 | -13.00 | Horizontal |
| 9331.27 | -39.16 | 2.7 | -36.46 | -13.00 | Horizontal |

| The Worst Test Results for Channel 190/836.6 MHz | | | | | |
|--|------------|------------------------|------------------------|------------|------------|
| Frequency(MHz) | Power(dBm) | A _{Rpl} (dBm) | P _{Mea} (dBm) | Limit(dBm) | Polarity |
| 1673.00 | -42.10 | -3.14 | -45.24 | -13.00 | Horizontal |
| 2063.36 | -38.64 | -0.71 | -39.35 | -13.00 | Vertical |
| 9276.02 | -40.30 | 3.05 | -37.25 | -13.00 | Vertical |

| The Worst Test Results for Channel 251/848.8 MHz | | | | | |
|--|------------|------------------------|------------------------|------------|------------|
| Frequency(MHz) | Power(dBm) | A _{Rpl} (dBm) | P _{Mea} (dBm) | Limit(dBm) | Polarity |
| 1698.00 | -39.47 | -2.73 | -42.20 | -13.00 | Horizontal |
| 2041.92 | -40.97 | -3.73 | -44.71 | -13.00 | Vertical |
| 2394.54 | -46.04 | -1.94 | -47.98 | -13.00 | Vertical |
| 9383.91 | -38.44 | 8.56 | -29.88 | -13.00 | Horizontal |

| The Worst Test Results for Channel 512/1850.2 MHz | | | | | |
|---|------------|------------------------|------------------------|------------|------------|
| Frequency(MHz) | Power(dBm) | A _{Rpl} (dBm) | P _{Mea} (dBm) | Limit(dBm) | Polarity |
| 1999.00 | -41.48 | 9.27 | -32.20 | -13.00 | Horizontal |
| 3881.56 | -38.27 | 7.39 | -30.88 | -13.00 | Horizontal |
| 13121.91 | -37.89 | 12.31 | -25.57 | -13.00 | Vertical |
| 18125.57 | -41.63 | 17.85 | -23.77 | -13.00 | Vertical |

| The Worst Test Results for Channel 661/1880.0 MHz | | | | | |
|--|------------|------------------------|------------------------|-------------|------------|
| Frequency(MHz) | Power(dBm) | A _{Rpl} (dBm) | P _{Mea} (dBm) | Limit (dBm) | Polarity |
| 2000.50 | -43.88 | 8.78 | -35.10 | -13.00 | Vertical |
| 9538.06 | -38.36 | 11.01 | -27.35 | -13.00 | Vertical |
| 13328.57 | -37.05 | 14.56 | -22.49 | -13.00 | Horizontal |
| 15224.78 | -39.87 | 14.61 | -25.26 | -13.00 | Vertical |
| 18131.40 | -44.04 | 20.31 | -23.73 | -13.00 | Horizontal |

| The Worst Test Results for Channel 810/1909.8 MHz | | | | | |
|--|------------|------------------------|------------------------|-------------|------------|
| Frequency(MHz) | Power(dBm) | A _{Rpl} (dBm) | P _{Mea} (dBm) | Limit (dBm) | Polarity |
| 2000.00 | -36.48 | 9.90 | -26.58 | -13.00 | Vertical |
| 9660.39 | -32.95 | 10.33 | -22.62 | -13.00 | Horizontal |
| 13663.75 | -41.77 | 11.31 | -30.46 | -13.00 | Horizontal |
| 15553.66 | -37.45 | 15.62 | -21.83 | -13.00 | Vertical |
| 18156.75 | -38.37 | 19.30 | -19.07 | -13.00 | Horizontal |

Note: Below 30MHZ no Spurious found and The GSM modes is the worst condition.

7. MAINS CONDUCTED EMISSION

7.1 MEASUREMENT METHOD

The measurement procedure specified in ANSI C63.4-2003 was used for testing. Conducted Emission was measured with travel charger.


7.2 PROVISIONS APPLICABLE

| Frequency of Emission (MHz) | Conducted Limit(dBuV) | |
|-----------------------------|-----------------------|------------|
| | Quasi-Peak | Average |
| 0.15 – 0.5 | 66 to 56 * | 56 to 46 * |
| 0.5 – 5 | 56 | 46 |
| 5 – 30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

7.3 MEASUREMENT RESULT


LINE CONDUCTED EMISSION - L



Site: Conduction Phase: *L1* Temperature: 26
 Limit: FCC Class B Conduction(QP) Power: Humidity: 60 %
 EUT: GSM Mobile Phone
 M/N: KROME
 Mode: CALL
 Note:

| No. | Freq. (MHz) | Reading Level (dBuV) | | | Correct Factor | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
|-----|----------------|-------------------------|----|-------|-------------------|-----------------------|------|-------|-----------------|-------|----------------|--------|-----|---------|
| | | Peak | QP | AVG | | dB | Peak | QP | AVG | QP | AVG | QP | AVG | |
| 1 | 0.1965 | 45.87 | | 27.45 | 10.21 | 56.08 | | 37.66 | 63.75 | 53.75 | -7.67 | -16.09 | P | |
| 2 | 0.2620 | 44.02 | | 22.04 | 10.27 | 54.29 | | 32.31 | 61.36 | 51.36 | -7.07 | -19.05 | P | |
| 3 | 0.3940 | 39.13 | | 13.29 | 10.33 | 49.46 | | 23.62 | 57.98 | 47.98 | -8.52 | -24.36 | P | |
| 4 | 2.8220 | 38.33 | | 14.51 | 10.51 | 48.84 | | 25.02 | 56.00 | 46.00 | -7.16 | -20.98 | P | |
| 5 | 5.8459 | 37.83 | | 23.75 | 10.27 | 48.10 | | 34.02 | 60.00 | 50.00 | -11.90 | -15.98 | P | |
| 6 | 9.8498 | 42.89 | | 14.76 | 10.18 | 53.07 | | 24.94 | 60.00 | 50.00 | -6.93 | -25.06 | P | |

LINE CONDUCTED EMISSION - N



| No. | Freq. (MHz) | Reading_Level (dBuV) | | | Correct Factor | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
|-----|----------------|-------------------------|----|-------|-------------------|-----------------------|----|-------|-----------------|-------|----------------|--------|-----|---------|
| | | Peak | QP | AVG | | Peak | QP | Avg | QP | Avg | QP | Avg | | |
| 1 | 0.1980 | 44.34 | | 28.17 | 10.21 | 54.55 | | 38.38 | 63.69 | 53.69 | -9.14 | -15.31 | P | |
| 2 | 0.3301 | 41.48 | | 15.47 | 10.30 | 51.78 | | 25.77 | 59.45 | 49.45 | -7.67 | -23.68 | P | |
| 3 | 2.8340 | 37.80 | | 18.90 | 10.51 | 48.31 | | 29.41 | 56.00 | 46.00 | -7.69 | -16.59 | P | |
| 4 | 5.9298 | 42.08 | | 21.25 | 10.28 | 52.36 | | 31.53 | 60.00 | 50.00 | -7.64 | -18.47 | P | |
| 5 | 7.8418 | 42.73 | | 19.79 | 10.34 | 53.07 | | 30.13 | 60.00 | 50.00 | -6.93 | -19.87 | P | |
| 6 | 21.8216 | 35.42 | | 14.44 | 10.12 | 45.54 | | 24.56 | 60.00 | 50.00 | -14.46 | -25.44 | P | |

Note: The GSM850 modes is the worst condition.

8. FREQUENCY STABILITY

8.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 , Measure the carrier frequency at room temperature.
- 2 , Subject the EUT to overnight soak at -10°C.
- 3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 , channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 , Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6 , Subject the EUT to overnight soak at +50°C.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 , Repeat the above measurements at 10°C increments from +50°C to -10°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 , At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

8.2 PROVISIONS APPLICABLE

8.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.4VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

8.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

8.3 MEASUREMENT RESULT

| Frequency Error Against Voltage for GSM 850 MHz | | |
|---|---------------------|----------------------|
| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
| 3.4 | 19 | 0.023 |
| 3.7 | 16 | 0.019 |
| 4.2 | 15 | 0.018 |

| Frequency Error Against Temperature for GSM 850 MHz | | |
|---|---------------------|----------------------|
| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
| -10 | 35 | 0.042 |
| 0 | 31 | 0.037 |
| 10 | 26 | 0.031 |
| 20 | 20 | 0.024 |
| 30 | 26 | 0.031 |
| 40 | 29 | 0.035 |
| 50 | 40 | 0.048 |

Note: The EUT doesn't work below -10°C

| Frequency Error Against Voltage for PCS 1900 MHz | | |
|---|---------------------|----------------------|
| Voltage(V) | Frequency error(Hz) | Frequency error(ppm) |
| 3.4 | 30 | 0.016 |
| 3.7 | 29 | 0.015 |
| 4.2 | 34 | 0.018 |

| Frequency Error Against Temperature for PCS 1900 MHz | | |
|---|---------------------|----------------------|
| temperature(°C) | Frequency error(Hz) | Frequency error(ppm) |
| -10 | 43 | 0.023 |
| 0 | 37 | 0.020 |
| 10 | 32 | 0.017 |
| 20 | 30 | 0.016 |
| 30 | 31 | 0.016 |
| 40 | 37 | 0.020 |
| 50 | 43 | 0.023 |

Note: The EUT doesn't work below -10°C

9. OCCUPIED BANDWIDTH

9.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

9.2 PROVISIONS APPLICABLE

The occupied bandwidth (99%) shall not exceed 300 KHz.

9.3 MEASUREMENT RESULT

| Occupied Bandwidth (99%) for GSM 850 MHz | | |
|--|----------------|--------------------------------|
| Mode | Frequency(MHz) | Occupied Bandwidth (99%)(kHz) |
| Low Channel | 824.2 | 248.07 |
| Middle Channel | 836.6 | 247.33 |
| High Channel | 848.8 | 246.55 |

| Occupied Bandwidth (99%) for PCS 1900 MHz | | |
|---|----------------|--------------------------------|
| Mode | Frequency(MHz) | Occupied Bandwidth (99%)(kHz) |
| Low Channel | 1850.2 | 248.24 |
| Middle Channel | 1880.0 | 246.11 |
| High Channel | 1909.8 | 245.84 |

10. EMISSION BANDWIDTH

10.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

10.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

10.3 MEASUREMENT RESULT

| Emission Bandwidth (-26dBc) for GSM 850 MHz | | |
|---|----------------|-----------------------------------|
| Mode | Frequency(MHz) | Emission Bandwidth (-26dBc)(kHz) |
| Low Channel | 824.2 | 313.37 |
| Middle Channel | 836.6 | 310.84 |
| High Channel | 848.8 | 311.04 |

| Emission Bandwidth (-26dBc) for PCS 1900 MHz | | |
|--|----------------|-----------------------------------|
| Mode | Frequency(MHz) | Emission Bandwidth (-26dBc)(kHz) |
| Low Channel | 1850.2 | 312.69 |
| Middle Channel | 1880.0 | 311.11 |
| High Channel | 1909.8 | 316.43 |

11. BAND EDGE

11.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

11.2 PROVISIONS APPLICABLE

as Specified in FCC rules of 22.917(b) and 24.238(b)


11.3 MEASUREMENT RESULT

Please refers to Appendix III for compliance test plots for band edges


APPENDIX I

TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION


CONDUCTED EMISSION IN GSM BAND
Conducted Emission Transmitting Mode CH 128 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 128 1GHz – 9GHz




Conducted Emission Transmitting Mode CH 190 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 190 1GHz – 9GHz




Conducted Emission Transmitting Mode CH 251 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 251 1GHz – 9GHz




Conducted Emission Idle Mode 30MHz – 1GHz




Conducted Emission Idle Mode 1GHz – 9GHz




CONDUCTED EMISSION IN PCS BAND
Conducted Emission Transmitting Mode CH 512 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 512 1GHz – 20GHz




Conducted Emission Transmitting Mode CH 661 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 661 1GHz – 20GHz



Conducted Emission Transmitting Mode CH 810 30MHz – 1GHz



Conducted Emission Transmitting Mode CH 810 1GHz – 20GHz



APPENDIX II

TEST PLOTS FOR OCCUPIED BANDWIDTH (99%) EMISSION BANDWIDTH (-26dBc)

Occupied Bandwidth (99%) GSM 850 BAND CH 128



Occupied Bandwidth (99%) GSM 850 BAND CH 190



Occupied Bandwidth (99%) GSM 850 BAND CH 251




Occupied Bandwidth (99%) PCS 1900 BAND CH 512



Occupied Bandwidth (99%) PCS 1900 BAND CH 661




Occupied Bandwidth (99%) PCS 1900 BAND CH 810




APPENDIX III

TEST PLOTS FOR BAND EDGES


Low Band Edge GSM 850 BAND CH 128




High Band Edge GSM 850 BAND CH 251



Low Band Edge PCS 1900 BAND CH 512



High Band Edge PCS 1900 BAND CH 810




APPENDIX IV

PHOTOGRAPHS OF TEST SETUP

CONDUCTED EMISSION



RADIATED SPURIOUS EMISSION



APPENDIX V

PHOTOGRAPHS OF EUT

TOP VIEW OF SAMPLE



BOTTOM VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE



FRONT VIEW OF SAMPLE



BACK VEIW OF SAMPLE



ALL VIEW OF SAMPLE




OPEN VIEW OF SAMPLE-1




OPEN VIEW OF SAMPLE-2




OPEN VIEW OF SAMPLE -3



INTERNAL VIEW OF SAMPLE – 1



INTERNAL VIEW OF SAMPLE – 2



----END OF REPORT----