

# **FCC Test Report**

Report No.: RF180314C22-1

FCC ID: ZOQ-FEU

Test Model: UOC-FEU

Received Date: Mar. 14, 2018

Test Date: Apr. 10, 2018 ~ Apr. 26, 2018

Issued Date: May 11, 2018

**Applicant:** Verizon Connect

Address: 2002 Summit Blvd, Suite 1800, Atlanta Georgia 30319, United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C)

Test Location: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, Taiwan, R.O.C.

FCC Registration /

788550 / TW0003

**Designation Number:** 





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. Afailure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: RF180314C22-1 Page No. 1 / 36 Report Format Version: 6.1.1



# **Table of Contents**

Re	Release Control Record4				
1	Cer	tificate of Conformity	5		
2	Sun	nmary of Test Results	6		
	2.1	Measurement Uncertainty	6		
		Modification Record			
3	Gen	neral Information	7		
	2 1	General Description of EUT	7		
		Description of Test Modes			
	0.2	3.2.1 Test Mode Applicability and Tested Channel Detail			
	3.3	Duty Cycle of Test Signal			
	3.4	Description of Support Units			
	۰.	3.4.1 Configuration of System under Test			
		General Description of Applied Standards			
4		t Types and Results			
	4.1	Radiated Emission and Bandedge Measurement			
		4.1.1 Limits of Radiated Emission and Bandedge Measurement			
		4.1.2 Test Instruments			
		4.1.4 Deviation from Test Standard			
		4.1.5 Test Set Up			
		4.1.6 EUT Operating Conditions			
		4.1.7 Test Results			
	4.2	Conducted Emission Measurement			
		4.2.1 Limits of Conducted Emission Measurement			
		4.2.2 Test Instruments			
		4.2.3 Test Procedures			
		4.2.5 TEST SETUP			
		4.2.6 EUT Operating Conditions			
		4.2.7 Test Results			
	4.3	6 dB Bandwidth Measurement	25		
		4.3.1 Limits of 6 dB Bandwidth Measurement			
		4.3.2 Test Setup			
		4.3.3 Test Instruments	_		
		4.3.4 Test Procedure			
		4.3.6 EUT Operating Conditions			
		4.3.7 Test Result			
	4.4	Occupied Bandwidth Measurement			
		4.4.1 Test Setup	27		
		4.4.2 Test Instruments			
		4.4.3 Test Procedure			
		4.4.4 Deviation From Test Standard			
		4.4.5 EUT Operating Conditions			
	45	Conducted Output Power Measurement			
	٠.٠	4.5.1 Limits of Conducted Output Power Measurement			
		4.5.2 Test Setup			
		4.5.3 Test Instruments			
		4.5.4 Test Procedures			
		4.5.5 Deviation from Test Standard			
		4.5.6 EUT Operating Conditions			
		4.5.7 Test Results	29		



4.6 Power S	spectral Density Measurement	30
	mits of Power Spectral Density Measurement	
	est Setup	
	est Instruments	
	est Procedure	
	eviation from Test Standard	
	JT Operating Condition	
	est Results	
	ed Out of Band Emission Measurement	
	mits of Conducted Out of Band Emission Measurement	
4.7.2 Te	est Setup	32
	est Instruments	
	est Procedure	
	eviation from Test Standard	
	JT Operating Condition	
	est Results	
5 Pictures of T	est Arrangements	35
Appendix - Info	ormation on the Testing Laboratories	36



# **Release Control Record**

Issue No.	Description	Date Issued
RF180314C22-1	Original Release	May 11, 2018

Report No.: RF180314C22-1 Page No. 4 / 36 Report Format Version: 6.1.1



# 1 Certificate of Conformity

Product: FEU

**Brand:** Verizon Telematics

Test Model: UOC-FEU

Sample Status: Production Unit

Applicant: Verizon Connect

**Test Date:** Apr. 10, 2018 ~ Apr. 26, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: , Date: May 11, 2018

Rona Chen / Specialist

**Approved by :** , **Date:** May 11, 2018

Dylan Chiou / Project Engineer

Report No.: RF180314C22-1 Page No. 5 / 36 Report Format Version: 6.1.1



# 2 Summary of Test Results

	47 CFR FCC Part 15, Subpart C (Section 15.247)						
FCC Clause	Test Item	Result	Remarks				
15.207 AC Power Conducted Emission		Pass	Meet the requirement of limit.  Minimum passing margin is -19.51 dB at 17.69417 MHz.				
15.205 & 209 Radiated Emissions		Pass	Meet the requirement of limit.  Minimum passing margin is -2.7 dB at 7440.00 MHz.				
15.247(d)	Band Edge Measurement	Pass	Meet the requirement of limit.				
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.				
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.				
	Occupied Bandwidth Measurement	Pass	Reference only				
15.247(b)	Conducted power	Pass	Meet the requirement of limit.				
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.				
15.203	Antenna Requirement	Pass	No antenna connector is used.				

# 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	3.63 dB
Radiated Emissions up to 1 GHZ	200 MHz ~1000 MHz	3.64 dB
Padiated Emissions above 1 CHz	1 GHz ~ 18 GHz	2.29 dB
Radiated Emissions above 1 GHz	18 GHz ~ 40 GHz	2.29 dB

# 2.2 Modification Record

There were no modifications required for compliance.

Report No.: RF180314C22-1 Page No. 6 / 36 Report Format Version: 6.1.1



# 3 General Information

# 3.1 General Description of EUT

Product	FEU
Brand	Verizon Telematics
Test Model	UOC-FEU
Status of EUT	Production Unit
Power Supply Rating	12 Vdc (DC Power Supply)
Modulation Type	GFSK
Transfer Rate	Up to 1 Mbps
Operating Frequency	2402 ~ 2480 MHz
Number of Channel	40
Output Power	0.873 mW
Antenna Type	Internal antenna with 2.8 dBi gain
Antenna Connector	NA
Accessory Device	N/A
Data Cable Supplied	N/A

# Note:

1. The EUT contains two SKU which are listed as below.

SKU	Brand	Model	Difference			
1			Super Cap Sku (without Battery)			
2	Verizon Telematics	UOC-FEU	Battery (without super cap)			
* The difference of above SKU has no effect on RF test. Therefore, only SKU 1 was chosen as a representative for the final test.						

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

Report No.: RF180314C22-1 Page No. 7 / 36 Report Format Version: 6.1.1



# 3.2 Description of Test Modes

40 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure		Applica	able To	Decembrican	
Mode	RE≥1G	RE<1G	PLC	APCM	Description
-	<b>V</b>	<b>V</b>	<b>V</b>	√	SKU 1

Where **RE≥1G:** Radiated Emission above 1 GHz

RE<1G: Radiated Emission below 1 GHz

PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Y-plane.

### Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

### Radiated Emission Test (Below 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0	GFSK	1

#### **Power Line Conducted Emission Test:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
 Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0	GFSK	1

#### **Antenna Port Conducted Measurement:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)	
-	0 to 39	0, 19, 39	GFSK	1	


Report No.: RF180314C22-1 Page No. 9 / 36 Report Format Version: 6.1.1




# **Test Condition:**

Applicable To	Environmental Conditions	Input Power	Tested by	
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	James Yang	
RE<1G	<b>RE&lt;1G</b> 25 deg. C, 65 % RH		Noah Chang	
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Adair Peng	
APCM	25 deg. C, 65 % RH	12 Vdc	Wayne Lin	

# 3.3 Duty Cycle of Test Signal







# 3.4 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	DC Power Supply	Topward	33010D	807748	N/A

No.	Signal Cable Description Of The Above Support Units
1.	N/A

Note:

# 3.4.1 Configuration of System under Test



# 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

# FCC Part 15, Subpart C (15.247) KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Report No.: RF180314C22-1 Page No. 11 / 36 Report Format Version: 6.1.1

<sup>1.</sup> All power cords of the above support units are non-shielded (1.8m).



# 4 Test Types and Results

# 4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

### Note:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Report No.: RF180314C22-1 Page No. 12 / 36 Report Format Version: 6.1.1



# 4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Oct. 17, 2017	Oct. 16, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Aug. 18, 2017	Aug. 17, 2018
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Dec. 11, 2017	Dec. 10, 2018
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-1170	Dec. 13, 2017	Dec. 12, 2018
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Dec. 01, 2017	Nov. 30, 2018
Loop Antenna EMCI	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Fixed Attenuator Mini-Circuits	BW-N4W5+	1301	Aug. 14, 2017	Aug. 13, 2018
Preamplifier Agilent (Below 1GHz)	8447D	2944A10631	Aug. 08, 2017	Aug. 07, 2018
Preamplifier Agilent (Above 1GHz)	8449B	3008A01922	Sep. 15, 2017	Sep. 14, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MY 13380+295012/0 4	Aug. 08, 2017	Aug. 07, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH4-03 (250724)	Aug. 08, 2017	Aug. 07, 2018
High Speed Peak Power Meter	ML2495A	0824012	Aug. 18, 2017	Aug. 17, 2018
Power Sensor	MA2411B	0738171	Aug. 18, 2017	Aug. 17, 2018
RF signal cable Woken	8D-FB	Cable-CH9-01	Aug. 01, 2017	Jul. 31, 2018
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021703	NA	NA
Turn Table BV ADT	TT100	TT93021703	NA	NA
Turn Table Controller BV ADT	SC100	SC93021703	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note: 1. The calibration interval of the above test instruments is 12/24 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 9.
- 3. The IC Site Registration No. is IC7450F-9.



#### 4.1.3 Test Procedures

#### For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

### For Radiated emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

### Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz. (RBW = 1 MHz, VBW = 10 kHz)
- 4. All modes of operation were investigated and the worst-case emissions are reported.

### 4.1.4 Deviation from Test Standard


No deviation.

Report No.: RF180314C22-1 Page No. 14 / 36 Report Format Version: 6.1.1




# 4.1.5 Test Set Up

# <Radiated Emission below 30 MHz>




# <Radiated Emission 30 MHz to 1 GHz>





# <Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

# 4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.



# 4.1.7 Test Results

# Above 1 GHz Data:

CHANNEL	TX Channel 0	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	2390.00	56.5 PK	74.0	-17.5	2.64 H	133	24.3	32.2	
2	2390.00	46.5 AV	54.0	-7.5	2.64 H	133	14.3	32.2	
3	*2402.00	97.6 PK			2.59 H	136	65.4	32.2	
4	*2402.00	70.5 AV			2.59 H	136	38.3	32.2	
5	4804.00	46.3 PK	74.0	-27.7	1.75 H	175	45.2	1.1	
6	4804.00	36.8 AV	54.0	-17.2	1.75 H	175	35.7	1.1	
		ANTENN	A POLARITY	/ & TEST DI	STANCE: VI	ERTICAL AT	Г3 М		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	2390.00	56.2 PK	74.0	-17.8	2.22 V	254	24.0	32.2	
2	2390.00	46.6 AV	54.0	-7.4	2.22 V	254	14.4	32.2	
3	*2402.00	94.6 PK			2.27 V	250	62.4	32.2	
4	*2402.00	67.4 AV			2.27 V	250	35.2	32.2	
5	4804.00	45.4 PK	74.0	-28.6	1.53 V	288	44.3	1.1	
6	4804.00	35.0 AV	54.0	-19.0	1.53 V	288	33.9	1.1	

# REMARKS:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " \* ": Fundamental frequency.

Report No.: RF180314C22-1 Page No. 17 / 36 Report Format Version: 6.1.1



CHANNEL	TX Channel 19	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	96.6 PK			2.56 H	166	64.6	32.0
2	*2440.00	69.8 AV			2.56 H	166	37.8	32.0
3	4880.00	46.2 PK	74.0	-27.8	1.59 H	184	44.9	1.3
4	4880.00	40.9 AV	54.0	-13.1	1.59 H	184	39.6	1.3
5	7320.00	52.6 PK	74.0	-21.4	2.09 H	284	44.0	8.6
6	7320.00	46.1 AV	54.0	-7.9	2.09 H	284	37.5	8.6
		ANTENN	A POLARITY	/ & TEST DI	STANCE: VI	ERTICAL AT	Г3 М	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	90.5 PK			1.70 V	256	58.5	32.0
2	*2440.00	66.5 AV			1.70 V	256	34.5	32.0
3	4880.00	46.5 PK	74.0	-27.5	2.11 V	297	45.2	1.3
4	4880.00	41.2 AV	54.0	-12.8	2.11 V	297	39.9	1.3
5	7320.00	55.0 PK	74.0	-19.0	1.19 V	295	46.4	8.6
6	7320.00	48.9 AV	54.0	-5.1	1.19 V	295	40.3	8.6

# **REMARKS**:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " \* ": Fundamental frequency.

Report No.: RF180314C22-1 Page No. 18 / 36 Report Format Version: 6.1.1



CHANNEL	TX Channel 39	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

		ANTENNA	POLARITY (	& TEST DIS	TANCE: HO	RIZONTAL A	AT 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	98.6 PK			2.49 H	163	66.5	32.1
2	*2480.00	72.0 AV			2.49 H	163	39.9	32.1
3	2483.50	56.5 PK	74.0	-17.5	2.44 H	165	24.4	32.1
4	2483.50	46.0 AV	54.0	-8.0	2.44 H	165	13.9	32.1
5	4960.00	48.8 PK	74.0	-25.2	1.75 H	180	46.9	1.9
6	4960.00	44.0 AV	54.0	-10.0	1.75 H	180	42.1	1.9
7	7440.00	54.8 PK	74.0	-19.2	2.07 H	295	46.4	8.4
8	7440.00	48.9 AV	54.0	-5.1	2.07 H	295	40.5	8.4
		ANTENN	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL AT	Г3 М	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	91.3 PK			1.72 V	244	59.2	32.1
2	*2480.00	67.3 AV			1.72 V	244	35.2	32.1
3	2483.50	56.4 PK	74.0	-17.6	1.77 V	248	24.3	32.1
4	2483.50	46.0 AV	54.0	-8.0	1.77 V	248	13.9	32.1
5	4960.00	45.6 PK	74.0	-28.4	1.92 V	295	43.7	1.9
6	4960.00	39.8 AV	54.0	-14.2	1.92 V	295	37.9	1.9
7	7440.00	56.5 PK	74.0	-17.5	1.15 V	301	48.1	8.4
8	7440.00	51.3 AV	54.0	-2.7	1.15 V	301	42.9	8.4

# **REMARKS**:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " \* ": Fundamental frequency.

Report No.: RF180314C22-1 Page No. 19 / 36 Report Format Version: 6.1.1



# 9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

### 30 MHz ~ 1 GHz Worst-Case Data:

CHANNEL	TX Channel 39	DETECTOR	Ougoi Book (OD)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	59.01	21.4 QP	40.0	-18.6	2.00 H	37	35.5	-14.1	
2	144.38	15.0 QP	43.5	-28.5	1.00 H	6	28.9	-13.9	
3	239.46	15.3 QP	46.0	-30.7	1.00 H	231	30.0	-14.7	
4	443.21	20.3 QP	46.0	-25.7	1.00 H	6	29.6	-9.3	
5	681.87	24.4 QP	46.0	-21.6	1.50 H	93	28.9	-4.5	
6	870.09	27.4 QP	46.0	-18.6	1.00 H	10	28.0	-0.6	
		ANTENN	A POLARIT	/ & TEST DI	STANCE: V	ERTICAL AT	Г3 М		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	93.93	20.0 QP	43.5	-23.5	2.00 V	232	39.1	-19.1	
2	171.55	13.5 QP	43.5	-30.0	1.50 V	262	27.4	-13.9	
3	454.85	19.4 QP	46.0	-26.6	1.00 V	245	28.5	-9.1	
4	617.84	23.8 QP	46.0	-22.2	2.00 V	81	29.3	-5.5	
5	868.15	27.9 QP	46.0	-18.1	1.50 V	17	28.6	-0.7	
6	924.42	27.6 QP	46.0	-18.4	1.00 V	182	27.2	0.4	

# REMARKS:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value

Report No.: RF180314C22-1 Page No. 20 / 36 Report Format Version: 6.1.1



#### 4.2 Conducted Emission Measurement

#### 4.2.1 Limits of Conducted Emission Measurement

Eroguenov (MU=)	Conducted Limit (dBuV)				
Frequency (MHz)	Quasi-peak	Average			
0.15 - 0.5	66 - 56	56 - 46			
0.50 - 5.0	56	46			
5.0 - 30.0	60	50			

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 23, 2017	Nov. 22, 2018
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2017	Sep. 04, 2018
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 06, 2018	Mar. 05, 2019
LISWAMN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 15, 2017	Aug. 14, 2018
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.

### 4.2.3 Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit 20 dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz - 30 MHz.


Report No.: RF180314C22-1 Page No. 21 / 36 Report Format Version: 6.1.1



# 4.2.4 Deviation from Test Standard

No deviation.

# 4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

# 4.2.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.



# 4.2.7 Test Results


# **CONDUCTED WORST-CASE DATA**

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz			
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 70%RH			
Tested by	Adair Peng	Test Date	2018/4/12			

	Phase Of Power : Line (L)									
No	Frequency	Correction Factor		g Value uV)			Limit (dBuV)		Margin (dB)	
INO	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16173	10.10	4.01	2.54	14.11	12.64	65.37	55.37	-51.26	-42.73
2	0.77169	10.13	2.04	1.33	12.17	11.46	56.00	46.00	-43.83	-34.54
3	0.90854	10.14	1.97	1.54	12.11	11.68	56.00	46.00	-43.89	-34.32
4	8.82238	10.55	2.59	1.99	13.14	12.54	60.00	50.00	-46.86	-37.46
5	17.69026	11.08	15.47	12.30	26.55	23.38	60.00	50.00	-33.45	-26.62
6	23.12907	11.27	17.17	14.74	28.44	26.01	60.00	50.00	-31.56	-23.99

#### Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






i <u></u>			
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 70%RH
Tested by	Adair Peng	Test Date	2018/4/12

	Phase Of Power : Neutral (N)									
	Frequency	Correction	Reading	g Value	Emissio	n Level	Limit		Margin	
No		Factor	(dB	uV)	(dB	uV)	(dB	luV)	(d	B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.44325	10.12	2.54	1.57	12.66	11.69	57.00	47.00	-44.34	-35.31
2	0.62311	10.12	5.22	2.45	15.34	12.57	56.00	46.00	-40.66	-33.43
3	1.21352	10.14	3.44	1.56	13.58	11.70	56.00	46.00	-42.42	-34.30
4	17.69417	10.84	22.75	19.65	33.59	30.49	60.00	50.00	-26.41	-19.51
5	20.37643	10.95	18.42	14.07	29.37	25.02	60.00	50.00	-30.63	-24.98
6	22.42527	10.97	16.38	2.76	27.35	13.73	60.00	50.00	-32.65	-36.27

# Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






#### 4.3 6 dB Bandwidth Measurement

#### 4.3.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100 kHz
- b. Set the video bandwidth (VBW)  $\geq$  3 x RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

# 4.3.6 EUT Operating Conditions


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF180314C22-1 Page No. 25 / 36 Report Format Version: 6.1.1



# 4.3.7 Test Result


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.51	0.5	Pass
19	2440	0.51	0.5	Pass
39	2480	0.51	0.5	Pass





# 4.4 Occupied Bandwidth Measurement

### 4.4.1 Test Setup



#### 4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

### 4.4.4 Deviation From Test Standard

No deviation.

### 4.4.5 EUT Operating Conditions


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF180314C22-1 Page No. 27 / 36 Report Format Version: 6.1.1



# 4.4.6 Test Results

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
0	2402	1.02	Pass
19	2440	1.02	Pass
39	2480	1.02	Pass






# 4.5 Conducted Output Power Measurement

# 4.5.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt (30 dBm)

# 4.5.2 Test Setup



#### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.5.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

#### 4.5.5 Deviation from Test Standard

No deviation.

# 4.5.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

# 4.5.7 Test Results

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
0	2402	0.8072	-0.93	30	Pass
19	2440	0.8395	-0.76	30	Pass
39	2480	0.873	-0.59	30	Pass

Report No.: RF180314C22-1 Page No. 29 / 36 Report Format Version: 6.1.1




# 4.6 Power Spectral Density Measurement

### 4.6.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm.

### 4.6.2 Test Setup



# 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW  $\geq$  3 × RBW.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

# 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF180314C22-1 Page No. 30 / 36 Report Format Version: 6.1.1



# 4.6.7 Test Results

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	2402	-16.71	8	Pass
19	2440	-16.56	8	Pass
39	2480	-16.34	8	Pass






#### 4.7 Conducted Out of Band Emission Measurement

#### 4.7.1 Limits of Conducted Out of Band Emission Measurement

Below -20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

#### 4.7.2 Test Setup



### 4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.7.4 Test Procedure

### **MEASUREMENT PROCEDURE REF**

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

# **MEASUREMENT PROCEDURE OOBE**

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep = auto couple.
- 5. Trace Mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum amplitude level.

### 4.7.5 Deviation from Test Standard

No deviation.


### 4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


Report No.: RF180314C22-1 Page No. 32 / 36 Report Format Version: 6.1.1



# 4.7.7 Test Results









5 Pictures of Test Arrangements
Please refer to the attached file (Test Setup Photo).

Report No.: RF180314C22-1 Page No. 35 / 36 Report Format Version: 6.1.1



# Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a>
Web Site: <a href="mailto:www.bureauveritas-adt.com">www.bureauveritas-adt.com</a>

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: RF180314C22-1 Page No. 36 / 36 Report Format Version: 6.1.1