

**PROJECT****AZIO CASCADE COLLECTION****DOCUMENT**Cascade Quick Start Guide
AZIO-CASCADE-QSG-V01**BY**Tanc Peng
tanc@aziocorp.com**DATE**

2022.08.15

AZIO CASCADE
WIRELESS MECHANICAL KEYBOARD • HOT SWAPPABLE SWITCHES • 105 LAYOUT
SOUND DAMPENING • 7 LED COLORS & RGB LIGHT MODES • ALUMINUM TOP PLATE

QUICK START GUIDE

SETUP via BLUETOOTH

Press the CONNECTION MODE switch to BT MODE.

1. CONNECTION MODES
1.2 MODES
BT MODE
USB MODE

SETUP via USB CABLE

Toggle the switch to MAC or PC to set the keyboard compatible to your operating system.

SETUP via USB CABLE

Toggle the CONNECTION MODE switch to BT MODE.

SETUP via USB CABLE

Toggle the CONNECTION MODE switch to BT MODE.

HOT KEY LEGENDS

Keys	MacOS	PC	Keys	MacOS & PC	Keys	MacOS & PC					
F1	⌘ + ⌘	Increase Display Brightness	F1	⌘ + ⌘	Email Application	F1	⌘ + ⌘	Previous Track	F7	END	Backlight Modes
F2	⌘ + ⌘	Decrease Display Brightness	F2	⌘ + ⌘	Media Player	F8	⌘ + ⌘	Play / Pause	F8	Arrow	Backlight Brightness
F3	⌘ + ⌘	Expose	F3	⌘ + ⌘	Calculator	F9	⌘ + ⌘	Next Track	F9	UP/DN	Backlight Speed
F4	⌘ + ⌘	Search	F4	⌘ + ⌘	Web Browser	F10	⌘ + ⌘	Mute Volume	F10	Left & Right Arrow	Backlight Color
F5	None	My Computer	F5	None	None	F11	⌘ + ⌘	Decrease Volume	F11	Up & Down Arrow	Battery Level
F6	None	None	F6	None	None		⌘ + ⌘	Increase Volume		⌘ + ⌘	Battery Level

CHECK BATTERY LEVEL

Connect the Cascade keyboard to your computer's available USB port with the USB Type-C Cable. The keyboard will light up in red for 5 seconds when a successful connection establishes.

STEP 01
Switch the keyboard to BT Mode. Activate the Bluetooth pairing mode. Press the Fn key and the 1, 2, or 3 key together. The 1, 2, or 3 key will change to a blue back light for a brief moment.

STEP 02
Press the Fn key and the same number key (1, 2, or 3) together for 3-5 seconds. The keyboard will light up in red for 5 seconds and the back-light will indicate the keyboard is now discoverable by your computer's Bluetooth Mode.

STEP 03
You should be able to find "Keyboard" in your discovered device list. Click on it to connect. The keyboard will light up in red for 5 seconds and the display name will change to "AZIO CASCADE". After a few minutes of inactivity, the keyboard will hibernate. Press any key to wake up and reconnect.

STEP 04
Press FN Key + ESC Key to check battery level. Battery level will display through F1 to F10.

STEP 05
The wireless receiver might be a subject of charge in future.

USING HOT-SWAPPABLE SWITCHES

Scan QR code to view the full user guide of CASCADE. Visit www.aziocorp.com/support for any additional questions or support needs.

STEP 1. REMOVE KEYCAP

You will need the Keycap & Switch Puller provided in the package to begin removing your switches.

STEP 2. REMOVE SWITCHES

With the keycap off, you should see the switch underneath. Use the long side of the puller to hook underneath the switch and pull it straight out. Use the rectangular side of the puller to pull and release the plastic caps off gently. Please make sure not to yank the keycap off.

STEP 3. INSTALL SWITCHES

Now you may gently pull and wiggle the switches out. Please avoid jacking on the switch when extracting.

STEP 4. TEST KEYS

When you are ready to install new switches, please make sure the pins on your new switches are bent in the correct direction.

FCC STATEMENT

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. There is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.
Increase the separation between the equipment and receiver.
Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

T. +1.909.468.1198
F. +1.909.468.3066
19933 Harrison Ave
City of Industry, CA 91789

This document contains confidential, copyrighted, and privileged information. If you are not the intended recipient or believe that you have received this document in error, please inform AZIO Corporation immediately and delete this document from your possession. Please do not print, copy, retransmit or otherwise use of this document without permission and consent of AZIO Corporation.

Copyrighted @ 2021

www.aziocorp.com