

Variant FCC Test Report

Report No.: RF150401C19E

FCC ID: ZQAT30

Test Model: A0013

Received Date: Jul. 01, 2016

Test Date: Jul. 12, 2016 ~ Aug. 15, 2016

Issued Date: Aug. 18, 2016

Applicant: Nest Labs Inc

Address: 3400 Hillview Ave. Palo Alto California, United States 94304

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

| | |
|--|-----------|
| Release Control Record | 3 |
| 1 Certificate of Conformity | 4 |
| 2 Summary of Test Results..... | 5 |
| 2.1 Measurement Uncertainty..... | 5 |
| 2.2 Modification Record | 5 |
| 3 General Information | 6 |
| 3.1 General Description of EUT | 6 |
| 3.2 Description of Test Modes..... | 7 |
| 3.2.1 Test Mode Applicability and Tested Channel Detail..... | 8 |
| 3.3 Description of Support Units | 9 |
| 3.3.1 Configuration of System under Test | 9 |
| 3.4 General Description of Applied Standards..... | 9 |
| 4 Test Types and Results | 10 |
| 4.1 Radiated Emission and Bandedge Measurement | 10 |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 10 |
| 4.1.2 Test Instruments | 11 |
| 4.1.3 Test Procedures..... | 12 |
| 4.1.4 Deviation from Test Standard | 12 |
| 4.1.5 Test Set Up | 13 |
| 4.1.6 EUT Operating Conditions..... | 13 |
| 4.1.7 Test Results | 14 |
| 5 Pictures of Test Arrangements..... | 22 |
| Appendix – Information on the Testing Laboratories | 23 |

Release Control Record

| Issue No. | Description | Date Issued |
|--------------|------------------|---------------|
| RF150401C19E | Original Release | Aug. 18, 2016 |

1 Certificate of Conformity

Product: Nest Learning Thermostat

Test Model: A0013

Sample Status: Production Unit

Applicant: Nest Labs Inc

Test Date: Jul. 12, 2016 ~ Aug. 15, 2016

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

This report is issued as a supplementary report to BV ADT report no.: RF150401C19 R1. This report shall be used by combining with its original report.

Prepared by : Evonne Liu, **Date:** Aug. 18, 2016

Evonne Liu / Specialist

Approved by : Stanley Wu, **Date:** Aug. 18, 2016

Stanley Wu / Assistant Manager

2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) | | | |
|--|-----------------------------|--------|--|
| FCC Clause | Test Item | Result | Remarks |
| 15.207 | AC Power Conducted Emission | NA | Refer to Note |
| 15.205 & 209 | Radiated Emissions | Pass | Meet the requirement of limit. Minimum passing margin is -11.55 dB at 2484 MHz. |
| 15.247(d) | Band Edge Measurement | NA | Refer to Note |
| 15.247(d) | Antenna Port Emission | NA | Refer to Note |
| 15.247(a)(2) | 6 dB Bandwidth | NA | Refer to Note |
| 15.247(b) | Conducted power | NA | Refer to Note |
| 15.247(e) | Power Spectral Density | NA | Refer to Note |
| 15.203 | Antenna Requirement | NA | Refer to Note |

Note: Only Radiated Emissions test was performed for this addendum. Refer to original report for other test data.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

| Measurement | Frequency | Expended Uncertainty (k=2) (±) |
|--------------------------------|--------------------|--------------------------------|
| Radiated Emissions up to 1 GHz | 30 MHz ~ 200 MHz | 2.93 dB |
| | 200 MHz ~ 1000 MHz | 2.95 dB |
| Radiated Emissions above 1 GHz | 1 GHz ~ 18 GHz | 2.26 dB |
| | 18 GHz ~ 40 GHz | 1.94 dB |

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

| | |
|----------------------------|---------------------------------|
| Product | Nest Learning Thermostat |
| Test Model | A0013 |
| Status of EUT | Production Unit |
| Power Supply Rating | 5.0Vac (Adapter) |
| Modulation Type | GFSK |
| Transfer Rate | 1 Mbps |
| Operating Frequency | 2402 ~ 2480 MHz |
| Number of Channel | 40 |
| Antenna Type | Chip antenna with -1.4 dBi gain |
| Antenna Connector | N/A |
| Accessory Device | Refer to Note as below |
| Data Cable Supplied | Refer to Note as below |

Note:

1. This report is issued as a supplementary report to BV ADT report no. RF150401C19 R1. The difference compared with original report is adding material of outer casing. Therefore, only Radiated Emissions was verified and recorded in this report.
2. The EUT contains following accessory devices.

| Product | Brand | Model | Description |
|----------------|--------------|--------------|--|
| Adapter | Nest | A0017 | I/P: 100-240Vac, 50/60Hz, 0.35A O/P: 5Vdc, 2.5A |
| USB Cable | Nest | NA | 2.0m shielded cable w/o core |
| Stand | Nest | Stand | -- |

3. The device has 3 configurations as below.

Main sample (A): Material of outer casing for DLC

2nd sample (B): Material of outer casing for Copper

3rd sample (C): Material of outer casing for Ceramic

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Description of Test Modes

40 channels are provided to this EUT:

| Channel | Freq. (MHz) |
|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| 0 | 2402 | 10 | 2422 | 20 | 2442 | 30 | 2462 |
| 1 | 2404 | 11 | 2424 | 21 | 2444 | 31 | 2464 |
| 2 | 2406 | 12 | 2426 | 22 | 2446 | 32 | 2466 |
| 3 | 2408 | 13 | 2428 | 23 | 2448 | 33 | 2468 |
| 4 | 2410 | 14 | 2430 | 24 | 2450 | 34 | 2470 |
| 5 | 2412 | 15 | 2432 | 25 | 2452 | 35 | 2472 |
| 6 | 2414 | 16 | 2434 | 26 | 2454 | 36 | 2474 |
| 7 | 2416 | 17 | 2436 | 27 | 2456 | 37 | 2476 |
| 8 | 2418 | 18 | 2438 | 28 | 2458 | 38 | 2478 |
| 9 | 2420 | 19 | 2440 | 29 | 2460 | 39 | 2480 |

3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable To | | Description |
|--------------------|---------------|-----------|-------------------|
| | RE \geq 1G | RE $<$ 1G | |
| A | √ | - | Sample A: DLC |
| B | √ | - | Sample B: Copper |
| C | √ | √ | Sample C: Ceramic |

Where RE \geq 1G: Radiated Emission above 1 GHz RE $<$ 1G: Radiated Emission below 1 GHz

NOTE: 1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane** for mode A/B, **X-plane** for mode C.

2. “-” means no effect.

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A, B, C | 0 to 39 | 39 | GFSK | 1 |

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| C | 0 to 39 | 39 | GFSK | 1 |


Test Condition:

| Applicable To | Environmental Conditions | Input Power | Tested by |
|---------------|--------------------------|----------------|-----------|
| RE \geq 1G | 25 deg. C, 65 % RH | 120 Vac, 60 Hz | Gavin Wu |
| RE $<$ 1G | 25 deg. C, 65 % RH | 120 Vac, 60 Hz | Gavin Wu |

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v03r05

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).

The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F (kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F (kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{uV}/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.1.2 Test Instruments

| Description & Manufacturer | Model No. | Serial No. | Date of Calibration | Due Date of Calibration |
|--|----------------|---------------------|---------------------|-------------------------|
| Test Receiver Agilent | N9038A | MY51210203 | Jan. 21, 2016 | Jan. 20, 2017 |
| Spectrum Analyzer Agilent | N9010A | MY52220314 | Sep.03, 2015 | Sep. 02, 2016 |
| BILOG Antenna SCHWARZBECK | VULB9168 | 9168-472 | Jan. 07, 2016 | Jan. 06, 2017 |
| HORN Antenna SCHWARZBECK | BBHA 9120 D | 9120D-969 | Jan. 04, 2016 | Jan. 03, 2017 |
| HORN Antenna SCHWARZBECK | BBHA 9170 | 9170-480 | Jan. 08, 2016 | Jan. 07, 2017 |
| Loop Antenna | LPA600 | 270 | Aug. 20, 2015 | Aug. 19, 2017 |
| Agilent Communications Tester-Wireless | 8960 Series 10 | MY53201073 | Jul. 03, 2015 | Jul. 02, 2017 |
| Preamplifier EMCI | EMC 012645 | 980115 | Dec. 21, 2015 | Dec. 20, 2016 |
| Preamplifier EMCI | EMC 184045 | 980116 | Dec. 21, 2015 | Dec. 20, 2016 |
| Preamplifier EMCI | EMC 330H | 980112 | Dec. 28, 2015 | Dec. 27, 2016 |
| RF signal cable HUBER+SUHNNER | SUCOFLEX 104 | 309219/4 2950114 | Oct. 12, 2015 | Oct. 11, 2016 |
| RF signal cable HUBER+SUHNNER | SUCOFLEX 104 | 250130/4 | Oct. 12, 2015 | Oct. 11, 2016 |
| RF Coaxial Cable Worken | 8D-FB | Cable-Ch10-01 | Oct. 12, 2015 | Oct. 11, 2016 |
| Software BV ADT | E3 6.120103 | NA | NA | NA |
| Antenna Tower MF | MFA-440H | NA | NA | NA |
| Turn Table MF | MFT-201SS | NA | NA | NA |
| Antenna Tower & Turn Table Controller MF | MF-7802 | NA | NA | NA |

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC7450F-10.

4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1/T for RMS Average (Duty cycle < 98 %) for Peak detection at frequency above 1 GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle \geq 98 %) for Average detection (AV) at frequency above 1 GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up

<Frequency Range below 1 GHz>



<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.


4.1.7 Test Results

ABOVE 1 GHz DATA :


Mode A (Peak power = 8.84 dBm)

| EUT Test Condition | | Measurement Detail | |
|--------------------------|--------------------|--------------------|---|
| Channel | Channel 39 | Frequency Range | 1 GHz ~ 25 GHz |
| Input Power | 120 Vac, 60 Hz | Detector Function | Peak (PK) RBW : 1MHz , VBW : 3MHz Average (AV) RBW : 1MHz , VBW : 3KHz |
| Environmental Conditions | 25 deg. C, 65 % RH | Tested By | Gavin Wu |

Horizontal



Vertical





| Antennal Polarity & Test Distance: Horizontal at 3 m | | | | | | | | | | |
|--|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
| 2356 | 34.29 | 40.92 | 54 | -19.71 | 26.81 | 4.05 | 37.49 | 100 | 264 | Average |
| 2356 | 56.25 | 62.88 | 74 | -17.75 | 26.81 | 4.05 | 37.49 | 100 | 264 | Peak |
| 2480 | 98.99 | 105.01 | | | 27.15 | 4.15 | 37.32 | 100 | 264 | Average |
| 2480 | 99.6 | 105.62 | | | 27.15 | 4.15 | 37.32 | 100 | 264 | Peak |
| 2484 | 42.45 | 48.47 | 54 | -11.55 | 27.15 | 4.15 | 37.32 | 100 | 264 | Average |
| 2484 | 58.85 | 64.87 | 74 | -15.15 | 27.15 | 4.15 | 37.32 | 100 | 264 | Peak |
| 4960 | 33.36 | 48.33 | 54 | -20.64 | 31.16 | 6.91 | 53.04 | 124 | 341 | Average |
| 4960 | 43.88 | 58.85 | 74 | -30.12 | 31.16 | 6.91 | 53.04 | 124 | 341 | Peak |
| Antennal Polarity & Test Distance: Vertical at 3 m | | | | | | | | | | |
| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
| 2380 | 34.37 | 40.93 | 54 | -19.63 | 26.86 | 4.08 | 37.5 | 100 | 4 | Average |
| 2380 | 56.1 | 62.66 | 74 | -17.9 | 26.86 | 4.08 | 37.5 | 100 | 4 | Peak |
| 2480 | 95.42 | 101.44 | | | 27.15 | 4.15 | 37.32 | 100 | 4 | Average |
| 2480 | 96.26 | 102.28 | | | 27.15 | 4.15 | 37.32 | 100 | 4 | Peak |
| 2484 | 39.14 | 45.16 | 54 | -14.86 | 27.15 | 4.15 | 37.32 | 100 | 4 | Average |
| 2484 | 56.78 | 62.8 | 74 | -17.22 | 27.15 | 4.15 | 37.32 | 100 | 4 | Peak |
| 4965 | 33.13 | 48.1 | 54 | -20.87 | 31.16 | 6.91 | 53.04 | 105 | 332 | Average |
| 4965 | 44.03 | 59 | 74 | -29.97 | 31.16 | 6.91 | 53.04 | 105 | 332 | Peak |

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2480 MHz: Fundamental frequency.

Mode B (Peak power = 8.84 dBm)

| EUT Test Condition | | Measurement Detail | |
|--------------------------|--------------------|--------------------|---|
| Channel | Channel 39 | Frequency Range | 1 GHz ~ 25 GHz |
| Input Power | 120 Vac, 60 Hz | Detector Function | Peak (PK) RBW : 1MHz , VBW : 3MHz Average (AV) RBW : 1MHz , VBW : 3KHz |
| Environmental Conditions | 25 deg. C, 65 % RH | Tested By | Gavin Wu |

Horizontal

Vertical




| Antennal Polarity & Test Distance: Horizontal at 3 m | | | | | | | | | | |
|--|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
| 2384 | 34.52 | 41.08 | 54 | -19.48 | 26.86 | 4.08 | 37.5 | 176 | 65 | Average |
| 2384 | 57.23 | 63.79 | 74 | -16.77 | 26.86 | 4.08 | 37.5 | 176 | 65 | Peak |
| 2480 | 97.79 | 103.81 | | | 27.15 | 4.15 | 37.32 | 176 | 65 | Average |
| 2480 | 98.43 | 104.45 | | | 27.15 | 4.15 | 37.32 | 176 | 65 | Peak |
| 2484 | 41.32 | 47.34 | 54 | -12.68 | 27.15 | 4.15 | 37.32 | 176 | 65 | Average |
| 2484 | 57.44 | 63.46 | 74 | -16.56 | 27.15 | 4.15 | 37.32 | 176 | 65 | Peak |
| 4960 | 33.51 | 48.48 | 54 | -20.49 | 31.16 | 6.91 | 53.04 | 129 | 57 | Average |
| 4960 | 43.94 | 58.91 | 74 | -30.06 | 31.16 | 6.91 | 53.04 | 129 | 57 | Peak |
| Antennal Polarity & Test Distance: Vertical at 3 m | | | | | | | | | | |
| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
| 2316 | 34.24 | 41.01 | 54 | -19.76 | 26.67 | 4.03 | 37.47 | 229 | 318 | Average |
| 2316 | 56.46 | 63.23 | 74 | -17.54 | 26.67 | 4.03 | 37.47 | 229 | 318 | Peak |
| 2480 | 94.76 | 100.78 | | | 27.15 | 4.15 | 37.32 | 229 | 318 | Average |
| 2480 | 95.58 | 101.6 | | | 27.15 | 4.15 | 37.32 | 229 | 318 | Peak |
| 2488 | 39.54 | 45.5 | 54 | -14.46 | 27.2 | 4.16 | 37.32 | 229 | 318 | Average |
| 2488 | 56.51 | 62.47 | 74 | -17.49 | 27.2 | 4.16 | 37.32 | 229 | 318 | Peak |
| 4960 | 33.04 | 48.01 | 54 | -20.96 | 31.16 | 6.91 | 53.04 | 109 | 298 | Average |
| 4960 | 44.67 | 59.64 | 74 | -29.33 | 31.16 | 6.91 | 53.04 | 109 | 298 | Peak |

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2480 MHz: Fundamental frequency.

Mode C (Peak power = 8.84 dBm)

| EUT Test Condition | | Measurement Detail | |
|--------------------------|--------------------|--------------------|---|
| Channel | Channel 39 | Frequency Range | 1 GHz ~ 25 GHz |
| Input Power | 120 Vac, 60 Hz | Detector Function | Peak (PK) RBW : 1MHz , VBW : 3MHz Average (AV) RBW : 1MHz , VBW : 3KHz |
| Environmental Conditions | 25 deg. C, 65 % RH | Tested By | Gavin Wu |

Horizontal

Vertical


| Antennal Polarity & Test Distance: Horizontal at 3 m | | | | | | | | | | |
|--|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|---------|
| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
| 2378 | 34.69 | 41.26 | 54 | -19.31 | 26.86 | 4.07 | 37.5 | 196 | 248 | Average |
| 2378 | 56.63 | 63.2 | 74 | -17.37 | 26.86 | 4.07 | 37.5 | 196 | 248 | Peak |
| 2480 | 90.51 | 96.53 | | | 27.15 | 4.15 | 37.32 | 196 | 248 | Average |
| 2480 | 91.22 | 97.24 | | | 27.15 | 4.15 | 37.32 | 196 | 248 | Peak |
| 2498 | 37.31 | 43.2 | 54 | -16.69 | 27.2 | 4.16 | 37.25 | 196 | 248 | Average |
| 2498 | 57.18 | 63.07 | 74 | -16.82 | 27.2 | 4.16 | 37.25 | 196 | 248 | Peak |
| 4960 | 33.61 | 48.58 | 54 | -20.39 | 31.16 | 6.91 | 53.04 | 106 | 212 | Average |
| 4960 | 44.55 | 59.52 | 74 | -29.45 | 31.16 | 6.91 | 53.04 | 106 | 212 | Peak |
| Antennal Polarity & Test Distance: Vertical at 3 m | | | | | | | | | | |
| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
| 2354 | 34.64 | 41.27 | 54 | -19.36 | 26.81 | 4.05 | 37.49 | 174 | 9 | Average |
| 2354 | 57.45 | 64.08 | 74 | -16.55 | 26.81 | 4.05 | 37.49 | 174 | 9 | Peak |
| 2480 | 96.89 | 102.91 | | | 27.15 | 4.15 | 37.32 | 174 | 9 | Average |
| 2480 | 97.57 | 103.59 | | | 27.15 | 4.15 | 37.32 | 174 | 9 | Peak |
| 2484 | 41.44 | 47.46 | 54 | -12.56 | 27.15 | 4.15 | 37.32 | 174 | 9 | Average |
| 2484 | 59.72 | 65.74 | 74 | -14.28 | 27.15 | 4.15 | 37.32 | 174 | 9 | Peak |
| 4960 | 33.15 | 48.12 | 54 | -20.85 | 31.16 | 6.91 | 53.04 | 100 | 131 | Average |
| 4960 | 43.13 | 58.1 | 74 | -30.87 | 31.16 | 6.91 | 53.04 | 100 | 131 | Peak |

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2480 MHz: Fundamental frequency.

9 kHz ~ 30 MHz DATA:


The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz WORST-CASE DATA:


Mode C (Peak power = 8.84 dBm)

| EUT Test Condition | | Measurement Detail | |
|--------------------------|--------------------|--------------------|---|
| Channel | Channel 39 | Frequency Range | 30 MHz ~ 1 GHz |
| Input Power | 120 Vac, 60 Hz | Detector Function | Peak (PK) RBW : 120KHz , VBW : 360KHz Quasi-peak (QP) |
| Environmental Conditions | 25 deg. C, 65 % RH | Tested By | Gavin Wu |

Horizontal



Vertical



Antennal Polarity & Test Distance: Horizontal at 3 m

| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
|-----------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|--------|
| 41.64 | 17.24 | 34.07 | 40 | -22.76 | 13.56 | 0.66 | 31.05 | 136 | 4 | Peak |
| 141.55 | 15.72 | 33.78 | 43.5 | -27.78 | 12.41 | 1.16 | 31.63 | 105 | 37 | Peak |
| 290.93 | 16.8 | 34.2 | 46 | -29.2 | 12.68 | 1.61 | 31.69 | 104 | 100 | Peak |
| 376.29 | 18.63 | 33.95 | 46 | -27.37 | 14.77 | 1.85 | 31.94 | 111 | 24 | Peak |
| 487.84 | 21.01 | 33.65 | 46 | -24.99 | 17.08 | 2.07 | 31.79 | 108 | 135 | Peak |
| 515 | 22.43 | 34.23 | 46 | -23.57 | 17.66 | 2.12 | 31.58 | 130 | 225 | Peak |

Antennal Polarity & Test Distance: Vertical at 3 m

| Frequency (MHz) | Emission Level (dBuV/m) | Read Level (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Antenna Height (cm) | Table Angle (Degree) | Remark |
|-----------------|-------------------------|-------------------|----------------|-------------|-----------------------|-----------------|--------------------|---------------------|----------------------|--------|
| 60.07 | 14.92 | 33.53 | 40 | -25.08 | 11.94 | 0.81 | 31.36 | 127 | 262 | Peak |
| 164.83 | 15.47 | 33.91 | 43.5 | -28.03 | 12.25 | 1.12 | 31.81 | 136 | 134 | Peak |
| 291.9 | 16.46 | 33.84 | 46 | -29.54 | 12.71 | 1.61 | 31.7 | 106 | 157 | Peak |
| 337.49 | 19.59 | 35.84 | 46 | -26.41 | 13.84 | 1.73 | 31.82 | 133 | 255 | Peak |
| 421.88 | 19.36 | 33.69 | 46 | -26.64 | 15.77 | 1.94 | 32.04 | 105 | 6 | Peak |
| 495.6 | 21.61 | 33.99 | 46 | -24.39 | 17.23 | 2.08 | 31.69 | 103 | 156 | Peak |

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---