FCC PART 15.249 EMI MEASUREMENT AND TEST REPORT

For

The Car Nanny, LLC

21113 Osborne St. Canoga Park, Los Angeles, CA 91304, USA

FCC ID: ZRG-35N360

July 16, 2011

Equipment Type: This Report Concerns:

3.5" Digital Wireless LCD Baby Original Report

BST11060197Y-1ER-3

Monitor

Test Engineer: Eric Li

Report No.:

Receive EUT

Date/Test Date: July 6, 2011/ July 7-16, 2011

Reviewed By: printing) ong Christina (

Shenzhen BST Technology Co.,Ltd.

3F, Weames Technology Building, No. 10 Kefa Road, Science Park, Prepared By: Nanshan District, Shenzhen, Guangdong, China

Tel: 0755-26747751 ~ 3

Fax: 0755-26747751 ~ 3 ext.826

Note: The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of Shenzhen BST Technology Co.,Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

1.	GEN	ERAL INFORMATION	3
	1.1.	Report information	3
	1.2.	Measurement Uncertainty	3
2.	PRO	DUCT DESCRIPTION	4
	2.1.	EUT Description	4
	2.2.	Block Diagram of EUT Configuration	4
	2.3.	Support Equipment List	5
	2.4.	Test Conditions	5
3.	FCC	ID LABEL	6
4.	TEST	Γ RESULTS SUMMARY	7
	Modi	fications	7
5.	TEST	Γ EQUIPMENT USED	8
6.	ANT	ENNA REQUIREMENT	9
	6.1.	STANDARD APPLICABLE	9
	6.2.	ANTENNA CONNECTED CONSTRUCTION	9
	6.3.	Result	9
7.	CON	DUCTED POWER LINE TEST	10
	7.1.	Test Equipment	10
	7.2.	Test Procedure	10
	7.3.	TR G .	10
		Test Setup	
	7.4.	Conducted Power line Emission Limits	10
	7.4. 7.5.	Conducted Power line Emission Limits	10 11
8.	7.4. 7.5.	Conducted Power line Emission Limits	10 11
8.	7.4. 7.5. RAD 8.1.	Conducted Power line Emission Limits	10 11 13
8.	7.4. 7.5. RAD 8.1. 8.2.	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure	10 11 13 13 13
8.	7.4. 7.5. RAD 8.1. 8.2. 8.3.	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure Radiated Test Setup	10 11 13 13 13
8.	7.4. 7.5. RAD 8.1. 8.2. 8.3.	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit	10 11 13 13 13 13
	7.4. 7.5. RAD 8.1. 8.2. 8.3. 8.4.	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result	10 11 13 13 13 13 14 15
8. 9.	7.4. 7.5. RAD 8.1. 8.2. 8.3. 8.4. 8.5. BAN	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result	10 11 13 13 13 14 15 17
	7.4. 7.5. RAD 8.1. 8.2. 8.3. 8.4. 8.5. BAN 9.1.	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result D EDGE Test Equipment	10 11 13 13 13 14 15 17
	7.4. 7.5. RAD 8.1. 8.2. 8.3. 8.4. 8.5. BAN 9.1. 9.2.	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result D EDGE Test Equipment Test Procedure	10 11 13 13 13 14 15 17 17
	7.4. 7.5. RAD 8.1. 8.2. 8.3. 8.4. 8.5. BAN 9.1.	Conducted Power line Emission Limits Conducted Power Line Test Result IATED EMISSION TEST Test Equipment Test Procedure Radiated Test Setup Radiated Emission Limit Radiated Emission Test Result D EDGE Test Equipment	10 11 13 13 13 14 15 17 17

1. GENERAL INFORMATION

1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BST approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BST in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BST therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BST, unless the applicant has authorized BST in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of emitel (Shenzhen) Limited

(FCC Registered Test Site Number: 746887) on

Building 2, 171 Meihua Road, Futian District, Shenzhen, 518049 China The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

Available upon request.

2. PRODUCT DESCRIPTION

2.1. EUT Description

Description : 3.5" Digital Wireless LCD Baby Monitor

Applicant : The Car Nanny, LLC

21113 Osborne St. Canoga Park, Los Angeles, CA 91304,

USA

Model Number : 35N360

Trade Name : N/A

Frequency : 2409.750MHz-2475.000MHz

Number of Channels : 18

Power Supply : DC 3.7V Li-ion Battery or DC 5V powered by Adapter

2.2. Block Diagram of EUT Configuration




Figure 2 EUT Setup

2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used " "
Adapter Input: AC 100-240V, 50/60Hz, 0.25Amax Output: DC 5V, 1000mA	FKS106HSC-0501000U	/	/	

2.4. Test Conditions

Temperature: 20~25

Relative Humidity: 50~63 %

3. FCC ID LABEL

FCC ID: ZRG-35N360

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1. This device may not cause harmful interference, and 2. This device must accept any interference received, including interference that may cause undesired operation.

Label Location on EUT





4. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.249

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	Compliant
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.209 Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant

Remark: "N/A" means "Not applicable".

Modifications

No modification was made.

5. TEST EQUIPMENT USED

Equipment/Facilities	Manufacturer	Model #	Serial no.	Date of Cal.	Cal. Interval
Cable	Resenberger	N/A	NO.1	Mar 10 , 2011	1 Year
Cable	SCHWARZBECK	N/A	NO.2	Mar 10 , 2011	1 Year
Cable	SCHWARZBECK	N/A	NO.3	Mar 10 , 2011	1 Year
LISN	Rohde & Schwarz	ESH3-Z5	100305	Mar 10 , 2011	1 Year
50 Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Mar 10 , 2011	1 Year
EMI Test Receiver	Rohde & Schwarz	ESP13	100180	Oct.11,2010	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSP40	100273	Sep.10,2010	1 Year
3m Semi-Anechoic Chamber	Albatross Projects	9m×6m×6m	N/A	Feb.20,2011	1 Year
Signal Generator	FLUKE	PM5418 + Y/C	LO747012	Feb.20,2011	1 Year
Signal Generator	FLUKE	PM5418TX	LO738007	Feb.20,2011	1 Year
Loop Antenna	SCHWARZBECK	FMZB1516	113	Jan.30,2011	1 Year
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	9161-4079	Sep.22,2010	1 Year
Broad-Band Horn	SCHWARZBECK	BBHA9120D	9120D-564	Sep.22,2010	1 Year
Antenna					
Ultra Broadband Antenna	Rohde & Schwarz	HL-562	100110	June.15,2011	1 Year
AMN	Rohde & Schwarz	ESH3-Z5	100196	Oct.11,2010	1 Year
AMN	Rohde & Schwarz	ESH3-Z5	100197	Oct.11,2010	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
Power Meter	Rohde & Schwarz	NRVD	100041	Feb.20,2011	1 Year
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	Feb.20,2011	1 Year
Coaxial Cable with N-connectors	SCHWARZBECK	AK9515H	95549	Sep.22,2010	1 Year
Radio Communication Test Set	Rohde & Schwarz	CMS 54	846621/024	Feb.20,2011	1 Year
Modulation Analyzer	Hewlett-Packard	8901B	2303A00362	Feb.20,2011	1 Year
Absorbing clamp	Rohde & Schwarz	MDS-21	N/A	Oct.11,2010	1 Year

6. ANTENNA REQUIREMENT

6.1. STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2. ANTENNA CONNECTED CONSTRUCTION

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna used in this product is short soldered wire antenna. The antenna is permanently attached. Refer to the product photo.

6.3. Result

Compliance

7. CONDUCTED POWER LINE TEST

7.1. Test Equipment


Please refer to section 5 this report.

7.2. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uh coupling inpedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uh coupling inpedance with 50ohm termination.

Both sides of A.C. Line are check for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and al of the interface cables must be changed according to ASIN C63.4:2003 on conducted measurement. Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9Khz.

7.3. Test Setup



For the actual test configuration, Please refer to the related items-Photos of testing

7.4. Conducted Power line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)				
Frequency Range	Class A	Class B		
(MHZ)	QP/AV	QP/AV		
0.15-0.5	79/66	65-56/56-46		
0.5-5.0	73/60	56-46		
5.0-3.0	73/60	60-50		

Note: In the above table, the tighter limit applies at the band edges.

7.5. Conducted Power Line Test Result

Pass.

Date of Test: July 10, 2011 Temperature: 25°C


EUT: 3.5" Digital Wireless LCD Baby Monitor Humidity: 50%

Model No.: 35N360 Power Supply: AC120V/60Hz

Test Mode: TX Test Engineer: Eric Li

			Limit	Over			
	Freq	Level			Remark	Pol/Phase	
-	MHz	dBuV.	dBuV	dB		=	
1 Max	0.20				Average	LINE	
2		24.54			Average	LINE	
2 3 4					Average	LINE	
5					Average Average	LINE LINE	
	Freq	Level		Over Limit	Remark	Pol/Phase	
	MHz	dBu₹	dBu∛	dB		- Validation and the second	
1 Max 2		43. 13 39. 81		-20.41 -21.44		LINE LINE	
2 3 4	0.89	31.66	56.00	-24.34		LINE	
4		33.26				LINE	
5	2.25	34.79	56.00	-21.21	Peak	LINE	
	Freq	Level	Limit Line	Over Limit	Remark	Pol/Phase	
- 500	MHz	dBu₹	dBuV	dB			
1	0.20	23.05	53.62	-30.57	Average	NEUTRAL	
1 2	0.60	17.94	46.00	-28.06	Average	NEUTRAL	
3 4 Max					Average		
4 Max	2.27				Average	NEUTRAL	
5	12.25	14.17	50.00	-35.83	Average	NEUTRAL.	
	Freq	Level	Limit Line	Over Limit	Remark	Pol/Phase	
	MHz	dBu₹	dBu∀	dB			
1	0.20 0.66	37.79		-26.01		NEUTRAL	
0	11 16 16	33.05	5b. UU	-22.95	reak	NEUTRAL	
2				-22 FF	Dools	METITEAT	
2 3 4 Max	1.57	33. 45 33. 55	56.00	-22.55 -22.45		NEUTRAL NEUTRAL	

The spectral diagrams in below display the measurement of Peak and Average values.



8. RADIATED EMISSION TEST

8.1. Test Equipment

Please refer to section 5 this report.


8.2. Test Procedure

- 1. The EUT was tested according C63.4-2003. The radiated test was performed at FCC Registration laboratory .
- 2. The EUT, peripherals were put on the turntable which table size of $1m \times 1.5m$, table high 0.8m. All set up is according to ANSI C63.4-2003.
- 3. The frequency spectrum from 30MHZ to 1 GHZ was investigated. All readings from 30MHZ to 1 GHZ are quasi-peak values with a resolution bandwidth of 120 KHZ. All readings are above 1GHZ ,prak values with a resolution bandwidth of 1 MHZ. Measurements were made at 3 merers.
- 4. The antenna high is varied from 1m to 4m high to find the maximum emission for each frequency.
- 5. Maximizing procedure was performed on the six(6)highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 Db of specification

limit), and are distinguished with a "QP" in the data table.

- 6. The antenna polarization: Vertical polarization and Horizontal polarization.
- 7. Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit.

8.3. Radiated Test Setup



For the accrual test configuration, pleas refer to the related items-photos of Testing.

8.4. Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A . FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Frequency	Distance	Field Strength
(MHZ)	(m)	(dBuV/m)
30-88	3	40.0
88-*216	3	43.5
216-960	3	46.0
ABOVE 960	3	54.0

- Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)
 - (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
 - (3) The emission limit in this paragraph os based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

B.Frequencies in restricted band are complied to limit on Paragraph 15.209.

Fundamental Frequency	Field as trength of Fundamental(3m)			Field as trength of Harmonics(3m)		
(MHZ)	mV/m	dBuV/m		uV/m	dBuV/m	
902~928	50	94(AV)	114(Peak	500	54(AV)	74(Peak)
2400~2483.5	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

- (2) In the Above Table, the tighter limit applies at the band edges.
 - (3) Distagnce refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

8.5. Radiated Emission Test Result

Pass

A. Fundamental Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2409.750	84.78/89.52	VERT	94/114	9.22/24.48
2409.750	87.56/91.82	HORIZ	94/114	6.44/22.18

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2442.375	85.03/90.04	VERT	94/114	8.97/23.96
2442.375	87.46/92.61	HORIZ	94/114	6.54/21.39

CH High

0				
Freq.	Emission(dBuV/m)	HORIZ/	Limits(dBuV/m)	Margin
(MHz)	AV/PK	VERT	AV/PK	(dB)
2475.000	84.22/88.63	VERT	94/114	9.78/25.37
2475.000	86.86/91.74	HORIZ	94/114	7.14/22.26

B.Harmonics Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4819.500	46.24/51.42	VERT	54.0/74.0	7.76/22.58
4819.500	46.35/51.62	HORIZ	54.0/74.0	7.65/22.38

Emissions attenuated more than 20 dB below the permissible value are not reported.

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4884.750	43.42/48.76	VERT	54.0/74.0	10.58/25.24
4884.750	44.11/48.88	HORIZ	54.0/74.0	9.89/25.12

Emissions attenuated more than 20 dB below the permissible value are not reported.

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4950.000	45.77/50.23	VERT	54.0/74.0	8.23/23.77
4950.000	45.65/50.90	HORIZ	54.0/74.0	8.35/23.10

Emissions attenuated more than 20 dB below the permissible value are not reported.

C. General Radiated Emissions Data

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
-	-	HORIZ	-	-
-	-	VERT	-	-

Emissions attenuated more than 20 dB below the permissible value are not reported.

9. BAND EDGE

9.1. Test Equipment

Please refer to Section 5 this report.

9.2. Test Procedure

- 1. The EUT was tested according C63.4-2003. The radiated test was performed at FCC Registration laboratory .
- 2. The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.
- 3.As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2438.5MHz, than mark the higher-level emission for comparing with the FCC rules.

9.3. Band Edge FCC 15.249(d) Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50dB

below that in the 100kHz bandwidth within the band that contains the desired power, based on either an RF conducted or a radited measurement, Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

9.4. Band Edge Test Result

Pass

TX 2409.750MHz

Frequency	Result(dBµV/m)		Limit(dBµV/m)		Margin(dB)		Polarization
(MHz)	AV	PEAK	AV	PEAK	AV	PEAK	
2400.000	32.35	37.54	54	74	21.65	36.46	Vertical
2400.000	32.39	37.73	54	74	21.61	36.27	Horizontal


Emissions attenuated more than 20 dB below the permissible value are not reported.

TX 2475.000MHz


Frequency	Result(dBµV/m)		Limit(dBµV/m)		Margin(dB)		Polarization
(MHz)	AV	PEAK	AV	PEAK	AV	PEAK	
2483.500	31.64	36.75	54	74	22.36	37.25	Vertical
2483.500	32.03	37.21	54	74	21.97	36.79	Horizontal

Emissions attenuated more than 20 dB below the permissible value are not reported.


Vertical TX 2409.750MHz




Horizontal TX 2409.750MHz




Vertical TX 2475.000MHz



Horizontal TX 2475.000MHz



Occupied Bandwidth plot



20dB Occupied Bandwidth = 864kHz.