

## RF Exposure Evaluation

Product Description: Body-worn Wireless Microphone

Model Number: VHF-06BP

FCC ID: ZRIVHF-06BP

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

According to the test report:

$P_t = 1.25 \text{ mW}$

The result is rounded to one decimal place for comparison

Worse case is as below: [171.905MHz - 1.25mW output power]

$(1.25 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{0.172(\text{GHz})}] = \underline{0.10} < 3.0 \text{ for 1-g SAR}$

Then SAR evaluation is not required

**NOTE:** For the maximum power, you can refer FCC test report.