


RF TEST REPORT



Report No.: 17070655-FCC-R2

Supersede Report No.: N/A

Applicant	SHENZHEN KENXINDA TECHNOLOGY CO.,LTD	
Product Name	Mobile Phone	
Model No.	K6900	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	August 23 to September 10, 2017	
Issue Date	September 11, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070655-FCC-R2
Page	3 of 67

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	7
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	10
6.1 ANTENNA REQUIREMENT	10
6.2 CHANNEL SEPARATION.....	11
6.3 20DB BANDWIDTH	15
6.4 PEAK OUTPUT POWER	19
6.5 NUMBER OF HOPPING CHANNEL	23
6.6 TIME OF OCCUPANCY (DWEEL TIME).....	25
6.7 BAND EDGE & RESTRICTED BAND	29
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	37
6.9 RADIATED EMISSIONS & RESTRICTED BAND.....	43
ANNEX A. TEST INSTRUMENT	50
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	51
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	62
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	66
ANNEX E. DECLARATION OF SIMILARITY	67

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070655-FCC-R2	NONE	Original	September 11, 2017

2. Customer information

Applicant Name	SHENZHEN KENXINDA TECHNOLOGY CO.,LTD
Applicant Add	18TH FLOOR,FUCHUN ORIENT BUILDING,SHENNAN AV 7006,SHENZHEN,CHINA
Manufacturer	SHENZHEN KENXINDA TECHNOLOGY CO.,LTD
Manufacturer Add	18TH FLOOR,FUCHUN ORIENT BUILDING,SHENNAN AV 7006,SHENZHEN,CHINA

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Test Report	17070655-FCC-R2
Page	6 of 67

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	K6900
Serial Model:	N/A
Date EUT received:	August 22, 2017
Test Date(s):	August 23 to September 10, 2017
Equipment Category :	DSS
Antenna Gain:	GSM850: 0.5dBi PCS1900: 0.8dBi Bluetooth: 1.0dBi
Antenna Type:	BT: Monopole antenna GSM: PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Max. Output Power:	1.029dBm
Number of Channels:	GSM 850: 124CH PCS1900: 299CH Bluetooth: 79CH
Port:	USB Port, Earphone Port
Input Power:	Adapter: Model: HWT-2.5W-5050G Input: AC100-240V~50/60Hz,100mA Output: DC 5.0V,500mA

Battery:

Spec: 3.7V, 2000mAh, 7.4Wh

Trade Name : Kenxinda

GPRS/ EGPRS Multi-slot class 8/10/12

FCC ID: ZSHK6900

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge& Restricted Band and Radiated Emissions& Restricted Band	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached PIFA antenna for GSM/PCS, the gain is 0.5dBi for GSM850, the gain is 0.8dBi for PCS1900.

A permanently attached Monopole antenna for Bluetooth, the gain is 1.0dBi for Bluetooth.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	23 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	September 04, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.606	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.605	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.604	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.002	0.895	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.887	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.887	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.874	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.873	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.872	Pass
	Adjacency Channel	2479			


Test Plots

Channel Separation measurement result





8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	23 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	September 04, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW $\geq$ 1% of the 20 dB bandwidth - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Measurement result

Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	0.9030	0.8424
	Mid	2441	0.9037	0.8399
	High	2480	0.9274	0.8388
$\pi/4$ DQPSK	Low	2402	1.332	1.1905
	Mid	2441	1.330	1.1854
	High	2480	1.330	1.1875
8-DPSK	Low	2402	1.318	1.2025
	Mid	2441	1.315	1.2046
	High	2480	1.307	1.1975


Test Plots

20dB Bandwidth measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	23 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	September 04, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☒
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☒
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☐

Test Setup	 Spectrum Analyzer EUT
------------	--

Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW $>$ the 20 dB bandwidth of the emission being measured - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.
----------------	---

	- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Peak Output Power measurement result


Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	-0.640	1000	Pass
		Mid	2441	-0.451	1000	Pass
		High	2480	-0.715	1000	Pass
	$\pi/4$ DQPSK	Low	2402	0.715	125	Pass
		Mid	2441	0.980	125	Pass
		High	2480	-0.761	125	Pass
	8-DPSK	Low	2402	0.653	125	Pass
		Mid	2441	1.029	125	Pass
		High	2480	-0.572	125	Pass

Test Plots


Output Power measurement result




GFSK Output power - Low CH 2402




GFSK Output power - Mid CH 2441




GFSK Output power - High CH 2480




$\pi/4$ DQPSK Output power - Low CH 2402




$\pi/4$ DQPSK Output power - Mid CH 2441




$\pi/4$ DQPSK Output power - High CH 2480



8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	23 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	September 04, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz $\geq$ 15 channels	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW $\geq$ 1% of the span - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	23 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	September 04, 2017
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.910	310.400	400	Pass
		Mid	2.940	313.600	400	Pass
		High	2.920	311.467	400	Pass
	π /4 DQPSK	Low	2.920	311.467	400	Pass
		Mid	2.920	311.467	400	Pass
		High	2.910	310.400	400	Pass
	8-DPSK	Low	2.910	310.400	400	Pass
		Mid	2.910	310.400	400	Pass
		High	2.920	311.467	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						


Test Plots

Dwell Time measurement result






8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge & Restricted Band

Temperature	23 °C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	August 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. □	☒

Test Setup	
------------	--


Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,
----------------	--

	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail



Test Data ☐ Yes ☒ N/A
Test Plot ☒ Yes (See below) ☐ N/A

Test Plots

GFSK Mode:



Note: Both Horizontal and vertical polarities were investigated.



GFSK-Left Side-PK

Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)



Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV

GFSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.

$\pi/4$ DQPSK Mode:




$\pi/4$ DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz

$\pi/4$ DQPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz





Note: (no need if PK value less than the AV limit)

$\pi/4$ DQPSK-Hopping Left-AV

$\pi/4$ DQPSK-Hopping Right-AV

Note: Both Horizontal and vertical polarities were investigated.




$\pi/4$ DQPSK-Left Side-PK

Note: F1 is frequency 2400MHz

$\pi/4$ DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz




Note: (no need if PK value less than the AV limit)

$\pi/4$ DQPSK-Left Side-AV


$\pi/4$ DQPSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.

8-DPSK Mode:




Note: Both Horizontal and vertical polarities were investigated.




8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz



8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



8DPSK-Left Side-AV

Note: (no need if PK value less than the AV limit)

8DPSK-Right Side-AV


Note: Both Horizontal and vertical polarities were investigated.

6.8 AC Power Line Conducted Emissions

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1024mbar
Test date :	August 24, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report	17070655-FCC-R2
Page	38 of 67

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode:	Bluetooth Mode
-------------------	-----------------------




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1695	41.79	QP	10.03	51.82	64.98	-13.16
2	L1	0.1695	26.57	AVG	10.03	36.60	54.98	-18.38
3	L1	0.5595	29.11	QP	10.03	39.14	56.00	-16.86
4	L1	0.5595	8.27	AVG	10.03	18.30	46.00	-27.70
5	L1	1.1172	26.08	QP	10.03	36.11	56.00	-19.89
6	L1	1.1172	14.37	AVG	10.03	24.40	46.00	-21.60
7	L1	2.4042	27.27	QP	10.05	37.32	56.00	-18.68
8	L1	2.4042	10.11	AVG	10.05	20.16	46.00	-25.84
9	L1	3.9126	23.20	QP	10.07	33.27	56.00	-22.73
10	L1	3.9126	7.19	AVG	10.07	17.26	46.00	-28.74
11	L1	5.7807	20.64	QP	10.09	30.73	60.00	-29.27
12	L1	5.7807	3.93	AVG	10.09	14.02	50.00	-35.98

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1695	45.29	QP	10.02	55.31	64.98	-9.67
2	N	0.1695	31.91	AVG	10.02	41.93	54.98	-13.05
3	N	0.2280	40.35	QP	10.02	50.37	62.52	-12.15
4	N	0.2280	25.19	AVG	10.02	35.21	52.52	-17.31
5	N	0.4503	33.88	QP	10.02	43.90	56.87	-12.97
6	N	0.4503	21.56	AVG	10.02	31.58	46.87	-15.29
7	N	0.9846	24.48	QP	10.03	34.51	56.00	-21.49
8	N	0.9846	5.15	AVG	10.03	15.18	46.00	-30.82
9	N	2.4900	26.11	QP	10.04	36.15	56.00	-19.85
10	N	2.4900	3.37	AVG	10.04	13.41	46.00	-32.59
11	N	7.1067	19.46	QP	10.10	29.56	60.00	-30.44
12	N	7.1067	3.42	AVG	10.10	13.52	50.00	-36.48

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1677	48.34	QP	10.03	58.37	65.07	-6.70
2	L1	0.1677	27.54	AVG	10.03	37.57	55.07	-17.50
3	L1	0.2514	45.07	QP	10.03	55.10	61.71	-6.61
4	L1	0.2514	24.62	AVG	10.03	34.65	51.71	-17.06
5	L1	0.3528	38.63	QP	10.03	48.66	58.90	-10.24
6	L1	0.3528	19.47	AVG	10.03	29.50	48.90	-19.40
7	L1	1.0080	30.42	QP	10.03	40.45	56.00	-15.55
8	L1	1.0080	18.08	AVG	10.03	28.11	46.00	-17.89
9	L1	1.6203	31.75	QP	10.04	41.79	56.00	-14.21
10	L1	1.6203	20.33	AVG	10.04	30.37	46.00	-15.63
11	L1	2.9580	29.75	QP	10.05	39.80	56.00	-16.20
12	L1	2.9580	19.85	AVG	10.05	29.90	46.00	-16.10

Test Mode:	Bluetooth Mode
-------------------	-----------------------



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1656	40.01	QP	10.02	50.03	65.18	-15.15
2	N	0.1656	23.98	AVG	10.02	34.00	55.18	-21.18
3	N	0.4386	34.70	QP	10.02	44.72	57.09	-12.37
4	N	0.4386	26.14	AVG	10.02	36.16	47.09	-10.93
5	N	0.5478	33.26	QP	10.02	43.28	56.00	-12.72
6	N	0.5478	25.81	AVG	10.02	35.83	46.00	-10.17
7	N	0.9885	32.99	QP	10.03	43.02	56.00	-12.98
8	N	0.9885	26.22	AVG	10.03	36.25	46.00	-9.75
9	N	2.3067	31.06	QP	10.04	41.10	56.00	-14.90
10	N	2.3067	21.23	AVG	10.04	31.27	46.00	-14.73
11	N	3.7332	29.72	QP	10.06	39.78	56.00	-16.22
12	N	3.7332	17.42	AVG	10.06	27.48	46.00	-18.52


6.9 Radiated Emissions & Restricted Band

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1024mbar
Test date :	August 24, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	☒																
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>0.009~0.490</td><td>2400/F(KHz)</td></tr><tr><td>0.490~1.705</td><td>24000/F(KHz)</td></tr><tr><td>1.705~30.0</td><td>30</td></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216 960	200	Above 960	500
		Frequency range (MHz)		Field Strength (µV/m)															
		0.009~0.490		2400/F(KHz)															
		0.490~1.705		24000/F(KHz)															
		1.705~30.0		30															
		30 – 88		100															
		88 – 216		150															
		216 960		200															
Above 960	500																		

Test Setup	 The diagram illustrates the test setup for radiated emissions. It shows an Equipment Under Test (EUT) placed on a stand that is 0.8 meters high. A Loop Antenna is positioned 3 meters away from the EUT. The entire setup is on a Ground Plane. An RF Test Receiver is connected to the antenna.
------------	---

	
Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. - The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Test Result:

Test Mode:	Transmitting Mode
------------	-------------------

Frequency range: 9KHz - 30MHz

Freq.	Detection	Factor	Reading	Result	Limit@3m	Margin
(MHz)	value	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Test Mode: Bluetooth Mode

30MHz -1GHz

80.0 dBuV/m




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()
1	H	35.2512	26.40	peak	17.37	22.25	0.76	22.28	40.00	-17.72	200	173
2	H	76.5121	28.91	peak	7.67	22.41	0.99	15.16	40.00	-24.84	100	289
3	H	99.5281	29.56	peak	10.29	22.32	1.11	18.64	43.50	-24.86	100	30
4	H	208.5803	28.39	peak	11.98	22.36	1.57	19.58	43.50	-23.92	100	319
5	H	296.1836	29.10	peak	13.43	22.29	1.78	22.02	46.00	-23.98	100	54
6	H	790.6188	28.53	peak	21.29	21.17	2.94	31.59	46.00	-14.41	100	33

30MHz -1GHz

80.0 dBuV/m



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	31.9546	30.50	peak	19.89	22.27	0.67	28.79	40.00	-11.21	100	75
2	V	47.4918	40.88	peak	9.50	22.33	0.77	28.82	40.00	-11.18	100	182
3	V	105.2718	33.71	peak	11.32	22.33	1.15	23.85	43.50	-19.65	100	35
4	V	132.2206	31.35	peak	13.11	22.39	1.22	23.29	43.50	-20.21	200	339
5	V	248.5519	40.34	peak	11.42	22.29	1.70	31.17	46.00	-14.83	100	298
6	V	322.1886	30.72	peak	14.07	22.23	1.90	24.46	46.00	-21.54	100	186

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel: $\pi/4$ DQPSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4804	39.25	AV	V	33.39	7.22	48.46	31.4	54	-22.6
4804	38.87	AV	H	33.39	7.22	48.46	31.02	54	-22.98
4804	47.95	PK	V	33.39	7.22	48.46	40.1	74	-33.9
4804	45.62	PK	H	33.39	7.22	48.46	37.77	74	-36.23
8191	26.13	AV	V	37.89	7.3	47.29	24.03	54	-29.97
8191	25.92	AV	H	37.89	7.3	47.29	23.82	54	-30.18
8191	44.17	PK	V	37.89	7.3	47.29	42.07	74	-31.93
8191	41.16	PK	H	37.89	7.3	47.29	39.06	74	-34.94

Middle Channel: 8-DPSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4882	40.17	AV	V	33.62	7.53	48.36	32.96	54	-21.04
4882	39.68	AV	H	33.62	7.53	48.36	32.47	54	-21.53
4882	48.31	PK	V	33.62	7.53	48.36	41.1	74	-32.9
4882	47.22	PK	H	33.62	7.53	48.36	40.01	74	-33.99
12468	25.55	AV	V	40.44	13.42	46.15	33.26	54	-20.74
12468	23.77	AV	H	40.44	13.42	46.15	31.48	54	-22.52
12468	43.11	PK	V	40.44	13.42	46.15	50.82	74	-23.18
12468	41.63	PK	H	40.44	13.42	46.15	49.34	74	-24.66

High Channel: 8-DPSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	39.64	AV	V	33.89	7.86	48.31	33.08	54	-20.92
4960	37.19	AV	H	33.89	7.86	48.31	30.63	54	-23.37
4960	48.26	PK	V	33.89	7.86	48.31	41.7	74	-32.3
4960	47.82	PK	H	33.89	7.86	48.31	41.26	74	-32.74
17802	24.48	AV	V	43.11	19.14	44.2	42.53	54	-11.47
17802	23.63	AV	H	43.11	19.14	44.2	41.68	54	-12.32
17802	42.4	PK	V	43.11	19.14	44.2	60.45	74	-13.55
17802	40.98	PK	H	43.11	19.14	44.2	59.03	74	-14.97

Note:

- 1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
- 4, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.


Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	☒
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	☒
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	☒
ISN	ISN T800	34373	09/24/2016	09/23/2017	☐
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	☒
Power Splitter	1#	1#	08/31/2016	08/30/2017	☒
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☒
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	☒
Horn Antenna	BBHA9170	3145226D1	09/28/2016	09/27/2017	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☒
Active Antenna (9kHz-30MHz)	AL-130	121031	10/13/2016	10/12/2017	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☒
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter View



EUT - Front View



EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo


Cover Off - Top View 1



Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard without button - Front View




Mainboard with shielding - Rear View




Mainboard without shielding - Rear View




LCD - Front View




LCD – Rear View




BT - Antenna View



GSM - Antenna View



Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
SHENZHEN KENXINDA TECHNOLOGY CO.,LTD	Adapter	HWT-2.5W-5050G	N/A
SHENZHEN KENXINDA TECHNOLOGY CO.,LTD	headset	K6900	N/A
Agilent	Wireless Connectivity Test Set	N4010A	N/A
OEM	omnidirectional antenna	AntSuck	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A