

# **SAR Test Report**

Product Name: GSM MOBILE PHONE

Model No. : S-250

FCC ID : ZSHS-250

Applicant: SHENZHEN KENXINDA TECHNOLOGY CO.,LTD

Address: 18TH FLOOR, FUCHUN ORIENT BUILDING, SHENNAN

AV 7006, FUTIAN, SHENZHEN, P.R.CHINA

Date of Receipt: 03/11/2011

Date of Test : 06/11/2011

Issued Date : 08/11/2011

Report No. : 11BS012R-HP-US-P03V01

Report Version : V1.1

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.



# **Test Report Certification**

Issued Date: 08/11/2011

Report No.: 11BS012R-HP-US-P03V01

# QuieTek

Product Name : GSM MOBILE PHONE

Applicant : SHENZHEN KENXINDA TECHNOLOGY CO.,LTD

Address : 18TH FLOOR, FUCHUN ORIENT BUILDING, SHENNAN AV 7006,

FUTIAN, SHENZHEN, P.R.CHINA

Manufacturer : SHENZHEN KENXINDA TECHNOLOGY CO., LTD BAO'AN BRANCH

Address : 1-6 FLOOR, NO.105 WORK SHOP&1-5 FLOOR, NO.104 WORK

SHOP, XINWEIHUANING ROAD, DALANG COMMUNITY, DALANG

STREET, BAO'AN DISTRICT, SHENZHEN, P.R.CHINA

Model No. : S-250

FCC ID : ZSHS-250

Brand Name : SEFTON

EUT Voltage : DC 3.7V

Applicable Standard FCC Oet65 Supplement C June 2001

IEEE Std. 1528-2003,47CFR § 2.1093

Test Result : Max. SAR Measurement (1g)

Head: 0.556 W/kg

Body: 1.110 W/kg

Performed Location : Suzhou EMC Laboratory

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech

Development Zone., Suzhou, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098

FCC Registration Number: 800392

Documented By

(Engineering ADM: Alice Ni)

Reviewed By :

(Engineering Supervisor: Robin Wu)

Approved By : Marlinchen

(Engineering Manager: Marlin Chen)



Norway

## **Laboratory Information**

We, **QuieTek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C. : BSMI, NCC, TAF

Nemko, DNV

Germany : TUV Rheinland

USA : FCC, NVLAP

Japan : VCCI

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site: <a href="http://www.quietek.com/tw/ctg/cts/accreditations.htm">http://www.quietek.com/tw/ctg/cts/accreditations.htm</a>
The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site: <a href="http://www.quietek.com/">http://www.quietek.com/</a>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

#### **HsinChu Testing Laboratory:**







#### **LinKou Testing Laboratory:**







#### Suzhou (China) Testing Laboratory:









# TABLE OF CONTENTS

| Description  | Page |
|--|------|
| 1. General Information   | 6    |
| 1.1. EUT Description   | 6    |
| 1.2. Test Environment  | 8    |
| 2. SAR Measurement System                                      | 9    |
| 2.1. DASY5 System Description                                  | 9    |
| 2.1.1. Applications  | 10   |
| 2.1.2. Area Scans  | 10   |
| 2.1.3. Zoom Scan (Cube Scan Averaging)                         | 10   |
| 2.1.4. Uncertainty of Inter-/Extrapolation and Averaging       | 10   |
| 2.2. DASY5 E-Field Probe                                       | 11   |
| 2.2.1. Isotropic E-Field Probe Specification                   | 11   |
| 2.3. Boundary Detection Unit and Probe Mounting Device         | 12   |
| 2.4. DATA Acquisition Electronics (DAE) and Measurement Server | 12   |
| 2.5. Robot   | 13   |
| 2.6. Light Beam Unit   | 13   |
| 2.7. Device Holder   |      |
| 2.8. SAM Twin Phantom  | 14   |
| 3. Tissue Simulating Liquid                                    | 15   |
| 3.1. The composition of the tissue simulating liquid           | 15   |
| 3.2. Tissue Calibration Result                                 | 16   |
| 3.3. Tissue Dielectric Parameters for Head and Body Phantoms   | 17   |
| 4. SAR Measurement Procedure                                   | 18   |
| 4.1. SAR System Validation                                     | 18   |
| 4.1.1. Validation Dipoles                                      | 18   |
| 4.1.2. Validation Result                                       | 19   |
| 4.2. SAR Measurement Procedure                                 | 20   |
| 5. SAR Exposure Limits   | 21   |
| 6. Test Equipment List   | 22   |
| 7. Measurement Uncertainty                                     | 27   |
| 8. Conducted Power Measurement                                 | 28   |
| 9. Test Results  | 28   |



| 9.1.   | SAR Test Results Summary                        | 29 |
|--------|---|----|
| Append | dix A. SAR System Validation Data               | 34 |
| Append | dix B. SAR measurement Data                     | 38 |
| Append | dix C. Test Setup Photographs & EUT Photographs | 62 |
| Append | dix D. Probe Calibration Data                   | 69 |
| Append | dix E. Dipole Calibration Data                  | 76 |
| Append | dix F. DAE Calibration Data                     | 94 |



# 1. General Information

# 1.1. EUT Description

| Product Name            | GSM MOBILE PHONE                              |  |
|-------------------------|---|--|
| Model No.               | S-250   |  |
| Hardware Version        | MP2.0   |  |
| Software Version        | PAC_6620_SL71_A36620_K082_M10_SL71_V011_LAN(A |  |
|                         | 6)  |  |
| Device Category         | Portable                                      |  |
| RF Exposure Environment | Uncontrolled                                  |  |
| Antenna Type            | Internal                                      |  |
| 2G                      |   |  |
| Support Band            | GSM850/PCS1900                                |  |
| GPRS Type               | Class B                                       |  |
| GPRS Class              | Class 10                                      |  |
| Tx Frequency Range      | GSM 850: 824~849MHz                           |  |
|                         | PCS 1900: 1850~1910MHz                        |  |
| Rx Frequency Range      | GSM 850: 869~894MHz                           |  |
|                         | PCS 1900: 1930~1990MHz                        |  |
| Release Version         | R99   |  |
| Type of modulation      | GMSK for GSM/GPRS                             |  |
| Antenna Gain            | 1dBi  |  |
| Bluetooth               |   |  |
| Bluetooth Frequency     | 2402~2480MHz                                  |  |
| Type of modulation      | FHSS  |  |
| Data Rate               | 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK) |  |
| Antenna Gain            | 1dBi  |  |
| Components              |   |  |
| Headset Model Number    | N/A   |  |
| Battery                 | Brand name: KENXINDA                          |  |
|                         | Model No. N/A                                 |  |
|                         | Voltage and Capacitance: DC 3.7V 900mAh       |  |
| Adapter                 | Brand name: SEFTON                            |  |
|                         | Model No. HWT-2.5W-5050G                      |  |
|                         | Input: AC 100-240V 50/60Hz                    |  |
|                         | Output: DC 5.0V 500mAh                        |  |
| Max. Output Power       | GSM850: 31.37 dBm                             |  |

Page: 6 of 98



| (Avg. Burst Power) | PCS1900: 26.87 dBm       |
|--------------------|--------------------------|
| Max. Output Power  | GSM850: 30.25 dBm- ERP   |
| (Radiated)         | PCS1900: 28.56 dBm- EIRP |



# 1.2. Test Procedure

| 1 | Setup the EUT and simulators as shown on above.                                |
|---|--|
| 2 | Turn on the power of all equipment.  |
| 3 | EUT communicate with CMU 200, and test them respectively at GSM 850 & PCS1900. |

# 1.3. Test Environment


Ambient conditions in the laboratory:

| Items            | Required | Actual  |
|------------------|----------|---------|
| Temperature (°C) | 18-25    | 21.5± 2 |
| Humidity (%RH)   | 30-70    | 52      |



# 2. SAR Measurement System

# 2.1. DASY5 System Description



The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.



## 2.1.1. Applications

Predefined procedures and evaluations for automated compliance testing with all worldwide standards, e.g., IEEE 1528, OET 65, IEC 62209-1, IEC 62209-2, EN 50360, EN 50383 and others.

#### 2.1.2. Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm<sup>2</sup> step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE 1528-2003, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan).

# 2.1.3. Zoom Scan (Cube Scan Averaging)

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications utilize a physical step of 7x7x7 (5mmx5mmx5mm) providing a volume of 30mm in the X & Y axis, and 30mm in the Z axis.

## 2.1.4. Uncertainty of Inter-/Extrapolation and Averaging

In order to evaluate the uncertainty of the interpolation, extrapolation and averaged SAR calculation algorithms of the Postprocessor, DASY5 allows the generation of measurement grids which are artificially predefined by analytically based test functions. Therefore, the grids of area scans and zoom scans can be filled with uncertainty test data, according to the SAR benchmark functions of IEEE 1528. The three analytical functions shown in equations as below are used to describe the possible range of the expected SAR distributions for the tested handsets. The field gradients are covered by the spatially flat distribution f1, the spatially steep distribution f3 and f2 accounts for H-field cancellation on the phantom/tissue surface.

Page: 10 of 98



$$f_1(x,y,z) = Ae^{-\frac{z}{2a}}\cos^2\left(\frac{\pi}{2}\frac{\sqrt{x'^2 + y'^2}}{5a}\right)$$

$$f_2(x,y,z) = Ae^{-\frac{z}{a}}\frac{a^2}{a^2 + x'^2}\left(3 - e^{-\frac{2z}{a}}\right)\cos^2\left(\frac{\pi}{2}\frac{y'}{3a}\right)$$

$$f_3(x,y,z) = A\frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2}\left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a+2z)^2}\right)$$

#### 2.2. DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 62209-1, IEC 62209, etc.) under ISO 17025. The calibration data are in Appendix D.

## 2.2.1. Isotropic E-Field Probe Specification

| Model         | EX3DV4  |                    |  |
|---------------|---|--------------------|--|
| Construction  | Symmetrical design with triangular core Built-in s charges PEEK enclosure material (resistant to c DGBE)  | 5 5                |  |
| Frequency     | 10 MHz to 6 GHz<br>Linearity: ± 0.2 dB (30 MHz to 6 GHz)  |                    |  |
| Directivity   | ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)  | /                  |  |
| Dynamic Range | 10 μW/g to 100 mW/g<br>Linearity: ± 0.2 dB (noise: typically < 1 μW/g)  |                    |  |
| Dimensions    | Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm                  |                    |  |
| Application   | High precision dosimetric measurements in ar (e.g., very strong gradient fields). Only pr compliance testing for frequencies up to 6 GHz v 30%. | robe which enables |  |



## 2.3. Boundary Detection Unit and Probe Mounting Device

The DASY5 probes use a precise connector and an additional holder for the probe, consisting of a plastic tube and a flexible silicon ring to center the probe. The connector at the DAE is flexibly mounted and held in the default position with magnets and springs. Two switching systems in the connector mount detect frontal and lateral probe collisions and trigger the necessary software response.




## 2.4. DATA Acquisition Electronics (DAE) and Measurement Server

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit.

Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE4 is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chipdisk and 128MB RAM. The necessary circuits for communication with the DAE electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.





#### 2.5. Robot

The DASY5 system uses the high precision robots TX90 XL type out of the newer series from Stäubli SA (France). For the 6-axis controller DASY5 system, the CS8C robot controller version from Stäubli is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- > Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- ➢ 6-axis controller



# 2.6. Light Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.





#### 2.7. Device Holder

The DASY5 device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY5 device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon r = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



#### 2.8. SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left head
- > Right head
- > Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.



# 3. Tissue Simulating Liquid

# 3.1. The composition of the tissue simulating liquid

| INGREDIENT | 835MHz | 835MHz | 1900MHz | 1900MHz |
|------------|--------|--------|---------|---------|
| (% Weight) | Head   | Body   | Head    | Body    |
| Water      | 40.45  | 52.4   | 54.90   | 40.5    |
| Salt       | 1.45   | 1.40   | 0.18    | 0.50    |
| Sugar      | 57.6   | 45.0   | 0.00    | 58.0    |
| HEC        | 0.40   | 1.00   | 0.00    | 0.50    |
| Preventol  | 0.10   | 0.20   | 0.00    | 0.50    |
| DGBE       | 0.00   | 0.00   | 44.92   | 0.00    |



# 3.2. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY5 Dielectric Probe Kit and Agilent Vector Network Analyzer E5071C

| Head Tissue Simulant Measurement |                  |                       |              |              |  |
|----------------------------------|------------------|-----------------------|--------------|--------------|--|
| Frequency                        | Description      | Dielectric Parameters |              | Tissue Temp. |  |
| [MHz]                            | Description      | e <sub>r</sub>        | σ [s/m]      | [°C]         |  |
| 835 MHz                          | Reference result | 41.50                 | 0.90         | N/A          |  |
|                                  | ± 5% window      | 39.43 to 43.58        | 0.86 to 0.95 | IN/A         |  |
|                                  | 06-11-2011       | 40.80                 | 0.88         | 21.0         |  |
|                                  |                  |                       |              |              |  |

| Body Tissue Simulant Measurement |                  |                |              |              |  |
|----------------------------------|------------------|----------------|--------------|--------------|--|
| Frequency                        | Description      |                | arameters    | Tissue Temp. |  |
| [MHz]                            | Description      | 8 <sub>r</sub> | σ [s/m]      | [°C]         |  |
| 835 MHz                          | Reference result | 55.2           | 0.97         | N/A          |  |
|                                  | ± 5% window      | 52.44 to 57.96 | 0.92 to 1.02 | IN/A         |  |
|                                  | 06-11-2011       | 53.70          | 0.99         | 21.0         |  |
|                                  |                  |                |              |              |  |

| Head Tissue Simulant Measurement |                  |                       |              |              |  |
|----------------------------------|------------------|-----------------------|--------------|--------------|--|
| Frequency                        | Description      | Dielectric Parameters |              | Tissue Temp. |  |
| [MHz]                            | Description      | 13                    | σ [s/m]      | [°C]         |  |
|                                  | Reference result | 40.0                  | 1.40         | N/A          |  |
| 1900 MHz                         | ± 5% window      | 38.00 to 42.00        | 1.33 to 1.47 | IN/A         |  |
|                                  | 06-11-2011       | 38.70                 | 1.47         | 21.0         |  |
|                                  |                  |                       |              |              |  |

| Body Tissue Simulant Measurement |                  |                       |              |              |  |
|----------------------------------|------------------|-----------------------|--------------|--------------|--|
| Frequency                        | Description      | Dielectric Parameters |              | Tissue Temp. |  |
| [MHz]                            | Description      | ε <sub>r</sub>        | σ [s/m]      | [°C]         |  |
| 1900 MHz                         | Reference result | 53.3                  | 1.52         | N/A          |  |
|                                  | ± 5% window      | 50.64 to 55.97        | 1.44 to 1.60 | IN/A         |  |
|                                  | 06-11-2011       | 52.50                 | 1.56         | 21.0         |  |
|                                  |                  |                       |              | •            |  |



## 3.3. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

| Target Frequency | He             | ad      | Во             | dy      |
|------------------|----------------|---------|----------------|---------|
| (MHz)            | $\epsilon_{r}$ | σ (S/m) | ٤ <sub>r</sub> | σ (S/m) |
| 150              | 52.3           | 0.76    | 61.9           | 0.80    |
| 300              | 45.3           | 0.87    | 58.2           | 0.92    |
| 450              | 43.5           | 0.87    | 56.7           | 0.94    |
| 835              | 41.5           | 0.90    | 55.2           | 0.97    |
| 900              | 41.5           | 0.97    | 55.0           | 1.05    |
| 915              | 41.5           | 0.98    | 55.0           | 1.06    |
| 1450             | 40.5           | 1.20    | 54.0           | 1.30    |
| 1610             | 40.3           | 1.29    | 53.8           | 1.40    |
| 1800 – 2000      | 40.0           | 1.40    | 53.3           | 1.52    |
| 2450             | 39.2           | 1.80    | 52.7           | 1.95    |
| 3000             | 38.5           | 2.40    | 52.0           | 2.73    |
| 5800             | 35.3           | 5.27    | 48.2           | 6.00    |


( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho$  = 1000 kg/m³)



## 4. SAR Measurement Procedure

# 4.1. SAR System Validation

# 4.1.1. Validation Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles.

| Frequency | L (mm) | h (mm) | d (mm) |
|-----------|--------|--------|--------|
| 835MHz    | 161.0  | 89.8   | 3.6    |
| 1900MHz   | 68.0   | 39.5   | 3.6    |



## 4.1.2. Validation Result

# Validation Kit: D835V2-SN 4d094

| Freque<br>[MH: |     | Description                      | SAR [w/kg]<br>1g      | SAR [w/kg]<br>10g    | Tissue Temp.<br>[°C] |
|----------------|-----|----------------------------------|-----------------------|----------------------|----------------------|
| 835 M          | lHz | Reference result<br>± 10% window | 9.70<br>8.73 to 10.67 | 6.30<br>5.67 to 6.93 | N/A                  |
|                |     | 06-11-2011                       | 9.92                  | 6.48                 | 21.0                 |

# Validation Kit: D1900V2-SN 5d121

| Frequency<br>[MHz] | Description                      | SAR [w/kg]<br>1g       | SAR [w/kg]<br>10g      | Tissue Temp.<br>[°C] |
|--------------------|----------------------------------|------------------------|------------------------|----------------------|
| 1900 MHz           | Reference result<br>± 10% window | 39.8<br>35.82 to 43.78 | 21.1<br>18.99 to 23.21 | N/A                  |
|                    | 06-11-2011                       | 42.40                  | 21.76                  | 21.0                 |

Note: All SAR values are normalized to 1W forward power.

# System Performance Check at 835MHz &1900MHz for Body

# Validation Kit: D835V2-SN 4d094

| Frequency<br>[MHz] | Description                      | SAR [w/kg]<br>1g      | SAR [w/kg]<br>10g    | Tissue Temp.<br>[°C] |
|--------------------|----------------------------------|-----------------------|----------------------|----------------------|
| 835 MHz            | Reference result<br>± 10% window | 9.90<br>8.91 to 10.89 | 6.53<br>5.88 to 7.18 | N/A                  |
|                    | 06-11-2011                       | 9.88                  | 6.40                 | 21.0                 |

## Validation Kit: D1900V2-SN 5d121

| Frequency<br>[MHz] | Description                      | SAR [w/kg]<br>1g       | SAR [w/kg]<br>10g      | Tissue Temp. [°C] |
|--------------------|----------------------------------|------------------------|------------------------|-------------------|
| 1900 MHz           | Reference result<br>± 10% window | 41.4<br>37.26 to 45.54 | 22.3<br>20.07 to 24.53 | N/A               |
|                    | 06-11-2011                       | 42.80                  | 21.72                  | 21.0              |

Note: All SAR values are normalized to 1W forward power.



#### 4.2. SAR Measurement Procedure

The DASY5 calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

σ: represents the simulated tissue conductivity

p: represents the tissue density

The EUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm<sup>2</sup>) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm<sup>3</sup>).



# 5. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 "Uncontrolled Environments" limits. These limits apply to a location which is deemed as "Uncontrolled Environment" which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

| Type Exposure  | Uncontrolled      |
|--|-------------------|
|  | Environment Limit |
| Spatial Peak SAR (1g cube tissue for brain or body)      | 1.60 W/kg         |
| Spatial Average SAR (whole body)                         | 0.08 W/kg         |
| Spatial Peak SAR (10g for hands, feet, ankles and wrist) | 4.00 W/kg         |



# 6. Test Equipment List

| Instrument             | Manufacturer | Model No.     | Serial No.      | Cali. Due Date |
|------------------------|--------------|---------------|-----------------|----------------|
| Stäubli Robot TX60L    | Stäubli      | TX60L         | F10/5C90A1/A/01 | only once      |
| Controller             | Stäubli      | SP1           | S-0034          | only once      |
| Dipole Validation Kits | Speag        | D835V2        | 4d094           | 2012.03.15     |
| Dipole Validation Kits | Speag        | D1900V2       | 5d121           | 2012.03.23     |
| SAM Twin Phantom       | Speag        | SAM           | TP-1561/1562    | N/A            |
| Device Holder          | Speag        | SD 000 H01 HA | N/A             | N/A            |
| Data                   | Speag        | DAE4          | 1220            | 2012.12.03     |
| Acquisition Electronic |              |               |                 |                |
| E-Field Probe          | Speag        | EX3DV4        | 3710            | 2012.02.25     |
| SAR Software           | Speag        | DASY5         | V5.2 Build 162  | N/A            |
| Power Amplifier        | Mini-Circuit | ZVA-183-S+    | N657400950      | N/A            |
| Directional Coupler    | Agilent      | 778D          | 20160           | N/A            |
| Universal Radio        | R&S          | CMU 200       | 117088          | 2012.04.29     |
| Communication Tester   |              |               |                 |                |
| Vector Network         | Agilent      | E5071C        | MY48367267      | 2012.04.10     |
| Signal Generator       | Agilent      | E4438C        | MY49070163      | 2012.04.23     |
| Power Meter            | Anritsu      | ML2495A       | 0905006         | 2012.01.12     |
| Wide Bandwidth Sensor  | Anritsu      | MA2411B       | 0846014         | 2012.01.12     |

Note: Per KDB 450824 D02 requirements for dipole calibration, QuieTek Lab has adopted two years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:


- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss is within 20% of calibrated measurement (Show below);
- 4. Impedance is within  $5\Omega$  of calibrated measurement (Show below).




# Impedance Plot for D835V2

#### 835 Head

Calibrated impedance: 52.2  $\Omega$ ; Measured impedance: 50.322  $\Omega$  (within  $5\Omega$ )




Calibrated return loss: -29.4 dB; Measured impedance: -27.246 dB (within 20%)






## 835 Body

Calibrated impedance: 48.0  $\Omega$ ; Measured impedance: 48.611  $\Omega$  (within  $5\Omega$ )



Calibrated return loss: -25.5 dB; Measured impedance: -26.333 dB (within 20%)







# Impedance Plot for D1900V2

#### 1900 Head

Calibrated impedance: 50.6  $\Omega$ ; Measured impedance: 51.610  $\Omega$  (within  $5\Omega$ )




Calibrated return loss: -22.7 dB; Measured impedance: -23.651 dB (within 20%)






# 1900 Body

Calibrated impedance: 46.1  $\Omega$ ; Measured impedance: 45.692  $\Omega$  (within  $5\Omega$ )



Calibrated return loss: -21.5 dB; Measured impedance: -20.425 dB (within 20%)





# 7. Measurement Uncertainty

|                         | DASY5 Uncertainty |       |      |      |      |            |        |      |
|-------------------------|-------------------|-------|------|------|------|------------|--------|------|
| Measurement uncertainty |                   |       |      |      |      | / 10 gram. |        |      |
| Error Description       | Uncert.           | Prob. | Div. | (Ci) | (Ci) | Std.       | Std.   | (Vi) |
|                         | value             | Dist. |      | 1g   | 10g  | Unc.       | Unc.   | Veff |
|                         |                   |       |      |      |      | (1g)       | (10g)  |      |
| Measurement System      |                   |       |      |      |      |            |        |      |
| Probe Calibration       | ±6.5%             | N     | 1    | 1    | 1    | ±6.5%      | ±6.5%  | ∞    |
| Axial Isotropy          | ±4.7%             | R     | √3   | 0.7  | 0.7  | ±1.9%      | ±1.9%  | ∞    |
| Hemispherical Isotropy  | ±9.6%             | R     | √3   | 0.7  | 0.7  | ±3.9%      | ±3.9%  | ∞    |
| Boundary Effects        | ±1.0%             | R     | √3   | 1    | 1    | ±0.6%      | ±0.6%  | ∞    |
| Linearity               | ±4.7%             | R     | √3   | 1    | 1    | ±2.7%      | ±2.7%  | ∞    |
| System Detection Limits | ±1.0%             | R     | √3   | 1    | 1    | ±0.6%      | ±0.6%  | ∞    |
| Readout Electronics     | ±0.3%             | N     | 1    | 1    | 1    | ±0.3%      | ±0.3%  | ∞    |
| Response Time           | ±0.8%             | R     | √3   | 1    | 1    | ±0.5%      | ±0.5%  | ∞    |
| Integration Time        | ±2.6%             | R     | √3   | 1    | 1    | ±1.5%      | ±1.5%  | ∞    |
| RF Ambient Noise        | ±3.0%             | R     | √3   | 1    | 1    | ±1.7%      | ±1.7%  | ∞    |
| RF Ambient Reflections  | ±3.0%             | R     | √3   | 1    | 1    | ±1.7%      | ±1.7%  | ∞    |
| Probe Positioner        | ±0.4%             | R     | √3   | 1    | 1    | ±0.2%      | ±0.2%  | ∞    |
| Probe Positioning       | ±2.9%             | R     | √3   | 1    | 1    | ±1.7%      | ±1.7%  | ∞    |
| Max. SAR Eval.          | ±1.0%             | R     | √3   | 1    | 1    | ±0.6%      | ±0.6%  | ∞    |
| Test Sample Related     |                   |       | 1    | 1    |      | •          | •      |      |
| Device Positioning      | ±2.9%             | N     | 1    | 1    | 1    | ±2.9%      | ±2.9%  | 145  |
| Device Holder           | ±3.6%             | N     | 1    | 1    | 1    | ±3.6%      | ±3.6%  | 5    |
| Power Drift             | ±5.0%             | R     | √3   | 1    | 1    | ±2.9%      | ±2.9%  | ∞    |
| Phantom and Setup       |                   | •     | 1    | 1    | •    | 1          | 1      |      |
| Phantom Uncertainty     | ±4.0%             | R     | √3   | 1    | 1    | ±2.3%      | ±2.3%  | ∞    |
| Liquid Conductivity     | . 5 00/           | _     | -    | 0.04 | 0.40 | .4.00/     | .4.00/ |      |
| (target)                | ±5.0%             | R     | √3   | 0.64 | 0.43 | ±1.8%      | ±1.2%  | ∞    |
| Liquid Conductivity     | 10.50/            | N     | 4    | 0.64 | 0.42 | 14.60/     | 14.40/ | ∞    |
| (meas.)                 | ±2.5%             | N     | 1    | 0.64 | 0.43 | ±1.6%      | ±1.1%  | ∞    |
| Liquid Permittivity     | LE 00/            | R     | 19   | 0.6  | 0.49 | ±1.7%      | ±1.4%  | ∞    |
| (target)                | ±5.0%             | П     | √3   | 0.0  | 0.48 | II./ 70    | ±1.470 | ~    |
| Liquid Permittivity     | ±2.5%             | N     | 1    | 0.6  | 0.49 | ±1.5%      | ±1.2%  | ∞    |
| (meas.)                 | 12.0/0            | 11    | '    | 0.0  | 0.43 | ±1.0/0     | ⊥1.∠/0 |      |
| Combined Std. Uncertain | nty               |       |      |      |      | ±11.3%     | ±11.0% | 387  |
| Expanded STD Uncertain  | nty               |       |      |      |      | ±22.5%     | ±22.1% |      |



# 8. Conducted Power Measurement

| Mode   | Frequency (MHz) | Avg. Burst Power | Duty Cycle  | Frame Power |
|--|-----------------|------------------|-------------|-------------|
|  |                 | (dBm)            | Factor (dB) | (dBm)       |
| Maximum Power <s< td=""><td>SIM 1&gt;</td><td></td><td></td><td></td></s<> | SIM 1>          |                  |             |             |
|  | 824.2           | 31.25            | -9          | 22.25       |
| GSM850   | 836.4           | 31.37            | -9          | 22.37       |
|  | 848.6           | 31.28            | -9          | 22.28       |
|  | 824.2           | 30.69            | -6          | 24.69       |
| GPRS850(2 Slot)  | 836.4           | 30.70            | -6          | 24.70       |
|  | 848.6           | 30.62            | -6          | 24.62       |
|  | 1850.2          | 26.87            | -9          | 17.87       |
| PCS1900  | 1880.0          | 26.26            | -9          | 17.26       |
|  | 1909.8          | 26.09            | -9          | 17.09       |
|  | 1850.2          | 27.27            | -6          | 21.27       |
| GPRS1900(2 Slot)   | 1880.0          | 26.82            | -6          | 20.82       |
|  | 1909.8          | 26.58            | -6          | 20.58       |
| Maximum Power <s< td=""><td>SIM 2&gt;</td><td></td><td></td><td></td></s<> | SIM 2>          |                  |             |             |
| GSM850   | 836.4           | 31.34            | -9          | 22.34       |
| PCS1900 1880.0   |                 | 26.24            | -9          | 17.24       |
| Maximum Power <s< td=""><td>SIM 3&gt;</td><td></td><td></td><td></td></s<> | SIM 3>          |                  |             |             |
| GSM850   | 836.4           | 31.31            | -9          | 22.31       |
| PCS1900 1880.0   |                 | 26.22            | -9          | 17.22       |

Note: All SAR testing was done in SIM 1.



#### 9. Test Results

### 9.1. SAR Test Results Summary

#### 9.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE1528, and Body SAR was performed with the device 15mm from the phantom. Body SAR was also performed with the headset attached and without.

# 9.1.2. Body SAR with Headset

Testing with the headset was performed at the position and channels that resulted in the highest body SAR. This testing was performed with GPRS transmitting with 2 uplink timeslots. This operation mode represents the maximum SAR situation, when downloading data via GPRS and listening to music by headset. SAR without the headset attached was significantly higher than with the headset, and also was verified several times and confirmed, so the final test data shown were the worst case without headset.

In the Body SAR test result table, body-worn means display of device down, body-front means display of device up.

#### 9.1.3. Operation Mode

This is a multislot class 10 device capable of 2 uplink timeslots. During the head SAR test, the device was transmitting with 1 uplink timeslot; during the body SAR test, it was transmitting with 2 uplink timeslots. Additionally, this device doesn't support dual transfer mode (DTM).

#### 9.1.4. Co-located SAR

According to KDB 648474, the closest separation between GSM antenna and BT antenna is 5mm, Bluetooth Max peak power is lower than pref and GSM SAR value is less than 1.2W/kg, thus, stand-alone SAR and simultaneous transmission SAR for Bluetooth is not required.

Other reference document: KDB 941225, KDB 447498.



# 9.1.5. Test Result

| Liquid Temperature (°C) : 21.0 ±2 | Depth of Liquid (cm):>15  |
|-----------------------------------|---------------------------|
|                                   |                           |
| Ambient Temperature (°C): 21.5 ±2 | Relative Humidity (%): 52 |
| SAR MEASUREMENT                   |                           |

Product: GSM MOBILE PHONE

Test Mode: GSM850 <SIM 1>

| Test Position | Antenna  | Frequency |       | Frame Power | Power Drift | SAR 1g | Limit |  |  |
|---------------|--|-----------|-------|-------------|-------------|--------|-------|--|--|
| Head          | ead Position Channel MHz (dBm)   |           | (dBm) | (<±0.2)     | (W/kg)      | (W/kg) |       |  |  |
| Left-Cheek    | Fixed  | 128       | 824.2 | 22.25       |             |        | 1.6   |  |  |
| Left-Cheek    | Fixed  | 189       | 836.4 | 22.37       | 0.026       | 0.497  | 1.6   |  |  |
| Left-Cheek    | Fixed  | 251       | 848.6 | 22.28       |             |        | 1.6   |  |  |
| Left-Tilted   | Fixed  | 189       | 836.4 | 22.37       | -0.166      | 0.341  | 1.6   |  |  |
| Right-Cheek   | Fixed  | 128       | 824.2 | 22.25       |             |        | 1.6   |  |  |
| Right-Cheek   | Fixed  | 189       | 836.4 | 22.37       | 0.115       | 0.556  | 1.6   |  |  |
| Right-Cheek   | Fixed  | 251       | 848.6 | 22.28       |             |        | 1.6   |  |  |
| Right-Tilted  | Fixed  | 189       | 836.4 | 22.37       | -0.053      | 0.372  | 1.6   |  |  |
| Test Mode: GS | SM850 <sin< td=""><td>1 2&gt;</td><td></td><td></td><td></td><td></td><td></td></sin<> | 1 2>      |       |             |             |        |       |  |  |
| Right-Cheek   | Fixed  | 189       | 836.4 | 22.34       | 0.070       | 0.552  | 1.6   |  |  |
| Test Mode: GS | Test Mode: GSM850 <sim 3=""></sim>   |           |       |             |             |        |       |  |  |
| Right-Cheek   | Fixed  | 189       | 836.4 | 22.31       | -0.071      | 0.541  | 1.6   |  |  |
|               |  |           |       |             |             |        |       |  |  |

Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional, refer to KDB 941225.



| CVD | MFA:    |      | TIN     |
|-----|---------|------|---------|
| SAR | IVIT A. | אנוכ | - I W I |

Ambient Temperature (°C): 21.5 ±2 Relative Humidity (%): 52

Liquid Temperature (°C): 21.0  $\pm$ 2 Depth of Liquid (cm):>15

Product: GSM MOBILE PHONE

Test Mode: GSM850

| Test Position               | Antenna                  | Frequency |       | Separation<br>Distance | Frame<br>Power | Power<br>Drift | SAR 1g | Limit  |  |
|-----------------------------|--------------------------|-----------|-------|------------------------|----------------|----------------|--------|--------|--|
| Body                        | Position                 | Channel   | MHz   | (mm)                   | (dBm)          | (<±0.2)        | (W/kg) | (W/kg) |  |
| Body-worn                   | Fixed                    | 128       | 824.2 | 15                     | 22.25          | 1              |        | 1.6    |  |
| Body-worn                   | Fixed                    | 189       | 836.4 | 15                     | 22.37          | -0.179         | 0.540  | 1.6    |  |
| Body-worn                   | Fixed                    | 251       | 848.6 | 15                     | 22.28          |                |        | 1.6    |  |
| Test Mode: GPR              | Test Mode: GPRS850 2slot |           |       |                        |                |                |        |        |  |
| Body-worn                   | Fixed                    | 128       | 824.2 | 15                     | 24.69          | -0.108         | 0.671  | 1.6    |  |
| Body-worn                   | Fixed                    | 189       | 836.4 | 15                     | 24.70          | -0.186         | 0.916  | 1.6    |  |
| Body-worn                   | Fixed                    | 251       | 848.6 | 15                     | 24.62          | -0.102         | 1.110  | 1.6    |  |
| Body-front                  | Fixed                    | 189       | 836.4 | 15                     | 24.70          | -0.120         | 0.343  | 1.6    |  |
| Body-worn<br>(With Headset) | Fixed                    | 189       | 836.4 | 15                     | 24.70          | -0.199         | 0.573  | 1.6    |  |

Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional, refer to KDB 941225.



| SAR | M = Z | 112  | REI | MEN | ЛT |
|-----|-------|------|-----|-----|----|
| JAK |       | へいしょ | r   | VII | VI |

Ambient Temperature (°C): 21.5 ±2 Relative Humidity (%): 52

Liquid Temperature (°C): 21.0 ±2 Depth of Liquid (cm):>15

Product: GSM MOBILE PHONE

Test Mode: PCS1900 <SIM 1>

| Test Position   | Antenna  | Frequency |        | Frame Power | Power Drift | SAR 1g | Limit  |  |
|-----------------|--|-----------|--------|-------------|-------------|--------|--------|--|
| Head            | Position   | Channel   | MHz    | (dBm)       | (<±0.2)     | (W/kg) | (W/kg) |  |
| Left-Cheek      | Fixed  | 512       | 1850.2 | 17.87       |             |        | 1.6    |  |
| Left-Cheek      | Fixed  | 661       | 1880.0 | 17.26       | 0.039       | 0.152  | 1.6    |  |
| Left-Cheek      | Fixed  | 810       | 1909.8 | 17.09       |             |        | 1.6    |  |
| Left-Tilted     | Fixed  | 661       | 1880.0 | 17.26       | -0.110      | 0.175  | 1.6    |  |
| Right-Cheek     | Fixed  | 512       | 1850.2 | 17.87       | 1           | 1      | 1.6    |  |
| Right-Cheek     | Fixed  | 661       | 1880.0 | 17.26       | 0.007       | 0.204  | 1.6    |  |
| Right-Cheek     | Fixed  | 810       | 1909.8 | 17.09       | -           | 1      | 1.6    |  |
| Right-Tilted    | Fixed  | 661       | 1880.0 | 17.26       | -0.042      | 0.267  | 1.6    |  |
| Test Mode: PCS1 | 900 <sim 2<="" td=""><td>2&gt;</td><td></td><td></td><td></td><td></td><td></td></sim> | 2>        |        |             |             |        |        |  |
| Right-Tilted    | Fixed  | 661       | 1880.0 | 17.24       | -0.081      | 0.255  | 1.6    |  |
| Test Mode: PCS1 | 900 <sim< td=""><td>3&gt;</td><td></td><td></td><td></td><td></td><td></td></sim<>     | 3>        |        |             |             |        |        |  |
| Right-Tilted    | Fixed  | 661       | 1880.0 | 17.22       | -0.101      | 0.245  | 1.6    |  |

Note: when the 1-g SAR is  $\leq$  0.8 W/kg, testing for low and high channel is optional, refer to KDB 941225.



| SAR | $M = \Delta$ | SII | RFI | MEN             | JТ  |
|-----|--------------|-----|-----|-----------------|-----|
| JAK | IVIL         |     | r   | $v_{I} - \iota$ | v i |

Ambient Temperature (°C): 21.5 ±2 Relative Humidity (%): 52

Liquid Temperature (°C): 21.0  $\pm$ 2 Depth of Liquid (cm):>15

Product: GSM MOBILE PHONE

Test Mode: PCS1900

| Test Position<br>Body       | Antenna<br>Position       | Frequ<br>Channel | ency<br>MHz | Separation Distance (mm) | Frame<br>Power<br>(dBm) | Power<br>Drift<br>(<±0.2) | SAR 1g<br>(W/kg) | Limit<br>(W/kg) |  |
|-----------------------------|---------------------------|------------------|-------------|--------------------------|-------------------------|---------------------------|------------------|-----------------|--|
| Body-worn                   | Fixed                     | 512              | 1850.2      | 15                       | 17.87                   |                           |                  | 1.6             |  |
| Body-worn                   | Fixed                     | 661              | 1880.0      | 15                       | 17.26                   | -0.089                    | 0.177            | 1.6             |  |
| Body-worn                   | Fixed                     | 810              | 1909.8      | 15                       | 17.09                   |                           |                  | 1.6             |  |
| Test Mode: GPRS             | Test Mode: GPRS1900 2slot |                  |             |                          |                         |                           |                  |                 |  |
| Body-worn                   | Fixed                     | 512              | 1850.2      | 15                       | 21.27                   |                           |                  | 1.6             |  |
| Body-worn                   | Fixed                     | 661              | 1880.0      | 15                       | 20.82                   | -0.107                    | 0.302            | 1.6             |  |
| Body-worn                   | Fixed                     | 810              | 1909.8      | 15                       | 20.58                   |                           |                  | 1.6             |  |
| Body-front                  | Fixed                     | 661              | 1880.0      | 15                       | 20.82                   | -0.108                    | 0.074            | 1.6             |  |
| Body-worn<br>(With Headset) | Fixed                     | 661              | 1880.0      | 15                       | 20.82                   | -0.101                    | 0.280            | 1.6             |  |

Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional, refer to KDB 941225.



# Appendix A. SAR System Validation Data

Date/Time: 06-11-2011

Test Laboratory: QuieTek Lab System Check Head 835MHz

**DUT: Dipole 835 MHz D835V2; Type: D835V2** 

Communication System: CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz;  $\sigma = 0.88$  mho/m;  $\epsilon r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

• Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/System Check GSM850 Head/Area Scan (6x19x1): Measurement grid: dx=10mm, dy=10mm, Maximum value of SAR (measured) = 2.56 mW/g

Configuration/System Check GSM850 Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 55.7 V/m; Power Drift = -0.078 dB

Peak SAR (extrapolated) = 3.75 W/kg

**SAR(1 g) = 2.48 mW/g; SAR(10 g) = 1.62 mW/g** Maximum value of SAR (measured) = 2.68 mW/g



0 dB = 2.68 mW/g



Date/Time: 06-11-2011

Test Laboratory: QuieTek Lab System Check Body 835MHz

**DUT: Dipole 835 MHz D835V2; Type: D835V2** 

Communication System: CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz;  $\sigma = 0.99$  mho/m;  $\epsilon r = 53.7$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59


Configuration/System Check GSM835 Body/Area Scan (8x16x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 2.54 mW/g

Configuration/System Check GSM835 Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 52.1 V/m; Power Drift = 0.027 dB

Peak SAR (extrapolated) = 3.76 W/kg

SAR(1 g) = 2.47 mW/g; SAR(10 g) = 1.6 mW/g Maximum value of SAR (measured) = 2.67 mW/g



0 dB = 2.67 mW/g



Date/Time: 06-11-2011

Test Laboratory: QuieTek Lab System Check Head 1900MHz

#### DUT: Dipole 1900 MHz D1900V2; Type: D1900V2

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle: 1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz;  $\sigma = 1.47$  mho/m;  $\epsilon r = 38.7$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59


# Configuration/System Check PCS1900 Head/Area Scan (6x11x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 11.1 mW/g

Configuration/System Check PCS1900 Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 90.8 V/m; Power Drift = -0.099 dB

Peak SAR (extrapolated) = 20 W/kg

SAR(1 g) = 10.6 mW/g; SAR(10 g) = 5.44 mW/g Maximum value of SAR (measured) = 12 mW/g



0 dB = 12mW/g



Test Laboratory: QuieTek Lab System Check Body 1900MHz

DUT: Dipole 1900 MHz D1900V2; Type: D1900V2

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle: 1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz;  $\sigma = 1.56$  mho/m;  $\epsilon r = 52.5$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section; Input Power=250mW

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561

Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59


Configuration/System Check PCS1900 Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 12.1 mW/g

Configuration/System Check PCS1900 Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm, Reference Value = 88.6 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 19.8 W/kg

SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.43 mW/g Maximum value of SAR (measured) = 12 mW/g



0 dB = 12.1 mW/g



### Appendix B. SAR measurement Data

Date/Time: 06-11-2011

Test Laboratory: QuieTek Lab GSM850 Mid Touch-Left

**DUT: GSM Mobile Phone ; Type: S-250** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 40.8$ ;  $\rho = 1000$  kg/m³; Phantom section: Left Section

Ambient temperature (°C): 21.5, Liquid temperature (°C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Left/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.519 mW/g

Configuration/GSM850 Mid Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.663 W/kg

SAR(1 g) = 0.497 mW/g; SAR(10 g) = 0.350 mW/g Maximum value of SAR (measured) = 0.521 mW/g



0 dB = 0.521 mW/g



Test Laboratory: QuieTek Lab

GSM850 Mid Tilt-Left

**DUT: GSM Mobile Phone ; Type: S-250** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 40.8$ ;  $\rho = 1000$  kg/m³; Phantom section: Left Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Tilt-Left/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.361 mW/g

Configuration/GSM850 Mid Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 18.3 V/m; Power Drift = -0.166 dB

Peak SAR (extrapolated) = 0.464 W/kg

SAR(1 g) = 0.341 mW/g; SAR(10 g) = 0.238 mW/g Maximum value of SAR (measured) = 0.363 mW/g



0 dB = 0.363 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Touch-Right

**DUT: GSM Mobile Phone ; Type: S-250** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 40.8$ ;  $\rho = 1000$  kg/m³; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.565 mW/g

Configuration/GSM850 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 16.8 V/m; Power Drift = 0.115 dB

Peak SAR (extrapolated) = 0.765 W/kg

**SAR(1 g) = 0.556 mW/g; SAR(10 g) = 0.389 mW/g** Maximum value of SAR (measured) = 0.590 mW/g



0 dB = 0.590 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Tilt-Right

**DUT: GSM Mobile Phone ; Type: S-250** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 40.8$ ;  $\rho = 1000$  kg/m³; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Tilt-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.351 mW/g

Configuration/GSM850 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 17 V/m; Power Drift = -0.053 dB

Peak SAR (extrapolated) = 0.553 W/kg

**SAR(1 g) = 0.372 mW/g; SAR(10 g) = 0.255 mW/g** Maximum value of SAR (measured) = 0.396 mW/g



0 dB = 0.396 mW/g



Test Laboratory: QuieTek Lab
GSM850 Mid Touch-Right <SIM 2>

DUT: GSM Mobile Phone ; Type: S-250

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 40.8$ ;  $\rho = 1000$  kg/m³; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.562 mW/g

Configuration/GSM850 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 17.7 V/m; Power Drift = 0.070 dB

Peak SAR (extrapolated) = 0.763 W/kg

SAR(1 g) = 0.552 mW/g; SAR(10 g) = 0.387 mW/g Maximum value of SAR (measured) = 0.582 mW/g



0 dB = 0.582 mW/g



Test Laboratory: QuieTek Lab
GSM850 Mid Touch-Right <SIM 3>

DUT: GSM Mobile Phone ; Type: S-250

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.89$  mho/m;  $\epsilon r = 40.8$ ;  $\rho = 1000$  kg/m³; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.843, 4.303, 4.435); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Touch-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.555 mW/g

Configuration/GSM850 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 17.5 V/m; Power Drift = -0.071 dB

Peak SAR (extrapolated) = 0.743 W/kg

SAR(1 g) = 0.541 mW/g; SAR(10 g) = 0.380 mW/g Maximum value of SAR (measured) = 0.571 mW/g



0 dB = 0.571 mW/g



Test Laboratory: QuieTek Lab GSM850 Mid Body-Back

**DUT: GSM Mobile Phone ; Type: S-250** 

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz); Duty Cycle: 1:8.3; Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.99$  mho/m;  $\epsilon r = 53.7$ ;  $\rho = 1000$  kg/m³; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GSM850 Mid Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.576 mW/g

Configuration/GSM850 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 12 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.732 W/kg

**SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.379 mW/g** Maximum value of SAR (measured) = 0.572 mW/g



0 dB = 0.572 mW/g



Test Laboratory: QuieTek Lab GPRS850 Low Body-Back(2up)

DUT: GSM Mobile Phone ; Type: S-250

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 824.2 MHz; Medium parameters used: f = 824.2 MHz;  $\sigma = 0.98$  mho/m;  $\epsilon r = 53.8$ ;  $\rho = 1000$ 

kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1220; Calibrated: 03/12/2010


Phantom: SAM2; Type: SAM; Serial: TP1562

Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Low Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.709 mW/g

Configuration/GPRS850 Low Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 15 V/m; Power Drift = -0.108 dB
Peak SAR (extrapolated) = 0.916 W/kg

SAR(1 g) = 0.671 mW/g; SAR(10 g) = 0.471 mW/g Maximum value of SAR (measured) = 0.712 mW/g



0 dB = 0.712 mW/g



Test Laboratory: QuieTek Lab GPRS850 Mid Body-Back(2up)

DUT: GSM Mobile Phone ; Type: S-250

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.99$  mho/m;  $\epsilon r = 53.7$ ;  $\rho = 1000$ 

kg/m3; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Mid Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 1.01 mW/g

Configuration/GPRS850 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 17.7 V/m; Power Drift = -0.186 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.916 mW/g; SAR(10 g) = 0.644 mW/g Maximum value of SAR (measured) = 0.964 mW/g



0 dB = 0.964 mW/g



Test Laboratory: QuieTek Lab GPRS850 High Body-Back(2up)

DUT: GSM Mobile Phone ; Type: S-250

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2; Frequency: 848.6 MHz; Medium parameters used: f = 848.6 MHz;  $\sigma = 1$  mho/m;  $\epsilon r = 53.6$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 High Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 1.19 mW/g

Configuration/GPRS850 High Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 18.8 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 1.52 W/kg


SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.776 mW/g Maximum value of SAR (measured) = 1.17 mW/g



0 dB = 1.17 mW/g



#### **Z-Axis Plot**





Test Laboratory: QuieTek Lab GPRS850 Mid Body-Front(2up)

DUT: GSM Mobile Phone ; Type: S-250

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.99$  mho/m;  $\epsilon r = 53.7$ ;  $\rho = 1000$ 

kg/m³; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM2; Type: SAM; Serial: TP1562


• Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Mid Body-Front/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.368 mW/g

Configuration/GPRS850 Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 14.1 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.461 W/kg

SAR(1 g) = 0.343 mW/g; SAR(10 g) = 0.243 mW/g Maximum value of SAR (measured) = 0.364 mW/g



0 dB = 0.364 mW/g



Test Laboratory: QuieTek Lab

GPRS850 Mid Body-Back(2up)(with headset)

**DUT: GSM Mobile Phone ; Type: S-250** 

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: GSM850; Duty Cycle: 1:4.2;

Frequency: 836.4 MHz; Medium parameters used: f = 836.4 MHz;  $\sigma = 0.99$  mho/m;  $\epsilon r = 53.7$ ;  $\rho = 1000$ 

kg/m³; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(4.438, 4.985, 5.123); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM2; Type: SAM; Serial: TP1562
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS850 Mid Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.619 mW/g

Configuration/GPRS850 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 13.2 V/m; Power Drift = -0.199 dB

Peak SAR (extrapolated) = 0.795 W/kg

SAR(1 g) = 0.573 mW/g; SAR(10 g) = 0.399 mW/g Maximum value of SAR (measured) = 0.604 mW/g



0 dB = 0.604 mW/g



Test Laboratory: QuieTek Lab
PCS1900 Mid Touch-Left

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.45$  mho/m;  $\epsilon r = 1.45$ 

38.8;  $\rho$  = 1000 kg/m³; Phantom section: Left Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Touch-Left/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.148 mW/g

Configuration/PCS1900 Mid Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 10.6 V/m; Power Drift = 0.039 dB

Peak SAR (extrapolated) = 0.279 W/kg

**SAR(1 g) = 0.152 mW/g; SAR(10 g) = 0.082 mW/g** Maximum value of SAR (measured) = 0.169 mW/g



0 dB = 0.169 mW/g



Test Laboratory: QuieTek Lab

PCS1900 Mid Tilt-Left

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.45$  mho/m;  $\epsilon r =$ 

38.8;  $\rho$  = 1000 kg/m³; Phantom section: Left Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Left/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.169 mW/g

Configuration/PCS1900 Mid Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 11 V/m; Power Drift = -0.110 dB

Peak SAR (extrapolated) = 0.319 W/kg

**SAR(1 g) = 0.175 mW/g; SAR(10 g) = 0.092 mW/g** Maximum value of SAR (measured) = 0.197 mW/g



0 dB = 0.197 mW/g



Test Laboratory: QuieTek Lab PCS1900 Mid Touch-Right

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.45$  mho/m;  $\epsilon r = 38.8$ ;  $\rho = 1000$  kg/m³; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Touch-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.162 mW/g

Configuration/PCS1900 Mid Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 11.3 V/m; Power Drift = 0.007 dB

Peak SAR (extrapolated) = 0.419 W/kg

SAR(1 g) = 0.204 mW/g; SAR(10 g) = 0.102 mW/g Maximum value of SAR (measured) = 0.218 mW/g



0 dB = 0.218 mW/g



Test Laboratory: QuieTek Lab PCS1900 Mid Tilt-Right

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.45$  mho/m;  $\epsilon r = 1.45$ 

38.8;  $\rho$  = 1000 kg/m<sup>3</sup>; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.229 mW/g

Configuration/PCS1900 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 13.4 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 0.532 W/kg

SAR(1 g) = 0.267 mW/g; SAR(10 g) = 0.134 mW/g Maximum value of SAR (measured) = 0.296 mW/g



0 dB = 0.296 mW/g



Test Laboratory: QuieTek Lab
PCS1900 Mid Tilt-Right <SIM 2>

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.45$  mho/m;  $\epsilon r = 1.45$ 

38.8;  $\rho$  = 1000 kg/m<sup>3</sup>; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.238 mW/g

Configuration/PCS1900 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 13.2 V/m; Power Drift = -0.081 dB

Peak SAR (extrapolated) = 0.503 W/kg

SAR(1 g) = 0.255 mW/g; SAR(10 g) = 0.129 mW/g Maximum value of SAR (measured) = 0.285 mW/g



0 dB = 0.285 mW/g



Test Laboratory: QuieTek Lab
PCS1900 Mid Tilt-Right <SIM 3>

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.45$  mho/m;  $\epsilon r = 1.45$ 

38.8;  $\rho$  = 1000 kg/m³; Phantom section: Right Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:


- Probe: EX3DV4 SN3710; ConvF(3.609, 4.015, 4.146); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Tilt-Right/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.223 mW/g

Configuration/PCS1900 Mid Tilt-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 13.2 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.488 W/kg

**SAR(1 g) = 0.245 mW/g; SAR(10 g) = 0.122 mW/g** Maximum value of SAR (measured) = 0.265 mW/g



0 dB = 0.265 mW/g



Test Laboratory: QuieTek Lab PCS1900 Mid Body-Back

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: Generic GSM; Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz);

Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma$  = 1.53 mho/m;  $\epsilon r$  =

52.5;  $\rho$  = 1000 kg/m³; Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0


DASY5 Configuration:

- Probe: EX3DV4 SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1220; Calibrated: 03/12/2010
- Phantom: SAM1; Type: SAM; Serial: TP1561
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/PCS1900 Mid Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.171 mW/g

Configuration/PCS1900 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 10.2 V/m; Power Drift = -0.089 dB
Peak SAR (extrapolated) = 0.293 W/kg

SAR(1 g) = 0.177 mW/g; SAR(10 g) = 0.100 mW/g Maximum value of SAR (measured) = 0.192 mW/g



0 dB = 0.192 mW/g



Test Laboratory: QuieTek Lab GPRS1900 Mid Body-Back(2up)

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: PCS1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.53$  mho/m;  $\epsilon r = 52.5$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


• Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS1900 Mid Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.294 mW/g

Configuration/GPRS1900 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 13.7 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 0.493 W/kg


**SAR(1 g) = 0.302 mW/g; SAR(10 g) = 0.172 mW/g** Maximum value of SAR (measured) = 0.327 mW/g



0 dB = 0.327 mW/g



#### **Z-Axis Plot**





Test Laboratory: QuieTek Lab GPRS1900 Mid Body-Front(2up)

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: PCS1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.53$  mho/m;  $\epsilon r = 52.5$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010


Phantom: SAM1; Type: SAM; Serial: TP1561

Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS1900 Mid Body-Front/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.063 mW/g

Configuration/GPRS1900 Mid Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 6.95 V/m; Power Drift = -0.108 dB
Peak SAR (extrapolated) = 0.123 W/kg

SAR(1 g) = 0.074 mW/g; SAR(10 g) = 0.042 mW/g Maximum value of SAR (measured) = 0.081 mW/g



0 dB = 0.081 mW/g



Test Laboratory: QuieTek Lab

GPRS1900 Mid Body-Back(2up)(with headset)

**DUT: GSM Mobile Phone; Type: S-250** 

Communication System: GPRS/EGPRS-2 Slot; Communication System Band: PCS1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1880 MHz;  $\sigma = 1.53$  mho/m;  $\epsilon r = 52.5$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.5, Liquid temperature ( $^{\circ}$ C): 21.0

DASY5 Configuration:

Probe: EX3DV4 - SN3710; ConvF(4.193, 4.677, 4.833); Calibrated: 25/02/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1220; Calibrated: 03/12/2010

Phantom: SAM1; Type: SAM; Serial: TP1561


Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 59

Configuration/GPRS1900 Mid Body-Back/Area Scan (5x8x1): Measurement grid: dx=20mm, dy=20mm Maximum value of SAR (measured) = 0.279 mW/g

Configuration/GPRS1900 Mid Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm, Reference Value = 12.9 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.473 W/kg

SAR(1 g) = 0.280 mW/g; SAR(10 g) = 0.159 mW/g Maximum value of SAR (measured) = 0.303 mW/g




0 dB = 0.303 mW/g




# **Appendix C. Test Setup Photographs & EUT Photographs**






Left-Cheek Touch



Left-Tilt 15°






Right-Cheek Touch




Right-Tilt 15°






Body SAR Back 15mm



Body SAR Front 15mm






Body SAR Back 15mm with Headset



# Depth of the liquid in the phantom – Zoom in

Note: The position used in the measurements were according to IEEE 1528 - 2003





# **EUT Photographs**

### (1) EUT Photo



### (2) EUT Photo



## (3) EUT Photo





## (4) EUT Photo



### (5) EUT Photo





## **Appendix D. Probe Calibration Data**

### 国家无线电监测中心检测中心 The State Radio monitoring center Testing Center

## 校准证书

#### **Calibration Certificate**



器具名称

电场探头 E-Field Probe

Instrument-

EX3DV4

型号/规格 Type/Model-

生产厂家

Schmid & Partner Engineering AG

Manufacturer

SN:3710

出厂编号 Serial No-

客户名称

客户地址

快特电波科技 (苏州) 有限公司

Name of Client-

苏州工业园区娄葑高新技术开发区宏业路 99 号

Address of Client-

2011.2.25

校准日期 Calibration Date-

所有的校准工作都是在屏蔽实验室中完成:环境温度 (22±3) ℃ 湿度<70%

All calibrations have been conducted in the closed laboratory facility: environment

temperature (22±3) °C and humidity<70%

Approved by

地址: 北京市西城区北礼士路80号

Add: No.80 Bei Lishi Road, Xi Cheng District Beijing 100037, P.R. China

电话 Tel: +86-10-68009202 68009203 传真 Fax: +86-10-68009205 68009195

第1页 共7页

证书编号 Certificate No.SRTC2011-CAL002-001



## 国家无线电监测中心检测中心 The State Radio monitoring center Testing Center

校准规范 Reference documents of the measurement(Code, Name)

SRMC3003-V2.0.0 比吸收率 (SAR) 测试系统校准规范

校准环境及地点 Place and environmental condition of the measurement

温度 Temperature

23.2°C

湿度 Humidity 32.5 %

地点 Location SRTC room 226

| 主要校准设备                          | 型号         | 序列号            | 校准日期     | 校准有效期至      |
|---------------------------------|------------|----------------|----------|-------------|
| Primary Calibration Equipment   | Model/Type | ID#            | Cal Date | Scheduled   |
| used                            |            |                |          | Calibration |
| 功率计 Power meter                 | E4417A     | SN: MY45101004 | 2010.8   | 2011.8      |
| 功率传感器 Power sensor              | E9300B     | SN: MY41496001 | 2010.8   | 2011.8      |
| 功率传感器 Power sensor              | E9300B     | SN: MY41496003 | 2010.8   | 2011.8      |
| 参考 DAE Reference DAE            | DAE4       | SN: 720        | 2011.1   | 2012.1      |
| 信号源 Signal generator            | SML03      | SN:103514      | 2010.8   | 2011.8      |
| 网络分析仪 Network analyzer          | 8714ET     | SN:US40372083  | 2010.8   | 2011.8      |
| 次要校准设备                          | 型号         | 序列号            |          |             |
| Secondary Calibration Equipment | Model/Type | ID#            |          |             |
| 波导 Waveguide                    | WGLS R9    | SN:1006        |          |             |
| 波导 Waveguide                    | WGLS R14   | SN:1003        |          |             |
| 波导 Waveguide                    | WGLS R22   | SN:1006        |          |             |

人大三 1

地址:北京市西城区北礼士路 80 号 Add: No.80 Bei Lishi Road, Xi Cheng District Beijing 100037, P.R. China 电话 Tel: +86-10-68009202 68009203 传真 Fax: +86-10-68009205 68009195

第2页 共7页

证书编号 Certificate No.SRTC2011-CAL002-001