

# FCC Test Report

## FCC ID: ZSHS9

**Product:** Mobile phone

**Trade Mark:** KXD, Kenxinda, EL, E&L, Ken mobile

**Model Number:** S9

**Family Model:** S7

**Report No.:** STR190625003007E

**Prepared for**

SHENZHEN KENXINDA TECHNOLOGY CO.,LTD  
18TH FLOOR, FUCHUN ORIENT BUILDING, SHENNAN AV 7006,  
SHENZHEN, China

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen P.R. China  
Tel.: +86-755-6115 6588  
Fax.: +86-755-6115 6599  
Website: <http://www.ntek.org.cn>

## TEST RESULT CERTIFICATION

**Applicant's name** ..... : SHENZHEN KENXINDA TECHNOLOGY CO.,LTD  
Address ..... : 18TH FLOOR,FUCHUN ORIENT BUILDING, SHENNAN AV 7006,  
SHENZHEN, China

**Manufacturer's Name** ..... : SHENZHEN KENXINDA TECHNOLOGY CO.,LTD  
Address ..... : 18TH FLOOR,FUCHUN ORIENT BUILDING, SHENNAN AV 7006,  
SHENZHEN, China

### Product description

Product name ..... : Mobile phone

Model and/or type reference : S9

Family Model: S7

FCC Part15B

**Standards** ..... : ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

**Date of Test** .....

Date (s) of performance of tests..... : 26 Jun. 2019 ~ 16 Jul. 2019

Date of Issue ..... : 22 Jul, 2019

Test Result..... : **Pass**

Testing Engineer :   
(Allen Liu)

Technical Manager :   
(Jason Chen)


Authorized Signatory :   
(Sam Chen)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.4 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
3.2.2 TEST PROCEDURE	17
3.2.3 TEST SETUP	18
3.2.4 TEST RESULTS	19
3.2.5 TEST RESULTS(1000~26500MHz)	21

## 1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

### 1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

FCC Registration Number:463705; IC Registration Number:9270A-1

CNAS Registration Number:L5516

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

#### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

#### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~12.4GHz	5.0	

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Mobile phone				
Trade Mark	KXD, Kenxinda, EL, E&L, Ken mobile				
Model Name	S9				
Family Model	S7				
Model Difference	All models are the same circuit and RF module, except the model name.				
Product Description	<p>The EUT is a Mobile phone.</p> <table border="1"><tr><td>Connecting I/O port:</td><td>Micro USB, Earphone</td></tr><tr><td>Operation Frequency:</td><td>2.568GHz</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Connecting I/O port:	Micro USB, Earphone	Operation Frequency:	2.568GHz
Connecting I/O port:	Micro USB, Earphone				
Operation Frequency:	2.568GHz				
Power Source	DC 3.8V/5000mAh from Battery or DC 5V from USB Port.				
Adapter	Model: K12S Input: 100-240V~50/60Hz 0.25A Output: 5V ---1.5A				
HW Version	S550-MB-V2.0				
SW Version	NRD90M				

### 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM

For Conducted Test	
Final Test Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM


For Radiated Test	
Final Test Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM

Note: Final Test Mode: Through Pre-scan, find the mode 1 is the worst case.


Only the worst case mode is recorded in the report.

## 2.2 DESCRIPTION OF TEST SETUP

CE



RE



### 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
AE-1	PC	DELL	FT4Y23X	N/A	Peripherals
AE-2	KB	DELL	SK-8185	N/A	Peripherals
AE-3	Mouse	DELL	MS111-P	N/A	Peripherals
AE-4	Monitor	N/A	N/A	N/A	Peripherals
AE-5	Printer	Canon	L11121E	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	NO	NO	1.0m	
C-2	KB Cable	NO	NO	1.2m	
C-3	Mouse Cable	NO	NO	1.2m	
C-4	HDMI Cable	YES	YES	1.0m	
C-5	USB Cable	NO	NO	1.2m	

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

## 2.4 MEASUREMENT INSTRUMENTS LIST

## Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2019.05.13	2020.05.12	1 year
2	Test Receiver	R&S	ESPI	101318	2019.05.13	2020.05.12	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2019.04.15	2020.04.14	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2019.05.13	2020.05.12	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2019.05.13	2020.05.12	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2019.04.15	2020.04.14	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2019.05.13	2020.05.12	1 year
8	Amplifier	EMC	EMC051835SE	980246	2018.08.05	2019.08.04	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2019.05.13	2020.05.12	1 year
10	Power Meter	DARE	RPR3006W	15I00041S NO84	2018.08.05	2019.08.04	1 year
11	Power Sensor	R&S	URS9-Z4	0395.1619.05	2019.05.13	2020.05.12	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
13	High Test Cable(1G-40 GHz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
14	High Test Cable(1G-40 GHz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year

## AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2019.05.13	2020.05.12	1 year
2	LISN	R&S	ENV216	101313	2019.04.15	2020.04.14	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2019.05.13	2020.05.12	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2019.05.13	2020.05.12	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.

## 3.1.5 TEST RESULTS


EUT:	Mobile phone	Model Name. :	S9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-07-08
Test Mode:	Mode 1	Phase :	L
Test Voltage:	DC 5V from PC AC120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
						Remark
0.2020	36.60	9.76	46.36	63.52	-17.16	QP
0.2020	30.57	9.76	40.33	53.52	-13.19	AVG
0.3020	19.80	9.74	29.54	60.19	-30.65	QP
0.3020	8.71	9.74	18.45	50.19	-31.74	AVG
1.1019	19.38	9.74	29.12	56.00	-26.88	QP
1.1019	9.78	9.74	19.52	46.00	-26.48	AVG
4.3060	22.26	9.86	32.12	56.00	-23.88	QP
4.3060	17.59	9.86	27.45	46.00	-18.55	AVG
15.7220	41.58	10.11	51.69	60.00	-8.31	QP
15.7220	31.28	10.11	41.39	50.00	-8.61	AVG
25.0419	33.81	10.72	44.53	60.00	-15.47	QP
25.0419	19.30	10.72	30.02	50.00	-19.98	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.




EUT:	Mobile phone	Model Name. :	S9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-07-08
Test Mode:	Mode 1	Phase :	N
Test Voltage:	DC 5V from PC AC120V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.2020	35.98	9.73	45.71	63.52	-17.81	QP
0.2020	30.15	9.73	39.88	53.52	-13.64	AVG
0.4020	26.32	9.75	36.07	57.81	-21.74	QP
0.4020	15.94	9.75	25.69	47.81	-22.12	AVG
0.5020	28.88	9.75	38.63	56.00	-17.37	QP
0.5020	19.13	9.75	28.88	46.00	-17.12	AVG
5.6100	26.60	9.95	36.55	60.00	-23.45	QP
5.6100	18.22	9.95	28.17	50.00	-21.83	AVG
15.7220	44.13	10.10	54.23	60.00	-5.77	QP
15.7220	33.71	10.10	43.81	50.00	-6.19	AVG
24.9420	33.59	10.65	44.24	60.00	-15.76	QP
24.9420	19.37	10.65	30.02	50.00	-19.98	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Mobile phone	Model Name.:	S9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-07-08
Test Mode:	Mode 1	Phase :	L
Test Voltage:	DC 5V from PC AC240V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.1980	36.80	9.76	46.56	63.69	-17.13	QP
0.1980	30.80	9.76	40.56	53.69	-13.13	AVG
0.3020	20.54	9.74	30.28	60.19	-29.91	QP
0.3020	10.71	9.74	20.45	50.19	-29.74	AVG
3.3060	21.99	9.84	31.83	56.00	-24.17	QP
3.3060	17.84	9.84	27.68	46.00	-18.32	AVG
5.6099	26.57	9.88	36.45	60.00	-23.55	QP
5.6099	16.70	9.88	26.58	50.00	-23.42	AVG
15.7220	41.86	10.11	51.97	60.00	-8.03	QP
15.7220	30.81	10.11	40.92	50.00	-9.08	AVG
25.0419	34.02	10.72	44.74	60.00	-15.26	QP
25.0419	19.79	10.72	30.51	50.00	-19.49	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Mobile phone	Model Name. :	S9
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2019-07-08
Test Mode:	Mode 1	Phase :	N
Test Voltage:	DC 5V from PC AC240V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.2020	37.13	9.73	46.86	63.52	-16.66	QP
0.2020	29.21	9.73	38.94	53.52	-14.58	AVG
0.4020	26.60	9.75	36.35	57.81	-21.46	QP
0.4020	16.90	9.75	26.65	47.81	-21.16	AVG
0.5020	28.73	9.75	38.48	56.00	-17.52	QP
0.5020	21.69	9.75	31.44	46.00	-14.56	AVG
5.6097	27.43	9.95	37.38	60.00	-22.62	QP
5.6097	17.90	9.95	27.85	50.00	-22.15	AVG
15.5220	43.81	10.10	53.91	60.00	-6.09	QP
15.5220	33.89	10.10	43.99	50.00	-6.01	AVG
25.0458	34.04	10.66	44.70	60.00	-15.30	QP
25.0458	22.46	10.66	33.12	50.00	-16.88	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### 3.2.2 TEST PROCEDURE

##### **Test Arrangement for Radiated Emissions up to 1 GHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

##### **Test Arrangement for Radiated Emissions above 1 GHz.**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Avg	1 MHz	10 Hz

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



## 3.2.4 TEST RESULTS


## TEST RESULTS (30~1000 MHz)

EUT:	Mobile phone	Model Name:	S9
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2019-07-08
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V from PC AC120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	55.8047	24.47	6.97	31.44	40.00	-8.56	QP
H	165.4866	26.59	11.41	38.00	43.50	-5.50	QP
H	254.7284	26.27	15.23	41.50	46.00	-4.50	QP
H	283.9791	24.81	15.89	40.70	46.00	-5.30	QP
H	394.8544	17.39	19.30	36.69	46.00	-9.31	QP
H	766.0571	12.69	27.50	40.19	46.00	-5.81	QP

## Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




EUT:	Mobile phone	Model Name :	S9
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2019-07-08
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V from PC AC120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	46.9947	15.52	11.28	26.80	40.00	-13.20	QP
V	56.5929	24.88	6.86	31.74	40.00	-8.26	QP
V	165.4866	28.64	11.41	40.05	43.50	-3.45	QP
V	253.8367	26.69	15.18	41.87	46.00	-4.13	QP
V	597.2233	11.66	23.76	35.42	46.00	-10.58	QP
V	796.1830	10.95	27.26	38.21	46.00	-7.79	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



## 3.2.5 TEST RESULTS(1000~26500MHz)

EUT:	Mobile phone	Model Name :	S9
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2019-07-08
Test Mode :	Mode 1		
Test Power :	DC 5V from PC AC120V/60Hz		

All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequency	Reading	Correc	Result	Limit	Over Limit	Remar
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
V	2955	40.66	-2.45	38.21	74.00	-35.79	peak
V	2955	30.7	-2.45	28.25	54.00	-25.75	AVG
V	5335	33.60	6.38	39.98	74.00	-34.02	peak
V	5335	23.64	6.38	30.02	54.00	-23.98	AVG
V	8480	-7.62	53.32	45.70	74.00	-28.30	peak
V	8480	-19.87	53.32	33.45	54.00	-20.55	AVG
V	10605	-8.66	56.65	47.99	74.00	-26.01	peak
V	10605	-21.53	56.65	35.12	54.00	-18.88	AVG
V	13282.5	-10.11	60.85	50.74	74.00	-23.26	peak
V	13282.5	-20.75	60.85	40.10	54.00	-13.90	AVG
V	15662.5	-10.76	60.57	49.81	74.00	-24.19	peak
V	15662.5	-24.88	60.57	35.69	54.00	-18.31	AVG
H	2955	40.87	-2.45	38.42	74.00	-35.58	peak
H	2955	29.10	-2.45	26.65	54.00	-27.35	AVG
H	4272.5	35.53	3.69	39.22	74.00	-34.78	peak
H	4272.5	24.75	3.69	28.44	54.00	-25.56	AVG
H	4867.50	35.07	5.96	41.03	74.00	-32.97	peak
H	4867.50	24.19	5.96	30.15	54.00	-23.85	AVG
H	10605.00	-8.45	56.65	48.20	74.00	-25.80	peak
H	10605.00	-24.33	56.65	32.32	54.00	-21.68	AVG
H	13240.00	-9.92	60.82	50.90	74.00	-23.10	peak
H	13240.00	-20.70	60.82	40.12	54.00	-13.88	AVG
H	14430.00	-10.76	61.90	51.14	74.00	-22.86	peak
H	14430.00	-20.88	61.90	41.02	54.00	-12.98	AVG

## Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

Note: Only the worst results data points are reported in the report.