



Report No.:SZ11030032E03

FCC TEST REPORT

Issued to

UN Cells Limited

For

Mobile Phone

Model Name: Chairman
Trade Name: SCI Innovations Limited
Brand Name: UN Cells
FCC ID: ZTBCHMN-01
Standard: 47 CFR Part 15 Subpart B
Test date: June 21, 2011 – July 22, 2011
Issue date: September 8, 2011

by

Shenzhen Morlab Communications Technology Co., Ltd.



Tested by

Tu Lang
Tu Lang

Date

2011.9.8

Review by

Cao Shaodong
Cao Shaodong

Date

2011.9.8

CTIA Authorized Test Lab

LAB CODE 20081223-06

IEEE 1725

OTA

OFTA

電訊管理局



GCF

Official Observer of
Global Certification Forum

Bluetooth

BQTF

FCC

Reg. No.
741109

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it - or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Shenzhen MORLAB Communication Technology Co., Ltd.

3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 61281201 Fax: +86 755 86130218

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1	EUT Description	3
1.2	Test Standards and Results.....	4
1.3	Facilities and Accreditations	5
1.3.1	Facilities	5
1.3.2	Test Environment Conditions.....	5
1.3.3	Measurement Uncertainty	5
2.	TEST CONDITIONS SETTING.....	6
2.1	Test Setup and Equipments List.....	9
2.1.1	Conducted Emission.....	9
2.1.2	Radiated Emission.....	10
3.	47 CFR PART 15B REQUIREMENTS	11
3.1	Conducted Emission	11
3.1.1	Requirement	11
3.1.2	Test Description	11
3.1.3	Test Result	11
3.2	Radiated Emission	15
3.2.1	Requirement	15
3.2.2	Test Description	15
3.2.3	Test Result.....	15

Change History		
Issue	Date	Reason for change
1.0	September 8, 2011	First edition

1. GENERAL INFORMATION

1.1 EUT Description

EUT Type Mobile Phone
Serial No..... (n.a, marked #1 by test site)
Hardware Version..... V4.4
Software Version Chairman_GAPPS-eng 2.2 MAIN eng.duy.20110614.170756 test-keys
Applicant..... UN Cells Limited
16C Hurst End, Folly Lane, Newport Pagnell, Buckinghamshire MK16 9HS,
United Kingdom
Manufacturer Flextronics (SBS)
Munkas ut 28, PO Box 33, HU-8660 Tab, Hungary
Modulation Type FHSS, DSSS, GPRS/GSM Mode with GMSK Modulation
EDGE Mode with 8PSK Modulation
WCDMA Mode with QPSK Modulation
HSDPA Mode with QPSK Modulation
HSUPA Mode with QPSK Modulation
Power Supply Battery
Model Name: UN Cells
Brand name: 763740AR
Capacitance: 1340mAh
Rated Voltage: 3.7V
Charge Limit: 4.2V
Ancillary Equipment 1 ... AC Adapter (Charger for Battery)
Model Name: FW7711
Brand Name: FRIWO
Serial No.: (n.a. marked #1 by test site)
Rated Input: ~ 100-240V, 100mA, 50/60Hz
Rated Output: = 5V, 700mA

Note 1: The EUT is a Mobile Phone; it supports GSM 850MHz, 900MHz, 1800MHz, 1900MHz, GPRS, EDGE, WCDMA 850MHz, WCDMA 900MHz, WCDMA 1900MHz, WCDMA 2100MHz, HSUPA, HSDPA, GPS, ISM 2.4GHz Bluetooth and 2.4GHz WIFI module.

Note 2: The EUT is equipped with a T-Flash card slot; equipped with a special port which can be connected to the ancillary equipments supplied by the manufacturer e.g. the AC Adapter and the USB Adapter Cable.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-09 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4 2003.

1.3 Facilities and Accreditations

1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	$\pm 1.8\text{dB}$
Uncertainty of Radiated Emission:	$\pm 3.1\text{dB}$

2. TEST CONDITIONS SETTING

1. GSM Test Mode

(1) The first test mode (GSM850MHz)

The EUT configuration of the emission tests is EUT + Battery + Charger.

During the measurement of Traffic operating mode, A communication link was established between the EUT and a System Simulator (SS). The EUT operated at mid ARFCN (190) and maximum output power (level 5).

(2) The second test mode (GSM850MHz with Bluetooth earphone and wireless network)

The EUT configuration of the emission tests is EUT + Battery + Charger+ Bluetooth earphone + wireless network.

During the measurement of Traffic operating mode, A communication link was established between the EUT and a System Simulator (SS). The EUT operated at mid ARFCN (190) and maximum output power (level 5).

A communication link was established between the EUT and the Bluetooth earphone, and maintained until test end, and the EUT was connected with a wireless network, and transmitting data via the WIFI.

(3) The third test mode (GPRS – GSM850MHz)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, a GPRS link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(4) The fourth test mode (EDGE – GSM850MHz)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, an EDGE link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(5) The fifth test mode (PCS)

The EUT configuration of the emission tests is EUT + Battery + Charger.

During the measurement of Traffic operating mode, A communication link was established between the EUT and a System Simulator (SS). The EUT operated at mid ARFCN (661) and maximum output power (0).

(6) The sixth test mode (PCS with Bluetooth earphone and wireless network)

The EUT configuration of the emission tests is EUT + Battery + Charger+ Bluetooth earphone + wireless network.

During the measurement of Traffic operating mode, A communication link was established between the EUT and a System Simulator (SS). The EUT operated at mid ARFCN (661) and maximum output power (0).

A communication link was established between the EUT and the Bluetooth earphone, and maintained until test end, and the EUT was connected with a wireless network, and

transmitting data via the WIFI.

(7) The seventh test mode (GPRS – PCS1900MHz)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, a GPRS link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(8) The eighth test mode (EDGE – PCS1900MHz)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, an EDGE link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(9) The ninth test mode (Idle)

The EUT configuration of the emission tests is EUT + Battery + Charger.

During the test, The EUT was synchronized to the BCCH, listening to the CCCH and able to respond to paging message. Periodic location updating was disabled.

NOTE: All test modes are performed, only the worst cases are recorded in this report.

2. WCDMA Test Mode

(1) The first test mode (WCDMA-850MHz)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, a communication link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(2) The second test mode (WCDMA-850MHz with Bluetooth earphone and wireless network)

The EUT configuration of the emission tests is EUT + Battery + Charger+ Bluetooth earphone + wireless network.

In this test mode, a communication link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

A communication link was established between the EUT and the Bluetooth earphone, and maintained until test end, and the EUT was connected with a wireless network, and transmitting data via the WIFI.

(3) The third test mode (850MHz-HSDPA)

The EUT configuration of the emission tests is EUT + Battery + AC Adapter.

In this test mode, a HSDPA link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(4) The fourth test mode (850MHz-HSUPA)

The EUT configuration of the emission tests is EUT + Battery + AC Adapter.

In this test mode, a HSUPA link was established between the EUT and a System Simulator

(SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(5) The fifth test mode (WCDMA-1900MHz)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, a communication link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(6) The sixth test mode (WCDMA-1900MHz with Bluetooth earphone and wireless network)

The EUT configuration of the emission tests is EUT + Battery + Charger+ Bluetooth earphone + wireless network.

In this test mode, a communication link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

A communication link was established between the EUT and the Bluetooth earphone, and maintained until test end, and the EUT was connected with a wireless network, and transmitting data via the WIFI.

(7) The seventh test mode (1900MHz-HSDPA)

The EUT configuration of the emission tests is EUT + Battery + AC Adapter.

In this test mode, a HSDPA link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

(8) The eighth test mode (1900MHz-HSUPA)

The EUT configuration of the emission tests is EUT + Battery + AC Adapter.

In this test mode, a HSUPA link was established between the EUT and a System Simulator (SS); data was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

NOTE: All test modes are performed, only the worst cases are recorded in this report.

3. Amusement Test Mode

(1) The first test mode (USB)

The EUT configuration of the emission tests is TransFlash Card + EUT + Battery + PC.

In this test mode, the EUT with a TransFlash Card embedded is connected with a PC via a special USB cable supplied by applicant. During the measurement, a communication link was established between the EUT and a System Simulator (SS), simultaneously, the data is transmitting between the PC and the TransFlash Card of the EUT.

(2) The second test mode (GPS)


During the test, the GPS function was active.

NOTE: All test modes are performed, only the worst cases are recorded in this report.

2.1 Test Setup and Equipments List

2.1.1 Conducted Emission

A. Test Setup:




The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
Receiver	Agilent	E7405A	US44210471	2011.05
LISN	Schwarzbeck	NSLK 8127	812744	2011.05
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)
System Simulator	Agilent	E5515C	GB43130131	2011.05
Personal Computer	IBM	IBM_T20	(n.a.)	(n.a.)
Bluetooth-Headset	Nokia	HS-36W	(n.a.)	(n.a.)
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)

2.1.2 Radiated Emission

C. Test Setup:



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower. The Common Antenna is used for the call between the EUT and the System Simulator (SS).

D. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
Receiver	Agilent	E7405A	US44210471	2011.05
Semi-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2011.05
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2011.05
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2011.05
System Simulator	Agilent	E5515C	GB43130131	2011.05
Personal Computer	IBM	IBM_T20	(n.a.)	(n.a.)
Bluetooth-Headset	Nokia	HS-36W	(n.a.)	(n.a.)
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)

3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description


See section 2.1.1 of this report.

3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

3.1.3.1 GSM Test Mode

A. Test Plot and Suspicious Points:



(Plot A: L Phase)




(Plot B: N Phase)


Test Result : PASS

3.1.3.2 WCDMA Test Mode

A. Test Plots and Suspicious Point




(Plot A: L Phase)




(Plot B: N Phase)

3.1.3.3 Amusement Test Mode

A. Test Plot and Suspicious Points:



(Plot A: L Phase)



(Plot B: N Phase)

Test Result : PASS

3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength	
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

NOTE:

- Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V/m})]$.
- In the emission tables above, the tighter limit applies at the band edges.

3.2.2 Test Description

See section 2.1.2 of this report.


3.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.


3.2.3.1 GSM Test Mode

A. Test Plots and Suspicious Points:

Note: Following is the plots for emission measurement; please note that marked spikes near 850MHz with circle should be ignored because they are MS and SS carrier frequency.




(Plot A: Test Antenna Vertical)




(Plot B: Test Antenna Horizontal)

3.2.3.2 WCDMA Test Mode

A. Test Plots and Suspicious Points:




(Plot A: Test Antenna Vertical)




(Plot B: Test Antenna Horizontal)

3.2.3.3 Amusement Test Mode

B. Test Plots and Suspicious Points:



(Plot A: Test Antenna Vertical)



(Plot B: Test Antenna Horizontal)

Test Result : PASS

**** END OF REPORT ****